1 **evo3D: a generalised framework for structure-informed evolutionary analysis,**
2 **implemented in R**

3 Bradley K. Broyles[a], Qixin He[a*]

4 [a] Department of Biological Sciences, Purdue University, West Lafayette, IN, USA

5 [*] Correspondence: heqixin@purdue.edu

Abstract

Selection pressures often act at the level of protein structure, yet most evolutionary analyses
remain confined to linear sequences. Early structure-informed approaches improved
interpretation by mapping single-site metrics onto protein structures, and later methods
introduced 3D sliding windows to capture spatial neighbourhoods missed by linear analyses.
These frameworks, however, are restricted to predefined statistics and narrowly defined 3D
window types, limiting the scope of questions that can be addressed. We developed an R
package, `evo3D`, a generalised framework for structure-informed evolutionary analysis that
supports any downstream statistic and scales from simple to complex structures. `evo3D`
extracts structure-informed multiple sequence alignment subsets (spatial haplotypes), making the
structure-informed unit of analysis directly available to users. The framework provides fixed-
count and fixed-distance spatial windows, supports residue and codon analysis modes, and
extends across multimers, interfaces, and multiple structural models through a single wrapper,
`run_evo3d()`. We demonstrate `evo3D`'s utility by performing an epitope-level diversity scan
of Hepatitis C virus E1/E2 complex, identifying conserved spatial neighbourhoods missed by
linear sliding windows, and by evaluating `evo3D`'s scalability on the octameric Chikungunya
virus E1/E2 assembly. By formalising the core components of structure-informed genetic
analysis and removing the technical barriers, `evo3D` streamlines the evaluation of evolutionary
patterns directly within 3D structural contexts and we anticipate its wide application in molecular
evolution studies. The package is available at github.com/bbroyle/evo3D.

Introduction

Selection pressures acting on protein-coding regions frequently target three-dimensional (3D) features such as catalytic domains, ligand-binding sites, protein–protein interfaces, and overall structural stability, where selected phenotypes emerge from neighbourhoods of spatially organized residues (Golding and Dean 1998; Echave et al. 2016). Linear analyses, whether based on single sites or sliding windows, cannot capture this spatial context and are therefore limited in inferring selection on structural features. Incorporating 3D information has improved detection of conserved interaction surfaces (Lichtarge et al. 1996; Armon et al. 2001; Landgraf et al. 2001; Chivot et al. 2025) and adaptive evolution at epitopes and ligand-binding regions (Suzuki 2004; Berglund et al. 2005; Guy et al. 2018; Ciubotariu et al. 2024). Yet existing approaches for incorporating structural context remain restricted to fixed statistics and narrowly defined spatial window types, limiting the scope of evolutionary questions that can be asked. We developed `evo3D`, a generalised framework for structure-informed analysis that supports any downstream genetic statistics and scales from monomers to multimeric assemblies.

The general principle of structure-informed analysis is to evaluate genetic diversity within spatially defined windows, requiring two inputs: a nucleotide or amino acid multiple sequence alignment (MSA) and a corresponding protein structure (PDB). Spatial windows are conceptually similar to sequence sliding windows, with residues grouped by three-dimensional rather than sequential proximity. In practice, however, constructing spatial windows is considerably more complex. The residues included in a window depend on both the distance metric used to define inter-residue proximity and on the specific structural model, as conformational differences between models alter spatial neighbourhoods. When extending spatial analysis to multimers, additional complexities arise because a single codon may map to multiple residues and spatial windows can cross gene boundaries.

These complexities raise several biological and analytical considerations that, to our knowledge, have not been previously addressed. A single codon may map to multiple residues across equivalent chains, possibly producing duplicated codons within a spatial window. In these cases, we introduce window mode to specify how the duplicated codons are treated: "residue" mode retains duplicated codons while "codon" mode collapses to unique codons. Whether to retain or deduplicate these copies depends on the downstream statistic, with spatial averaging of single-site metrics generally requiring deduplication. Additionally, `evo3D` supports two analysis modes that determine how spatial windows are assigned and scored. Residue analysis mode creates a separate spatial window for every residue, enabling comparisons across conformational states such as open and closed enzyme forms. Codon analysis mode collapses all residue-level windows for a codon into one codon-level window, merging distance and solvent-exposure information across chains and allowing extended MSA coverage through multiple structural models. Spatial windows in multimers may also span residues encoded by different genes, raising the question of whether spatial haplotypes should allow combining residues of different genes from different genomes or be restricted to true haplotypes/genotypes from the same

genome. This choice depends on the statistic, with haplotype-based measures generally requiring

true haplotypes. `evo3D` formalises each of these multimer considerations for the first time,

allowing users to select biologically and statistically appropriate definitions for their analysis.

Even at the monomer level, several methodological and implementation issues continue to limit

structure-informed analysis. Most tools are designed for a single pre-defined statistic, such as

`HotMAPS` (Tokheim et al. 2016) and `CONSTRUCT` (Chivot et al. 2025), and therefore do not

provide general methods. Others, `BioStructMap` (Guy et al. 2018), prepackage multiple

statistics but are not readily extensible. The straightforward path to generalised methods, which

has not been previously implemented, is to return spatial haplotypes to users. Existing structure-

informed approaches also present practical barriers, since they are either external-dependency

heavy (`BioStructMap`) or restricted to specific operating systems (`HotMAPS`, `CONSTRUCT`).

Although these methods include more specialised features we have not implemented in `evo3D`,

such as `BioStructMap`'s handling of intron-exon splicing, `CONSTRUCT`'s optimisation of

window-distance cutoffs, and `HotMAPS`' design for large cancer mutation datasets, there remains

a clear need for easy-to-implement, generalised methods that link MSAs and structures.

Methodologically, these previous approaches also inherit two persistent oversights that are

shared across structure-informed workflows. The first is the unexamined alignment between

MSA codons and PDB residues. Reference nucleotide sequences must be translated and aligned

to structural chains, yet all existing methods treat this mapping as implicitly correct and do not

expose it to users. This allows potential alignment errors, particularly in proteins with unresolved

regions, to propagate into downstream analyses. `evo3D` addresses this by returning internal

alignments and allowing restarts of the workflow after user-adjusted mappings. The second

limitation is that spatial windows are defined exclusively by distance cutoffs, which produces

variable-sized windows that complicate comparisons across sites and proteins. `evo3D` constructs

either fixed-distance or fixed-size windows, depending on the desired analysis. Additionally,

`evo3D` can extract functional regions, such as protein interfaces or other user-defined windows.

Together, `evo3D` formalises a transparent and accurate structural mapping from MSAs to

proteins, spanning monomer handling and robust multimer integration. The `evo3D` R package is

dependency-free and cross-platform, with a single function entry point, `run_evo3d()`, that

generalises across diverse use cases. Below, we briefly outline the package workflow and

demonstrate its application through analyses of two viral protein complexes. `evo3D` identifies

conserved antibody-accessible regions that are missed in linear analyses of the Hepatitis C virus

E1/E2 complex; it also reveals elevated diversity adjacent to, but not within, receptor-binding

domains in the octameric Chikungunya virus E1/E2 assembly. With accurate deep-learning

structural prediction now routine (Jumper et al. 2021; Lin et al. 2023), structural information is

no longer a bottleneck, and `evo3D` enables a broad range of evolutionary analyses to be

performed directly within the 3D environments where selection operates.

Implementation

`evo3D` is implemented entirely in R (R Core Team 2024) and provides a single entry point, `run_evo3d()`, which performs a complete structure-informed evolutionary analysis (Fig. 1). The package maintains minimal external dependencies, using `bio3d` (Grant et al. 2006) for MSA and PDB input file handling, `msa` (Bodenhofer et al. 2015) for alignment utilities, `seqinr` (Charif and Lobry 2007) for nucleotide to amino-acid translation, `pegas` (Paradis 2010) for population-genetic statistics, and `Rcpp` (Eddelbuettel and François 2011; Eddelbuettel 2013; Eddelbuettel and Balamuta 2018; Eddelbuettel et al. 2024) for high-performance solvent-accessibility calculations. The full parameter space is described in the package documentation and Supplementary Methods (Table S2). Default parameters can be inspected via `show_evo3d_defaults()` and adjusted as arguments to `run_evo3d()`.

All results are returned as a structured S3 list containing:

- `evo3d_df` – a data frame object with sequence-structure alignments, codon-indexed windows and window information, and any computed statistics

- `final_msa_subsets` – list object of spatial haplotypes (MSA subsets for each spatial window) with names corresponding to the `msa_subset_id` column in `evo3d_df`

- `msa_info_sets` – input MSAs, internally generated reference sequence, translated reference sequence, and detected sequence type (nucleotide, protein)

- `pdb_info_sets` – input PDBs, `residue_df` with residue information and residue-indexed windows, peptide sequences for analysis chains, and residue-residue distance matrix

- `aln_info_sets` – `aln_df` with both codon and residue indexed windows, `coverage` for alignment quality, and `pos_mat`, which contains correctable MSA-PDB alignments.

- `call_info` – full parameter record, input file paths, and internal automatic chain assignments for reproducibility

The wrapper workflow begins with `msa_to_ref()`, which validates the MSA input, detects nucleotide versus amino-acid input, and generates a corresponding peptide reference sequence. Structural files are then loaded, and chains are matched to the MSA using fast k-mer similarity; users may override this with `chain = "A"` to force specific mappings or chain strings such as `"ABC"` to force mappings to multiple chains. `pdb_to_patch()` defines spatial neighbourhoods around each residue using distance-based or fixed-count rules with user-set exposure and geometry parameters, producing residue-indexed 3D windows.

Next, `aln_msa_to_pdb()` aligns the reference peptide to the structural chain, maps MSA codons to residues, corrects gap-induced inconsistencies, and converts residue-indexed windows into codon-indexed windows. `collapse_to_codon()` merges per residue windows into per codon representations using multiple schemes. `extract_msa_subsets()` isolates the MSA subsets corresponding to each spatial window, generating discontinuous but structurally coherent spatial haplotypes. Finally, `calculate_patch_stats()` applies the user-selected population-genetic or evolutionary statistics (e.g., block entropy (Olsen et al. 2011), nucleotide diversity (Nei 1987), haplotype diversity (Nei and Tajima 1981), Tajima's D (Tajima 1989)) to each haplotype.

The wrapper design minimises user workload, and tunable parameters are organized as control lists arguments (e.g., pdb_controls = list(dist_cutoff = 10)). All internal modules are exposed as standalone functions for custom workflows. Select submodular functions are exported with the package while others are accessible as internal functions (e.g. `evo3D:::.align_sequences()`). Highly useful is the submodular function, `.calculate_accessibility()`, invoked by `pdb_to_patch()`, which couples R and C++ to reproduce DSSP-style solvent-accessibility calculations (Kabsch and Sander 1983; Hekkelman et al. 2025). Additional utilities outside the wrapper function include functions that map selection scores to PDB structures for visualisation and that generate null models that mirror the observed codon usage and window definitions.

Results and Discussion

We demonstrate `evo3D`'s capabilities with 3D evolutionary analysis on two protein complexes, using a set of fixed criteria for surface residue filtering, residue distance definitions, and fixed-size spatial windows (`sasa_cutoff` ≥ 10, `distance_method` = "all", `max_patch` = 15; see Methods: Input Parameters). While adjustable by users in `run_evo3d()`, these parameters were fixed here for clarity.

Hepatitis C Virus E1/E2 complex

The Hepatitis C virus (HCV) E1/E2 glycoprotein complex is a leading vaccine candidate, yet its genetic diversity complicates broad-coverage vaccine design (Bailey et al. 2019; Metcalf et al. 2023). To address this challenge, we applied `evo3D` as an epitope-level diversity scan, with the goal of uncovering conserved regions of an average antibody binding site (15 residues) (Reis et al. 2022). Additionally, several functional regions of E1/E2 are already characterised, which allowed us to test `evo3D`'s built-in null model framework and its ability to recover these known functional regions. Finally, we repeated both analyses in a linear framework, allowing a direct comparison of spatial versus linear approaches.

The dataset comprised 271 HCV genotype 1b genomes obtained from BV-BRC (Olson et al.
2023), from which we extracted E1 and E2 coding regions to build two nucleotide multiple
sequence alignments (MSAs). Structural context was provided by PDB ID: 8fsj (Metcalf et al.
2023). Residue numbering discussed in the text also refers to this structure file. As a preliminary
dataset validation step, we calculated amino acid Shannon entropy per codon (see methods 1.11),
which confirmed the expected high diversity of variable region 2 (VR2). When mapped onto
structure, these values also reproduced the known general split between conserved and diverse
faces of E1/E2, consistent with previous reports (Torrents de la Peña et al. 2022; Metcalf et al.
2023) (Fig. 2a).

We next carried out an epitope-level diversity scan of the E1/E2 surface, which requires
measuring the combined diversity of entire spatial neighbourhoods rather than single positions.
For this, we calculated block entropy, which is defined as the Shannon entropy of amino acid
haplotype frequencies. The approach has been systematically applied in T-cell vaccine research
(Olsen et al. 2011; Hu et al. 2013; Raman et al. 2020; Tharanga et al. 2025) and here extended
into the spatial domain of B-cell antibodies (Fig. 2b). Importantly, we identified highly
conserved spatial regions on the otherwise diverse and immune-exposed face of E1/E2 (Torrents
de la Peña et al. 2022), most prominently around E2 606 (block entropy = 0.6 bits) and E2 561
(0.7). Across the E1/E2 surface, block entropy varied from complete conservation around E2 685
(0.0) to extreme diversity around E2 476 (7.7), with a median score of 3.7 bits. These results
underscore the difficulty in developing a broad coverage HCV vaccination, as the median score
of 3.7 bits corresponds to effectively 13 equal-frequency haplotypes sharing a typical epitope-
sized region on the E1/E2 surface. However, `evo3D` identified two promising regions around E2
606 and E2 561, which are accessible to antibodies (Fig. S1) and dominated by single haplotypes
covering more than 90% of the genomes sampled.

In addition to calculating spatial diversity, `evo3D` supports significance testing to identify outlier
spatial neighbourhoods by generating empirical null models. We re-purposed the block entropy
scores to address two additional questions: do significant regions correspond to known or
inferred functions, and could they have been detected in an equivalent linear analysis?
Comparing spatial block entropy scores against the null distribution revealed five significant
neighbourhoods (see Methods 2.5), four conserved and one diverse (Fig. 2c). In contrast, an
equivalent linear block entropy and null model comparison revealed only two significant regions,
one conserved and one diverse, each also detected in spatial analysis.

Among the significant spatial regions missed in linear analysis were two conserved
neighbourhoods around E2 685 and E2 662, both of which participate in the protein-protein
interface of the higher-order dimer of E1/E2 heterodimers (Fig. S1). Additionally, the conserved
region around E2 606, highlighted above as a potential broad-coverage vaccine target, was
significant in spatial analysis but not in linear analysis. Regions detected by both spatial and
linear analyses were E2 476, corresponding to the diverse VR2 segment implicated in
modulating antibody recognition (Alhammad et al. 2015) and E2 507, which has been suggested

to contribute to E1/E2 oligomerization (Augestad et al. 2024). A complementary role for the
conserved spatial region around E2 507 may be participation in higher-order trimer interfaces, as
evident in an AlphaFold3 (Abramson et al. 2024) predicted trimer (Fig. S1) and supported by
evidence that E1 forms trimers (Falson et al. 2015).

When statistical thresholds were relaxed (see Methods 2.5), the linear approach recovered E2
685 and E2 662, but with a reduced level of confidence compared to spatial analysis (Benjamin-
Hochberg: q = 0.046 for linear vs. q = 0.003 for spatial). However, the conserved region of E2
606 was never detected by linear methods. These comparisons demonstrate that `evo3D`'s
framework can detect functional regions, including conserved protein-protein interfaces and
diverse immune-modulating segments. Critically, 3D-organized features were detected with
greater sensitivity under spatial analysis, with the E2 606 region identified exclusively by
`evo3D`. This supports earlier findings that spatially informed methods improve the detection of
3D features (Landgraf et al. 2001; Suzuki 2004; Berglund et al. 2005).

While spatial analysis captured features missed by linear methods, the two approaches did
partially overlap in findings. Direct comparison of block entropy scores showed moderate
correlation (Pearson r = 0.66), reflecting that spatial and linear windows shared an average of 7.5
out of 15 residues. However, individual windows differed substantially, sharing as few as two
and as many as 13 residues, and spatial minus linear block entropy scores ranging from -5.8 to
+3.9 bits (Fig. 2d). In terms of effective haplotype diversity, this corresponds to regions nearly
60 times more conserved to 15 times more diverse in the spatial view, re-emphasizing that linear
and spatial approaches capture different signals.

When the features of interest are inherently 3D, as many protein features are, the spatial
perspective is not merely complementary but essential. More broadly, the HCV use cases, which
included epitope-level scanning and spatial significance testing, identified conserved vaccine
targets and recovered known functional features that linear methods overlooked. Applying
`evo3D` to other protein systems requires only sequence alignment data and a structural context
and is not limited to epitope-sized windows or the block entropy statistic, making it a general
framework for evolutionary analysis of 3D features.

Chikungunya Virus E1/E2 complex
To illustrate `evo3D`'s scalability and to demonstrate several features specific to multimeric
systems, we applied the workflow to the Chikungunya virus (ChikV) E1/E2 octameric complex,
which is nearly an order of magnitude larger than the HCV example. This system provides a
setting to highlight distinctions between window modes and analysis modes and to show how
interfaces can be treated as their own spatial haplotypes. The increased structural size produced a
corresponding rise in runtime: the HCV analysis completed in five seconds, whereas the ChikV
analysis required approximately 1.5 minutes. Most of this increase was due to the construction of
the all-atom distance matrix. When distances were computed using Cα or centroid coordinates,
runtime decreased to approximately 20 seconds and memory usage to roughly 1 GB (see

Methods 1.5).

We obtained 379 ChikV genomes from BV-BRC (Olson et al. 2023), constructed nucleotide
MSAs for E1 and E2, and used the octameric structure PDB ID: 8fcg (Chmielewski et al. 2024)
for structural context and residue referencing in the text. Each MSA mapped to four chain copies
(Fig. 3a), producing four distinct spatial environments per codon. This system illustrates the
window and analysis-mode distinctions formalised in `evo3D`: whether spatial windows retain all
residues or are deduplicated to unique codons, and whether analysis assigns one spatial window
for every residue or one for every codon. Because block entropy is unaffected by repeated
codons, we constructed residue-mode windows containing 15 residues. Only 1.2 percent of
windows contained codon duplicates, with some windows comprising as few as ten unique
codons among fifteen residues. Although infrequent, such cases would distort any spatially
averaged statistic, highlighting the need for explicit control over window mode.

To evaluate how consistently the same codon is represented across its four structural
environments, we performed the analysis in residue mode, assigning a separate window and
score to every residue-level environment and therefore generating four scores per codon (Fig.
3b). Comparing the maximum and minimum block entropy values for each codon showed that
the four environments were generally consistent (median difference = 0.03 bits, IQR = 0–0.12).
Fourteen codons, however, showed differences of at least 1.0 bits, with a maximum difference of
1.7 bits. These larger differences reflect chain-specific variation in solvent exposure of the
neighbouring residues. The octamer contains the full set of burial and exposure contexts each
codon encounters in the intact viral envelope, but these contexts are distributed across different
chains. By switching to codon analysis mode, `evo3D` can merge these chain-specific
environments into a single codon-level representation that captures the complete structural
context for each codon (see Methods 1.8).

After comparing residue-level environments, we collapsed these values into a single codon-level
score by averaging the block entropy values across chains (Fig. 3c-d). Overall diversity ranged
from 0 to 2.2 bits (median 0.4), with E2 showing higher diversity (median 0.6) than E1 (median
0.2). The highest-diversity window was centred on E2 residue 119, which is notable because
residue 119 forms a contact with MXRA8, the human entry receptor (Zhang et al. 2018; Song et
al. 2019), as determined from PDB ID: 6jo8 (Fig. S2a). Although this window represents the
most diverse local environment on the E1/E2 surface, E2 residue 119 itself is completely
invariant. This illustrates a key property of spatial windows: block entropy measures the
diversity of the three-dimensional neighbourhood, rather than the central codon anchoring the
window.

To characterize the MXRA8 interface directly, `evo3D` supports constructing spatial haplotypes
for specified interfaces. Interfaces were included by setting `interface_chain =`
`c("M","N","O")` in the wrapper call. Using PDB ID: 6jo8 (Song et al. 2019), where chains

M, N, and O correspond to MXRA8, contacts within 4 Å of MXRA8 and E1/E2 were extracted.
Because block entropy is window-size dependent, we compared per-site amino acid Shannon
entropy of MXRA8-contacting codons with the full E1/E2 surface. Interface codons were
strongly conserved: only one exceeded 1 bit (E2 residue 74, 1.2 bits), while four codons
exceeded 1 bit on the full E1/E2 surface (maximum at E1 residue 211, 1.6 bits). The interface
had a median per-site entropy of 0 and an interquartile range of 0 to 0.03, slightly higher than the
surface as a whole (median 0; IQR 0–0). This highlights the importance of treating interfaces as
their own analytical units. The highest-diversity spatial window on E1/E2 is centred on a residue
that contacts MXRA8, but that residue is invariant and the MXRA8-binding site is largely
invariant. Thus, diversity is highest near the MXRA8-binding surface, not within it.

This example illustrates the general framework implemented in evo3D. The wrapper provides
access to multiple window and analysis modes and supports interfaces as separate analytical
units. Applied to the ChikV octamer, these components allow chain-specific environments to be
compared directly or merged into unified codon-level contexts and allow the MXRA8-binding
interface to be examined as its own spatial haplotype. The full analysis, which mapped two
MSAs to four chains each and constructed spatial haplotypes for every surface residue, can be
completed in approximately 20 seconds on a laptop with an Intel Core i7-13620H CPU. These
results show that evo3D is generalised not only in its tunable parameter space, but also in its
ability to handle structurally complex assemblies efficiently.

Conclusion

evo3D provides a practical framework for linking MSAs to three-dimensional structure and
returning spatially defined haplotypes for any downstream statistic. The package is designed to
support a wide range of applications, from basic evolutionary summaries to more specialized
analyses of immune recognition, viral diversification, and scaling from monomers to multimer
assemblies. By formalizing the structural integration layer and making each step transparent and
reproducible, evo3D offers a general tool that can be applied to many fundamental research
questions in molecular evolution.
316

Methods

1. Package details

1.1 Workflow overview

evo3D consists of a set of modular components that perform each step of structure-informed
evolutionary analysis. These modules are described in the Implementation section, but in
practice, they are orchestrated through the run_evo3d() wrapper, which removes technical
barriers and provides a unified interface. The wrapper accepts one or many MSA and PDB
inputs, builds an internal run grid that maps PDB chains to MSAs through fast k-mer similarity,
and executes the full analysis in a single, seamless workflow (Fig. 1).

1.2 Parameter-control structure

The behaviour of `evo3D`'s underlying modules is governed by named control lists supplied to `run_evo3d()`. Controls are grouped according to the stage of the workflow they modify: `msa_controls`, `pdb_controls`, `aln_controls`, `collapse_controls`, `stat_controls`, and `output_controls`. Each list contains only the parameters relevant to its corresponding modules, allowing the wrapper to remain compact while supporting extensive customization. Default values for all controls can be viewed with `show_evo3d_defaults()`, and individual settings may be overridden as needed.

1.3 Automatic chain mapping

Chain assignment is performed only when the `run_evo3d()` chain argument is set to `"auto"` (the default). In this mode, `run_evo3d()` identifies which structural chain corresponds to each MSA during run-grid construction. Matching is based on fast k-mer similarity between the MSA-derived peptide reference and the amino-acid sequences of each chain in the structural model; chains are ranked by k-mer overlap, and the highest-scoring chain is selected. These assignments are stored explicitly within each run-grid entry and are used by all downstream modules. Users may bypass automatic mapping entirely by supplying chain specifications directly through the chain argument (See Supplementary Methods S.1.1).

1.4 MSA preprocessing and reference construction (msa_to_ref)

The `msa_to_ref()` module standardizes user-supplied MSAs and generates the peptide reference sequence used for aligning the MSA to the PDB. Inputs may be nucleotide or amino-acid MSAs provided as matrices (for example, from `bio3d::read.fasta()`) or as file paths. The module detects sequence type automatically by examining the most frequent character types for the first 100 columns of input MSA.

A reference sequence is then constructed according to parameters defined in `msa_controls`. Users may select the least-gapped sequence in the alignment, a specified MSA row, or a consensus sequence computed from non-gap positions. Nucleotide MSAs are translated to amino acids using a user-specified genetic code. The module returns a standardized S3 object containing the original MSA, the reference sequence, and the translated reference peptide. These outputs form the sequence foundation for all subsequent MSA to PDB alignment steps.

1.5 Structural parsing and spatial-window generation (pdb_to_patch)

The `pdb_to_patch()` module parses structural files and constructs residue indexed spatial windows that define the three-dimensional neighbourhoods used throughout `evo3D`. Inputs may be PDB or mmCIF file paths or pre-loaded objects from `bio3d::read.pdb()` or `bio3d::read.cif()`. The module first validates file format and standardizes fields such as insertion codes to ensure consistent residue indexing across chains.

Sequences from the user or wrapper specified chains are extracted, and inter-residue distances are computed according to the method specified in `pdb_controls`. Users may select minimum all-atom distances, Cα–Cα distances, or distances between residue centroids. Solvent accessibility is then calculated with the DSSP-style algorithm (see section 1.6) incorporated into `evo3D`, and residues are classified as exposed or buried based on user-defined thresholds. Optional identification of inter-chain contacts, guided by the `interface_chain` argument, allows interface-specific windows to be generated when required.

Using these distance and exposure measures, the module constructs spatial windows around each residue according to either fixed size or distance cutoff rules. These windows are defined entirely at the structural level, before any reference to the MSA, and therefore reflect the geometric properties of the input model. The output is a standardized S3 object containing the structural data, the chain sequences, distance matrices, and a table of residue centred spatial windows and exposure values for each residue.

1.6 Solvent-accessibility calculation

Solvent-accessible surface area (SASA) was computed with a DSSP-style algorithm re-implemented in C++ and integrated into `evo3D` through the function `.calculate_accessibility()`. The implementation reproduces the geometric definitions of DSSP (Kabsch and Sander 1983), including atom-specific van der Waals radii and geodesic-sphere sampling of atomic surfaces to estimate accessibility. Validation against MKDSSP v4.4.10 (Hekkelman et al. 2025) across 95 protein structures (114,140 residues) showed near-perfect agreement (Pearson r = 0.9999784) with per-residue deviations of −0.5 to +0.5 Å², well within the ≈1 Å² numerical variance reported in the original DSSP publication (Kabsch and Sander 1983) .

1.7 MSA-to-structure alignment and codon mapping (aln_msa_to_pdb)

The `aln_msa_to_pdb()` module aligns the reference peptide generated by `msa_to_ref()` to the residue sequence extracted from each structural chain and establishes the mapping between MSA codons and PDB residues. Alignment is performed with the `msa` package (Bodenhofer et al. 2015), which provides the Clustal Omega algorithm (Sievers et al. 2011). The resulting alignment table is stored and returned to the user at the end of the workflow. If a user modifies this alignment, `run_evo3d()` can be restarted with the revised table, which provides a fully transparent and reproducible mapping process.

The residue-indexed windows produced by `pdb_to_patch()` are then converted into codon-indexed windows. Each residue is assigned a codon position based on the reference alignment. Residues that align to gaps in the MSA reference do not have corresponding codons and are removed from codon-indexed windows. Codon duplicates that arise in multimeric assemblies are retained or removed according to the deduplication rules specified in `aln_controls`. When fixed-count windows are requested, the module reconstructs any windows that fall below the target size so that downstream analyses operate on consistent codon counts.

400 The module returns a standardized S3 object that includes a table of codon-to-residue mappings
401 and codon indexed windows for all residues in the specified PDB chains, the individual MSA to
402 PDB chain alignments for optional user correction, and a coverage list summarizing the
403 completeness and identity of each MSA relative to each structural chain.

1.8 Codon-level window merging and multimer integration (collapse_to_codon)

The `collapse_to_codon()` module converts the residue-level table produced by
`aln_msa_to_pdb()` into a codon-level table. In multimeric assemblies or multi-model
analyses, a single codon may appear multiple times because it maps to several structural
residues. For example, the same codon may correspond to positions 127 in chains E, F, and G,
each with its own residue-centred window. `collapse_to_codon()` condenses these separate
neighborhoods into one representation per codon and merges their windows according to the
mode specified in `collapse_controls`. The available modes are `union`, `distance`, and
`exposure_distance`. Detailed definitions of each mode are provided in the Supplementary
Methods (S.2).

1.9 Extraction of spatial haplotypes (extract_msa_subsets)

The `extract_msa_subsets()` is a submodular function generally applied with the
`aln_msa_to_pdb()` or `collapse_to_codon()` module, but within the wrapper function
`run_evo3d()`, it is placed after the `collapse_to_codon()` module. This function
extracts the MSA subsets corresponding to each codon-indexed window and returns them as
spatial haplotypes. For every window, the module gathers the codon positions defined by
`aln_msa_to_pdb()` and `collapse_to_codon()` and slices the original MSAs to
produce discontinuous but structurally coherent subsets that serve as inputs for downstream
statistics.

Haplotype construction across multiple MSAs is controlled by the `use_sample_names`
parameter in `aln_controls`. When this option is set to `TRUE`, discontinuous sequence
segments are concatenated only where row names are identical. Sequences from one MSA with
no identical name in other MSAs are dropped. This ensures that codons drawn from different
genes or loci originate from the same genome. When `use_sample_names` is `FALSE`, MSA
subsets are concatenated row-wise, and any sequences left unpaired after exhausting one MSA
are padded with gap characters.

1.10 Calculation of window-level statistics (calculate_patch_stats)

The `calculate_patch_stats()` module provides six built-in statistics that can be applied
directly within the `evo3D` workflow. These include Shannon entropy for single sites, averaging
single-site Shannon entropy per patch, and block entropy, along with several summary statistics
from the `pegas` (Paradis 2010) package, such as nucleotide diversity, Tajima's D, and haplotype
diversity. These functions are intended as convenient defaults rather than a complete analysis
suite.

Because `evo3D` returns all spatial haplotypes to the user, most statistical analyses can be applied
independently outside the wrapper. Users may compute any custom metric directly on the
returned spatial haplotypes without modifying the `evo3D` workflow. The internal statistics
module, therefore, serves primarily as an optional shortcut for standard diversity measures.

1.11 Single-site entropy (Fig. 2a, Fig. S2)
Multiple sequence alignments were translated to amino acid sequences using the R package
`seqinr` (Charif and Lobry 2007), with translation tables specified by the `genetic_code`
parameter in `msa_controls` when alternative codon systems were required. Shannon entropy
(Shannon 1948) was calculated for each alignment position from observed amino-acid
frequencies. Gaps and ambiguous residues ("X") were excluded on a per-position basis.

$$H(x) = -\sum_{i=1}^{n} p_i(x)\log_2(p_i(x))$$

Where H is Shannon entropy, x denotes the alignment position, i represents an amino acid type, n
is the number of distinct amino acid residues at position x, and $p_i(x)$ is the observed frequency of
amino acid i at position x.

1.12 Block entropy (Fig. 2b, Fig. 3b-d)
As described in Olsen *et al* (Olsen et al. 2011), haplotype-level Shannon entropy (block entropy)
was computed from the frequency distribution of amino acid haplotypes within spatial or linear
windows. Haplotypes were translated to amino acids using `seqinr`, and sequences containing
gaps or ambiguous residues were excluded before frequency estimation.

$$H(B) = -\sum_{w=1}^{n} p_w(B)\log_2(p_w(B))$$

Where H is Shannon entropy, B denotes the MSA subset, w represents a haplotype, n is the
number of distinct haplotypes in MSA subset B, and $p_w(B)$ is the observed frequency of the
haplotype in the MSA subset B.

1.13 Return structure of `run_evo3d()`
The `run_evo3d()` wrapper returns a structured S3 list that contains all sequence, structure,
alignment, and window-level information produced during the analysis. This list serves as both
the final output and a complete record of all intermediate steps, which allows users to inspect any
component, rerun modules with corrected inputs, or perform additional analyses directly on the
returned objects.

The return object includes:

- `evo3d_df`
  A table of the final MSA-PDB alignment, codon-indexed windows, and optional statistics per window.

- `final_msa_subsets`
  All spatial haplotypes extracted for each window.

- `msa_info_sets`
  output objects from runs of `msa_to_ref()`

- `pdb_info_sets`
  output objects from runs of `pdb_to_patch()`

- `aln_info_sets`
  output objects from runs of `aln_msa_to_pdb()`

- `call_info`
  A full record of parameters supplied to `run_evo3d()`, including all control settings used during the analysis, and the run grid built internally.

This return structure provides full transparency across all stages of the workflow and gives users direct access to both spatial haplotypes and the intermediate tables needed for independent or extended analyses.

1.11 Limitations

Several technical limitations remain in the current implementation of `evo3D`. Non-canonical amino acids present as HETATM records in structural files are not incorporated into sequence parsing or solvent-accessibility calculations. These residues can be converted to ATOM records prior to analysis, but they are otherwise omitted from both sequence and window generation. A more complete solution would assign each non-canonical residue to the closest canonical type, but this requires manual inspection.

The workflow assumes coding-strand MSAs and does not handle exon-intron splicing. Users working with genomic alignments should preprocess their data to generate coding-only MSAs before supplying them to `evo3D`. A final limitation concerns structural file formats. The mmCIF reader in `bio3d` has incomplete support for recent formats produced by AlphaFold3, which may cause some structures to be parsed incorrectly. Converting AlphaFold3 mmCIF outputs to PDB format resolves this issue. Future versions of `evo3D` will include a dedicated parser that removes this dependency.

2. Analysis details

2.1 Hepatitis C Virus (HCV) genetic data

HCV genotype 1b genomes were retrieved from BV-BRC (accessed July 24 2025; n = 274; (Olson et al. 2023)) and formatted as a local nucleotide BLAST database. A representative SwissProt genotype 1b polyprotein (accession O92972; (The UniProt Consortium 2025)) was trimmed to the E1-E2 region and used as the tblastn query (BLAST+ v2.13.0; (Camacho et al. 2009)). Hits spanning the full-length query were retained. One partial hit beginning at query position two was manually extended by one codon to recover the complete region, yielding 273 full-length matches. Corresponding nucleotide segments were extracted with blastdbcmd and translated with SeqKit (v2.3.1; (Shen et al. 2024)). Sequences containing internal stop codons or fewer than 95% standard amino acid characters were removed, leaving 271 genomes. The E1-E2 amino acid reference sequence (O92972) was appended before multiple sequence alignment (MSA) with MUSCLE (v5.1; (Edgar 2022)). The amino acid alignment was mapped to nucleotide sequences to insert triplet gaps and preserve the reading frame. Alignment columns with >90% gaps were removed. Based on SwissProt-defined gene boundaries, the final E1 and E2 nucleotide MSAs were extracted for downstream analysis.

2.2 Chikungunya virus (ChikV) genetic data

ChikV genomes were retrieved from BV-BRC (accessed October 30, 2025; n = 1,139; (Olson et al. 2023)) and filtered to retain sequences collected between 2016 and 2025 (n = 632). From these, up to 50 genomes per sampling year were selected, yielding 385 genomes, which were formatted as a local nucleotide BLAST database. A representative SwissProt ChikV polyprotein (accession Q5XXP3; (The UniProt Consortium 2025)) was trimmed to the E2-E1 region and used as the tblastn query (BLAST+ v2.13.0; (Camacho et al. 2009)). Hits spanning the full-length query were retained, producing 380 complete matches. The corresponding nucleotide regions were extracted with blastdbcmd and translated with SeqKit (v2.3.1; (Shen et al. 2024)). Sequences containing internal stop codons or fewer than 95% standard amino acid characters were removed, leaving 379 genomes. The E2-E1 amino acid reference sequence (Q5XXP3) was appended before multiple sequence alignment with MUSCLE (v5.1; (Edgar 2022)). The amino acid alignment was mapped to nucleotide sequences to insert triplet gaps and preserve the reading frame. Alignment columns with >90% gaps were removed. Based on SwissProt-defined gene boundaries, the final E1 and E2 nucleotide MSAs were extracted for downstream analysis.

2.3 Parameterization for HCV and ChikV examples

HCV and ChikV analyses were performed using the run_evo3d() wrapper with the following parameters specified in the argument pdb_controls = list(max_patch = 15, distance_method = "all", and sasa_cutoff = 10). The max_patch parameter defines fixed-size spatial windows containing the specified number of residues. The distance_method parameter determines how inter-residue distances are calculated: "all" uses the minimum distance between all non-hydrogen atom pairs. The sasa_cutoff parameter filters residues by solvent accessibility, retaining only those with solvent-accessible surface area (SASA) above the defined threshold.

541 **2.4 Linear sliding windows (HCV)**

542 For linear comparisons, 15-amino acid sliding windows were generated across each MSA,

543 bounded by the start and end of resolved regions in the structural models PDB ID: 8fsj (Metcalf

544 et al. 2023). To maintain complete window coverage, terminal regions were extended by up to

545 seven residues when possible.

546 **2.5 Null-model generation and significance testing (Fig. 2c)**

547 Null models were generated using the function `generate_null_models()` in `evo3D`,

548 which constructs 10,000 synthetic haplotypes of the same fixed size (15 amino acids) as used in

549 the analyses, sampling codons according to their observed frequencies across all analysis

550 windows. Significance testing followed Berglund *et al.* (Berglund et al. 2005): windows were

551 ranked by absolute Z-score ($|z|$), and to approximate independence, overlapping windows ($\geq 33\%$

552 shared codons) were iteratively pruned in descending order of $|z|$ using the function

553 filter_overlaps(). Empirical p-values were adjusted using the Benjamini-Hochberg (BH, $\alpha =$

554 0.05) and Bonferroni ($\alpha = 0.1$) corrections (Benjamini and Hochberg 1995). Two significance

555 tiers were defined: a stringent threshold requiring significance under both corrections and a

556 relaxed threshold requiring significance under BH only. For linear analyses, null distributions

557 were generated separately for E1 and E2, restricting synthetic haplotypes to be constructed

558 within each gene.

559 **2.6 Comparison of spatial and linear entropy (Fig. 2d)**

560 Differences between spatial and linear block entropy were calculated as (spatial minus linear) per

561 window, enabling direct comparison of the two window approaches centred on the same amino

562 acid.

563 **2.7 Multimeric averaging and codon-collapsing modes (Fig. 3c-d)**

564 For the ChikV multimer, entropy values from residue-centred windows were averaged across all

565 residues mapped to each codon, producing a single representative score per codon. This approach

566 merges values but not window contexts, as each codon still spans multiple residue-centred

567 windows. More direct codon-collapsing methods, `union`, `distance`, and

568 `exposure_distance`, are implemented in `evo3D` to merge residue-centred windows into

569 unified codon-level representations.

570 **2.8 Interface capture of ChikV E1-E2 and Mxra8 (Fig. S2)**

571 Interface residues were identified using the CHIKV E1/E2-MXRA8 complex PDB ID: 6jo8

572 (Song et al. 2019). Inter-chain contacts were defined by a 4 Å distance threshold

573 (`interface_dist_cutoff`, default = 4) specified in `pdb_controls`.

574

575 # Acknowledgments

576 The authors thank Ilinca Ciubotariu and Giovanna Carpi for an earlier collaboration that shaped

577 our appreciation for structure-informed analysis and motivated this work. We also acknowledge

578   the support of the Rosen Center for Advanced Computing at Purdue University.
579

Author Contributions

581   B.K.B.: Conceptualisation, Data curation, Formal analysis, Software, Writing; Q.H.:
582   Conceptualisation, Funding acquisition, Supervision, Writing

Funding

584   B.K.B. and Q.H. were supported in part by NIH award 1R21AI187928-01A1 and BIO-SPARK
585   award. B.K.B. was supported by the Yeunkyung Woo Achieve Excellence Travel Award to share
586   early `evo3D` developments at Evolution 2025.
587

Data Availability

589   `evo3D` package code is available at https://github.com/bbroyle/evo3D, and can be installed
590   through `devtools::install_github('bbroyle/evo3D')`. Data and code for all
591   results and supplementary results are available at 10.5281/zenodo.17913899.

  FIGURES AND FIGURE LEGENDS:

Figure 1. Illustration of the `evo3D` workflow and the spatial haplotype extraction process.
(a) Required user inputs include a multiple sequence alignment (MSA) (nucleotide or amino acid) and a PDB/mmCIF structure (single chain or complex). In the example of user inputs, two gene MSAs correspond to one protein complex. `run_evo3d()` automatically maps structure chains to MSAs, defines 3D neighbourhoods (patches), aligns the PDB sequence to the MSA, and computes spatial haplotype statistics. Outputs include an MSA-PDB mapping table, spatial haplotypes (MSA subsets) (optionally written to file), and selection maps projected onto the structure. **(b)** Spatial haplotypes are constructed by (1) defining a 3D neighbourhood around a centroid residue (tuneable parameters control neighbourhood definition); (2) propagating residue positions to codon positions via the PDB→MSA map; and (3) extracting and concatenating those MSA columns to generate spatial haplotypes. The process is more complicated for multimeric assemblies (see the main text). *Abbreviations:* aa, amino acid; nt, nucleotide.

Figure 2. Spatial block entropy analysis of the Hepatitis C virus E1E2 complex. (a)
Normalised single-site Shannon entropy of amino acid frequencies across 271 genotype 1b
genomes, mapped onto PDB ID: 8fsj. Values are scaled to the maximum observed value of 3.4.
Invariant sites are shown in grey. **(b)** Normalised spatial block entropy, calculated as Shannon
entropy of haplotype frequencies for each spatial neighbourhood, scaled to the maximum
observed entropy of 7.7. Spatial neighbourhood is defined as a surface-accessible centroid
residue and its 14 nearest surface-accessible neighbouring residues. The entropy values of the
neighbourhoods are mapped to centroid residues. Grey indicates buried residues excluded by the
solvent-accessibility filter. **(c)** Significantly conserved and diverse spatial neighbourhoods
identified by comparison to an empirical null model of randomized surface haplotypes (see
Methods). Four conserved patches (507, 606, 662, 685) and one diverse patch (476) were
detected on E2 (residue numbering following 8fsj). **(d)** Block entropy differences between spatial
and linear haplotypes. Both haplotype definitions are centred on the same amino acid: linear
haplotypes include ±7 residues along sequence, while spatial haplotypes include the 14 nearest
surface residues in 3D. Colours represent spatial minus linear values on a symmetric scale (–6 to
+6). The maximum observed positive difference was +3.9 bits and maximum observed negative
difference was -5.8 bits.

Figure 3. `evo3D` analysis of large multimeric complexes illustrated with the Chikungunya virus E1E2 octamer. (a) Domain organization of the E1E2 octamer, composed of four E1E2 heterodimers. E2 chains are shown in blue, orange, green, and yellow; E1 chains are shown in shades of grey. **(b)** Spatial neighbourhoods defined for residue 146 of E2 (8fcg numbering), with residue 146 in magenta. Chain colours are consistent with panel A. The source chain of residue 146 and the block entropy of each neighbourhood are indicated above the corresponding window. Because each codon is represented in four chains, values in (c) and (d) are merged across chains, such that the displayed block entropy was averaged across the four neighbourhoods. **(c)** Isolated E1 and E2 chains from (d), shown separately for clarity. Spatial neighbourhoods can cross E1 and E2 chains, as illustrated in panel B. **(d)** Normalized block entropy, values are scaled to the observed maximum of 2.2. Grey residues in (c) and (d) are solvent-inaccessible and therefore excluded from spatial neighbourhoods.

Supplementary Figure Legends

Figure S1. Accessibility of significantly conserved and diverse surface patches in the Hepatitis C virus E1E2 complex. (a) Significantly conserved (blue) and diverse (red) neighbourhoods identified in Fig. 2c (PDB ID: 8fsj) are shown superimposed on the experimentally solved E1E2 dimer (PDB ID: 8rjj; RMSD = 1.295 across 2043 atoms). The neighbourhood of residue 606 is surface-accessible, while the neighbourhood of residue 507 is likely less accessible as an epitope due to steric hindrance. The neighbourhood of residue 476 is diverse and fully accessible, consistent with known frequent immune recognition. **(b)** The same significant patches mapped to the predicted trimer by superimposing 8fsj onto an AlphaFold3-predicted trimer (RMSD = 2.091 across 2176 atoms). Neighbourhoods for residues 606 and 476 are predicted to be accessible, while the conserved neighbourhood around residue 507 participates in the predicted trimer interface.

Figure S2. Interface-aware capture in `evo3D` enables binding interfaces to be analysed as spatial neighbourhoods. (a) MXRA8 (pink) bound to the Chikungunya virus E1/E2 complex (PDB ID: 6jo8), with the viral surface coloured by normalised block-entropy values derived from spatial windows constructed on the octameric assembly (PDB ID: 8fcg) (see Fig. 3d). This visualisation shows how variable and conserved spatial patches identified in Fig. 3d relate to the MXRA8-binding footprint. The grey region in the upper left corresponds to the E3 protein, for which no MSA information was generated in this study. **(b)** Per-site amino acid entropy across the three copies of E1/E2 - MXRA8 binding interface compared to per-site entropy of the full E1/E2 surface (computed using 8fcg). Interface contacts were defined from 6jo8. Because both 6jo8 and 8fcg map to the same MSAs, codon positions are directly comparable, allowing an interface defined in one structure to be evaluated on the other.

References

Abramson J, Adler J, Dunger J, Evans R, Green T, Pritzel A, Ronneberger O, Willmore L, Ballard AJ, Bambrick J, et al. 2024. Accurate structure prediction of biomolecular interactions with AlphaFold 3. *Nature* 630:493–500.

Alhammad Y, Gu J, Boo I, Harrison D, McCaffrey K, Vietheer PT, Edwards S, Quinn C, Coulibaly F, Poumbourios P, et al. 2015. Monoclonal Antibodies Directed toward the Hepatitis C Virus Glycoprotein E2 Detect Antigenic Differences Modulated by the N-Terminal Hypervariable Region 1 (HVR1), HVR2, and Intergenotypic Variable Region. *Journal of Virology* 89:12245–12261.

Armon A, Graur D, Ben-Tal N. 2001. ConSurf: an algorithmic tool for the identification of functional regions in proteins by surface mapping of phylogenetic information1. *Journal of Molecular Biology* 307:447–463.

Augestad EH, Holmboe Olesen C, Grønberg C, Soerensen A, Velázquez-Moctezuma R, Fanalista M, Bukh J, Wang K, Gourdon P, Prentoe J. 2024. The hepatitis C virus envelope protein complex is a dimer of heterodimers. *Nature* 633:704–709.

Bailey JR, Barnes E, Cox AL. 2019. Approaches, Progress, and Challenges to Hepatitis C Vaccine Development. *Gastroenterology* 156:418–430.

Benjamini Y, Hochberg Y. 1995. Controlling the False Discovery Rate: A Practical and Powerful Approach to Multiple Testing. *Journal of the Royal Statistical Society: Series B (Methodological)* 57:289–300.

Berglund A-C, Wallner B, Elofsson A, Liberles DA. 2005. Tertiary Windowing to Detect Positive Diversifying Selection. *J Mol Evol* 60:499–504.

Bodenhofer U, Bonatesta E, Horejš-Kainrath C, Hochreiter S. 2015. msa: an R package for multiple sequence alignment. *Bioinformatics* 31:3997–3999.

Camacho C, Coulouris G, Avagyan V, Ma N, Papadopoulos J, Bealer K, Madden TL. 2009. BLAST+: architecture and applications. *BMC Bioinformatics* 10:421.

Charif D, Lobry JR. 2007. SeqinR 1.0-2: a contributed package to the R project for statistical computing devoted to biological sequences retrieval and analysis. In: Bastolla U, Porto M, Roman HE, Vendruscolo M, editors. Structural approaches to sequence evolution: Molecules, networks, populations. Biological and Medical Physics, Biomedical Engineering. New York: Springer Verlag. p. 207–232.

Chivot L, Mathieux N, Cosson A, Bridier-Nahmias A, Favennec L, Gelly J-C, Clain J, Coppée R. 2025. CONSTRUCT: an algorithmic tool for identifying functional or structurally important regions in protein tertiary structure. *Bioinformatics* 41:btaf166.

Chmielewski D, Su G-C, Kaelber JT, Pintilie GD, Chen M, Jin J, Auguste AJ, Chiu W. 2024. Cryogenic electron microscopy and tomography reveal imperfect icosahedral symmetry in alphaviruses. *PNAS Nexus* 3:pgae102.

Ciubotariu II, Broyles BK, Xie S, Thimmapuram J, Mwenda MC, Mambwe B, Mulube C, Matoba J, Schue JL, Moss WJ, et al. 2024. Diversity and selection analyses identify transmission-blocking antigens as the optimal vaccine candidates in Plasmodium falciparum. *eBioMedicine* [Internet] 106. Available from: https://www.thelancet.com/journals/ebiom/article/PIIS2352-3964(24)00262-7/fulltext?uuid=uuid%3Ade4697ba-b668-4420-835b-b7a82f238a3b

Echave J, Spielman SJ, Wilke CO. 2016. Causes of evolutionary rate variation among protein sites. *Nat Rev Genet* 17:109–121.

Eddelbuettel D. 2013. Seamless R and C++ Integration with Rcpp. New York: Springer

Eddelbuettel D, Balamuta JJ. 2018. Extending R with C++: A Brief Introduction to Rcpp. *The American Statistician* 72:28–36.

Eddelbuettel D, François R. 2011. Rcpp: Seamless R and C++ Integration. *Journal of Statistical Software* 40:1–18.

Eddelbuettel D, Francois R, Allaire JJ, Ushey K, Kou Q, Russell N, Ucar I, Bates D, Chambers J. 2024. Rcpp: Seamless R and C++ Integration. Available from: https://CRAN.R-project.org/package=Rcpp

Edgar RC. 2022. Muscle5: High-accuracy alignment ensembles enable unbiased assessments of sequence homology and phylogeny. *Nat Commun* 13:6968.

Falson P, Bartosch B, Alsaleh K, Tews BA, Loquet A, Ciczora Y, Riva L, Montigny C, Montpellier C, Duverlie G, et al. 2015. Hepatitis C Virus Envelope Glycoprotein E1 Forms Trimers at the Surface of the Virion. *Journal of Virology* 89:10333–10346.

Golding GB, Dean AM. 1998. The structural basis of molecular adaptation. *Molecular Biology and Evolution* 15:355–369.

Grant BJ, Rodrigues APC, ElSawy KM, McCammon JA, Caves LSD. 2006. Bio3d: an R package for the comparative analysis of protein structures. *Bioinformatics* 22:2695–2696.

Guy AJ, Irani V, Richards JS, Ramsland PA. 2018. BioStructMap: a Python tool for integration of protein structure and sequence-based features. *Bioinformatics* 34:3942–3944.

Hekkelman ML, Salmoral DÁ, Perrakis A, Joosten RP. 2025. DSSP 4: FAIR annotation of protein secondary structure. *Protein Science* 34:e70208.

Hu Y, Tan PT, Tan TW, August JT, Khan AM. 2013. Dissecting the Dynamics of HIV-1 Protein Sequence Diversity. *PLOS ONE* 8:e59994.

Kabsch W, Sander C. 1983. Dictionary of protein secondary structure: Pattern recognition of
hydrogen-bonded and geometrical features. *Biopolymers* 22:2577–2637.

Landgraf R, Xenarios I, Eisenberg D. 2001. Three-dimensional cluster analysis identifies
interfaces and functional residue clusters in proteins1. *Journal of Molecular Biology*
307:1487–1502.

Lichtarge O, Bourne HR, Cohen FE. 1996. An Evolutionary Trace Method Defines Binding
Surfaces Common to Protein Families. *Journal of Molecular Biology* 257:342–358.

Metcalf MC, Janus BM, Yin R, Wang R, Guest JD, Pozharski E, Law M, Mariuzza RA, Toth EA,
Pierce BG, et al. 2023. Structure of engineered hepatitis C virus E1E2 ectodomain in
complex with neutralizing antibodies. *Nat Commun* 14:3980.

Nei M. 1987. Molecular Evolutionary Genetics. New York Chichester, West Sussex: Columbia
University Press Available from: https://doi.org/10.7312/nei-92038

Nei M, Tajima F. 1981. DNA polymorphism detectable by restriction endonucleases. *Genetics*
97:145–163.

Olsen LR, Zhang GL, Keskin DB, Reinherz EL, Brusic V. 2011. Conservation Analysis of
Dengue Virus T-cell Epitope-Based Vaccine Candidates Using Peptide Block Entropy. *Front
Immunol* 2:69.

Olson RD, Assaf R, Brettin T, Conrad N, Cucinell C, Davis JJ, Dempsey DM, Dickerman A,
Dietrich EM, Kenyon RW, et al. 2023. Introducing the Bacterial and Viral Bioinformatics
Resource Center (BV-BRC): a resource combining PATRIC, IRD and ViPR. *Nucleic Acids
Res* 51:D678–D689.

Paradis E. 2010. pegas: an R package for population genetics with an integrated–modular
approach. *Bioinformatics* 26:419–420.

R Core Team. 2024. R: A Language and Environment for Statistical Computing. Vienna, Austria:
R Foundation for Statistical Computing Available from: https://www.R-project.org/

Raman HSA, Tan S, August JT, Khan AM. 2020. Dynamics of Influenza A (H5N1) virus protein
sequence diversity. *PeerJ* 7:e7954.

Reis PBPS, Barletta GP, Gagliardi L, Fortuna S, Soler MA, Rocchia W. 2022. Antibody-Antigen
Binding Interface Analysis in the Big Data Era. *Front. Mol. Biosci.* [Internet] 9. Available
from: https://www.frontiersin.org/journals/molecular-
biosciences/articles/10.3389/fmolb.2022.945808/full

Shannon CE. 1948. A mathematical theory of communication. *The Bell System Technical Journal*
27:379–423.

Shen W, Sipos B, Zhao L. 2024. SeqKit2: A Swiss army knife for sequence and alignment
processing. *iMeta* 3:e191.

Sievers F, Wilm A, Dineen D, Gibson TJ, Karplus K, Li W, Lopez R, McWilliam H, Remmert M,
Söding J, et al. 2011. Fast, scalable generation of high-quality protein multiple sequence
alignments using Clustal Omega. *Mol Syst Biol* 7:539.

Song H, Zhao Z, Chai Y, Jin X, Li C, Yuan F, Liu S, Gao Z, Wang H, Song J, et al. 2019.
Molecular Basis of Arthritogenic Alphavirus Receptor MXRA8 Binding to Chikungunya
Virus Envelope Protein. *Cell* 177:1714-1724.e12.

Suzuki Y. 2004. Three-Dimensional Window Analysis for Detecting Positive Selection at
Structural Regions of Proteins. *Molecular Biology and Evolution* 21:2352–2359.

Tajima F. 1989. Statistical method for testing the neutral mutation hypothesis by DNA
polymorphism. *Genetics* 123:585–595.

Tharanga S, Ünlü ES, Hu Y, Sjaugi MF, Çelik MA, Hekimoğlu H, Miotto O, Öncel MM, Khan
AM. 2025. DiMA: sequence diversity dynamics analyser for viruses. *Brief Bioinform*
26:bbae607.

The UniProt Consortium. 2025. UniProt: the Universal Protein Knowledgebase in 2025. *Nucleic*
Acids Res 53:D609–D617.

Tokheim C, Bhattacharya R, Niknafs N, Gygax DM, Kim R, Ryan M, Masica DL, Karchin R.
2016. Exome-Scale Discovery of Hotspot Mutation Regions in Human Cancer Using 3D
Protein Structure. *Cancer Research* 76:3719–3731.

Torrents de la Peña A, Sliepen K, Eshun-Wilson L, Newby ML, Allen JD, Zon I, Koekkoek S,
Chumbe A, Crispin M, Schinkel J, et al. 2022. Structure of the hepatitis C virus E1E2
glycoprotein complex. *Science* 378:263–269.

Zhang R, Kim AS, Fox JM, Nair S, Basore K, Klimstra WB, Rimkunas R, Fong RH, Lin H,
Poddar S, et al. 2018. Mxra8 is a receptor for multiple arthritogenic alphaviruses. *Nature*
557:570–574.