pylifemap: Mapping Data onto the Tree of Life

Julien Barnier[1,*], Cassandra Bompard[1], Aurélie Siberchicot[1], Vincent Navratil[2,3,4], Joaquim Martin[5], Damien M. de Vienne[1,6,*]

[1] Université de Lyon, Université Lyon 1, UMR CNRS 5558 Laboratoire de Biométrie et Biologie Évolutive, 69622 Villeurbanne, France

[2] PRABI, Pôle Rhône-Alpes Bioinformatics Center, Université Claude Bernard Lyon 1, 69622, Villeurbanne, France

[3] Institut Français de Bioinformatique, IFB-Core, UMS 3601, 2 rue Gaston Crémieu, Évry Cedex 91057, France

[4] European Virus Bioinformatics Center, Leutragraben 1, Jena 07743, Germany

[5] Independent Software Engineer, 38200 Saint-Sorlin-de-Vienne, France

[6] Biodiversity Computing Group, Institute of Computer Science, Foundation for Research and Technology Hellas, 100 Nikolaou Plastira, 70013 Heraklion, Crete, Greece

[*] Corresponding authors:
    DAMIEN M. DE VIENNE, JULIEN BARNIER
    Université Lyon 1, CNRS
    Laboratoire de Biométrie et Biologie Évolutive
    Bâtiment Mendel 43 boulevard du 11 Novembre 1918
    69622 VILLEURBANNE CEDEX
    E-mails: damien.de-vienne@univ-lyon1.fr ; julien.barnier@cnrs.fr

Abstract

The need to visualize data associated with NCBI Taxonomy Identifiers (taxids) is growing in various biological fields ranging from comparative genomics to metagenomics and metabarcoding, and even for outreach. No tool today allows to visualize such data while still keeping the full vision of the whole taxonomy, possibly causing a biased view of the data at hand. Here we introduce *pylifemap*, a python package that allows users to map their own data directly on the interactive taxonomic tree proposed by Lifemap. Through a simple syntax, layers (points, lines, icons, heatmaps, etc.) depicting any type of data are superimposed on the Lifemap basemap, producing an interactive map to inspect biological datasets. The produced visualizations can easily be shared with others through notebooks or standalone html files, or exported as static images. We illustrate the utility of *pylifemap* in the exploration of two contrasted datasets: the IUCN Red List of Threatened Species and the output of a large-scale environmental metagenomics experiment.

pylifemap is released under the MIT license and is available at PiPy and easily installable with pip or uv.data s The development version can be found at https://github.com/Lifemap-ToL/pylifemap and extensive documentation with examples is available at https://lifemap-tol.github.io/pylifemap.

Keywords: Lifemap, metagenomics, taxonomic classification, visualization, Tree of Life

1. Introduction

Visualization of large datasets associated with taxonomic identifiers is increasingly essential across various fields. In metagenomics for instance, sequenced biological samples and their subsequent analysis leads to lists of taxa, identified by their taxonomic identifiers, associated with estimated abundance information. In comparative genomics, genomic data relevant to groups of species can be computed and analyzed. In ecology, diverse ecological data are routinely obtained for species, with their taxid being extractable. In all these cases (and others), visualizing these data is crucial, as it facilitates accurate data interpretation and helps reduce possible biases.

In 2016, we released Lifemap (https://lifemap.cnrs.fr), a web application for the interactive exploration of the entire NCBI taxonomy (de Vienne 2016). The Lifemap explorer resembles modern interactive geographical maps, except that the map is taxonomical instead of geographical. Exploration of the full taxonomy (as provided by the NCBI, Federhen 2012; Schoch et al. 2020) is done by zooming and panning, and only the relevant information is given at each zoom level. This way, the entire taxonomy can be explored intuitively and interactively. Lifemap has become over the years a reference for exploring and presenting the Tree of Life with around 20k unique visitors/month. In addition to being a useful resource to explore taxonomy and get easy access to related databases (e.g. NCBI, IUCN, GBIF 2025; iNaturalist 2025, etc.), Lifemap also provides a unique interactive map of the whole taxonomy that can be reused for other purposes.

By employing Lifemap as a basemap (or background map), we propose here a tool, *pylifemap,* for easily displaying information related to various taxa on the map directly. With this python package, users can input and visualize data of any type associated with NCBI taxonomy identifiers (taxids). These identifiers are used to locate the position of each taxa on the Lifemap basemap, and user-defined layers (points, lines, heatmaps, etc.) are overlaid on the map to display the desired information. These layers can represent different aspects of the data, and users can define as many layers as necessary to suit their specific needs.

This new visualization method of taxa-related biological data offers many benefits: (i) very large datasets (up to millions of taxa and associated data) can be explored easily because the map (and thus the associated data) is interactive, (ii) it provides a broad (complete) taxonomic context for the data by encompassing the entire taxonomy, rather than solely focusing on taxa with available data, as is the typical practice (e.g. Ondov et al. 2011; Breitwieser and Salzberg 2020), and (iii) it provides an evolutionary view of the data at hand, which is primordial for a full understanding of biological patterns ("Nothing in biology makes sense except in the light of evolution", Dobzhansky 1973).

In order to illustrate the use of *pylifemap* and briefly present its underlying syntax, we used two datasets. The first one is the IUCN Red List of Threatened Species, a list of 172,620 animals, fungi and plants categorized based on their risk of extinction (IUCN 2025). The second is the output of the taxonomic classification tool Kraken2 (Wood et al. 2019) applied to environmental samples collected in 2020 in the Huanan seafood market in Wuhan, China (Liu et al. 2024). To facilitate comparison and visualization, this dataset was combined with another one listing the wild animal species sold in the same market just prior to the pandemic (Xiao et al. 2021). This comparison is important for understanding the potential origins of the SARS-CoV-2 pandemic (Crits-Christoph et al. 2024).

As the volume of available sequence data continues to grow (e.g. Katz et al. 2022), downstream analyses will inevitably generate an increasing number of datasets as well. Approaches such as the

one proposed here for visualizing extensive data on an interactive and exhaustive taxonomic map may soon become a standard practice.

2. *pylifemap* overview

pylifemap allows mapping data associated with NCBI taxonomy identifiers (hereafter taxids) on the interactive taxonomy explorer Lifemap (de Vienne 2016). To do so, *pylifemap* takes as input a pandas or polars data frame with one column listing the taxids of interest and other columns containing associated data of any kind (numerical, categorical, textual, etc.). From this, *pylifemap* proceeds through a two-step process: first, it calls the Lifemap database to retrieve the coordinates of the different taxids and of their ancestors on the map. Second, it maps the data provided by the user at the correct location on the map, following the graphical and mapping instructions given by the user.

The basemap (or background map) on which the data are plotted is the same as the one on which the public Lifemap website relies (https://lifemap.cnrs.fr), although it can be differently styled for cleaner visualization and easier integration of the produced visualizations in publications. The taxonomy displayed in the basemap is automatically updated weekly, in order to be always up to date with the latest version of the NCBI taxonomy (Federhen 2012; Schoch et al. 2020).

Under the hood, the visualizations produced by *pylifemap* are Jupyter widgets powered by the *anywidget* framework (Manz et al. 2024). These widgets can be produced and used interactively in notebook-like environments such as Jupyter, Marimo or Quarto, or generated from a Python script to be viewed in a web browser or saved as an HTML file.

Visualization options and basics syntax

pylifemap proceeds by the superposition of layers on the basemap. Each layer can display either points, lines, text, icons, heatmap, donut charts or screengrid, and graphical options allow these layers to be precisely parametrized (e.g. colors, radius size, line width, etc.) according to the data. Popups (opening on click) and their associated content can also be defined, parametrized by the user and associated to each element in each layer.

The syntax used by *pylifemap* for visualization is straightforward. A general function `Lifemap()` is used to load the dataset, and define general parameters for the map such as the theme, the width and height, the initial center and zoom level, etc. Then a list of layer methods (e.g. `Lifemap.layer_points()`) are used to define the elements present on the map, their appearance (color, size, etc.) and their dependence with values of the input dataframe (inherited from the `Lifemap()` function or defined for each layer). Finally, the `Lifemap.show()` and the `Lifemap.save()` functions are used to respectively open the map for interactive visualization (in the browser or as a widget) or save the map as an HTML file for easy sharing and integration in websites. As an example, for a dataframe `df` the basic syntax for plotting points for taxa in column "`taxid`" with radius proportional to column "`value`" is:

```
Lifemap(df).layer_points(radius="value").show()
```

More syntax examples are provided below along with the biological illustrations.

Inferred values at parent nodes

pylifemap also provides functions to compute values associated with parent nodes in the taxonomy for each variable of the initial dataset. Three such "aggregation" functions are provided: `aggregate_count()` to count at each nodes the number of descendant taxids present in the initial dataset, `aggregate_num()` to apply a function (min, max, mean, median and sum) to numerical variables associated to taxids present in the dataset, and `aggregate_freq()` to compute frequencies of categorical variables associated to the taxids in the initial dataset.

These functions (and others ones, more technical and not detailed here) help visualizing very large datasets, because the information present at deep zoom levels in the taxonomy can be summarized at lower zoom levels (higher taxonomic ranks), leveraging the amount of information to be plotted simultaneously on the map.

Utility functions

Utility functions are provided along *pylifemap* to better characterize the dataset at hand: the function `get_unknown_taxids()` lists the taxids in the dataset that are unknown in Lifemap (e.g. in the latest version of the NCBI taxonomy presented in Lifemap, i.e. one week old at must); the function `get_duplicated_taxids()` retrieves the list of taxids in the dataset that are duplicated. Note that only the first occurrence of the taxid in the dataset (first row where it appears) is used for plotting in *pylifemap*. In case of unknown or duplicated taxids in the dataset, visualization functions still work but a warning is issued to the user.

3. Illustrative example of the use of *pylifemap* on biological datasets

In order to demonstrate how *pylifemap* can be utilized, we present here two different examples of its usage in the visualization of datasets in distinct biological contexts. Note that because the Lifemap explorer is interactive by nature, rendering the visual experience on static images is not ideal. The examples presented below with a single image export (Figure 1) are also available online for interactive exploration in a gallery (along with other examples) accessible at https://lifemap-tol.github.io/pylifemap/gallery/gallery.html.

IUCN Red List

The International Union for Conservation of Nature's Red List of Threatened Species is an indicator of the health of the world's biodiversity. Focusing on animals, plants and fungi, it provides an up-to-date extinction risk status for 172,620 species (IUCN 2025).

For 103,116 of these species, we could recover their corresponding NCBI taxid by mapping their latin name to the latest taxonomy using the ete3 python package (Huerta-Cepas et al. 2016). We then used the function `aggregate_freq()` of *pylifemap* to compute the proportion of species belonging to each one of the 11 IUCN categories for each node of the taxonomy (see Supplementary Material for full details on the data and method used). These proportions were plotted with *pylifemap* using donuts charts. The code leading to this visualization is given below; a snapshot of the visualization itself is provided in Figure 1A.

```
# Load libraries
from pylifemap import Lifemap, aggregate_freq
import pandas as pd
```

```
# Read data
df = pd.read_csv("IUCN_with_taxid_SMALL.csv")

# Compute frequencies of each category at each taxa
df_agg = aggregate_freq(df, column="redlistCategory")

# Plot data
(
  Lifemap(df_agg, theme="lightgrey")
  .layer_donuts(counts_col="redlistCategory", scheme="Turbo", radius=50, lazy_zoom=4,
declutter=False, opacity=0.8)
  .show()
)
```

The example code illustrates some of the many visualization options proposed: the basemap theme can be chosen, the color palette (scheme) for categories can be changed, lazy loading of data is possible (i.e. only data associated to taxa visible at the current zoom level and around is displayed), decluttering (preventing elements overlap) can be activated or not, etc.

The obtained visualization (Figure 1A and online gallery) is displaying a clear view of the proportion of species with each IUCN category for each node of the taxonomy. Through an exploration of the map we can easily identify, for instance, that within Batrachia, the proportion of Caudata (comprising salamanders) being endangered or critically endangered (almost 50%) is much higher than within its sister group Anura (comprising frogs, around 15%, Figure 1A). This type of visualization also illustrates an important aspect of data visualization with *pylifemap*: even a large dataset of hundreds of thousands of entries can be smoothly explored, visualized, and ultimately interpreted because data are organized and viewed in a hierarchical manner, simply following the hierarchical nature of the entities (here taxa) it is related to.

Metagenomics

Metagenomics studies involve the collection of diverse biological samples from a variety of environments, such as gut, soil, water or air to gain insights into the microbial communities present in these ecosystems. Tools such as Kraken2 (Wood et al. 2019), STAT (Katz et al. 2021), or Metaphlan (Blanco-Míguez et al. 2023) are commonly utilized to identify and classify the taxonomic composition of the microbial communities present in these samples, using a reference database for the assignment. This taxonomic characterization is then used for downstream analyses, such as microbial diversity analyses, comparative analyses, and ecological modeling.

Visualization of taxonomic content data is critical in these analyses, and multiple tools have been developed for this purpose over the years (McMurdie and Holmes 2015; Wagner et al. 2018; Thrash et al. 2019; Breitwieser and Salzberg 2020). In all cases, the taxonomic classification viewers only display taxa on which reads have been mapped, or/and their ancestors, hindering having a full picture of where in the whole taxonomy reads mapped and reads didn't map. *pylifemap*, because it relies on the full NCBI explorer Lifemap, and also because multiple layers can be superimposed, overcomes this limitation and opens new perspectives.

The metagenomics data we used here are taxonomic assignations (performed with Kraken2) of environmental samples collected in the Huanan seafood market (Wuhan, China) in the early 2020, few days after the beginning of the SARS-CoV-2 pandemic (Liu et al. 2024). To each identified

taxid is associated a number of reads uniquely pointing to it (referred to as "fragment_number"). Following (Crits-Christoph et al. 2024), and in order to best illustrate the capacities of *pylifemap* for complex data exploration, we decided to cross this metagenomics data with the list of 38 wild animal species that were found to be sold in the same market between May 2017 and November 2019 (Xiao et al. 2021), just before the beginning of the pandemics. Because these animals all belong to Amniota, we decided to subsample the metagenomics data to only the reads mapping to this clade.

Using the script below (see Supplementary Material for more explanation on file names), we used *pylifemap* to visualize these data using three layers (Figure 1B and online gallery): a point layer with size and color representing the "fragment number" from the Kraken2 output, a line layer to highlight the taxa present in the reference database used for the taxonomic assignation, and finally an icon layer to highlight – with a red cross – the wild species sold in the market (Xiao et al. 2021).

```python
# Load libraries
from pylifemap import Lifemap, aggregate_freq
import pandas as pd

# Get all metagenomics read data (Kraken2)
df = pd.read_parquet("data/wuhan_taxid_kraken2.parquet", engine='pyarrow')

# Get all taxids in the reference database at the time of the study
alltaxid = pd.read_parquet("data/kraken2_nt_28112022_inspect_tax_id.parquet",
engine="pyarrow")

# Get all taxids belonging to Amniota
amniota_taxid = pd.read_csv("data/amniota_taxid_list.csv")
amniota_taxid = amniota_taxid["taxid"].tolist()

# Subsample datasets to only Amniota
df_amniota = df[df["taxid"].isin(amniota_taxid)].copy()
alltaxid_amniota = alltaxid[alltaxid["taxid"].isin(amniota_taxid)].copy()

# Aggregate along tree nodes
alltaxid_amniota_agg = aggregate_count(alltaxid_amniota)

# Get species present in Wuhan market
wuhan_taxid_df = pd.read_csv("data/wuhan_taxid_df.csv")

# PLOT
(
  Lifemap(df_amniota[df_amniota["count"]>=1000], theme="lightgrey", center=32524,
zoom=12.5)
  .layer_lines(alltaxid_amniota_agg, color="#f4aa44", width=1.5).
  .layer_icons(wuhan_taxid_df, icon="img/cross.png", scale=0.2, popup=False,
declutter=False).
  .layer_points(radius="count", fill="count", label="fragment number", radius_range =
[4,25], scheme="YlOrRd")
  .show()
)
```

Figure 1. Two exports of interactive visualizations obtained with *pylifemap*. **A.** Visualization of the proportion of species at each taxonomic rank that belong to each one of the 11 IUCN Red List categories. Numbers inside donuts represent the total number of species belonging to each clade catalogued by IUCN (data from IUCN 2025). **B.** Complex visualization of the Wuhan market metagenomics datasets with three layers: (i) the number of reads mapping to taxa – as represented by the color and size of the points – following a taxonomic classification with Kraken2 (data from Liu et

al. 2024, see text); (ii) the paths to the taxa available in the reference GenBank nt database used as a reference for Kraken2, represented by orange lines along the tree branches; (iii) the wild animals sold on the Wuhan market just before the pandemics, highlighted by red crosses (data from Xiao et al. 2021). The interactive visualizations associated to these snapshots are available at https://lifemap-tol.github.io/pylifemap/gallery/sources/iucn.html (for **A**) and https://lifemap-tol.github.io/pylifemap/ gallery/sources/wuhan.html (for **B**).

Interactive exploration of the obtained map allows an easy identification of taxa with large numbers of reads mapping to them. Looking at the red crosses, we also observe that some of these taxa correspond to wild species sold in the market prior to the pandemic. This is the case of the common pig (*Sus scrofa*), the chinese bamboo (*Rhizomys sinensis*), Reeves's muntjac (*Muntiacus reevesi*), Amur hedgehog (*Erinaceus amurensis*) and the racoon dog (*Nyctereutes procyonoides*). Coloring the evolutionary path from the root to the list of species included in the reference database used by Kraken2 highlights interesting cases where the genomes of animals present in the market are not available in the reference database (like the masked palm civet *Paguma larvata*) or more complex cases where the taxonomic assignment occurs with known similar genomes (Siberian weasel (*Mustela sibirica*)). The interactive visualization, taxonomy-oriented, also reveals thousands of reads assigned to species belonging to *Cetacea, Chiroptera, Gekkota*, either suggesting Kraken2 taxonomic assignment errors, or revealing the presence of living organisms found in the market (e.g. *Pipistrellus pipistrellus*) or species not reported as sold by the vendors (e.g. a turtle of the sub-order *Cryptodira*).

Discussion and conclusion

The visualization tool we propose here with *pylifemap* consists in mapping data on a pre-established map, or basemap, representing the taxonomic relationships between all taxa present in the NCBI taxonomy. This way of displaying and analyzing information directly on a map recalls Geographic Information Systems (GISs), i.e. computer systems where geographic data (location information) are linked with various descriptive information, enabling the visualization but also the analysis of data related to spatial relationships and patterns (for a review on GIS, see Wieczorek and Delmerico 2009). What we propose here could be referred to as a Taxonomic Information System (TIS), although very simple, where taxonomic data (the identity and localization of taxa on Lifemap) – in place of geographic data – are connected to various descriptive information and can be visualized and analyzed. This new way of treating biological data in a taxonomic context (i.e. as a TIS) may open new perspectives for the analysis and visualization of large taxonomy-centered datasets. Still, clear differences remain. For instance, GIS manipulates a basemap that is continuous and complete, when taxonomy might be incomplete or difficult to map to datasets that do not rely on taxonomy identifiers from the start, as seen with the two examples presented here. Similarly, spatial distances have a clear and constant meaning in GIS, when taxonomic distance is discrete, is changing through time, and does not correlate with the distance observed in the Lifemap basemap. These differences show the limits of treating TIS as GIS, but making the parallel could undoubtedly inspire analytical principles to enrich the exploration of large taxonomy-structured datasets.

In conclusion, the *pylifemap* package provides an effective and user-friendly solution for visualizing and sharing taxid-associated biological data on the NCBI taxonomic tree viewer, Lifemap. The package is highly customizable, allowing for easy computation and visualization of summary statistics at internal nodes. The demonstration of the utility of *pylifemap* on two contrasting biological datasets emphasizes its potential to explore and analyze large, complex and diverse

datasets, making it a valuable resource for researchers in (meta)genomics, microbiology, ecology, and related fields, but also for outreach activities around taxonomy, systematics, and the Tree of Life.

Acknowledgment
This work was performed using the computing facilities of the CC LBBE/PRABI.

Funding
This work was supported by ANR-18-CE02-0007 to Damien M. de Vienne and by the project Virome@tlas (SHAPE-Med@Lyon) to Vincent Navratil.

References

Blanco-Míguez A., Beghini F., Cumbo F., McIver L.J., Thompson K.N., Zolfo M., Manghi P., Dubois L., Huang K.D., Thomas A.M., Nickols W.A., Piccinno G., Piperni E., Punčochář M., Valles-Colomer M., Tett A., Giordano F., Davies R., Wolf J., Berry S.E., Spector T.D., Franzosa E.A., Pasolli E., Asnicar F., Huttenhower C., Segata N. 2023. Extending and improving metagenomic taxonomic profiling with uncharacterized species using MetaPhlAn 4. *Nature Biotechnology*.:1–12.

Breitwieser F.P., Salzberg S.L. 2020. Pavian: interactive analysis of metagenomics data for microbiome studies and pathogen identification. *Bioinformatics*. 36:1303–1304.

Crits-Christoph A., Levy J.I., Pekar J.E., Goldstein S.A., Singh R., Hensel Z., Gangavarapu K., Rogers M.B., Moshiri N., Garry R.F., Holmes E.C., Koopmans M.P.G., Lemey P., Peacock T.P., Popescu S., Rambaut A., Robertson D.L., Suchard M.A., Wertheim J.O., Rasmussen A.L., Andersen K.G., Worobey M., Débarre F. 2024. Genetic tracing of market wildlife and viruses at the epicenter of the COVID-19 pandemic. *Cell*. 187:5468-5482.e11.

Dobzhansky T. 1973. Nothing in Biology Makes Sense except in the Light of Evolution. *The American Biology Teacher*. 35:125–129.

Federhen S. 2012. The NCBI Taxonomy database. *Nucleic Acids Research*. 40:D136–D143.

GBIF. 2025. Available from https://www.gbif.org/fr/.

Huerta-Cepas J., Serra F., Bork P. 2016. ETE 3: Reconstruction, Analysis, and Visualization of Phylogenomic Data. *Molecular Biology and Evolution*. 33:1635–1638.

iNaturalist. 2025. Available from https://www.inaturalist.org/.

IUCN. 2025. The IUCN Red List of Threatened Species. Version 2025-2. Available from https://www.iucnredlist.org.

Katz K., Shutov O., Lapoint R., Kimelman M., Brister J.R., O'Sullivan C. 2022. The Sequence Read Archive: a decade more of explosive growth. *Nucleic Acids Research*. 50:D387–D390.

Katz K.S., Shutov O., Lapoint R., Kimelman M., Brister J.R., O'Sullivan C. 2021. STAT: a fast, scalable, MinHash-based k-mer tool to assess Sequence Read Archive next-generation sequence submissions. *Genome Biology*. 22:270.

Liu W.J., Liu P., Lei W., Jia Z., He X., Shi W., Tan Y., Zou S., Wong G., Wang J., Wang F., Wang G., Qin K., Gao R., Zhang J., Li M., Xiao W., Guo Y., Xu Z., Zhao Y., Song J., Zhang J., Zhen W., Zhou W., Ye B., Song J., Yang M., Zhou W., Dai Y., Lu G., Bi Y., Tan W., Han J., Gao G.F., Wu G. 2024. Surveillance of SARS-CoV-2 at the Huanan Seafood Market. *Nature*. 631:402–408.

Manz T., Abdennur N., Gehlenborg N. 2024. anywidget: reusable widgets for interactive analysis and visualization in computational notebooks. *Journal of Open Source Software*. 9:6939.

McMurdie P.J., Holmes S. 2015. Shiny-phyloseq: Web application for interactive microbiome analysis with provenance tracking. *Bioinformatics*. 31:282–283.

Ondov B.D., Bergman N.H., Phillippy A.M. 2011. Interactive metagenomic visualization in a Web browser. *BMC bioinformatics*. 12:385.

Schoch C.L., Ciufo S., Domrachev M., Hotton C.L., Kannan S., Khovanskaya R., Leipe D., Mcveigh R., O'Neill K., Robbertse B., Sharma S., Soussov V., Sullivan J.P., Sun L., Turner S., Karsch-Mizrachi I. 2020. NCBI Taxonomy: a comprehensive update on curation, resources and tools. *Database: The Journal of Biological Databases and Curation*. 2020:baaa062.

Thrash A., Arick M., Barbato R.A., Jones R.M., Douglas T.A., Esdale J., Perkins E.J., Garcia-Reyero N. 2019. Keanu: a novel visualization tool to explore biodiversity in metagenomes. *BMC Bioinformatics*. 20:103.

de Vienne D.M. 2016. Lifemap: exploring the entire tree of life. *PLoS biology*. 14:e2001624.

Wagner J., Chelaru F., Kancherla J., Paulson J.N., Zhang A., Felix V., Mahurkar A., Elmqvist N., Corrada Bravo H. 2018. Metaviz: interactive statistical and visual analysis of metagenomic data. *Nucleic Acids Research*. 46:2777–2787.

Wieczorek W.F., Delmerico A.M. 2009. Geographic information systems. *WIREs Computational Statistics*. 1:167–186.

Wood D.E., Lu J., Langmead B. 2019. Improved metagenomic analysis with Kraken 2. *Genome Biology*. 20:257.

Xiao X., Newman C., Buesching C.D., Macdonald D.W., Zhou Z.-M. 2021. Animal sales from Wuhan wet markets immediately prior to the COVID-19 pandemic. *Scientific Reports*. 11:11898.