A geometric-surface PDE model for cell-nucleus translocation through confinement

Francesca Ballatore[1*], Anotida Madzvamuse[2,3,4,5], Cécile Jebane[6,¤], Emmanuèle Helfer[6], Rachele Allena[1,7]

1 Laboratoire Jean Alexandre Dieudonné CNRS UMR7351, Nice, France
2 Mathematics Department, University of British Columbia, Vancouver, Canada
3 Department of Mathematics and Computational Sciences, University of Zimbabwe, Mt Pleasant, Harare, Zimbabwe.
4 Department of Mathematics and Applied Mathematics, University of Pretoria, Pretoria, 0132, South Africa.
5 Applied Mathematics, University of Johannesburg, PO Box 524 Auckland Park Johannesburg, 2006, South Africa.
6 Aix-Marseille Université, CNRS, CINAM, Turing Centre for Living Systems, Marseille, France
7 Institut Universitaire de France, France

¤Current Address: A51, Tour Montparnasse, 33 avenue du Maine, 75015 Paris, France
* francesca.ballatore@univ-cotedazur.fr

Abstract

Understanding how cells migrate through confined environments is crucial for elucidating fundamental biological processes, including cancer invasion, immune surveillance, and tissue morphogenesis. The nucleus, as the largest and stiffest cellular organelle, often limits cellular deformability, making it a key factor in migration through narrow pores or highly constrained spaces. In this work, we introduce a geometric surface partial differential equation (GS-PDE) model in which the cell plasma membrane and nuclear envelope are described as evolving energetic closed surfaces governed by force-balance equations. We replicate the results of a biophysical experiment, where a microfluidic device is used to impose compressive stresses on cells by driving them through narrow microchannels under a controlled pressure gradient. The model is validated by reproducing cell entry into the microchannels. A parametric sensitivity analysis highlights the dominant influence of specific parameters, whose accurate estimation is essential for faithfully capturing the experimental setup. We found that surface tension and confinement geometry emerge as key determinants of translocation efficiency. Although tailored to this specific setup for validation purposes, the framework is sufficiently general to be applied to a broad range of cell mechanics scenarios, providing a robust and flexible tool for investigating the interplay between cell mechanics and confinement. It also offers a solid foundation for future extensions integrating more complex biochemical processes such as active confined migration.

Author summary

Cells often migrate through very narrow spaces in tissues, a process critical for cancer invasion, immune surveillance, and tissue development. In particular, the stiffness of the nucleus, the largest and most rigid organelle, can limit migration through tight pores.

In this study, we present a mathematical model describing the motion of a cell and its nucleus through a microchannel during cell translocation, using a geometric formulation based on surface partial differential equations. The model is general and applicable to a variety of scenarios involving confined cell transport. The model is validated by reproducing key experiments on translocation through narrow microchannels. The framework incorporates essential surface features, including mechanical responses, bending rigidity, and surface tension. Sensitivity analysis highlights surface tension and channel geometry as the parameters most strongly influencing translocation. Overall, the model provides new insights into the mechanics of confined cell transport, grants access to cellular quantities that are difficult to measure experimentally, such as cell and nucleus areas, perimeters, and stresses, and establishes a foundation for future extensions incorporating more complex biochemical processes.

Introduction

Cell migration in confined environments is a fundamental mechanobiological process that plays a crucial role in many aspects of cellular life, including development and embryogenesis [1, 2], immune response [3, 4], and cancer metastasis [5, 6]. Cells may need to migrate through pores of varying sizes, which can sometimes be sub-cellular or even sub-nuclear. During migration through interstitial matrices, cells must overcome the physical barriers imposed by the dense extracellular network [7, 8]. To circumvent these constraints, cells secrete proteases that degrade the matrix, thereby enlarging pores and facilitating cell migration [9, 10]. Alternatively, cells that are unable to degrade the extracellular matrix (ECM) must squeeze through pre-existing pores in the matrix [11]. In this context, the role of the nucleus cannot be neglected, as it often represents the largest (ranging from 5 to 20 μm) and stiffest organelle within the cell, acting as a physical barrier that can slow down movement or even inhibit migration altogether [12]. Cellular displacement under confinement is regulated by a complex interplay between biochemical signaling, cytoskeletal remodeling, and mechanical forces exerted by the ECM [13, 14]. Nevertheless, the precise mechanical response of cells to spatial confinement remains poorly understood. Recent studies have shown that cells adapt by modulating nuclear deformability, actomyosin contractility, and cytoskeletal organization to overcome geometric restrictions [15], indicating that confinement is not merely a passive barrier but an active determinant of cell behavior and fate. Cells forced through microfluidic constrictions provide a valuable experimental platform for probing and quantifying their mechanical properties in vitro [16–18]. By observing how cells deform and transit through narrow channels, researchers can gain insights into cellular stiffness, elasticity, and viscoelastic responses under controlled conditions.

To achieve a deeper understanding of this phenomenon, numerous mathematical models have been developed in recent years to quantify stress and strain fields and to identify the key parameters governing cellular responses to different stimuli [19]. Mathematical modeling serves as a powerful tool to investigate these processes, particularly when experimental data are scarce or difficult to obtain. Moreover, computational approaches are crucial for validating theoretical predictions against empirical observations, ultimately offering new perspectives on cell dynamics. The majority of these studies employ discrete approaches to examine cell invasiveness, focusing on parameters such as migration speed, displacement, and nuclear deformability. In [20], the authors investigate the role of nuclear deformability in regulating the ability of a cell to penetrate a three-dimensional extracellular structure, adopting a continuum mechanics description of the nucleus. Their findings emphasize the crucial interplay between the mechanical compliance of the nucleus and the cell's capacity to form adhesive bonds, showing that both aspects jointly determine the

efficiency of cell infiltration. In [21, 22], the authors employ a Cellular Potts Model to develop a computational framework for confined migration that explicitly accounts for both cell and nuclear sizes as well as their stiffness. These studies highlight the strength of multi-compartment modeling in unravelling the relative contributions of different physical factors that collectively shape migration under confinement. In particular, their results demonstrate that the size of the surrounding environment plays a decisive role in determining the observed migration phenotype. Mathematical models can also serve as powerful tools for designing microfluidic systems and organ-on-a-chip devices. For example, in [23], the authors establish a direct connection between computer-aided designs of microfluidic platforms and lattice-based frameworks for discrete cell modeling, enabling the simulation of collective cellular interactions. The entry of a cell into a microchannel has also been investigated in [24] using a Newtonian liquid-drop model, where the authors examine the translocation of breast cancer epithelial cells into a microchannel through both simulations and experiments. Their aim is to link the observed entry dynamics to the mechanical properties of the cells, thereby distinguishing between benign and malignant phenotypes.

On the other hand, [25] developed a hybrid agent-based/finite element model designed to capture distinct migration strategies. This multiscale framework for cancer cell motility integrates several key biological processes, including actin–polymerization-driven protrusions, cellular contractility, bleb formation, nuclear mechanics, and variable ECM attachment, as well as heterogeneity in ECM topology, thereby providing a comprehensive representation of cell migration dynamics under different conditions. Furthermore, coupled bulk–surface reaction–diffusion models for simulating single-cell migration have been developed in [26–28]. In particular, [27] demonstrated that the coupling between bulk and surface components allows a local perturbation on the cell membrane to generate propagating reaction waves, which eventually stabilise into a steady-state pattern due to the interaction with the bulk dynamics. In [28], a mechanobiochemical model for two-dimensional cell migration was proposed, coupling the mechanical properties of the cytosol with biochemical processes occurring near or on the plasma membrane. Moreover, [29] presented a conservative arbitrary Lagrangian–Eulerian (ALE) finite element method for the approximate solution of bulk–surface reaction–diffusion systems on evolving two-dimensional domains. Finally, the multiplicative decomposition of the deformation gradient was introduced in [30, 31] to account for both active and passive strains experienced by the cell. This mechanics-based computational approach successfully reproduces cell migration across different configurations, including migration under confinement through sub-nuclear microchannels, durotaxis, and locomotion on flat substrates. Taken together, these approaches have provided valuable insights into specific aspects of confined cell migration and translocation, yet their reliance on simplifying assumptions or their limited ability to simultaneously capture both cellular and nuclear mechanics leaves open important questions that motivate the development of complementary frameworks.

In this study, we adapt a geometric surface partial differential equation (GS-PDE) framework, previously developed in [32–35], to investigate cell translocation under confinement. Our choice of a GS-PDE framework is motivated by its ability to directly embed mechanical parameters within a geometrically consistent representation of both the cell plasma membrane and the nuclear envelope, thereby overcoming the limitations of previous models and enabling a more faithful reproduction of experimentally observed behaviors. The model is formulated in terms of evolution laws derived from a force balance principle applied to both the cell plasma membrane and the nuclear envelope. Within this framework, the cell plasma membrane and nuclear envelope are represented as dynamically evolving hypersurfaces, whose motion is governed by the interplay of multiple surface forces acting per unit area in the normal direction, as well

as by their mutual interactions. The primary objective of this work is to assess how the mechanical properties of the cell and nucleus, together with the integrity of nucleus–cytoskeleton connections, influence cellular translocation in constrained environments. To achieve this, we aim to replicate the biophysical experiments described in [36], thereby validating the predictive capabilities of our mathematical model and reproducing key aspects of the observed cell behavior. We aim to reproduce the physical and mechanical response of skin fibroblasts from healthy donor used as control cells in the experiments. Establishing this validation will enable the model to support further *in silico* investigations, providing deeper insight into the mechanistic basis of confined cell translocation and informing experimental design, thanks to the generality, applicability, and robustness of the modeling framework. Once validated in the context of confined transport, the model is then extended to predict the more complex process of confined active migration.

Materials and methods

In this section, we first provide a brief overview of the experimental setup and measurements that we aim to model and later use for validation. Details of the experiments are described in [36]. Building upon this framework, we introduce the biophysical model and the governing equations developed to describe cell translocation through the microchannel. We then outline the numerical techniques employed to solve the model and discuss the key parameters that define the system's behavior.

Microfluidic experiments

We provide here a brief description of the biophysical experiments (Fig. 1), further details can be found in [36]. Microfluidic chips, fabricated from polydimethylsiloxane (PDMS), consist of a large quasi-two-dimensional flow channel (6 mm long, 0.3 mm wide, and 10 μm high to limits cells into one layer) with smaller microchannels in the middle (of 6×6 μm^2 squared cross-section and 100 μm in length). Each chip held inlets to inject cells and buffer and an outlet that allowed to drive cells through the microchannels under controlled pressure gradient. Cells passing through microchannels were observed in brightfield microscopy and movies were acquired at frame rates varying from 125 to 1000 fps (see S1 Movie acquired at 500 fps as en example, corresponding to the cell shown in Fig. 1(b-c)). Experiments were performed at 37°C, pressure gradient was fixed at 165 mbar. Movies were pre-processed using FIJI software to segment the cells, then their contour was analyzed using a home-made Matlab routine to measure the temporal elongation of the cell tongue while they entered constrictions.

GS-PDEs for modeling the interplay between the cell plasma membrane and nuclear envelope during confined translocation

We consider a model for cell transport based on a geometric evolution law for two distinct yet coupled hypersurfaces, representing the cell plasma membrane and the nuclear envelope. Following the framework introduced in [33, 34], both surfaces evolve according to force balance equations per unit area, which incorporate the internal elastic response and the interaction forces between them. Specifically, we denote by Γ_c and Γ_n the evolving C^2-smooth closed hypersurfaces, where the subscripts c and n refer to the cell plasma membrane and the nuclear envelope, respectively. Moreover, we consider here the case in which the cell passes through a microchannel under the action of an applied pulling pressure to reproduce the experimental conditions of [36]. A 2D projection of the initial configuration of the system is shown in Fig. 2. It must be noted

Fig 1. Biophysical experiment of cell translocation through microchannels. (a) Schematic top view of the microfluidic setup, with zoomed 3D-view of the microchannels. The cells passing through microchannels are observed from the bottom in brightfield microscopy. (b) Timelapse of a 15-µm cell passing through a microchannel. Time in sec. Scale bar: 10 µm. The timelapse is built from images extracted from Supp. Movie 1. (c) Cell tongue elongation in the microchannel over time, corresponding to the cell shown in (b). The cell was observed at frame rate of 500 fps.

that the mathematical formulation presented below is general and applies both to hypersurfaces embedded in three-dimensional space and to curves embedded in the two-dimensional plane.

A geometric surface force balance equation for the cell plasma membrane

The force balance on the cell plasma membrane surface takes the form:

$$\mathbf{0} = \left(\mathcal{F}_{\mathrm{v}}^c + \mathcal{F}_{\mathrm{visc}}^c + \mathcal{F}_{\mathrm{s}}^c + \mathcal{F}_{\mathrm{b}}^c + \mathcal{F}_{\mathrm{sr}}^c + \mathcal{F}_{\mathrm{mech}}^c + \mathcal{F}_{\mathrm{ext}}^c\right)\boldsymbol{\nu}_c \quad \text{on } \Gamma_c\,, \tag{1}$$

where $\boldsymbol{\nu}_c$ denotes the outward pointing unit normal to the surface Γ_c posed at each material point on the continuously deforming surface. The terms on the right-hand side are described below.

- Experimental evidence indicates that, although the cell surface area can vary during translocation, the enclosed volume remains approximately constant [36–38]. We incorporate this observation as a hard constraint, implying that the cell can instantaneously compensate for small deviations in volume. We introduce a volume conservation model through the use of a Lagrange multiplier, denoted by $\lambda_m(t)$, which can be interpreted as the time-dependent pressure difference between the cell interior and the surrounding environment. The resulting force associated with volume conservation is then expressed as

$$\mathcal{F}_{\mathrm{v}}^c = \lambda_m(t)\,. \tag{2}$$

It is important to note that $\lambda_m(t)$ is spatially uniform, representing a homogeneous force that ensures the conservation of the cell volume throughout its

Fig 2. Schematic illustration of the initial configuration adopted in the 2D simulations to reproduce the 3D experimental conditions of [36]. The cell (light blue) and nucleus (dark blue) are placed at the entrance of a microchannel of width $w = 6\,\mu$m width and length $L = 100\,\mu$m.

evolution. It satisfies the following first-order ordinary differential equation, corresponding to a proportional–integral control of the area:

$$\frac{\mathrm{d}\lambda_m}{\mathrm{d}t} = K_p \left(\frac{A_{\text{ref}} - A(t)}{A_{\text{ref}}} \right) - K_i\,\lambda_m(t)\,, \tag{3}$$

where K_p and K_i are positive constants representing the proportional and integral gains, respectively, and $A(t)$ is the instantaneous cell area. The proportional term drives λ_m in response to the instantaneous deviation of the area from its reference value, while the integral term accumulates the effect of past deviations, ensuring long-term conservation. This formulation is similar to the approach originally proposed in [32, 39]. The parameters K_p and K_i are tuned to ensure stability and to achieve the desired level of accuracy in the area conservation.

- We include a viscous force that opposes motion:

$$\mathcal{F}_{\text{visc}}^c = -\omega V\,, \tag{4}$$

where $\omega > 0$ is a kinetic coefficient, and V is defined such that $V\,\boldsymbol{\nu}_c = \boldsymbol{V}$, with $\boldsymbol{V}$ denoting the material velocity of the cell plasma membrane, which is assumed to be normal to the membrane.

- Resistance of the cell boundary to stretching may be incorporated by means of a surface energy of the form:

$$E_{\text{s}} = \int_{\Gamma_c} k_{\text{s}}\,, \tag{5}$$

where $k_{\text{s}} > 0$ can be interpreted as a surface tension. The first variation of the surface area yields the mean curvature [40], hence the force arising from the surface energy is given by:

$$\mathcal{F}_{\text{s}}^c = -k_{\text{s}}H\,, \tag{6}$$

where H denotes the mean curvature of Γ_c, understood here as the sum of the principal curvatures, i.e. $H = \nabla_{\Gamma_c} \cdot \boldsymbol{\nu}_c = \text{tr}(\nabla_{\Gamma_c}\boldsymbol{\nu}_c)$. In the following, ∇_{Γ_c} and Δ_{Γ_c} denote, respectively, the surface gradient and the Laplace–Beltrami operator, defined for an extension function η in a neighbourhood of Γ_c as

$$\nabla_{\Gamma_c}\eta := \nabla\eta - \nabla\eta \cdot \boldsymbol{\nu}_c\boldsymbol{\nu}_c\,, \quad \Delta_{\Gamma_c}\eta := \nabla_{\Gamma_c} \cdot (\nabla_{\Gamma_c}\eta)\,. \tag{7}$$

- The lipid bilayer forming the basic component of the cell plasma membrane also resists bending. We consider the established model of Helfrich [41] for the bending energy:

$$E_{\rm b} = \int_{\Gamma_c} \frac{k_{\rm b}}{2} H^2 \,, \tag{8}$$

where $k_{\rm b} > 0$ is the bending rigidity. The variation of the bending energy with respect to the surface yields the corresponding force contribution

$$\mathcal{F}_{\rm b}^c = k_{\rm b} \left(\Delta_{\Gamma_c} H + H \left| \nabla_{\Gamma_c} \boldsymbol{\nu}_c \right|^2 - \frac{1}{2} H^3 \right) \,, \tag{9}$$

where $| \cdot |$ denotes the Frobenius norm, so that $\left| \nabla_{\Gamma_c} \boldsymbol{\nu}_c \right|^2$ measures the local variation of the unit normal vector along the surface.

- To prevent non-physical self-intersections of the cell plasma membrane during large deformations, we introduce a self-repulsive force $\mathcal{F}_{\rm sr}^c$ acting on each membrane point $\boldsymbol{x}^i$. This force is designed specifically to penalize configurations in which distant points on the membrane come excessively close and are oppositely oriented. In particular, for each membrane point $\boldsymbol{x}^i$, we evaluate its interaction with all other points $\boldsymbol{x}^j \neq \boldsymbol{x}^i$ that lie within a fixed distance threshold. The self-repulsive force at $\boldsymbol{x}^i$ is then defined as the maximum among these contributions:

$$\mathcal{F}_{\rm sr}^c \left(\boldsymbol{x}^i \right) = \max_{j \neq i} \left\{ \left(\frac{1 + \tanh \left(\kappa_n \left(\delta_n - \boldsymbol{\nu}_c^i \cdot \boldsymbol{\nu}_c^j \right) \right)}{2} \right) \cdot D \exp \left[\kappa_d (\delta_d - \| \boldsymbol{x}^i - \boldsymbol{x}^j \|) \right] \right\} \,, \tag{10}$$

where $\boldsymbol{\nu}_c^i$ and $\boldsymbol{\nu}_c^j$ denote the unit outward normals at points $\boldsymbol{x}^i$ and $\boldsymbol{x}^j$, respectively, and $\| \cdot \|$ represents the Euclidean norm. The first factor reflects the alignment of the normals, becoming larger when the two normals are oppositely oriented. The second factor represents the proximity-based repulsion, which increases as the distance between the points decreases. The parameter κ_n controls the sensitivity to the relative orientation of the normals, and δ_n sets a threshold to detect near-opposing directions. The exponential term models the distance-dependent decay of the interaction, where D is the self-interaction strength per unit area, κ_d controls the sharpness of the decay and δ_d sets a threshold for the minimal distance between two points.

- We aim to capture and quantify the mechanical response of the cell surface within our model. This enables the direct integration of mechanical parameters estimated from biophysical experiments into the simulations. Embedding mechanics within the GS-PDE framework represents a significant advance compared to previous models, as it explicitly incorporates the mechanical response at the surface level. As a first step, the mechanical behavior of the cell surface is described using a linear elastic constitutive law, in which the elastic restoring force arises from the internal stresses induced by deformations of the cell plasma membrane. Denoting by $\boldsymbol{u}$ the displacement field of the cell plasma membrane, the stress tensor $\boldsymbol{\sigma}$ is defined according to the classical isotropic linear elasticity formulation:

$$\boldsymbol{\sigma}(\boldsymbol{u}) = \lambda \operatorname{tr}(\boldsymbol{\varepsilon}(\boldsymbol{u}))\boldsymbol{I} + 2\mu \, \boldsymbol{\varepsilon}(\boldsymbol{u}), \tag{11}$$

where $\boldsymbol{\varepsilon}(\boldsymbol{u}) = \frac{1}{2}(\nabla_{\Gamma_c} \boldsymbol{u} + \nabla_{\Gamma_c} \boldsymbol{u}^T)$ is the linearised strain tensor defined on the surface, with the superscript T denoting the transpose, $\boldsymbol{I}$ is the identity tensor, and λ and μ are the Lamé parameters, defined in terms of the cell Young's

modulus E_c and Poisson's ratio ν as:

$$\lambda = \frac{\nu E_c}{(1+\nu)(1-2\nu)}\,, \quad \text{and} \quad \mu = \frac{E_c}{2(1+\nu)}\,. \tag{12}$$

In order to capture time-dependent mechanical effects of the cell plasma membrane, we adopt a linear viscoelastic model of Jeffrey type posed on a surface. This model, originally introduced by Harold Jeffreys in the context of earth rheology [42], combines an elastic spring with two dashpots arranged in parallel and series, respectively, and is particularly suited to describing both instantaneous elastic response and stress relaxation over time. In such a model, the stress–strain relation is expressed in terms of an internal variable $\boldsymbol{\varepsilon}^v$ representing the viscous contribution to the total strain. In this case, the Cauchy stress tensor is given by

$$\boldsymbol{\sigma}(\boldsymbol{u}) = E_c\left(\boldsymbol{\varepsilon}(\boldsymbol{u}) - \boldsymbol{\varepsilon}^v\right)\,, \tag{13}$$

where E_c is still the Young's modulus. The evolution of the internal strain variable is governed by a linear relaxation equation of the form

$$\frac{d\boldsymbol{\varepsilon}^v}{dt} + \frac{1}{\tau}\boldsymbol{\varepsilon}^v = \frac{1}{\tau_2}\boldsymbol{\varepsilon}(\boldsymbol{u})\,, \tag{14}$$

with $\tau = (\eta_1 + \eta_2)/E_c$ and $\tau_2 = \eta_2/E_c$, where η_1 and η_2 are the viscosities associated with the two dashpots. This formulation allows the material to exhibit both instantaneous elastic response and time-dependent viscous effects, with stress relaxation determined by the evolution of $\boldsymbol{\varepsilon}^v$. The two constitutive laws, described by the distinct Cauchy stress tensors in Eqs. (11) and (13), will be tested and compared in the results and discussion sections, since the precise mechanical response is not yet known.

The elastic force acting on the cell plasma membrane is then computed as:

$$\mathcal{F}^c_{\text{mech}} = [\boldsymbol{\sigma}(\boldsymbol{u})\boldsymbol{\nu}_c]\cdot\boldsymbol{\nu}_c\,. \tag{15}$$

This force contributes to restoring the cell towards its original configuration and provides resistance to deformation against external actions.

- Finally, we consider the external forces $\mathcal{F}^c_{\text{ext}}$ acting on the cell membrane, which, in our case, result from the sum of the following force contributions:

$$\mathcal{F}^c_{\text{ext}} = \mathcal{F}^c_{\text{bar}} + \mathcal{F}^c_{\text{pr}} + \mathcal{F}^c_{\text{rep}} + \mathcal{F}^c_{\text{el}}\,. \tag{16}$$

  - First, to model the interaction between the cell and external physical constraints, such as microchannel walls or obstacles, we introduce a barrier force $\mathcal{F}^c_{\text{bar}}$ [33, 35]. This force prevents the cell from penetrating predefined regions by exerting a repulsive action whenever the membrane approaches specific barrier centers. We consider a cell passing through a microchannel of fixed width. The interaction with the barrier is modeled using an exponential repulsion force of the form

$$\mathcal{F}^c_{\text{bar}}(\boldsymbol{x}^i) = \sum_j B\,\exp\left(-\beta\,d_{\text{bar}}(\boldsymbol{x}^i,\boldsymbol{y}^j)\right)\boldsymbol{\nu}^j_{\text{bar}}\cdot\boldsymbol{\nu}^i_c\,, \tag{17}$$

  where $\boldsymbol{y}^j$ represents the points on the barrier. The coefficients B and β denote the amplitude and steepness of the cell plasma membrane and barrier interaction, respectively, and $d_{\text{bar}}(\boldsymbol{x}^i,\boldsymbol{y}^j)$ is the distance between the point $\boldsymbol{x}^i$ on the cell surface Γ_c and a point $\boldsymbol{y}^j$ on the barrier. Finally, $\boldsymbol{\nu}^j_{\text{bar}}$ represents the outward-pointing normal vector at the barrier point $\boldsymbol{y}^j$.

– Second, we introduce the force $\mathcal{F}_{\mathrm{pr}}^c$ to account for the active pressure used to pull the cell in the microchannel. This force is modelled as a constant vector field applied in a fixed direction. In our model, we assume that this force acts uniformly in the positive x-direction, and it is defined as:

$$\mathcal{F}_{\mathrm{pr}}^c = F_{\mathrm{pr}}\, \boldsymbol{e}_x \cdot \boldsymbol{\nu}_n \,, \tag{18}$$

where F_{pr} is a constant magnitude and $\boldsymbol{e}_x$ denotes the unit vector in the x-direction.

– Moreover, we add the force $\mathcal{F}_{\mathrm{rep}}^c$, which ensures that the nucleus remains confined within the cell plasma membrane, specifically preventing it from crossing the cortical layer. This physical constraint is enforced via a penalization mechanism that introduces a repulsive interaction when the nucleus approaches the cortex. Let $\delta(\boldsymbol{x}^i) = \min_j d(\boldsymbol{x}^i, \boldsymbol{z}^j)$ denote the minimal distance between a fixed point $\boldsymbol{x}^i \in \Gamma_c$ on the cell plasma membrane and all the points $\boldsymbol{z}^j \in \Gamma_n$ on the nuclear envelope. The repulsive force is defined as:

$$\mathcal{F}_{\mathrm{rep}}^c(\boldsymbol{x}^i) = k_{\mathrm{rep}}\, \phi(\delta(\boldsymbol{x}^i)) \,, \tag{19}$$

where $k_{\mathrm{rep}} > 0$ is a stiffness parameter that determines the strength of the penalization and $\phi(\delta)$ is a positive, increasing function as δ becomes smaller and closer to zero, for example:

$$\phi(\delta) = e^{-\alpha\,\delta}, \quad \text{with } \alpha > 0 \,. \tag{20}$$

– Lastly, we describe the interaction between the cell and the nucleus, due to the mechanical coupling via the cytoskeletal components, as an elastic force that prevents the cell plasma membrane from moving too far from the nucleus. For each point on the cell plasma membrane, we compute the distance from the nuclear lamina, denoted by δ_{el}. The resulting force included in our model is defined as:

$$\mathcal{F}_{\mathrm{el}}^c = \begin{cases} -k_{\mathrm{el}}\, \delta_{\mathrm{el}} \,, & \text{if } \delta_{\mathrm{el}} > r_c - r_n \,, \\ 0 \,, & \text{otherwise} \,. \end{cases} \tag{21}$$

In the expression above, k_{el} is a constant parameter characterizing the stiffness of the interaction, r_c is the initial radius of the cell, and r_n is the initial radius of the nucleus.

By combining all the contributions described above, the resulting balance of forces leads to the following governing 4th order GS-PDE for the evolution of the cell plasma membrane:

$$\omega \boldsymbol{V} = \left(-k_{\mathrm{s}} H + k_{\mathrm{b}}(\Delta_{\Gamma_c} H + H\, |\nabla_{\Gamma_c} \boldsymbol{\nu}_c|^2 - \frac{1}{2} H^3) + \lambda_m(t) + \mathcal{F}_{\mathrm{sr}}^c + \mathcal{F}_{\mathrm{mech}}^c + \mathcal{F}_{\mathrm{ext}}^c \right) \boldsymbol{\nu}_c \,.$$

A geometric surface force balance equation of the nuclear envelope

The formulation is completed by introducing the surface force balance equation for the nuclear envelope. Specifically, the nuclear envelope is subjected to its own set of forces, including contributions from volume conservation, viscous resistance, and mechanical stresses. In addition, external interactions with the cell plasma membrane are incorporated. The overall balance of forces acting on the nuclear envelope in the normal direction is expressed as:

$$\boldsymbol{0} = (\mathcal{F}_{\mathrm{v}}^n + \mathcal{F}_{\mathrm{visc}}^n + \mathcal{F}_{\mathrm{s}}^n + \mathcal{F}_{\mathrm{b}}^n + \mathcal{F}_{\mathrm{sr}}^n + \mathcal{F}_{\mathrm{mech}}^n + \mathcal{F}_{\mathrm{ext}}^n)\, \boldsymbol{\nu}_n \quad \text{on } \Gamma_n \,. \tag{22}$$

The main difference lies in the treatment of the external contributions, taking the following form:

$$\mathcal{F}_{\text{ext}}^n = \mathcal{F}_{\text{bar}}^n + \mathcal{F}_{\text{rep}}^n + \mathcal{F}_{\text{dr}}^n. \tag{23}$$

In this case, the nuclear envelope is subjected to the same barrier force, $\mathcal{F}_{\text{bar}}^n$, that also acts on the cell plasma membrane, as well as to a repulsive force $\mathcal{F}_{\text{rep}}^n$ applied at every point of the nuclear surface. This repulsive force has the same functional form and parameters as the one acting on the cell plasma membrane, but with an opposite sign. In addition, we account for the dragging force, $\mathcal{F}_{\text{dr}}^n$. To ensure that the nucleus is carried along with the cell, we introduce a dragging force through which the plasma membrane transmits motion to the nucleus. This force represents the mechanical coupling between the cytoskeleton and the nucleus, ensuring that the nucleus follows the cell's overall direction of movement. Its orientation is defined by the line connecting the cell center $\boldsymbol{x}_c$, to the nuclear center, $\boldsymbol{x}_n$. Since only the normal components of the forces are considered in our framework, the interaction is projected onto the local normal vector of the nuclear surface. The resulting force is expressed as:

$$\mathcal{F}_{\text{dr}}^n = \tilde{k}(H_n)\frac{\boldsymbol{x}_c - \boldsymbol{x}_n}{\|\boldsymbol{x}_c - \boldsymbol{x}_n\|} \cdot \boldsymbol{\nu}_n\,, \tag{24}$$

where $\tilde{k}$ denotes the dragging coefficient, which depends on the curvature of the nucleus, H_n. When the nucleus is undeformed or has fully traversed the microchannel, so that the cell is in a symmetrical configuration and the curvature at the front equals that at the rear, we set $\tilde{k} = k_n$. Conversely, during nuclear translocation through the microchannel, the ability of the cell to drag the nucleus is reduced, and we set $\tilde{k} = k_n/p$, with $p > 1$.

Numerical implementation

In the following, we present the variational formulation of the geometric surface evolution laws together with their corresponding finite element discretization. Since the models are almost identical except for some forces, we only present one variational formulation in a generalized form. Superscripts are omitted, and a unified framework valid for both cases is provided. We focus on the case of a curve embedded in the two-dimensional plane, corresponding to the biological problem we intend to model. The formulation can be naturally extended to three-dimensional evolving hypersurfaces. This extension is left for future studies.

The derivation is based on well-established results from differential geometry, reported in detail in [43]. We seek $\boldsymbol{x} \in H^1(\Gamma(t))^2$ and $H \in H^1(\Gamma(t))$, where $H^1(\Gamma(t))$ denotes the Sobolev space of functions on the surface $\Gamma(t)$ whose values and first derivatives are square-integrable and t represents the time, such that

$$\begin{cases} \displaystyle\int_{\Gamma(t)} \left(\omega\,\partial_t\boldsymbol{x}\cdot\boldsymbol{\nu}\,\chi + k_b\,\nabla_{\Gamma(t)}H\cdot\nabla_{\Gamma(t)}\chi - k_b H\,|\nabla_\Gamma\boldsymbol{\nu}|^2\chi + \tfrac{1}{2}k_b H^3\chi + k_s H\chi\right)\,\mathrm{d}\ell \\ \qquad\qquad\qquad\qquad = \int_{\Gamma(t)}\left(\lambda_m(t) + \mathcal{F}_{\text{sr}} + \mathcal{F}_{\text{mech}} + \mathcal{F}_{\text{ext}}\right)\chi\,\mathrm{d}\ell\,, \\ \displaystyle\int_{\Gamma(t)} \left(H\,\boldsymbol{\nu}\cdot\boldsymbol{\chi} - \nabla_{\Gamma(t)}\boldsymbol{x}:\nabla_{\Gamma(t)}\boldsymbol{\chi}\right)\,\mathrm{d}\ell = 0\,, \end{cases} \tag{25}$$

for all test functions $\chi \in H^1(\Gamma(t))$ and $\boldsymbol{\chi} \in H^1(\Gamma(t))^2$. Here, $\boldsymbol{V} = \partial_t\boldsymbol{x}$, since we are working in a Lagrangian framework, where the material velocity coincides with the rate of change of the material points in time. In the above, we have called upon the Divergence Theorem and no boundary conditions since the surface has no boundary.

Then, a spatial and temporal discretization is performed, based on evolving surface finite elements [44–46]. We discretize the time interval $[0, T]$ into N subintervals

$0 < t_1 < \cdots < t_N = T$ with a fixed timestep τ. The method is based on parameterizing the surface $\Gamma_h^{m+1} := \Gamma_h(t_{m+1})$ over Γ_h^m. Given a triangulated surface Γ_h, we define the finite element space as

$$\mathbb{V}(\Gamma_h) := \{\chi \in C(\Gamma_h) : \ \chi|_s \text{ is quadratic, } \forall s \in \mathcal{T}_h\} \ . \tag{26}$$

Then, for $n = 0, \ldots, N-1$, given $\boldsymbol{x}_h^n \in (\mathbb{V}^n)^2$ and $H_h^n \in \mathbb{V}^n$, we seek $\boldsymbol{x}_h^{n+1} \in (\mathbb{V}^{n+1})^2$ and $H_h^{n+1} \in \mathbb{V}^{n+1}$ such that

$$
\begin{cases}
\displaystyle\int_{\Gamma_h^n} \big(\frac{\omega}{\tau_{n+1}} \left(\boldsymbol{x}_h^{n+1} - \boldsymbol{x}_h^n\right) \cdot \boldsymbol{\nu}_h^n \, \chi_h + k_b \, \nabla_{\Gamma_h^n} H_h^{n+1} \cdot \nabla_{\Gamma_h^n} \chi_h \\
\hspace{3cm} - \dfrac{1}{2} k_b \, (H_h^n)^2 \, H_h^{n+1} \, \chi_h + k_s \, H_h^{n+1} \, \chi_h\big) \, \mathrm{d}\ell \\
\hspace{2cm} = \displaystyle\int_{\Gamma_h^n} \left(\lambda_m^{n+1} + \mathcal{F}_{\mathrm{sr}}^n + \mathcal{F}_{\mathrm{mech}}^n + \mathcal{F}_{\mathrm{ext}}^n\right) \, \chi_h \, \mathrm{d}\ell \, , \\
\displaystyle\int_{\Gamma_h^n} \left(H_h^{n+1} \, \boldsymbol{\nu}_h^n \cdot \boldsymbol{\chi}_h - \nabla_{\Gamma_h^n} \boldsymbol{x}_h^{n+1} : \nabla_{\Gamma_h^n} \boldsymbol{\chi}_h\right) \, \mathrm{d}\ell = 0 \, ,
\end{cases}
\tag{27}
$$

where ":" denotes the Frobenius inner product between two tensors. Here, we employ a Picard-type iteration to obtain a fully implicit backward Euler scheme.

Moreover, the Lagrange multiplier λ_m^{n+1} to enforce area conservation is updated using the discrete version of proportional–integral scheme described in (3):

$$\lambda_m^{n+1} = \left(\lambda_m^n + \tau K_p \, \frac{A_{\mathrm{ref}} - A^n}{A_{\mathrm{ref}}}\right) (1 + \tau K_i)^{-1} \, , \tag{28}$$

where A_{ref} denotes the reference initial area, A^n is the area at time step n, and K_p and K_i are the prescribed proportional and integral gains, respectively. It can be observed that, as the timestep approaches zero ($\tau \to 0$), the Lagrange multiplier remains effectively constant, i.e., $\lambda_m^{n+1} = \lambda_m^n$.

Parameter selection

Identifying and accurately estimating numerical parameters is essential for developing robust and reliable predictive models. However, many of these quantities are difficult to determine directly and must instead be inferred from in vitro measurements or estimated indirectly. In this work, parameter values were selected from previously published experimental and modelling studies, with particular reference to the experimental results reported by [36], so as to enable a direct comparison between our numerical simulations and their findings. The selected parameter values, together with the biological ranges found in the literature and the relative references, are summarized in Table 1.

First, we describe the geometrical dimensions of the cell and the microchannel, which are schematically illustrated in Fig. 2. Focusing on the size of the cell and its nucleus, we refer to the control skin fibroblasts reported in [36]. Accordingly, we consider an initial cell radius of $r_c = 13 \ \mu$m and an initial nuclear radius of $r_n = 5 \ \mu$m. As for the microchannel, we used the same width as in the reference paper [36], namely $w = 6 \ \mu$m.

Second, in all numerical simulations, the following numerical parameters were adopted. The time step was set to $\tau = 10^{-3}$ s, while the characteristic length, corresponding to the typical size of the mesh elements, was chosen as $l_c = 5.0 \cdot 10^{-2} \ \mu$m for both the cell plasma membrane and the nuclear envelope. These values were selected to ensure numerical stability and convergence of the scheme, providing a suitable compromise between computational cost and accuracy.

Then, it is necessary to select appropriate values for the surface tension and the bending stiffness of the cell plasma membrane, since these parameters play a key role in

determining cell shape and deformability under confinement. For the surface tension, we adopt the value $k_s = 1.6\,\text{nN}/\mu\text{m}$, which is consistent with the experimental estimates reported in [47–49]. For the bending stiffness, we use $k_b = 10^{-4}\,\text{nN} \cdot \mu\text{m}$, in agreement with the characterization provided in [50]. For the nuclear envelope, we increased both parameters by one order of magnitude to account for its higher rigidity.

Determining an appropriate value for the kinetic coefficient ω in the viscous force was not straightforward for either the cell or the nucleus, as only limited references are available in the literature. Following [51], and considering that this parameter directly influences the overall entry time of the cell into the microchannel, we calibrated it against the experimental data reported in [36]. On this basis, we set $\omega = 0.1\,\text{g}/\left[(\mu\text{m})^2 \cdot \text{s}\right]$, a choice that can be generalized without loss of accuracy by a suitable rescaling of the time variable. Additional simulations performed with different values of ω confirmed its role in modulating the system dynamics. In the present study, we adopted the same value of ω for both the cell and the nucleus, although this assumption is not strictly necessary.

Regarding the proportional and integral gains K_p and K_i in Eq. (28), we tuned them to enforce a reasonable constraint on the change in cell area. Accordingly, we chose $K_p = 1.2 \cdot 10^5\,\text{nN}/(\mu\text{m}^2 \cdot \text{s})$ and $K_i = 500\,\text{s}^{-1}$.

For the self-repulsive force, all parameters were calibrated to reproduce the expected behavior. Specifically, we set the self-interaction strength per unit area to $A = 1.0\,\text{kPa}$, the decay sharpness to $\kappa_d = 5.0\,\mu\text{m}^{-1}$, and the threshold to $\delta_d = 0.1\,\mu\text{m}$. In addition, the sensitivity to the relative orientation of the normals was set to $\kappa_n = 5.0$, with a corresponding threshold of $\delta_n = -0.7$.

We now consider the mechanical properties of both the cell plasma membrane and the nuclear envelope. For control fibroblasts, the Young's modulus of the cell was estimated as a weighted average between a membrane stiffness of 100 Pa and a cytosolic stiffness of 10 Pa, yielding $E_c = 0.0103\,\text{kPa}$. For the nucleus, we adopted a reference value of $E_n = 5.0\,\text{kPa}$. These choices are based on experimental measurements reported in [52] and on reference values used in previous mathematical models [31]. In both cases, we used a Poisson's ratio of $\nu = 0.45$ and viscosities $\eta_1 = 0.02\,\text{kPa} \cdot \text{s}$ and $\eta_2 = 0.3\,\text{kPa} \cdot \text{s}$, as estimated in [36].

Finally, we discuss the parameters associated with the external contributions. For the barrier force per unit area, we set the amplitude to $B = 30\,\text{kPa}$ and the steepness to $\beta = 3.5\,\mu\text{m}^{-1}$. The pulling pressure acting on the cell was taken from the experiments reported in [36], with a value of $16\,\text{kPa}$. The penalization strength governing the repulsive interaction between the cell and the nucleus was set to $k_{\text{rep}} = 12\,\text{kPa}$, with a steepness parameter $\alpha = 5\,\mu\text{m}^{-1}$. In addition, the elastic restoring force per unit area preventing the cell plasma membrane from moving too far from the nucleus was assigned a magnitude of $k_{\text{el}} = 3\,\text{kPa}$, while the coupling strength enabling the cell to drag the nucleus during translocation was set to $k_n = 10\,\text{kPa}$, with the parameter p fixed at 4.

Results

In this section, we present the results of the proposed model, which successfully reproduce the biophysical experiments reported in [36]. In addition, we carry out a sensitivity analysis of key parameters involved in the model in order to assess how variations in their values affect the model predictions. This approach enables us to explore a broader range of scenarios and provides a means to evaluate the overall robustness and reliability of the model.

Par.	Value	Unit	Physical Meaning	Refs.
r_c	13	μm	Cellular radius	[36]
r_n	5	μm	Nuclear radius	[36]
w	6	μm	Width of the micro-channel	[36]
τ	10^{-3}	s	Time step of the simulation	estimated
l_c	$5.0 \cdot 10^{-2}$	μm	Characteristic length	estimated
k_s	1.6	nN/μm	Surface tension	[47–49]
k_b	10^{-4}	nN$\cdot\mu$m	Bending stiffness	[50]
ω	0.1	g/$\left[(\mu\text{m})^2 \cdot \text{s}\right]$	Kinetic coefficient	estimated
K_p	$1.2 \cdot 10^5$	nN/$(\mu\text{m}^2 \cdot \text{s})$	Proportional gain	estimated
K_i	500	1/s	Integral gain	estimated
D	1.0	kPa	Self-interaction strength	estimated
κ_d	5.0	1/μm	Sharpness of the decay	estimated
δ_d	0.1	μm	Minimal distance threshold	estimated
κ_n	5.0	-	Normal orientation sensitivity	estimated
δ_n	-0.7	-	Normal orientation threshold	estimated
E_c	0.0103	kPa	Cell Young's modulus	[31, 52]
E_n	5.0	kPa	Nucleus Young's modulus	[31, 52]
ν	0.45	-	Poisson's ratio	[31, 52]
η_1	0.02	kPa $\cdot$ s	Short-time viscosity	[36]
η_2	0.3	kPa $\cdot$ s	Long-time viscosity	[36]
B	30	kPa	Barrier force amplitude	estimated
β	3.5	1/μm	Barrier force steepness	estimated
F_{pr}	16	kPa	Pulling pressure acting on the cell	[36]
k_{rep}	12	kPa	Cell-nucleus repulsive force amplitude	estimated
α	5	1/μm	Cell-nucleus repulsive force steepness	estimated
k_{el}	3	kPa	Cell elastic restoring force amplitude	estimated
k_n	10	kPa	Cell dragging force amplitude	estimated
p	4	-	Cell dragging reduction factor	estimated

Table 1. Reference parameters derived from biophysical experiments and literature

Numerical model matches experimental results

In this section, we investigate the model's ability to reproduce cell translocation within the microchannel, as well as the spatio-temporal evolution of the cell and nuclear shape deformations. This simulation employs the parameters listed in Table 1 and is designed to replicate the experiments reported in [36] and concisely summarized in the Microfluidic experiments section. Initially, the mechanical force is modeled under the elastic hypothesis (11). Figure 3 illustrates the cell's progression through the microchannel at various time points (see S2 Movie for the corresponding simulation). The simulation outcomes are in good agreement with the experimental observations presented in Fig. 1(b), where the passage of a cell through a microchannel is illustrated. To enable a more quantitative comparison, we examine the dynamics of cell entry into the constriction by analyzing the temporal evolution of the portion of the cell protruding inside the microchannel, hereafter referred to as the cell tongue like in [36]. The cell tongue length, evaluated at each time step, is reported in Fig. 4 and can be directly compared with Fig. 1(b). The dynamics can be divided into three successive phases. Phase I describes the cell entering the microchannel while the nucleus remains completely outside, Phase II corresponds to the nucleus entering the microchannel, and Phase III represents the cell passing through the microchannel once the nucleus is entirely inside. Each phase is characterized by a distinct linear increase in cell tongue length over time, i.e., a specific entry velocity. The computed velocities are

Fig 3. Snapshots of the cell plasma membrane (light blue closed curve) and the nuclear envelope (dark blue curve) at different time points for a microchannel width of $6\,\mu$m. The simulation was carried out using the parameter values reported in Table 1 and a linear elastic constitutive law.

Fig 4. Time evolution of the length of the cell tongue (red line). The black vertical dotted line marks the time at which the nucleus first contacts the microchannel, whereas the blue vertical dotted line indicates the time at which the nucleus is fully inside, as outlined in the snapshots above the lines. Phase I describes the cell entering the microchannel while the nucleus remains completely outside, Phase II corresponds to the nucleus entering the microchannel, and Phase III represents the cell passing through the microchannel once the nucleus is entirely inside.

$v_{\mathrm{I}} = 151.9\,\mu\mathrm{m/s}$, $v_{\mathrm{II}} = 17.4\,\mu\mathrm{m/s}$, and $v_{\mathrm{III}} = 117.6\,\mu\mathrm{m/s}$. Our results are in good agreement with the experimental findings reported in [36], where the same three phases were observed (see Fig. 1(c)), and the measured values are of comparable order. It can be observed that in Phase II the nucleus slows down cell translocation, in agreement with experimental observations in other studies [53,54]. Once both the cell and nucleus have fully entered the channel, the cell picks up speed. This acceleration likely occurs because, once the nucleus has crossed the entry constriction, the cell experiences a more uniform confinement and reduced geometric resistance, allowing the driving forces to act more effectively and sustain a higher migration speed. It should be emphasized that the velocity values may vary considerably across different cell types, as one can expect, but also within the same cell type, as clearly observed by Jebane et al. [36]: such strong variations are indeed due to the dispersion in cell size and in cell mechanical parameters within the same population as well as between different populations. However, as discussed in the Parameter selection section, the parameter ω can be tuned to reproduce different behaviors. For example, increasing ω by one order of magnitude relative to the previously adopted value leads to velocity reduction by one order of magnitude as well, namely $v_{\mathrm{I}} = 15.2\,\mu\mathrm{m/s}$, $v_{\mathrm{II}} = 1.74\,\mu\mathrm{m/s}$, and $v_{\mathrm{III}} = 11.8\,\mu\mathrm{m/s}$. To note, the simulation provides additional information on the position of the nucleus relative to the microchannel (see the vertical dotted lines in Fig. 4) which could not be measured in the microfluidic experiments.

Figure 5 illustrates the temporal evolution of the principal quantities of interest. The figure highlights a key strength of our model: it provides access to quantities that are difficult to measure experimentally, including cell and nucleus area and perimeter, normal stress, surface energy, and bending energy. These are computed directly from the evolving cell and nucleus surfaces in the simulation, offering valuable insights for experimentalists and enabling the investigation of biophysical properties that would otherwise be challenging to measure experimentally. In the first row, we show the time evolution of the total cell area (including the nucleus) and the nuclear area in Fig. 5(a), their perimeters in Fig. 5(b), and the velocity of the cell centroid during translocation in Fig. 5(c). All these quantities were computed from the discrete coordinates of the membrane and nuclear contours, by evaluating the enclosed area and the corresponding perimeter length. The area of the nucleus remains nearly constant throughout the simulation, whereas the area of the cell displays transient perturbations during entry into the microchannel and under full confinement due to compression. This indicates that the cytoplasm is softer than the nucleus, consistent with experimental observations [55,56]. Quantitative measurements have shown that the nucleus is stiffer than the surrounding cytoplasm in many eukaryotic cells, with the latter allowing more pronounced area changes due to its lower stiffness. The cell perimeter exhibits a marked increase during the initial stage of channel entry due to stretching and compression, consistent with the absence of perimeter constraints in the model. Variations in the nucleus perimeter are negligible, because the choice of the parameters for the nucleus makes it much stiffer than the cell plasma membrane. The centroid velocity shows a marked slowdown at the onset of cell penetration, followed by a further decrease as the nucleus enters, since its higher rigidity hinders translocation. A partial recovery occurs once the cell has completely passed through the constriction, after which the velocity stabilizes. The second row shows the evolution of the membrane normal stress in Fig. 5(d), which increases sharply during cell entry due to the compression experienced by the cell, then continues to rise more gradually during nuclear translocation as the plasma membrane keeps compressing at a slower rate to allow complete entry, and finally undergoes a slight reduction once the cell has fully entered and its shape stabilizes. Finally, the surface energy and bending energy, defined in (5) and (8), are shown in Fig. 5(e) and in Fig. 5(f), respectively. Regarding the surface energy, it

exhibits a similar trend to the normal stress over time, with a sharp increase at the 480
beginning when the cell starts entering the microchannel, followed by a slower rise 481
during nuclear translocation as the cell entry rate decreases, and finally a slight decrease 482
once the cell is fully inside and reaches a steady shape. Similarly, the bending energy 483
increases during the initial deformation of the cell as it adapts to the channel geometry, 484
and then sharply decreases once the cell elongation becomes more uniform and 485
curvature variations along the membrane are reduced.

Fig 5. Time evolution of the main quantities of interest. The first row shows the
evolution of the cell and nucleus area and perimeter, as well as the velocity of the cell
centroid. The second row shows the evolution of the cell's normal stress component,
surface energy, and bending energy. The black dotted lines mark the time at which the
nucleus first contacts the microchannel, and the blue dotted lines indicate when it is
fully inside

We next reduce the microchannel width to $w = 5\,\mu$m in order to assess the behavior 487
of the cell under a more severe geometric confinement. Using the mechanical parameters 488
listed in Table 1, we find that the cell is unable to enter the channel and remains 489
arrested at the entrance, as shown in Fig. 6. This response contrasts with the 490
translocation observed in wider channels and indicates that the level of confinement has 491
surpassed the cell's ability to deform and squeeze through. In Fig. 7, the time evolution 492
of the main quantities of interest is reported. Regarding the area evolution in Fig. 7(a), 493
a slight decrease in the cell area is observed as the cell initially attempts to enter the 494
microchannel, after which it becomes arrested. A similar trend is seen for the perimeter 495
in Fig. 7(b), which initially increases when the cell protrudes into the channel but then 496
remains constant once the motion stops. No significant changes are observed in the 497
nuclear area or perimeter. Concerning the velocity of the cell centroid in Fig. 7(c), a 498
rapid decrease is observed compared to the initial value, until it eventually reaches zero 499
when the cell is completely blocked at the channel entrance and no longer moves. 500
Finally, for the normal stress in Fig. 7(d), surface energy in Fig. 7(e), and bending 501
energy in Fig. 7(f), we observe an initial increase followed by a plateau, as the cell shape 502
and position remain unchanged after being trapped at the microchannel entrance. The 503
results emphasize the pivotal role of geometric constriction in determining the predicted 504
dynamics, which emerges as one of the two key factors governing cell translocation. The 505

other crucial factor is the mechanical response of the cell itself: an accurate
representation of stiffness and cortical tension is essential to capture whether a cell can
adapt to extreme confinement or instead becomes mechanically trapped. Indeed,
maintaining the same microchannel width of $w = 5\,\mu$m but halving both the nuclear
Young's modulus and surface tension allows the cell to deform sufficiently to pass
through the constriction. These findings indicate that the nucleus acts as the primary
mechanical barrier to cell translocation through narrow microchannels, and that
softening its mechanical properties facilitates successful passage.

Fig 6. Snapshots of the cell plasma membrane (light blue closed curve) and the nuclear
envelope (dark blue curve) at different time points for a microchannel width of
$w = 5\,\mu$m. The simulation was carried out using the parameter values reported in Table
1 and a linear elastic constitutive law.

Comparison between the viscoelastic and linear elastic models

We then simulate the linear viscoelastic response of Jeffrey-type models for both the cell
plasma membrane and the nuclear envelope, as described by the Cauchy stress tensor in
(13), which contributes to the mechanical forces. The corresponding results are reported
in Fig. 8. Compared to the purely linear elastic case described by the Cauchy stress
tensor in (11) and used in the previous section, the primary effect of viscoelasticity is a
reduction in the overall cell velocity, leading to an increased entry time. Fig. 9
illustrates the differences in cell centroid velocities and cell tongue length between the
two cases during passage through the microchannel. Notably, the viscoelastic model
exhibits a clear time-delay with respect to the linear elastic response: characteristic
features such as the recovery of cell centroid velocity and the transitions in tongue
length occur later in the viscoelastic case. Both graphs show the largest variation during
Phase II, which depends strongly on nucleus size and mechanical parameters. The
slower translocation observed in the viscoelastic case can be explained by the intrinsic
dissipative nature of the material response. Unlike the purely elastic case, where the
stress instantaneously follows deformation, viscoelasticity introduces time-dependent
relaxation, causing part of the mechanical energy to be dissipated rather than stored.
As a result, the cell deforms more slowly under the same driving forces, leading to a

Fig 7. Time evolution of the main quantities of interest when the microchannel width is set to $w = 5\,\mu$m. The first row shows the evolution of the cell and nucleus area and perimeter, as well as the velocity of the cell centroid. The second row shows the evolution of the cell's normal stress component, surface energy, and bending energy. The black dotted lines mark the time at which the nucleus first contacts the microchannel.

reduced velocity and a longer entry time. In particular, the viscous component opposes   532
rapid shape changes, delaying both compression and recovery phases during transport   533
through the constriction. Since this divergence is most pronounced when the nucleus   534
begins entering the constriction, it indicates that a viscoelastic response of the nucleus   535
has a greater impact on slowing translocation than applying viscoelasticity to the   536
plasma membrane. As a proof of concept, we verified that when the cell plasma   537
membrane is assumed viscoelastic but the nuclear envelope remains linearly elastic, the   538
standard behavior of the linear elastic case is essentially restored. On the contrary, if we   539
assume a viscoelastic behavior of the nucleus and an elastic behavior for the cell plasma   540
membrane, we recover the viscoelastic behavior obtained in Fig. 8. Overall, the only   541
noticeable effect is a slight reduction in cell velocity, leading to a time-delay of roughly   542
half a second in the total passage time, with no other significant differences observed. It   543
is also worth noting that introducing viscoelasticity substantially increases   544
computational cost. Therefore, in the following, we focus on the linear elastic case,   545
while keeping in mind that the viscoelastic formulation can be easily implemented and   546
may become necessary if the parameter set is changed.   547

Sensitivity analysis   548

To assess the robustness of the proposed model and identify the parameters that most   549
strongly influence cell dynamics under confinement, we performed a sensitivity analysis.   550
The aim was to quantify how small perturbations in selected mechanical and   551
geometrical parameters affect key observables associated with the translocation process.   552
Specifically, we examined variations in the cell area, cell perimeter, velocity of the cell   553
centroid, and the average stress along the normal direction. Each parameter was   554
independently perturbed by $\pm 10\%$ around its reference value, as reported in Table 1,   555
while all others were kept fixed. The parameters considered in this study include the   556

$t = 0.0$ s $\quad\quad$ $t = 0.5$ s

$t = 1.0$ s $\quad\quad$ $t = 1.5$ s

Fig 8. Snapshots of the cell plasma membrane (light blue closed curve) and the nuclear envelope (dark blue curve) at different time points for a microchannel width of $6\,\mu$m. The simulation was carried out using the parameter values reported in Table 1 and adopting a linear viscoelastic constitutive law of the Jeffrey type.

Fig 9. Comparison of the cell centroid velocity and cell tongue length between the linear elastic case (Fig. 3) and the viscoelastic case (Fig. 8).

cell Young's modulus E_c, the nucleus Young's modulus E_n, the microchannel width w, the pulling pressure acting on the cell F_{pr}, and the surface tension k_s of both the cell and the nucleus.

Regarding the cell Young's modulus, the corresponding results are presented in Fig. 10. Variations in this parameter exhibit a limited influence on both the cell and nucleus areas (see Fig. 10(a)), as well as on their perimeters (see Fig. 10(b)). Similarly, the cell velocity in Fig. 10(c) shows only minor changes. This is consistent with the experimental study where cells affected by a mutation of a component of the nuclear envelope, or by a biochemical treatment with a similar effect, did not display strong changes in the elastic modulus. This confirms that the Young's modulus and the dynamics of confined transport are poorly related. However, as expected, modifications in the cell stiffness lead to noticeable variations in the average stress along the normal direction shown in Fig. 10(d), reflecting how changes in mechanical properties influence force transmission through the cell membrane even when overall shape changes are minimal. Subsequently, we performed a similar set of simulations in which the cell Young's modulus was fixed at its reference value, while the Young's modulus of the nucleus, E_n, was varied. No substantial differences were observed, and the results appear quite similar to those reported in Fig. 10, except for the average stress along the normal direction over time. Since this quantity is computed on the cell plasma membrane Γ_c variations in the nuclear Young's modulus produce less pronounced effects.

Fig 10. Sensitivity of (a) cell and nucleus areas, (b) perimeters, (c) centroid velocity, and (d) average normal stress to variations in the cell Young's modulus E_c: standard value, -10%, and +10 %.

We next investigated the effect of a key geometrical parameter, the microchannel width w, which was previously identified as having a strong influence on cell passage. The results of this sensitivity analysis are shown in Fig. 11. Variations in w induce moderate changes in cell area (see Fig. 11(a)), perimeter (see Fig. 11(b)), and average normal stress (see Fig. 11(d)); however, the most pronounced effect is observed on the cell velocity reported in Fig. 11(c). In particular, increasing the microchannel width

enables the cell to traverse the constriction more rapidly, whereas reducing it causes the cell to remain trapped at the entrance within the simulated time frame.

Fig 11. Sensitivity of (a) cell and nucleus areas, (b) perimeters, (c) centroid velocity, and (d) average normal stress to variations in the microchannel width w: standard value, -10%, and +10 %.

We also examined the influence of the pulling pressure acting on the cell F_{pr}. The corresponding results are reported in Fig. 12. Overall, the variations induced by changes in this parameter are not substantial; however, slightly larger effects are observed in the cell perimeter in Fig. 12(b) and, more markedly, in the cell velocity in Fig. 12(c). In particular, after the nucleus has completely traversed the microchannel, a higher pulling pressure results in a higher steady-state velocity of the cell.

Finally, we considered the surface tension k_s, which was varied simultaneously for both the cell and the nucleus. The results, presented in Fig. 13, reveal significant changes across all analysed quantities, confirming that surface tension is a key determinant of the model behaviour. Its influence is particularly evident for the nucleus, as it alters the time required for the nucleus to pass through the microchannel. This effect is especially visible in the velocity profile shown in Fig. 13(c), where the time at which the cell velocity increases, corresponding to the complete passage of the nucleus, depends on the value of k_s.

Overall, this analysis highlights the parameters that most significantly affect the mechanical and transport response of the cell under confinement. In particular, surface tension and confinement geometry emerge as key determinants of transport efficiency, whereas cell stiffness primarily modulate local stress distributions. These findings provide valuable insight into the interplay between mechanical properties and geometric constraints, guiding future efforts in model calibration and experimental validation aimed at quantifying cellular and nuclear mechanics.

Fig 12. Sensitivity of (a) cell and nucleus areas, (b) perimeters, (c) centroid velocity, and (d) average normal stress to variations in the pulling pressure acting on the cell F_{pr}: standard value, -10%, and +10 %.

Fig 13. Sensitivity of (a) cell and nucleus areas, (b) perimeters, (c) centroid velocity, and (d) average normal stress to variations in the surface tension k_s: standard value, -10%, and +10 %.

Discussion and conclusion

In this work, we introduced a computational framework for simulating cell translocation under confinement. The proposed model successfully reproduces key experimental observations reported in [36]. Our main objective was to investigate the role of the nucleus, the stiffest organelle within the cell, during translocation through a narrow microchannel and to assess how its mechanical properties influence overall cell dynamics. The framework is based on geometric surface partial differential equations describing the evolution of both the plasma membrane and the nuclear envelope, as well as their mutual interactions and interactions with the surrounding environment. Each surface is characterized by specific mechanical properties, including surface tension, bending stiffness, and elastic or viscoelastic behavior. Model parameters were calibrated using experimental measurements from [36] and values available in the literature.

The model captures several key experimental trends, most notably the evolution of the cell tongue length, which exhibits three distinct phases. As the cell approaches the constriction, the tongue length initially increases, then slows when the nucleus reaches the microchannel entrance, and finally increases again once the nucleus fully enters the constriction. Overall, these results highlight that nuclear stiffness is a key regulator of translocation efficiency: a stiffer nucleus markedly hinders progression through confined environments, whereas a more compliant nucleus facilitates entry and passage. By contrast, cytoplasmic mechanics exert a comparatively secondary influence on the translocation process. Beyond reproducing measurable quantities, the model provides access to mechanical and geometric variables that are difficult to measure directly, such as the time evolution of the cell and nuclear area, perimeter, and the position of the nucleus relative to the microchannel. It also enables computation of averaged normal stresses, surface energy, and bending energy, offering deeper insight into the mechanical state of the cell during translocation. Analysis of these quantities shows that, although total cell area is subject to a conservation constraint, it undergoes a slight reduction under compression, while the perimeter increases as the cell deforms to enter the constriction. Similar trends are observed for average normal stress, surface energy, and bending energy, which sharply rise as the cell begins entering the microchannel, increase more slowly during nuclear translocation, and relax once the cell reaches a steady configuration within the channel.

A key aspect of the model concerns the mechanical characterization of the nucleus. We implemented two constitutive formulations: a purely linear elastic model and a viscoelastic model of Jeffreys type. Comparison between these descriptions highlights the strong influence of nuclear rheology on overall translocation dynamics. When the nucleus is modeled as viscoelastic rather than purely elastic, the cell velocity decreases markedly, increasing translocation time. This arises from the viscous component, which resists rapid shape changes and delays both compression and recovery phases during passage through the constriction. However, viscoelasticity also increases computational cost, making simulations more demanding. The mechanical role of the nucleus is further evident when considering geometric confinement: reducing the microchannel width while keeping mechanical parameters constant causes the nucleus to become the limiting factor, blocking cell entry and preventing complete translocation.

Finally, a sensitivity analysis identified the parameters that most strongly influence translocation under confinement. Surface tension emerges as a major determinant of velocity, especially for the nucleus, directly affecting the time required for nuclear passage through the constriction. The degree of geometric confinement, namely the microchannel width, also strongly impacts translocation and can determine whether a cell can successfully pass or becomes mechanically trapped at entrance.

This study represents a first step toward a predictive mechanical model of single-cell translocation, developed within a surface-based spatiotemporal framework. The current

setup serves as a validation benchmark, reproducing experimental observations and providing a robust foundation for future *in silico* studies. Future developments will incorporate biologically inspired cytosolic and membrane kinetics via surface reaction–diffusion equations, where state variables represent biomolecules regulating cellular protrusions, adhesion, and contractility. Inclusion of chemotactic cues will allow analysis of how cells sense and respond to spatial gradients under confinement. Incorporating the extracellular matrix will allow us to explore translocation through heterogeneous, anisotropic environments, while extending the framework to multiple interacting cells will enable the study of collective transport and mechanical coupling between cells in confined geometries, also understanding tissue and organ formations.

Acknowledgments

This work has been funded by the Agence National de la Recherche (ANR) through the MultiPhysC2M project (ANR-24-CE45-0690). The experimental work (CJ and EH) has been supported by Excellence Initiative of Aix-Marseille University - A*MIDEX (A-M-AAP-ID-17-66-170301-11.30). The authors gratefully acknowledge the IdEx program of Université Côte d'Azur for partially supporting the collaboration between the Jean Alexandre Dieudonne Laboratory and the University of British Columbia. Moreover, this work (AM) was supported by the Canada Research Chair (Tier 1) in Theoretical and Computational Biology (CRC-2022-00147), the Natural Sciences and Engineering Research Council of Canada (NSERC), Discovery Grants Program (RGPIN-2023-05231), the British Columbia Knowledge Development Fund (BCKDF), Canada Foundation for Innovation – John R. Evans Leaders Fund – Partnerships (CFI-JELF), and the British Columbia Foundation for Non Animal Research. EH belongs to the French Consortium Approches Quantitatives du Vivant/Quantitative approaches to living systems (GDR AQV). FB is member of the National Group of Mathematical Physics (GNFM) of the Italian Institute for High Mathematics (INdAM).

References

1. Montell D. Border-cell migration: The race is on. Nature Reviews Molecular Cell Biology. 2003 02;4:13-24. doi:10.1038/nrm1006.

2. Uriu K, Morelli L, Oates A. Interplay between intercellular signaling and cell movement in development. Seminars in Cell & Developmental Biology. 2014 05;35. doi:10.1016/j.semcdb.2014.05.011.

3. Friedl P, Weigelin B. Interstitial leukocyte migration and immune function. Nature Immunology. 2008 10;9:960-9. doi:10.1038/ni.f.212.

4. Othmer H. Eukaryotic cell dynamics from crawlers to swimmers. Wiley Interdisciplinary Reviews: Computational Molecular Science. 2018 07;9. doi:10.1002/wcms.1376.

5. Friedl P, Wolf K. Tumour-cell invasion and migration: Diversity and escape mechanisms. Nature Rviews Cancer. 2003 06;3:362-74. doi:10.1038/nrc1075.

6. Warner H, Wilson B, Caswell P. Control of adhesion and protrusion in cell migration by Rho GTPases. Current Opinion in Cell Biology. 2018 10;56:64-70. doi:10.1016/j.ceb.2018.09.003.

7. Wisdom K, Adebowale K, Chang J, Lee J, Nam S, Desai R, et al. Matrix mechanical plasticity regulates cancer cell migration through confining

microenvironments. Nature Communications. 2018 10;9. doi:10.1038/s41467-018-06641-z.

8. Saraswathibhatla A, Indana D, Chaudhuri O. Cell-extracellular matrix mechanotransduction in 3D. Nature reviews Molecular cell biology. 2023 02;24. doi:10.1038/s41580-023-00583-1.

9. Wolf K, Liu Y, Geiger J, Tam E, Overall C, Stack M, et al. Multi-step pericellular proteolysis controls the transition from individual to collective cancer cell invasion. Nature Cell Biology. 2007 09;9:893-904. doi:10.1038/ncb1616.

10. Friedl P, Wolf K. Plasticity of cell migration: A multiscale tuning model. The Journal of Cell Biology. 2009 12;188:11-9. doi:10.1083/jcb.200909003.

11. Wolf K, Muller R, Borgmann S, Bröcker E, Friedl P. Amoeboid shape change and contact guidance: T-lymphocyte crawling through fibrillar collagen is independent of matrix remodeling by MMPs and other proteases. Blood. 2003 12;102:3262-9. doi:10.1182/blood-2002-12-3791.

12. Wolf K, Lindert M, Vortmeyer (Krause) M, Alexander S, te Riet J, Willis A, et al. Physical limits of cell migration: Control by ECM space and nuclear deformation and tuning by proteolysis and traction force. The Journal of Cell Biology. 2013 06;201:1069-84. doi:10.1083/jcb.201210152.

13. Pathak A, Kumar S. Independent regulation of tumor cell migration by matrix stiffness and confinement. Proceedings of the National Academy of Sciences of the United States of America. 2012 06;109:10334-9. doi:10.1073/pnas.1118073109.

14. André G, Labouesse C. Mechanobiology of 3D cell confinement and extracellular crowding. Biophysical Reviews. 2024 10;16. doi:10.1007/s12551-024-01244-z.

15. Lautscham L, Kämmerer C, Lange J, Kolb T, Mark C, Schilling A, et al. Migration in confined 3D environments is determined by a combination of adhesiveness, nuclear volume, contractility, and cell stiffness. Biophysical Journal. 2015 09;109:900-13. doi:10.1016/j.bpj.2015.07.025.

16. Guillou L, Dahl J, Lin JM, Barakat AI, Husson J, Muller SJ, et al. Measuring cell viscoelastic properties using a microfluidic extensional flow device. Biophysical Journal. 2016 11;111. doi:10.1016/j.bpj.2016.09.034.

17. Chen Z, Zhu Y, Xu D, Alam M, Shui L, Chen H. Cell elasticity measurement using a microfluidic device with real-time pressure feedback. Lab on a Chip. 2020 05;20. doi:10.1039/D0LC00092B.

18. Abarca Ortega A, González-Bermúdez B, Domínguez C, López A, Alcaraz C, Rodríguez M, et al. Single-cell mechanical characterization in constriction-based cytometry. International Journal of Mechanical Sciences. 2024 01;268. doi:10.1016/j.ijmecsci.2024.108979.

19. Buttenschön A, Edelstein-Keshet L. Bridging from single to collective cell migration: A review of models and links to experiments. PLOS Computational Biology. 2020 12;16:e1008411. doi:10.1371/journal.pcbi.1008411.

20. Giverso C, Grillo A, Preziosi L. Influence of nucleus deformability on cell entry into cylindrical structures. Biomechanics and Modeling in Mechanobiology. 2013 07;13. doi:10.1007/s10237-013-0510-3.

21. Kumar S, Das A, Sen S. Multi-compartment cell-based modeling of confined migration: regulation by cell intrinsic and extrinsic factors. Molecular Biology of the Cell. 2018 05;29. doi:10.1091/mbc.E17-05-0313.

22. Scianna M, Preziosi L. Modeling the influence of nucleus elasticity on cell invasion in fiber networks and microchannels. Journal of Theoretical Biology. 2012 11;317. doi:10.1016/j.jtbi.2012.11.003.

23. Ballesteros J, Ramos M, Diaz Lantada A. Modeling living cells within microfluidic systems using Cellular Automata models. Scientific Reports. 2019 10;9:1-10. doi:10.1038/s41598-019-51494-1.

24. Leong F, li Q, Lim CT, Chiam KH. Modeling cell entry into a micro-channel. Biomechanics and modeling in mechanobiology. 2010 11;10:755-66. doi:10.1007/s10237-010-0271-1.

25. Tozluoğlu M, Tournier A, Jenkins R, Hooper S, Bates P, Sahai E. Matrix geometry determines optimal cancer cell migration strategy and modulates response to interventions. Nature Cell Biology. 2013 06;15. doi:10.1038/ncb2775.

26. Madzvamuse A, Chung A. The bulk-surface finite element method for reaction-diffusion systems on stationary volumes. Finite Elements in Analysis and Design. 2016 01;108:9-21. doi:10.1016/j.finel.2015.09.002.

27. Cusseddu D, Edelstein-Keshet L, Mackenzie JA, Portet S, Madzvamuse A. A coupled bulk-surface model for cell polarisation. Journal of Theoretical Biology. 2018 09;481. doi:10.1016/j.jtbi.2018.09.008.

28. Hernández-Aristizábal D, Garzón-Alvarado D, Duque-Daza C, Madzvamuse A. A bulk-surface mechanobiochemical modelling approach for single cell migration in two-space dimensions. Journal of Theoretical Biology. 2024 10;595:111966. doi:10.1016/j.jtbi.2024.111966.

29. Mackenzie JA, Rowlatt C, Insall R. A conservative finite element ALE scheme for mass-conservative reaction-diffusion equations on evolving two-dimensional domains. SIAM Journal on Scientific Computing. 2021 01;43:B132-66. doi:10.1137/19M1298585.

30. Allena R. The discriminant role of mechanics during cell migration. Journal of Cellular Immunotherapy. 2018 09;4. doi:10.1016/j.jocit.2018.09.007.

31. Allena R. Potential theramechanics for cancer invasion: an in silico study. Mathematics in Medical and Life Sciences. 2024 10;1. doi:10.1080/29937574.2024.2404052.

32. Neilson M, Mackenzie JA, Webb S, Insall R. Modeling cell movement and chemotaxis using pseudopod-based feedback. SIAM Journal on Scientific Computing. 2011 05;33:1035-57. doi:10.1137/100788938.

33. Elliott C, Stinner B, Venkataraman C. Modelling cell motility and chemotaxis with evolving surface finite elements. Journal of the Royal Society Interface. 2012 06;9:3027-44. doi:10.1098/rsif.2012.0276.

34. Ryder L, Dagdas Y, Venkataraman C, Madzvamuse A, Yan X, Cruz-Mireles N, et al. A sensor kinase controls turgor-driven plant infection by the rice blast fungus. Nature. 2019 10;574:1-5. doi:10.1038/s41586-019-1637-x.

35. Giverso C, Jankowiak G, Preziosi L, Schmeiser C. The influence of nucleus mechanics in modelling adhesion-independent cell migration in structured and confined environments. Bulletin of Mathematical Biology. 2023 08;85. doi:10.1007/s11538-023-01187-8.

36. Jebane C, Varlet AA, Karnat M, Cedillo L, Lecchi A, Bedu F, et al. Enhanced cell viscosity: A new phenotype associated with lamin A/C alterations. iScience. 2023 08;26:107714. doi:10.1016/j.isci.2023.107714.

37. Keren K, Pincus Z, Allen G, Barnhart E, Marriott G, Mogilner A, et al. Mechanism of shape determination in motile cells. Nature. 2008 06;453:475-80. doi:10.1038/nature06952.

38. Traynor D, Kay R. Possible roles of the endocytic cycle in cell motility. Journal of Cell Science. 2007 08;120:2318-27. doi:10.1242/jcs.007732.

39. Macdonald G, Mackenzie JA, Nolan M, Insall R. A computational method for the coupled solution of reaction–diffusion equations on evolving domains and manifolds: Application to a model of cell migration and chemotaxis. Journal of Computational Physics. 2015 12;309. doi:10.1016/j.jcp.2015.12.038.

40. Deckelnick K, Elliott C. Computation of geometric partial differential equations and mean curvature flow. Acta Numerica. 2005 05;14:139-232. doi:10.1017/S0962492904000224.

41. Helfrich W. Elastic properties of lipid bilayers: Theory and possible experiments. Zeitschrift für Naturforschung C. 2014 06;28. doi:10.1515/znc-1973-11-1209.

42. Jeffreys H. The Earth: Its Origin, History and Physical Constitution. 1st ed. Cambridge: Cambridge University Press; 1929.

43. Do Carmo MP. Differential geometry of curves and surfaces. Prentice Hall; 1976.

44. Barreira R, Elliott C, Madzvamuse A. The surface finite element method for pattern formation on evolving biological surfaces. Journal of Mathematical Biology. 2011 12;63:1095-119. doi:10.1007/s00285-011-0401-0.

45. Barrett J, Garcke H, Nürnberg R. On the parametric finite element approximation of evolving hypersurfaces in R3. Journal of Computational Physics. 2008 04;227:4281-307. doi:10.1016/j.jcp.2007.11.023.

46. Dziuk G, Elliott CM. Finite element methods for surface PDEs. Acta Numerica. 2013;22:289–396. doi:10.1017/S0962492913000056.

47. Fischer-Friedrich E, Hyman A, Jülicher F, Müller D, Helenius J. Quantification of surface tension and internal pressure generated by single mitotic cells. Scientific Reports. 2014 08;4:6213. doi:10.1038/srep06213.

48. Tinevez JY, Schulze U, Salbreux G, Roensch J, Joanny JF, Paluch E. Role of cortical tension in bleb growth. Proceedings of the National Academy of Sciences of the United States of America. 2009 11;106:18581-6. doi:10.1073/pnas.0903353106.

49. Salbreux G, Charras G, Paluch E. Actin cortex mechanics and cellular morphogenesis. Trends in Cell Biology. 2012 08;22:536-45. doi:10.1016/j.tcb.2012.07.001.

50. Himbert S, D'Alessandro A, Qadri S, Majcher M, Hoare T, Sheffield W, et al. The bending rigidity of the red blood cell cytoplasmic membrane. PLOS One. 2022 08;17:e0269619. doi:10.1371/journal.pone.0269619.

51. Larripa K, Mogilner A. Transport of a 1D viscoelastic actin-myosin strip of gel as a model of a crawling cell. Physica A Statistical Mechanics and its Applications. 2007 01;372:113-23. doi:10.1016/j.physa.2006.05.008.

52. Crick FHC, Hughes AFW. The physical properties of cytoplasm: A study by means of the magnetic particle method Part I. Experimental. Experimental Cell Research. 1950 01;1:37–80. doi:10.1016/0014-4827(50)90048-6.

53. Cao X, Moeendarbary E, Isermann P, Davidson PM, Wang X, Chen MB, et al. A chemomechanical model for nuclear morphology and stresses during cell transendothelial migration. Biophysical Journal. 2016;111(7):1541-52. doi:10.1016/j.bpj.2016.08.011.

54. McGregor A, Hsia CR, Lammerding J. Squish and squeeze—the nucleus as a physical barrier during migration in confined environments. Current Opinion in Cell Biology. 2016 06;40:32-40. doi:10.1016/j.ceb.2016.01.011.

55. Guilak F, Tedrow J, Burgkart R. Viscoelastic properties of the cell nucleus. Biochemical and Biophysical Research Communications. 2000 04;269:781-6. doi:10.1006/bbrc.2000.2360.

56. Ofek G, Natoli R, Athanasiou K. In situ mechanical properties of the chondrocyte cytoplasm and nucleus. Journal of Biomechanics. 2009 04;42:873-7. doi:10.1016/j.jbiomech.2009.01.024.

Supporting information

S1 Movie

Movie of a 15-μm cell passing through a $6 \times 6 \times 100$ μm^3 microchannel, corresponding to Fig. 1(b-c). The images have been acquired at 500 fps.

S2 Movie

Movie presenting the numerical simulation results of a cell passing through a microchannel of width 6 μm, corresponding to Figs. 3-4.