1 **XTree enables memory-efficient, accurate short and long sequence alignment to millions**
2 **of genomes across the tree of life**

3 Gabriel A Al-Ghalith*[1,2], Krista A Ryon[1], James R Henriksen[1,3], David C Danko[4], Brett Farthing[5], Matteo
4 Marengo[6], George M Church[1,7], Raquel S Peixoto[8], Chirag J Patel[1,6], Dan Knights[9], Braden T Tierney*[1,6]
5
1 The Two Frontiers Project, Fort Collins, CO, USA
2 Holobiome, Boston, MA, USA
3 National Renewable Energy Laboratory, Colorado State University, CO, USA
4 Biotia Inc., New York, NY, USA
5 Zymo Research, Irvine, CA, USA
6 Department of Biomedical Informatics, Harvard Medical School, Boston, MA, USA
7 Wyss Institute for Biologically Inspired Engineering, Harvard Medical School, Boston, MA, USA
8 Division of Biological and Environmental Science and Engineering (BESE), King Abdullah University of
Science and Technology (KAUST), Thuwal, Saudi Arabia
9 Biotechnology Institute, University of Minnesota, Saint Paul, MN, USA
16
17 *Corresponding authors:
18
19 Braden Tierney, braden@twofrontiers.org
20 Gabriel Al-Ghalith, gabe@holobiome.org

21
Abstract

XTree is a k-mer-based aligner enabling rapid, memory-efficient alignment of sequencing reads
to whole-genome reference databases with up to millions of genomes. Here, we detail XTree's
performance on short and long read sequencing data and demonstrate its high accuracy across
diverse bacterial, viral, and eukaryotic genomes. Benchmarking demonstrates superior and/or
comparable precision and recall over existing tools, with more scalable indexing and efficient
memory mapping. We additionally provide pre-indexed databases, including (1) the Genome
Taxonomy Database (versions r214-r226), (2) representative GenBank fungi and protozoan
genomes and (3) the Pan-Viral-Compendium, a bespoke data resource spanning 6.6 million,
quality-controlled, viral genomes.

Main Text
33
The alignment of Next Generation Sequencing (NGS) data to reference genomes is

foundational to modern genomics. Mapping bulk sequencing reads to large databases of known

genomes underpins our ability to quantify the genomic and taxonomic diversity of complex

ecosystems. However, alignment algorithms designed many years ago do not necessarily: (1)

computationally scale to today's large reference databases; (2) guarantee high sensitivity and

specificity with continually increasing species diversity across the domains of life, nor; (3)

perform well on newer sequencing methods (e.g., long read sequencing).

Here, we present XTree and its accompanying alignment databases. XTree (see *Methods*) is a

k-mer-based aligner designed for memory-efficient (and virtual/out-of-core memory) parallel

alignment of long or short sequencing reads to millions of genomes. Its earlier incarnations

(e.g., BURST, Utree) have been used in both academia and industry over the past decade[1–11].

XTree extends upon prior k-mer based genome indexing and read assignment strategies[12,13]

(Fig 1) by using: (1) memory mapping for efficient database usage by simultaneous processes;

(2) motif-based sequence indexing (as opposed to using minimizers); (3) canonicalization of

reference k-mers into a binary search tree for quick look ups, and; (4) "capitalist" read

redistribution, which involves storing all possible read alignments and identifying the set of

references that minimize all matches.

XTree additionally identifies multiple types of k-mers and reports associated coverage "types"

with each: unique k-mers are any found specifically in a single genome, whereas Adamantine,

or "maximally unique" k-mers are those that are a Levenshtein distance of > 1 (i.e., more than 1

base edit) away from all other references, enabling strain-specific classification. By default,

XTree reports total coverage of a genome (proportion of an entire genome covered), unique

coverage (unique regions of a genome covered), and Adamantine coverage (Adamantine

regions of a genome covered).

To showcase XTree's utility and guide its use, we evaluated its alignment performance on

representative Genome Taxonomy Database (GTDB) genomes indexed at different k-mers

(Supp Fig 1A). We used 200 synthetic metagenomes spanning species simulated at high and

low relative abundances. Performance remained consistent for k ≥ 21, with k = 29 yielding the

highest mean F1 (Table 1, Supp Table 1, Supp Fig 1B). XTree achieved near-perfect

performance on representative (i.e., "training") genomes (k=29, mean F1 scores for high and

low abundance genomesets: 0.992+/-0.006 and 0.958+/-0.014, respectively) and similarly

strong results on non-representative (i.e., "testing") strains (mean F1 scores: 0.920+/-0.023 and

0.891+/-0.028), despite the fact that they were not included when the XTree database was

indexed.Optimal F1 coverage thresholds varied by abundance—3% unique, 16% total for low;

9% unique, 36% total for high (Supp Fig 1C). Unique coverage (the minimum of both

Adamantine and "weakly unique" (see *Methods*) coverage), minimized false positives while

maximizing true positives (Fig 1B).

We compared XTree to Kraken2/Bracken and MetaPhlAn4 on the same synthetic metagenome

testing set[12,14,15] (Table 1). We chose these approaches due to their frequent usage in

metagenomics; specifically, we included Kraken2 because it is also a kmer-based method that

is frequently used for pan-domain alignment. Constructing a 716GB Kraken2 database on the

GTDB took over three days, whereas XTree completed indexing in <3 hours with the same

resources, producing a more compact 260GB database (for k=29, compression mode 2).

MetaPhlAn4, a marker-gene-based approach using Bowtie2, was tested with its default

database mapped to GTDB taxonomy.

Across all tests, XTree performed comparably to or outperformed other methods (Fig 1C, Table

1, Supp Table 1). Kraken2, without coverage thresholds, had high recall but low precision

(mean F1 score, high abundance non-representative genomes: 0.124+/-0.009; mean F1 score,

low abundance non-representative genomes: 0.0235+/-0.015); applying a coverage threshold

improved classification performance (mean F1 high abundance non-representative genomes:

0.759+/-0.041; mean F1 low abundance non-representative genomes: 0.759+/0.041). XTree

additionally outperformed MetaPhlan4, which had poor performance on GTDB representative

strains and better performance on non-representative strains. Comparing expected versus

predicted relative abundances for true positive classifications, XTree, MetaPhlan4, and Kraken2

(via Bracken) performed similarly in accurately recapitulating expected relative abundances

(Supp Fig 1D).

We next analyzed how F1-optimized unique and total coverage thresholds varied across

bacterial orders to guide species and strain abundance estimation in complex communities.

While a threshold of <10% unique coverage was sufficient for most organisms (Fig 1D), we

found that for optimal total coverage thresholds, clades with reported larger pangenomes (e.g.,

Cyanobacteriales) required different cutoffs to maximize F1 score. Thus, we propose XTree's

unique coverage as a robust threshold for presence/absence detection across diverse bacterial

clades and suggest its F1-optimized cutoffs offer a scalable approach to quantifying pangenome

size.

To assess the impact of database memory mapping on efficiency, we compared XTree and

Kraken2 alignments across 15 samples with varying parallelism (Fig 1E). XTree's default

memory mapping minimized RAM increases as parallel tasks rose from 1 to 3, requiring 260GB

for the database and 40–50GB per alignment. In contrast, Kraken2's median RAM usage

doubled with additional tasks running the default settings. XTree completed runs in about one-

third of Kraken2's runtime while using, maximally, 40% of its RAM (381GB for 3 tasks). Notably,

XTree's disk-backed memory mapping enables alignment on lower-memory systems using

SSDs, albeit with a speed tradeoff. We additionally note that, with specific parameters and

utilizing RAM disk storage, Kraken2 can be made more efficient, however, this is not its default

settings, as opposed to XTree, which will automatically optimize memory usage for a given

system.

We then evaluated XTree on long read sequencing data from multiple platforms, comparing

PacBio's Hi-Fi reads, PromethION data, and GridION data. In lieu of generating synthetic

metagenomes, we used real data on microbial mock communities, a subset of which were used

in a previous aligner benchmarking study (Fig 1F-G)[16]. Precision and recall were high on

average (overall mean precision = 0.972, overall mean recall = 0.883), especially for Hi-Fi data,

but we did find that the log-distributed samples and those on older Nanopore technologies

suffered poorer performance. XTree did perform well compared to the published benchmarks on

the same datasets[17], and we therefore claim that it is a viable tool for long read sequencing,

especially for modern chemistries with low error rates.

To demonstrate XTree's ability to work with viral genomes, we developed the Pan-Viral

Compendium (PVC) by integrating nine published datasets spanning human and environmental

viromes comprising 2,851,990 non-redundant genomes (Supp Table 2, see *Methods*). We

provide various subsets by genome quality (e.g., complete/high genomes only) as raw FASTA

files and indexed XTree databases at multiple k-mer lengths. Additional PVC metadata includes

genome composition (DNA vs. RNA viruses), geNomad and GenBank taxonomies, 90% identity

genome clustering, non-redundant gene catalogs, and Pfam/KEGG HMM-based protein

annotations (Supp Fig 1F-G).[18–21]

XTree databases indexed at k-mer lengths >17 performed well for viral synthetic metagenomes

(Fig 2A), with unique and total coverage cutoffs yielding similar F1 values (Supp Fig 1E). A

database indexed with k=21 performed the best (as opposed to k=29 for bacteria). We also

assessed performance on a challenging set of non-representative PVC genomes, which

included fragmented sequences likely to introduce noise. Despite this, classification remained

strong at higher taxonomic levels (e.g., Family, Class, Order, Phylum, Fig 2B) using a 1%

unique coverage cutoff. As Kraken2 could not feasibly index the full PVC, we used its standard

database for comparison at broader taxonomic levels. While not a direct benchmark, the recall

differences suggest the PVC captures viral diversity absent from conventional reference

databases. We additionally observed concordance between expected and observed abundance

for both representative and non-representative genomes (Fig 2C).

Finally, we additionally indexed and completed a brief evaluation of multiple Eukaryotic

alignment databases. Specifically, these included the full set of dereplicated, representative,

complete and draft fungal (n = 6,317) and protozoan (n = 1,054) genomes from GenBank as of

May and April 2024, respectively. We evaluated the ability of XTree to accurately classify the

presence and abundance of genomes from these datasets in ten synthetic metagenomes and

found the results to be satisfactory (Fig 2D-E). Mean precision and recall for fungal genomes

were 0.96+/- 0.09 and +0.86+/-0.27, respectively. These values were 0.94+/-0.13 and 0.95+/-

0.05 for protozoan genomes.

In summary, in this manuscript, we describe XTree, an aligner built for robust and flexible

whole-genome-based classification across diverse use-cases. The codebase, as well as

download links for all databases and synthetic data in this study, are fully available at

https://github.com/two-frontiers-project/2FP-XTree. We hope the scientific community finds

these to be impactful tools.

Figures and Tables

Figure 1: Description, optimization, and evaluation of XTree on short and long read,
bacterial metagenomes. A) Overview of the XTree algorithm. XTree utilizes k-mer-based
indexing with motif-based compression, canonicalization via binary search trees, and "capitalist"
read redistribution for optimal read assignment, as well as multiple options for Lowest Common
Ancestor (LCA) analysis. B) The utility of total vs. unique coverage thresholds on minimizing
false positives. Each point represents a different genome in a sample, and red lines indicate
optimized coverage cutoffs for high and low-abundance genomes. C) Comparison of XTree,
Kraken2, and MetaPhlAn4 on classification against GTDB non-representative genomes. D)
Optimizing XTree coverage cutoffs across discrete clades E) Memory usage over time for
processing 15 gut metagenomes for XTree and Kraken2 across different levels of parallelism. F)
XTree's performance on long read sequencing of defined communities. G) Observed vs.
expected abundance of bacterial genomes for long read sequencing.
165
Figure 2: XTree's performance on viral and eukaryotic genomes. A) The utility of total vs.
unique coverage thresholds on minimizing false positives when aligning to different indexed
versions of the Pan Viral Compendium. Each point represents a different genome in a sample,
and red lines indicate coverage cutoffs that maximize F1 score. The databases used were
indexed with a k-mer of 21. C = Complete genomes, H = High-quality, M = Medium-quality, L =
Low quality. B) Comparing the performance of Kraken2 and XTree on classifying viral genomes.
C) The expected versus observed relative abundances generated by XTree on representative
(e.g., training) and non-representative (e.g., testing) viral genomes. D) The performance of
XTree on GenBank fungal and protozoal genomes. E) The expected versus observed relative
abundances generated by XTree on GenBank fungal and protozoan genomes.
176
177

	XTree	Kraken2	Metaphlan4
Classification approach	Exact multi-mapping k-mer classification and pseudoalignment on whole genomes/genes	K-mer–based classification using LCA on minimizers	Bowtie2 on marker genes
Intended input data type	Short/long reads, genes, genomes	Short reads	Short reads
Intended domains for alignment	Bacteria, Eukaryotes, Viruses	Bacteria, Eukaryotes, Viruses	Bacteria
Primary database structure	Prefix-hashed left binary search tree	Hash map	Bowtie2 index
Database size on disk	260GB (GTDB r214, comp=2, k =29)	716GB (GTDB r214)	23G (default DB)
RAM usage for 3 parallel processes, (default memory settings), classifying against GTDB	399GB	1014GB	N/A (very low)
GTDB alignment results, representative, high abundance genomes	Mean F1: 0.992 +/- 0.006	Mean F1: 0.977+/0.012	Mean F1: 0.418+/-0.067
GTDB alignment results, non-representative, high abundance genomes	Mean F1: 0.920 +/- 0.023	Mean F1: 0.759+/-0.041	Mean F1: 0.407+/0.067
GTDB alignment results, representative, low abundance genomes	Mean F1: 0.958 +/- 0.014	Mean F1: 0.739+/0.042	Mean F1: 0.832+/-0.033
GTDB alignment results, non-representative, low abundance genomes	Mean F1: 0.891 +/- 0.028	Mean F1: 0.759+/0.041	Mean F1: 0.807+/-0.035

Long read alignment results	Mean F1: 0.916+/-0.122	N/A	N/A
Viral alignment results, PVC representative genomes	Mean F1: 0.989+/-0.00812	N/A	N/A
Viral alignment results, PVC non-representative genomes	Mean F1: 0.743+/-0.0358	N/A	N/A
Viral alignment results, taxonomies (all ranks, PVC for XTree and default viral database for Kraken2)	Mean F1: 0.951 +/- 0.0541	Mean F1: 0.347+/-0.140	N/A
Fungal alignment results	Mean F1: 0.884+/-0.207	N/A	N/A
Protozoan alignment results	Mean F1: 0.946+/-0.0905	N/A	N/A

Table 1: Comparing the algorithms and performance of XTree, MetaPhlan4, and Kraken2.
All outputs are reported for the default settings for MetaPhlAn4 and 5% coverage cutoffs for
XTree (referring to unique coverage) and Kraken2, respectively. The XTree values report the
k=29 index. Additional details on aligner performance in Supplementary Table 1. GTDB =
Genome Taxonomy Database.

Supplement

Supplemental Figure 1: Additional information on experimental design and alignment statistics.
A) Synthetic metagenome and database generation process. Green boxes were training
sets/databases; orange is the "testing sets" of genomes XTree had not been trained on. B)
Performance of XTree with different kmer sizes. We recommend tailoring kmer choice to the
domain of life analyzed and keeping kmers above 17. C) Precision-Recall curves showing F1-
optimized unique/total coverage values for bacterial genomes indexed at k = 29. D) Expected
vs. observed abundance across aligners. E) K-mer optimization for viral genomes. F) Gene
catalog summary statistics for the Pan-Viral-Compendium.

Supplementary Table 1: Additional aligner comparison and performance statistics to provide
more context for Table 1.

Supplementary Table 2: List of databases found in the Pan Viral Compendium.

198 **Methods**
199
200 *XTree databases and indexing*
201 XTree is a k-mer-based aligner. It matches reference sub-sequences of length k – determined
202 during the database build step – to kmers found in input sequences. These input sequences can
203 be in FASTQ and FASTA form, paired or single-ended, and of any length. The general process
204 for the XTree algorithm, both database construction and alignment, is described in Figure 1.
205
Databases can be constructed of any set of contigs in FASTA format. We recommend high-
quality genomes that are dereplicated at a level between 90% and 99% nucleotide identity (e.g.,
95% and 99% for bacterial and viral genomes, respectively). We do not recommend
constructing databases from multiple domains of life, as the optimal k-mer length or
dereplication cutoff may vary depending on genome size and complexity. Genome dereplication
is important prior to database generation as it enables the identification of species or strain-
specific k-mers, which in turn inform a user's ability to design coverage cutoffs.
213
Databases are built using a motif-based search, with the motifs selected varying depending on
the compression level (i.e., number of kmers) selected. At varying compression levels, different
motifs are used to determine which kmers are preserved in the index (sampling stride); the
motifs in question were chosen to capture a wide range of genomic sequences while reducing
the redundancy of stored information (i.e., minimizing tightly overlapping k-mers while retaining
comparability of the same k-mers regardless of context). For compression level 0, all kmers of a
given length are stored, resulting in larger database sizes. For compression level 1, all kmers
preceded by an A are stored. For compression level 2, all kmers following AT, AC, or AG 2-
mers are stored. This results in a compression level 2 database size being similar to the input
fasta file used to generate it.
224
XTree currently stores all k-mers that meet these motif-based criteria, and it additionally can
track k-mers that appear in a single reference as being "unique" and/or "Adamantine." Unique
kmers are those found in a single genome. Adamantine kmers are a subset of these; each
Adamantine kmer is more than 1 base pair edit (Levenshtein distance of 2 or greater) from all
other kmers present in other genomes; this makes Adamantine k-mers a more ironclad
indicator of that specific reference, rather than a simple off-by-one sequencing error/small
mutation/noise flip. We propose them to be useful for tracking strains when you have multiple
similar strains, as sequencing noise can often flip a k-mer to appear like it's from another similar
genome. We do not recommend using Adamantine k-mers in cases where strain-level
specificity is not necessary.
235
During alignment, query k-mers are canonicalized into a binary format consisting of a binary
prefix (for use as initial perfect hash index) and a suffix, which is looked up within a binary tree
stored at that prefix. We use a flattened binary tree due to its efficiency of data structure, with
lower RAM usage than a full hash map given its ability to assemble full kmers on the fly using
only their stored suffices combined with the tree structure. Effectively, lookup consists of an
initial perfect hash lookup of the binary prefix, which provides the index range within the
flattened tree array containing suffix-keyed leaves, within which the (first) suffix match is
identified by left-first binary search (LBS) within that range.
244
The completed lookup provides an index into all matching genomes and associated metadata
(e.g., source genome identifier, the source genome's taxonomy, etc). If present in the database
structure, a secondary "Adamantine" tree is also searched by default for each unique k-mer to
determine whether the k-mer is "weakly unique" (e.g., found within 1 Levenshtein distance of a

k-mer in another genome); if a unique k-mer is not specified as weakly unique, it is Adamantine
(strongly unique). The adamantine tree is generated by default on database construction,
though, as mentioned above, for analyses not reliant on strain-level differentiation, it can be
omitted during the database build step (or not utilized during alignment even if present in the
database), enabling downstream efficiency gains during alignment.
254
If a taxonomy map is provided in the database BUILD process, two forms of taxonomy output
are available in ALIGN mode using the --tax-out flag. Using the flag will default to using Lowest
Common Ancestor (LCA) taxonomic assignment by performing a root-to-leaf interpolation
among each query's set of identified matches, adhering to the user-specified confidence (--
confidence) level at each level of the hierarchy; a simple leaf-only voting scheme will be used
instead if --shallow-lca is specified[22]. Alternatively, the Capitalist read redistribution algorithm will
be used for both taxonomy assignment and reference re-assignment if --redistribute is specified,
similar to its use in BURST but using an expectation maximization step to approximate BURST's
graph-pruning method for simplicity[1]. When Capitalist is enabled with --tax-out, taxonomy will be
reported at the leaf node of the winning taxonomic label (highest specificity).
265
During the alignment process, a given database is mapped to memory, enabling multiple XTree
processes on the same machine to simultaneously use a single copy of the loaded database in
dynamic shared memory backed by a single location on physical disk, reducing overall memory
footprint, enabling "warm starts" for subsequent runs, and allowing for simultaneous instances
to run. Small databases can alternatively be copied to CPU-local memory (--copymem),
providing each process greater locality of reference; on some architectures (such as multi-
socket systems for which NUMA controls are not enabled) or for some very small databases
that can partially fit within L3 cache, this may be preferred. We note that as CPU-local memory
sizes increase, XTree's performance will increase for proportionally larger databases. Notably,
due to memory mapping, XTree does not strictly require the entire database to fit within RAM at
one time. Users with limited memory (as low as <= 64GB) but with fast direct NVME SSD
storage may run XTree without issue but incur a speed penalty approximately proportional to
both the difference between the size of the database and the free RAM, and the speed
differential between the SSD random read performance and system RAM bandwidth.
280
XTree alignment, read assignment, and memory efficiency
Upon ingestion of reads, XTree begins its k-mer search in the same manner as it approaches
database indexing. All k-mers for a given read with the appropriate motifs (depending on the
reference database's compression level) are stored in memory. These k-mers are matched to
the canonicalized reference database and the appropriate leaves of the binary search tree are
searched. Each potential match to a given reference genome is stored.
287
By default, XTree is run in "Capitalist Redistribution" (i.e., winner takes all) mode, where the
space of all possible k-mer matches are searched and the set of assignments that minimize the
total number of references assigned is selected. Capitalist is a global read redistribution
algorithm, as opposed to a per-read greedy assignment method. Its purpose is to resolve multi-
mapping reads across the entire dataset simultaneously, as opposed to doing so for every
query at once. It leverages the fact that XTree records all possible reference hits for every k-mer
in every read, producing a large, multi-mapped space describing which reads could feasibly
derive from which sources. Capitalist performs an expectation-maximization procedure over this
space; in each iteration, reads are provisionally assigned to the reference that is most strongly
supported by other reads across the entire dataset. As assignments aggregate, the relative
support for competing references shifts accordingly. This process continues until convergence
on a given reference, or until an iteration threshold is reached, producing a one-to-one

assignment in which a read is assigned to a single reference. The phrase "winner takes all"
refers to this globally considered outcome, as opposed to a per-read or per-reference approach.
Therefore, capitalist redistribution is approximating the solution to a global set-cover-like
problem without explicitly solving an NP-complete formulation, using dataset-wide competition
among references to converge on a parsimonious explanation across all reads, jointly.
305
This behavior is distinct from other approaches (e.g., fast read mappers or Kraken2), which rely
on per-read best-hit (or stored LCA-based) assignment modes. Other read redistribution
techniques (e.g. Bracken) use post hoc abundance redistribution without access to information
on each read's specific multi-mappings, and do not explicitly leverage the set of multi-mappings
across all queries in a dataset for making assignment decisions. If Capitalist Redistribution
mode is disabled, the reference genome with the highest number of k-mer matches is simply
assigned (with "first stored reference" as a tie breaker).
313
If XTree is run with the --tax-out command (without Capitalist Redistribution), XTree will
independently compute the LCA among all reference genomes matched by the query.
Importantly, LCA is not stored per reference k-mer based on a pre-computed database; it is
computed among the specific matches for each query during alignment. Specifically, the LCA
taxonomic assignment of a read is computed after the k-mer lookup stage by traversing the
taxonomic subtree formed by all references with matching k-mers in the read; if --tax-out is run
with Capitalist Redistribution, the taxonomic call of a read is also determined based on the full-
dataset-aware read assignment on the taxonomic string provided; in tandem with the reference-
level capitalist redistribution, this enables multiple independent granularities of assignment for a
single query, leveraging the different scales of evidence available at different set granularities.
324
XTree outputs and coverage thresholding
In addition to the timing and alignment statistics printed to stdout by default, XTree generates up
to four output files depending on user specification: tax, cov, ref, and perq. The tax file, as
previously described, contains taxonomic information in a simple tab-delimited format of key-
value association (reference, followed by semicolon-delimited hierarchical string). To use "--tax-
out" mode, the taxonomy map must be supplied during database construction (we plan for
future versions to allow supplying an arbitrary taxonomy at runtime). The taxonomy file may
contain up to two hierarchies (e.g., two different taxonomic schemas or granularities, or a
taxonomy and a GO hierarchy if genes are used as references instead of genomes), both of
which will independently be used for alignment summarization in the tax output file. The cov file
contains a complete set of total, unique, and Adamantine breadth-of-coverage and depth-of-
coverage (i.e., pileup) statistics for each genome or reference sequence, separated into total k-
mer coverage, unique, and adamantine. Since specific coordinates of alignments are not stored,
these values are approximated via kmer set coverage and multiplicity of coverage per reference
of different kmer types (e.g., total adamantine coverage, total unique coverage, total coverage).
340
Depth of coverage can be interpreted as read pileup, which can be used to generate relative
abundance estimates. The ref file contains a simple table of references matched, and the
number of queries assigned to each.. Finally, the perq out file will report the potential
assignments of every read, enabling users to further understand their alignment results (e.g.,
filtering multi-mapping reads). Note that each output type is only computed if it is requested by
the associated --out flag, to avoid unnecessary bookkeeping.
347
By default, XTree does not threshold based on coverage in order to determine genome
presence and absence. While this step is critical for determining meaningful compositional
analysis downstream, the decision is left up to the user, as the selected threshold will vary

based on sampleset and tolerance to noise. Based on the analysis in this manuscript, we
recommend a 1% to 10% threshold derived from the minimum of total, unique, and Adamantine
coverage. Recall that, for example, 1% adamantine coverage does not correspond to covering
1% of the genome; it instead indicates 1% of coverage of the ultra-unique (adamantine) regions
of the genome. We provide scripts for assisting with coverage thresholding in the GitHub
repository.
357
358 *XTree*   *pseudocode*
359
360 Below is pseudocode for the XTree algorithm:
361
Inputs:
1. Reference genomes $G = \{g_1 \dots g_N\}$
2. Query reads $Q = \{q_1 \dots q_M\}$
3. k-mer length K (BUILD mode)
4. Prefix length PL (BUILD mode)
5. Compression level C (BUILD mode)
6. Optional taxonomy mapping T (BUILD mode)
369
370 <u>BUILD:</u>
371
372 Construct lookup data structure PrefixBins with length = all possible prefixes
373   1. For each reference genome g_i in G:
374   a. Stream through g_i and extract canonical k-mers, defined as the lexicographically
375   smaller of the forward k-mer and its reverse complement.
376   b. Apply motif-based subsampling according to compression level C.
377   c. For each retained k-mer, split it into a prefix pfx of length PL and a suffix sfx.
378   d. Append the pair (sfx, i) to the bin PrefixBins[pfx][] corresponding to prefix pfx.
379
380 For each prefix bin:
381   ● Sort all stored (sfx, i) pairs lexicographically by sfx, then by reference index i.
382
383 If adamantine enabled, construct the adamantine disqualifier tree:
384   1. Initialize a new prefix-bin data structure WeakBins with length = all possible prefixes.
385   2. For each reference genome g_i in G:
386   a. Extract to identify unique k-mers by examining multiplicity of suffixes within each
387   prefix bin in PrefixBins.
388   b. For each unique k-mer, determine weakly unique status
389   i. Generate all possible singly-mutated k-mers, k_mut
390   ii. Look up each k_mut in PrefixBins. Consider each returned tuple (sfx,j).
391   iii. If tuple exists and i != j, add to WeakBins[pfx] (it is "weakly unique").
392
393 Store the database as:
394   ● A prefix offset array mapping each prefix to a contiguous suffix range.
395   ● A flat, suffix-sorted array of (suffix, reference index) pairs.
396   ● Reference metadata and optional taxonomy mappings.
397   ● Optionally, the adamantine disqualifier tree, by flattening WeakBins.
398
399 <u>ALIGN:</u>
400
401 For each query read q_j in Q:

402   1. Extract canonical k-mers and split each into (pfx, sfx).
403   a. For each (pfx, sfx):
404   i.   Locate the suffix range corresponding to pfx.
405   ii. Left-first binary-search for sfx within that range.
406   iii. Enumerate all reference indices sharing that suffix.
407   iv. Aggregate k-mer hit counts per reference for q_j.
2. If taxonomy output is requested, derive taxonomic labels for q_j directly from the set of
possible reference hits using lowest-common-ancestor interpolation with a confidence
threshold.
a. If shallow LCA selected, use voting scheme among leaves
3. Assign q_j to exactly one reference using one of the following modes:
a. BEST: select the reference with the highest k-mer count for q_j.
b. CAPITALIST: defer assignment for global redistribution.
415
416 If coverage output is requested:
417   1. Tally matched k-mers per reference across all reads.
418   2. Compute total, unique, and Adamantine coverage statistics.
419   a. If --forage is specified, consider all references with at least 1 k-mer match
420   b. If --half-forage is specified, consider the set of k-mers mapping to the highest
421   supported reference and all others within 50% of the k-mer support
422   c. If neither is specified, consider the set of k-mers mapping to the highest
423   supported reference only
424   3. If CAPITALIST redistribution is enabled:
425   a. Iteratively reassign reads to references using a global expectation–maximization-
426   like procedure until convergence.
427   b. Output final one-to-one read-to-reference assignments.
428
429 Outputs:
430   ● Reference assignments, optional taxonomy summaries, and optional coverage statistics.
431
432 *Construction of XTree bacterial reference databases*
433 We constructed XTree databases on the representative genomes provided by the Genome
434 Taxonomy Database (GTDB) Release 214. We indexed these with XTree's BUILD function at k
435 = 17, 21, 24, and 29.
436
437 *Construction of and benchmarking on synthetic bacterial metagenomes*
438 To evaluate the performance of XTree, we constructed synthetic metagenomes. We assessed
439 XTree's performance on both high- and low-abundance genomes across multiple k-mer sizes
440 and taxonomic groups. The workflow for synthetic metagenome construction is detailed in
441 Supplementary Figure 1A.
442
We then generated four sets of 50 synthetic metagenomes, each comprising between 75 and
100 bacterial genomes sampled randomly from the GTDB. The four datasets created were at
high abundance (0.1x coverage to 10x coverage) and from GTDB representative species, low
abundance (0.001x coverage to 1x coverage) from GTDB representative species, high
abundance from GTDB non-representative species, and low abundance from GTDB non-
representative species. Within each of the 200 metagenomes, every genome was assigned an
abundance (i.e., depth of coverage) following random sampling from a uniform distribution, with
a minimal coverage threshold enforced to ensure at least one read per genome.
451

To generate synthetic Illumina sequencing reads for each metagenome, we used DWGSIM with
an error rate of 0.001, a paired-end read length of 150 bp. Each synthetic metagenome was
created by concatenating reads from all genomes in a given set. The synthetic reads were
subsequently aligned to a corresponding XTree reference database. Alignments were run with
forage mode (--doforage) and capitalist redistribution (default, Fig 1) enabled[1]. For this and all
other synthetic metagenome evaluation tests, expected relative abundance was equal to the
specified DWGSIM coverage for a given genome, normalized to sum to one. Observed relative
abundance was the similarly normalized depth of coverage (pileup) output by XTree.

Evaluation of runtime and memory usage
We selected and downloaded fifteen samples at random from a major gut microbiome study
with publicly available metagenomic data[23]. Tracking memory usage and runtime, we ran the
sequencing reads through XTree and Kraken2 with the same parameters as used in the other
benchmarking studies to the GTDB-indexed databases (again using the k = 29 database in the
case of XTree).

Benchmarking on bacterial long read data
We benchmarked XTree on long read data across a variety of platforms. We first downloaded
publicly available datasets used in prior benchmarking studies
(https://github.com/LomanLab/mockcommunity as well as SRR11606871 and SRR13128014).
The samples contained sequencing data on the (1) Zymo Research Mock Community Standard
(comprising samples with both even and log distributed abundances), (2) the Zymo Research
Mock Gut Community, and (3) the ATCC MSA-1003 Mock Community. These data were PacBio
Hi-Fi sequencing as well as sequencing from Oxford Nanopore PromethION and GridION
devices. The specific chemistries and flow cells are available on the above GitHub repository.
We additionally were provided with PacBio Hi-Fi sequencing by Zymo Research on their even
abundance Mock Community. After downloading, we quality controlled samples with Shi7
(parameters 500 8 FLOOR 4 ASS_QUALITY 10)[24]. We then ran XTree on this data with the
default parameters and filtered for 10% unique coverage (again computed using the minimum of
Adamantine and unique coverage).

Constructing the Pan Viral Compendium (PVC)
We downloaded assembled contigs from the databases listed in Supp Table 2 (most recent
versions as of October 31st, 2023). The resultant 6,658,852 contigs were then combined and
de-replicated (via greedy clustering of length-sorted contigs with AkronyMer) at a 99% identity
threshold, yielding 2,851,990 non-redundant contigs. These were then processed with CheckV
(default settings, V1.0.1) and separated into low, medium, high, and complete quality based on
the outputs[25]. Pfam annotations were generated for each assembly with HMMER3 --notextw --
noali --nobias --nseq_buffer 100000 --nhmm_buffer 1000, V3.3.2)[26]. Each contig was
taxonomically annotated with GeNomad (default settings, V1.6.1)[18]. We additionally provide
GenBank taxonomy for dereplicated contigs that either 1) were derived directly from the
GenBank complete database (and therefore had an associated taxonomy) and/or 2) were
representative contigs for a cluster of genomes containing GenBank assembly. We used the
GenBank species-level annotation for the sensitivity analysis in the manuscript regarding the
accuracy of high-resolution taxonomic classifications (Fig 2, Supp Fig 1, Supp Table 1). The
sequences which comprise the Pan Viral Compendium (PVC), taxonomic annotations, Pfam
annotations, gene catalog, and other associated metadata are available at
https://figshare.com/articles/dataset/PVC_Release_V0_1/24566995?file=43154491.

PVC XTree database generation

For sets of dereplicated contigs stratified by quality (complete, high, medium, low), we
generated and compared different XTree databases, varying the k-mer length used to index the
genome sets, which we hypothesized would bias the dataset towards different clades based on
genome features (e.g, length, repetitiveness), while suffering potential tradeoffs in alignment
time (i.e., a smaller k-mer index yields a smaller database, meaning faster alignments).

507
Generation of and benchmarking on synthetic viral datasets
For viral benchmarking, we constructed synthetic metagenomes using the Pan Viral
Compendium (PVC), a curated database of 6.6 million viral genomes. To systematically assess
alignment performance across different genome qualities, we stratified the PVC into four
groups: (1) Complete-High (CH) quality genomes, (2) Complete-High-Medium (CHM) quality
genomes, (3) Complete-High-Medium-Low (CHML) quality genomes, and (4) Non-
representative genomes (testing set). Each synthetic viral metagenome consisted of 100 to 250
randomly selected genomes per set, simulated at 1x–10x coverage using the same DWGSIM
pipeline as bacterial metagenomes. Viral reads were aligned to XTree databases indexed at k =
17, 21, 24, and 29.

518
519 To evaluate classification performance, we compared XTree's predictions against known
520 ground-truth taxonomic labels from the PVC. We computed precision, recall, and F1-score,
521 analyzing classification accuracy across multiple taxonomic levels, including species, genus,
522 family, order, and phylum.

523
Each synthetic dataset was aligned to its respective XTree database, and classification
accuracy was assessed based on genome coverage thresholds. The benchmarking workflow
involved five key steps: (1) random genome selection from the reference database, (2)
coverage level assignment using a uniform sampling function, (3) read simulation with
DWGSIM, (4) alignment with XTree using memory-mapped database indexing, and (5)
performance evaluation using standard precision-recall metrics.

530
531 *Generation and benchmarking of synthetic eukaryotic datasets*
532
We downloaded the full set of complete and draft protozoan and fungal genomes from GenBank
as of May and April 2024, respectively. We dereplicated each set at 95% identity and build
XTree databases at compression level 2 with k=29. We created 10 synthetic metagenomes per
dataset. We randomly selected between 10 and 25 genomes from each collection. We used
DWGSIM with the same parameters as before to create synthetic reads for each genome at a
random coverage level between 0.01 and 0.1, combining the outputs to create a metagenome.
We aligned these reads back against the indexed references and estimated true and false
positive rate 1% adamantine coverage.

541
542 **Data Availability**
543
544 All code used in this study can be accessed through the Two Frontiers Project XTree Github
545 repository (https://github.com/two-frontiers-project/2FP-XTree). The Pan-Viral-Compendium and
546 additional sequencing data that is not publicly available can be accessed at
547 https://figshare.com/articles/dataset/PVC_Release_V0_1/24566995?file=43154491.

548
549 **Competing Interests**
550
551 GAG is an employee of Holobiome and consults for Seed Health. BF is an employee of Zymo
552 Research, which had no role in funding this study other than providing sequencing data of one

sample. BTT and GMC have additional conflicts as founders and consultants at a variety of
biotechnology companies, none of which were involved in this study.

Acknowledgements

We thank Zymo Research for providing PacBio Hi-Fi sequencing of their microbial standard. We
thank Heng Li and Jim Shaw for their feedback on an earlier version of this manuscript.

References

1. Al-Ghalith, G. & Knights, D. BURST enables mathematically optimal short-read alignment

    for big data. *Bioinformatics* (2020).

2. Priya, S. *et al.* Identification of shared and disease-specific host gene-microbiome

    associations across human diseases using multi-omic integration. *Nat. Microbiol.* **7**, 780–

    795 (2022).

3. Tierney, B. T. *et al.* Longitudinal multi-omics analysis of host microbiome architecture and

    immune responses during short-term spaceflight. *Nat. Microbiol.* **9**, 1661–1675 (2024).

4. Button, J. E. *et al.* Precision modulation of dysbiotic adult microbiomes with a human-milk-

    derived synbiotic reshapes gut microbial composition and metabolites. *Cell Host Microbe*

    31, 1523–1538.e10 (2023).

5. Tolonen, A. C. *et al.* Synthetic glycans control gut microbiome structure and mitigate colitis

    in mice. *Nat. Commun.* **13**, 1244 (2022).

6. Lin, C.-Y. *et al.* Longitudinal fecal microbiome and metabolite data demonstrate rapid shifts

    and subsequent stabilization after an abrupt dietary change in healthy adult dogs. *Anim.*

    Microbiome **4**, 46 (2022).

7. Johnson, K. E. *et al.* Human cytomegalovirus in breast milk is associated with milk

    composition and the infant gut microbiome and growth. *Nat. Commun.* **15**, 6216 (2024).

8. Vinithakumari, A. A. *et al.* Clostridioides difficile infection dysregulates brain dopamine

    metabolism. *Microbiol. Spectr.* **10**, e0007322 (2022).

9. Tierney, B. T. *et al.* Towards geospatially-resolved public-health surveillance via

wastewater sequencing. *Nat. Commun.* **15**, 8386 (2024).

10. Napier, B. A., Van Den Elzen, C., Al-Ghalith, G. A. & Avena, C. V. Mo1894 A MULTI-

SPECIES SYNBIOTIC (DS-01) ALLEVIATES CONSTIPATION AND ABDOMINAL PAIN IN

IRRITABLE BOWEL SYNDROME SUBTYPE …. *Gastroenterology* (2024).

11. Napier, B. A. *et al.* Mo1894 A MULTI-SPECIES SYNBIOTIC (DS-01) ALLEVIATES

CONSTIPATION AND ABDOMINAL PAIN IN IRRITABLE BOWEL SYNDROME SUBTYPE

MIXED (IBS-M) SUBJECTS WHILE BOOSTING SYNBIOTIC SPECIES ASSOCIATED

WITH DECREASED SYSTEMIC INFLAMMATION AND NET FORMATION.

Gastroenterology **166**, S–1164 (2024).

12. Wood, D. E., Lu, J. & Langmead, B. Improved metagenomic analysis with Kraken 2.

Genome Biol. **20**, 257 (2019).

13. Irber, L. *et al.* sourmash v4: A multitool to quickly search, compare, and analyze genomic

and metagenomic data sets. *J. Open Source Softw.* **9**, 6830 (2024).

14. Blanco-Míguez, A. *et al.* Extending and improving metagenomic taxonomic profiling with

uncharacterized species using MetaPhlAn 4. *Nat. Biotechnol.* **41**, 1633–1644 (2023).

15. Lu, J., Breitwieser, F. P., Thielen, P. & Salzberg, S. L. Bracken: estimating species

abundance in metagenomics data. *PeerJ Comput. Sci.* **3**, e104 (2017).

16. Marić, J., Križanović, K., Riondet, S., Nagarajan, N. & Šikić, M. Comparative analysis of

metagenomic classifiers for long-read sequencing datasets. *BMC Bioinformatics* **25**, 15

(2024).

17. Helal, A. A., Saad, B. T., Saad, M. T., Mosaad, G. S. & Aboshanab, K. M. Benchmarking

long-read aligners and SV callers for structural variation detection in Oxford nanopore

sequencing data. *Sci. Rep.* **14**, 6160 (2024).

18. Camargo, A. P. *et al.* Identification of mobile genetic elements with geNomad. *Nat.*

Biotechnol. **42**, 1303–1312 (2024).

19. Punta, M. *et al.* The Pfam protein families database. *Nucleic Acids Res.* **40**, D290–301

(2012).

20. Kanehisa, M., Furumichi, M., Sato, Y., Kawashima, M. & Ishiguro-Watanabe, M. KEGG for

taxonomy-based analysis of pathways and genomes. *Nucleic Acids Res.* **51**, D587–D592

(2023).

21. Federhen, S. The NCBI taxonomy database. *Nucleic Acids Res.* **40**, D136–43 (2012).

22. Farach-Colton, M. Lowest common ancestors in trees. in *Encyclopedia of Algorithms* 1169–

1174 (Springer New York, New York, NY, 2016).

23. Lloyd-Price, J. *et al.* Multi-omics of the gut microbial ecosystem in inflammatory bowel

diseases. *Nature* **569**, 655–662 (2019).

24. Al-Ghalith, G. A., Hillmann, B., Ang, K., Shields-Cutler, R. & Knights, D. SHI7 is a self-

learning pipeline for multipurpose short-read DNA quality control. *mSystems* **3**,

10.1128/msystems. 00202–17 (2018).

25. Nayfach, S. *et al.* CheckV assesses the quality and completeness of metagenome-

assembled viral genomes. *Nat. Biotechnol.* **39**, 578–585 (2021).

26. Eddy, S. R. A new generation of homology search tools based on probabilistic inference.

Genome Inform. **23**, 205–211 (2009).