SurvMarker: An R Package for Identifying Survival-Associated Molecular Features Using PCA-Based Weighted Scores

Dona Hasini Gammune[1], Tongjun Gu[1,2,3*]

[1]Versiti Blood Research Institute, Milwaukee, Wisconsin

[2]Data Science Institute, Medical College of Wisconsin, Milwaukee, Wisconsin

[3]Department of Biostatistics, University of Florida, Gainesville, Florida

*Corresponding author:

Tongjun Gu, PhD
Versiti Blood Research Institute
8727 W Watertown Plank Rd, Milwaukee, WI 53226
Email: tgu@versiti.org
Office: 414-937-3884

Abstract

Summary: SurvMarker is an R package for identifying survival-associated features in

high-dimensional molecular data using PCA-based weighted scoring. The method

aggregates feature loadings across survival-associated principal components (PCs) and

evaluates feature significance against a feature-specific empirical null distribution,

enabling stable, parsimonious, and statistically calibrated prognostic feature selection.

Availability and Implementation: SurvMarker is implemented in R and distributed

under the MIT License (MIT). The package includes comprehensive documentation, a

reference manual, and a reproducible workflow example, and is provided as

Supplementary Material. Source code and documentation are openly available at the

GitHub repository https://github.com/tjgu/SurvMarker.

Contact: tgu@versiti.org

Introduction

High-dimensional transcriptomic RNA profiling has become central to biomarker discovery and prognostic modeling in cancer and other complex diseases. In survival analysis settings, dimensionality reduction is often required to stabilize inference, reduce multiple-testing burden, and retain biologically meaningful signal. Principal component analysis (PCA) is widely used for this purpose, as it captures dominant patterns of variation in expression data and provides orthogonal latent representations suitable for downstream survival modeling.

Despite its widespread use, there is no principled and widely accepted approach for selecting molecular features from principal components (PCs). The most common strategy is to select a fixed number of top-loading features from each PC (Pollen et al., 2014), an approach also adopted in our earlier work (Gammune et al., 2025). While effective, this strategy has several limitations. First, it relies on an arbitrary per-PC cutoff. Second, PCs are treated independently, without integrating information across multiple survival-associated PCs. Consequently, features with moderate but consistent contributions across several PCs, potentially reflecting biologically meaningful and prognostic relevant signals, may be overlooked.

To address these limitations, we developed SurvMarker, an R package that implements a novel, data-driven PCA-based feature selection framework for survival analysis. Rather than selecting a fixed number of features from individual PCs, SurvMarker aggregates loading information across all survival-associated PCs and explicitly anchors feature importance to survival relevance.

Within this framework, PCA is performed on a normalized high-dimensional expression

matrix, and survival-associated PCs are identified using Cox proportional hazards

models, with optional adjustment for clinical covariates. Feature importance is quantified

by aggregating loadings across all survival-associated PCs, weighted by the variance

explained by each PC, yielding a single interpretable score for each gene that reflects

its overall contribution to survival-relevant latent structure. Statistical significance is

assessed using an empirical null distribution constructed from non–survival-associated

PCs, enabling estimation of empirical p-values and false discovery rates.

To our knowledge, this loading-based feature scoring strategy has not been reported

previously. The most closely related methodology is supervised PCA (Bair et al., 2006),

which links dimensionality reduction to outcome-guided component selection. However,

supervised PCA typically derives feature importance from a single supervised

component or from direct correlations between features and outcome-guided latent

variables. In contrast, our approach aggregates information across multiple survival-

associated PCs, incorporates variance-based weighting, and uses an empirical null

framework for inference. This results in a more stable, interpretable, and statistically

grounded ranking of prognostic features, particularly in settings where survival signal is

distributed across multiple latent dimensions.

The proposed framework is implemented in the SurvMarker R package, provides end-

to-end functionality for PCA-based survival screening, feature scoring, empirical null

construction, and visualization. While motivated by transcriptomic expression data,

SurvMarker is applicable to any normalized high-dimensional molecular matrix,

including miRNA expression, proteomic and metabolic measurements, and DNA
methylation ratios.

The remainder of this paper describes the SurvMarker framework and its
implementation. Figure 1 presents representative outputs generated using real-world
biological data, and additional methodological details and extended analyses are
provided in the Supplementary Material.

SurvMarker: Implementation and Results

SurvMarker is implemented as an R package and distributed under the MIT License
(MIT). R was chosen due to its widespread adoption in the bioinformatics community,
rich ecosystem of statistical and visualization tools, and seamless integration with
existing transcriptomic and survival analysis workflows. The package is designed to
support reproducible analyses and straightforward incorporation into established
genomic pipelines.

PCA-based feature selection in high-dimensional survival analysis involves several
nontrivial methodological choices, including the number of PCs to evaluate, how
information should be aggregated across PCs, and how statistical significance should
be assessed while controlling false discoveries. SurvMarker provides a transparent and
flexible framework that exposes these decisions through well-documented parameters,
enabling users to tune analyses while maintaining robust default behavior.
Representative outputs are shown in Figure 1, while the complete feature scoring
methodology is illustrated in Supplementary Figure 1.

Core workflow and feature scoring

A typical SurvMarker analysis is performed using a single function call:

```
pca_based_weighted_score(
  X = X, time = time, status = status, covar = covariates,
  n_pcs = 50, pc_fdr_cutoff = 0.05, feature_fdr_cutoff = 0.05,
  null_B = 500, scale_pca = TRUE, use_abs_loadings = TRUE,
  store_null = TRUE, seed = 1)
```

The input matrix, `X`, is a normalized high-dimensional dataset with samples in rows and features (e.g. genes or miRNAs) in columns. Survival follow-up time and event status are provided via `time` and `status` (1 = event, 0 = censored), respectively. Optional clinical covariates (`covar`) may be included to adjust Cox proportional hazards models for PC–survival associations (e.g., age, sex, and European LeukemiaNet (ELN) 2022 risk).

SurvMarker provides two complementary strategies for determining the number of PCs evaluated. Users may specify a fixed number via `n_pcs`, or alternatively select the minimum number of PCs (`n_pcs`) required to explain a desired fraction of variance via `cumvar_threshold`, with `max_pcs` (default 50PCs) acting as a safety cap. Survival association is tested for each PC, and multiple testing is controlled using False Discovery Rate (FDR) across PCs (`pc_fdr_cutoff`, default 0.05), defining the set of survival-associated components.

Rather than selecting a fixed number of top-loading features per PC, SurvMarker

aggregates feature loadings across all survival-associated PCs to compute a single

weighted score S_j for each feature. Loadings can be taken in absolute value

(`use_abs_loadings = TRUE`) and are weighted by the variance explained by each

PC, prioritizing features that contribute consistently to survival-relevant latent structure.

Statistical significance is assessed using an empirical null distribution constructed by

repeatedly sampling from non–survival-associated PCs (`null_B`, default 500).

Empirical *p*-values and Benjamini–Hochberg (BH)-adjusted *p*-values are computed, and

prioritized features are selected using a user-defined FDR threshold

(`feature_fdr_cutoff`, default 0.05).

The returned object includes a ranked feature table (`feature_table`) containing each

feature's loadings on survival-associated PCs, the aggregated score S_j, empirical *p*-

value, and BH-adjusted *p*-value, as well as PC-level summaries of variance explained

and survival associations (`pc_table`). For reproducibility and diagnostic purposes,

SurvMarker optionally stores the full null score matrix (`null_scores` when

`store_null = TRUE`), PC scores, and PCA objects, all of which interface directly with

downstream visualization functions**.**

Visualization, diagnostics, and sensitivity analysis

SurvMarker provides companion functions for diagnosing PCA structure, visualizing

survival-associated signal, and assessing feature stability. Functions such as

`plot_scree()` and `plot_cumvar()` summarize variance explained and cumulative

variance across PCs, supporting transparent and reproducible PC selection (Figure 1A-

B). Survival-associated latent structure can be visualized using `plot_pc12()` and

`plot_top2_survival_pcs()`, which display PC scores colored by clinical or

molecular annotations (Figure 1C-D).

Feature-level inference is further supported by `plot_null_vs_observed()`, which

contrasts observed feature score with its empirical null distribution. Significant features

exhibit scores in the extreme tails of the null distribution (Figure 1E), whereas non-

significant features show close agreement with the null (Figure 1F). All visualizations

support flexible annotation and color mapping, allowing users to tailor graphical outputs

while maintaining consistent representation across plots.

To evaluate robustness to PC choice, SurvMarker supports sensitivity analyses via

`run_survival_pca_multi_pc()`, which applies the scoring framework across a

user-specified grid of PC counts and returns the resulting feature sets. Feature overlap

and   stability   can   be   visualized   using   `plot_venn()`(Figure   1G),   and

`plot_feature_set_tradeoff()` summarizes the relationship between cumulative

variance explained and feature set size (Figure 1H). In the example dataset, the number

of selected genes decreases as more PCs are included, reflecting a strengthening

empirical null model and increasingly stringent calibration of feature scores. Features

retained under larger PC sets therefore represent robust contributors to survival-

associated latent structure.

Fig 1. Survival-associated PCA-based feature scoring and visualization framework implemented in SurvMarker. (A) Scree plot showing the proportion of variance explained by each principal component (PC). (B) Cumulative variance explained across PCs. (C) Scatter plot of PC1 versus PC2. (D) Scatter plot of the top two survival-associated PCs. (E–F) Feature-specific empirical null distributions of the weighted score for a prognostically significant gene (HMGA2) and a non-significant gene (KAT), respectively. (G) Overlap of selected features across multiple PC thresholds. n denotes the number of features selected at different thresholds. (H) Trade-off between feature set size and cumulative variance explained as the number of

Comparison with fixed-threshold selection

To demonstrate the practical advantages of the proposed framework, we applied SurvMarker to gene expression profiles from the TCGA-LAML cohort (dbGaP accession: phs000178) and evaluated performance using the previously defined 19-gene and 16-miRNA prognostic panels. Unlike the earlier fixed per-PC selection strategy, SurvMarker integrates information across all survival-associated PCs through a unified, statistically calibrated feature score.

Supplementary Figure 2 illustrates that SurvMarker produces a more compact and stable feature sets that is substantially less sensitive to the number of PCs considered. Across Top10, Top20, Top30, and Top50 PC settings, 11 of the 19 prognostic genes and 12 of the 16 prognostic miRNAs are consistently retained, defining a robust core set. Additional genes are incorporated gradually as PC count increases, reflecting progressive refinement rather than abrupt changes driven by analysis choices. In contrast, the fixed-threshold approach yields gene sets whose size increases rapidly with the number of PCs, complicating biological interpretation and limiting reproducibility.

Together, these results demonstrate that SurvMarker improves parsimony, stability, and robustness in feature selection while preserving prognostic signal. By unifying survival analysis, PCA-based feature scoring, empirical null inference, and diagnostic visualization into a single, coherent workflow, SurvMarker provides a practical and reproducible solution for biomarker discovery in high-dimensional survival studies. The package is fully documented with a strong emphasis on transparency, reproducibility,

and ease of use. Sensible default settings enable rapid application to new datasets,

while flexible user options allow fine-tuning of PC selection, FDR thresholds, covariate

adjustment, and visualization preferences. A comprehensive reference manual detailing

all functions, arguments, defaults, and plotting options is provided in the Supplementary

Material, ensuring that SurvMarker can be readily adapted to diverse high-dimensional

datasets and facilitating the robust translation of transcriptomic signals into clinically

interpretable prognostic features.

Acknowledgements

SurvMarker was developed by building on the extensive R ecosystem for statistical

modeling and visualization. Core functionality relies on `prcomp` (R Core Team, 2024) for

principal component analysis, the `survival` (Therneau, 2024) package for Cox

proportional hazards modeling, and widely used visualization tools including `ggplot2`

(Wickham, 2016), and `VennDiagram` (Chen et al., 2011) for overlap and stability

visualizations. We thank Drs. Timothy J. Ley and Christopher A. Miller (Washington

University); Richard Corbett, and Drs. Emilia Lim and Marco Marra (University of British

Columbia) for their invaluable assistance in acquiring the gene and miRNA datasets.

We thank the broader open-source R community for maintaining the foundational

packages that made this work possible.

Funding information

This work was supported, in part, by Institutional Research Grant IRG #22-151-37-IRG

from the American Cancer Society and by the Medical College of Wisconsin (MCW)

Cancer Center.

Conflict of Interest: None declared.

References

Pollen, A. A., *et al.* (2014) Low-coverage single-cell mRNA sequencing reveals cellular

heterogeneity and activated signaling pathways in developing cerebral cortex.

Nat Biotechnol. 32(10),1053–1058.

Gammune, D. H., Bui, D., and Gu, T. (2025) Discovery of miRNA:RNA biomarkers for

risk stratification in acute myeloid leukemia with multi-cohort validation. *bioRxiv*,

2025.11.26.690852.

Bair, E., Hastie, T., Paul, D., and Tibshirani, R. (2006) Prediction by supervised principal

components. *Journal of the American Statistical Association*, 101(473), 119–137.

R Core Team (2024). R: A Language and Environment for Statistical Computing. R

Foundation for Statistical Computing, Vienna, Austria.

Therneau T (2024). *A Package for Survival Analysis in R*. R package version 3.8-

3, https://CRAN.R-project.org/package=survival.

Wickham H (2016). *ggplot2: Elegant Graphics for Data Analysis*. Springer-Verlag New

York. ISBN 978-3-319-24277-4, https://ggplot2.tidyverse.org.

Chen, H. and Boutros, P. C. (2011) VennDiagram: a package for the generation of highly

customizable Venn and Euler diagrams in R. *BMC Bioinformatics*, 12, 35.