resolveS: An ultra-fast, memory-efficient and reference-free tool for RNA-seq
Strandedness Detection

Xi Long[1,2], Ting Zhao[2,] *, Dalang Yu[1,] *
1. Hangzhou Institute for Advanced Study, University of Chinese Academy of Sciences
2. Zhejiang Provincial Key Laboratory of Crop Genetic Resources, Institute of Crop
Science, Plant Precision Breeding Academy, College of Agriculture and
Biotechnology, Zhejiang University, Hangzhou, China

* Correspondence to: Dalang Yu (yudalang@ucas.edu.cn) and Ting Zhao
(0618041@zju.edu.cn)

Abstract

Public sequencing data repositories, such as the European Nucleotide Archive and
Sequence Read Archive are vital resources for biological discovery, however their
associated metadata often lacks essential experimental details, specifically the strand
specificity (strandedness) of RNA-sequencing data. Accurate determination of
strandedness is critical for downstream analysis, yet existing tools are often limited by
computational inefficiency, complex workflows, or a reliance on high-quality, species-
specific reference genomes and gene annotations. To address these limitations, we
developed resolveS, a rapid, resource-efficient and user-friendly tool designed to detect
RNA-sequencing strandedness without requiring organism-specific genomic resources.
By leveraging the evolutionary conservation of ribosomal RNA combined with a robust
statistical framework, resolveS eliminates the dependency on reference genomes.
Benchmarking demonstrates that resolveS outperforms existing methods in both speed
and efficiency, processing samples in under 10 seconds with a minimal memory footprint
(<0.5 GB). Furthermore, to enhance reproducibility and facilitate seamless integration
into bioinformatics pipelines, we provide ready-to-use Singularity and Apptainer images
alongside a portable executable version.

Keywords: RNA-Sequencing; Strandedness; Quality control; Non-model Organisms

Introduction

High-throughput RNA sequencing (RNA-seq) has revolutionized our understanding of transcriptomes, enabling precise quantification of gene expression, alternative splicing, and novel transcript discovery (Conesa, et al., 2016; Gondane and Itkonen, 2023; Hong, et al., 2020; Sahraeian, et al., 2017; Stark, et al., 2019). Modern RNA-seq protocols frequently employ strand-specific library preparation (Figure 1A), a capability essential for distinguishing transcripts originating from overlapping genes encoded on opposite strands. The overlapping genes compose approximately a quarter of human protein-coding genes and are widespread in compact genomes (Chen, et al., 2019). Incorrect specification of the strandedness parameter in downstream analysis tools (Figure 1B), such as featureCounts (Liao, et al., 2014) or Trinity (Haas, et al., 2013), can severely bias analytical results. Despite the importance of this this parameter, it is frequently omitted from the metadata in public repositories, such as the European Nucleotide Archive and Sequence Read Archive, and is often absent from corresponding publications. Notably, a systematic investigation found that approximately 44% of associated studies failed to explicitly report the library preparation method(Signal and Kahlke, 2022).

Existing tools attempt to address this demand but face significant limitations. For instance. RSeQC's infer_experiment.py requires a genome-aligned BAM file and genome annotation file recodes the gene information with bed format (Wang, et al., 2012). Similarly, how_are_we_stranded_here (Signal and Kahlke, 2022) improves speed by using pseudoalignment on a subset of reads to generate a genome-sorted BAM file before running infer_experiment.py. However, a fundamental limitation of these methods is their reliance on species-specific reference genomes and GTF annotation files. This dependence poses a significant challenge for studies involving newly sequenced or non-model organisms where high-quality genomic resources are unavailable. It is worthy that there is complex pipeline to address this problem, one can use the Trinity (Haas, et al., 2013) to assemble the transcriptome data first (with guess of 3 types of the strandedness Figure 1A) and then estimate the annotation file via the TransDecoder (https://github.com/TransDecoder/TransDecoder) and convert the gff3 to bed file by BEDOPS (Neph, et al., 2012), next align the fastq to the assembly to get the bam file, finally employ the RSeQC to infer the strandedness by input the gff3 and bed. The solution takes user to install plenty of software and operates several procedures which hinds the large-scale application. Furthermore, the accuracy and validity of this ad hoc strategy have not been rigorously established.

In this work, we developed resolveS, an ultra-fast, reference-agnostic solution. The principal novelty of resolveS lies in its independence of species-specific genomics annotations, instead, it utilizes a compact, curated database of universal rRNA sequences as a mapping target. This design leverages the evolutionary conservation of ribosomal

RNA (rRNA) across the tree of life and the abundant known knowledge making them an ideal universal proxy. Furthermore, we address a common statistical pitfall in NGS data analysis—the sensitivity of P-values to large sample sizes—by implementing a progressive detection strategy that evaluates rRNA targets based on mapping quality. In addition to reporting the strandedness type, resolveS also provides confidence estimates under various complex scenarios. By combination this universal rRNA database with the optimized, stop-on-max-reads functionality of Bowtie2<Langmead, 2012 #16}, resolveS achieve remarkable speed and resource efficiency, establishing it as an ideal tool for universal strandedness-detection.

Materials and methods

The test datasets

Data sets with ground truth from the animal and plants(Shi, et al., 2025) are tested. The animal cell line data is from our own unpublished and others from Naphade (Naphade, et al., 2022), Sigurgeirsson (Sigurgeirsson, et al., 2014). Large scale benchmarking data from Signal(Signal and Kahlke, 2022) supplement collection. Five samples from the Signal et al. are removed, according to careful evaluation.

The universal rRNA reference strategy

We employed a lightweight, universal reference database that derived from the SortMeRNA database (Kopylova, et al., 2012). which includes representative rRNA sequences. There are three versions of the rRNA files, we choose the default version as default reference based on our empirical experiencing and practical comparisons, while a high-sensitivity version is provided as an alternative.
Details indexing instructions are available at https://github.com/yudalang3/resolveS/tree/main/docs.

Aligner choice and subsampling optimization strategy

Speed and memory efficiency were primary design goals. We compared established DNA aligners, form matured BWA(0.7.19-r1273) (Li and Durbin, 2009), Bowtie2 (2.5.4) (Langmead and Salzberg, 2012) to the fresh LexiMap(v0.8.0) (Shen, et al., 2025) and found Bowtie2 is best for our assignment because it significantly outperforms BWA and LexiMap for this specific task:

Speed Optimization: Bowtie2 supports the -u parameter to stop alignment after a specified maximum number of reads (max_reads), dramatically accelerating the inference process. BWA lacks this feature. The LexiMap is not pretty slow for mapping the fastq millons numbers of reads.

Resource Efficiency: Bowtie2's index files are smaller (214 MB vs. 521 MB for BWA), and the original FASTA library file is not required after indexing, reducing storage overhead. Furthermore, testing showed Bowtie2 requires half the memory and runs 2-3 times faster than BWA for alignment.

125 After evaluated such mainstream aligners, we selected Bowtie2 for its outstanding
126 performance of speed and low memory footprint.
127
Unlike tools that map the entire FASTQ file, resolveS employ a cheap head subsampling
strategy. We utilize the -u (stop after N reads) capability of Bowtie2 to map only the first
sufficient batch of reads (default: 1,000,000 reads) to the rRNA index. This reduces the
runtime complexity from $O(N)$ (where N is total library size) to $O(1)$ (constant time),
allowing the tool to return results in seconds regardless of whether the input file is 100
MB or 100 GB.
134

Statistical Framework for Strandedness Inference

135
136
137 Besides the commonly used Chi-square test. Several simple but powerful effect size
138 metrics ("Fwd_Ratio", "F2R_Ratio", "Rel_Diff", "Cohens_h", "Cramers_V",
139 "Bayes_Factor", "Epsilon", "Hellinger", "Entropy") were implemented to provide robust
140 inference of the strandedness, see
141 https://github.com/yudalang3/resolveS/blob/main/check_strand.py for details.
142
143 The final metric we choose is the signed symmetric relative difference, short as Ref_Diff.
144 We choose the empirical value abs (Ref_Diff) = 0.6 as the cutoff for the stranded-
145 specificity and the number of samples for the "insufficient-data" to be less than 18. The
146 rationality is validated by the test datasets.
147

The strandedeness detection level

148
149
150 Earlier versions inferred strandness from global fragment counts, whereas the current
151 implementation determines strandness via per☐chromosome voting among the most
152 covered chromosomes (with adaptive MAPQ filtering). The "resolveS_fast" version still
153 employs this approach.
154
Strandedness detection uses a progressive majority vote across the top chromosomes
ranked by valid read counts, but it is run under an adaptive MAPQ filter. The algorithm
first evaluates reads with MAPQ ≥ 20; if the detection level is all-insufficient-fallback, it
retries with lower thresholds (MAPQ 10, then 3, then 0) until sufficient evidence is found
or all levels fail. For each run, chromosomes with too few reads are labeled "insufficient-
data" and excluded from voting. The majority check proceeds 3/3 → 4/5 → 6/7 → 7/8, and
the first passing level is reported (e.g., 3of3, 4of5, 6of7, 7of8). If no majority is reached, a
fallback level is recorded and a global forward/reverse ratio is calculated to determine the
final inference.
164
165

A. The strand-specific sequencing and the derived consequence

B. Main application of resolveS

Precise RNA-seq quantification

Transcriptome assembly

Strand-specific data mining

C. Strand-specificity assessment framework

Step 1 · rRNA reference
Download conserved rRNA database
Use balanced default database

Step 2 · Read alignment
Choose fast short-read aligner
BWA or Bowtie2 (Bowtie2 preferred)

Step 3 · Strand counts
Select primary alignments to rRNA reference
Count forward-strand and reverse-strand reads

Step 4 · Statistical metrics
Compute chi-square test and effect sizes:
Cohen's h, Cramer's V, relative_difference,
ratio change

Step 5 · Library classification
Determine strand specificity of the library
By a progressive majority vote alone quality

D. Accuracy

167
168
Figure 1: Accuracy, robust framework and application of resolveS
A. The principle of the resolveS. The strandness of the RNA is defined by the RNA molecule and the derived
consequences is intuitional for the "fr-firststrand" type is R2 sequence same as the original RNA and the "fr-secondstrand"
is vice versa. For the authenticity, a small fraction of the RNA may contain the Nature Antisense transcripts.
B. Overview of the main application areas of resloveS.
C. The framework summary: First, A conservative, universal rRNA database with default version
(https://github.com/sortmerna/sortmerna/releases) is downloaded and indexed. Next, reads alignment with the curated
maximum size sampling using Bowtie2. Third, only primary alignments are retained, and counts for forward and reverse
strands are recorded. Then, Strandedness Inference: Several statistics are computed. We put forward several non-sample
size aware statistics as indices to estimate the strandedness. Finally, Library classification by the statistics.
D. Accuracy and robustness of the resolveS. The representative statistics (Relative difference) have the maximum range
to distinguish the strandedness. [∗RM = enriched with RiboMinus, RZ = enriched with RiboZero, SS = strand specific, NS
= non-stranded. A431, U251 and U2OS denote different cell lines] (Sigurgeirsson, et al., 2014). Additional statistical
distributions and full details are provided in the supplements.
183

Results

An accuracy- and robustness-oriented framework for strandedness detection

The resolveS workflow is streamlined as a dedicated pipeline for maximum efficiency (Figure 1C, Table 1). After tests several aligners, we found the Bowtie2 is best suit for our purpose (Method section2). We tested the rRNA database version provided by the SortMeRNA, the default version is almost no difference with the sensitive version. The input RNA volume and RNA enrichment experiment methods even the RiboZero protocol is not confounding the accuracy (Figure 1D). Although RNA-seq library preparation protocols, such as poly(A) enrichment or Ribo-Zero depletion, aim to remove rRNA, these methods are rarely 100% efficient. resolveS exploit this "contamination" as a signal.

A common challenge in analyzing NGS count data is the "P-value fallacy", where trivial deviations become statistically significant simply due to the massive number of reads (counts). A standard Chi-square test might reject the null hypothesis of uniformity even when the deviation is biologically irrelevant (e.g., 50.1% vs 49.9%). To overcome this, we implemented robust, sample-size-independent statistical metrics to ensure reliable inference. All 9 metrices (Methods section 4) are distinguishable to the strand specificity (Supplement Figure1-3).

The relative difference index has the greatest range to distinguish strandedness (Figure 1D). Also, for the simplicity, we reduce reversal metrices to only the relative difference. Besides give final strandedness, we also provide the confident level of the inference. The most reliable level is the "MAPQ-20" and "3of3" means filter the mapping quality by the score 20 and the top 3 rRNA sequence concordantly agree to be one type. While the worst level is the "MAPQ-0" with "multi-of8-fallback", which means although setting the mapping quality to lowest value, the top 8 rRNA transcripts still give over 2 candidates.

To validate accuracy, we tested resolveS on a ground-truth dataset where library preparation methods were known. Without require any data clean approach, resolveS achieved 98.81% (249/252) concordance with the metadata labels for both unstranded and stranded libraries. And in the failed 3 samples, resolveS correctly gives the clues of the fallback detection level. When compared with existing approaches, resolveS demonstrates superior convenience and efficiency (Table 2).

Table 1 The summary of the running speed and memory usage of the resolveS_fast

Input type	Approach	Threads number	Maximum align reads	Time cost (s)	Memory cost (GiB)
Batch_gzip_fastq_5	Apptainer_image	15	1000000	18.7733(0.3099)	0.3240(0.0017)
Batch_gzip_fastq_5	Apptainer_image	15	4000000	68.0333(4.3625)	0.3277(0.0025)
Batch_gzip_fastq_5	Apptainer_image	8	1000000	21.1567(0.4267)	0.2813(0.0021)
Batch_gzip_fastq_5	Apptainer_image	8	4000000	75.1567(2.7356)	0.2833(0.0006)

Batch_gzip_fastq_5	Bash_script	15	1000000	21.9400(0.5011)	0.3280(0.0017)
Batch_gzip_fastq_5	Bash_script	15	4000000	79.6300(2.5363)	0.3310(0.0000)
Batch_gzip_fastq_5	Bash_script	8	1000000	19.8900(0.5862)	0.2833(0.0021)
Batch_gzip_fastq_5	Bash_script	8	4000000	72.6667(4.3824)	0.2857(0.0006)
Batch_gzip_fastq_5	Singularity_image	15	1000000	19.9367(0.1464)	0.3267(0.0012)
Batch_gzip_fastq_5	Singularity_image	15	4000000	65.6567(0.4693)	0.3293(0.0006)
Batch_gzip_fastq_5	Singularity_image	8	1000000	21.7067(0.5609)	0.2800(0.0017)
Batch_gzip_fastq_5	Singularity_image	8	4000000	70.7333(0.9570)	0.2857(0.0029)
Single_gzip_fastq	Apptainer_image	15	1000000	3.6867(0.0252)	0.3227(0.0006)
Single_gzip_fastq	Apptainer_image	15	4000000	10.8867(0.2371)	0.3250(0.0017)
Single_gzip_fastq	Apptainer_image	8	1000000	4.1033(0.1159)	0.2783(0.0006)
Single_gzip_fastq	Apptainer_image	8	4000000	11.7100(0.2706)	0.2817(0.0023)
Single_gzip_fastq	Bash_script	15	1000000	2.9900(0.0300)	0.3243(0.0006)
Single_gzip_fastq	Bash_script	15	4000000	9.7700(0.6791)	0.3283(0.0029)
Single_gzip_fastq	Bash_script	8	1000000	2.9767(0.0231)	0.2810(0.0000)
Single_gzip_fastq	Bash_script	8	4000000	10.7567(0.6309)	0.2850(0.0000)
Single_gzip_fastq	Singularity_image	15	1000000	3.6133(0.1041)	0.3240(0.0026)
Single_gzip_fastq	Singularity_image	15	4000000	11.5267(0.8363)	0.3283(0.0051)
Single_gzip_fastq	Singularity_image	8	1000000	3.8433(0.0379)	0.2807(0.0023)
Single_gzip_fastq	Singularity_image	8	4000000	11.5700(0.1609)	0.2790(0.0000)

225 The CPU is 13th Gen Intel(R) Core(TM) i7-13700 and storage is WD Green SN350 1TB
226 The output style is Mean (Standard Deviation)
227
228

229 ## Installation and documentation

230 All source codes publicly available without restriction at:

231 https://github.com/yudalang3/resolveS. Portable version and container image files can

232 be download directly from the Release page.

233
234
235 Table 2 Comparison with Existing approaches to infer strandedness

Software	Reference Requirement	Primary Alignment Target	Speed/Efficiency	Installation friendliness	Key Advantage
RSeQC (infer_experiment.py)	Requires Reference Genome and annotations	Genome/Transcriptome	Slow (requires full alignment/BAM)	Conda/mamba and pip	Established method.
how_are_we_stranded_here	Requires Reference Transcriptome/GTF	Transcriptome (Pseudoalignment via Kallisto)	Fast (seconds/sample)	Conda/mamba and pip	Fast for organisms with high-quality reference.

Trinity/Tran sDecoder Workflow	No (but requires massive compute)	De novo assembly	Extremely Slow/High Resource	Conda/mam ba and extra configuratio n	For discovery in totally de novo context.
resolveS (Ours)	No Reference Genome Required	Universal rRNA Database	Ultra-Fast (< 10s) and Low Memory (< 0.5GiB)	Conda/mam ba and one-stop container images	Universal applicability across nearly all species, including non-model ones.

Conclusion and future work

In this work, we present resolveS, an open-source, efficient and user-friendly tool for rapid determining RNA-seq library strandedness and give the detection confident level. FASTQ files from any processing stage (raw or trimmed) are supported, however, we recommend directly using the raw data for simplicity. Its capacity to operate independently of species-specific genomics annotation extends its utility beyond model organisms, ensuring that researchers analyzing non-model or poorly annotated species can still reliably ascertain this critical experimental parameter. We strongly recommend incorporating resolveS into upstream quality control pipelines to ensure the accuracy and reproducibility of downstream quantitative and assembly analyses.

One limitation of current approach is the theoretical dependence on residual rRNA. However, in our extensive testing across samples, we have not encountered datasets with zero rRNA alignments, although ambiguous fallback cases are occasionally observed, most likely due to low-level contamination from other samples. Future work will focus on accelerating the sequencing mapping speed to reduce the total running time. Specifically, we aim to develop a customized mapping strategy to optimize this task.

Author contributions

Dalang Yu (Conceptualization [lead], Data curation [lead], Formal analysis [lead], Funding acquisition [lead], Investigation [lead], Methodology [lead], Project administration [lead],
Resources [lead], Software [lead], Supervision [lead], Validation [lead], Visualization [lead], Writing—original draft [lead], Writing—review & editing [lead])

Xi Long (Data curation [lead], Formal analysis [lead], Funding acquisition [lead], Investigation [lead], Methodology [lead], Project administration [lead],
Resources [lead], Software [lead], Supervision [lead], Validation [lead], Visualization [lead], Writing—original draft [lead], Writing—review & editing [lead])

Ting Zhao (Conceptualization [lead], Supervision [lead], Validation [lead], Visualization [lead], Writing—review & editing [lead])

Conflict of interest: None declared.

Acknowledgement

I thank for the kindness of the advisers from Professor Lin Li for the application of the RNA-seq analysis in the signaling transduction.

Supplement Materials:

See supplement zip files for all tests results and the statics distributions.

Funding

This work was supported by Supported by the Youth Fund of the National Natural Science Foundation of China (No. 32400511).

References

Chen, C.H., Pan, C.Y. and Lin, W.C. Overlapping protein-coding genes in human genome and their coincidental expression in tissues. *Sci Rep* 2019;9(1):13377.

Conesa, A.*, et al.* A survey of best practices for RNA-seq data analysis. *Genome Biology* 2016;17(1).

Gondane, A. and Itkonen, H.M. Revealing the History and Mystery of RNA-Seq. *Current Issues in Molecular Biology* 2023;45(3):1860-1874.

Haas, B.J.*, et al.* De novo transcript sequence reconstruction from RNA-seq using the Trinity platform for reference generation and analysis. *Nat Protoc* 2013;8(8):1494-1512.

Hong, M.*, et al.* RNA sequencing: new technologies and applications in cancer research. *Journal of Hematology & Oncology* 2020;13(1).

Kopylova, E., Noe, L. and Touzet, H. SortMeRNA: fast and accurate filtering of ribosomal RNAs in metatranscriptomic data. *Bioinformatics* 2012;28(24):3211-3217.

Langmead, B. and Salzberg, S.L. Fast gapped-read alignment with Bowtie 2. *Nat Methods* 2012;9(4):357-359.

Li, H. and Durbin, R. Fast and accurate short read alignment with Burrows-Wheeler transform. *Bioinformatics* 2009;25(14):1754-1760.

Liao, Y., Smyth, G.K. and Shi, W. featureCounts: an efficient general purpose program for assigning sequence reads to genomic features. *Bioinformatics* 2014;30(7):923-930.

Naphade, S.*, et al.* Systematic comparative analysis of strand-specific RNA-seq library preparation methods for low input samples. *Scientific Reports* 2022;12(1).

Neph, S.*, et al.* BEDOPS: high-performance genomic feature operations. *Bioinformatics* 2012;28(14):1919-1920.

Sahraeian, S.M.E.*, et al.* Gaining comprehensive biological insight into the transcriptome by performing a broad-spectrum RNA-seq analysis. *Nature Communications* 2017;8(1).

Shen, W., Lees, J.A. and Iqbal, Z. Efficient sequence alignment against millions of prokaryotic genomes with LexicMap. *Nat Biotechnol* 2025.

Shi, W.*, et al.* Nanopore sequencing and multiomics reveal predictable non-coding RNA activation in DNA methylation deficient Arabidopsis thaliana. *Commun Biol* 2025.

Signal, B. and Kahlke, T. how_are_we_stranded_here: quick determination of RNA-Seq strandedness. *BMC Bioinformatics* 2022;23(1).

Sigurgeirsson, B., Emanuelsson, O. and Lundeberg, J. Analysis of stranded information using an automated procedure for strand specific RNA sequencing. *BMC Genomics* 2014;15(1):631.

Stark, R., Grzelak, M. and Hadfield, J. RNA sequencing: the teenage years. *Nature Reviews Genetics* 2019;20(11):631-656.

Wang, L., Wang, S. and Li, W. RSeQC: quality control of RNA-seq experiments. *Bioinformatics* 2012;28(16):2184-2185.