Searching the Druggable Genome using Large Language Models

Lars Schimmelpfennig[1], Matthew Cannon[2], Quentin Cody[3], Joshua McMichael[4], Adam C.

Coffman[1], Susanna Kiwala[1], Kilannin Krysiak[5], Alex H. Wagner[2,6†], Malachi Griffith[1,4,7†], Obi L.

Griffith[1,4,7†]

[1] Department of Medicine, Washington University School of Medicine, St. Louis, Missouri, USA

[2] Institute for Genomic Medicine (IGM), Nationwide Children's Hospital, Columbus, OH

[3] Independent Researcher, Philadelphia, PA, USA

[4] McDonnell Genome Institute, Washington University School of Medicine, St. Louis, Missouri,

USA

[5] Department of Pathology, Washington University School of Medicine, St. Louis, Missouri, USA

[6] Department of Pediatrics, The Ohio State University College of Medicine, Columbus, OH

[7] Siteman Cancer Center, Washington University School of Medicine, St. Louis, Missouri, USA

Correspondence:

[†]Obi L Griffith, PhD, Washington University School of Medicine, Room MCC10116, 4590

Childrens Pl, Saint Louis, MO 63110. Phone: (314) 747-9248. Email: obigriffith@wustl.edu

[†]Malachi Griffith, PhD, Washington University School of Medicine, Room MCC10115, 4590

Childrens Pl, Saint Louis, MO 63110. Phone: (314) 286-1274. Email: mgriffit@wustl.edu

[†]Alex Wagner, PhD, Nationwide Children's Hospital, Room WB3155, Research Building 3, 575

Children's Crossroad, Columbus, OH 43210. Phone: (614) 355-1645, Email:

Alex.Wagner@nationwidechildrens.org

ABSTRACT

Summary: The druggable genome encompasses the genes that are known or predicted to

interact with drugs. The Drug-Gene Interaction Database (DGIdb) provides an integrated resource

for discovering and contextualizing these interactions, supporting a broad range of research and

clinical applications. DGIdb is currently accessed through structured web interfaces and API calls,

requiring users to translate natural-language questions into database-specific query patterns. To

allow for the use of DGIdb through natural language, we developed the DGIdb Model Context

Protocol (MCP) server, which allows large language models (LLMs) access to up-to-date

information through the DGIdb API. We demonstrate that the MCP server greatly enhances an

LLM's ability to answer questions requiring accurate, up-to-date biomedical knowledge drawn

from structured external resources.

Availability and implementation: The DGIdb MCP server is detailed at

https://github.com/griffithlab/dgidb-mcp-server and includes instructions for accessing the server

through the Claude desktop app.

1. Introduction

Drug-gene interactions play a central role in precision medicine, as they help determine which treatments are likely to be effective for a given patient and which may lead to resistance or adverse effects. As large-scale molecular studies increasingly reveal large sets of genes associated with disease, researchers need tools that can connect these findings to potential therapeutic strategies. The Drug-Gene Interaction Database (DGIdb)[1–5] addresses this need by aggregating and harmonizing drug-gene interaction information from multiple sources, providing a centralized resource for assessing gene druggability and therapeutic relevance. DGIdb supports downstream research and clinical-informatics applications, including gene-drug linking for prioritized disease genes[6], exploratory hypothesis generation[7], drug repurposing[8], genomic gene-list annotation[9], and precision oncology workflows[10]. The value of searching a catalog of drug-gene interactions is well illustrated by the challenge of *FLT3-mutated Acute Myeloid Leukemia*. Although the FLT3 inhibitor *Gilteritinib* is initially effective, patients often develop resistance due to additional genetic changes that emerge during treatment.[11] In such settings, DGIdb could be used to identify drugs known or predicted to interact with genes implicated in resistance, supporting exploratory analyses and prioritization of alternative therapeutic candidates.

Despite DGIdb's utility, this process can be time-consuming in multistep analyses, such as studies of acquired drug resistance, where users must first identify resistance-associated genes, then perform separate queries for each gene, and finally manually combine and prioritize potentially large lists of interacting drugs. As a result, DGIdb is difficult to use directly within natural-language workflows and is largely inaccessible to large language models (LLMs), which cannot natively construct or execute these structured queries. At the same time, LLMs have emerged as promising tools for a wide range of biomedical applications, including literature summarization and clinical decision support, due to their ability to synthesize complex information and respond flexibly to natural-language questions.[12–16] However, LLMs rely on static internal knowledge, may generate inaccurate or unsupported statements, and cannot directly access

curated biomedical resources without additional infrastructure.[17] These limitations restrict their

reliability in settings where accuracy and traceability are essential.

To address these challenges, the Model Context Protocol (MCP) provides a standardized

way to connect LLMs to authoritative external data sources. MCP servers serve as a bridge

between the flexibility of LLMs and the precision of curated biomedical databases and have been

increasingly applied to biomedical domain APIs, databases, and literature search endpoints,

including variant-level knowledgebases via the CIViC MCP server.[18–20] The DGIdb MCP server

builds upon this framework, allowing LLMs and researchers to retrieve, interpret, and cite drug-

gene interaction information directly from the curated resources, making it easier to integrate

accurate interaction data into genome-wide analyses and therapeutic decision-making.

2. DGIdb MCP Server Description

The DGIdb MCP server is publicly available through Cloudflare. The server provides four

tools, each corresponding to predefined GraphQL queries for integration with LLMs. These tools

allow LLMs to retrieve drug information, gene information, and drug-gene interactions based on

either a supplied gene list or drug list. The drug information tool returns key attributes such as

FDA approval status, drug classifications including immunotherapy and antineoplastic drugs, and

additional characteristics such as drug class. The gene information tool provides DGIdb gene

category annotations, such as kinase, ligase, and nuclear receptor designations, along with other

attributes relevant to gene druggability. Together, these data sources supply structured and well-

curated information that supplements an LLM's understanding of the drug-gene interaction space.

When the LLM calls the corresponding interaction query with a supplied list of genes or drugs,

the server returns a ranked list of their known interactions. Each interaction includes an interaction

type and, when applicable, directionality (activating or inhibitory) which together describe the

mechanism of action and effect on biological activity. Every interaction is also linked to its

supporting evidence, which may come from a publication or a curated database. Interactions are

ranked primarily according to the FDA approval status of the associated drugs, and secondarily

according to the DGIdb interaction score, which was introduced in the DGIdb 4.0 release.[4] The

score combines evidence strength (number of supporting publications and curated sources) with

interaction specificity, calculated from the relative number of known partners for the drug and

gene compared to global averages. The final score prioritizes interactions that are both well

supported and more specific, and remains static within a data release. This ranking strategy

allows LLMs to prioritize clinically informative and well-supported interactions.

To accommodate spelling variations and alternate names, the MCP server normalizes

drug and gene inputs to the closest matching label recognized by DGIdb. Alias similarity is scored

using Dice's coefficient over bigrams, which requires limited memory making it ideal for Cloudflare

workers. The MCP server obtains drug and gene aliases from the VICC Normalization Services,

which provide a standardized set of identifiers and synonyms for use during the scoring

process.[21,22]

3. Example Use Cases

1. A user might ask, "Which FDA-approved drugs target the gene *KIT*, and what is the

supporting evidence?" In response, the LLM identifies the gene of interest and the user's intent,

then invokes the appropriate MCP tool. The MCP server normalizes the gene name and issues

the corresponding GraphQL query to the DGIdb API. It returns a ranked list of drugs that interact

with *KIT*, along with interaction metadata such as interaction score, interaction type and direction,

FDA-approval status, and supporting sources. Using this structured output, the LLM composes a

user-facing answer that includes relevant evidence and links to the cited publications. A more

complete list of use cases for the DGIdb MCP server are outlined in Supplementary Table 1.

2. A second example use case demonstrates the joint use of the CIViC MCP[20] and DGIdb

MCP servers for drug candidate selection (Figure 1). A user may ask, "What genes can cause

resistance to *Ibrutinib* in *Chronic Lymphocytic Leukemia*, and what alternative drugs can target

them?" The LLM identifies the relevant CIViC entities (Therapy, Disease, Clinical Significance)

and invokes the appropriate tool from the CIViC MCP server to retrieve variant evidence. The

CIViC MCP server issues a GraphQL query to the CIViC API, which returns structured Evidence

Items associated with *Ibrutinib* resistance in *CLL*. From these records, the LLM extracts *BTK* as

the primary gene implicated in resistance and composes a query to the DGIdb MCP server to

identify other drugs that interact with *BTK*. The server returns a ranked list of drug-gene

interactions, enabling the LLM to respond with the highest-priority drug candidates, including

Tirabrutinib, Acalabrutinib, and *Zanubrutinib*. Using the outputs from each MCP server, the LLM

returns an answer that cites relevant curated evidence and publications. Additional examples of

how the DGIdb and CIViC MCP servers can be used together are outlined in Supplementary

Table 2.

4. Benchmarking LLM Performance with DGIdb and CIViC MCP Servers

We developed a set of classification and information-retrieval tasks to measure how

effectively the MCP server enhances an LLM's ability to answer questions requiring accurate and

current biomedical knowledge. As a first task, we asked GPT-5 to label drugs according to three

DGIdb-derived attributes: FDA approval status, immunotherapy classification, and antineoplastic

classification (Supplementary Table 3). We selected 100 drug names using stratified sampling to

approximate a 50/50 balance of positive and negative examples for each label. Because relatively

few drugs in DGIdb are classified as immunotherapies, achieving a perfectly even split was not

possible. GPT-5 was prompted to return three comma-separated YES/NO values to facilitate

parsing (Supplementary Prompt 1). Across all labels, GPT-5 augmented with the DGIdb MCP

substantially outperformed GPT-5 alone achieving a macro weighted F1-score of 0.99 compared

to 0.75. GPT-5 without MCP struggled particularly with identifying immunotherapies, producing

many false negatives and yielding a recall of only 0.38.

Next, we compared how often GPT-5 would invoke the DGIdb MCP server when

requesting the same drug information without explicitly mentioning DGIdb (Supplementary

Prompt 2). The DGIdb MCP server was available to the model in the same configuration as the

previous task, but tool use was not explicitly instructed. GPT-5 did not use the DGIdb MCP server

for 55 out of the 100 drugs. Among cases where GPT-5 did not invoke the MCP server,

performance declined, particularly for immunotherapy and antineoplastic classification. Recall

dropped from 1.00 to 0.68 for immunotherapies and from 0.88 to 0.68 for antineoplastic drugs

(Supplementary Table 4). To understand when GPT-5 decided to use the MCP server, we

manually inspected a random subset of predictions. In these examples, the MCP server was

generally not invoked for widely used, FDA-approved therapeutics with unambiguous, commonly

referenced names (e.g. Tamoxifen), but was preferentially used for uncommon, structurally

complex molecules, or database-style identifiers (e.g. ODM-203), indicating that GPT-5

selectively employed the MCP server when additional disambiguation or external grounding was

likely required.

Lastly, we evaluated a task that used both the CIViC MCP and DGIdb MCP servers to

demonstrate the potential of LLM-assisted drug candidate selection, as outlined in Supplementary

Figure 1. To allow for direct evaluation of the intermediate gene list, this task utilized two prompts.

In the first step, GPT-5 was prompted to identify genes associated with resistance to a specified

therapy in a given disease using CIViC-derived information (Supplementary Prompt 3). In the

second step, we issued a separate prompt for each gene identified in the first step, asking GPT-

5 to list drugs that interact with that gene using DGIdb-derived information (Supplementary

Prompt 4). To keep runtime manageable, we limited the request to the top 20 interacting drugs

per gene, as full interaction lists for a single gene can exceed 500 entries. For this evaluation, we

randomly selected 50 disease-therapy combinations from CIViC evidence as starting points for

the drug-candidate identification process. GPT-5 was instructed to rank genes according to the

strength of their associated CIViC evidence. Genes were ordered first by Evidence Level, with

level A considered the strongest and level E the weakest, and then by Evidence Rating, prioritizing

higher ratings (5 to 1). Drugs were ranked primarily by FDA approval status and secondarily by

interaction score. Because the multihop task requires GPT-5 to return genes and drugs in a

prioritized order, we evaluate correctness using precision, recall, and F1, and we assess ranking

quality using normalized discounted cumulative gain (NDCG). NDCG is a common information

retrieval metric that measures how well the model ranks relevant items, giving greater weight to

items that appear earlier in the list. NDCG ranges from 0 to 1, with higher values indicating

rankings that more closely match the ideal ordering. GPT-5 augmented with the CIViC and DGIdb

MCP servers substantially outperformed GPT-5 alone on the drug-list task, improving F1 from

0.14 to 0.95 and NDCG from 0.19 to 0.93 (Supplementary Table 5).

5. Conclusion

We demonstrate that the DGIdb MCP server enables reliable, structured exploration of

drug-gene interactions by allowing an LLM to query a comprehensive, curated interaction

resource in response to natural-language questions. By grounding GPT-5 in DGIdb, this approach

supports accurate retrieval, ranking, and contextualization of interaction evidence, which is

particularly important for tasks such as identifying alternative therapeutic candidates and

interpreting resistance-associated genes.

We further show that LLMs can make effective use of multiple MCP servers

simultaneously. In a drug-candidate identification task for therapy resistance, GPT-5 successfully

combined variant-level evidence retrieved from the CIViC MCP server with drug-gene interaction

data from the DGIdb MCP server, demonstrating how MCP servers can be composed to support

multi-step biomedical reasoning workflows that require information from multiple sources.

Our evaluation also highlights an important practical consideration: GPT-5 did not

consistently invoke MCP servers unless the relevant biomedical resource is mentioned explicitly

in the prompt. When the source (e.g., "DGIdb") is named, GPT-5 reliably delegates retrieval to

the MCP server. When it is omitted, however, the model often defaults to its internal knowledge,

resulting in reduced accuracy, particularly for identifying immunotherapies. This finding

emphasizes the importance of prompt design in ensuring consistent MCP usage.

While the MCP framework has previously been applied to variant-level knowledge through

the CIViC MCP server[20], this work extends the paradigm to the drug-gene interaction domain and

illustrates how multiple MCP servers can be integrated to address more complex biomedical

questions. As future work, the development of standardized benchmarks for MCP-assisted

biomedical tasks, such as drug-gene interaction retrieval, variant interpretation, and cross-

knowledgebase reasoning, will be critical for enabling consistent evaluation and comparison of

MCP-enabled LLM systems.

Figure 1. Joint use of the CIViC MCP and DGIdb MCP servers for drug candidate selection with Claude. A user asks, "What genes can cause resistance to Ibrutinib in Chronic Lymphocytic Leukemia, and what alternative drugs can target them?" The LLM: (1) extracts the users intent

and relevant entities (Therapy, Disease, Significance), (2) composes a query to the CIViC MCP

server with the appropriate tool selection, (3) the CIViC MCP server queries the CIViC API and

returns Evidence Items, (4) the LLM parses the MCP response and identifies the BTK as an

ibrutinib resistance gene, (5) the LLM composes a new query to the DGIdb MCP server to identify

other drugs that interact with BTK, (6) the DGIdb MCP server queries the DGIdb API and returns

drug interactions for BTK, (7) the LLM composes a summary.

CONFLICT OF INTEREST

None declared.

FUNDING

This work was supported by the National Institutes of Health (NIH), including the National Cancer

Institute (NCI) under award numbers U24CA305456, U24CA237719, U24CA258115, and

U24CA275783, and the National Human Genome Research Institute (NHGRI) under award

number R35HG011949.

REFERENCES

1. Griffith M, Griffith OL, Coffman AC, et al. DGIdb: mining the druggable genome. *Nat*

Methods. 2013;10(12):1209-1210. doi:10.1038/nmeth.2689

2. Wagner AH, Coffman AC, Ainscough BJ, et al. DGIdb 2.0: mining clinically relevant drug-

gene interactions. *Nucleic Acids Res*. 2016;44(D1):D1036-1044. doi:10.1093/nar/gkv1165

3. Cotto KC, Wagner AH, Feng YY, et al. DGIdb 3.0: a redesign and expansion of the drug-

gene interaction database. *Nucleic Acids Res*. 2018;46(D1):D1068-D1073.

doi:10.1093/nar/gkx1143

4.   Freshour SL, Kiwala S, Cotto KC, et al. Integration of the Drug-Gene Interaction Database

(DGIdb 4.0) with open crowdsource efforts. *Nucleic Acids Res*. 2021;49(D1):D1144-D1151.

doi:10.1093/nar/gkaa1084

5.   Cannon M, Stevenson J, Stahl K, et al. DGIdb 5.0: rebuilding the drug-gene interaction

database for precision medicine and drug discovery platforms. *Nucleic Acids Res*.

2024;52(D1):D1227-D1235. doi:10.1093/nar/gkad1040

6.   Pranata R, Ratnasari N, Bayupurnama P, et al. Genomic analysis unlocks the potential of

denosumab as a targeted therapy for Crohn's disease. *Sci Rep*. 2025;15(1):44713.

doi:10.1038/s41598-025-28395-7

7.   Gupta S, Srivastava P, Daniel R, et al. Germline activating sequence variations in

RASopathy spectrum genes: genotype–phenotype correlation in a North Indian cohort. *Front*

Genet. 2025;16. doi:10.3389/fgene.2025.1677143

8.   Torricelli F, Sauta E, Manicardi V, et al. An Innovative Drug Repurposing Approach to

Restrain   Endometrial   Cancer   Metastatization.   *Cells*.   2023;12(5):794.

doi:10.3390/cells12050794

9.   Lamisa AB, Ahammad I, Bhattacharjee A, et al. A meta-analysis of bulk RNA-seq datasets

identifies potential biomarkers and repurposable therapeutics against Alzheimer's disease. *Sci*

Rep. 2024;14(1):24717. doi:10.1038/s41598-024-75431-z

10.   Cha S, Lee J, Shin JY, et al. Clinical application of genomic profiling to find druggable

targets for adolescent and young adult (AYA) cancer patients with metastasis. *BMC Cancer*.

2016;16:170. doi:10.1186/s12885-016-2209-1

11.   McMahon CM, Ferng T, Canaani J, et al. Clonal Selection with RAS Pathway Activation

Mediates Secondary Clinical Resistance to Selective FLT3 Inhibition in Acute Myeloid

Leukemia. *Cancer Discov*. 2019;9(8):1050-1063. doi:10.1158/2159-8290.CD-18-1453

12.   Wang Z, Cao L, Danek B, Jin Q, Lu Z, Sun J. Accelerating clinical evidence synthesis with

large language models. *Npj Digit Med*. 2025;8(1):509. doi:10.1038/s41746-025-01840-7

13. Chen Q, Hu Y, Peng X, et al. Benchmarking large language models for biomedical natural

language processing applications and recommendations. *Nat Commun*. 2025;16:3280.

doi:10.1038/s41467-025-56989-2

14. Williams CYK, Miao BY, Kornblith AE, Butte AJ. Evaluating the use of large language

models to provide clinical recommendations in the Emergency Department. *Nat Commun*.

2024;15(1):8236. doi:10.1038/s41467-024-52415-1

15. Hager P, Jungmann F, Holland R, et al. Evaluation and mitigation of the limitations of large

language models in clinical decision-making. *Nat Med*. 2024;30(9):2613-2622.

doi:10.1038/s41591-024-03097-1

16. Li Y, Zhao J, Li M, et al. RefAI: a GPT-powered retrieval-augmented generative tool for

biomedical literature recommendation and summarization. *J Am Med Inform Assoc JAMIA*.

2024;31(9):2030-2039. doi:10.1093/jamia/ocae129

17. Bhattacharyya M, Miller VM, Bhattacharyya D, Miller LE. High Rates of Fabricated and

Inaccurate References in ChatGPT-Generated Medical Content. *Cureus*. 2023;15(5):e39238.

doi:10.7759/cureus.39238

18. Ding P, Brettin T, Stevens R. BioR5: A Three-Layer Architecture for Biological Reasoning

in Scientific AI. In: *Proceedings of the SC '25 Workshops of the International Conference for*

High Performance Computing, Networking, Storage and Analysis. SC Workshops '25.

Association for Computing Machinery; 2025:594-601. doi:10.1145/3731599.3767400

19. Türei D, Schaul J, Palacio-Escat N, et al. OmniPath: integrated knowledgebase for multi-

omics analysis. *Nucleic Acids Res*. Published online November 18, 2025:gkaf1126.

doi:10.1093/nar/gkaf1126

20. Schimmelpfennig L, Cody Q, McMichael J, et al. CIViC MCP: Integrating Large Language

Models with the Clinical Interpretations of Variants in Cancer. *bioRxiv*. Preprint posted online

October 16, 2025:2025.10.13.682185. doi:10.1101/2025.10.13.682185

279 21. Cannon M, Stevenson J, Kuzma K, et al. Normalization of drug and therapeutic concepts

280 with Thera-Py. *JAMIA Open*. 2023;6(4):ooad093. doi:10.1093/jamiaopen/ooad093

281 22. Kuzma K, Stevenson J, Wagner A. VICC Gene Normalization Service. Published online

282 July 21, 2025. doi:10.5281/zenodo.16272753