8   **Hierarchical Reconfiguration of Neurocognitive Task Set Representations Mediates**

9   **Cognitive Flexibility**

11   Stephanie C. Leach[1] [*], Xitong Chen[1], and Kai Hwang[1,2]

13   [1] Psychological and Brain Sciences, The University of Iowa, Iowa City, IA.

14   [2] Cognitive Control Collaborative (CCC).

16   * Corresponding Author

17   E-mail: stephanie-leach@uiowa.edu

41 pages

6 figures

250 words abstract

693 words introduction

1530 words discussion

Abstract
25
Cognitive control organizes contexts, stimuli, and actions into hierarchically structured

representations that support flexible, goal-directed behavior. This organization allows

appropriate actions to be selected in response to changing demands, contexts, and sensory inputs.

Critically, different hierarchical levels place unequal demands on flexibility: sensory–motor

plans must be updated rapidly to enable behavioral flexibility, whereas higher-level contextual

goals are typically updated less frequently. A behavioral consequence of managing these

demands is the task switch cost, the performance penalty observed when task representations are

reconfigured across trials. Here, we investigated the behavioral and neural sources of switch

costs using a hierarchical control task that dissociates context reconfiguration from subordinate

rule switching. Functional MRI and behavioral data were collected from healthy human

participants (both male and female). Behaviorally, subordinate rule switches were faster than

context switches but were more strongly influenced by task-irrelevant perceptual changes,

whereas context switches were relatively insensitive to such interference. To characterize the

neural basis of these effects, we introduced a novel measure "neural distance", which quantifies

trial-to-trial reconfiguration of multivoxel activity patterns. Across the brain, larger neural

distances predicted larger RT switch costs, linking representational reorganization to behavioral

performance. Importantly, representational reconfiguration differed across hierarchical levels and

anatomical systems. Subordinate rule updating was modulated by perceptual input and expressed

in distributed perceptual and motor networks, whereas context reconfiguration engaged the

lateral middle frontal cortex and was comparatively insulated from interference. Our results

reveal the structure of neural representations supporting flexible updating and interference-

shielded contextual representations subserving control behavior.

Significance

Daily activities often require a mixture of both high and low flexibility demands that need to

be performed concurrently. Driving requires maintaining a stable destination goal while rapidly

updating motor plans (brake, accelerate, turn, etc.) in response to changing sensory information.

Although people perform such tasks with ease, it remains unclear how neural and cognitive

representations are structured to respond to these different demands. The present study suggests

that sensory-motor plans prioritize high flexibility by allowing greater influence from sensory

inputs, which can create interference across brain networks when that input is task-irrelevant.

Contextual information is shielded from this interference by representing contexts as distinctly as

possible in the lateral prefrontal cortex, resulting in slower but more stable context switching.

1. Introduction
60
Everyday tasks often consist of a mixture of high and low flexibility in goal directed

behavior. For example, driving requires maintaining an overarching destination goal while

continuously updating route plans and switching between accelerating and braking in response to

dynamic sensory inputs. Because this overarching destination goal does not require frequent

updating, flexibility demands are low. Conversely, more immediate route and sensory-motor

plans require fast and accurate updating, therefore flexibility demands are high. Understanding

how these demands are jointly supported requires examining the representational structures

encoded in the brain that implement cognitive control (Monsell, 2003; Meiran et al., 2000;

Rogers & Monsell, 1995; Badre et al., 2021).

Cognitive control depends on representations incorporating goals, contexts, stimuli, and

actions. How these representations are structured and encoded shapes cognitive flexibility.

Contextual representations, often attributed to the rostral portions of mid-lateral prefrontal cortex

(Badre & D'Esposito, 2007; Badre et al., 2009; Nee & Brown, 2013), are assumed to bias

downstream processes to prioritize task-relevant information for contextually guided hierarchical

cognitive control (Miller & Cohen, 2001; Nee & D'Esposito, 2017). Such biasing can prioritize

shielding representations from interference, which in some cases can incur additional cost of

flexibility (Geddert & Egner, 2024; Dreisbach & Fröber, 2018; Mayr & Grätz, 2024). Yet the

same system can also support high flexibility by integrating and updating sensory-motor

representations under changing contexts (Kikumoto & Mayr, 2020; Kikumoto et al., 2024) and

redirecting attention toward alternative task rules or stimuli dimensions (Cellier et al., 2022).

High flexibility may therefore be facilitated when control representations permit greater bottom-

up influence from sensory inputs (Schumacher & Hazeltine, 2016).

The structure of control representations can be probed by examining trial-to-trial

reconfiguration (Dykstra et al., 2022). Behavioral paradigms have historically focused on trial-

wise transitions, based on the assumption that internal structures should constrain observable

actions. One ubiquitous measure is response time "switch costs"—the additional time it takes to

make a response when a task changes from one trial to the next (Monsell, 2003; Rogers &

Monsell, 1995; Wylie & Allport, 2000). By systematically analyzing factors influencing switch

costs, one can identify the representational properties supporting flexibility. For example, if high

flexibility is implemented by increasing sensory-driven influence, then task-irrelevant sensory

information should show greater influence on switch costs.

Although switch costs provide a behavioral readout of reconfiguration processes, their

neural basis remains unclear. Recent work suggests information is encoded in distributed activity

patterns across neuron populations, voxels, or electrodes (Ebitz & Hayden, 2021; Mur et al.,

2009). Under this population view, cognitive flexibility entails transforming one activity pattern

into another. The farther the system must travel in multivariate space, the longer the

transformation should take, producing a larger switch cost (Qiao et al., 2017). Distance traveled

can be estimated by calculating the multivariate distance between the activity pattern on a switch

trial versus the preceding trial. A small distance would require minimal energy, whereeas a

larger distance, reflecting costly reorganization, would predict a larger behavioral switch cost.

By that logic, more concrete task-rules and sensory-motor representations requiring high

flexibility should minimize representational distance. Thereby, producing smaller switch costs at

the price of increased vulnerability to sensory driven feed-forward interference. In comparison,

less flexible contextual representations should be encoded as distinctively as possible (i.e., larger

representational distance) to minimize interference.

106   Given these hypotheses, our study pursued two main goals. First, we used response time

switch costs to determine how distinct cognitive task representations are reconfigured during

hierarchical cognitive control. Second, we quantified trial-to-trial shifts in multivoxel activity

patterns, which we refer to as "neural distance", to examine how neural representational

reconfiguration is influenced by both the hierarchical structure of the task and additional factors,

such as perceptual processes, and the interactions among these factors. Results confirmed that

larger neural distances predicted larger RT switch costs. Moreover, representational

reconfiguration differed across hierarchical levels in its sensitivity to perceptual input. Increased

feedforward perceptual influence modulated subordinate rule selection but not contextual rule

selection. This result suggests that contextual representations may organize lower-level rule–

stimulus–response conjunctions in a way that limits interference from irrelevant perceptual

information. Finally, greater neural reconfiguration in subcortical structures was associated with

greater post-error slowing.

2. **Methods**

2.1. Participants. Participants were recruited for two experiments, experiment 1 involved

MRI scanning, and experiment 2 was a behavioral only experiment conducted to replicate in-

scanner behavioral effects. For experiment 1, we recruited 73 healthy participants (53 female, 20

male, $M_{age} = 22.31$, $SD_{age} = 4.45$, $Range_{age} = 18-35$ years). Out of these 73 participants, 10 were

excluded for poor behavioral performance (accuracy < 75% for at least one condition), and 9

were excluded for excessive movement artifacts (mean framewise displacement > 0.4 mm across

runs). After exclusion, we included data from 54 participants (39 female, 15 male, $M_{age} = 22.38$,

$SD_{age} = 4.87$, $Range_{age} = 18-35$ years). These data were also published in our previous study

(Chen et al., 2024). For experiment 2, we recruited 65 healthy participants (55 female, 9 male, 1

non-binary, $M_{age} = 18.63$, $SD_{age} = 0.71$, $Range_{age} = 18-21$ years). Out of these 65 participants, 8

were excluded for poor behavioral performance (accuracy < 75% for at least one condition).

After exclusion, we included data from 57 participants (50 female, 7 male, $M_{age} = 18.63$, $SD_{age} =$

0.72, $Range_{age} = 18-21$ years). Both experiments were approved by the University of Iowa

Institutional Review Board. All participants were recruited from the University of Iowa and

surrounding area to participate. All participants had normal or corrected to normal visual acuity

and color vision, were right-handed, and with no history of epilepsy, psychiatric, or neurological

conditions. All participants gave written informed consent. The experiments were conducted in

compliance with the ethical principles expressed in the Declaration of Helsinki.

2.2. MRI data Acquisition. Imaging data were collected at the Magnetic Resonance

Research Facility at the University of Iowa using a 3T GE SIGNA Premier scanner with a 48-

channel head coil. Structural images were acquired using a multi-echo MPRAGE sequence (TR

= 2348.52ms; TE = 2.968ms; flip angle = 8°; field of view = 256*256; 200 sagittal slices; voxel

size = 1mm^3). Functional images were acquired using an echo-planar sequence sensitive to blood

oxygenated level-dependent (BOLD) contrast (Multiband acceleration factor = 2; no in-plane

acceleration; TR = 1800ms; TE = 30ms; flip angle = 75°; voxel size = 1.718 mm*1.718mm *2.5

mm).

2.3. MRI Data Preprocessing. All fMRI data were preprocessed using fMRIPrep

version 20.1.1 (Esteban et al., 2019) to reduce noise and transform data from subject native space

to the ICBM 152 Nonlinear Asymmetrical template version 2009c for group analysis (Fonov et

al., 2011). Preprocessing steps include bias field correction, skull-stripping, co-registration

between functional and structural images, tissue segmentation, motion correction, and spatial

normalization to the standard space. We did not perform any spatial smoothing and did not apply

conventional nuisance regression. Instead, noise suppression was implemented during within the

GLMsingle procedure (Prince et al., 2022). GLMsingle combines voxel-wise GLM estimation

with automated denoising procedures from GLMdenoise (Kay et al., 2013), which uses cross-

validation to identify and apply the optimal combination of nuisance regressors. Nuisance

regressors, motion estimates, and principal components were learned to best improve cross-

validation performance from whole-brain regions of interest. The framework also estimates

single-trial beta weights while correcting for temporal autocorrelation and optimizing the

hemodynamic response function on a voxel-wise basis (see section 2.7). This approach provides

improved sensitivity and reliability for our trial-by-trial transition analyses.

2.4. Experimental Design. In experiment 1, participants underwent an fMRI scanning

session while performing a hierarchical cognitive control task. Before entering the scanner, all

participants completed a tutorial and a practice session. Once participants achieved at least 80%

on the practice, the experiment's scanning session began. We collected eight runs of functional

scans, with each run consisting of 51 task trials. This resulted in a total of 408 task trials across

all eight runs. Each functional run lasted approximately 6.5 minutes. In experiment 2,

participants performed the same hierarchical cognitive control task behaviorally with the same

training procedure, trial timing, block structure, and number of trials. The purpose was to

replicate the behavioral effects we observed in scanner.

2.5. Behavioral Tasks. To study the representation structure for flexible hierarchical

cognitive control, we developed a hierarchical cognitive control task (Chen et al., 2024). The

task implements a three-level hierarchy in which texture defines context, context determines the

relevant feature dimension, and the feature dimension maps onto a response rule.

2.5.1. *Task structure and trial sequence*. In this task, each trial began with a cue object

presented for 500 milliseconds, followed by an image of either a face or a scene presented for

2000 milliseconds (**Figure 1A**). The inter-trial interval (ITI) was jittered between 1.5 to 10.5

seconds with an average duration of 4.25 seconds. Depending on the cue object presented before

the image, participants made a yes/no judgment on one of two response rules: (1) was the image

a face? (2) was the image a scene?

2.5.2. *Hierarchical rule structure*. To determine which response rule to use on a given

trial, participants had to integrate three sources of information associated with three perceptual

features of the cue object: texture, shape, and color (**Figure 1A**). The cue's texture determined

whether the response rule was signaled by shape or color. If the texture of the cue object was

filled in, the shape of the object (square or circle) would indicate which rule they needed to use

(square being the face rule, "is the image a face?", and circle being the scene rule, "is the image a

scene?"). Alternatively, if the texture of the cue object was hollow (i.e., only an outline), the

color of the object (red or blue) would indicate which rule they needed to use (blue being the

face rule and red being the scene rule). Half of the participants completed a counterbalanced

version of this task with alternative yes/no response key mappings, and in which the top level of

the hierarchy was flipped (i.e., hollow texture cues shape and filled texture cues color).

197
198   **Figure 1**. Hierarchical control task design. A) Depiction of the task rule hierarchy embedded
199   within the 8 potential cue objects. B) Example trial sequence: A cue object presented for 500ms
200   followed by an image of either a face or a scene for 2000ms and a jittered ITI (range: 1.5-10.5
201   seconds; average: 4.25 seconds. Example cue transitions across trials depicts how perceptual
202   change is operationalized. Example face image is an author on this manuscript.
203

2.5.3. *Hierarchical rule switching*. This task design yields three types of trial-to-trial

transitions that differ in the level of hierarchical reconfiguration required: Stay, intra-dimension

switch (IDS), and extra-dimension switch (EDS). On Stay trials, participants repeated the same

rule as the previous trial, preserving both the texture-defined context and feature-to-rule mapping

(e.g., which color or shape indicates the face task). On IDS trials, participants switched between

task-relevant features (shape vs. color) within the same texture context. On EDS trials, they

updated the highest-level context by switching texture cues (filled vs. hollow), thereby changing

which feature signaled the response rule.

2.5.4. *Trial-to-trial transitions, perceptual, and motor factors*. In addition to hierarchical

rule switching, the task design allowed us to quantify trial-to-trial perceptual and motor

influences on performance. Specifically, (1) whether texture, shape, or color repeated from the

previous trial, (2) how many cue object features changed (range: 0-3), (3) whether the targeted,

relevant feature repeated or switched from the previous trial (e.g., if the relevant feature on trial

N-1 was color red, whether it repeated or switched on the current trial), (4) whether the motor

response repeated, and (5) how these factors interacted with rule switching. As described in

detail below, we used linear regression to quantify the influence of each factor on response times

and reconfiguration on voxel activity patterns.

2.5.5 Behavioral (Response Time) Switch Costs. To quantify behavioral costs associated

with hierarchical task reconfiguration, we analyzed trial-wise response times using linear mixed-

effects regression. This approach allowed us to estimate the contributions of hierarchical rule

switching, perceptual feature transitions, and motor processes to performance costs while

accounting for repeated measurements within subjects.

2.6. Multivariate Activity Pattern Distance. The goal of this analysis was to

characterize how neural activity patterns that instantiate cognitive task representations are

reconfigured from trial to trial. To this end, we quantified trial-to-trial changes in multivoxel

BOLD activity patterns and examined how these representational shifts from trial-to-trial

(hereafter described as neural distance; Fig. 2). Using the same analytical logic as our behavioral

switch cost analysis, we fitted regression models to neural distance to determine how

reconfiguration was influenced by hierarchical task structure, perceptual and motor factors, and

error-related processes. This analysis included a multistep pipeline consisting of trial-wise

activity estimation, computation of multivariate pattern distances, and regression-based modeling

that paralleled to the behavioral switch-cost analysis.

A) Neural Distance Method

238
239   Figure 2. Neural Distance Method. A) depiction of how neural distance is calculated on adjacent
240   trial multivoxel activity patterns. A greater change in multivoxel activity patterns is associated
241   with a greater correlation, or neural distance.
242
2.6.1. *Trial-wise activity estimate*. Preprocessed fMRI time-series (outputs of fMRIPrep)

were first submitted to GLMsingle (Prince et al., 2022) to estimates trial-wise beta estimates.

GLMsingle employs a cross-validation framework in which voxel-wise noise regressors are

derived from the data itself and evaluated on held-out runs; these regressors are then

incorporated into a general linear model (GLM) to improve the reliability of single-trial β-

estimates. Another key feature of GLMsingle is that every voxel will have its own best

hemodynamic response function, so instead of assuming the same HRF across the whole-brain

this procedure can account for difference in neurovascular coupling between regions. A further

benefit of GLMsingle estimates trial-wise beta-estimates via ridge regression. After constructing

the design matrix with one regressor per trial, GLMsingle fits a penalized GLM in which a

regularization parameter λ is chosen by cross-validation. This approach minimizes the inflated

correlations in beta estimates between adjacent trials. At the end, this procedure yielded one

amplitude estimate per trial per voxel. To ensure that variability in RT did not drive the neural-

distance measures, we regressed each trial's RT from its corresponding amplitude estimate on a

voxel-by-voxel basis before further analyses.

2.6.2. *Neural distance*. Using these RT-corrected trial-wise maps, we then calculated

multivariate distances between trial-wise activity patterns. This was done with an 8 mm radius

volumetric searchlight analysis, restricting to gray matter voxels. Within each searchlight sphere,

signals were first "whitened" by applying the noise covariance matrix (equation 1) estimated

across all trials and voxels in that sphere to remove shared noise correlations (equation 2) before

measuring pattern shifts (Walther et al., 2016).

$$\Sigma = \frac{1}{T} R^T R \qquad \text{(eq 1)}$$

265   Where R is the model residuals matrix of size T x P. Note, T is the number of time points

266   and P is the number of voxels. The covariance matrix, Σ, is size P x P.

$$b_k^* = b_k \Sigma^{-\frac{1}{2}} \qquad \text{(eq 2)}$$

268   Where b_k is a searchlight sphere multivoxel activity pattern of size P corresponding to

269   one condition, k, of the possible K conditions.

270   This procedure removes voxel-wise correlations attributable to shared noise. We then computed

271   the correlation distance (equations 3 and 4) between consecutive trials:

$$d_{cosine}(b_k, b_j) = 1 - \frac{\langle b_k, b_j \rangle}{\|b_k\|\|b_j\|} = 1 - \cos(\angle b_k b_j) \qquad \text{(eq 3)}$$

Where b_j is a searchlight sphere multivoxel activity pattern of size P corresponding to one

condition, j, of the possible K conditions.

$$b_k = b_k - \bar{b}_k 1$$

$$b_j = b_j - \bar{b}_j 1$$

$$d_{correlation}(b_k, b_j) = 1 - \frac{\langle \tilde{b}_k, \tilde{b}_j \rangle}{\|\tilde{b}_k\| \|\tilde{b}_j\|} = 1 - \cos(\angle \tilde{b}_k, \tilde{b}_j) \qquad \text{(eq 4)}$$

Where 1 is a row vector of ones of size 1xP and $\bar{b}$ is the voxel mean.

Correlation distance was chosen over Euclidean or Mahalanobis metrics because we were

primarily interested in changes in the neural representation geometry rather than overall

amplitude shifts. This procedure yielded, for each voxel, a time series of neural distance values

reflecting trial-to-trial representational reconfiguration.

2.7. Statistical Analyses

2.7.1 Behavioral Model overview. The primary goal of the behavioral model was to

identify factors that influence response time switch costs during hierarchical cognitive control.

Specifically, the model tested how performance costs varied as a function of (1) the level of

hierarchical rule reconfiguration (Stay, IDS, EDS), (2) trial-to-trial changes in perceptual cue

features, and (3) interactions between hierarchical switching and perceptual change. Additional

regressors were included to control for known effects of motor repetition, task repetition, and

error-related adjustments.

2.7.2. Behavioral preprocessing and dependent variable (z-scored response times). The

dependent variable was trial-wise response time, normalized as z-scored response times (zRTs).

Specifically, we first normalized each participants' RT within each experimental block and

response modality (i.e., yes versus no response). When normalizing RTs we did not include error

or post-error trials when calculating the mean or standard deviation because of extensive work

showing error and post-error slowing effects (Rabbitt, 1966; McClure et al., 2003). We then

applied the following exclusion criteria: (1) the first trial of each run, (2) any zRTs exceeding 3

standard deviations from the mean, (3) any trials with missing responses, (4) any post-error trials

that were also erroneous.

2.7.3. Primary behavioral model predictors. For the model regressors, we included the

following fixed effects. First, we included hierarchical task switching (Stay, IDS, EDS) as a

categorical predictor to capture the effects of abstract rule structures on performance cost. To

determine how perceptual representations of the cue attributes influence switch costs beyond

abstract rules, we incorporated several perceptual factors: cue texture, color, and shape, along

with the number of features that changed from the previous trial (range: 0-3).

We further included an additional binary regressor indicating whether the target feature

repeated or switched from the previous trial. For example, if the relevant feature on trial N-1

was color (red), the target feature was coded as "repeated" if the cue on trial N was also red, and

"switched" if the cue was a different color (e.g., blue). This regressor indexed how the previous

trial's task-relevant sensory representation influences current trial performance.

Critically, we included an interaction between hierarchical task switching and the number

of perceptual features that changed from the previous trial. This critical interaction tested our

hypotheses about flexibility prioritization. If lower-level rule representations prioritize

flexibility, we expected a significant positive interaction between IDS trials and feature change

count. Conversely, if contextual representations prioritize stability, we expected no significant

interaction between EDS trials and feature change.

2.7.4. Behavioral model control variables and conjunction related interactions. To

account for known influences on response times, we included several control variables: task-rule

repetition vs. switch, yes/no response repetition vs. switch, and probe-image repetition vs.

switch. We also controlled for trial-by-trial performance fluctuations by including separate

regressors for post-error trials and error trials to account for post-error slowing effects.

Beyond controlling for nuisance variance, the model incorporated a set of theoretically

motivated interaction terms to replicate established task-switching effects. In particular, prior

work suggests that flexible behavior is supported by conjunctive representations that integrate

task rules, stimuli, and responses, and that the strength of such conjunctions can be indexed

indirectly through partial switch costs (Kikumoto & Mayr, 2020; Grzyb & Hubner, 2013;

Kleinsorge & Heuer, 1999). Partial switch costs arise when some, but not all, components of a

task representation change across trials, requiring unbinding and rebinding of the prior

conjunction (Li et al., 2019). Therefore, we further included a theoretically motivated interaction

term: task-rule repetition with response repetition. This interaction terms tests the canonical

partial switch costs, characterized by faster responses on full repetition and full switch trials

relative to partial repetition/switch trials (Grzyb & Hubner, 2013; Kleinsorge & Heuer, 1999).

Because this interaction term indexing conjunction related effects could differ as a

function of hierarchical context, we ran a second mixed effects regression model where we

replaced hierarchical switch type (Stay/IDS/EDS) with a binary regressor indicated in context

repeated or switched. This further allowed us to include two-way interactions between (1)

context repeat and task repeat and (2) context repeat and response repeat, as well as the 3-way

interaction of primary interest: context repeat by task repeat by response repeat. If contextual

representations organize lower-level rule–stimulus–response associations, then partial switch

costs should primarily occur within contexts and be weaker across contexts. In other words, we

should observe a significant three-way interaction between context, task, and response that is

driven by the existence of (1) a significant two-way interaction between task and response within

context, but (2) a non-significant two-way interaction between task and response when switching

across context.

2.7.5. Behavioral model random effects structure. We treated subject as a random

intercept and estimated random slopes for each individual cue feature (color, shape, and texture)

to capture individual differences in sensitivity to these perceptual factors. Due to the complexity

of the model, we kept the random effects structure as simple as possible to avoid convergence

issues.

2.7.6. Behavioral (response time) supplementary analysis. It is important to note a subtle

difference between IDS and EDS trials regarding trials where two features changed. For IDS, a

two-feature change always reflects a change in both a task-relevant and task-irrelevant feature. In

contrast, a two-feature change on EDS trials does not always mean a change in one relevant and

one irrelevant feature. Sometimes a two-feature change on EDS trials means two relevant

features change and no task-irrelevant features change. Therefore, we ran an additional follow-up

paired samples t-test where we ensure EDS trials where two features changed were restricted to

only trials where one feature was task-relevant and the other was task-irrelevant. We then

contrasted these trials with trials where only one task-relevant feature changed.

2.7.7 Regression model for neural distance. For each subject, the neural distance time

series was entered as the dependent variable in a linear regression model closely paralleling the

behavioral model described in Section 2.6.3. The primary predictors included hierarchical task-

switching condition (Stay, IDS, EDS), perceptual feature-change variables, motor repetition,

error and post-error indicators, and their theoretically motivated interactions. Unlike the

behavioral model, regressors indexing the absolute texture, color, or shape of the current trial's

cue were not included because the dependent variable was a measure of dissimilarity between the

current trial and previous trial, whereas the behavioral model's dependent variable was a

measure of the magnitude of the current trial cost.

To further control for potential RT effects on the BOLD response (Mumford et al., 2024),

which was used to calculate neural distance, we added a regressor reflecting the magnitude of

trial-to-trial changes in zRT (difference in zRT across adjacent trials) and a regressor reflecting

the magnitude of the current trial's zRT .

2.7.8 Group analysis of neural distance. This procedure yielded, for each subject, a

whole-brain beta map of each regressor that was then entered into a one-sample t-test across

participants. To control the family-wise error rate for multiple comparisons, we employed

AFNI's 3dClustSim using the residuals from the GLM procedure (Cox et al., 2017). First, spatial

autocorrelation of the residuals was estimated using the autocorrelation function (ACF),

producing three ACF parameters that characterize the spatial smoothness of the data. These

parameters were then supplied to 3dClustSim to estimate the minimum cluster size for a

corrected cluster-level threshold. Significant clusters for parametric modulation are based on

these calculated minimum cluster sizes of 22 voxels (cluster p-value threshold of .001 and a

voxel-level p-value threshold of .005).

2.8. Behavioral Switch Cost and Neural Distance Predictions. Our framework posits

that representations supporting flexibility can be readily adapted by incorporating changing

sensory inputs to modify action plans. Such flexibility, however, can come at a cost of increased

susceptibility to feed-forward sensory inputs from task-irrelevant information. Representations

not prioritizing flexibility are better shielded from sensory inputs, thereby minimizing

interference but making reconfiguration more effortful. From this framework, we derive specific,

testable predictions for both behavioral performance (zRT switch costs) and neural

reconfiguration (neural distance) that we describe in detail below.

For representations that prioritize flexibility, we predict increased sensitivity to

interference from task-irrelevant perceptual changes. Specifically, we expect the reconfiguration

of this representation to be more susceptible to interference from task-irrelevant information due

to (1) smaller representational distance and (2) greater sensory-driven influence driving

representational reconfiguration. As a result, interference from irrelevant features should slow

RTs and increase neural distance. Accordingly, these predictions can be tested by examining the

interaction between hierarchical task switching that only involved lower-level rule

reconfiguration (IDS) and the number of features (i.e., texture, color, shape) that changed across

trials. Specifically, IDS trials require that the contextual texture repeats while the relevant feature

switches (e.g., color). If only one feature changes, then only the task-relevant dimension has

changed. If multiple features change, then both task-relevant and task-irrelevant dimensions have

changed. We predict that these changes in task-irrelevant features will increase both switch costs

and neural distance in brain regions encoding representations that prioritize flexibility. This

pattern reflects stronger bottom-up influence from sensory inputs during subordinate rule

updating during hierarchical control.

For EDS trials, which require switching the context, we predict the opposite pattern.

Because contextual representations prioritize stability, we hypothesize that they are separated by

larger representational distances and thus should be less influenced by trial-to-trial changes in

perceptual and motor factors. This further shields against the processing of task-irrelevant

features. Consequently, the interaction between the number of cue features changing across trials

and context reconfiguration (EDS) should be weaker than that for either subordinate rule

reconfiguration (IDS) or no rule reconfiguration (Stay). On EDS trials, even when multiple cue

features change, irrelevant features should exert weaker effect on RTs and neural distances. In

parallel, regions dedicated to reconfiguring contextual representation should exhibit larger neural

distance for EDS when compared to IDS.

3. Results
419
We analyzed both behavioral (z-scored RTs) and neural representation (neural distance)

measures using a common regression framework to identify factors that influence observable

behavioral costs and neural reconfiguration costs during a hierarchical cognitive control task.

Our central prediction was that prioritizing cognitive flexibility would reduce

switch/reconfiguration costs, albeit at the expense of increased susceptibility to interference from

task-irrelevant information. More specifically, subordinate rule switches would be faster than

context switches, but at the cost of being more vulnerable to interference from task-irrelevant cue

feature changes, whereas context switches would incur greater reconfiguration costs but reduced

interference from task-irrelevant information.

To investigate potential mechanisms underlying reduced processing of task-irrelevant

information during context reconfiguration, we investigate potential interactions between context

and conjunctions—integrated representations incorporating rules, stimuli, and responses, that

support cognitive flexibility (Kikumoto and Mayr, 2020). More specifically, we leverage partial

switch costs as an indirect measure of conjunction strength, to test whether different contexts are

split into distinct representational subspaces, within which context-dependent conjunctions are

embedded. Finally, we consider how post-error processes might interact with this underlying

hierarchical task representation structure to drive internally driven error correction.

3.1. Distinct hierarchical level representations interact differently with task-relevant and -
irrelevant perceptual influences during reconfiguration.
439
440   Traditionally, a hierarchical representation structure has been assessed by comparing the

magnitude of switch costs across different levels of hierarchical rule switching (Fig. 3A, top

panel). Larger switch costs when context switches relative to subordinate-rule switches have

been taken as evidence of an underlying hierarchical representation structure (Cellier et al., 2022;

Chen et al., 2024). The present dataset displays these expected switch cost effects of larger zRT

switch costs for context switches (EDS) as compared to both subordinate rule switches (IDS;

$t(53)=8.010$, $p<.001$), and rule repeats ($t(53)=18.128$, $p<.001$), as well as subordinate rule

switches (IDS) as compared to rule repeats (Stay; $t(53)=11.195$, $p<.001$; Fig. 3B). Switch costs

that increase with reconfiguration of increasingly superordinate rules suggest an underlying

hierarchical organization of task representations in the present dataset.

450
Figure 3. Response Time Switch Costs. **A)** Depiction of switch cost predictions for a hierarchical
representation structure (top) and cognitive flexibility predictions for a more fine-grained switch
cost analysis (bottom). **B)** Switch cost analyses comparing hierarchical rule switch conditions.
Significance is based on two-tailed paired sample t-tests with zRTs. **C)** Switch cost comparisons

from the interaction between the hierarchical rule (Stay/IDS/EDS) and the number of features
that changed from the last trial (perceptual change). Significance is based on post-hoc
comparisons between estimated marginal means for hierarchical rule (Stay/IDS/EDS) and
perceptual change.
459

However, focusing solely on the magnitude of switch costs across different levels of

hierarchical rule switching neglects critical interactions between hierarchical task structure and

the processing of task-relevant versus task-irrelevant information across trials. Additionally,

previous investigations have largely overlooked trial-to-trial transition factors that arise from

perceptual continuity or change. For example, whether task-relevant or task-irrelevant cue

features repeat or change from one trial to the next. Concretely, a cue might switch from a solid

red circle to a solid red square, in which case only the task-relevant feature (shape) changes

while the task-irrelevant feature (color) repeats; alternatively, the cue might switch from a red

circle to a blue square, in which case both the task-relevant and task-irrelevant features change.

This is important to consider because, when cognitive flexibility is prioritized, faster switching

may come at the cost of increased susceptibility to interference from task-irrelevant perceptual

changes.

Therefore, we conducted more fine-grained analyses investigating how trial-to-trial

changes in perceptual cue features interact with the reconfiguration of different levels of

hierarchical representations. Because rule switches are indicated through changes in cue object

features, we further divided switch trials (IDS and EDS) into two subgroups, those where only

the task-relevant feature changed (i.e., trials where only one cue feature changed), and those

where both task-relevant and task-irrelevant features changed (i.e., trials where two cue features

changed). This distinction allowed us to test whether representations are shielded from

perceptual interference, as we expect for context representations, or are vulnerable to

interference, as we expect for subordinate rule representations.

Consistent with our predictions (Fig. 3A-bottom), if subordinate rules prioritize flexibility

by allowing greater bottom-up influence from perceptual input, then subordinate rule

reconfiguration should be more susceptible to interference from changes in task-irrelevant cue

features. Supporting this prediction, trial-level mixed-effects models (with random intercepts for

subjects) revealed positive slopes for the number of features changing across trials (perceptual

change) for both rule repeat (Stay; $\beta = 0.151$, $SE = 0.017$, $CI = [0.117, 0.184]$), and subordinate

rules switch (IDS; $\beta = 0.072$, $SE = 0.023$, $CI = [0.026, 0.118]$) and a negative slope for context

switch (EDS; $\beta = -0.051$, $SE = 0.023$, $CI = [-0.095, -0.007]$).

Follow-up contrasts confirmed that these positive slopes were associated with

significantly slower response times when more cue features changed for both rule repeats (Stay;

zero versus one; *mean difference* $= 0.151$, $t(19588) = 8.835$, $p < .001$), and subordinate rule

switches (IDS; one versus two; *mean difference* $= 0.072$, $t(20227) = 3.063$, $p = .013$; Bonferroni

corrected; Fig. 3C). This indicated that, as predicted, the additional task irrelevant feature change

incurred an additional switch cost, i.e., slower response times, for subordinate rule switches.

Moreover, for EDS trials there was no significant increase in response times when more cue

features changed for context switch (EDS) trials (one versus two, *mean difference* $= 0.051$,

t(20888) $= -2.266$, *p* $= .141$; Fig. 3C; one versus three, *mean difference* $= 0.102$, *t(20888)* $= -$

2.266, *p* $= .141$, two versus three, *mean difference* $= 0.051$, *t(20888)* $= -2.266$, *p* $= .141$;

Bonferroni corrected). This suggests that context reconfiguration is better shielded from potential

feedforward perceptual interference from task-irrelevant feature changes. Note, because a two-

feature change on EDS trials did not always mean both a task-relevant and task-irrelevant feature

change, we ran a supplementary post-hoc paired sample t-test where we ensured this was the

case (see methods section *Behavioral (response time) supplementary analysis* for more details).

Critically, this analysis also found no difference in the magnitude of zRT switch costs between

one versus two features changing (paired-sample t-test $t(53) = -0.010$, $p = .797$).

Finally, we found a significant interaction between these perceptual change slopes for the

different rule reconfiguration conditions (i.e., IDS versus EDS), indicating that this slope is

significantly more positive for IDS trials as compared to EDS trials ($\beta = 0.123$, $t(20860) = 4.123$,

$p < .001$). To summarize, these results support our hypotheses on cognitive flexibility.

Specifically, the degree of perceptual change in the cue object interacts with rule reconfiguration

differently depending on which hierarchical rule level is being reconfigured. Subordinate rule

representations support flexibility at the cost of greater perceptual interference during

reconfiguration, whereas contextual representations are less influenced by perceptual

interference during reconfiguration.

To investigate potential neural underpinnings of these zRT switch cost effects, we

conducted a parallel analysis using trial-to-trial changes in neural representational patterns

("neural distance") as a neural analogue of switch costs. We applied the same regression model

used for the behavioral switch cost analysis to predict neural distance. We included zRT and the

difference in zRT across adjacent trials as additional predictors to control for potential effects of

RTs on neural dissimilarity patterns (Mumford et al., 2024).

Based on prior work implicating the middle frontal gyrus (MFG) in contextual encoding

and hierarchical cognitive control (Badre & D'Esposito, 2007; Badre & Nee, 2018; Nee &

D'Esposito, 2016), we predicted that context reconfiguration (EDS) would elicit a larger neural

distance in MFG than subordinate rule reconfiguration (IDS). In parallel with behavioral

525 findings, we further predicted that EDS reconfiguration would be relatively insensitive to

526 perceptual interference. In contrast, we predicted that IDS reconfiguration would show an

527 interaction with perceptual interference (Fig. 4A). Specifically, we predicted that neural distance

528 in MFG during EDS trials would be unaffected by the number of perceptual cue features

529 changing across trials. In contrast, we predicted that premotor and visual attention regions would

530 show larger neural distances on IDS trials when a greater number of perceptual features changed,

531 reflecting both the encoding of subordinate rules in premotor regions (Nee & Brown, 2013;

532 Badre & Frank, 2012) and increased processing of task-irrelevant perceptual information during

533 subordinate rule reconfiguration.

534
535 Figure 4. Neural Distance. **A**) Depiction of expected effects for context reconfiguration versus
536 subordinate rule reconfiguration. **B**) Observed main effect of context reconfiguration contrasted
537 with subordinate rule reconfiguration—significant clusters in MFG and IFS, regions belonging to
538 the control and salient/ventral attention networks. Note, there were no significant clusters for the
539 main effect of subordinate rule contrasted with stay (rule repeat) trials. **C-D**) Interactions
540 between perceptual change (i.e., number of cue object features changing across trials; range 0-3)
541 and subordinate rule reconfiguration (**C**) or rule repeat (Stay) trials (**D**). **E**) Main effect of

542   perceptual change. **F**) Bar plots depicting overlap between significant clusters from **B-E** and the
543   Yeo 17 networks.
544

In line with these predictions, we identified two significant clusters in lateral frontal

regions showing greater neural distance for EDS compared to IDS (IFS and caudal MFG; Fig.

4B). In contrast, widespread clusters showed significantly greater neural distance for the overall

main effect of the number of changing cue features (Fig. 4E) and its interactions with both IDS

trials (Fig. 4C) and Stay trials (Fig. 4D). Within these regions, the neural distance was greater

when both task-relevant and task-irrelevant features changed compared to when only the task-

relevant feature changed, consistent with increased susceptibility to perceptual interference

during subordinate rule processing. These clusters were localized in a widely distributed fashion,

such as those associated with the dorsal and ventral attention networks, the visual networks, as

well as the default mode networks (Fig. 4F).

Regarding the control variables, after including the primary measures of interest

(hierarchical switch type and perceptual change), we found no significant response time switch

costs associated with task switch ($\beta = 0.018$, $t(20880) = 0.506$, $p = .613$), response switch ($\beta =$

0.019, $t(20880) = 0.683$, $p = .495$), or probe switch ($\beta = 0.027$, $t(20880) = 1.071$, $p = .284$). On

the other hand, we did find a significant switch cost associated with previous target feature

switches ($\beta = 0.063$, $t(20900) = 3.040$, $p = .002$). For the neural distance regression, we found

clusters associated with a significantly larger neural distance for response, probe, and previous

target feature switches. For response switching, we found significantly greater neural distance in

left motor cortex and visual cortex (Fig. S1A), a pattern that is expected given that our task

required responses to be made with the right hand. For probe switches, we found significantly

greater neural distance in ventral occipital and temporal regions (Fig. S1B), such as fusiform face

area (FFA) and parahippocampal place area (PPA), as expected given that our task used face and

place images. Finally, for target feature switches, we found significantly greater neural distance

in distributed clusters, including caudal PFC, primary visual cortex, right parahippocampus to

inferior and middle temporal gyrus, and the right putamen (Fig. S1C). We limit further

discussion on these control variables as they are not of primary interest.

Taken together, these results suggest that the slowing of response times during IDS trials

with multiple feature changes reflects larger shifts in representational patterns across distributed

regions. These larger neural distances likely index greater sensitivity to task-irrelevant feature

changes, consistent with increased bottom-up influence during subordinate rule reconfiguration.

By contrast, modulation of neural distance in MFG suggests that context reconfiguration elicits

large representational shifts irrespective of the number of perceptual features changing across

trials, consistent with reduced susceptibility to perceptual feedforward interference.

578
579   **3.2. Conjunction representations supporting cognitive flexibility are context dependent.**
580
Prior work suggests cognitive flexibility, i.e., fast and efficient switching between

rules/tasks, is supported by the creation of conjunctive representations (Kikumoto and Mayr,

2020). These conjunctive representations consist of rules, stimuli, and responses. A common

measure of conjunctions has been partial switch costs—greater switch costs when only a subset

of conjunction components change across trials, as compared to trials where all components

switch or repeat (Grzyb & Hubner, 2013; Kleinsorge & Heuer, 1999). When all components of a

conjunction repeat, then the previous trial's conjunction can be re-instantiated. However, when

some components repeat and some switch, the previous conjunction needs to first be unbound so

that a new conjunction can be created with the components that repeat across trials. Furthermore,

the conjunction components that repeat across trials can cause increased interference when

sensory-motor plans differ between these two trials. Thus, this unbinding and rebinding in

addition to increased interference that needs to be resolved cause the observed "cost'. When all

components of a conjunction switch, the unbinding process can be skipped and the lack of shared

components with the previous trial means no additional interference needs to be overcome.

However, a new conjunction still needs to be constructed, which is why response times are still

slower overall than trials where the previous conjunction can be re-instated and utilized.

Previous work on conjunctive representations has largely examined tasks with a single

level of rule structure (Kikumoto and Mayr, 2020; Rangel et al., 2023). As such, it remains an

open question as to whether conjunctions consist of only the lower-level rule, or if they include

higher-order context-level information that our task was designed to probe. Recent evidence

suggests that conjunctive representations may be organized into context-specific subspaces,

enabling more efficient readout of task-relevant information (Kikumoto et al., 2024). Given that

in our task, context indicates if color or shape is the currently relevant rule, we predicted that

conjunction-related partial switch costs would be observed within each context, but not when

switching across contexts. Under this account, context serves to index distinct conjunctive

subspaces, such that switching context both circumvents the need to unbind the previous

conjunction and reduces interference from the previous conjunction.

To measure this, we first ran a modified version of the above RT mixed effects model

where the hierarchical rule switch (Stay/IDS/EDS) was replaced with a variable indicating if

context switched or repeated (2 levels). This allowed us to run a three-way interaction between

context, task, and response, while controlling for all the same additional variables as before. As

expected, we found a significant three-way interaction ($\beta = 0.128$, $t(20930) = 2.142$, $p = .032$).

Post-hoc comparisons revealed that the two-way interaction between task and response, which

reflects partial switch costs, was only significant when context repeated (β = -0.124, $t(20916)$ = -

2.300, p = .022; Fig. 5A), but not when context switched (β = 0.004, $t(20926)$ = 0.065, p = .949;

Fig. 5B). To replicate this result, we ran a follow-up behavioral experiment with the same

experimental paradigm. As expected, we found a significant three-way interaction (β = 0.251,

$t(21690)$ = 4.173, p < .001). Post-hoc comparisons revealed that the two-way interaction between

task and response, which reflects partial switch costs, was only significant when context repeated

(β = -0.247, $t(21704)$ = -4.891, p < .001; Fig. 5C), but not when context switched (β = 0.004,

$t(21687)$ = 0.056, p = .955; Fig. 5D).

622
623   Figure 5. Partial Switch Costs and Context. **A**) Bar plots showing expected partial switch cost
624   effects when context repeats. **B**) Bar plots showing lack of partial switch costs when context
625   switches. Significance based on post-hoc comparisons between estimated marginal means for
626   3way interaction between context, task, and response repeat/switch.
627
The existence of a significant two-way interaction between task and response within

context matches prior findings of partial switch costs (Kikumoto and Mayr, 2020; Rangel et al.,

2023). In contrast, the lack of a significant two-way interaction when switching contexts

suggests that partial switch costs are weakened during context reconfiguration. These results lend

further support to the idea that cognitive flexibility is supported by creating context-specific

conjunctive representations, which enable faster subordinate rule switching within context and

decreased interference when switching across context.

To address the neural underpinnings of partial switch costs indicative of potential

context-specific conjunctive representations, we conducted a parallel analysis with a very similar

regression model to predict neural distance. Key differences were that cue color, shape, and

texture were removed (similar to the regression predicting neural distance reported in 3.1) and

regressors indicating the zRT and zRT difference between adjacent trials were included.

However, we found no significant clusters associated with a three-way interaction between

context, task, and response repeat/switch. This suggests that, although the observed partial switch

cost effect on context repeat trials, but not context switch trials, is robust for response times, its

neural underpinnings likely arise from a combination of distributed neural representations rather

than from anatomically focal, restricted sources.

3.3. Distinct hierarchical level interactions with post-error correction.
647
The above results further implicate error detection and correction processes as operating

over the underlying hierarchical structure of task representations. Error detection and correction

processes must utilize the underlying task representation structure to properly attribute the source

of the error and re-establish the appropriate task representation to guide subsequent behavior.

Although the initial cause of an error has multiple possibilities (e.g., instantiating the wrong

context, erroneous button presses, lapses in attention), post-error correction should be more

uniform in the sense that it re-engages the underlying task representation structure. Therefore,

more effective post-error correction should be accompanied by greater reconfiguration of

multivoxel activity patterns.

To investigate interactions between the underlying hierarchical task representation

structure and error processes, we included error and post-error trials in the regressions predicting

zRTs and neural distance. The average error rate (Fig. 6B-left) was .034 (SE = .004) for Stay

trials, .051 (SE = .005) for IDS trials, and .065 (SE = .006) for EDS trials. Post-error trial

proportions (Fig. 6B-right) were highly similar between task switching conditions (Stay M=.048,

SE=.004; IDS M=.046, SE=.005; EDS M=.053, SE=.005). Consistent with existing literature

(Rabbitt, 1966; McClure et al., 2003), the mixed effects regression predicting zRTs showed

significantly slower zRTs on error trials (*t(20,870)* = 10.504, *p* < .001), and post-error slowing (

t(20,820) = 2.359, *p* = .018). Note, the experimental paradigm reported here provided no

feedback. Therefore, the observed post-error slowing of RTs and greater neural distance

following error trials suggest that participants engaged in internal error monitoring in the absence

of external feedback. To ensure we were looking at error correction on post-error trials, we

restricted analyses to post-error trials where participants performed accurately following an error.

670   The neural distance results showed no significant clusters associated with errors on the

671   current trial. However, post-error trials were associated with significant increases in neural

672   distance in distributed clusters, indicating substantial representational reconfiguration following

673   errors (Fig. 6A). Critically, we observed cortical clusters in mPFC, parahippocampus, as well as

674   subcortical clusters in the basal ganglia and mediodorsal thalamus.

676
677   Figure 6. Errors and Post-error Correction. A) Significant clusters with a larger neural distance
678   on post-error trials B) Error and Post-error trial rates by hierarchical rule condition
679   (Stay/IDS/EDS).

4. Discussion

In this study, we investigated the behavioral (response time) and neural correlates of switch costs associated with hierarchical cognitive control. We were primarily interested in how the reconfiguration of distinct cognitive representations would interact with (1) the underlying hierarchical task representation structure and (2) other systems/processes necessary for goal-directed behavior, such as perceptual or error processes. To address these questions, we combined a hierarchical task design with trial-by-trial behavioral switch cost analyses and a novel multivoxel pattern–based measure of "neural distance", allowing us to characterize both performance costs and representational reconfiguration during hierarchical cognitive control. In the sections that follow, we interpret these findings in the context of existing theories of cognitive control and representational flexibility.

The behavioral phenomenon of performance costs on trials requiring a task switch is well-established (Monsell, 2003; Rogers & Monsell, 1995; Wylie & Allport, 2000; Allport et al., 1994). However, relatively fewer studies have investigated the neural underpinning of behavioral switch costs, particularly how they relate to the internal structure of task representations. A previous study found that greater dissimilarity in multivoxel activity patterns on task switch trials predicted greater response time task switch costs (Qiao et al., 2017). Nevertheless, given the multifaceted nature of task representations (Schumacher & Hazeltine, 2016; Botvinick, 2008), several critical questions remain unresolved: whether representational reconfiguration operates similarly across different hierarchical levels, how abstract contextual representations interact or are interfered with by changes in perceptual input, and whether perceptual and error-related processes shape reconfiguration in ways that support cognitive flexibility. The present study

addresses these gaps by extending a novel neural distance analyses to a hierarchical task

structure that specifically investigates contextual updating and subordinate rule reconfiguration,

allowing us to directly test how different representational levels vary in their susceptibility to

perceptual interference.

A complementary line of work suggests that stimulus-response associations are bound

into an event file (Hommel, 1998, 2004), or conjunction (Kikumoto & Mayr, 2020). When this

integrated sensory-motor representation can be re-used across trials, performance is faster and

more accurate than when this integrated representation needs to be updated. Additionally,

performance is slower and less accurate when there is partial overlap between components across

adjacent trials—commonly referred to as partial switch costs (Grzyb & Hubner, 2013;

Kleinsorge & Heuer, 1999). Despite this, most previous hierarchical control studies have not

systematically investigated whether task-relevant and irrelevant perceptual features repeat or

switch across trials, nor have they examined how such feature-level continuity interacts with

hierarchical task structure. As a result, how different hierarchical levels are differentially affected

by perceptual interference has remained largely unexplored. By considering these factors when

investigating the behavioral and neural correlates of switch costs, the present study reveals novel

findings regarding interactions between the reconfiguration of distinct hierarchical levels and

perceptual interference.

Specifically, we found a clear distinction between context reconfiguration and

subordinate rule reconfiguration in the degree of susceptibility to feedforward perceptual

interference. Subordinate rule reconfiguration showed the greatest amount of feedforward

perceptual influence on reconfiguration processes. When task-irrelevant features changed across

trials, we observed slower RTs and a greater neural distance in distributed regions, notably,

premotor and visual attention regions. Presumably, this increased dissimilarity in trial-to-trial

multivoxel activity patterns when task-irrelevant features changed reflected greater processing of

this irrelevant perceptual event. In contrast, the lack of modulation of neural distance in MFG

(i.e., equally large neural distance regardless of whether task-irrelevant cue features changed)

suggested that context reconfiguration was better shielded from potential feedforward perceptual

interference. Given prior work suggesting MFG encodes high dimensional, abstract, task rule

structures (Badre et al., 2021; Badre & Nee, 2018), this reduced susceptibility to interference is

critical for successful goal-directed behavior.

One explanation for why context reconfiguration appears to be better shielded from

feedforward perceptual interference is that contextual information may organize more lower-

level sensory-motor representations into distinct latent representational spaces. Recent work by

Kikumoto and colleagues (2024) suggests that the control system might encode conjunctive

representations (integrated representations of rules, stimuli, and responses) in distinct latent

subspaces. More specifically, these distinct representational subspaces, indexed by a contextual

cue, can contain context-specific conjunctions that drive cognitive flexibility. Context-specific

conjunctions would allow for a smaller representational distance within context, meaning greater

flexibility, i.e., faster switching, while also shielding the current goal-relevant conjunctions from

interference across contexts. This greater flexibility within context likely drives the observed

partial switch costs when context repeats. The greater representational distance that must be

traveled when switching contextual subspaces could explain the overall slower response times

and lack of partial switch costs when switching context. Presumably, the latter would be due to

the lack of interference from the previous context-specific conjunction. Moreover, the lack of a

robust 3-way interaction between context, task, and response repeat/switch predicting neural

distance suggests that the neural underpinnings of partial switch costs arise form distributed

neural assemblies and not an anatomically focal, or restricted, source.

Organizing task representations into context-specific latent spaces may confer additional

benefits. By separating contexts, our control system can more optimally learn subordinate rules

and their unique stimulus-response associations that are specific to each context. This would

allow for greater context-dependent flexibility while reducing interference across context. Such

representational organization may also support adaptive error processing. Related to this idea, we

observed significant post-error slowing on post-error trials, accompanied by increased neural

distance in the mediodorsal thalamus. It is possible that this increased neural distance reflects

context-related reconfiguration following error detection, whereby the mediodorsal thalamus

contributes to updating or re-engaging the appropriate contextual representation to guide

subsequent behavior. This interpretation is consistent with our prior work demonstrating that the

mediodorsal thalamus encodes contextual information and exhibits signals related to context and

latent state updating during hierarchical cognitive control (Chen et al., 2024; Leach et al., 2025),

suggesting a role for this region in resetting or stabilizing task representations after errors.

The notion that context-dependent cognitive flexibility involves distinct representational

subspaces also points to an interesting avenue for future research with the arousal system.

Hierarchical contexts can be understood as internal control states that govern which sets of task

rules and stimulus–response associations are currently active. Shifting between such contexts

therefore requires coordinated reconfiguration of internal states, rather than simple updating of

stimulus–response mappings. From this perspective, the neuromodulatory systems that facilitate

state transitions may play a critical role in hierarchical cognitive control. For example, Bouret

and Sara (2005) suggest the locus coeruleus (LC) norepinephrine (NE) system acts as a network

reset system, making it easier to shift internal states. Although previous has largely focused on

how this impacts latent, or hidden, state shifting (Nassar, 2024), this same mechanism could

support reconfiguration of contextual representations during hierarchical control. Specifically,

NE release may make it easier to shift, or reconfigure, context by disrupting recurrent activity

maintaining the current context in MFG. If two distinct activity patterns encode each context and

the current context is maintained through recurrent connections, then disrupting this recurrent

activity would make it easier for an external switch signal to shift to the activity pattern encoding

the alternative context. Another explanation is that post-error slowing is context specific because

ongoing associative learning and error correction needs to be context specific. In other words,

errors must be properly attributed to the correct context for optimal goal-directed behavior. This

latter point relates to the literature on latent, or hidden, states, which require predictive inference

specific to distinct latent states (Nassar et al., 2019). The LC/NE system has been proposed to

help with latent state shifting at contextual change points to aid predictive learning (Nassar,

2024). Although the present task utilizes cue objects that explicitly indicate context, it could

engage similar mechanism, including the need to disrupt recurrent PFC activity to aid context

switching and the need to properly assign errors to the appropriate context when engaging error

correction systems. Therefore, future work on hierarchical task control should incorporate

estimates of arousal system activity. For example, how the arousal system might relate to context

reconfiguration, even in the absence of salient error events.

In conclusion, we report three major findings regarding switch costs and hierarchical

cognitive control. First, trial-to-trial reconfiguration of neural activity patterns encoding distinct

hierarchical levels drive observable switch costs. Greater reconfiguration of neural activity

patterns predicted larger observable switch costs. Second, the reconfiguration of distinct

hierarchical representation levels is differentially impacted by feedforward perceptual

information, as is evident through both response time and neural distance measure. More

specifically, subordinate rule representations associated with more concrete sensory-motor plans

prioritized greater flexibility at the cost of greater interference from feedforward perceptual

information. In other words, showing slower response times and greater neural activity pattern

reconfiguration when task irrelevant cue features changed across trials. To counter this increased

interference, contextual representations prioritized shielding information from feedforward

perceptual interference at the cost of reduced flexibility. In other words, showing overall slower

response times and greater neural distance that is not modulated by task-irrelevant cue feature

changes. This likely reflects a balance of cognitive flexibility that maximizes fast and efficient

switching of concrete sensory-motor plans while also shielding internally maintained contextual

rules from interference. Finally, response time switch cost results tentatively suggest this

shielding is achieved by partitioning context into distinct representational, or latent, spaces.

809
810
811

References

Monsell, S. (2003). Task switching. *Trends in Cognitive Sciences, 7*(3), 134-140. doi:10.1016/s1364-6613(03)00028-7

Meiran, N., Chorev, Z., & Sapir, A. (2000). Component processes in task switching. *Cogn Psychol, 41*(3), 211-253. doi:10.1006/cogp.2000.0736

Rogers, R. D., & Monsell, S. (1995). Costs of a predictible switch between simple cognitive tasks. *Journal of Experimental Psychology: General, 124*(2), 207-231. doi:10.1037/0096-3445.124.2.207

Badre, D., Bhandari, A., Keglovits, H., & Kikumoto, A. (2021). The dimensionality of neural representations for control. *Curr Opin Behav Sci, 38*, 20-28. doi:10.1016/j.cobeha.2020.07.002

Badre, D., & D'Esposito, M. (2007). Functional Magnetic Resonance Imaging Evidence for a Hierarchical Organization of the Prefrontal Cortex. *Journal of Cognitive Neuroscience, 19*(12), 2082-2099.

Badre, D., Hoffman, J., Cooney, J. W., & D'Esposito, M. (2009). Hierarchical cognitive control deficits following damage to the human frontal lobe. *Nat Neurosci, 12*(4), 515-522. doi:10.1038/nn.2277

Nee, D. E., & Brown, J. W. (2013). Dissociable frontal-striatal and frontal-parietal networks involved in updating hierarchical contexts in working memory. *Cereb Cortex, 23*(9), 2146-2158. doi:10.1093/cercor/bhs194

Miller, E. K., & Cohen, J. D. (2001). An integrative theory of prefrontal cortex function. *Annual Review Neuroscience, 24*.

Nee, D. E., & D'Esposito, M. (2017). Causal evidence for lateral prefrontal cortex dynamics supporting cognitive control. *Elife, 6*. doi:10.7554/eLife.28040

Geddert, R., & Egner, T. (2024). Contextual control demands determine whether stability and flexibility trade off against each other. *Atten Percept Psychophys, 86*(7), 2529-2551. doi:10.3758/s13414-024-02955-x

Dreisbach, G., & Fröber, K. (2018). On How to Be Flexible (or Not): Modulation of the Stability-Flexibility Balance. *Current Directions in Psychological Science, 28*(1), 3-9. doi:10.1177/0963721418800030

Mayr, U., & Grätz, D. (2024). Does cognitive control have a general stability/flexibility tradeoff problem? *Current Opinion in Behavioral Sciences, 57*. doi:10.1016/j.cobeha.2024.101389

Kikumoto, A., & Mayr, U. (2020). Conjunctive representations that integrate stimuli, responses, and rules are critical for action selection. *Proceedings of the National Academy of Sciences, 117*(19), 10603-10608. doi:10.1073/pnas.1922166117

Kikumoto, A., Bhandari, A., Shibata, K., & Badre, D. (2024). A transient high-dimensional geometry affords stable conjunctive subspaces for efficient action selection. *Nat Commun, 15*(1), 8513. doi:10.1038/s41467-024-52777-6

Cellier, D., Petersen, I. T., & Hwang, K. (2022). Dynamics of Hierarchical Task Representations. *J Neurosci, 42*(38), 7276-7284. doi:10.1523/JNEUROSCI.0233-22.2022

Schumacher, E. H., & Hazeltine, E. (2016). Hierarchical task representation: Task files and response selection. *Current Directions in Psychological Science, 25*(6), 449-454. doi:10.1177/0963721416665085

Dykstra, T., Smith, D. M., Schumacher, E. H., & Hazeltine, E. (2022). Measuring task structure
with transitional response times: Task representations are more than task sets. *Psychon*
Bull Rev, 29(5), 1812-1820. doi:10.3758/s13423-021-02035-3
Wylie, G., & Allport, A. (2000). Task switching and the measurement of switch costs.
Psychological Research, 63, 21.
Ebitz, R. B., & Hayden, B. Y. (2021). The population doctrine in cognitive neuroscience.
Neuron, 109(19), 3055-3068. doi:10.1016/j.neuron.2021.07.011
Mur, M., Bandettini, P. A., & Kriegeskorte, N. (2009). Revealing representational content with
pattern-information fMRI--an introductory guide. *Soc Cogn Affect Neurosci, 4*(1), 101-
109. doi:10.1093/scan/nsn044
Qiao, L., Zhang, L., Chen, A., & Egner, T. (2017). Dynamic Trial-by-Trial Recoding of Task-Set
Representations in the Frontoparietal Cortex Mediates Behavioral Flexibility. *J Neurosci,*
37(45), 11037-11050. doi:10.1523/JNEUROSCI.0935-17.2017
Chen, X., Leach, S. C., Hollis, J., Cellier, D., & Hwang, K. (2024). The thalamus encodes and
updates context representations during hierarchical cognitive control. *PLoS Biol, 22*(12),
e3002937. doi:10.1371/journal.pbio.3002937
Esteban, O., Markiewicz, C. J., Blair, R. W., Moodie, C. A., Isik, A. I., Erramuzpe, A., . . .
Gorgolewski, K. J. (2019). fMRIPrep: a robust preprocessing pipeline for functional
MRI. *Nat Methods, 16*(1), 111-116. doi:10.1038/s41592-018-0235-4
Fonov, V., Evans, A. C., Botteron, K., Almli, C. R., McKinstry, R. C., & Collins, D. L. (2011).
Unbiased average age-appropriate atlases for pediatric studies. *Neuroimage, 54*.
doi:10.1016/j.neuroimage.2010.07.033314
Prince, J. S., Charest, I., Kurzawski, J. W., Pyles, J. A., Tarr, M. J., & Kay, K. N. (2022).
Improving the accuracy of single-trial fMRI response estimates using GLMsingle. *Elife*.
doi:10.7554/eLife.77599
Kay, K. N., Rokem, A., Winawer, J., Dougherty, R. F., & Wandell, B. A. (2013). GLMdenoise: a
fast, automated technique for denoising task-based fMRI data. *Front Neurosci, 7*, 247.
doi:10.3389/fnins.2013.00247
Walther, A., Nili, H., Ejaz, N., Alink, A., Kriegeskorte, N., & Diedrichsen, J. (2016). Reliability
of dissimilarity measures for multi-voxel pattern analysis. *Neuroimage, 137*, 188-200.
doi:10.1016/j.neuroimage.2015.12.012
Rabbitt, P. A. (1966). Errors and error correction in choice-response tasks. *Journal of*
Experimental Psychology, 71(2).
McClure, S. M., Berns, G. S., & Montague, P. R. (2003). Temporal prediction errors in a passive
learning task activate human striatum. *Neuron, 38*.
Grzyb, K. R., & Hubner, R. (2013). Excessive response-repetition costs under task switching
How response inhibition amplifies response conflict. *Journal of Experimental*
Psychology: Learning, Memory, and Cognition, 39, 13.
Kleinsorge, T., & Heuer, H. (1999). Hierarchical switching in a multi-dimensional task space.
Psychological Research, 62, 12.
Li, J., Cao, B., Han, J., Xie, L., & Li, F. (2019). Not inertia but reconfiguration: Asymmetric
switch cost in a hierarchical task. *Brain Res, 1720*, 146291.
doi:10.1016/j.brainres.2019.06.010
Mumford, J. A., Bissett, P. G., Jones, H. M., Shim, S., Rios, J. A. H., & Poldrack, R. A. (2024).
The response time paradox in functional magnetic resonance imaging analyses. *Nat Hum*
Behav, 8(2), 349-360. doi:10.1038/s41562-023-01760-0

Cox, R. W., Chen, G., Glen, D. R., Reynolds, R. C., & Taylor, P. A. (2017). fmri clustering and
false-positive rates. *PNAS, 114*(17), 2. doi:10.1073/pnas.1614961114Fig
Badre, D., & Nee, D. E. (2018). Frontal Cortex and the Hierarchical Control of Behavior. *Trends*
in Cognitive Science, 22(2), 170-188. doi:10.1016/j.tics.2017.11.005
Nee, D. E., & D'Esposito, M. (2016). The hierarchical organization of the lateral prefrontal
cortex. *Elife, 5*, e12112. doi:10.7554/eLife.12112
Badre, D., & Frank, M. J. (2012). Mechanisms of hierarchical reinforcement learning in cortico-
striatal circuits 2: evidence from fMRI. *Cereb Cortex, 22*(3), 527-536.
doi:10.1093/cercor/bhr117
Allport, A., Styles, E. A., & Hsieh, S. (1994). Shifting intentional set Exploring the dynamic
control of tasks.
Botvinick, M. M. (2008). Hierarchical models of behavior and prefrontal function. *Trends Cogn*
Sci, 12(5), 201-208. doi:10.1016/j.tics.2008.02.009
Hommel, B. (1998). Event Files: Evidence for Automatic Integration of Stimulus-Response
Episodes. *Visual Cognition, 5*(1-2), 183-216. doi:10.1080/713756773
Hommel, B. (2004). Event files: feature binding in and across perception and action. *Trends*
Cogn Sci, 8(11), 494-500. doi:10.1016/j.tics.2004.08.007
Nassar, M. R. (2024). Toward a computational role for locus coeruleus/norepinephrine arousal
systems. *Curr Opin Behav Sci, 59*. doi:10.1016/j.cobeha.2024.101407
Nassar, M. R., Bruckner, R., & Frank, M. J. (2019). Statistical context dictates the relationship
between feedback-related EEG signals and learning. *Elife, 8*. doi:10.7554/eLife.46975
925
926

Acknowledgments

Author contributions: SCL wrote the first draft of the paper, SCL and KH edited the

paper, KH and SCL designed research, SCL and XC performed research, SCL and KH analyzed

data, SCL wrote the paper.

Authors declare that they have no competing interest.

All data and code will be made available upon publication.

Research reported here was supported by a National Institutes of Mental Health grant

R01MH122613 (KH) and the Iowa Neuroscience Institute. This work was conducted on an MRI

instrument funded by 1S10OD025025-01

Figure 1. Hierarchical control task design. A) Depiction of the task rule hierarchy embedded

within the 8 potential cue objects. B) Example trial sequence: A cue object presented for 500ms

followed by an image of either a face or a scene for 2000ms and a jittered ITI (range: 1.5-10.5

seconds; average: 4.25 seconds. Example cue transitions across trials depicts how perceptual

change is operationalized. Example face image is an author on this manuscript.

Figure 2. Neural Distance Method. A) depiction of how neural distance is calculated on adjacent

trial multivoxel activity patterns. A greater change in multivoxel activity patterns is associated

with a greater correlation, or neural distance.

Figure 3. Response Time Switch Costs. **A**) Depiction of switch cost predictions for a hierarchical

representation structure (top) and cognitive flexibility predictions for a more fine-grained switch

cost analysis (bottom). **B**) Switch cost analyses comparing hierarchical rule switch conditions.

Significance is based on two-tailed paired sample t-tests with zRTs. **C**) Switch cost comparisons

from the interaction between the hierarchical rule (Stay/IDS/EDS) and the number of features

that changed from the last trial (perceptual change). Significance is based on post-hoc

comparisons between estimated marginal means for hierarchical rule (Stay/IDS/EDS) and

perceptual change.

Figure 4. Neural Distance. **A**) Depiction of expected effects for context reconfiguration versus

subordinate rule reconfiguration. **B**) Observed main effect of context reconfiguration contrasted

with subordinate rule reconfiguration—significant clusters in MFG and IFS, regions belonging to

the control and salient/ventral attention networks. Note, there were no significant clusters for the

main effect of subordinate rule contrasted with stay (rule repeat) trials. **C-D**) Interactions

between perceptual change (i.e., number of cue object features changing across trials; range 0-3)

and subordinate rule reconfiguration (**C**) or rule repeat (Stay) trials (**D**). **E**) Main effect of

perceptual change. **F**) Bar plots depicting overlap between significant clusters from **B-E** and the

Yeo 17 networks.

Figure 5. Partial Switch Costs and Context. **A**) Bar plots showing expected partial switch cost

effects when context repeats. **B**) Bar plots showing lack of partial switch costs when context

switches. Significance based on post-hoc comparisons between estimated marginal means for

3way interaction between context, task, and response repeat/switch.

Figure 6. Errors and Post-error Correction. A) Significant clusters with a larger neural distance

on post-error trials B) Error and Post-error trial rates by hierarchical rule condition

(Stay/IDS/EDS).