8   **Hierarchical Reconfiguration of Neurocognitive Task Set Representations Mediates**

9   **Cognitive Flexibility**

11   Stephanie C. Leach[1,2] *, Xitong Chen[1,2], and Kai Hwang[1,2]

13   [1] Psychological and Brain Sciences, The University of Iowa, Iowa City, IA.

14   [2] Cognitive Control Collaborative (CCC).

16   * Corresponding Author

17   E-mail: stephanie-leach@uiowa.edu

47 pages

5 figures

249 words abstract

677 words introduction

1445 words discussion

Abstract
25

Cognitive control organizes abstract contexts, stimuli, and actions into hierarchically structured

representations. This organization supports flexible behavior but requires updating at multiple

levels of the hierarchy, a process reflected in task switch costs. However, it remains unclear how

updating differs across levels of abstraction and how these differences relate to behavior and

neural representations. Here, we investigated the behavioral and neural sources of switch costs

using fMRI and behavioral data from healthy adult participants (male and female). We employed

a hierarchical control task that dissociates abstract context reconfiguration from more concrete

task-set reconfiguration of stimulus-response mappings. We predicted that task sets, which

incorporate sensory–motor mappings, would be more strongly influenced by feedforward inputs

than higher-level contextual goals, which are more abstracted from immediate perceptual and

motor demands. As predicted, subordinate rule switches were faster and were more strongly

influenced by task-irrelevant perceptual changes, whereas context switches were slower and

relatively insensitive to such interference. To characterize the neural basis of these effects, we

quantified trial-to-trial reconfiguration of multivoxel activity patterns. Across the brain, larger

pattern shifts predicted larger RT switch costs, linking representational reorganization to

behavioral performance. Importantly, representational reconfiguration differed across

hierarchical levels and anatomical systems. Subordinate rule updating was modulated by task-

irrelevant perceptual features and expressed in distributed perceptual and motor networks,

whereas context reconfiguration engaged the mid-lateral frontal cortex and was comparatively

insulated from interference. Our results reveal how the hierarchical structure of neural

representations supports flexible updating with interference-shielded contextual representations

subserving behavioral control.

Significance

Daily activities often require simultaneously updating different tasks and thoughts.

Driving requires maintaining a stable destination goal while rapidly updating motor plans (brake,

accelerate, turn, etc.) in response to changing perceptual information (traffic lights, pedestrians,

etc.). Although people perform such tasks with ease, it remains unclear how neural and cognitive

representations are structured to respond to these flexibility demands. The present study suggests

that sensory-motor plans prioritize flexibility by allowing greater influence from sensory inputs,

which can create interference across brain networks when that input is task-irrelevant.

Contextual information is insulated from this interference by representing contexts as distinctly

as possible in the lateral prefrontal cortex, resulting in slower but more stable context switching.

1. Introduction
60
Everyday tasks require maintaining/updating multiple cognitive representations to

support flexible, goal-directed behavior. For example, driving involves maintaining an

overarching destination goal while continuously updating route plans and switching between

accelerating and braking in response to dynamic sensory inputs. These representations operate at

different levels of abstraction. Task sets specify stimulus–response mappings and therefore likely

incorporate perceptual and motor representations tied to current sensory inputs, whereas

contextual representations are more abstract and rely on internally maintained goals and memory

(Badre & D'Esposito, 2007; Sakai, 2008). This organization introduces a core challenge: to

support flexibility, control systems must update representations that differ in levels of abstraction

and sensitivity to feedforward sensory inputs. Understanding how this flexibility is achieved

requires characterizing the representational structures encoded in the brain that implement

cognitive control (Monsell, 2003; Rogers & Monsell, 1995; Badre et al., 2021).

The structure of control representations encoding goals, contexts, task sets, stimuli, and

actions shapes cognitive flexibility. Contextual representations, often attributed to the rostral

portions of mid-lateral prefrontal cortex (Badre & D'Esposito, 2007; Badre et al., 2009; Nee &

Brown, 2013), are assumed to bias downstream processes to prioritize task-relevant information

for hierarchical control (Miller & Cohen, 2001; Nee & D'Esposito, 2017). Such biasing can

prioritize shielding representations from interference (Sakai et al., 2002), while enabling flexible

updating as contexts change and attention is redirected (Cellier et al., 2022), including the

selection of task-relevant rule–stimulus–response conjunctions (Kikumoto & Mayr, 2020).

Flexibility may therefore depend on how abstract contexts organize representations that differ in

their sensitivity to feedforward inputs (Schumacher & Hazeltine, 2016).

The structure of control representations can be probed by examining trial-to-trial

reconfiguration (Dykstra et al., 2022; Bustos et al., 2024). Behavioral paradigms have

traditionally examined reconfiguration via response time (RT) switch costs—the additional time

it takes to make a response when a task changes from one trial to the next (Monsell, 2003;

Rogers & Monsell, 1995; Wylie & Allport, 2000). Because internal representations constrain

observable behavior, systematic variation in switch costs can reveal their underlying structure.

We therefore hypothesize that the extent to which control representations incorporate sensory–

motor features will influence their sensitivity to feedforward interference. If task sets are closely

tied to perceptual and motor features, then task-irrelevant perceptual changes should exert

greater influence on switch costs. In contrast, if context cues specifying task sets are more

abstracted away from perceptual and motor representations, then context switch costs should be

less sensitive to task-irrelevant perceptual changes.

Although switch costs provide a behavioral readout of reconfiguration processes, their

neural basis remains unclear. Recent work suggests information is encoded in distributed activity

patterns across neuron populations, voxels, or electrodes (Ebitz & Hayden, 2021; Mur et al.,

2009). Under this population view, cognitive flexibility entails transforming one activity pattern

into another. The magnitude of this transformation can be quantified as the multivariate

similarity between activity patterns on successive trials, in which a larger dissimilarity reflects

greater representational reorganization and predicts greater RT switch costs (Qiao et al., 2017).

Building on these findings, we hypothesize that representations closer to perceptual and motor

features may undergo smaller reconfiguration, whereas the more abstract contextual

representations cuing these task-sets are encoded in more distinct patterns. Such representational

organization provides a potential mechanism through which hierarchical structure supports

cognitive flexibility.

Given these hypotheses, our study pursued two main goals. First, we used RT switch

costs to determine how the reconfiguration of distinct hierarchical control representations is

influenced by both the hierarchical structure of the task and feedforward perceptual influences.

Second, we quantified trial-to-trial shifts in multivoxel activity patterns, which we refer to as

"multivoxel pattern shifts", to examine neural correlates of this representational reconfiguration

and feedforward perceptual influence. Results confirmed that larger pattern shifts predicted

larger RT switch costs. Moreover, representational reconfiguration differed across hierarchical

levels in its sensitivity to perceptual input. Increased feedforward perceptual influence modulated

subordinate rule selection but not contextual rule selection. Therefore, results suggest that

contextual representations organize task sets and rule–stimulus–response conjunctions in a way

that limits interference from task-irrelevant perceptual information.

2. Methods
120
2.1. Participants. Participants were recruited for two experiments, experiment 1 involved

MRI scanning, and experiment 2 was a behavioral only experiment conducted to replicate in-

scanner behavioral effects. For experiment 1, we recruited 73 healthy participants (53 female, 20

male, $M_{age} = 22.31$, $SD_{age} = 4.45$, $Range_{age} = 18$-35 years). Out of these 73 participants, 10 were

excluded for poor behavioral performance (accuracy < 75% for at least one condition), and 9

were excluded for excessive movement artifacts (mean framewise displacement > 0.4 mm across

runs). After exclusion, we included data from 54 participants (39 female, 15 male, $M_{age} = 22.38$,

$SD_{age} = 4.87$, $Range_{age} = 18$-35 years). These data were also published in our previous study

(Chen et al., 2024). For experiment 2, we recruited 65 healthy participants (55 female, 9 male, 1

non-binary, $M_{age} = 18.63$, $SD_{age} = 0.71$, $Range_{age} = 18$-21 years). Out of these 65 participants, 8

were excluded for poor behavioral performance (accuracy < 75% for at least one condition).

After exclusion, we included data from 57 participants (50 female, 7 male, $M_{age} = 18.63$, $SD_{age} =$

0.72, $Range_{age} = 18$-21 years). Both experiments were approved by the University of Iowa

Institutional Review Board. All participants were recruited from the University of Iowa and

surrounding area to participate. All participants had normal or corrected to normal visual acuity

and color vision, were right-handed, and with no history of epilepsy, psychiatric, or neurological

conditions. All participants gave written informed consent. The experiments were conducted in

compliance with the ethical principles expressed in the Declaration of Helsinki.

2.2. MRI data Acquisition. Imaging data were collected at the Magnetic Resonance

Research Facility at the University of Iowa using a 3T GE SIGNA Premier scanner with a 48-

channel head coil. Structural images were acquired using a multi-echo MPRAGE sequence (TR

= 2348.52ms; TE = 2.968ms; flip angle = 8°; field of view = 256*256; 200 sagittal slices; voxel

size = 1mm^3). Functional images were acquired using an echo-planar sequence sensitive to blood

oxygenated level-dependent (BOLD) contrast (Multiband acceleration factor = 2; no in-plane

acceleration; TR = 1800ms; TE = 30ms; flip angle = 75°; voxel size = 1.718 mm*1.718mm *2.5

mm).

2.3. MRI Data Preprocessing. All fMRI data were preprocessed using fMRIPrep

version 20.1.1 (Esteban et al., 2019) to reduce noise and transform data from subject native space

to the ICBM 152 Nonlinear Asymmetrical template version 2009c for group analysis (Fonov et

al., 2011). Preprocessing steps include bias field correction, skull-stripping, co-registration

between functional and structural images, tissue segmentation, motion correction, and spatial

normalization to the standard space. We did not perform any spatial smoothing and did not apply

conventional nuisance regression. Instead, noise suppression was implemented during within the

GLMsingle procedure (Prince et al., 2022). GLMsingle combines voxel-wise GLM estimation

with automated denoising procedures from GLMdenoise (Kay et al., 2013), which uses cross-

validation to identify and apply the optimal combination of nuisance regressors. Nuisance

regressors, motion estimates, and principal components were learned to best improve cross-

validation performance from whole-brain regions of interest. The framework also estimates

single-trial beta weights while correcting for temporal autocorrelation and optimizing the

hemodynamic response function on a voxel-wise basis (see section 2.7). This approach provides

improved sensitivity and reliability for our trial-by-trial transition analyses.

2.4. Experimental Design. In experiment 1, participants underwent an fMRI scanning

session while performing a hierarchical cognitive control task. Before entering the scanner, all

participants completed a tutorial and a practice session. Once participants achieved at least 80%

on the practice, the experiment's scanning session began. We collected eight runs of functional

scans, with each run consisting of 51 task trials. This resulted in a total of 408 task trials across

all eight runs. Each functional run lasted approximately 6.5 minutes. In experiment 2,

participants performed the same hierarchical cognitive control task behaviorally with the same

training procedure, trial timing, block structure, and number of trials. The purpose was to

replicate the behavioral effects we observed in scanner.

2.5. Behavioral Tasks. To study the representation structure for flexible hierarchical

cognitive control, we developed a hierarchical cognitive control task (Chen et al., 2024). The

task implements a three-level hierarchy in which texture defines context, context determines the

relevant feature dimension (color or shape), and the feature dimension maps onto a response rule.

2.5.1. *Task structure and trial sequence*. In this task, each trial began with a cue object

presented for 500 milliseconds, followed by an image of either a face or a scene presented for

2000 milliseconds (**Figure 1A**). The inter-trial interval (ITI) was jittered between 1.5 to 10.5

seconds with an average duration of 4.25 seconds. Depending on the cue object presented before

the image, participants made a yes/no judgment on one of two response rules: (1) was the image

a face? (2) was the image a scene? The luminance of probe images (faces/scenes) was equalized

using the SHINE toolbox (Willenbockel et al., 2010). Face images included a scrambled

background to control for low level spatial frequency to match the scene images. Probe images

were randomly selected from a set of 50 unique faces and 50 unique scene images. Finally, we

ensured that adjacent trials never used the exact same face or scene image.

2.5.2. *Hierarchical rule structure*. To determine which response rule to use on a given

trial, participants had to integrate three sources of information associated with three perceptual

features of the cue object: texture, shape, and color (**Figure 1B**). The cue's texture determined

whether the response rule was signaled by shape or color. If the texture of the cue object was

filled in, the shape of the object (square or circle) would indicate which rule they needed to use

(square being the face rule, "is the image a face?", and circle being the scene rule, "is the image a

scene?"). Alternatively, if the texture of the cue object was hollow (i.e., only an outline), the

color of the object (red or blue) would indicate which rule they needed to use (blue being the

face rule and red being the scene rule). Half of the participants completed a counterbalanced

version of this task with alternative yes/no response key mappings, and in which the top level of

the hierarchy was flipped (i.e., hollow texture cues shape and filled texture cues color).

Figure 1. Hierarchical control task design.

A) Depiction of the task rule hierarchy embedded within the 8 potential cue objects. Context switch (EDS) trials reflect switching between the shape and color rule, or switching between a filled and hollow cue object. Subordinate rule switch (IDS) trials reflect repeating context, but switching between either circle and square or red and blue, depending on the context rule (shape or color). Finally, Stay trials are trials where both context and subordinate rule repeat.

B) More detailed depiction of perceptual change showing eight possible transitions following a trial with a filled, blue, circle cue object. Across trials, 0-3 features could change.

C) Example trial sequence: a cue object is presented for 0.5 seconds, followed by an image of either a face or a scene for 2 seconds, and a jittered ITI (range: 1.5-10.5 seconds; average: 4.25 seconds). Example cue transitions across trials depicts how perceptual change is operationalized. The first Stay trial shows a cue transition with 0 features changing. The second Stay trial shows a cue transition where one cue feature changes (shape, a task-irrelevant feature in this example). The EDS trial shows a cue transition where all three cue features change. The IDS trial shows a cue transition where two features change (shape, task-relevant; color, task-irrelevant). Example face images are authors on this manuscript.

2.5.3. *Hierarchical rule switching*. This task design yields three types of trial-to-trial

transitions that differ in the level of hierarchical reconfiguration required: Stay, intra-dimension

switch (IDS), and extra-dimension switch (EDS). On Stay trials, participants repeated the same

rule as the previous trial, preserving both the texture-defined context and feature-to-rule mapping

(e.g., which color or shape indicates the face task). On IDS trials, participants switched between

task-relevant features (shape vs. color) within the same texture context. On EDS trials, they

updated the highest-level context by switching texture cues (filled vs. hollow), thereby changing

which feature signaled the response rule.

2.5.4. *Trial-to-trial transitions, perceptual, and motor factors*. In addition to hierarchical

rule switching, the task design allowed us to quantify trial-to-trial perceptual and motor

influences on performance. Specifically, (1) whether the texture, shape, or color of the cue object

repeated from the previous trial, (2) how many cue object features changed (range: 0-3; **Figure**

1C) and (3) how these factors interacted with rule switching, (4) whether the motor response

repeated, (5) whether the targeted, relevant feature repeated or switched from the previous trial.

Here, previous target feature refers to the specific cue feature (i.e., red, blue, circle, or square)

that defines the task rule. For example, if the current subordinate rule is the color rule and the

current cue object is red, then the targeted, relevant feature is "red". If on the next trial the

current subordinate rule is the shape rule, but the cue object is still red, then the targeted relevant

feature from the previous trial repeated even though the subordinate rule switched. As described

in detail below, we used linear regression to quantify the influence of each factor on response

times and reconfiguration on voxel activity patterns.

2.5.5 *Behavioral (Response Time) Switch Costs.* To quantify behavioral costs associated

with hierarchical task reconfiguration, we analyzed trial-wise response times using linear mixed-

effects regression. This approach allowed us to estimate the contributions of hierarchical rule

switching, perceptual feature transitions, and motor processes to performance costs while

accounting for repeated measurements within subjects.

2.6. Trial-to-Trial Shifts in Multivoxel Activity Patterns. The goal of this analysis was

to characterize how neural activity patterns that instantiate cognitive task representations are

reconfigured from trial to trial. To this end, we quantified trial-to-trial changes in multivoxel

BOLD activity patterns and examined how these representational shifts from trial-to-trial

(hereafter described as "multivoxel pattern shifts" or "pattern shifts"; Fig. 2). Using the same

analytical logic as our behavioral switch cost analysis, we fitted regression models to pattern

shifts to determine how reconfiguration was influenced by hierarchical task structure as well as

perceptual and motor factors. This analysis included a multistep pipeline consisting of trial-wise

activity estimation, computation of multivariate pattern similarity, and regression-based

modeling that paralleled to the behavioral switch-cost analysis.

A) Measuring trial-to-trial pattern shifts

B) Relationship between representational distance and multivoxel pattern shifts

255
Figure 2. Multivoxel Pattern Shifts Method.
A) Depiction of how pattern shifts are calculated on adjacent trial multivoxel activity patterns. A
greater change in multivoxel activity patterns is associated with a greater correlation, or
similarity.
B) Depiction of relationship between pattern shifts and representational distance. In general, a
larger representational distance should result in a greater pattern shift while a smaller
representational distance should result in a smaller pattern shift.

2.6.1. *Trial-wise activity estimate*. Preprocessed fMRI time-series (outputs of fMRIPrep)

were first submitted to GLMsingle (Prince et al., 2022) to estimates trial-wise beta estimates.

GLMsingle fits a general linear model (GLM) with one regressor per trial and uses cross-

validation to improve estimation. Specifically, voxel-wise noise regressors are derived from the

data and evaluated on held-out runs, and a regularized (ridge) regression model is fit with the

regularization parameter (λ) selected via cross-validation. This approach reduces collinearity

among adjacent trial estimates and improves the stability of single trial β values. In addition,

GLMsingle estimates a voxel-specific hemodynamic response function (HRF), allowing the

model to account for regional differences in neurovascular coupling rather than assuming a fixed

HRF across the brain. The model was implemented with a 0.5 s event duration corresponding to

cue onset, because there was no temporal jitter between the cue and probe stimuli, the estimated

responses reflect activity across the entire trial. A library of gamma functions with varying

shapes was used to identify the best-fitting HRF for each voxel to fully capture responses to cue

and probe objects. At the end, this procedure yielded one amplitude estimate per trial per voxel.

To ensure that variability in RT did not drive the multivoxel pattern shifts, we regressed each

trial's RT from its corresponding amplitude estimate on a voxel-by-voxel basis before further

analyses.

2.6.2. Multivoxel Pattern Shifts. Using these RT-corrected trial-wise maps, we then

calculated multivariate distances between trial-wise activity patterns. This was done with an 8

mm radius volumetric searchlight analysis, restricting to gray matter voxels. Within each

searchlight sphere, signals were first "whitened" by applying the noise covariance matrix

(equation 1) estimated across all trials and voxels in that sphere to remove shared noise

correlations (equation 2) before measuring pattern shifts (Walther et al., 2016).

287
$$\Sigma = \frac{1}{T} R^T R$$
(eq 1)

288   Where R is the model residuals matrix of size T x P. Note, T is the number of time points

289   and P is the number of voxels. The covariance matrix, Σ, is size P x P.

290
$$b_k^* = b_k \Sigma^{-\frac{1}{2}}$$
(eq 2)

291   Where b_k is a searchlight sphere multivoxel activity pattern of size P corresponding to

292   one condition, k, of the possible K conditions.

293   This procedure removes voxel-wise correlations attributable to shared noise. We then computed

294   the correlation distance (equations 3 and 4) between consecutive trials:

295
$$d_{cosine}(b_k, b_j) = 1 - \frac{\langle b_k, b_j \rangle}{\|b_k\| \|b_j\|} = 1 - \cos(\angle b_k b_j)$$
(eq 3)

296   Where b_j is a searchlight sphere multivoxel activity pattern of size P corresponding to one

297   condition, j, of the possible K conditions.

298
$$b_k = b_k - \bar{b}_k 1$$

299
$$b_j = b_j - \bar{b}_j 1$$

300
$$d_{correlation}(b_k, b_j) = 1 - \frac{\langle \tilde{b}_k, \tilde{b}_j \rangle}{\|\tilde{b}_k\| \|\tilde{b}_j\|} = 1 - \cos(\angle \tilde{b}_k, \tilde{b}_j)$$
(eq 4)

Where 1 is a row vector of ones of size 1xP and $\bar{b}$ is the voxel mean.

Correlation distance was chosen over Euclidean or Mahalanobis metrics because we were

primarily interested in changes in the neural representation geometry rather than overall

amplitude shifts. This procedure yielded, for each voxel, a time series of pattern shifts values

reflecting trial-to-trial representational reconfiguration.

2.7. Statistical Analyses

2.7.1 Behavioral Model overview. The primary goal of the behavioral linear mixed

effects model (Bates et al., 2015) was to identify factors that influence response time switch

costs during hierarchical cognitive control. Specifically, the model tested how performance costs

varied as a function of (1) the level of hierarchical rule reconfiguration (Stay, IDS, EDS), (2)

trial-to-trial changes in perceptual cue features, and (3) interactions between hierarchical

switching and perceptual change. Additional regressors were included to control for known

effects of motor repetition, task repetition, and error-related adjustments.

2.7.2. Behavioral preprocessing and dependent variable (z-scored response times). The

dependent variable was trial-wise response time, normalized as z-scored response times (zRTs).

Specifically, we first normalized each participants' RT within each experimental block and

response modality (i.e., yes versus no response). When normalizing RTs we did not include error

or post-error trials when calculating the mean or standard deviation because of extensive work

showing error and post-error slowing effects (Rabbitt, 1966; McClure et al., 2003). We then

applied the following exclusion criteria: (1) the first trial of each run, (2) any zRTs exceeding 3

standard deviations from the mean, (3) any trials with missing responses, (4) any post-error trials

that were also erroneous.

2.7.3. Primary behavioral model predictors. For the model regressors, we included the

following fixed effects. First, we included hierarchical task switching (Stay, IDS, EDS) as a

categorical predictor to capture the effects of abstract rule structures on performance cost. To

determine how perceptual representations of the cue attributes influence switch costs beyond

abstract rules, we incorporated several perceptual factors: cue texture, color, and shape, along

with the number of features that changed from the previous trial (range: 0-3).

We further included an additional binary regressor indicating whether the target feature

repeated or switched from the previous trial. For example, if the relevant feature on trial N-1

was color (red), the target feature was coded as "repeated" if the cue on trial N was also red, and

"switched" if the cue was a different color (e.g., blue). This regressor indexed how the previous

trial's task-relevant perceptual representation influences current trial performance.

Critically, we included an interaction between hierarchical task switching and the number

of perceptual features that changed from the previous trial. This critical interaction tested our

hypotheses about flexibility prioritization. If lower-level rule representations prioritize

flexibility, we expected a significant positive interaction between IDS trials and feature change

count, given that a greater number of perceptual features changing meant task-irrelevant features

were also changing. Conversely, if contextual representations prioritize stability, we expected no

significant interaction between EDS trials and feature change.

2.7.4. Behavioral model control variables and conjunction related interactions. To

account for known influences on response times, we included several control variables: task-rule

repetition vs. switch, yes/no response repetition vs. switch, and probe-image repetition vs.

switch. We also controlled for trial-by-trial performance fluctuations by including separate

regressors for post-error trials and error trials to account for post-error slowing effects.

Beyond controlling for nuisance variance, the model incorporated a set of theoretically

motivated interaction terms to replicate established task-switching effects. In particular, prior

work suggests that flexible behavior is supported by conjunctive representations that integrate

task rules, stimuli, and responses, and that the strength of such conjunctions can be indexed

indirectly through partial switch costs (Kikumoto & Mayr, 2020; Grzyb & Hubner, 2013;

Kleinsorge & Heuer, 1999). Partial switch costs arise when some, but not all, components of a

task representation change across trials, requiring unbinding and rebinding of the prior

conjunction (Li et al., 2019). Therefore, we further included a theoretically motivated interaction

term: task-rule repetition with response repetition. This interaction terms tests the canonical

partial switch costs, characterized by faster responses on full repetition and full switch trials

relative to partial repetition/switch trials (Grzyb & Hubner, 2013; Kleinsorge & Heuer, 1999).

Because this interaction term indexing conjunction related effects could differ as a

function of hierarchical context, we ran a second mixed effects regression model where we

replaced hierarchical switch type (Stay/IDS/EDS) with a binary regressor indicated in context

repeated or switched. This further allowed us to include two-way interactions between (1)

context repeat and task repeat and (2) context repeat and response repeat, as well as the 3-way

interaction of primary interest: context repeat by task repeat by response repeat. If contextual

representations organize lower-level task sets, i.e., task rule–stimulus–response associations, then

partial switch costs should primarily occur within contexts and be weaker across contexts. In

other words, we should observe a significant three-way interaction between context, task, and

response that is driven by the existence of (1) a significant two-way interaction between task and

response within context, but (2) a non-significant two-way interaction between task and response

when switching across context.

2.7.5. Behavioral model random effects structure. We treated subject as a random

intercept and estimated random slopes for each individual cue feature (color, shape, and texture)

to capture individual differences in sensitivity to these perceptual factors. Due to the complexity

of the model, we kept the random effects structure as simple as possible to avoid convergence

issues. The full model was specified as:

$zscoredRT = \beta_0 + \beta_1 Error_1 + \beta_2 PostError_2 + \beta_3 PerceptualChange_3 +$

$\beta_4 HierarchicalSwitchType_4 + \beta_5 TaskSwitch_5 + \beta_6 ResponseSwitch_6 +$

$\beta_7 ProbeSwitch_7 + \beta_8 PreviousTargetFeatureSwitch_8 + \beta_9 Color_9 + \beta_{10} Shape_{10} +$

$\beta_{11} Texture_{11} + \beta_{12} PerceptualChange_3 * HierarchicalSwitchType_4 + \beta_{13} TaskSwitch_5 *$

$ResponseSwitch_6 + (1 + Color + Shape + Texture \mid subject)$ (eq 5)

2.7.6. Behavioral (response time) supplementary analysis. It is important to note a subtle

difference between IDS and EDS trials regarding trials where two features changed. For IDS, a

two-feature change always reflects a change in both a task-relevant and task-irrelevant feature. In

contrast, a two-feature change on EDS trials does not always mean a change in one relevant and

one irrelevant feature. Sometimes a two-feature change on EDS trials means two relevant

features change and no task-irrelevant features change. Therefore, we ran an additional follow-up

paired samples t-test where we ensure EDS trials where two features changed were restricted to

only trials where one feature was task-relevant and the other was task-irrelevant. We then

contrasted these trials with trials where only one task-relevant feature changed.

2.7.7 Regression model for pattern shifts. For each subject, the pattern shift time series

was entered as the dependent variable in a linear regression model closely paralleling the

behavioral model described in above. The primary predictors included hierarchical task-

switching condition (Stay, IDS, EDS), perceptual feature-change variables, motor repetition,

error and post-error indicators, and their theoretically motivated interactions. Unlike the

behavioral model, regressors indexing the absolute texture, color, or shape of the current trial's

cue were not included because the dependent variable was a measure of dissimilarity between the

current trial and previous trial, whereas the behavioral model's dependent variable was a

measure of the magnitude of the current trial's performance cost.

To further control for potential RT effects on the BOLD response (Mumford et al., 2024),

which was used to calculate pattern shifts, we added a regressor reflecting the magnitude of trial-

to-trial changes in zRT (difference in zRT across adjacent trials) and a regressor reflecting the

magnitude of the current trial's zRT . The model was specified as:

$pattern\_shift = \beta_0 + \beta_1 Error_1 + \beta_2 PostError_2 + \beta_3 PerceptualChange_3 +$

$\beta_4 HierarchicalSwitchType_4 + \beta_5 TaskSwitch_5 + \beta_6 ResponseSwitch_6 +$

$\beta_7 ProbeSwitch_7 + \beta_8 PreviousTargetFeatureSwitch_8 + \beta_9 zRT_9 +$

$\beta_{10} zRT\_difference_{10} + \beta_{11} PerceptualChange_3 * HierarchicalSwitchType_4 +$

$\beta_{12} TaskSwitch_5 * ResponseSwitch_6$ (eq 5)

2.7.8 Group analysis of pattern shifts. This procedure yielded, for each subject, a whole-

brain beta map of each regressor that was then entered into a one-sample t-test across

participants. To control the family-wise error rate for multiple comparisons, we employed

AFNI's 3dClustSim using the residuals from the GLM procedure (Cox et al., 2017). First, spatial

autocorrelation of the residuals was estimated using the autocorrelation function (ACF),

producing three ACF parameters that characterize the spatial smoothness of the data. These

parameters were then supplied to 3dClustSim to estimate the minimum cluster size for a

corrected cluster-level threshold. Significant clusters for parametric modulation are based on

these calculated minimum cluster sizes of 22 voxels (cluster p-value threshold of .001 and a

voxel-level p-value threshold of .005).

2.8. Behavioral Switch Cost and Multivoxel Pattern Shift Predictions. Our

framework posits that hierarchically organized representations differ in their level of abstraction

and their sensitivity to sensory input. Task sets, which implement task rule-stimulus–response

mappings, are more tightly coupled to immediate sensory-motor plans, whereas contextual

representations are more abstracted from these immediate sensory-motor plans. These

differences are expected to influence both behavioral switch costs and trial-to-trial changes in

multivoxel activity patterns (pattern shifts).

Our predictions follow the population representation framework in which multivoxel

pattern similarity is taken to reflect representational similarity (Mur et al., 2009; Kriegeskorte et

al., 2008). Under this framework, different task representations evoke distinct distributed activity

patterns, and greater dissimilarity between patterns indexes less similar underlying

representations (Cox & Savoy, 2003; Kriegeskorte et al., 2008). Prior work has shown that both

categorical and parametric differences in representational content, including abstract task

variables, are reflected in systematic variation in multivoxel patterns (Garvert et al., 2017; Park

et al., 2020). Accordingly, we used multivoxel pattern shifts as an index of changes the

underlying representations engaged by the task.

For representations that incorporate sensory-motor plans, we predict increased sensitivity

to interference from task-irrelevant perceptual changes. Specifically, we expect the

reconfiguration of these representations to be more susceptible to interference from task-

irrelevant information due to (1) smaller representational distance and (2) greater sensory-driven

influence driving representational reconfiguration. We test this prediction by examining the

interaction between lower-level rule reconfiguration (IDS) and the number of stimulus features

(texture, color, shape) that change across trials. On IDS trials, the contextual texture repeats

while the relevant feature (color or shape) switches. When only one feature changes, only the

task-relevant dimension is updated; however, when multiple features change, both relevant and

irrelevant dimensions are updated. We predict that changes in task-irrelevant features will

increase both switch costs and pattern shifts, reflecting greater feedforward influence.

For EDS trials, which require switching the context, we predict the opposite pattern.

Contextual representations are abstracted away from immediate sensory-motor plans, and

therefore we hypothesize that they are separated by larger representational distances and less

influenced by trial-to-trial changes in perceptual and motor factors. Accordingly, the interaction

between feature change and switch type should be weaker for EDS than for IDS or Stay trials. In

addition, because context switching involves transitions between more distinct task sets, we

expect larger overall pattern shifts for EDS relative to IDS.

2.9. Code and Data Availability. All raw data are publicly accessible on OpenNeuro

(https://openneuro.org/datasets/ds005600/). Any preprocessing/analysis scripts used in this study

can be found on GitHub

(https://github.com/HwangLabNeuroCogDynamics/Neurocognitive_TaskSets).

3. Results
461
We analyzed both behavioral (z-scored RTs) and neural reconfiguration (pattern shifts)

measures using a common regression framework to identify factors influencing switch costs and

multivoxel pattern reconfiguration during hierarchical control. Specifically, we examined how

hierarchical level (context vs. subordinate rule switching) and perceptual factors modulated

behavioral performance and multivoxel pattern shifts. In addition, we tested interactions between

context and rule–stimulus–response conjunctions (Kikumoto and Mayr, 2020). More

specifically, we leverage partial switch costs as an indirect measure of conjunction strength, to

test whether different contexts are split into distinct representational subspaces, within which

context-dependent conjunctions are embedded.

3.1. Distinct hierarchical level representations interact differently with task-relevant and
task-irrelevant perceptual influences during reconfiguration.
473
Traditionally, a hierarchical representation structure has been assessed by comparing the

magnitude of switch costs across different levels of hierarchical rule switching (Fig. 3A, top

panel). Larger switch costs when context switches relative to subordinate-rule switches have

been taken as evidence of an underlying hierarchical representation structure (Cellier et al., 2022;

Chen et al., 2024). The present dataset displays these expected switch cost effects of larger z-

scored RT switch costs for context switches (EDS) as compared to both subordinate rule

switches (IDS; $t(53)=8.010$, $p<.001$), and rule repeats ($t(53)=18.128$, $p<.001$), as well as

subordinate rule switches (IDS) as compared to rule repeats (Stay; $t(53)=11.195$, $p<.001$; Fig.

3B). Switch costs that increase with reconfiguration of increasingly superordinate rules suggest

an underlying hierarchical organization of task representations in the present dataset.

484
Figure 3. Response Time Switch Costs.

A) Schematic of predicted switch cost patterns for a hierarchical representation structure (top)
and a more fine-grained analysis incorporating influences from task-relevant and task-irrelevant
features (bottom).
B) Switch cost comparisons across hierarchical rule conditions (Stay, IDS, EDS), showing
increasing switch cost magnitude with increasing abstraction. Significance is based on two-tailed
paired sample t-tests with z-scored RTs.
C-D) Switch cost effects from the interaction between hierarchical rule (Stay, IDS, EDS) and the
number of features that changed from the previous trial (perceptual change). Switch costs
increased with task-irrelevant feature changes during subordinate rule switching (**C**), but not
during context switches (**D**). Significance is based on post-hoc comparisons between estimated
marginal means for hierarchical rule (Stay/IDS/EDS) and perceptual change.
*** means p < .001, ** means p < .01, * means p < .05, n.s. means p >.05.
498

However, focusing solely on the magnitude of switch costs across hierarchical levels

neglects critical interactions between hierarchical task structure and the processing of task-

relevant versus task-irrelevant perceptual information across trials. In particular, trial-to-trial

changes in cue features can influence performance depending on whether task-relevant or task-

irrelevant cue features repeat or switch. Consider two examples. First, a cue may change from a

red circle to a red square, in which only the task-relevant feature (shape) changes while the task-

irrelevant feature (color) repeats. Second, a cue may change from a red circle to a blue square, in

which both task-relevant and task-irrelevant features change. At present, it remains an open

question as to whether these two example transitions differentially interact with subordinate rule

and contextual reconfiguration processes.

Arguably, sensitivity to task-irrelevant perceptual change should provide a behavioral

marker of how representations are organized. If representations are closely tied to sensory–motor

features, changes in task-irrelevant dimensions should increase interference and slow

performance. In contrast, more abstract representations should be less influenced by such

changes. In other words, a benefit of a hierarchical representation structure is that contextual

representations can be abstracted away from immediate sensory-motor plans, insulating

superordinate levels from feedforward interference at the cost of overall greater performance

costs associated with contextual reconfiguration. To test this, we conducted more fine-grained

analyses examining how trial-to-trial perceptual feature changes interact with hierarchical rule

reconfiguration (Fig. 3A, bottom). Switch trials (IDS and EDS) were subdivided based on

whether only the task-relevant feature changed (one feature changed) or both task-relevant and

task-irrelevant features changed (two feature changed).

Consistent with our predictions (Fig. 3A-bottom), if subordinate rules prioritize flexibility

by allowing greater feedforward influence from perceptual input, then subordinate rule

reconfiguration should be more susceptible to interference from changes in task-irrelevant cue

features. Supporting this prediction, trial-level mixed-effects models (with random intercepts for

subjects) revealed positive slopes for the number of features changing across trials (perceptual

change) for both rule repeat (Stay; $\beta = 0.151$, $SE = 0.017$, $CI = [0.117, 0.184]$), and subordinate

rule switch (IDS; $\beta = 0.072$, $SE = 0.023$, $CI = [0.026, 0.118]$) and a negative slope for context

switch (EDS; $\beta = -0.051$, $SE = 0.023$, $CI = [-0.095, -0.007]$).

Follow-up contrasts confirmed that these positive slopes were associated with

significantly slower response times when more cue features changed for both rule repeats (Stay;

zero versus one; *mean difference* = 0.151, $t(19588) = 8.835$, $p < .001$; degrees of freedom reflect

trial-level mixed-effects analyses, Satterthwaite's approximation (Kuznetsova et al., 2017), with

all appropriate trials included, and subjects modeled as random intercepts), and subordinate rule

switches (IDS; one versus two; *mean difference* = 0.072, $t(20227) = 3.063$, $p = .013$; Bonferroni

corrected (Benjamini & Hochberg, 1995); Fig. 3C). This indicated that, as predicted, the

additional task irrelevant feature change incurred an additional switch cost, i.e., slower response

times, for subordinate rule switches. Moreover, for EDS trials there was no significant increase

in response times when more cue features changed for context switch (EDS) trials (one versus

two, *mean difference* = 0.051, *t(20888)* = -2.266, *p* = .141; Fig. 3D; one versus three, *mean*

difference = 0.102, *t(20888)* = -2.266, *p* = .141, two versus three, *mean difference* = 0.051,

t(20888) = -2.266, *p* = .141). This suggests that context reconfiguration is better shielded from

potential feedforward perceptual interference from task-irrelevant feature changes. Note, because

a two-feature change on EDS trials did not always mean both a task-relevant and task-irrelevant

feature change, we ran a supplementary post-hoc paired sample t-test where we ensured this was

the case (see methods section *Behavioral (response time) supplementary analysis* for more

details). Critically, this analysis also found no difference in the magnitude of zRT switch costs

between one versus two features changing (paired-sample t-test *t(53)* = -0.010, *p* = .797).

Finally, we found a significant interaction between these perceptual change slopes for the

different rule reconfiguration conditions (i.e., IDS versus EDS), indicating that this slope is

significantly more positive for IDS trials as compared to EDS trials (β = 0.123, *t(20860)* = 4.123,

p < .001). To ensure the effects reported above were not driven by other trial-to-trial factors, we

included several control regressors in the model, including task switches (β = 0.018, *t(20880)* =

0.506, *p* = .613), switching responses (β = 0.019, *t(20880)* = 0.683, *p* = .495), switching probe

images (β = 0.027, *t(20880)* = 1.071, *p* = .284), error trials (*t(20,870)* = 10.504, *p* < .001) and

post-error trials (*t(20,820)* = 2.359, *p* = .018), as well as switching the task-defining (target)

feature from the previous trial (*t(20,820)* = 2.359, *p* = .018).

All in all, these results support our hypotheses on cognitive flexibility. Specifically, the

degree of perceptual change in the cue object interacts with rule reconfiguration differently

depending on which hierarchical level is being reconfigured. Subordinate rule representations

support flexibility, i.e., faster switching, at the cost of greater perceptual interference during

reconfiguration. Conversely, contextual representations are abstracted away and therefore less

influenced by perceptual interference during reconfiguration, but show greater overall

performance costs, i.e., slower switching, as a result.

3.2. Hierarchical reconfiguration and feedforward perceptual inputs jointly shape
multivoxel pattern shifts
567

568   To investigate potential neural underpinnings of these z-scored RT switch cost effects,

569   we conducted a parallel analysis using trial-to-trial changes in neural representational patterns

570   ("multivoxel pattern shifts") as a neural analogue of switch costs. We applied the same

571   regression model used for the behavioral switch cost analysis to predict multivoxel pattern shifts.

572   We included trial-wise z-scored RT and its derivative as additional predictors to control for

573   potential effects of RTs on neural dissimilarity patterns (Mumford et al., 2024).

574   Based on prior work implicating the middle frontal gyrus (MFG) in contextual encoding

and hierarchical cognitive control (Badre & D'Esposito, 2007; Badre & Nee, 2018; Nee &

D'Esposito, 2016), we predicted that context reconfiguration (EDS) would elicit a larger pattern

shift in MFG than subordinate rule reconfiguration (IDS). In parallel with behavioral findings,

we further predicted that EDS reconfiguration would be relatively insensitive to perceptual

interference. In contrast, we predicted that IDS reconfiguration would interact with perceptual

interference (Fig. 4A). Specifically, we predicted that pattern shifts in MFG during EDS trials

would be unaffected by the number of perceptual cue features changing across trials. In contrast,

we predicted that premotor and visual attention regions would show larger pattern shifts on IDS

trials when a greater number of perceptual features changed. Presumably, the latter would reflect

both the encoding of subordinate rules in premotor regions (Nee & Brown, 2013; Badre & Frank,

2012) and increased processing of task-irrelevant perceptual information during subordinate rule

reconfiguration.

In line with these predictions, we identified two significant clusters in lateral frontal

regions showing greater pattern shifts for EDS compared to IDS (inferior frontal sulcus (IFS) and

caudal middle frontal gyrus (cMFG); Fig. 4B). Note, there were no significant clusters for the

contrast between IDS and Stay trials. One possibility is that this null effect reflects overlap

between this contrast and perceptual change, as well as our inclusion of the task switch control

variable in the model. To address this, we conducted a supplementary analysis excluding

perceptual change and task switch from the model (Fig. S1). This analysis revealed a significant

caudal PFC cluster, located superior and posterior to the MFG cluster shown in Fig. 4B, that

exhibited significantly greater pattern shift for IDS relative to Stay trials. Together, these results

suggest that in our paradigm, pattern shift differences between IDS and Stay are primarily driven

by perceptual change and task-switch related processes.

Figure 4. Reconfiguration of Multivoxel Patterns Across Hierarchical Levels Shows Differential Sensitivity to Perceptual Change.

A) Schematic of expected effects for context versus subordinate rule reconfiguration.
B) Observed main effect of context reconfiguration contrasted with subordinate rule reconfiguration in MFG and IFS. No significant clusters for the main effect of subordinate rule contrasted with stay (rule repeat) trials.
C) Main effect of perceptual change (i.e., number of cue object features changing across trials; range 0-3) showing greater pattern shifts as more cue features changed across trials regardless of rule repeat/switch.
D-E) Interactions between perceptual change and (**E**) subordinate rule reconfiguration or (**F**) rule repeat (Stay) trials showing distributed clusters with greater pattern shifts as more cue features changed. No significant clusters for the interaction between perceptual change and context reconfiguration.
F) Perceptual change slopes for the 3 hierarchical repeat/switch conditions (Stay/IDS/EDS) in the MFG/IFS cluster (defined using the Schaefer 900 ROIs atlas; ROIs 780, 786, 789, & 793). Significantly positive slopes for Stay and IDS, but not significantly different from zero for EDS.
G) Perceptual change slopes for each hierarchical conditions (Stay/IDS/EDS) in the caudal PFC cluster (Schaefer 900ROIs, 7 networks atlas; ROI 797), showing significantly positive slopes for Stay and IDS, but not for EDS.
*** means $p < .001$, ** means $p < .01$, * means $p < .05$, n.s. means $p > .05$.

In contrast to the selective effect of context switches, perceptual change exerted

widespread influences on multivoxel pattern shifts. A significant main effect of the number of

changing cue features was observed across distributed regions (Fig. 4C), along with condition-

specific simple effects of perceptual change within IDS trials (Fig. 4D) and Stay trials (Fig. 4E).

We did not find any significant clusters for perceptual change within EDS trials. Within these

regions, pattern shifts were greater when both task-relevant and task-irrelevant features changed

compared to when only the task-relevant feature changed. These results are consistent with our

hypothesis of increased susceptibility to perceptual interference during subordinate rule

reconfiguration. These clusters were localized in a widely distributed fashion.

To ensure that the primary effects reported above were not driven by factors other than

hierarchical switch type (Stay/IDS/EDS) and perceptual change, we examined several control

variables included in the model. Consistent with the response design (right index/middle finger

presses), response switches were associated with greater pattern shifts in left motor and visual

cortices (Fig. S2A), reflecting this right-hand response design. Probe switches elicited greater

pattern shifts in ventral occipito-temporal regions, including fusiform face area (FFA) and

parahippocampal place area (PPA; Fig. S2B), consistent with the use of face and place stimuli.

Previous target feature switches were associated with distributed effects spanning caudal PFC,

visual cortex, medial temporal lobe, and basal ganglia (Fig. S2C). Post-error trials showed

increased pattern shifts across medial prefrontal, medial temporal, and subcortical regions,

including basal ganglia and mediodorsal thalamus (Fig. S3). No significant clusters were

observed for the main effect of task switch, error trials, or the task × response interaction. We do

not consider these control effects further as they do not bear directly on the hypotheses of

interest.

To more precisely characterize the interaction between perceptual change and

hierarchical task structure, we conducted two unbiased ROI analyses focusing on contrasting

condition-specific effects of perceptual change within each hierarchical condition (Fig. 4F and

G). This approach allowed us to directly test the predicted dissociation: perceptual change should

have minimal impact during context switches (EDS) but modulate pattern shifts during

subordinate rule switches (IDS) and rule repetitions (Stay). We defined two sets of ROIs based

on independent whole-brain contrasts. First, to examine context-related effects, we selected ROIs

within the lateral IFS-MFG ROIs overlapping with our searchlight cluster showing greater

pattern shifts for EDS than IDS. Using the Schaefer 900-parcel (7-network) atlas, this cluster

corresponded to four parcels (ROIs 780, 786, 789, and 793). Second, to show the specificity of

this context switch effect in MFG, we selected an adjacent caudal MFG ROI that showed a main

effect of perceptual change (ROI 797 in the same atlas).

Within the lateral IFS-MFG cluster, we extracted mean pattern shifts from these ROIs

and applied the same pattern shift model as before, but in a mixed effects model with random

intercepts for subjects. Similar to our z-scored RT results, we found positive slopes for the

number of features changing across trials (perceptual change) for both rule repeat (Stay; $\beta =$

0.009, *SE* = 0.002, *CI* = [0.006, 0.013]), and subordinate rules switch (IDS; $\beta =$ 0.012, *SE* =

0.002, *CI* = [0.008, 0.017]) and no reliable effect for context switch (EDS; $\beta =$ -0.0002, *SE* =

0.002, *CI* = [-0.004, 0.004]). Follow-up contrasts confirmed that pattern shifts increased with

greater perceptual change for Stay (Stay; zero versus one feature change; *mean difference* = -

0.009, *t(20965)* = -2.792, *p* = .032), and IDS (one versus two features change; *mean difference* =

-0.012, $t(20957) = -2.878$, $p = .024$; Bonferroni corrected; Fig. 4F). In contrast, EDS trials

showed no reliable differences across levels of perceptual change. Direct comparison of slopes

further supported this dissociation, as the perceptual change slope was significantly more

positive for IDS than EDS ($\beta = 0.013$, $t(20953) = 2.394$, $p = .044$). A post-hoc contrast between

context switch and subordinate rule switch trials further confirmed that context switch trials

show significantly larger pattern shifts than subordinate rule switch trials ($\beta = 0.016$, $t(20952) =$

2.829, $p = .014$).

672   We next examined the caudal MFG ROI defined from the main effect of perceptual

change (Fig 4G). Using the same modeling approach, we again observed positive slopes for

perceptual change in Stay ($\beta = 0.010$, $SE = 0.004$, $CI = [0.004, 0.017]$) and IDS trials ($\beta = 0.015$,

$SE = 0.005$, $CI = [0.006, 0.023]$), with no reliable effect for EDS trials ($\beta = 0.002$, $SE = 0.004$, CI

$= [-0.005, 0.010]$). Follow-up contrasts replicated this pattern of slope effects: pattern shifts

increased with greater perceptual change for Stay (zero versus one feature; *mean difference* = -

0.010, $z = -2.982$, $p = .017$) and IDS trials (one versus two features change; *mean difference* = -

0.015, $z = -3.256$, $p = .007$), but not for EDS trials. However, slopes did not differ between

hierarchical conditions ($\beta = 0.013$, $t(20938) = 0.756$, $p = .730$). Moreover, we confirmed a lack

of a context switch effect ($\beta = 0.009$, $t(20956) = 1.649$, $p = .297$) for this more caudal PFC ROI.

682   These multivoxel pattern shifts results support our hypotheses on cognitive flexibility.

Perceptual change modulates neural representations differently depending on the level of

hierarchical representations. During subordinate rule switches (IDS), pattern shifts increase with

the number of changing cue features, indicating greater sensitivity to task-irrelevant perceptual

information. In contrast, context switches (EDS) elicit larger overall multivoxel pattern shifts

that are invariant to perceptual change, consistent with more abstract representations that are

better insulated from feedforward interference.

3.3. Conjunctive representations supporting cognitive flexibility are context dependent.

Prior work suggests cognitive flexibility, i.e., fast and efficient switching between

rules/tasks, is supported by the creation of conjunctive representations (Kikumoto and Mayr,

2020). These conjunctive representations consist of task rules, stimuli, and responses. A common

measure of conjunctions has been partial switch costs—greater switch costs when only a subset

of conjunction components change across trials, as compared to trials where all components

switch or repeat (Grzyb & Hubner, 2013; Kleinsorge & Heuer, 1999). When all components of a

conjunction repeat, then the previous trial's conjunction can be re-instantiated. However, when

some components repeat while others switch, the previous conjunction needs to first be unbound

so that a new conjunction can be created with the components that repeat across trials.

Furthermore, the conjunction components that repeat across trials can cause increased

interference when sensory-motor plans differ between these two trials. Thus, this unbinding and

rebinding in addition to increased interference that needs to be resolved cause the observed

"cost'. When all components of a conjunction switch, the unbinding process can be skipped and

the lack of shared components with the previous trial means no additional interference needs to

be overcome. However, a new conjunction still needs to be constructed, which is why response

times are still slower overall than trials where the previous conjunction can be re-instated and

utilized.

Previous work on conjunctive representations has largely examined tasks with a single

level rule structure (Kikumoto and Mayr, 2020; Rangel et al., 2023). As such, it remains an open

question as to whether conjunctions consist of only the task sets organizing sensory-motor plans,

or if they include the higher-order context-level information that our paradigm was designed to

probe. Recent evidence suggests that conjunctive representations may be organized into context-

specific subspaces, enabling more efficient readout of task-relevant information (Kikumoto et al.,

2024). Given that in our task, context indicates if color or shape is the currently relevant rule, we

predicted that conjunction-related partial switch costs would be observed within each context,

but not when switching across contexts. Under this account, context serves to index distinct

conjunctive subspaces, such that switching context both circumvents the need to unbind the

previous conjunction and reduces interference from the previous conjunction.

To measure this, we first ran a modified version of the above RT mixed effects model

where the hierarchical rule switch (Stay/IDS/EDS) was replaced with a variable indicating if

context switched or repeated (2 levels). This allowed us to run a three-way interaction between

context, task, and response, while controlling for all the same additional variables as before. We

found a significant three-way interaction ($\beta = 0.128$, $t(20930) = 2.142$, $p = .032$). Post-hoc

comparisons revealed that the two-way interaction between task and response, which reflects

partial switch costs, was only significant when context repeated ($\beta = -0.124$, $t(20916) = -2.300$, p

$= .022$; Fig. 5A), but not when context switched ($\beta = 0.004$, $t(20926) = 0.065$, $p = .949$; Fig. 5B).

To replicate this result, we ran a follow-up behavioral experiment with the same experimental

paradigm. As expected, we found a significant three-way interaction ($\beta = 0.251$, $t(21690) =$

4.173, $p < .001$). Post-hoc comparisons once again revealed that the two-way interaction between

task and response, which reflects partial switch costs, was only significant when context repeated

($\beta = -0.247$, $t(21704) = -4.891$, $p < .001$; Fig. 5C), but not when context switched ($\beta = 0.004$,

$t(21687) = 0.056$, $p = .955$; Fig. 5D).

Experiment 1 (fMRI)

Experiment 2 (behavioral)

734
Figure 5. Partial Switch Costs and Context Reconfiguration.
A&C) Bar plots showing expected partial switch cost effects when context repeats.
B&D) Bar plots showing lack of partial switch costs when context switches. Significance based
on post-hoc comparisons between estimated marginal means for 3way interaction between
context, task, and response repeat/switch.
*** means p < .001, ** means p < .01, * means p < .05, n.s. means p >.05.
741
742

The existence of a significant two-way interaction between task and response within

context matches prior findings of partial switch costs (Kikumoto and Mayr, 2020; Rangel et al.,

2023). In contrast, the lack of a significant two-way interaction when switching contexts

suggests that partial switch costs are not observed during context reconfiguration. These results

lend further support to the idea that cognitive flexibility is supported by creating context-specific

conjunctive representations, which enable faster subordinate rule switching within context and

decreased interference when switching across context.

To address the neural underpinnings of partial switch costs indicative of potential

context-specific conjunctive representations, we conducted a parallel analysis with a very similar

regression model to predict multivoxel pattern shifts. Key differences were that cue color, shape,

and texture were removed (similar to the regression predicting pattern shifts reported in the

previous results section) and regressors indicating the z-scored RT and its derivative were

included. However, we found no significant clusters associated with a three-way interaction

between context, task, and response repeat/switch. This suggests that, although the observed

partial switch cost effect on context repeat trials, but not context switch trials, is robust for

response times, its neural underpinnings likely arise from a combination of distributed neural

representations rather than from anatomically focal, restricted sources.

4. Discussion

In this study, we investigated the behavioral (RT) and neural correlates of switch costs

associated with hierarchical cognitive control. We were primarily interested in how the

reconfiguration of distinct cognitive representations would interact with (1) the underlying

hierarchical task representation structure and (2) perceptual systems/processes necessary for

goal-directed behavior. To address these questions, we combined a hierarchical control task with

trial-by-trial behavioral switch cost analyses and a multivariate distance measure on voxel

patterns ("pattern shifts"), allowing us to characterize both performance costs and

representational reconfiguration during hierarchical cognitive control. In the sections that follow,

we interpret these findings in the context of existing theories of cognitive control and

representational flexibility.

The behavioral phenomenon of performance costs on trials requiring a task switch is

well-established (Monsell, 2003; Rogers & Monsell, 1995; Wylie & Allport, 2000; Allport et al.,

1994). However, relatively fewer studies have investigated the neural underpinning of these

costs, particularly how they relate to representational structure. A previous study found that

greater dissimilarity in multivoxel activity patterns on task switch trials predicted greater

response time task switch costs (Qiao et al., 2017). Nevertheless, given the multifaceted nature of

task representations (Schumacher & Hazeltine, 2016; Botvinick, 2008), several critical questions

remain unresolved: whether representational reconfiguration operates similarly across different

hierarchical levels, how abstract contextual representations interact or are interfered with by

changes in perceptual input, and whether perceptual related processes shape reconfiguration in

ways that support cognitive flexibility. The present study addresses these gaps by extending a

multivoxel pattern shifts analysis to a hierarchical task structure that specifically investigates

contextual updating and subordinate rule reconfiguration, allowing us to directly test how

different representational levels vary in their susceptibility to perceptual interference.

A complementary line of work suggests that stimulus-response associations are bound

into an event file (Hommel, 1998, 2004), or conjunction that incorporates task rules (Kikumoto

& Mayr, 2020). When this integrated sensory-motor representation can be re-used across trials,

performance is faster and more accurate; when it must be updated, performance costs increase,

particularly under partial overlap between trial components (Grzyb & Hubner, 2013; Kleinsorge

& Heuer, 1999). Despite this, relatively little work has examined how conjunctive

representations operate within hierarchical task structures. Kikumoto and colleagues (2024)

found evidence for context-specific conjunctions; however, their study utilized context as a retro

cue indicating which conjunction to select. Thereby, leaving it an open question as to whether

context would be incorporated into the conjunctive representation if presented concurrently with

the rule cue. Accordingly, the present study tested how hierarchical context, feedforward

perceptual inputs, and conjunctive representations might interact to shape behavioral and neural

switch costs.

Specifically, we found a clear distinction between context reconfiguration and

subordinate rule reconfiguration in the degree of susceptibility to feedforward perceptual

interference. Subordinate rule reconfiguration showed the greatest amount of feedforward

perceptual influence on reconfiguration processes. When task-irrelevant features changed across

trials, we observed slower RTs and a greater multivoxel pattern shifts in distributed regions,

notably, premotor and occipitotemporal regions in addition to frontal regions. Presumably, this

increased dissimilarity in trial-to-trial multivoxel activity patterns when task-irrelevant features

changed reflected greater processing of this task-irrelevant perceptual event. In contrast, the lack

of modulation of pattern shifts in MFG (i.e., equally large pattern shifts regardless of whether

task-irrelevant cue features changed) suggested that context reconfiguration was better shielded

from potential feedforward perceptual interference. Given prior work suggesting MFG encodes

high dimensional, abstract, task rule structures (Badre et al., 2021; Badre & Nee, 2018), this

reduced susceptibility to interference is critical for successful goal-directed behavior.

One explanation for why context reconfiguration appears to be better shielded from

feedforward perceptual interference is that contextual information is abstracted from immediate

sensory-motor plans and organizes lower-level perceptual and motor representations into distinct

representational subspaces. Kikumoto and colleagues (2024) suggest the control system encodes

conjunctive representations (integrated representations of task rules, stimuli, and responses) in

distinct subspaces. Context-specific conjunctions would allow for a smaller representational

distance within context, meaning greater flexibility, i.e., faster switching, while also shielding the

current goal-relevant conjunctions from interference across contexts. This greater flexibility

within context likely contributes to the observed partial switch costs when context repeats. In

contrast, switching between contextual subspaces requires traversing larger representational

distances, which could explain the slower RTs and absence of partial switch costs when context

changes.

While our framework suggests context representations reduce feedforward interference,

an alternative account is that interference from task-irrelevant features still occurs during context

reconfiguration but unfolds in parallel with reconfiguration processes. If context updating is the

slower process, it could obscure behavioral cost arising from perceptual interference. This

account would predict a modulation of multivoxel pattern shifts by task-irrelevant features across

all hierarchical conditions. We found that, although both Stay and IDS trials showed increased

pattern shifts with task-irrelevant feature changes across distributed regions, no such effect was

observed for EDS trials in any region. Therefore, these results do not support the parallel

processing account and instead support our argument that contextual representations are

relatively insulated from feedforward perceptual interference.

The present findings raise a central question: What mechanism drives the observed

pattern shifts and supports the updating of hierarchical task representations? Converging

evidence from our prior work and others (Chen et al., 2024; Mukherjee et al., 2021; Rikhye et

al., 2018) points to the mediodorsal (MD) thalamus as a critical subcortical region in this

process. Previously, we found that the MD thalamus is more strongly engaged during context

updating (Chen et al., 2024). Building on this finding, the current results suggest that

thalamocortical interactions may regulate the extent to which feedforward perceptual inputs

influence the updating of context and context-specific conjunctive representations. In this way,

thalamocortical interactions may enable flexible reconfiguration while limiting interference from

task-irrelevant inputs.

One possibility is that the MD thalamus mediates a context-specific updating signal that

also implements a form of input gating (Rac-Lubashevsky & Frank, 2021). During context

reconfiguration, thalamocortical interactions mediated by MD could drive targeted updating of

cortical context representations while constraining the influence of competing feedforward

inputs. Although we did not observe significant corrected clusters in MD during EDS trials in the

present data, this account is supported by our prior findings where MD showed increased evoked

responses and functional connectivity during context switches (Chen et al., 2024). Under this

view, context updating may involve selectively admitting context-relevant signals while

restricting task-irrelevant sensory inputs from propagating into higher-order representations.

Such gating could be implemented via known circuits, including basal ganglia–mediated control

of thalamic relay activity (e.g., input/output gating; (Chatham et al., 2014; O'Reilly & Frank,

2006)) or inhibiting feedforward inputs through the thalamic reticular nucleus (TRN, (Halassa &

Acsady, 2016; Zikopoulos & Barbas, 2006)). However, the present fMRI data do not allow for

distinguishing between these possibilities. During IDS and Stay trials, when context is stable,

this gating may be relaxed or differently configured, allowing feedforward inputs to more

directly influence rule and conjunctive representations. This would permit multiple feature inputs

to contribute to the formation and updating of conjunctive representations, consistent with the

distributed cortical effects of perceptual change observed here, as well as the involvement of

posterior thalamic regions (Fig. 4C–D).

Our measure of multivoxel pattern shifts has limitations that need to be addressed. First,

while greater dissimilarity in multivoxel activity patterns implies less similar population

responses, it can also be driven by multiple coding geometries (e.g., orthogonal subspaces versus

shifts within a shared space). Our measure detects the net effect of representational changes

influencing voxel patterns, but it does not uniquely specify the underlying neuronal population

geometry beyond the resolution of fMRI. Distinct task variables may coexist within voxels and

may be implemented as partially separable subspaces within the same population within the

same voxel (Weber et al., 2023).

In conclusion, we report three major findings regarding switch costs and hierarchical

cognitive control. First, trial-to-trial reconfiguration of neural activity patterns drive observable

switch costs, with greater pattern reconfiguration predicting larger behavioral switch costs.

Second, the reconfiguration of distinct hierarchical representation levels is differentially

impacted by feedforward perceptual information, as is evident through both RT and pattern shift

measures. More specifically, subordinate rule representations associated with more concrete

sensory-motor plans prioritized greater flexibility at the cost of greater interference from

feedforward perceptual information. To counter this increased interference, contextual

representations, which are more abstracted away from immediate sensory-motor plans, shielded

information from feedforward perceptual interference at the cost of reduced flexibility. This

likely reflects a balance of cognitive flexibility that supports faster adaptation of concrete action

plans while shielding internally maintained contextual representations from interference. Finally,

RT switch cost results suggest that this shielding is achieved by partitioning contexts into distinct

representational subspaces and forming context-specific conjunctions within these subspaces.

886
887

References

Badre, D., & D'Esposito, M. (2007). Functional Magnetic Resonance Imaging Evidence for a
Hierarchical Organization of the Prefrontal Cortex. *Journal of Cognitive Neuroscience,*
19(12), 2082-2099.
Sakai, K. (2008). Task set and prefrontal cortex. *Annu Rev Neurosci, 31*(1), 26.
Monsell, S. (2003). Task switching. *Trends in Cognitive Sciences, 7*(3), 134-140.
doi:10.1016/s1364-6613(03)00028-7
Rogers, R. D., & Monsell, S. (1995). Costs of a predictible switch between simple cognitive
tasks. *Journal of Experimental Psychology: General, 124*(2), 207-231. doi:10.1037/0096-
3445.124.2.207
Badre, D., Bhandari, A., Keglovits, H., & Kikumoto, A. (2021). The dimensionality of neural
representations for control. *Curr Opin Behav Sci, 38*, 20-28.
doi:10.1016/j.cobeha.2020.07.002
Badre, D., Hoffman, J., Cooney, J. W., & D'Esposito, M. (2009). Hierarchical cognitive control
deficits following damage to the human frontal lobe. *Nat Neurosci, 12*(4), 515-522.
doi:10.1038/nn.2277
Nee, D. E., & Brown, J. W. (2013). Dissociable frontal-striatal and frontal-parietal networks
involved in updating hierarchical contexts in working memory. *Cereb Cortex, 23*(9),
2146-2158. doi:10.1093/cercor/bhs194
Miller, E. K., & Cohen, J. D. (2001). An integrative theory of prefrontal cortex function. *Annual*
Review Neuroscience, 24.
Nee, D. E., & D'Esposito, M. (2017). Causal evidence for lateral prefrontal cortex dynamics
supporting cognitive control. *Elife, 6*. doi:10.7554/eLife.28040
Sakai, K., Rowe, J. B., & Passingham, R. E. (2002). Active maintenance in prefrontal area 46
creates distractor-resistant memory. *Nat Neurosci, 5*(5), 479-484. doi:10.1038/nn846
Cellier, D., Petersen, I. T., & Hwang, K. (2022). Dynamics of Hierarchical Task Representations.
J Neurosci, 42(38), 7276-7284. doi:10.1523/JNEUROSCI.0233-22.2022
Kikumoto, A., & Mayr, U. (2020). Conjunctive representations that integrate stimuli, responses,
and rules are critical for action selection. *Proceedings of the National Academy of*
Sciences, 117(19), 10603-10608. doi:10.1073/pnas.1922166117
Schumacher, E. H., & Hazeltine, E. (2016). Hierarchical task representation: Task files and
response selection. *Current Directions in Psychological Science, 25*(6), 449-454.
doi:10.1177/0963721416665085
Dykstra, T., Smith, D. M., Schumacher, E. H., & Hazeltine, E. (2022). Measuring task structure
with transitional response times: Task representations are more than task sets. *Psychon*
Bull Rev, 29(5), 1812-1820. doi:10.3758/s13423-021-02035-3
Bustos, B., Mordkoff, J. T., Hazeltine, E., & Jiang, J. (2024). Task switch costs scale with
dissimilarity between task rules. *J Exp Psychol Gen, 153*(7), 1873-1886.
doi:10.1037/xge0001598
Wylie, G., & Allport, A. (2000). Task switching and the measurement of switch costs.
Psychological Research, 63, 21.
Ebitz, R. B., & Hayden, B. Y. (2021). The population doctrine in cognitive neuroscience.
Neuron, 109(19), 3055-3068. doi:10.1016/j.neuron.2021.07.011

Mur, M., Bandettini, P. A., & Kriegeskorte, N. (2009). Revealing representational content with pattern-information fMRI--an introductory guide. *Soc Cogn Affect Neurosci, 4*(1), 101-109. doi:10.1093/scan/nsn044

Qiao, L., Zhang, L., Chen, A., & Egner, T. (2017). Dynamic Trial-by-Trial Recoding of Task-Set Representations in the Frontoparietal Cortex Mediates Behavioral Flexibility. *J Neurosci, 37*(45), 11037-11050. doi:10.1523/JNEUROSCI.0935-17.2017

Chen, X., Leach, S. C., Hollis, J., Cellier, D., & Hwang, K. (2024). The thalamus encodes and updates context representations during hierarchical cognitive control. *PLoS Biol, 22*(12), e3002937. doi:10.1371/journal.pbio.3002937

Esteban, O., Markiewicz, C. J., Blair, R. W., Moodie, C. A., Isik, A. I., Erramuzpe, A., . . . Gorgolewski, K. J. (2019). fMRIPrep: a robust preprocessing pipeline for functional MRI. *Nat Methods, 16*(1), 111-116. doi:10.1038/s41592-018-0235-4

Fonov, V., Evans, A. C., Botteron, K., Almli, C. R., McKinstry, R. C., & Collins, D. L. (2011). Unbiased average age-appropriate atlases for pediatric studies. *Neuroimage, 54*. doi:10.1016/j.neuroimage.2010.07.033314

Prince, J. S., Charest, I., Kurzawski, J. W., Pyles, J. A., Tarr, M. J., & Kay, K. N. (2022). Improving the accuracy of single-trial fMRI response estimates using GLMsingle. *Elife*. doi:10.7554/eLife.77599

Kay, K. N., Rokem, A., Winawer, J., Dougherty, R. F., & Wandell, B. A. (2013). GLMdenoise: a fast, automated technique for denoising task-based fMRI data. *Front Neurosci, 7*, 247. doi:10.3389/fnins.2013.00247

Willenbockel, V., Sadr, J., Fiset, D., Horne, G. O., Gosselin, F., & Tanaka, J. W. (2010). Controlling low-level image properties: the SHINE toolbox. *Behav Res Methods, 42*(3), 671-684. doi:10.3758/BRM.42.3.671

Walther, A., Nili, H., Ejaz, N., Alink, A., Kriegeskorte, N., & Diedrichsen, J. (2016). Reliability of dissimilarity measures for multi-voxel pattern analysis. *Neuroimage, 137*, 188-200. doi:10.1016/j.neuroimage.2015.12.012

Bates, D., Mächler, M., Bolker, B., & Walker, S. (2015). Fitting Linear Mixed-Effects Models Usinglme4. *Journal of Statistical Software, 67*(1). doi:10.18637/jss.v067.i01

Rabbitt, P. A. (1966). Errors and error correction in choice-response tasks. *Journal of Experimental Psychology, 71*(2).

McClure, S. M., Berns, G. S., & Montague, P. R. (2003). Temporal prediction errors in a passive learning task activate human striatum. *Neuron, 38*.

Grzyb, K. R., & Hubner, R. (2013). Excessive response-repetition costs under task switching How response inhibition amplifies response conflict. *Journal of Experimental Psychology: Learning, Memory, and Cognition, 39*, 13.

Kleinsorge, T., & Heuer, H. (1999). Hierarchical switching in a multi-dimensional task space. *Psychological Research, 62*, 12.

Li, J., Cao, B., Han, J., Xie, L., & Li, F. (2019). Not inertia but reconfiguration: Asymmetric switch cost in a hierarchical task. *Brain Res, 1720*, 146291. doi:10.1016/j.brainres.2019.06.010

Mumford, J. A., Bissett, P. G., Jones, H. M., Shim, S., Rios, J. A. H., & Poldrack, R. A. (2024). The response time paradox in functional magnetic resonance imaging analyses. *Nat Hum Behav, 8*(2), 349-360. doi:10.1038/s41562-023-01760-0

Cox, R. W., Chen, G., Glen, D. R., Reynolds, R. C., & Taylor, P. A. (2017). fmri clustering and false-positive rates. *PNAS, 114*(17), 2. doi:10.1073/pnas.1614961114Fig

980   Kriegeskorte, N., Mur, M., & Bandettini, P. (2008). Representational similarity analysis -
981   connecting the branches of systems neuroscience. *Front Syst Neurosci, 2*, 4.
982   doi:10.3389/neuro.06.004.2008
983   Kuznetsova, A., Brockhoff, P. B., & Christensen, R. H. B. (2017). lmerTest Package: Tests in
984   Linear Mixed Effects Models. *Journal of Statistical Software, 82*(13).
985   doi:10.18637/jss.v082.i13
986   Benjamini, Y., & Hochberg, Y. (1995). Controlling the False Discovery Rate: A Practical and
987   Powerful Approach to Multiple Testing. *Journal of the Royal Statistical Society Series B:*
988   *Statistical Methodology, 57*(1), 289-300. doi:10.1111/j.2517-6161.1995.tb02031.x
989   Badre, D., & Nee, D. E. (2018). Frontal Cortex and the Hierarchical Control of Behavior. *Trends*
990   *in Cognitive Science, 22*(2), 170-188. doi:10.1016/j.tics.2017.11.005
991   Nee, D. E., & D'Esposito, M. (2016). The hierarchical organization of the lateral prefrontal
992   cortex. *Elife, 5*, e12112. doi:10.7554/eLife.12112
993   Badre, D., & Frank, M. J. (2012). Mechanisms of hierarchical reinforcement learning in cortico-
994   striatal circuits 2: evidence from fMRI. *Cereb Cortex, 22*(3), 527-536.
995   doi:10.1093/cercor/bhr117
996   Allport, A., Styles, E. A., & Hsieh, S. (1994). Shifting intentional set Exploring the dynamic
997   control of tasks.
998   Botvinick, M. M. (2008). Hierarchical models of behavior and prefrontal function. *Trends Cogn*
999   *Sci, 12*(5), 201-208. doi:10.1016/j.tics.2008.02.009
1000   Hommel, B. (1998). Event Files: Evidence for Automatic Integration of Stimulus-Response
1001   Episodes. *Visual Cognition, 5*(1-2), 183-216. doi:10.1080/713756773
1002   Hommel, B. (2004). Event files: feature binding in and across perception and action. *Trends*
1003   *Cogn Sci, 8*(11), 494-500. doi:10.1016/j.tics.2004.08.007
1004   Mukherjee, A., Lam, N. H., Wimmer, R. D., & Halassa, M. M. (2021). Thalamic circuits for
1005   independent control of prefrontal signal and noise. *Nature, 600*(7887), 100-104.
1006   doi:10.1038/s41586-021-04056-3
1007   Rikhye, R. V., Gilra, A., & Halassa, M. M. (2018). Thalamic regulation of switching between
1008   cortical representations enables cognitive flexibility. *Nat Neurosci, 21*(12), 1753-1763.
1009   doi:10.1038/s41593-018-0269-z
1010   Rac-Lubashevsky, R., & Frank, M. J. (2021). Analogous computations in working memory
1011   input, output and motor gating: Electrophysiological and computational modeling
1012   evidence. *PLoS Comput Biol, 17*(6), e1008971. doi:10.1371/journal.pcbi.1008971
1013   Chatham, C. H., Frank, M. J., & Badre, D. (2014). Corticostriatal output gating during selection
1014   from working memory. *Neuron, 81*(4), 930-942. doi:10.1016/j.neuron.2014.01.002
1015   O'Reilly, R. C., & Frank, M. J. (2006). Making working memory work A computational model
1016   of learning in the prefrontal cortex and basal ganglia. *Neural Computation, 18*.
1017   Halassa, M. M., & Acsady, L. (2016). Thalamic Inhibition: Diverse Sources, Diverse Scales.
1018   *Trends Neurosci, 39*(10), 680-693. doi:10.1016/j.tins.2016.08.001
1019   Zikopoulos, B., & Barbas, H. (2006). Prefrontal projections to the thalamic reticular nucleus
1020   form a unique circuit for attentional mechanisms. *J Neurosci, 26*(28), 7348-7361.
1021   doi:10.1523/JNEUROSCI.5511-05.2006
1022
1023

Acknowledgments

Author contributions: SCL wrote the first draft of the paper, SCL and KH edited the

paper, KH and SCL designed research, SCL and XC performed research, SCL and KH analyzed

data.

Authors declare that they have no competing interest.

All data and code will be made available upon publication.

Research reported here was supported by a National Institutes of Mental Health grant

R01MH122613 (KH) and the Iowa Neuroscience Institute. This work was conducted on an MRI

instrument funded by 1S10OD025025-01

1033

1034

1035

1036   **Figure Captions**

1037

Figure 1. Hierarchical control task design.
A) Depiction of the task rule hierarchy embedded within the 8 potential cue objects. Context
switch (EDS) trials reflect switching between the shape and color rule, or switching between a
filled and hollow cue object. Subordinate rule switch (IDS) trials reflect repeating context, but
switching between either circle and square or red and blue, depending on the context rule (shape
or color). Finally, Stay trials are trials where both context and subordinate rule repeat.
B) More detailed depiction of perceptual change showing eight possible transitions following a
trial with a filled, blue, circle cue object. Across trials, 0-3 features could change.
C) Example trial sequence: a cue object is presented for 0.5 seconds, followed by an image of
either a face or a scene for 2 seconds, and a jittered ITI (range: 1.5-10.5 seconds; average: 4.25
seconds). Example cue transitions across trials depicts how perceptual change is operationalized.
The first Stay trial shows a cue transition with 0 features changing. The second Stay trial shows a
cue transition where one cue feature changes (shape, a task-irrelevant feature in this example).
The EDS trial shows a cue transition where all three cue features change. The IDS trial shows a
cue transition where two features change (shape, task-relevant; color, task-irrelevant). Example
face images are authors on this manuscript.
1054

Figure 2. Multivoxel Pattern Shifts Method.
A) Depiction of how pattern shifts are calculated on adjacent trial multivoxel activity patterns. A
greater change in multivoxel activity patterns is associated with a greater correlation, or
similarity.
B) Depiction of relationship between pattern shifts and representational distance. In general, a
larger representational distance should result in a greater pattern shift while a smaller
representational distance should result in a smaller pattern shift.
1062

Figure 3. Response Time Switch Costs.
A) Schematic of predicted switch cost patterns for a hierarchical representation structure (top)
and a more fine-grained analysis incorporating influences from task-relevant and task-irrelevant
features (bottom).
B) Switch cost comparisons across hierarchical rule conditions (Stay, IDS, EDS), showing
increasing switch cost magnitude with increasing abstraction. Significance is based on two-tailed
paired sample t-tests with z-scored RTs.
C-D) Switch cost effects from the interaction between hierarchical rule (Stay, IDS, EDS) and the
number of features that changed from the previous trial (perceptual change). Switch costs
increased with task-irrelevant feature changes during subordinate rule switching (**C**), but not
during context switches (**D**). Significance is based on post-hoc comparisons between estimated
marginal means for hierarchical rule (Stay/IDS/EDS) and perceptual change.
*** means $p < .001$, ** means $p < .01$, * means $p < .05$, n.s. means $p > .05$.
1076

Figure 4. Reconfiguration of Multivoxel Patterns Across Hierarchical Levels Shows Differential
Sensitivity to Perceptual Change.
A) Schematic of expected effects for context versus subordinate rule reconfiguration.
B) Observed main effect of context reconfiguration contrasted with subordinate rule
reconfiguration in MFG and IFS. No significant clusters for the main effect of subordinate rule
contrasted with stay (rule repeat) trials.
C) Main effect of perceptual change (i.e., number of cue object features changing across trials;
range 0-3) showing greater pattern shifts as more cue features changed across trials regardless of
rule repeat/switch.
D-E) Interactions between perceptual change and (**E**) subordinate rule reconfiguration or (**F**) rule
repeat (Stay) trials showing distributed clusters with greater pattern shifts as more cue features
changed. No significant clusters for the interaction between perceptual change and context
reconfiguration.
F) Perceptual change slopes for the 3 hierarchical repeat/switch conditions (Stay/IDS/EDS) in
the MFG/IFS cluster (defined using the Schaefer 900 ROIs atlas; ROIs 780, 786, 789, & 793).
Significantly positive slopes for Stay and IDS, but not significantly different from zero for EDS.
G) Perceptual change slopes for each hierarchical conditions (Stay/IDS/EDS) in the caudal PFC
cluster (Schaefer 900ROIs, 7 networks atlas; ROI 797), showing significantly positive slopes for
Stay and IDS, but not for EDS.
*** means $p < .001$, ** means $p < .01$, * means $p < .05$, n.s. means $p > .05$.
1097

Figure 5. Partial Switch Costs and Context Reconfiguration.
A&C) Bar plots showing expected partial switch cost effects when context repeats.
B&D) Bar plots showing lack of partial switch costs when context switches. Significance based
on post-hoc comparisons between estimated marginal means for 3way interaction between
context, task, and response repeat/switch.
*** means $p < .001$, ** means $p < .01$, * means $p < .05$, n.s. means $p > .05$.
1104

1105