Semantic axes in the brain support analogical representations

Hanlin Zhu[1], Melissa Franch[1], Elizabeth A. Mickiewicz[1], James L. Belanger[1], Rhiannon L. Cowan[2], Kalman A. Katlowitz[1], Ana G. Chavez[1], Assia Chericoni[1], Danika Paulo[1], Xinyuan Yan[1], Eleonora Bartoli[1], Jay A. Hennig[3,4], Nicole R. Provenza[1,3,5,6], Elliot H. Smith[2], Steven T. Piantadosi[7], Sameer A. Sheth[1,4], and Benjamin Y. Hayden[1,4]

1. Department of Neurosurgery, Baylor College of Medicine, Houston, Texas
2. Department of Neurosurgery, University of Utah, Salt Lake City, Utah
3. Neuroengineering Initiative, Rice University, Houston, Texas
4. Department of Neuroscience, Baylor College of Medicine, Houston, Texas
5. Department of Electrical and Computer Engineering, Rice University
6. Department of Bioengineering, Rice University
7. Department of Psychology, Helen Wills Neuroscience Institute, University of California Berkeley, Berkeley, California

*Correspondence: Benjamin.Hayden@bcm.edu

Funding statement: This research was supported by the McNair Foundation and by NIH R01 MH129439.

Competing interests: S.A.S has consulting agreements with Boston Scientific, Zimmer Biomet, Koh Young, Abbott, and Neuropace. SAS is a Co-founder of Motif Neurotech. The rest of the authors have no competing interests to declare.

Acknowledgements: We thank Victoria Gates and Raissa Mathura for invaluable assistance.

Data availability: The data that support the findings of this study are available from the corresponding authors upon reasonable request.

ABSTRACT

In vectorial embeddings of word meaning, semantic features often reflect consistent directions—or axes—within a representational space. A classic example is gender: the vector spanning "*boy*"→"*girl*" can be added to the embedding for "*king*" to predict "*queen*." Here we show that the same principle governs semantically driven neural responses in the human brain. We recorded single-neuron activity in three brain regions while participants listened to podcasts. Across fifteen analogical categories —including gender, number, and antonymy—we observed consistent vectorial directions, resulting in parallelogram structure within the neural manifold. Among pronouns, vectors corresponding to grammatical case, number, person, and possession obeyed the principle of commutativity, resulting in a prismatic structure, demonstrating that semantic axes can be factorized. We found parallelogram structure in all three regions, with some regional specialization: noun pluralization was more robust in the hippocampus than in the anterior cingulate cortex (ACC) or orbitofrontal cortex, whereas verbal conjugation effects were more robust in the ACC. Finally, we found evidence for partial functional specialization at the neuron level: neurons most strongly involved in one analogy type were less involved in others. These principles parallel representational structure observed in large language models. Together, these findings support a geometric basis for analogical reasoning.

INTRODUCTION

Word meanings can be captured by vectorial embeddings that convey their important
features (Gärdenfors, 2000; Turney & Pantel, 2010). These representations are found in word
models, such as Word2Vec, which are based on co-occurrence statistics in large corpora
(Mikolov et al., 2013; Pennington et al., 2014) as well as earlier vector-space models of meaning
(Landauer & Dumais, 1997; Blei, Ng, & Jordan 2001). One powerful feature of such models is
that components of meaning are often stable across words. Thus, for example, we might identify
a *gender* vector by computing the vector that spans the embeddings from the words "*boy*" to
"*girl*". We can then add this *gender vector* to the vectorial representation of "*uncle*" to obtain the
vector for "*aunt*", which has an analogous semantic relationship. In other words, directions
correspond to consistent meanings, and can be used constructively to build new meanings and
make inferences about the meaning of even previously unseen words. This feature is valuable for
many aspects of reasoning such as analogical thought, generalization, comparison, and even
creativity (Gärdenfors, 2014; Lake et al., 2017; Piantadosi et al., 2024; Ward et al., 1999;
Hofstadter, 1995). As a result, appropriately constructed vectorial embeddings can serve as the
foundation for core cognitive capacities (Gentner, 1983, 2010; Hofstadter, 2001; Holyoak et al.,
2001). Indeed, this organization is found in large language models (LLMs), as well as in their
precursors, where it plays an important role in their ability to generalize across lexical and
conceptual domains (Mikolov et al., 2013; Devlin et al., 2019; Elman, 1990; Radford et al.,
2019; Touvron et al., 2023).
The elegance of the vectorial solution to analogical reasoning makes it an appealing
theory for brain representations. We currently lack a comprehensive theory for how semantic
meaning is represented in the brain (Binder et al., 2009; Patterson et al., 2007). A good deal of
evidence supports the idea that the brain, especially the medial temporal lobe, contains
specialized neurons with sparse amodal response fields that correspond to single concepts
(Quiroga et al., 2005; Quiroga, 2012). These representations, however, cannot readily be
decomposed into semantic features, and therefore cannot, as a general rule, be used for processes
like analogical reasoning (Quiroga, 2020). As such, we hypothesized that the brain may contain a
complementary representational system that allows for encoding of specific semantic features
using stable consistent high dimensional axes (cf. Courellis et al., 2024). Indeed, there is some
evidence from neuroimaging that the human brain organizes some features of meaning along
preserved axes, potentially supporting analogical thinking (Wu et al., 2022; Zhang et al., 2020).
More broadly, a growing body of evidence indicates that semantic representations in the brain
share some features in common with those observed in LLMs, including high-dimensional
distributed embeddings, partial factorization of semantic features, and linear structure supporting
analogical generalization (Caucheteux & King, 2022; Mitchell et al., 2008; Schrimpf et al.,
2021). Based on these findings, we hypothesized that semantic representations in the human
brain would show semantically meaningful axes.

A growing body of work suggests that neural representations may be organized in a
factorized (sometimes called *disentangled*) manner, in which distinct latent variables are encoded
along independent representational axes (Courellis et al., 2024; Fusi et al., 2016; Rigotti et al.,
2013; Bernardi et al., 2020). In such codes, population activity does not merely reflect similarity
structure among stimuli but instead forms low-dimensional geometries whose organization
mirrors the algebraic relationships among underlying variables (Behrens et al., 2018;
Whittington et al., 2020). One hallmark of factorized representations is a *prismatic* organization
of neural state space, in which combinations of factors occupy vertices of parallel subspaces
whose translations correspond to operations applied along independent dimensions (Trager et al.,
2024; Yang et al., 2019; Ostrow & Fiete, 2024). This geometry naturally gives rise to
commutativity: applying two transformations in different orders yields equivalent
representational displacements (Quessard et al., 2020; Higgins et al., 2018), reflecting the
additive structure of the underlying latent variables. While prior studies have emphasized the
parallelogram effect as evidence for vector-like coding (Constantinescu et al., 2016; Garvert et
al., 2017; Vigano & Piazza, 2020; Wu et al., 2022), parallelogram structure alone can arise from
local linear correlations or pairwise similarity constraints. In contrast, prismatic geometry
implies a stronger organizational principle: that multiple variables are simultaneously
represented in separable subspaces whose interactions obey consistent algebraic rules across the
full representational manifold—supporting systematic recombination and generalization (Lake et
al., 2017; Baroni, 2020) beyond individual stimulus pairs. Consequently, determining whether
neural representations adhere to these prismatic constraints—rather than merely exhibiting local
parallelograms—remains critical, especially in naturalistic settings lacking the scaffolding of
specialized laboratory tasks. We therefore investigated neural geometries during a continuous
speech-listening task to capture the contextualized meanings of words in their natural state,
distinguishing intrinsic representational structure from that imposed by experimental design.
The hippocampus is especially interesting in this regard due to its putative role in
conceptual representation (Mack et al., 2018; Kafkas et al., 2024; Theves et al., 2020;
Constantinescu et al., 2016; Behrens et al., 2018; Courellis et al., 2024; Bernardi et al., 2020),
including for language semantics (Blank et al., 2016; Davachi, 2006; Wolna et al., 2025). We
and others have argued that its role includes encoding word meanings during speech listening
(Franch et al., 2025; Katlowitz et al., 2025; Dijksterhuis et al., 2024; Blank et al., 2016).
Critically, we find that words that have more similar vectorial representations (and are therefore
more semantically similar) also have more similar neural responses (Franch et al., 2025). This
finding supports the idea that distances in neural coding space correspond to semantic distance
and raises the possibility that vectorial directions may correspondingly have semantic meanings.
To test these ideas, we examined neural encoding of analogical relationships in the hippocampus.
However, the hippocampus is not the only region associated with semantic coding (Huth et al.,
2016; Tang et al., 2023); for comparison, we therefore examined responses in two other brain
regions, the anterior cingulate cortex (ACC) and orbitofrontal cortex (OFC).

RESULTS

Fourteen native English-speaking patients (6 males and 8 females) undergoing neural monitoring for epilepsy listened to 47 minutes of English speech (six monologues taken from the Moth podcast, **Methods**, **Figure 1A** and **B,** Franch et al., 2025). We collected responses of isolated single neurons in the hippocampus (HPC, n = 437 neurons, 14 patients), the anterior cingulate cortex (ACC, n = 241 neurons, 12 patients), and the orbitofrontal cortex (OFC, n = 51 neurons, 5 patients). Many neurons showed a clear response to the onset of individual words, with a characteristic ramping to a peak, followed by a gradual decline in firing (**Figure 1C**, **Supplementary Figure 1**, Franch et al., 2025). We computed firing rates during a time window starting 80 ms after the onset of each word (to account for the approximate response latency) and lasting the duration of the word plus 40 ms.

Hippocampal neural populations have aligned semantic axes

We systematically searched the podcast text (7,346 words total, 1351 unique words) to identify word pairs that differed along single semantic dimensions. We identified fifteen analogical relationships (summarized in **Table 1**) that applied to 206 word pairs (full list in **Supplementary Table 1**). These analogical relationships were identified before inspection of the data and were based on well-known analogical categories from the literature. They included both semantic (e.g., gender) and grammatical (e.g., case) analogies (**Table 1**).

We focus first on hippocampal neurons given their putative role in conceptual representations. We found individual hippocampal neurons whose responses systematically differed along two the classes within an analogy (**Figure 1D**). For example, neuron 4.11 (i.e., patient 4, neuron 11) exhibited larger responses to twelve female-associated terms (e.g., "*girl*", "*queen*") than to the corresponding twelve male terms ("*boy*", "*king*"). Other neurons distinguished quantitative or grammatical modifiers. Neuron 10.18 differentiated between odd numbers and their immediate even successors (n and n+1, e.g., "*three*" vs. "*four*"), while neuron 13.7 differentiated comparative forms of adjectives from their stem forms (technically, the positive form, (e.g., "*cooler*" vs. "*cool*")). Meanwhile, neuron 10.40 differentiated negated from non-negated (i.e., affirmative) verbs (e.g., "*not come*" vs. "*come*"), and neuron 10.20 separated possessive from accusative pronouns (e.g., "his" vs. "him"). These example neurons raise the possibility that the brain may make use of consistent response axes for semantic information.

We quantified the firing rate separation between these groups at individual neuron level using a balanced AUC (area under the curve) metric (**Figure 1E**, **Methods**, Franch et al., 2025). A neuron's tuning strength was defined with its AUC p-value against a label-shuffled null distribution. In this example (**Figure 1E**), neuron 4.11 exhibited a significant (p = 0.01) but low AUC of 0.6 (chance = 0.5), indicating modest coding power to differentiate between male and female. This method is agnostic about which of the two conditions elicits a higher firing rate. For comparison, we quantified the proportion of modulated units in the last layer of BERT, a large language model (LLM) that serves as a benchmark for statistical learning of semantic

relationships (Devlin et al., 2019; Rogers et al., 2020; Schrimpf et al., 2021, **Figure 1F**).
Concretely, the BERT model we analyzed is a stack of transformer encoder layers that outputs,
for each input word at each layer, a 768-dimensional contextual hidden state (embeddings); we
treat each of the 768 dimensions as an artificial "unit" whose activation for that word is
analogous to an instantaneous firing rate. We found that BERT generally possesses a higher
density of units aligned with these semantic axes (two-sided two-proportion Z-test, FDR
corrected, $\alpha = 0.05$, $q < 0.05$). Specifically, it has a greater number of tuned units in 14 out of
the 15 analogy categories (all but qualifiers) tested when using the same words in the same
contexts (See **Table 1** for complete examples and words used in each of the 15 analogies). Thus,
the human hippocampus ($7.62\% \pm 0.72\%$ tuned neurons, mean $\pm$ s.e.m., n = 15 categories) more
sparsely encodes these semantic axes compared to an LLM ($53.59\% \pm 7.03\%$). Notably,
however, layer-wise scans of BERT and GPT-2 (**Supplementary Figure 2**) reveal that the
fraction of units meeting our analogy-tuning criterion generally decreases with increasing layer
depth. This may suggest a progressive compression of axis-aligned information into fewer
internal units, pointing toward a possible convergence with the sparse coding regime of the brain
in deeper model layers.
If ensemble responses to words like "*boy*," "*girl*," "*king*," and "*queen*" are vectors whose
features are coded as vectors, then this quartet of related words will have a parallelogram shape
on the neural manifold (**Figure 1G**, Rumelhart & Abrahamson, 1973; Mikolov et al., 2013;
Allen & Hospedales, 2019; Peterson et al., 2020). parallelogram-shaped representations have
many convenient properties; for example, they allow vector arithmetic to solve analogical
reasoning problems (**Figure 1H**, Rumelhart & Abrahamson, 1973).
In our stimulus set, the words "*boy*" and "*girl*" were each repeated four times, in various
contexts (**Figure 1I**). We calculated the average response evoked by these words from our a
priori gender-selective neurons (that is, neurons with high gender tuning strength, defined as
p(AUC) < 0.125, n = 100 out of 437 neurons), and defined the results as the ***neural embeddings***
of the two words, respectively. We then used the same procedure to derive neural embeddings
for "*kings*" and "*queen*" using the same set of neurons. We found that the direction of the
king→queen vector is more similar to the average *boy→girl* vector (cosine similarity = 0.57)
than to a random word→random word vector (cosine similarity = 0.007 ± 0.003, mean $\pm$ s.e.m.,
n = 10000 random word pairs, p = 0.013, permutation test, **Supplementary Figure 3**). To see
this result, we plot the vectors, using multidimensional scaling (MDS, Carroll & Arabie, 1980;
see **Methods**) to facilitate visualization (**Figure 1J**).

A. Hippocampal single neuron recordings with Behnke-Fried electrodes

Pt 1, Pt 2, Pt 3, Pt 4, Pt 5, Pt 6, Pt 7, Pt 8, Pt 9, Pt 10, Pt 11, Pt 12, Pt 13, Pt 14

B. So I get a phone call from my mom

cell 1, cell 13, cell 14, cell 19, cell 27

C. Pt.4 HPC neuron 10, Pt.9 HPC neuron 37, Pt.10 HPC neuron 40, Pt.13 HPC neuron 11

Time around word onset (ms)

D. Pt.4 neuron 11 Gender — female, male; Pt.14 neuron 7 Gender — female, male; Pt.10 neuron 18 Odd Number +1 — odd number+1, odd number; Pt.10 neuron 23 Pron. Obj/Poss — possessive, objective (accusative); Pt.10 neuron 40 Verb Negation — negation, verb; Pt.13 neuron 7 Adj Comparative — comparative, adjective

E. ROC of Pt4. neuron 11, decode gender, AUC = 0.602, p(AUC)= 0.01

F. Pron. Obj/Poss, Pron. Subj/Poss, Pron. Subj/Obj, Pron. Plural, Pron. 1st/3rd, Noun Plural, Verb -ed/-ing, Verb Negation, Adj Comparative, Qualifier, Gender, Residence, Protector, Odd Number +1, Antonyms — Tuned neuron %; Hippocampus, BERT

G. boy, girl, king, queen; neuron 1, neuron 2, neuron 3

H. ???, China, capital, Paris, France

I. if somebody starts singing Dancing Queen, we all join in our night to me I was a dancing queen, I was a wild woman of the we were the undisputed kings of Francis Stevens elementary I was crushed like imagining this boy at Spencer's with another powder from the grenade, but of course the boy did not know that hand you know as a boy, as a child, you know, maybe my little I was about thirteen, this really cute boy at school has asked me now, mind you, I'm a fourteen year old girl, I'm already awkward and I turn to the girl next to me, and I'm like, you know, your shirt like imaging this boy at Spencer's with another girl, so I didn't sitting in the back with a bunch of other girls, and I really want to

J. girl, boy, queen, kings; MDS-1, MDS-2, MDS-3

Figure 1 | Hippocampal single neurons encode semantic axes and support analogical vector geometry during natural speech.

A, Recording locations of hippocampal single units from 10 of the 14 epilepsy patients implanted with Behnke–Fried depth electrodes. Colored dots indicate electrode recording sites; colors correspond to individual patients (key below). ACC and OFC recording sites omitted for simplicity.

B, Experiment schematic showing continuous speech segment (waveform and spectrogram) with aligned spiking activity from five simultaneously recorded hippocampal neurons. Tick marks denote spike times; blue traces show smoothed firing rate. Word boundaries/onsets are indicated above the waveform. **A** and **B** partially adapted from Franch et al., 2025 with permission.

C, Peri-word onset responses for four example hippocampal neurons (Pt. = patient). Top: trial-averaged firing rate aligned to word onset (dashed line at 0 ms; shading indicates ± s.e.m.). Bottom: raster plots across word presentations

D, Example hippocampal neurons whose firing rates differentiate word pairs along specific semantic axes identified in the stimulus text. Left to right: gender (female vs male; Pt.4 neuron 11 and Pt.14 neuron 7), odd number vs odd number+1 (Pt.10 neuron 18), pronoun objective vs possessive (Pt.10 neuron 23), verb negation vs affirmative verb forms (Pt.10 neuron 40), and comparative vs positive (base) adjectives (Pt.13 neuron 7). Traces show mean firing rate aligned to word onset with shading (± s.e.m.); n(male) = 207 trials, n(female) = 85, n(odd number) = 45, n(odd number +1) = 34, n(objective) = 151, n(possessive) = 246, n(verb) = 384, n(negation) = 61, n(adjective) = 21, n(comparative) = 14 trials.

E, Receiver operating characteristic (ROC) analysis for decoding gender from the firing rate of Pt.4 neuron 11. Significance computed relative to a label-shuffled null distribution (1000 permutations).

F, Proportion of hippocampal neurons tuned to each of 15 semantic relationships (solid segments) compared to the proportion of tuned units (see Results for definition) in the last layer of BERT (dotted segments; 768 dimensions). Tuning was assessed using the same AUC-based method applied to neurons and model units (multiple-comparisons correction across 15 analogies). Asterisks denote categories with significant differences between hippocampus and BERT (two-proportion Z-test, q < 0.05; correction = FDR).

G, Schematic illustrating parallelogram geometry expected when a semantic axis is represented consistently: the displacement vector *"boy"*→*"girl"* parallels *"king"*→*"queen"* in an embedding space.

H, Schematic of analogical vector arithmetic (e.g., *"Paris"* − *"France"* + *"China"* ≈ ?/*"Beijing"*), illustrating how consistent axes enable analogy completion in a novel condition.

I, Example stimulus excerpt showing repeated occurrences of target lemma (black) across distinct contexts (grey).

J, Neural embeddings of *"boy"*, *"girl"*, *"kings"*, and *"queen"* computed from the population responses of 100 gender-selective neurons and visualized using multidimensional scaling. Translation vectors show that *"kings"*→*"queen"* aligns with *"boy"*→*"girl"*.

Gender-based word pairs have an aligned axis

We next extended the analysis to the eleven other word pairs having the same gender relationship as "*boy*"/"*girl*." Visual inspection shows that gender pairs are mostly aligned along a single axis (**Figure 2A and B**). We quantified this alignment using the high-dimension neural population difference vectors. (Note that we used full high dimension vectors, rather than MDS-reduced ones shown in the figures to avoid any risk that the MDS procedure artifactually aligns

vectors). To do this, we systematically removed each word pair and calculated the average
angular distance (cosine similarity) between that pair and all others. To determine significance,
we calculated a null distribution from random word differences and applied the Benjamini-
Hochberg false discovery rate (FDR) correction for multiple word pairs tested. (Benjamini &
Hochberg, 1995).

We found that neural difference vectors for valid analogical pairs were more aligned with
the word pairs in the same analogy category (**Figure 2C**) than random pairs were. The
significant pairs included "*mom*"/"*dad*," "*daughter*"/"*son*," and "*Beauty*"/"*Beast*" (referring to
characters in the Disney movie), as well as the approximate pair "*girlfriend*"/"*husband*". Two of
the twelve pairs ("*sister*"/"*brother*," q = 0.77 and "*her*"/"*him*," q = 0.26) did not reach statistical
significance. However, the overall proportion of *a priori* identified pairs (n = 10/12) was much
greater than chance (p < 0.0001, two-sided binomial test). This pattern is observed even if we
restrict our comparison set to all nouns (p < 0.0001), indicating that our result is not an artifact of
the part of speech of the control set having a single shared axis.

To assess the robustness of our axis-alignment results against different similarity
definitions (which we currently use cosine similarity) and evaluation regime, we recomputed
alignment using Euclidean and Chebyshev similarity and additionally tested an analogy-retrieval
paradigm (ranking the target under B−A+C); none of these changes altered our overall
conclusions on the number of significant aligned pairs across different analogies.
(**Supplementary Figure 4**; Wilcoxon signed-rank tests, q(cosine, Euclidean) = 0.07; q(cosine,
Chebyshev) = 0.22; p(cosine, retrieval) = 0.097).

The parallel organization of semantic axes for gender supports generalization (**Figure
2A-C**); however parallelism alone does not guarantee cross-condition generalization, since
generalization can be limited by the relative positioning of training vs. test conditions (e.g. test
cases being packed closer than the training cases) and by trial-to-trial variability (Bernardi et al.,
2020). We next assessed the cross condition generalization performance (CCGP) for neural
responses across categories (Bernardi et al., 2020; see also Tang et al., 2023; Courellis et al.,
2024). Unlike leave-one-out decoding, cross-condition generalization performance tests whether
a neural representation supports systematic generalization across words, thereby assessing
abstract, factorized population codes. In short, CCGP quantifies the ability of a linear readout to
recover an abstract relationship (e.g., gender) from a novel word pair it has never seen before. To
do so, we trained a linear classifier to distinguish between opposing poles of an analogy (e.g.,
male/female) using a subset of word pairs (e.g., "*king*"/"*queen*," "*boy*"/"*girl*") and then tested its
ability to correctly classify individual trials from a completely held-out pair (e.g.,
"*man*"/"*woman*"). CCGP requires that the neural decision boundary learned from specific
examples must transfer to novel word pairs. We found that the hippocampal population code
supports significant cross-condition generalization for gender (**Figure 2D**). The classifier
achieved high accuracy (0.788) on held-out pairs (red line). Crucially, this performance exceeded
not only the standard chance level derived from shuffling class labels "label null" (p(label
shuffle) = 0.022), but also a more rigorous "neuron-shuffle" null (p(neuron shuffle) = 0.032),

which preserves the firing rate statistics of individual neurons while destroying their consistent
identity across words, supporting an abstract geometry of gender (Courellis et al., 2024).
These patterns are similar to, but less strong, than the ones observed in a large language
model using the same stimulus set (BERT, Devlin et al., 2019). Specifically, BERT vectors were
very tightly aligned (**Figure 2E-G**), with the exception of "*Beauty*"/"*Beast*", presumably due to
their rarity in the training set. The lower performance of the neural data relative to the LLM is
consistent with the high noise observed in neural responses, as well as the fact that the
hippocampus is undoubtedly involved in a variety of other tasks aside from language processing.
Finally, as a control, we ran the same analysis on a set of 50 randomly chosen word pairs,
to validate that we don't see alignment for just any set of words. We do not (**Figure 2I-K**). For
example, vectors calculated based on randomly chosen words "*earth*"/"*extension*" don't predict
responses to "*clear*"/"*unconscious*" or "*said*"/"*gives*". Indeed, the randomly chosen word pairs
show a broad diversity of vector angles, consistent with their random selection.

Figure 2 | Word pairs sharing a semantic relationship form aligned directions in hippocampal population space and in BERT.

A, MDS visualization of neural embeddings for the gender analogy set (12 female–male word pairs). Each point is a word, and each arrow is the difference vector oriented from the male-associated term to the female-associated term. Colors identify individual word pairs and are used consistently across **A–C**. Grey points/arrows indicate pairs that do not reach significance in the alignment test in **C**. The grey plane is a visual aid for depth only (no interpretive meaning).

B, A visualization of the same vectors in **A** after translating all vector tails to a common origin (tail alignment), applying a rigid rotation so the mean direction (blue) points upward, and normalizing vector lengths to the unit sphere (visualization only; not a separate analysis). Colors correspond to the same pairs shown in **A** and **C**.

C, Quantification of vector alignment for each gender pair using cosine similarity computed in the high dimensional neural population space (not the MDS-reduced space). For each pair, the dot shows the leave-one-out mean cosine similarity between that pair's high-dimensional difference vector and the remaining gender vectors; dot colors correspond to the pair colors in **A–B**. Grey violins indicate the null distribution derived from random word-pair differences (n = 12 random pairs / 10000 draws). Asterisks denote significance after Benjamini–Hochberg FDR correction across the 12 tested pairs (q < 0.05). Pair labels are written as female − male.

D, Cross-condition generalization performance (CCGP) for gender in the neural population. A linear classifier is trained to discriminate gender using trials from a subset of word pairs and tested on a held-out pair (leave-one-pair-out; observed accuracy = 0.788, red markers/line). Grey violins show two null distributions: a label-shuffle null (shuffling gender labels; n = 600 shuffles) and a neuron-shuffle null (shuffling neuron identities while preserving per-neuron firing statistics; n = 600 shuffles). The dashed line indicates chance (0.5). p(label shuffle) = 0.022; p(neuron shuffle) = 0.032.

E–H, Same analyses as **A–D**, applied to contextual token embeddings from BERT using the same word tokens/contexts.

E, MDS visualization of BERT embeddings for the gender analogy set (colors correspond to the same word pairs as in **A**; grey indicates the pair(s) not significant in **G**).

F, Tail-aligned and unit-normalized BERT difference vectors, rotated so the mean direction points upward (visualization only).

G, Leave-one-out cosine similarity alignment test in BERT, shown with the same conventions as **C**

H, CCGP for gender same as in D but for BERT embedding space compared against label-shuffle and unit-shuffle null distributions **I–L,** Control analyses on 50 random word pairs.

I, MDS visualization of random word neural embeddings in HPC and their pairwise difference vectors (grey plane shown for depth cue only).

J, Tail-aligned and unit-normalized random difference vectors exhibit broad angular dispersion on the unit sphere.

K, Leave-one-out cosine similarity values for example random pairs compared to the null distribution (grey violins), showing no systematic alignment (stars absent after FDR; q > 0.05). 15 example words shown, see Supplementary Figure 3 for the full list.

L, CCGP for random pairs near chance and not exceeding null distributions.

Semantic axes generalize to diverse semantic relations

We next tested six other semantic relationships (**Figure 3A-C**). For example, we *a priori*
identified ten word pairs reflecting the abstract semantic relationship that we call **residence**,
corresponding to a place and a person or group that is associated in any way with that place.
These included "*doctor*"/"*hospital*," "*Texans*"/"*Texas*," and "*Christian*"/"*church*." Among the
ten pairs in our stimulus set, all were significantly more aligned than chance (q < 0.05,
permutation test), except for "*family*"/"*home*" (q = 0.12). Overall, the proportion of aligned pairs
was much greater than chance (p < 0.0001, binomial test; CCGP: p < 0.05).
We also identified the category of protectors, describing a relationship in which one agent
is charged with guarding, protecting, or guiding the other (**Figure 3D-F**). Our examples included
"*teacher*"/ "*fifth grader*," "*doctor*"/"*patient*," and "*sergeant*"/"*soldier*". All pairs showed greater
alignment than expected by chance, except for "*parents*"/"*child*" (q = 0.34). Overall, the
proportion of aligned pairs was much greater than chance (p < 0.0001, binomial test; CCGP: p <
0.05).
We observed the same with all categories. These included **antonyms** (**Figure 3G-I**), such
as "*different*"/"*same*", "*long*"/"*short*," and "*high*"/"*low*." (Note that for antonyms, we assigned
valence according to Mohammad, 2025). Overall, 12/22 pairs of antonyms were aligned.
Unaligned antonyms did not show any obvious pattern and included "*young*"/"*old*" and
"*wrong*"/"*right*" (q > 0.05). Nonetheless, the proportion of aligned pairs, while far from
complete, was still much greater than expected by chance (p < 0.001, binomial test).
We also tested **verbal negation**, in which the word "*not*" could appear before verbs like
"*realize*," "*laugh*," and "*happen*" (**Figure 3J-L**). Overall, 13/19 pairs of verbs and their negated
forms showed alignment (p < 0.0001, binomial test). Verbal negation has some conceptual
similarity to antonymy, although several philosophers and linguists have argued they serve
different linguistic functions (Clark & Chase, 1972; Kennedy, 2007; Montague & Thomason,
1978; Quine, 1960). We therefore asked whether the coding direction for antonyms is aligned
with the verb negation axis. It is not. Training on antonyms and testing on verb negation resulted
in only 2 of the 19 pairs showing significant alignment. This proportion is non-significant (p =
0.24, binomial test, **Supplementary Figure 5A-B**). We observed similar results in the reverse
direction: training on verbal negatives and testing on antonyms yielded only 2 of 22 significantly
aligned pairs, a proportion that is likewise non-significant (p = 0.30, binomial test).
We did, however, find alignment for two other grammatical operators, the nominal plural
marker -*s* ("*boy*"/"*boys*", **Figure 3M-O**), and the comparative marker -*er*, which changes
positive adjectives to comparatives ("*close*"/"*closer*", **Figure 3P-R**). We found alignment in two
other semantic relationships: odd number + 1 ("*one*"/"*two*") and qualifiers ("*kind of*" +,
"*slightly*" +) as well (**Supplementary Figure 3I–P**).
It is important to investigate if the apparent axis alignment arises from any systematic
changes in other vector properties—for example, if comparative forms simply differed from their
stem adjectives primarily by vector **magnitude/length**, or if negated verbs were represented as

near-perfect inversions (≈180° rotations) of their affirmative forms. They did not. We addressed
this by examining the geometry of the *word-pair vectors themselves* (**Supplementary Figure**
5C-D). Because our analysis normalizes vector length prior to computing difference vectors
(**Methods**), any residual alignment cannot be attributed to consistent differences in raw vector
norms across word forms. Moreover, direct analysis of pairwise vector angles showed that
neither verbal negation (e.g., "*grow*" vs. "not *grow*") nor comparison (e.g., "*tall*" vs. "*taller*")
behaved like simple inversions, consistent with Zuanazzi et al., (2024); instead, these
transformations tended to be expressed as directions that are approximately orthogonal to the
root-word vectors, rather than as sign flips or uniform length scaling (**Supplementary Figure**
5D). Together, these controls indicate that the semantic axes we identify reflect a genuine
direction-consistent relational transformation, rather than a byproduct of systematic norm
changes or antipodal structure in the underlying word vectors.
In all six relationships shown in **Figure 3**, as in the gender relationship (**Figure 2**),
limiting our control set to the matching part of speech (POS) did not compromise the measured
alignment (p < 0.05 in all cases, binomial test). And, not surprisingly, in all cases, we found the
same results with BERT no matter if we limit POS or not (p < 0.0001).
We also tested for potential confounds from morphosyntax. Fortunately, the English
language offers convenient controls, because the agentive derivational suffix *-er* is identical to
the adjective comparative suffix. We identified two word pairs in which our corpus contained
both a verb and its derived form ("*teach*"/"*teacher*" and "*keep*"/"*keeper*"). Neither of these was
aligned with the comparative adjective axis shown in Figure 3P (**Figure 3U**). While there are
only two, the chance that these two of them rank the lowest in cosine similarity together with the
adj comparative pairs is 2.78% (i.e., p = 0.0278). We conclude that the positive/comparative axis
is selective for that relationship; it is not a general *-er* axis. Likewise, in English, the third person
present tense, simple aspect conjugation *-s* ("he *pulls* the rope") has the same morphological
marking as the plural *-s* ("the *dogs* in the park"). We asked whether verb pairs in the infinitive
vs. present simple conjugations are aligned with the noun plural axis shown in Figure 3M. They
are not (**Figure 3V**). Indeed, only three of the 19 pairs were significant. This proportion is much
lower than the proportion of noun plural pairs (23/43) that are significant (p = 0.0051, left-tail
Fisher's exact test).
407

Figure 3 | Semantic axes for multiple analogical relations.
A–R, Six semantic relationships define consistent difference directions in hippocampal population space
and support cross-condition generalization. For each relationship, the left panel shows a 3D MDS
visualization of neural word embeddings with arrows indicating paired difference vectors (direction
defined by the relationship; MDS is for visualization only). Colored arrows/labels denote pairs whose
high-dimensional difference vectors are significantly aligned with other pairs in the same analogy
(permutation test against a random word-pair null; Benjamini–Hochberg FDR across pairs within
category); grey arrows/labels denote non-significant pairs. The blue arrow shows the mean direction
projected into the MDS view. Grey planes are visual aids only (no interpretive meaning). Middle panels
show the same vectors after tail alignment to a common origin and rigid rotation, so the mean direction
points upward, with vector lengths normalized to a unit sphere (visualization only; angles are preserved).
Right panels show cross-condition generalization performance (CCGP) for each relationship (red marker),
compared with a label-shuffle null and a neuron-shuffle null (grey violins; dashed line indicates chance).
Asterisks indicate $p < 0.05$ (permutation test; n shuffles = 600) relative to the corresponding null. See
Supplementary Figure 3 for a full list of word-pair labels in the MDS plot, color-coded consistently.
A–C, Residence. Difference vectors link an agent/group to an associated place (e.g., "*doctor*"→"*hospital*");
CCGP is significant.
D–F, Protectors. Vectors link a protector/guide to the protected individual/group (e.g.,
"*teacher*"→"*grader*"); CCGP is significant.
G–I, Antonyms. Antonym vectors are oriented according to valence; CCGP is significant. See
Supplementary Figure 3 for a full list of word-pair labels in the MDS plot, color-coded consistently.
J–L, Verb negation. Vectors connect affirmative verbs to their negated forms (e.g.,
"*laugh*"→"*not+laugh*"); CCGP is significant.
M–O, Noun plural. Vectors connect singular nouns to their plural forms (suffix -s); CCGP is significant
(p(label) < 0.05; p(neuron) > 0.05).
P–R, Adjective comparative. Vectors connect positive adjectives to comparative forms (e.g.,
"*tall*"→"*taller*"); CCGP is significant.
S, Testing whether the adjective comparative axis reflects a generic -er morphology: mean cosine similarity
of derivational agentive -er pairs (e.g., "*teacher*"−"*teach*", "*keeper*"−"*keep*") to the adjective comparative
pair directions, shown against a random-pair null (grey violin).
T, Testing whether the noun single/plural axis can be generalized to a verb +s axis: mean cosine similarity
of third-person singular verb vs base-form pairs (e.g., "*pulls*"−"*pull*") to the noun plural–single pair
directions.

Gender

male	female	HPC	ACC	OFC	BERT
man	woman	0.172	0.138	0.000	0.418
dad	mom	0.213	0.176	-0.026	0.456

Noun Plural

single	plural	HPC	ACC	OFC	BERT
bed	beds	0.164	-0.061	0.009	0.339
doctor	doctors	0.132	0.094	-0.047	0.317

Residence

human	places	HPC	ACC	OFC	BERT
Christian	church	0.202	0.398	0.209	0.290
doctor	hospital	0.275	0.399	-0.280	0.326

Verb -ed/-ing

verb-ed	verb-ing	HPC	ACC	OFC	BERT
fixed	fixing	-0.068	0.140	0.033	0.240
gave	giving	-0.029	0.137	-0.003	0.133

Protector

protector	human	HPC	ACC	OFC	BERT
doctor	patients	0.349	0.254	0.404	0.248
parents	child	0.035	0.423	0.371	0.384

Verb Negation

verb	negated	HPC	ACC	OFC	BERT
get	not+get	0.183	0.169	0.071	0.391
feel	not+feel	0.093	0.284	0.276	0.343

Antonyms

antonyms	low-valence	HPC	ACC	OFC	BERT
yes	no	0.134	0.222	0.075	0.084
big	little	0.122	0.109	0.089	-0.006

Adj Comparative

adjective	comparative	HPC	ACC	OFC	BERT
good	better	0.175	0.280	0.631	0.510
full	fuller	0.223	0.047	0.508	0.320

Odd Number +1

odd	odd+1	HPC	ACC	OFC	BERT
one	two	0.447	0.283	0.239	0.200
single	couple	0.359	-0.094	0.323	0.227

Qualifier

qualifer	word	HPC	ACC	OFC	BERT
q+figured	figure	0.431	0.256	0.320	0.307
q+fall	fall	0.368	0.181	0.243	0.230
q = (kind of)					

Pron. Obj/Poss

objective	possessive	HPC	ACC	OFC	BERT
me	my	0.331	0.327	0.241	0.557
him	his	0.212	0.323	0.381	0.575

Pron. Plural

single-pron.	plural-pron.	HPC	ACC	OFC	BERT
I	we	0.471	0.241	0.324	0.427
me	us	0.393	0.159	-0.096	0.426

Pron. Subj/Poss

subjective	possessive	HPC	ACC	OFC	BERT
I	my	0.276	0.284	0.226	0.688
us	our	0.126	-0.212	0.447	0.526

Pron. 1st/3rd

1st-person	3rd-person	HPC	ACC	OFC	BERT
we	they	0.207	-0.064	0.151	0.368
my	her	0.226	-0.040	0.441	0.327

Pron. Subj/Obj

subjective	objective	HPC	ACC	OFC	BERT
I	me	0.192	0.192	0.206	0.542
they	them	0.188	0.155	0.092	0.461

Neuron-count

	pair-count	HPC	ACC	OFC	BERT
Noun.Plural	43	28	17	14	138
VerbEd/Ing	39	36	39	11	146
VerbNeg	19	47	11	9	38
Adj/Comp	7	117	18	8	120
Qualifier	8	14	44	13	120
Obj/Pos	6	185	10	13	60
Sub/Pos	6	124	9	13	120
Sub/Obj	7	154	82	12	30
Pron.Number	6	11	38	8	120
Pron.1st3rd	6	148	19	8	120

Neuron-count

	pair-count	HPC	ACC	OFC	BERT
Gender	12	100	75	8	120
Residence	9	150	13	8	120
Protector	7	56	18	8	120
Antonyms	22	31	49	8	120
OddNumber+1	9	25	16	15	120

Table 1. Example word pairs and pair/neuron count summary. Top: Example word pairs of each analogy and their mean cosine similarities (after subtraction) with the other word pairs in the same analogy across different brain areas/LLM. Light blue means significantly aligned pairs. Bottom: number of word pairs and the number of neurons with strong tuning strength (low p(AUC) value) used for each analogy.

Semantic axes in pronouns formed prismatic structures

Our corpus contained all seven of the English personal pronouns in both nominative (e.g.,
"*I*") and accusative (e.g., "*me*") forms. Of these seven, we found alignment for five (only the pair
"*it (nominative)*"/"*it (accusative)*" and "*you (nominative)*"/"*you (accusative)*" were not aligned
(**Figure 4A-C**). This proportion is significant ($p < 0.0001$, binomial test). Our corpus also
contained all seven of the English personal pronouns in the possessive ("*my*") form. The
nominative/possessive forms ("*I*"/"*my*") were also aligned ($p < 0.0001$, **Figure 4E-F**). Of the
seven accusative/possessive pairs, we found alignment for six (only the pair "*her*"/"*her*" was not
aligned, **Figure 4G-I**). This proportion is much greater than chance ($p < 0.001$). English
pronouns also have a singular/plural semantic axis (e.g., "*I*"/"*we*"), which can also appear in the
accusative case ("*me*"/"*us*") and in the nominative possessive form ("*my*"/ "*our*"). All seven
examples of the singular/plural set were aligned, $p < 0.0001$, **Figure 4J-L**.
So far, we tested pronoun analogies one relation at a time. These pairwise tests do not
determine whether the full set of pronouns forms a jointly consistent geometry across multiple
features, nor do they constrain the relative magnitudes of the transformations. To address this,
we analyzed the twelve pronouns spanning the person × number × case, which included first
person {"*I*", "*me*", "*my*", "*we*", "*us*", "*our*"} and third person {"*he*", "*him*", "*his*", "*they*",
"*them*", "*their*"}. (We did not have all necessary (single/plural) pronoun type labels for the
second person "*you*" and "*your*", so they were only used for visualization, **Figure 4O, 4P** but not
any formal analysis). For statistical power, we pooled third person singular pronouns for this
analysis. For each word, we averaged firing rates across trials to obtain a single population
vector per pronoun, then z-scored each neuron's responses across the twelve words. The case ×
number combinations for the first-person pronouns reveal a clear prism-shaped structure in 3-d
space after dimension reduction (**Figure 4M**). Likewise, the case × number combinations for the
third person (**Figure 4N**) reveals another prism. Moreover, these prisms largely overlapped but
remained visually separable (**Figure 4O**).
To quantify whether these prisms reflect a genuinely compositional structure (Phillips,
2022)—rather than a set of independent pairwise parallels—we used a loop-closure
(commutativity) test defined on each 2×2 face of the prism (Andreas, 2019). Consider any
quadrangle with four vertices a, b, c, d arranged as `(plural, case1) = a`, `(singular,`
`case1) = b`, `(plural, case2) = c`, and `(singular, case2) = d`. If number and
case compose independently (i.e., the representation is locally factorized), then changing number
should not depend on case, and equivalently changing case should not depend on number. This
can be expressed as the commutator/closure vector `|(a - b) - (c - d)|`, which should
be close to zero in an ideal prism because `(a - b)` and `(c - d)` are the same "number shift"
computed in two different cases. By simple rearrangement, this is equivalent to `|(a - c) -`
`(b - d)|`, which instead compares the "case shift" at plural vs. singular. Thus, the same

statistic tests path–independence: going from singular→plural and then case1→case2 should
land in the same place as going case1→case2 and then singular→plural. From the non-reduced,
high- dimensional neural vector data we computed this closure error for the three unique case-
pair rectangles within each person prism separately (SUB–OBJ, SUB–POSS, OBJ–POSS) and
summarized prism distortion (non-closure) as the mean Euclidean norm of these closure vectors;
this statistic penalizes both directional and magnitude inconsistencies across the rectangle edges,
and goes beyond asking whether any single displacement (e.g., "*we*"–"*I*") is nonzero or parallel
to another displacement. Significance was assessed against a label-shuffled null distribution (500
shuffles).
Overall, loop-closure error across both person prisms was significantly lower than
expected under the null (p = 0.002, permutation test), indicating that the joint structure across
person/number/case is not explained by chance alignment of word means. When stratified by
person, loop closure was robust for first-person pronouns (p = 0.004) but substantially weaker
for third-person pronouns (p = 0.084 when considered in isolation). With a matched vertex label
swapping permutation test between the first and the third person prism, we further confirmed that
the first-person prism was significantly more closed than the third person one (p = 0.0312). This
dissociation can be observed in the plots (**Figure 4M-O**): the third-person configuration (**Figure
4N**) appeared more distorted, consistent with reduced commutativity (i.e., the rectangle edges
fail to match as closely across case/number for third person). Overall, these results extend the
earlier pairwise parallelogram analyses by showing that at least part of the pronoun system
satisfies global closure constraints expected from a prism-like (Trager et al., 2024) compositional
(Mitchell & Lapata, 2008, 2010) geometry, rather than only exhibiting local parallelograms.
We next asked whether the same conclusion is supported from a model-based perspective
that explicitly tests factorization across features (Kobak et al., 2016). We fit multivariate linear
encoding models to the pronoun-elicited neural population responses at individual trial level
using (i) a main-effects model with additive terms for person, number, and case and (ii) a full
model that also included interaction terms (**Methods**). In the neural data, the full model
explained a small fraction of total variance (`R2_full = 0.0175`), indicating substantial
neural variability in naturalistic listening that could plausibly reflect (among other factors)
context-dependent processing and predictive coding highlighted in prior work (Goldstein et al.,
2022; Jain & Huth, 2018; Kumar et al., 2024; Heilbron et al., 2022). Importantly, however, the
main-effects component accounted for a large fraction of the variance that was explainable by
the full model: the ratio `R2_main/R2_full` was 50.4%, and this fraction was significantly
larger than in the label-shuffled null (p = 0.006). Thus, even though the total predictable variance
is modest, the predictable component is disproportionately organized along separable axes
corresponding to person/number/case. This pattern suggests that the pattern differences
associated with each feature are relatively invariant across the other features (i.e., weak
interactions), consistent with an approximately separable / partially factorized component in
pronoun (Soto et al., 2018; Pooresmaeili et al., 2010) representation. Together, the loop-closure
and additive-model results indicate that the pronoun code is not merely a set of independent

analogies; it includes a structured component that supports joint composition across features,
albeit with person-dependent departures from ideal factorization that are most evident in third
person.
529   Finally, we repeated the same analyses on BERT embeddings for the same pronoun set in
the same story contexts (**Figure 4N**). In BERT, the low-dimensional embedding exhibited the
same prism-like organization found in the neural data, but with more clearly separated first- and
third-person prisms. Quantitatively, loop closure was observed, just as it was with neural data (p
= 0.002). In the additive-model analysis, BERT showed substantially higher overall explainable
structure (`R2_full` = 0.2874), and a stronger degree of factorization: `R2_main/R2_full`
was 78.6%, also significant relative to the shuffled null (p = 0.002). Thus, BERT implements a
strongly separable, idealized encoding of person/number/case.
537

Figure 4 | Compositional semantic axes in pronouns.

A–C, Subject–object case (Pron. Subj/Obj)**.** Difference vectors between nominative and accusative pronoun forms in the hippocampus (e.g., "*I*"→"*me*") are tail-aligned and visualized on a unit sphere ("globe"; **A**) after a rigid rotation so the within-relation mean direction points upward (blue; visualization only). **B,** For each pronoun pair, the dot shows its leave-one-out cosine similarity to the direction of other word pairs computed in the high-dimensional neural population space (not the visualization space); grey violins show the null distribution from random word-pair differences (n = 10000 draws; see **Methods**). Asterisks indicate significant alignment after Benjamini–Hochberg FDR correction across pairs within the relation (q < 0.05). Pairs shown in grey do not reach significance (including "*you*" and "*it*" in nominative vs accusative), yielding 5/7 aligned pairs overall (binomial p < 0.0001). **C,** Cross-condition generalization performance (CCGP) for decoding nominative vs accusative case using a linear classifier trained on a subset of pairs and tested on a held-out pair (see **Methods**). Red markers

show observed CCGP; grey violins show label-shuffle and neuron-shuffle nulls (n = 600 shuffles); dashed line

indicates chance.

D–F, Subject–possessive (Pron. Subj/Poss). Same conventions as **A–C**, but for nominative vs possessive

determiners (e.g., "*I*"→"*my*").

G–I, Object–possessive (Pron. Obj/Poss). Same conventions as **A–C**, but for accusative vs possessive forms (e.g.,

"*me*"→"*my*"). The homographic possessive/object form "*her*" (poss vs obj) does not show reliable alignment

(grey).

J–L, Number (Pron. Plural). Same conventions as **A–C**, but for singular→plural transformations expressed across

case/possessive contexts (e.g., "*I*"→"*we*", "*me*"→"*us*", "*my*"→"*our*", and third-person analogs). All tested

singular–plural pairs are aligned (binomial p < 0.0001). CCGP exceeds the label-shuffle null (asterisk) (p(label) <

0.05), but not the neuron-shuffle null.

Related visualizations. Multidimensional-scaling (MDS) plots of the individual pronoun analogies geometry

matching panels **A-L** are shown in Supplementary Fig. 5

M-O, Joint pronoun geometry in hippocampal population space. Multidimensional scaling (MDS) visualization of

the mean neural population vectors for pronouns spanning the person × number × case triad. Arrows highlight the

four component transformations tested in panels **A–L**, using a consistent color code: number (singular→plural;

blue), subject→object (nominative→accusative; red), subject→possessive (magenta), and object→possessive

(dark red/brown). The lower-left subplot **O** shows the full configuration with all pronoun vertices/edges; the top

M (first-person) and right **N** (third-person) subplots are the same embedding with the other pronouns removed for

clarity (coordinates unchanged). Third-person singular forms are pooled where indicated (e.g., "*she, he, it$_{subj}$*",

"*him, it*$_{obj}$", "*his, her*$_{poss}$"). Visually, the third-person prism appears more distorted than the first-person prism. n =

150 hippocampus neurons (top 50 most tuned neurons from each of the 4 analogies in panel A-L pooled).

N, Same analysis of M-O in BERT**.** MDS visualization of BERT contextual embeddings for the corresponding

pronoun set. n = 52 BERT units (top 30 most tuned units from each of the 4 analogies in panel A-L pooled).

Arrows use the same color conventions as in **M-O**, and the embedding exhibits a similar prism-like organization

with more clearly separated first- and third-person configurations.

Analogy type dependent semantic axes specialization in ACC and OFC

We next analyzed data from two other brain regions, ACC and OFC. We used neuron-

count-matched random subsampling (500 iterations) to account for smaller numbers of neurons

in these regions (**Figure 5A**). We found that alignment scores were largely similar to

hippocampus in ACC, but a bit lower in OFC (**Figure 5B and C**). In ACC, we found that 13 of

the 15 analogies showed alignment, while 10 of the 15 analogies showed alignment in OFC.

We assessed areal differences using a brain-area label-shuffling test: we computed the

observed cosine similarity under neuron-count matching, then generated a null distribution by

pooling neurons across areas, randomly permuting the HPC/ACC label assigned to each neuron

(500 shuffles), and repeating the same neuron-count-matched cosine-similarity computation for

each shuffle. This non-parametric test yielded p = 0.016, meaning that under random

reassignment of neurons to HPC/ACC labels, only 1.6% of shuffles produced an HPC–ACC

analogy-type distribution that was at least as divergent as the one observed. Thus, even when

controlling for neuron count, the distribution of significant word-pair counts across analogy

categories shows an area-specific structure, consistent with specialization of analogy-type
selectivity between HPC and ACC. This across analogy area specialization was also observed
between HPC and OFC, p = 0.002.
To pinpoint *where* this area-specific structure arises at the word-pair level, we
summarized each word pair with a 0–1 significance-prevalence score (sigPrev) that captures how
likely that pair is to be deemed significantly aligned with other pairs in HPC in an analogy under
ACC-matched sampling (i.e., in HPC, a higher value indicates a more reliably detectable
significant word-pair under neuron count matched random subsampling; In ACC, it means the
word pair is significant). We fit a linear mixed-effects model with fixed effects of (brain) Area,
(analogy) Type, and their interaction, and a random effect for word-pair identity: sigPrev ~
1+Area×Type+(1|PairID), n = 412 word pair observations. Marginal ANOVA tests indicated
significant effects of Area $F(1, 382) = 7.22$, p = 0.008, Type $F(14, 382) = 15.53$, p = 7.6e-30
and a robust Area × Type interaction $F(14, 382) = 9.67$, p = 1.8e-18. Thus, regional differences
in the reliability/prevalence of significant word-pairs depended on analogy type (highly
significant interaction terms (Wischnewski & Peelen, 2021)). The Area × Type interaction was
also significant when repeating the analysis with HPC and OFC $F(14, 382) = 5.68$, p = 4.8e-10.
Given the significant interaction, we ran follow-up simple-effects contrasts (Wald t-tests)
comparing HPC vs ACC within each analogy type (15 types) and controlled for multiple
comparisons using Benjamini–Hochberg FDR correction. After FDR correction, significant
HPC–ACC differences were observed for 4 of 15 types: Verb *-ed*/*-ing*: q = 5.5e-11 (more in
ACC), Pronoun 1st/3rd: q = 0.0016 (more prevalent in HPC) , Noun Plural: q = 9.0e-11 (more in
HPC) , Adj Comparative: q = 0.024 (more in HPC). All other analogy types showed no reliable
HPC–ACC differences after FDR correction (q > 0.05). Similarly, significant HPC–OFC
differences were observed for 6 of 15 types: Protector: q = 0.046 (more prevalent in OFC) , q <
0.05 more prevalent in HPC for Pronoun Plural, Noun Plural, Gender, Residence, Antonyms. All
other analogy types showed no reliable HPC–OFC differences (q > 0.05).
Figure 5D-F shows examples of an analogy type in which OFC shows more prevalent
relational structure than the hippocampus (HPC), and a final case in which ACC clearly
outperforms HPC (**Figure 5G–L**). For the Protector relationship (e.g., "*sergeant*"/"*soldier*",
"*teacher*"/"*(fifth) graders*", "*doctor*"/"*patients*"), OFC showed a coherent direction with multiple
aligned pairs (colored vectors in **Figure 5D**; concentrated directions in the tail-aligned
visualization in **Figure 5E**). This relational geometry is yet to support robust generalization:
CCGP was not well above chance, potentially due to the low neuron count in OFC (**Figure 5F**).
Finally, we observed a striking dissociation for the verb −*ed*/−*ing* relationship (past vs.
progressive aspectual forms; e.g., "*laughed*" vs "*laughing*", "*did*" vs "*doing*", "*told*" vs
"*telling*"). In ACC, these vectors exhibited strong within-category alignment (**Figure 5G–H**) and
supported above-chance generalization against label shuffle null (**Figure 5I**). In contrast, the
hippocampal population did not show a comparably consistent axis for the same verb −ed/−ing
pairs (**Figure 5J–K**), and CCGP remained near chance with no reliable improvement over either
null distribution (**Figure 5L**). This side-by-side comparison (**Figure 5G–L**) provides an

intuitive visualization of the region-level specialization: ACC expresses a much clearer
past/progressive axis than HPC, whereas HPC shows advantages for other semantic categories
such as pronoun person and noun nominal number.

636
Figure 5 | Complementary specialization of hippocampus against anterior cingulate cortex and
orbitofrontal cortex across analogy types.
A, Number of units included from hippocampus (HPC), anterior cingulate cortex (ACC), and
orbitofrontal cortex (OFC) along with the number of BERT units/dimensions used for comparison
B, Number of significant aligned word pairs for each analogy type in downsampled HPC (solid circles)
and ACC (dashed squares). Symbols denote analogy types with significant HPC–ACC differences after
Benjamini–Hochberg FDR correction (Wald t-tests; q < 0.05; see main text). Significant asterisk color
indicated which region had higher value (black, HPC; magenta, ACC)
C, Same as in B but for OFC.
D–F, Protector relationship in OFC. **D,** MDS visualization of OFC word embeddings and within-category
difference vectors (grey indicates non-significant pairs). Blue arrows denote the within-category mean
direction. Grey planes are visual aids only. Colors in D and E match each other. **E,** Tail-aligned unit-
sphere visualization of the same vectors, rotated so the mean direction points upward and normalized in
length (visualization only). **F,** Cross-condition generalization performance (CCGP; red) compared to
label-shuffle and neuron-shuffle null distributions (grey violins; dashed line indicates chance).
G–I, Verb −ed/−ing relationship in ACC, shown as in D–F. See Supplementary Figure 6 for a full list of
word pair labels in MDS plot color-coded consistently.
J–L, Verb −ed/−ing relationship in HPC, shown as in D–F.
M–O, P–R, Conventions: MDS panels are for visualization; cosine similarity/alignment

Partial neuron-level functional specialization for analogies

We next asked whether the coherent semantic axes we found are mediated by specialized
analogy neurons or reflect mixed-selective semantic coding (Rigotti et al., 2013; Fusi et al.,
2016). We therefore quantified how single-neuron tuning generalizes across analogy types and
how population readouts re-weight neurons across analogy types (**Figure 6**). Throughout, we use
the term *across-class* tuning to refer to the original class decoding for a given analogy (e.g.,
gender, **Figure 1E**), summarized by per-neuron area-under-the-curve (AUC, computed from
firing-rate based decoding within each analogy, **Figure 1E** and **Methods**). Analyses were
repeated under two inclusion regimes: (i) significantly selective neurons only ($p(AUC) < 0.05$)
and (ii) all neurons. The same analyses were performed on hippocampal neurons and on units in
the BERT embeddings (paired panels: hippocampus in the upper rows and BERT directly below;
e.g., **Figure 6B–D** vs **Figure 6E–G**), as well as in ACC and OFC (**Supplementary Figure 7**).
After sorting hippocampal neurons by their most strongly tuned analogy type, the AUC
matrix exhibited a near-diagonal block structure, suggestive of specialization (**Figure 6A**).
Specifically, each analogy type was associated with a distinct set of neurons that had elevated
participation in that analogy type, indicating that a partially discrete subsets of neurons
preferentially support different analogy dimensions. Importantly, however, there were also
moderate off-diagonal activations, indicating that many neurons had above-baseline tuning for
analogy types beyond their preferred one. Thus, semantic codes are partly multiplexed.
To quantify these observations, we used an intersection-over-union approach (IoU;
Jaccard index, Jaccard, 1912) between the sets of neurons significantly participating in each
analogy pair (**Figure 6B**). In the hippocampus, IoUs were generally low across most analogy
pairs, indicating that significant tuning is typically carried by distinct subpopulations for
different analogies. The inset example (gender vs. antonyms) illustrates this low overlap (6
shared neurons out of 48 and 30 tuned neurons, respectively; IoU = 0.08). Interestingly, analogy
pairs involving closely related, human-referential analogies (e.g., pronoun-related and social-role
analogies) tended to show comparatively higher IoU values than unrelated pairs, suggesting
partial sharing within semantically coherent clusters. In contrast, BERT exhibited substantially
larger overlaps between tuned unit sets across analogy types (**Figure 6E**). For the same
illustrative pair, gender and antonyms included 569 and 226 tuned units with 176 shared (IoU =
0.28), consistent with more widespread reuse of features across analogy types, potentially
reflecting the distributed mixing of information across embedding dimensions produced by the
model's repeated self-attention and densely connected feed-forward sublayers throughout the
transformer (Clark et al., 2019; Devlin et al., 2019).
Overlap alone does not determine whether neurons that participate in multiple analogies
do so with similar *strength*. We therefore asked, among neurons tuned to at least one of two
analogy types (union set: $p(AUC) < 0.05$ for either member of the pair), whether a neuron's
AUC for one analogy predicts its AUC for another. In the hippocampus, pairwise correlations of

AUC across analogy types were predominantly negative (**Figure 6C**; significant analogy type pairs marked after FDR correction), indicating specialization. In other words, neurons that strongly separate the two classes within one analogy tend to have weaker roles for other analogy types. The inset in Figure 6C (gender vs antonyms) shows an example negative relationship (r = −0.45). A limited set of positive correlations appeared, most notably among closely related pronoun-based analogies and select human-referential categories. BERT showed the same tendency under the tuned-unit restriction but with smaller magnitude correlations (**Figure 6F**), indicating that even when many units are significant for multiple analogies (high IoU, **Figure 6E**), tuning magnitude can still display specialization.

When we expanded the analysis to include all neurons, the AUC–AUC correlation structure shifted: correlations became weakly positive across much of the matrix in HPC (**Figure 6D**) and, similarly, moved toward near-zero/slightly positive in BERT (**Figure 6G**). This reversal suggests a two-tiered organization: specialized strongly selective neurons overlaid on a less specialized set of less selective generalists.

To test whether the same principles hold for population coding, we fit a logistic regression model decoding member classes (e.g., male vs female in the gender analogy) of each analogy type from neural population activities and decoder used the absolute weight magnitude (|w|) assigned to each neuron(brain)/unit(BERT) as an index of its contribution to that analogy's population decision variable. We then computed correlations between |w| vectors for each analogy pair. In the hippocampus, when restricting to tuned neurons, weight correlations were negative (**Figure 6H**), paralleling the AUC anti-correlations and showing that factorization persists at the level of the optimal linear readout (t-test for a correlation coefficient, q < 0.05 after FDR correction). The inset illustrates an example of strong negative correlation of weight vectors (Adj Comparative vs Qualifier; r = −0.54), indicating that decoders (or potential downstream neural readouts) for different analogy types tend to recruit the subsets of the tuned population at starkly divergent strengths. In BERT, tuned-unit weight correlations were generally closer to zero, with fewer significant effects (**Figure 6J**; example r = −0.31), again consistent with a less sharply segregated readout structure. When all neurons/units were included (hippocampus: **Figure 6I**; BERT: **Figure 6K**), weight correlations moved toward near-zero or weakly positive values (HPC example r = 0.07; BERT example r = 0.04), consistent with broadly distributed and orthogonalized contribution plus a tiny, shared component rather than sharply task-specific recruitment across the neural population.

Finally, we asked whether neurons that encode an analogy's (across-class separation) also encode *within-class* distinctions among words on the same side of the analogy—operationally defined as "role" coding within-class (e.g., "*man*" vs "*king*" within the male set; "*woman*" vs "*queen*" within the female set). They mostly do not. For each analogy type, we computed a within-class AUC (averaged over within-class pairwise discriminations) and correlated it across neurons with the original across-class AUC for that analogy (**Figure 6L–M**). Within high tuning strength (low p(AUC)) neurons, within-class and across-class tuning were often not or weakly related and could be either positively or negatively coupled depending on analogy type (**Figure**

6L). For verb tense (verb-*ed* vs verb-*ing*), within-class AUC was positively correlated with
across-class AUC (r = 0.41, p < 0.0001), whereas for word–qualifier the relationship was
strongly negative (r = −0.61, p < 0.0001). The prevalence of negative (and sometimes significant)
correlations indicates that across-class information and within-class role/identity information are
at least partly factorized across neurons: neurons best at separating the two sides of an analogy
are not necessarily those best at discriminating items within a side. BERT also showed a strong
tendency toward factorization for certain analogy types (**Figure 6M**), including a robust negative
relationship for word–qualifier (r = −0.50, p < 0.0001), while verb tense showed little coupling (r
= 0.05, p = 0.167). We observed qualitatively similar specialization effects in ACC and OFC
(**Supplementary Figure 7**).

Figure 6 | Partial factorization of analogy tuning across the neural population.

A, Across-class analogy tuning in hippocampus (HPC). Heat map shows per-neuron decoding strength (AUC values z-scored per analogy type) for each of 15 analogy types (rows) across all recorded hippocampal neurons (columns; n = 437). Neurons are sorted by their most strongly tuned analogy type, producing a near-diagonal block structure consistent with partial factorization.

B, Overlap of tuned-neuron sets across analogy types in HPC. Each cell shows the intersection-over-union between the sets of neurons significantly tuned to each pair of analogies significance assessed via the label-shuffled null described in Fig. 1E and **Methods**). Inset: example overlap for Gender vs Antonyms (48 and 30 tuned neurons, 6 shared; IoU = 0.08).

C, Pairwise coupling of tuning magnitudes across analogy types in HPC among tuned neurons. For each analogy pair, the color indicates the Pearson correlation (r) between neurons' AUC values computed for the two analogies, restricted to the union set of tuned neurons for either analogy (p(AUC) < 0.05 for at least one member of the pair). White dots indicate correlations significant after Benjamini–Hochberg FDR correction across analogy pairs (q < **0.05**). Inset: Gender AUC vs Antonyms AUC, each dot is a neuron, red line and shade is linear regression fit and 95% CI.

D, Same as **C**, but including all hippocampal neurons. Correlations shift toward weakly positive values, indicating weak shared structure when the full population is included.

E–G, Same analyses as **B–D**, performed on BERT embedding "units" (last-layer dimensions; 768 units;).

E, IoU overlap matrix for tuned BERT units. inset: Gender vs Antonyms (569 and 226 tuned units, 176 shared; IoU = 0.28). **F,** AUC–AUC correlation matrix among tuned units (white dots: FDR-significant; inset r = −0.14). **G,** AUC–AUC correlations across all units (inset r = 0.04).

H–K, Factorization at the level of optimal linear population readouts. For each analogy type, a logistic-regression decoder was fit and each neuron/unit's contribution was summarized by the absolute decoder weight |w|. Heat maps show pairwise Pearson correlations between |w| vectors across analogy types. **H,** HPC tuned neurons, with predominantly negative correlations; white dots indicate FDR-significant correlations (q < **0.05**). Inset: Adj Comparative vs Qualifier |w| (r = −0.54). **I,** HPC all neurons, with correlations near zero/weakly positive (inset r = 0.07). **J,** BERT tuned units (inset r = −0.31). **K,** BERT all units (inset r = 0.04).

L–M, Relationship between across-class and within-class coding. For each analogy type, within-class AUC (mean discriminability among words within the same side of the analogy) was compared to the original across-class AUC across neurons/units; the left column summarizes the correlation for each analogy type (color indicates the correlation coefficient). Insets show example relationships. **L,** HPC: within-class vs across-class AUC correlations can be positive (verb-ed vs verb-ing: r = 0.41, p < 0.0001) or negative (word–qualifier: r = −0.61, p < 0.0001), indicating partial separation of axis coding from within-side "role/identity" coding. **M,** BERT: weak coupling for verb-ed vs verb-ing (r = 0.05, p = 0.167) but strong negative coupling for word–qualifier (r = −0.50, p < 0.0001).

DISCUSSION

Analogical reasoning is the ability to understand a novel situation by mapping its
relational structure onto that of a known situation—focusing on relations between elements
rather than the elements themselves (Gentner, 1983; Gentner & Markman, 1997; Hofstadter,
2001; Holyoak & Thagard, 1996). It allows cognition to generalize across superficially different
domains by preserving higher-order structure (e.g., A relates to B as C relates to D). This
capacity is central to human thought because it supports abstraction, transfer of knowledge,
problem solving, and learning from sparse experience, and it underlies domains ranging from
language and mathematics to social inference and scientific discovery (Hofstadter, 1995;
Gentner, 2010). We find that semantic meaning is encoded in specific axes in high dimensional
neural space. These axes are consistent across multiple words with similar relationships, forming
a parallelogram-like shape in a neural embedding space. This structure offers a solution to the
problem of analogical reasoning, namely, it allows us to reason analogically by making use of
vectorial arithmetic (Gärdenfors, 2000, 2014; Mikolov et al., 2013; Rumelhart & Abrahamson,
1973). This geometry also provides a potential neural substrate for grammatical productivity,
consistent with speakers' ability to apply morphological rules to novel items (e.g., Berko, 1958).
The near-closed prism geometry for pronouns—spanning person × number × case —
supports the view that these grammatical features contribute an approximately separable
(invariant) component to the pronoun code—i.e., the displacement associated with one feature is
largely preserved across the levels of the others (Ashby & Townsend, 1986; Soto et al., 2018),
consistent with a transformation-based view of factorized representations (Higgins et al., 2018).
The prism's near-closure further implies approximate path-independence, such that applying
number- and case-related transformations in either order yields similar endpoints, consistent with
commuting transformations in symmetry-based accounts of factorized representations (Higgins
et al., 2018; Zhu et al., 2021). By contrast, a purely pairwise association / lookup-table scheme—
or an exemplar-based account in which each mapping is learned independently—does not,
without additional compositional structure, naturally predict systematic closure and order-
invariant composition across multiple dimensions (Nosofsky, 1986). Importantly, this kind of
closure is not guaranteed by high-dimensional representations in general; rather, these systematic
order-invariant composition is a diagnostic signature of structured factorization/disentanglement,
which typically requires specific inductive biases or architectural constraints (Higgins et al.,
2022; Locatello et al., 2020; Higgins et al., 2018), raising the possibility that the brain operates
under comparable compositional constraints. More broadly, the emergence of such factorized
structure at the level of neural population geometry suggests a concrete mechanism by which the
brain could support rule-like generalization over linguistic variables without invoking discrete
symbolic representations (Smolensky, 1988). Such an organization naturally supports
productivity, in that a small set of learned operators can be recombined to generate a large space
of grammatical forms, and it suggests a learning advantage whereby new combinations can be
inferred from existing structure rather than acquired through exhaustive experience (Berko,
1958; Courellis et al., 2024; Flesch et al., 2022, 2023; Kemp & Tenenbaum, 2008).

Our results confirm and extend previous studies looking at analogical representations in
the brain. Most relevantly, hemodynamic responses in fronto-temporo-parietal semantic network
show vector-arithmetic type properties in a tightly controlled stimulus set and task (Wu et al.,
2022). Moreover, during natural stories, brain-wide encoding models can find semantic axes in
many regions (Zhang et al., 2020). However, the relationship analyses rely on encoding model
predicted responses, and the dataset pools across subjects who listened to different stories; this
strategy is powerful for mapping but makes it difficult to separate genuine neural relational
geometry from the assumptions and inductive biases of the encoding model itself (Popov et al.,
2018; Kriegeskorte & Douglas, 2019). Indeed, voxel-level measures cannot easily address
whether "relation selectivity" reflects true specialization versus mixed selectivity, because a
single 1–10 mm³ voxel aggregates activity from many neurons that may each be selective for
different relations.
Meanwhile, during inferential reasoning, single units across the hippocampus
simultaneously encode multiple variables in a factorized format, and that this geometry emerges
specifically after learning to perform inference (Courellis et al., 2024). Our results confirm these
important results, and extend them to first-time (zero-shot) representations, to the listening
context, and to brain regions beyond the hippocampus. Finally in a controlled reading paradigm,
pronouns can reactivate hippocampal representations of their antecedent concepts (Dijksterhuis
et al., 2024). Our findings extend this view by showing that pronouns occupy a structured feature
space in hippocampal population activity (Figure 4). Our results therefore extend these past
results by showing that pronoun feature geometry can constrain and delimit candidate
antecedents (e.g., by narrowing person/number/case-consistent referents), while hippocampal
concept representations provide the content that is reinstated once a referent is selected.
Our parallel results in three brain regions suggest a partial division of labor rather than a
uniform, cortex-wide "analogy code." In most analogy types, hippocampus matched or
outperformed ACC, it also outperformed OFC similarly, consistent with a large body of work
showing that hippocampal circuits support flexible relational codes that extend beyond physical
space to non-spatial task variables and abstract manifolds (Aronov et al., 2017; Knudsen &
Wallis, 2021; Nieh et al., 2021), including in humans (Courellis et al., 2024). The clearest
exception in our dataset was verb morphology: the *-ed*/*-ing* relation was markedly stronger in
ACC than in hippocampus. One parsimonious explanation is functional: dorsal ACC sits on the
medial wall within a network of cingulate motor areas that project to motor cortex (and, in
primates, have direct spinal projections), and ACC neurons are widely implicated in linking
actions to outcomes and maintaining control-relevant task states—computations naturally
engaged by verb/event representations and sequential structure (Picard & Strick, 1996; Hayden
et al., 2010; Heilbronner & Hayden, 2016). Conversely, OFC showed comparatively strong
structure for the protector relation after matching neuron counts (**Figure 5C**), plausibly reflecting
OFC's role in representing latent "task states" and incorporating social context into value-related
representations (e.g., who benefits, who is harmed, who is responsible), as well as its sensitivity

to socially defined signals/categories (Wilson et al., 2014; Azzi et al., 2012; Watson & Platt,
2012).
Surprisingly, we found some evidence for specialization, in that neurons that most
strongly participate in one analogy type are relatively less likely to participate in another.
Mechanistically, specialization can emerge when the task family itself decomposes into reusable
sub-computations that a network can allocate to partially separable internal machinery. In
multitask recurrent neural networks, training one network on many cognitive tasks yields
functional clusters of units that become specialized for different processes (Yang et al., 2019).
Driscoll et al. (2024) similarly found that multitask training can produce modular computational
strategies, described as reconfigurable dynamical motifs that mirror the subtask structure of the
training set. Given that language is inherently multi-constraint and compositional (with
systematic reuse of morpho-syntactic operations and relational templates), it is plausible that the
same pressures could bias learning—biological or artificial—toward forming specialized
subpopulations that are straightforward to recruit and recombine across related relational
demands (Behrens et al., 2018; Lake et al., 2017).
BERT possesses a much higher density of aligned units (**Figure 1F**) and substantially
larger overlaps between tuned sets across analogy types compared to the hippocampus (**Figure
6E**). This dense, distributed coding likely stems from the standard transformer architecture,
which relies on dense mixing across hidden dimensions and all-to-all token interactions during
self-attention (Devlin et al., 2019; Vaswani et al., 2017). Strikingly, BERT embeddings exhibit
the same functional specialization that the brain does (**Figure 6F**). This is consistent with a large
literature showing that linguistic information is staged across layers (surface/syntax earlier;
higher-level semantics and discourse later, Jawahar et al., 2019; Tenney et al., 2019; Rogers et
al., 2020), and that only a subset of attention heads carry stable, linguistically interpretable roles
(e.g., dependency relations and coreference; Clark et al., 2019; Voita et al., 2019). In further
support of this view, our layer-wise scans of both BERT and GPT-2 (Radford et al., 2019;
Supplementary Figure 2) show that the fraction of embedding dimensions meeting our
analogy-tuning criterion generally decreases with layer depth, suggesting progressive
compression into fewer, more selectively engaged features.
Importantly, explicit specialization in LLM is *instrumentally useful* for scaling and
capability for LLM. Shazeer et al. (2017) and Fedus et al. (2022) showed that a mixture-of-
experts architecture can achieve >1000× increases in model capacity with only minor losses in
computational efficiency, this is because routing each input word through only a *small subset* of
specialist subnetworks allows the overall system to accumulate diverse functions without forcing
every parameter to participate in every computation. They reported that different experts become
highly specialized in ways that track syntax and semantics. In that light, our specialist analogy-
aligned subpopulations could be interpreted as "expert-like" neural resources: a way to store and
access many relational skills efficiently, potentially favored in brains because it increases
representational capacity and behavioral flexibility under tight metabolic and continual-learning

constraints. In other words, the LLM results provide a normative explanation for why the brain
would show aligned and factorized representations.

REFERENCES

Andreas, J. (2019). Measuring compositionality in representation learning. *International Conference on Learning Representations (ICLR)*

Allen, C., & Hospedales, T. (2019). Analogies explained: Towards understanding word embeddings. In K. Chaudhuri & R. Salakhutdinov (Eds.), Proceedings of the 36th International Conference on Machine Learning (ICML 2019) (Proceedings of Machine Learning Research, Vol. 97, pp. 223–231). PMLR

Aronov, D., Nevers, R., & Tank, D. W. (2017). Mapping of a non-spatial dimension by the hippocampal–entorhinal circuit. Nature, 543(7647), 719–722.

Ashby, F. G., & Townsend, J. T. (1986). Varieties of perceptual independence. Psychological review, 93(2), 154.

Azzi, J. C. B., Sirigu, A., & Duhamel, J.-R. (2012). Modulation of value representation by social context in the primate orbitofrontal cortex. Proceedings of the National Academy of Sciences of the United States of America, 109(6), 2126–2131.

Baroni, M. (2020). Linguistic generalization and compositionality in modern artificial neural networks. Philosophical Transactions of the Royal Society B: Biological Sciences, 375(1791).

Behrens, T. E. J., Muller, T. H., Whittington, J. C. R., Mark, S., Baram, A. B., Stachenfeld, K. L., & Kurth-Nelson, Z. (2018). What is a cognitive map? Organizing knowledge for flexible behavior. Neuron, 100(2), 490–509. doi:10.1016/j.neuron.2018.10.002

Benjamini, Y., & Hochberg, Y. (1995). Controlling the false discovery rate: A practical and powerful approach to multiple testing. *Journal of the Royal Statistical Society: Series B (Methodological), 57*(1), 289–300.

Berko, J. (1958). The child's learning of English morphology. Word, 14(2–3), 150–177.

Bernardi, S., Benna, M. K., Rigotti, M., Munuera, J., Fusi, S., & Salzman, C. D. (2020). The geometry of abstraction in the hippocampus and prefrontal cortex. Cell, 183(4), 954–967.e21. doi:10.1016/j.cell.2020.09.031

Binder, J. R., Desai, R. H., Graves, W. W., & Conant, L. L. (2009). Where is the semantic system? A critical review and meta-analysis of 120 functional neuroimaging studies. Cerebral Cortex, 19(12), 2767–2796.

Blank, I. A., Duff, M. C., Brown-Schmidt, S., & Fedorenko, E. (2016). Expanding the language
network: Domain-specific hippocampal recruitment during high-level linguistic processing.
bioRxiv. doi:10.1101/091900

Blei, D. M., Ng, A. Y., & Jordan, M. I. (2001). Latent Dirichlet allocation. In Advances in
Neural Information Processing Systems (Vol. 14).

Carroll, J. D., & Arabie, P. (1980). Multidimensional scaling. Annual Review of Psychology, 31,
607–649

Caucheteux, C., & King, J.-R. (2022). Brains and algorithms partially converge in natural
language processing. Communications Biology, 5(1), 134. doi:10.1038/s42003-022-03036-1

Chaure, F. J., Rey, H. G., & Quian Quiroga, R. (2018). A novel and fully automatic spike-sorting
implementation with variable number of features. Journal of Neurophysiology, 120(4), 1859–
1871. https://doi.org/10.1152/jn.00339.2018

Chavez, A. G., Franch, M., Mickiewicz, E. A., Baltazar, W., Belanger, J. L., Devara, D., ... &
Hayden, B. Y. (2025). Mirror manifolds: partially overlapping neural subspaces for speaking and
listening. bioRxiv, 2025-09.

Clark, H. H., & Chase, W. G. (1972). On the process of comparing sentences against pictures.
Cognitive Psychology, 3(3), 472–517.

Clark, K., Khandelwal, U., Levy, O., & Manning, C. D. (2019). What does BERT look at? An
analysis of BERT's attention. In Proceedings of the BlackboxNLP Workshop (EMNLP).

Constantinescu, A. O., O'Reilly, J. X., & Behrens, T. E. J. (2016). Organizing conceptual
knowledge in humans with a gridlike code. Science, 352(6292), 1464–1468.

Courellis, H. S., Minxha, J., Daigle, T. L., Zeng, H., Fusi, S., & Rutishauser, U. (2024). Abstract
representations emerge in human hippocampal neurons during inference. Nature, 632(8026),
841–849.

Dale, A. M., Fischl, B., & Sereno, M. I. (1999). Cortical surface-based analysis: I. Segmentation
and surface reconstruction. NeuroImage, 9(2), 179–194. https://doi.org/10.1006/nimg.1998.0395

Davachi, L. (2006). Item, context and relational episodic encoding in humans. Current Opinion
in Neurobiology, 16(6), 693–700. doi:10.1016/j.conb.2006.10.012

Devlin, J., Chang, M.-W., Lee, K., & Toutanova, K. (2019). BERT: Pre-training of deep
bidirectional transformers for language understanding. In Proceedings of the 2019 Conference of
the North American Chapter of the Association for Computational Linguistics: Human Language
Technologies, Volume 1 (Long and Short Papers) (pp. 4171–4186). Association for
Computational Linguistics.
990

991 Dijksterhuis, D. E., Self, M. W., Possel, J. K., Peters, J. C., van Straaten, E. C. W., Idema, S., …
992 Roelfsema, P. R. (2024). Pronouns reactivate conceptual representations in human hippocampal
993 neurons. Science, 385(6716), 1478–1484. doi:10.1126/science.adr2813
994

995 Driscoll, L. N., Shenoy, K., & Sussillo, D. (2024). Flexible multitask computation in recurrent
996 networks utilizes shared dynamical motifs. Nature Neuroscience, 27, 1349–1363.
997

998 Ebitz, R. B., Sleezer, B. J., Jedema, H. P., Bradberry, C. W., & Hayden, B. Y. (2019). Tonic
999 exploration governs both flexibility and lapses. PLoS computational biology, 15(11), e1007475.
1000

1001 Eisenreich, B. R., Hayden, B. Y., & Zimmermann, J. (2019). Macaques are risk-averse in a
1002 freely moving foraging task. Scientific reports, 9(1), 15091.
1003

1004 Elman, J. L. (1990). Finding structure in time. Cognitive Science, 14(2), 179–211.
1005

1006 Fedus, W., Zoph, B., & Shazeer, N. (2022). Switch transformers: Scaling to trillion parameter
1007 models with simple and efficient sparsity. Journal of Machine Learning Research, 23(120), 1–39.
1008

1009 Flesch, T., Saxe, A., & Summerfield, C. (2023). Continual task learning in natural and artificial
1010 agents. Trends in neurosciences, 46(3), 199-210.
1011

1012 Flesch, T., Juechems, K., Dumbalska, T., Saxe, A., & Summerfield, C. (2022). Orthogonal
1013 representations for robust context-dependent task performance in brains and neural networks.
1014 Neuron, 110(7), 1258-1270.
1015

1016 Franch, M., Mickiewicz, E. A., Belanger, J. L., Chericoni, A., Chavez, A. G., Katlowitz, K.
1017 A., … Hayden, B. Y. (2025). A vectorial code for semantics in human hippocampus. bioRxiv.
1018 doi:10.1101/2025.02.21.639601
1019

1020 Fusi, S., Miller, E. K., & Rigotti, M. (2016). Why neurons mix: High dimensionality for higher
1021 cognition. *Current Opinion in Neurobiology, 37*, 66–74.
1022

1023 Garvert, M. M., Dolan, R. J., & Behrens, T. E. (2017). A map of abstract relational knowledge in
1024 the human hippocampal–entorhinal cortex. elife, 6, e17086.
1025
1026 Gärdenfors, P. (2000). Conceptual spaces: The geometry of thought. MIT Press.
1027
1028 Gärdenfors, P. (2014). The geometry of meaning: Semantics based on conceptual spaces. MIT
1029 Press.
1030
1031 Gentner, D. (1983). Structure-mapping: A theoretical framework for analogy. Cognitive Science,
1032 7(2), 155–170.
1033
1034 Gentner, D. (2010). Bootstrapping the mind: Analogical processes and symbol systems.
1035 Cognitive Science, 34(5), 752–775.
1036
1037 Gentner, D., & Markman, A. B. (1997). Structure mapping in analogy and similarity. American
1038 Psychologist, 52(1), 45–56.
1039
1040 Goldstein, A., Zada, Z., Buchnik, E., Schain, M., Price, A., Aubrey, B., ... & Hasson, U. (2022).
1041 Shared computational principles for language processing in humans and deep language models.
1042 Nature neuroscience, 25(3), 369-380.
1043
1044 Groppe, D. M., Bickel, S., Dykstra, A. R., Wang, X., Mégevand, P., Mercier, M. R., Lado, F. A.,
1045 Mehta, A. D., & Honey, C. J. (2017). iELVis: An open source MATLAB toolbox for localizing
1046 and visualizing human intracranial electrode data. Journal of Neuroscience Methods, 281, 40–48.
1047 https://doi.org/10.1016/j.jneumeth.2017.01.022
1048
1049 Hayden, B. Y., Pearson, J. M., & Platt, M. L. (2010). Neurons in anterior cingulate cortex
1050 multiplex information about reward and action. Journal of Neuroscience, 30(9), 3339–3346.
1051
1052 Hayden, B. Y. (2019). Why has evolution not selected for perfect self-control?. Philosophical
1053 Transactions of the Royal Society B: Biological Sciences, 374(1766).
1054
1055 Hayden, B. Y., Heilbronner, S. R., & Yoo, S. B. M. (2025). Rethinking the centrality of brain
1056 areas in understanding functional organization. Nature Neuroscience, 1-12.
1057
1058 Heilbron, M., Armeni, K., Schoffelen, J. M., Hagoort, P., & De Lange, F. P. (2022). A hierarchy
1059 of linguistic predictions during natural language comprehension. Proceedings of the National
1060 Academy of Sciences, 119(32), e2201968119.
1061

Heilbronner, S. R., & Hayden, B. Y. (2016). Dorsal anterior cingulate cortex: A bottom-up view. Annual Review of Neuroscience, 39, 149–170.

Higgins, I., Amos, D., Pfau, D., Racaniere, S., Matthey, L., Rezende, D., & Lerchner, A. (2018). Towards a definition of disentangled representations. arXiv. arXiv:1812.02230

Higgins, I., Racanière, S., & Rezende, D. (2022). Symmetry-based representations for artificial and biological general intelligence. Frontiers in Computational Neuroscience, 16, 836498.

Hofstadter, D. R. (2001). Analogy as the core of cognition. In D. Gentner, K. J. Holyoak, & B. N. Kokinov (Eds.), The analogical mind: Perspectives from cognitive science (pp. 499–538). MIT Press.

Hofstadter, D. R. (1995). Fluid concepts and creative analogies: Computer models of the fundamental mechanisms of thought. Basic books.

Holyoak, K. J., Gentner, D., & Kokinov, B. N. (2001). Introduction: The place of analogy in cognition. In D. Gentner, K. J. Holyoak, & B. N. Kokinov (Eds.), The analogical mind: Perspectives from cognitive science (pp. 1–19). MIT Press.

Holyoak, K. J., & Thagard, P. (1996). Mental leaps: Analogy in creative thought. MIT press.

Huth, A. G., De Heer, W. A., Griffiths, T. L., Theunissen, F. E., & Gallant, J. L. (2016). Natural speech reveals the semantic maps that tile human cerebral cortex. Nature, 532(7600), 453-458.

Jain, S., & Huth, A. (2018). Incorporating context into language encoding models for fMRI. Advances in neural information processing systems, 31.

Jaccard, P. (1912). The distribution of the flora in the alpine zone. 1. New Phytologist, 11(2), 37–50.

Jawahar, G., Sagot, B., & Seddah, D. (2019). What does BERT learn about the structure of language? In Proceedings of the 57th Annual Meeting of the Association for Computational Linguistics.

Jenkinson, M., & Smith, S. (2001). A global optimisation method for robust affine registration of brain images. Medical Image Analysis, 5(2), 143–156. https://doi.org/10.1016/S1361-8415(01)00036-6

Jenkinson, M., Bannister, P., Brady, M., & Smith, S. (2002). Improved optimization for the robust and accurate linear registration and motion correction of brain images. NeuroImage, 17(2), 825–841. https://doi.org/10.1006/nimg.2002.1132

Johnston, W. J., Fine, J. M., Yoo, S. B. M., Ebitz, R. B., & Hayden, B. Y. (2024). Semi-orthogonal subspaces for value mediate a binding and generalization trade-off. Nature Neuroscience, 27(11), 2218-2230.

Joshi, A., Scheinost, D., Okuda, H., Belhachemi, D., Murphy, I., Staib, L. H., & Papademetris, X. (2011). Unified framework for development, deployment and robust testing of neuroimaging algorithms. Neuroinformatics, 9(1), 69–84. https://doi.org/10.1007/s12021-010-9092-8

Kafkas, A., Mayes, A. R., & Montaldi, D. (2024). The hippocampus supports the representation of abstract concepts: Implications for the study of recognition memory. Neuropsychologia, 199, 108899. doi:10.1016/j.neuropsychologia.2024.108899

Katlowitz, K. A., Belanger, J. L., Ismail, T., Chavez, A. G., Chericoni, A., Franch, M., … Hayden, B. Y. (2025). Attention is all you need (in the brain): Semantic contextualization in human hippocampus. bioRxiv. doi:10.1101/2025.06.23.661103

Katlowitz, K. A., Shah, S., Franch, M. C., Adkinson, J., Belanger, J. L., Mathura, R. K., ... & Sheth, S. A. (2025). Learning and language in the unconscious human hippocampus. bioRxiv, 2025-04.

Kemp, C., & Tenenbaum, J. B. (2008). The discovery of structural form. Proceedings of the National Academy of Sciences, 105(31), 10687-10692.

Kennedy, C. (2007). Vagueness and grammar: The semantics of relative and absolute gradable adjectives. Linguistics and Philosophy, 30(1), 1–45.

Knudsen, E. B., & Wallis, J. D. (2021). Hippocampal neurons construct a map of an abstract value space. Cell, 184(18), 4640–4650.

Kobak, D., Brendel, W., Constantinidis, C., Feierstein, C. E., Kepecs, A., Mainen, Z. F., … Machens, C. K. (2016). Demixed principal component analysis of neural population data. eLife, 5, e10989.

Kriegeskorte, N., & Douglas, P. K. (2019). Interpreting encoding and decoding models. Current opinion in neurobiology, 55, 167-179.

Kumar, S., Sumers, T. R., Yamakoshi, T., Goldstein, A., Hasson, U., Norman, K. A., ... &
Nastase, S. A. (2024). Shared functional specialization in transformer-based language models
and the human brain. Nature communications, 15(1), 5523.

Lake, B. M., Ullman, T. D., Tenenbaum, J. B., & Gershman, S. J. (2017). Building machines that
learn and think like people. Behavioral and Brain Sciences, 40, e253.

Landauer, T. K., & Dumais, S. T. (1997). A solution to Plato's problem: The latent semantic
analysis theory of acquisition, induction, and representation of knowledge. Psychological
Review, 104(2), 211–240.

Levy, O., & Goldberg, Y. (2014). Linguistic regularities in sparse and explicit word
representations. In Proceedings of the Eighteenth Conference on Computational Natural
Language Learning (pp. 171–180).

Li, X., Morgan, P. S., Ashburner, J., Smith, J., & Rorden, C. (2016). The first step for
neuroimaging data analysis: DICOM to NIfTI conversion. Journal of Neuroscience Methods,
264, 47–56. https://doi.org/10.1016/j.jneumeth.2016.03.001

Locatello, F., Bauer, S., Lucic, M., Rätsch, G., Gelly, S., Schölkopf, B., & Bachem, O. (2020). A
sober look at the unsupervised learning of disentangled representations and their evaluation.
Journal of Machine Learning Research, 21(209), 1-62.

Mack, M. L., Love, B. C., & Preston, A. R. (2018). Building concepts one episode at a time: The
hippocampus and concept formation. Neuroscience Letters, 680, 31–38.
doi:10.1016/j.neulet.2017.07.061

Magnotti, J. F., Wang, Z., & Beauchamp, M. S. (2020). RAVE: Comprehensive open-source
software for reproducible analysis and visualization of intracranial EEG data. NeuroImage, 223,
117341. https://doi.org/10.1016/j.neuroimage.2020.117341

Maisson, D. J. N., Cash-Padgett, T. V., Wang, M. Z., Hayden, B. Y., Heilbronner, S. R., &
Zimmermann, J. (2021). Choice-relevant information transformation along a ventrodorsal axis in
the medial prefrontal cortex. Nature communications, 12(1), 4830.
Mikolov, T., Chen, K., Corrado, G., & Dean, J. (2013). Efficient estimation of word
representations in vector space. arXiv. arXiv:1301.3781

Mickiewicz, E. A., Franch, M., Katlowitz, K. A., Chavez, A. G., Zhu, H., Chericoni, A., ... &
Hayden, B. Y. (2025). A semantotopic map in human hippocampus. bioRxiv, 2025-10.
1180

Mikolov, T., Sutskever, I., Chen, K., Corrado, G., & Dean, J. (2013). Distributed representations of words and phrases and their compositionality. In Advances in Neural Information Processing Systems (pp. 3111–3119).

Mitchell, J., & Lapata, M. (2008). Vector-based models of semantic composition. In Proceedings of ACL-08: HLT (pp. 236–244).

Mitchell, J., & Lapata, M. (2010). Composition in distributional models of semantics. Cognitive Science, 34(8), 1388–1429.

Mitchell, T. M., Shinkareva, S. V., Carlson, A., Chang, K.-M., Malave, V. L., Mason, R. A., & Just, M. A. (2008). Predicting human brain activity associated with the meanings of nouns. Science, 320(5880), 1191–1195.

Mohammad, S. M. (2025). *NRC VAD Lexicon v2: Norms for valence, arousal, and dominance for over 55k English terms*. arXiv. https://doi.org/10.48550/arXiv.2503.23547

Montague, R., & Thomason, R. H. (1978). Formal philosophy: selected papers of Richard Montague.

Nieh, E. H., Schottdorf, M., Freeman, N. W., Low, R. J., Lewallen, S., Koay, S. A., Pinto, L., Gauthier, J. L., Brody, C. D., & Tank, D. W. (2021). Geometry of abstract learned knowledge in the hippocampus. Nature, 595(7865), 80–84.

Nosofsky, R. M. (1986). Attention, similarity, and the identification–categorization relationship. Journal of Experimental Psychology: General, 115(1), 39–57.

Olman, C. A., Davachi, L., & Inati, S. (2009). Distortion and signal loss in medial temporal lobe. PLOS ONE, 4(12), e8160.

Ostrow M, Fiete I. How the human brain creates cognitive maps of related concepts. Nature. 2024 Aug;632(8026):744-745. doi: 10.1038/d41586-024-02433-2.

Patterson, K., Nestor, P. J., & Rogers, T. T. (2007). Where do you know what you know? The representation of semantic knowledge in the human brain. Nature Reviews Neuroscience, 8(12), 976–987. doi:10.1038/nrn2277

Paszke, A., Gross, S., Massa, F., Lerer, A., Bradbury, J., Chanan, G., Killeen, T., Lin, Z., Gimelshein, N., Antiga, L., Desmaison, A., Kopf, A., Yang, E., DeVito, Z., Raison, M., Tejani, A., Chilamkurthy, S., Steiner, B., Fang, L., ... Chintala, S. (2019). PyTorch: An imperative style,

high-performance deep learning library (arXiv:1912.01703). arXiv. https://arxiv.org/abs/1912.01703

Pennington, J., Socher, R., & Manning, C. D. (2014). GloVe: Global vectors for word representation. In Proceedings of the 2014 Conference on Empirical Methods in Natural Language Processing (pp. 1532–1543).

Pearson, J. M., Hayden, B. Y., & Platt, M. L. (2010). Explicit information reduces discounting behavior in monkeys. Frontiers in psychology, 1, 237.

Peterson, J. C., Chen, D., & Griffiths, T. L. (2020). Parallelograms revisited: Exploring the limitations of vector space models for simple analogies. *Cognition, 205*, 104440.

Phillips, S. (2022). What is category theory to cognitive science? Compositional representation and comparison. Frontiers in Psychology, 13, 1048975.

Piantadosi, S. T., Muller, D. C., Rule, J. S., Kaushik, K., Gorenstein, M., Leib, E. R., & Sanford, E. (2024). Why concepts are (probably) vectors. Trends in Cognitive Sciences, 28(9), 844–856.

Picard, N., & Strick, P. L. (1996). Motor areas of the medial wall: A review of their location and functional activation. Cerebral Cortex, 6(3), 342–353.

Pooresmaeili, A., Poort, J., Thiele, A., & Roelfsema, P. R. (2010). Separable codes for attention and luminance contrast in the primary visual cortex. Journal of Neuroscience, 30(38), 12701–12711.

Popov, V., Ostarek, M., & Tenison, C. (2018). Practices and pitfalls in inferring neural representations. NeuroImage, 174, 340-351.

Provenza, N. R., Reddy, S., Allam, A. K., Rajesh, S. V., Diab, N., Reyes, G., ... & Sheth, S. A. (2024). Disruption of neural periodicity predicts clinical response after deep brain stimulation for obsessive-compulsive disorder. Nature Medicine, 30(10), 3004-3014.

Quessard, R., Barrett, T., & Clements, W. (2020). Learning disentangled representations and group structure of dynamical environments. Advances in Neural Information Processing Systems, 33, 19727-19737.

Quiroga, R. Q. (2012). Concept cells: the building blocks of declarative memory functions. Nature Reviews Neuroscience, 13(8), 587-597.

Quiroga, R. Q. (2020). No pattern separation in the human hippocampus. Trends in Cognitive Sciences, 24(12), 994-1007.

Quiroga, R. Q., Reddy, L., Kreiman, G., Koch, C., & Fried, I. (2005). Invariant visual representation by single neurons in the human brain. Nature, 435(7045), 1102–1107.

Quine, W. V. O. (1960). *Word and object*. MIT Press

Radford, A., Wu, J., Child, R., Luan, D., Amodei, D., & Sutskever, I. (2019). Language models are unsupervised multitask learners (OpenAI technical report). OpenAI. https://cdn.openai.com/better-language-models/language_models_are_unsupervised_multitask_learners.pdf

Rigotti, M., Barak, O., Warden, M. R., Wang, X.-J., Daw, N. D., Miller, E. K., & Fusi, S. (2013). The importance of mixed selectivity in complex cognitive tasks. *Nature, 497*(7451), 585–590.

Rogers, A., Kovaleva, O., & Rumshisky, A. (2020). A primer in BERTology: What we know about how BERT works. Transactions of the Association for Computational Linguistics, 8, 842–866.

Rumelhart, D. E., & Abrahamson, A. A. (1973). A model for analogical reasoning. *Cognitive Psychology, 5*(1), 1–28.

Sassenhagen, J., & Fiebach, C. J. (2020). Traces of meaning itself: Encoding distributional word vectors in brain activity. Neurobiology of Language, 1(1), 54–76. doi:10.1162/nol_a_00003

Schrimpf, M., Blank, I. A., Tuckute, G., Kauf, C., Hosseini, E. A., Kanwisher, N., … Fedorenko, E. (2021). The neural architecture of language: Integrative modeling converges on predictive processing. Proceedings of the National Academy of Sciences of the United States of America, 118(45), e2105646118.

Shazeer, N., Mirhoseini, A., Maziarz, K., Davis, A., Le, Q., Hinton, G., & Dean, J. (2017). Outrageously large neural networks: The sparsely-gated mixture-of-experts layer. In Proceedings of the International Conference on Learning Representations.

Smolensky, P. (1988). On the proper treatment of connectionism. Behavioral and Brain Sciences, 11(1), 1–23.

Soto, F. A., Vucovich, L. E., & Ashby, F. G. (2018). Linking signal detection theory and encoding models to reveal independent neural representations from neuroimaging data. PLOS

Computational Biology, 14(10), e1006470.

Tang, J., LeBel, A., Jain, S., & Huth, A. G. (2023). Semantic reconstruction of continuous language from non-invasive brain recordings. Nature Neuroscience, 26(5), 858-866.

Tang, W., Shin, J. D., & Jadhav, S. P. (2023). Geometric transformation of cognitive maps for generalization across hippocampal-prefrontal circuits. *Cell Reports, 42*(3), 112246.

Tavares, R. M., Mendelsohn, A., Grossman, Y., Williams, C. H., Shapiro, M., Trope, Y., & Schiller, D. (2015). A map for social navigation in the human brain. Neuron, 87(1), 231–243. doi:10.1016/j.neuron.2015.06.011

Tenney, I., Das, D., & Pavlick, E. (2019). BERT rediscovers the classical NLP pipeline. In Proceedings of the 57th Annual Meeting of the Association for Computational Linguistics.

Theves, S., Fernandez, G., & Doeller, C. F. (2020). The hippocampus maps concept space, not feature space. Journal of Neuroscience, 40, 7318–7325.

Touvron, H., Lavril, T., Izacard, G., Martinet, X., Lachaux, M.-A., Rozière, B., … Lample, G. (2023). LLaMA: Open and efficient foundation language models. arXiv. arXiv:2302.13971

Touvron, H., Martin, L., Stone, K., Albert, P., Almahairi, A., Babaei, Y., … Scialom, T. (2023). Llama 2: Open foundation and fine-tuned chat models. arXiv. arXiv:2307.09288

Trager, M., Achille, A., Perera, P., Zancato, L., & Soatto, S. (2024). Compositional Structures in Neural Embedding and Interaction Decompositions. arXiv preprint arXiv:2407.08934.

Turney, P. D., & Pantel, P. (2010). From frequency to meaning: Vector space models of semantics. Journal of Artificial Intelligence Research, 37, 141–188.

Vaswani, A., Shazeer, N., Parmar, N., Uszkoreit, J., Jones, L., Gomez, A. N., Kaiser, Ł., & Polosukhin, I. (2017). Attention is all you need. In Advances in Neural Information Processing Systems (pp. 5998–6008).

Viganò, S., & Piazza, M. (2020). Distance and direction codes underlie navigation of a novel semantic space in the human brain. Journal of Neuroscience, 40(13), 2727-2736.

Voita, E., Talbot, D., Moiseev, F., Sennrich, R., & Titov, I. (2019). Analyzing multi-head self-attention: Specialized heads do the heavy lifting, the rest can be pruned. In Proceedings of the 57th Annual Meeting of the Association for Computational Linguistics.

Wang, M. Z., & Hayden, B. Y. (2021). Latent learning, cognitive maps, and curiosity. Current Opinion in Behavioral Sciences, 38, 1-7.

Ward, T. B., Smith, S. M., & Finke, R. A. (1999). Creative cognition. Handbook of creativity, 189, 212.

Watson, K. K., & Platt, M. L. (2012). Social signals in primate orbitofrontal cortex. Current Biology, 22(23), 2268–2273.

Whittington, J. C., Muller, T. H., Mark, S., Chen, G., Barry, C., Burgess, N., & Behrens, T. E. (2020). The Tolman-Eichenbaum machine: unifying space and relational memory through generalization in the hippocampal formation. Cell, 183(5), 1249-1263.

Wilson, R. C., Takahashi, Y. K., Schoenbaum, G., & Niv, Y. (2014). Orbitofrontal cortex as a cognitive map of task space. Neuron, 81(2), 267–279.

Wischnewski, M., & Peelen, M. V. (2021). Causal evidence for a double dissociation between object-and scene-selective regions of visual cortex: a preregistered TMS replication study. Journal of Neuroscience, 41(4), 751-756.

Wolna, A., Wright, A., & Fedorenko, E. (2025). The extended language network: Language-responsive brain areas whose contributions to language remain to be discovered. bioRxiv. doi:10.1101/2025.04.02.646835

Wolf, T., Debut, L., Sanh, V., Chaumond, J., Delangue, C., Moi, A., Cistac, P., Rault, T., Louf, R., Funtowicz, M., Davison, J., Shleifer, S., von Platen, P., Ma, C., Jernite, Y., Plu, J., Xu, C., Le Scao, T., Gugger, S., ... Rush, A. M. (2020). Transformers: State-of-the-art natural language processing. In Proceedings of the 2020 Conference on Empirical Methods in Natural Language Processing: System Demonstrations (pp. 38–45). Association for Computational Linguistics. https://doi.org/10.18653/v1/2020.emnlp-demos.6

Wu, M.-H., Anderson, A. J., Jacobs, R. A., & Raizada, R. D. S. (2022). Analogy-related information can be accessed by simple addition and subtraction of fMRI activation patterns, without participants performing any analogy task. Neurobiology of Language, 3(1), 1–17. doi:10.1162/nol_a_00045

Xiao, J., Adkinson, J. A., Myers, J., Allawala, A. B., Mathura, R. K., Pirtle, V., Najera, R., Provenza, N. R., Bartoli, E., Watrous, A. J., Oswalt, D., Gadot, R., Anand, A., Shofty, B., Mathew, S. J., Goodman, W. K., Pouratian, N., Pitkow, X., Bijanki, K. R., ... Sheth, S. A.

(2024a). Beta activity in human anterior cingulate cortex mediates reward biases. Nature Communications, 15(1), 5528. https://doi.org/10.1038/s41467-024-49600-7

Yacoub, E., Grier, M. D., Auerbach, E. J., Lagore, R. L., Harel, N., Adriany, G., ... & Zimmermann, J. (2020). Ultra-high field (10.5 T) resting state fMRI in the macaque. Neuroimage, 223, 117349.

Yang, A. I., Wang, X., Doyle, W. K., Halgren, E., Carlson, C., Belcher, T. L., Cash, S. S., Devinsky, O., & Thesen, T. (2012). Localization of dense intracranial electrode arrays using magnetic resonance imaging. NeuroImage, 63(1), 157–165. https://doi.org/10.1016/j.neuroimage.2012.06.039

Yan, X., Krishna, A., Arsdel, K. V., Gautam, I., Kim, B., Shrivastava, A., ... & Sheth, S. A. (2025). Shared neural geometries for bilingual semantic representations. bioRxiv, 2025-11.

Yang, G. R., Joglekar, M. R., Song, H. F., Newsome, W. T., & Wang, X.-J. (2019). Task representations in neural networks trained to perform many cognitive tasks. Nature Neuroscience, 22(2), 297–306.

Zhang, Y., Han, K., Worth, R., & Liu, Z. (2020). Connecting concepts in the brain by mapping cortical representations of semantic relations. Nature Communications, 11(1), 1877. doi:10.1038/s41467-020-15804-w

Zhu, X., Xu, C., & Tao, D. (2021). Commutative Lie group VAE for disentanglement learning. In Proceedings of the 38th International Conference on Machine Learning (pp. 12924–12934). PMLR.

Zuanazzi, A., Ripollés, P., Lin, W. M., Gwilliams, L., King, J. R., & Poeppel, D. (2024). Negation mitigates rather than inverts the neural representations of adjectives. PLoS biology, 22(5), e3002622.

METHODS

Human intracranial neurophysiology

Recordings of 11 adult patients (6 males, 5 females) were collected in the Epilepsy Monitoring Unit (EMU) at Baylor St. Luke's Hospital, following established intracranial recording procedures during epilepsy monitoring (see also Xiao et al., 2024; Franch et al., 2025). Recordings of 3 patients were collected in the University of Utah Hospital (3 females).

Single-neuron activity was obtained using stereotactic depth electrodes (sEEG), specifically AdTech Medical Behnke–Fried–style probes. On average, each participant had approximately three probes ending in the bilateral hippocampi. Twelve patients had approximately two probes in the bilateral ACC. Five patients had approximately one probe in the OFC. Electrode placement was confirmed by coregistering pre-operative MRI with post-operative CT.

Each depth probe carried eight microwires, and each microwire contained eight recording contacts optimized for unit activity. Signals were acquired with a 512-channel Blackrock Microsystems Neuroport system at 30 kHz. Spike detection and sorting were performed using Wave_clus (Chaure et al., 2018), followed by manual curation. Units (single- or multi-unit) were retained based on waveform stability and morphology (e.g., slope, amplitude, trough-to-peak features) and inter-spike-interval distributions consistent with a refractory period (no ISIs shorter than 1 ms). Unless otherwise noted, analyses included both single- and multi-unit activity (Franch et al., 2025).

Electrode visualization

Electrode localization followed a standardized imaging workflow (Franch et al., 2025). Briefly, contacts were reconstructed and visualized using iELVis (Groppe et al., 2017), with group-level plotting performed via RAVE (Magnotti et al., 2020). For each participant, pre-operative T1-weighted anatomical MRI and post-operative Stealth CT DICOM images were collected and converted to NIfTI format (Li et al., 2016). The post-operative CT was then aligned to the MRI coordinate space using FSL (Jenkinson & Smith, 2001; Jenkinson et al., 2002).

The aligned CT was imported into BioImage Suite (v3.5β1; Joshi et al., 2011), where electrode contacts were manually identified. Contact coordinates were then transformed into each participant's native space using iELVis MATLAB utilities (Yang et al., 2012) and displayed on cortical surfaces reconstructed with FreeSurfer (v7.4.1;

Dale et al., 1999). Microelectrode locations were defined relative to the first (deepest)
macro-contact of the Behnke–Fried depth electrode assembly. Finally, RAVE was used
to warp participant anatomy and electrode coordinates into MNI152 space to enable
across-subject visualization; pooled coordinates were rendered on an average (glass)
brain together with hippocampal segmentation, with points color-coded by participant
(Franch et al., 2025).
1457
1458 **Natural language stimuli**
1459
Participants listened to a set of naturalistic spoken narratives selected to be
engaging and linguistically diverse (Franch et al., 2025). Specifically, the stimulus set
comprised six episodes from The Moth Radio Hour (each approximately 5–13 minutes
long), totaling 47 minutes and 25 seconds of audio (7,346 words). In HPC and ACC
analysis, 34 words not heard by all patients with recordings in those two areas were
removed. The stories were: "Life Flight," "The One Club," "The Tiniest Bouquet," "My
Father's Hands," "Wild Women and Dancing Queens," and "Juggling and Jesus." Each
excerpt featured a single speaker delivering an autobiographical story to a live audience.
Audio was presented continuously through the built-in speakers of the participant's
hospital television. To synchronize stimulus timing with neural recordings, the audio
output from the playback computer was routed as an analog input directly into the Neural
Signal Processor (sampled at 30 kHz), ensuring precise temporal alignment between the
stimulus waveform and recorded neural activity.
1473
1474 **Audio transcription**
1475
After data collection, the stimulus .wav audio file was transcribed automatically
using a Python pipeline with AssemblyAI (Franch et al., 2025). The resulting word-level
transcript and timestamps were converted into a Praat-compatible TextGrid, which was
then loaded into Praat for manual review. The original .wav file was also imported into
Praat so that spectrograms and timing boundaries could be inspected directly. Word onset
and offset times were manually corrected to ensure accurate temporal alignment.
1482
1483 **Semantic embedding extraction from language models**
1484
1485 **BERT**
1486
1487   Extraction of BERT embeddings was implemented using "bert-base-cased"
1488 (Devlin et al., 2018) via Hugging Face Transformers (Wolf et al., 2020), following the
1489 approach in Katlowitz et al. (2025). Because BERT is an encoder-only, masked-language

1490 model that natively incorporates bidirectional context, embeddings were generated with
1491 an expanding-context method intended to approximate left-to-right (causal) processing.
1492
Specifically, the running text began as an empty string, and one new word was
appended at a time (retaining punctuation for context). After each addition, the sequence
was re-tokenized with BERT's tokenizer and passed through the model. A running
context of maximum size of 512 tokens (current word and past words) were kept.
Although BERT encodes both left and right context in principle, only the hidden states
associated with the newly appended word were extracted on each step, and subword-
piece vectors were averaged to yield a word-level embedding.
1500
1501   Hidden states from all 13 layers (embedding layer plus 12 transformer layers; 768
1502 dimensions per layer) were saved, with analyses focusing on the final layer (layer 12).
1503 The implementation used Python with PyTorch (Paszke et al., 2019).
1504
GPT-2
A parallel embedding pipeline was derived from the transcript using the GPT-2
"gpt2-large" model (Radford et al., 2019) accessed through Hugging Face Transformers
(Wolf et al., 2020), following the procedure described in Katlowitz et al. (2025). The
transcript spreadsheet was organized so that each row represented a single token,
including punctuation and end-of-sentence markers (e.g., ".", "?", "!"). Punctuation was
kept in the running text to preserve context, while being tracked to prevent token–word
alignment issues during later tokenization. The GPT-2 Large architecture contains 37
total layers (an embedding layer plus 36 transformer blocks), producing 1280-
dimensional hidden states, and supported contexts up to 1024 tokens.
1515
To respect GPT-2's autoregressive structure, embeddings were computed
incrementally. The input context started empty and then grew one word at a time to the
maximum of 1024 tokens. After each word was appended, the current string was
tokenized using GPT-2's byte-pair encoding tokenizer and passed through the model in
inference mode (no gradient computation). Hidden states were extracted from all layers;
to produce a single vector per transcript word, the vectors corresponding to that word's
subword pieces were averaged.
1523
AUC

We screened neurons for "analogy separability" using only trial-level firing rates and two
word-sets representing the two halves of each analogy (A-words and B-words, e.g., male-words
vs female-words). Repeated presentations of the same word, and surface variants grouped to the
same member (e.g., *man*/*men*), were pooled within their respective halves. Each word had 14.5 ±
1.9 trials (mean + s.e.m. median = 3 trials). The number of trials for a word pair (defined as the

minimum of the A or B side word) did not predict whether that pair was significantly aligned with the other pairs in the same analogy. This was determined using a Wald z-test on the logistic regression coefficient for trial count predicting significant alignment. (HPC: $p = 0.18$; ACC: $p = 0.78$; OFC: $p = 0.26$). For each neuron we quantified how well single-trial firing rates distinguished A-words from B-words using an orientation-free balanced AUC (Compute the usual AUC. If it is below 0.5, flip it by subtracting it from 1. Otherwise keep it as-is. The result is always at least 0.5, where 0.5 indicates chance). To assess whether a neuron's observed balanced AUC exceeded chance given the exact trial counts, we performed a label-shuffle permutation test at the trial level: Shuffle the A/B labels across trials (keeping the same number of A and B trials) R times. Each time, recompute the balanced AUC. Count how many shuffled values are greater than or equal to the observed balanced AUC, add one to that count, then divide by R plus one. That gives a one-sided p-value. We interpret this p-value as a tuning-strength score for analogy separation: smaller values indicate stronger, more reliable trial-level differences between the two halves. Downstream analyses can shortlist neurons by placing a threshold on this scalar, thereby retaining units that contribute consistent signal to subtraction-style population readouts and discarding units whose subtraction would be centered around zero (no firing rate differences) and thus dominated by random noise.

We developed two additional AUC null distributions, p(AUC-within-column) and p(AUC-word-level) and screened a small number of additional tuned neurons; they were not used (e.g., not in Figure 1E-F) unless otherwise specified. The second word-level permutation control, p(AUC-within-column), uses a within-column trial reassignment null: we keep each word's column label A/B fixed, but within each column separately we randomly reassign individual trials among the words in that column while preserving the number of trials contributed by each word. After this reassignment we recompute each word's aggregated firing rate (using the same aggregation rule as above) and then recompute the word-level AUC. This null and resulting p(AUC-within-column) asks whether the observed word-level separability depends on the specific mapping between trials and word identities within each column, while controlling for the empirical trial counts per word and the overall pool of trials available within each column.

In the third word-level AUC null p(AUC-word-level), we treat each unique word in the lexicon as a single data point (rather than each trial). For each neuron and each word, we first aggregate across all repeats of that word to obtain one firing-rate estimate per word (the mean of per-trial rates). Each word inherits its class label A/B from the lexicon column it appears in, and we then compute the same orientation-free AUC using these per-word rates. This word-level formulation reduces the influence of uneven repetition counts across words, because a word that appears many times still contributes only one point to the AUC.

Relational Similarity

1570

Our aim was to test whether the word pairs from two halves of an analogy share a
consistent direction in neural population space. For each analogy type we defined two word-
sets—"A-words" and "B-words" (for example, male-words vs female-words)—drawn from the
podcast vocabulary. Single-trial firing rates were first averaged across repetitions of the same
word to obtain one vector per word and neuron. Surface variants that belong to the same member
(for example, *man* and *men*) were pooled within the corresponding half by simple averaging.
Before forming any differences, each word's firing rate vector was L2-normalized to unit length
so that subsequent computations reflect direction rather than overall response magnitude.

For each row (one A-member paired with its B-member within the same analogy type),
we formed a difference vector by subtracting the A-member vector from the B-member vector
and then scaling this difference to unit length. To evaluate alignment for a held-out row, we
compared its unit difference vector ("test") to the unit difference vectors from all other rows of
the same analogy type ("training"). The observed score for that held-out row was the average
cosine similarity between the test vector and each individual training vector

Statistical evidence was obtained with a per-row permutation test based on random word
differences with random words sampled from the entire podcast vocabulary (not just the A/B
sets). In each of 10,000 draws we assembled as many random difference vectors as there are
training rows in the dataset, normalizing them exactly as done for the training/testing pairs. For a
given held-out row, its null distribution was built by taking, from each draw, the same number of
random differences as there are training rows and computing the mean cosine similarity between
those random differences and the test vector. The p-value equals "one plus the number of null
means at least as large as the observed mean" divided by "one plus ten thousand"; this plus-one
adjustment avoids zero p-values. While the number of training rows is constant under
leave-one-out, each held-out row has a different test vector, so each row naturally receives its
own null distribution of similarity (test vector vs random difference vectors) even as we shared
the underlying pool of random words. Intuitively, these null mean cosine similarities are
expected to center near zero for any test direction. We performed FDR correction on p values for
each analogy according to the number of pairs and corresponding number of p values before
designating/counting the number of significant word pairs per analogy type.

We searched a list of tuning strength score p(AUC) cutoffs (21 values from 0.01 to 0.35)
and selected a cutoff that yielded a high number of significant pairs per analogy. All neurons
with analogical tuning stronger than the cutoff are included in the population vector for words in
that analogy. This is based on our hypothesis that if a neuron's firing rate has no difference
between A vs B words (AUC close to 0.5, large p(AUC)), it should contribute to zero-centered
random noise during the A - B subtraction style analogy which we investigate. A minimum of 8
neurons with the strongest tuning were included when the criterion returned less than 8 neurons.
Due to the large number of artificial neurons(units) in BERT compared to any brain regions
(Figure 1F, 6E), we did not search by p(AUC) but instead grid searched [15 30 60 120] units in

BERT to identify the optimal number of neurons for this analysis. A complementary screening
approach (both p(AUC-within-column) and p(AUC-word-level) smaller than 0.01) were used but
yielded a nominal number of additional neurons incorporated in the population vector across 15
analogy types (ACC/OFC: 0.07 ± 0.26 neuron mean $\pm$ std, max 1; HPC: 0.47 ± 1.1 neuron, max
4).

For Supplementary Figure 5D only: Because neurons can only maintain non-negative
firing rates, raw word vectors tend to point into the same region (positive portions) of a space in
any dimension/axes and thus can never be more than 90 degrees with respect to each other; To
remove this bias, we centered each neuron by subtracting a baseline mean computed from words
outside the lexicon before forming the population vector used in Supplementary Figure 5D.

MDS visualization

1620

MDS was used for visualization only; we constructed a word-by-neuron response matrix
by averaging each neuron's firing rate across all trials for each word after pooling pre-specified
surface-form variants (e.g., singular/plural) into a single word identity. We did not impose any
A/B grouping for this analysis. To equalize scaling across neurons, we z-scored responses across
words separately for each neuron. We then computed pairwise dissimilarities between words
using cosine distance on the resulting population vectors and embedded the words into a 3-
dimensional space using MATLAB's mdscale() (metric multidimensional scaling). The
embedding was optimized to minimize the standard MDS stress criterion and plotted as a low-
dimensional visualization.

CCGP

We used a cross-condition generalization performance (CCGP) analysis to ask whether
neural population activity supports abstract structure that generalizes across matched word pairs,
and whether this generalization exceeds what would be expected from either random labels or
random geometry of the neural population. This analysis inherited the neuron selection criteria in
the relational similarity analysis.

a) Pseudo-population and matched word pairs. For each analysis we built a
pseudo-population by pooling neurons across patients and selecting a fixed subset of neurons
(same subset as relational(cosine) similarity analysis) and concatenating their responses into a
data matrix. For every neuron in this subset, trials were grouped by condition; in our case, a
condition corresponded to a particular lexical item (for example, the word "man", "woman",
"king", "queen", "boy", "girl", "mother", or "father"), possibly pooled across repeated
presentations and surface variants ("man" and "men"). For each neuron and condition we stored
a matrix containing all trial-by-trial firing rates..

Conditions were organized into matched pairs that instantiate the abstract distinction of interest.
A concrete example is a "gender"-like variable defined over four matched word pairs: man–
woman, king–queen, boy–girl, and mother–father. In this example, each pair contains a
masculine word and a feminine word. More generally, such matched pairs form a dichotomy in
our analysis; within each pair one condition is assigned to the "negative" class (for instance the
masculine member) and the other condition to the "positive" class (for instance the feminine
member). The analysis then asks whether a linear decoder trained to distinguish positive from
negative words on some subset of the pairs can correctly classify trails from the left-out pair.

b) Cross-condition generalization with leave-one-pair-out. To quantify CCGP, we used a
leave-one-matched-pair-out cross-validation scheme at the level of pairs. Suppose the dichotomy
is defined by the four gender word pairs, in one outer fold, we leave out the man–woman pair as
the test pair. All trials for "man" and "woman" are held aside, while the remaining three pairs
(king–queen, boy–girl, mother–father) are used for training.

Within each fold, we enforced equal sampling size across conditions. For every neuron
and every condition included in that fold, we randomly subsampled a fixed number of trials per
condition without replacement. These subsampled trials were stacked across conditions to form a
trial-by-neuron matrix. Trials from all "negative" conditions (e.g. man, king, boy, father) were
assigned one label, and trials from all "positive" conditions (woman, queen, girl, mother) were
assigned the opposite label. We then standardized each neuron's activity by z-scoring across
trials within that fold.

We trained a linear regression with logistic loss on the subsampled training data from the
three training pairs and then evaluated it on all subsampled trials from the held-out pair.
Accuracy on the held-out pair provides a measure of CCGP for that outer fold. We repeated this
procedure, in turn, leaving out each matched pair as the test pair (so we also evaluated
generalization to king–queen when the other pairs were used for training, and so on) and
averaged accuracy across these outer folds to obtain one CCGP value for that bootstrap iteration.

To obtain a stable estimate that is not driven by a particular choice of trials, we repeated
the entire subsampling and left-one-pair-out procedure 600 times, each time drawing a new
random subsample of trials per condition. The primary CCGP estimate reported for each
population and dichotomy is the mean accuracy across these iterations.

c) Regularized linear decoding and nested cross-validation. To avoid overfitting
idiosyncratic fluctuations in the training data, decoding was performed with a linear classifier
with logistic loss and L2 regularization. However, the optimal strength of regularization is not
known in advance and may differ across populations and dichotomies. To choose the
regularization strength in a data-driven way, we used nested cross-validation inside the outer
leave-one-pair-out loop. Returning to the four-pair example, consider again the outer fold where
man–woman is held out as the test pair. The remaining three pairs—king–queen, boy–girl, and

1681 mother–father—serve as the training pairs. Within this training set, we perform an inner
1682 leave-one-pair-out cross-validation to select the regularization parameter. For a candidate value
1683 of λ, first, we hold out one of the training pairs as an inner validation pair, for example boy–girl.
1684 We train the classifier on subsampled and standardized trials from the remaining pairs (king–
1685 queen and mother–father) using that λ, then measure how well it predicts the labels for the
1686 held-out validation pair boy–girl. We repeat this inner procedure holding out each training pair in
1687 turn (boy–girl, king–queen, mother–father), and average the validation errors across these inner
1688 folds to obtain a cross-validated error for that λ.

1689  We repeat the inner leave-one-pair-out procedure for a small grid of candidate λ values
1690 (1/N, 3e−3,1e−2, 3e−2, 6e−2, 1e−1, 3e-1, where N is the number of neurons) The λ that yields
1691 the lowest average validation error is selected for that outer fold; if multiple λ values perform
1692 equally well within numerical precision, we choose a value near the center of this set on a
1693 logarithmic scale.

1694  d) Geometric (neuron-shuffle) null. To determine whether high CCGP truly reflects
1695 meaningful structure in the population code, we compared the empirical CCGP to a geometric
1696 null model that disrupts the consistent identity of neurons across conditions while preserving
1697 activity distributions within each condition. For this null, we repeated the entire analysis
1698 described above, but before decoding we shuffled neuron identities within each condition.
1699 Concretely, for a given condition (e.g. all trials of "man"), we assembled a trial-by-neuron matrix
1700 and randomly permuted the order of neurons (columns) within that matrix. This operation was
1701 performed independently in each condition (man, woman, king, queen, etc.). As a result, each
1702 neuron's pattern of responses is effectively reassigned to a different label in each condition,
1703 preserving the distribution of firing rates across trials and across neurons within each condition
1704 but destroying the consistent mapping between neurons and their tuning across different words
1705 and pairs.

1706  After this neuron shuffling, we ran the same nested leave-one-pair-out decoding
1707 procedure as for the empirical data, including the same trial subsampling and regularization
1708 selection. The resulting distribution of CCGP values across iterations provides a geometric null
1709 that captures how much cross-pair generalization would be expected from high-dimensional
1710 variability alone, in the absence of stable neuron-specific codes that align across conditions.

1711  e) Label-shuffle null. As a complementary control, we also constructed a label-shuffle
1712 null model that preserves the neural data but destroys the relationship between neural activity
1713 and the semantic variable being decoded. In this variant we used the original, unshuffled neural
1714 responses but, within each outer fold, randomly permuted the class labels assigned to trials
1715 before training and testing the decoder. The entire nested cross-validation procedure was then
1716 run on these randomly relabeled data. This null provides a baseline for CCGP that would be
1717 expected if the decoder were applied to the same neural activity but the mapping between

population patterns and the conceptual dichotomy (e.g. masculine vs feminine words) were
arbitrary.

f) Summary and statistical comparison. For each analogy, we therefore obtained three
CCGP distributions across bootstrap iterations: one from the intact data, one from the
neuron-shuffle (geometric) null, and one from the label-shuffle null. The empirical CCGP for a
given population was taken as the mean accuracy across iterations on the intact data. To assess
significance, we compared this value to the corresponding null distributions by computing the
proportion of null iterations whose CCGP was at least as large as the empirical mean, with a
small finite-sample correction. In the man–woman, king–queen, boy–girl, mother–father
example, a high and significant CCGP means that a linear decoder trained to distinguish three of
these word pairs reliably predicts the left-out pair, in a way that cannot be explained by shuffled
labels or by random reassignments of neuron identity.
1730

1731 **Additive factor model of pronoun-evoked population activity**

1732

We quantified the extent to which pronoun-evoked hippocampal population activity
could be explained by an additive (factorized) representation of grammatical features versus
feature interactions. This analysis was performed at the individual-trial level, using the trial-by-
neuron firing rate matrix Z (T trials × N neurons) restricted to the 12 pronoun categories: {i, me,
my, we, us, our, he, him, his, they, them, their}. Each trial t had a word label label(t), and Z(t,n)
denotes the firing rate of neuron n on trial t. For each retained trial, we assigned three categorical
factors based on the pronoun identity:

1740

case(t)∈{sub,obj,poss}
sub:i,we,he,they
obj:me,us,him,them
poss:my, our, his, their

number(t) ∈ {sing, plur}
sing: i, me, my, he, him, his
plur: we, us, our, they, them, their

person(t) ∈ {p1, p3}
p1: i, me, my, we, us, our
p3: he, him, his, they, them, their

We fit multivariate linear regressions that predict the N-dimensional population response
on each trial from dummy-coded grammatical factors. The models were fitted simultaneously
across neurons by ordinary least squares (OLS), using the same design matrix X for all neurons.
The main-effects model included an intercept plus additive terms for case, number, and person.

Using reference coding with baselines case=sub, number=sing, person=p1, the main-effects
design matrix contained the following regressors: intercept (all ones), I(case=obj), I(case=poss),
I(number=plur), I(person=p3). I() is the indicator function. Let X_main be the resulting T ×
P_main matrix and B_main be the P_main × N coefficient matrix. Coefficients were estimated
by OLS: B_main = X_main \ Z, Zhat_main = X_main * B_main. The full model expanded the
main-effects design matrix with interaction terms up to three-way:
1761
1762   case × number interactions: I(case=obj)*I(number=plur), I(case=poss)*I(number=plur)
1763   case × person interactions: I(case=obj)*I(person=p3), I(case=poss)*I(person=p3)
1764   number × person interaction: I(number=plur)*I(person=p3)
1765   case × number × person interactions: I(case=obj)*I(number=plur)*I(person=p3),
1766   I(case=poss)*I(number=plur)*I(person=p3)
1767
Let X_full be the resulting T × P_full matrix. Coefficients and predictions were computed
analogously: B_full = X_full \ Z, Zhat_full = X_full * B_full. Model fit quality was summarized
as a single population-level R2, computed by pooling squared errors across all trials and neurons
(rather than computing R2 per neuron). For a generic prediction Zhat, we computed: SSE = sum
over all t,n of $(Z(t,n) - Zhat(t,n))^2$, SST = sum over all t,n of $(Z(t,n) - mean\_t\ Z(t,n))^2$, where
mean_t Z(t,n) is the mean firing rate of neuron n across the T included trials. The pooled R2 was
then: R2 = 1 − (SSE / SST)
We computed R2_main using Zhat_main and R2_full using Zhat_full. Because the full
model includes additional degrees of freedom, R2_full is expected to be greater than or equal to
R2_main. To quantify the relative contribution of additive structure within the explainable
component, we also computed the fraction: frac_main = R2_main / R2_full.
Statistical significance of additive factorization was assessed using a label-shuffle null
distribution. On each permutation, we randomly permuted the trial-wise word labels label(t)
across the retained trials (keeping Z fixed), recomputed case(t), number(t), and person(t) from
the shuffled labels, rebuilt X_main and X_full, refit both models by OLS, and recomputed
R2_main, R2_full, and frac_main. This procedure preserves the marginal distribution of firing
rates and trial counts while destroying the correspondence between population activity and
pronoun identity/feature structure
The observed frac_main was compared to the permutation distribution using a one-sided
test (higher frac_main indicates a more factorized, main-effects–dominant structure). With
N_perm shuffles, the p-value was computed as:
p = (1 + number of permutations with frac_main_perm >= frac_main_obs) / (N_perm + 1)
1790
1791
1792 **Differences across brain areas.**
1793

We tested whether the prevalence of significant word-pair effects differed between
hippocampus (HPC) and anterior cingulate cortex (ACC) across 15 analogy types. Same sets of
analysis was repeated comparing HPC to OFC. To make the regional comparison robust to
differences in neuronal sample size, we summarized each word pair with a 0–1 significance-
prevalence score that reflects how likely that pair is to be deemed significantly aligned with other
pairs in an analogy under ACC neuron count-matched sampling. Concretely, this score
corresponds to whether a pair is significant in ACC, and—because HPC had a larger neuronal
pool—to the fraction of neuron-matched resamples (500 resamples) in HPC that yield a
significant effect. This yields a common metric across areas in which larger values indicate more
reliably detectable word-pair effects at comparable sampling, rather than simply reflecting
differences in the number of recorded neurons.

1805

1806   We fit a linear mixed-effects model with fixed effects of Area, Type, and their
1807 interaction, and a random intercept for word-pair identity (pairID) :
1808 sigPrev∼1+Area×Type+(1|PairID), 412-word pair observations; Residual method for the degrees
1809 of freedom. Marginal ANOVA tests indicated significant effects of Area, Type and a robust Area
1810 × Type.

1811

To complement the linear mixed-effects analysis, we performed a brain area
label-shuffling, size-matched resampling test that asks whether HPC and ACC show different
profiles of significant word-pair counts across the 15 analogy types, independent of unequal
neuron counts. For each area we computed a 15-element vector,
vArea=[sigCount1,…,sigCount15] where each element is the number of significant word pairs
(*sigCount*) for that analogy type. We quantified the similarity between the two area profiles
using cosine similarity between the HPC and ACC vectors (lower cosine similarity = more
different profiles).

Because the number of recorded neurons differed between areas, we used balanced
resampling: in each iteration we randomly downsampled HPC neurons to match the ACC neuron
count, recomputed the HPC and ACC *sigCount* vectors, and then computed cosine similarity. We
repeated this procedure 500 times and used the average cosine similarity across the 500
downsamplings as the observed (non-shuffled) profile similarity.

To generate a null distribution under the hypothesis that area identity does not matter
(i.e., neurons are exchangeable between HPC and ACC), we pooled neurons across areas,
randomly permuted (shuffled) the area label assigned to each neuron, then repeated the same
size-matched sampling and cosine-similarity computation 500 times. We then asked how often
the shuffled data produced a profile similarity as low as (or lower than) the observed value—i.e.,
a pattern as different or more different than the real HPC vs ACC profiles.

1831

1832 **Supplementary Figures**

1833

1834

1835 **Supplementary Figure 1 | PSTH for example neurons in other brain areas.**

1836 Same as Figure 1C but for example ACC/OFC neurons.

1837

Supplementary Figure 2 | Analogical representation across BERT and GPT layers.
We analyzed 13 layers of BERT (blue) and 37 layers of GPT-2 (red), normalizing the x-axis by relative
depth (e.g., the 6th layer of BERT appears at 0.46). Across 15 analogy types, the fraction of dimensions
meeting our criterion generally dropped as layers deepened (increased layer index). This suggests that
later layers rely on fewer specialized embedding dimensions. Exceptions include context-dependent
operations (e.g., negation ("feel" vs "(not) feel" and qualifier "fall" vs "(kind of) fall" modification),
where performance depends on contextual binding.

Supplementary Figure 3 | Additional hippocampal analogy cosine similarities/additional analogy
types supporting Fig2 and Fig3
A–H, Alignment of individual word-pair difference vectors to the other word pairs within-category
in HPC. For each semantic relationship, we computed a leave-one-out mean difference direction from
high-dimensional neural word embeddings (population firing-rate vectors) and measured mean cosine
similarity between each held-out word-pair difference vector and the training direction. Grey violins
indicate a random word-pair null distribution; dots indicate observed similarities (colored: significant
after Benjamini–Hochberg FDR correction across pairs within category; grey: non-significant). **A,** Gender
(subset shown). **B,** Random word pairs (control), only 35 pairs shown, see Figure 2 for the rest 15 pairs.
C–H, Residence, protector, antonyms (valence-oriented), noun plural, adjective comparative, and verb
negation. These panels correspond to the alignment analyses shown in the main figures; see Figure 3 for
the accompanying MDS and CCGP for these relationships.
I–P, Two additional semantic relationships show consistent axes and support cross-condition
generalization. We identified aligned difference directions for **odd number + 1** and for **qualifiers**
(words preceded by *kind of* / *slightly*; shown as "q+" prefixes). **I,M,** 3D MDS visualization of neural
word embeddings with arrows indicating paired difference vectors (MDS shown for visualization only;
grey planes are visual aids). Colored arrows/labels denote pairs whose high-dimensional difference
vectors are significantly aligned to the within-category direction (permutation test against random
word-pair null; Benjamini–Hochberg FDR across pairs within category); grey arrows/labels denote
non-significant pairs. Blue arrows indicate the mean direction projected into the MDS view. **J,N,** The
same vectors after tail alignment and rigid rotation so the mean direction points upward, with vector
lengths normalized to a unit sphere (visualization only; angles preserved). **K,O,** mean Cosine similarity of
each pair to the leave-pair-out directions from other word pairs in the same category with null
distributions (grey violins). **L,P,** Cross-condition generalization performance (CCGP) for each
relationship (red marker), compared to label-shuffle and neuron-shuffle nulls (grey violins; dashed line
indicates chance). Asterisks indicate $p < 0.05$ (permutation test; n shuffles = 600) relative to the
corresponding null.

1874

1875
1876
1877

1878

1879
Supplementary Figure 4 | Robustness to similarity metric and limited analogy retrieval from neural
vector arithmetic.
A–C, Distance-metric robustness for alignment. For the gender analogy set in hippocampus (HPC),
pairwise alignment between within-category difference vectors was recomputed using alternative
similarity metrics. **A,** Euclidean similarity (1 - euclidean distance) between each gender difference vector
(e.g., "*woman*"−"*man*") and the leave-one-out mean gender direction; grey violins indicate a random-
pair null distribution and colored dots show observed similarity (asterisks: significant after within-
category multiple-comparisons control, as in the main analysis). **B,** Same analysis using 1 - Chebyshev
distance. Across analogy types, the number of significant aligned word pairs is comparable under
Euclidean, cosine, and Chebyshev similarity (paired Wilcoxon signed-rank tests, n.s.).
D–F, Analogy retrieval is weak and insensitive to scoring choice. D, For each analogy type, mean rank
of the correct target word under vector-arithmetic retrieval: for each pair A:B and source word C, the
model predicts a target D from D(estimate)=(B−A)+C and ranks all candidate words in the corpus by
similarity to D(estimate) (lower rank indicates better retrieval). **E,** Example retrieval rank distributions for
the gender set; only "*girl*"–"*boy*" is retrieved significantly above chance relative to a random-difference
baseline. **F,** The number of significant retrieved word pairs is not significantly different when using a
magnitude-aware scoring rule versus cosine similarity after L2 normalization (paired Wilcoxon signed-
rank test, n.s.).
1898
Supplementary result and discussion for this figure: We primarily relied on cosine similarity to
quantify vector-offset analogies, as it remains the standard in the field (Mikolov et al., 2013).
However, given that this metric could be sensitive to normalization and scoring choices (Levy &
Goldberg, 2014), we investigated whether our neural axis-alignment findings were robust across

metrics or merely artifacts of specific distance calculations. Recomputing pairwise alignment
with Euclidean and Chebyshev similarity (1 - distance) produced the same qualitative outcome
and did not significantly change the number of significant aligned pairs across analogy types
(**Supplementary Figure 4**, Wilcoxon signed-rank tests, $p > 0.05$). We also evaluated a stricter
"analogy retrieval" criterion—ranking the true target word against all other words using vector
arithmetic $(B - A + C)$—and found that retrieval was only modestly above chance: across
analogy families, the target routinely ranked well outside the top set of candidates
(typically >100), and in the gender set only "*girl*"–"*boy*" was reliably retrieved above chance
(**Supplementary Figure 4**). The number of significant word pairs did not alter by switching
from cosine similarity scoring to this analogy retrieval regime, reinforcing that our primary
alignment results are largely distance-metric or paradigm agnostic, while leaving open what
similarity computation downstream circuits implement and whether the exact parallelogram-style
retrieval is the algorithm the brain uses to solve SAT style analogy reasoning tasks.
1916
1917
1918

Supplementary Figure 5 | Distinct semantic axes and control analyses for vector geometry, with
additional pronoun results supporting Figure 2-4
A–B, Antonym and verb-negation axes do not generalize to one another. We tested whether the
coding directions learned from one analogy family predicts pairwise directions in another by training the
directions on one set of word-pair difference vectors and then computing cosine similarity between those
directions and each held-out pair in the other set (grey violins: random-pair null; dots: observed mean
similarities; asterisks: significant alignment vs. null after multiple-comparison correction within panel).
C–D, Axis alignment is not explained by systematic changes in vector magnitude or simple sign
inversions. C, Signed differences in raw vector length (Δ vector length; units reflect firing-rate vector
magnitude) between the two words within each pair, computed consistently using the top 30 tuned
(lowest p(AUC)) neurons for that analogy type. Blue labels indicate which side of the pair had the larger
mean length; asterisks denote analogy types with a significant nonzero mean Δ length (paired t-test across
word pairs, Benjamini–Hochberg FDR). For visualization only, pronoun analogies are plotted separately
from the other analogy types (the repeated y-axis is identical). Because our main analyses L2-normalize
each word vector before subtraction (**Methods**), systematic differences in raw vector length cannot
account for the observed axis alignment. **D,** Angles between the two raw word vectors within each pair.
Negation (e.g., "not *grow*" vs. "*grow*") and comparative morphology (e.g., "*taller*" vs. "*tall*") are not
consistent with antipodal inversions (~180°), but instead tend to be approximately orthogonal (~90°) to
the corresponding root-word vectors (cf. Zuanazzi et al., 2024).
E, Pronoun analogies shown in MDS for visualization. Low-dimensional MDS plots for four pronoun
analogy families (subject/object, object/possessive, plural, and subject/possessive). These MDS
visualizations are provided for reference; associated mean-direction, cosine-alignment, and CCGP
analyses are shown in Fig. 4.
F–I, First-/third-person pronoun analogy. F, MDS visualization for the first-/third-person axis. **G,** Tail-
aligned difference vectors projected onto a unit sphere and rotated so the mean direction points upward.
H, mean Cosine similarity of each first-/third-person pair to the leave-one-out training directions (rest of
the word-pairs) (null distributions in grey); 5/6 pairs are significantly aligned (binomial test p < 0.001). **I,**
Cross-condition generalization performance (CCGP) for first vs. third person, shown relative to label-
shuffled and neuron-shuffled null distributions. Asterisks indicate p < 0.05 (permutation test; n shuffles =
600) relative to the corresponding null.
1950

1953 **Supplementary Figure 6 | Pairwise cosine-similarity evidence for analogy axes in ACC and OFC**
1954 **supporting Figure 5.**
1955 **A,** Protector analogy in orbitofrontal cortex (OFC). For each protector word pair, we computed the mean
1956 cosine similarity between that pair's high-dimensional population difference vector and that of remaining
1957 word-pairs (leave-one-out) within OFC. Grey violins show a null distribution obtained from random
1958 word-pair difference vectors; dots indicate observed similarities. Colored dots/labels mark pairs that are
1959 significantly aligned with the rest of the pairs after Benjamini–Hochberg FDR correction across pairs
1960 within the category; grey labels indicate non-significant pairs. Dot colors match the corresponding
1961 vectors/labels in the MDS visualization in Figure 5.
1962 **B–C,** Verb *-ed/-ing* analogy in anterior cingulate cortex (ACC) and hippocampus (HPC). Same analysis
1963 as in **A**, shown for the verb *-ed/-ing* relationship in **ACC** (**B**) and **HPC** (**C**). In ACC, many verb pairs
1964 exhibit significant alignment to a shared *-ed/-ing* direction (colored points), whereas in HPC the
1965 corresponding cosine similarities cluster near the null distribution and do not show robust pairwise
1966 alignment. Colors again correspond to the matched word pairs/vectors in the MDS panels in Figure 5.
1967

Supplementary Figure 7 | Specialization in OFC and ACC neurons.

1970   Same specialization results as in Figure 6 but for OFC and ACC neurons.

Pron. Obj/Poss			Pron. Subj/Poss			Pron. Subj/Obj	
objective	**possessive**		**subjective**	**possessive**		**subjective**	**objective**
me	my		i	my		i	me
you_o	your		she	her		you_s	you_o
her_o	her		you_s	your		he	him
him	his		he	his		she	her_o
us	our		they	their		it_s	it_o
them	their		we	our		we	us
						they	them
Pron. Plural			**Pron. 1st/3rd**			**Adj Comparative**	
single-pron.	**plural-pron.**		**1st-person**	**3rd-person**		**adjective**	**comparative**
i	we		i	she, he, it_s		good	better
me	us		me	her_o, him, it_o		tall	taller
my	our		my	her, his		young	younger
she, he, it_s	they		we	they		old	older
her_o, him, it_o	them		us	them		full	fuller
his, her	their		our	their		close	closer
						complicated	more complicated
Qualifier			**Protector**			**Odd Number +1**	
word	**qualifier**		**human**	**protector**		**odd**	**odd+1**
q+figured	figure, figuring		teacher	student's, graders		one	two
q+fall	fall		sergeant	soldier		either	both
q+coming	coming		doctor, doctors	patients		single	couple
q+different	different		parents			three	four, fours

			child, children	15	16
q+freaked	freaked, freaking		counselors	bunkmates	five, fiving	six
q+pushed	push, pushing		(offensive) lineman	quarterback	seven	eight
q+end	end		God	Christian	eleven	12
q+staring	staring				13	14
_o/_s: when the word serves as the object/subject in a sentence.						
q+: words under the modification of "kind of", "sort of", "slightly", qualifiers themselves were not used.						

1977
1978

Verb Negation			Antonyms	
verb	negated		high valence	low valence
laugh, laughed, laughs, laughing	not+laughing		balance	imbalance
help, helped, helps	not+helping		clean	dirty
stop, stopped, stops	not+stopped		closer, close	far
happen, happened, happens	not+happened		young, youngest, younger	older, old, oldest
do, did_a, does	not+do		new	old_a
knew, know, known, knows	not+know		pull, pulls, pulling, pulled	pushing, pushed
remember, remembered, realize	not+remember, not+remembered, not+realize		good, nice, best, better	awful, worst, worse
go, went, gone, goes	not+go		yes	no
hear, heard, hears	not+hear		right	wrong
get, gets, got, gotten, getting	not+get, not+getting		heat	cold
make, made, makes, making	not+make		different	same
describe, say, said, says, saying, talk, talked, talks, talking, speak, spoke,	not+describe, not+say, not+talked,		laugh, laughing, laughed	cried, crying, sobbing
			inside	outside

spoken, speaks, tell, told, tells, telling	not+talk, not+told, not+speak		long	short
			remember, remembered	forget
feel, felt, feels	not+feel		after	before
need, needed, needs	not+need		high	low
want, wanted, wants, wanting, wanna	not+wanna, not+want, not+wanted		big, giant	smallest, little
see, saw, seen, sees, seeing	not+seen		answers, answer	questions, question
grow, grew, grown, grows	not+grow		quiet	loud
play, played, plays, playing	not+play		lift	fall
let, lets, letting	not+let		front	back

not+: verb under negation of "not", "hasn't", "don't", "never", "couldn't", "didn't", "wasn't" etc.

old_a: when "old" means "not new", rather than "not young".

did_a: when "did" means an action "the first thing that I did" rather than other meanings as in "I did tell you that" or "I did not do it".

1979
1980

Verb -ed/-ing		Verb -ed/-ing Cont.			Gender	
verb-ed	**verb-ing**	**verb-ed**	**verb-ing**		**male**	**female**
got, gotta	getting	loved	loving		men, man	woman, women
told	telling	raised	raising		kings	queen
gone, went	going, gonna	made	making		sir	lady
did, didn't, done	doing	laughed	laughing		husband	girlfriend
been	being	turned	turning		beast	beauty
knew, known	knowing	pushed	pushing		dad	mom
grew	growing	sat	sitting		brother, brothers	sister, sisters
fixed	fixing	asked	asking		son	daughter
taken, took	taking	brought	bringing		boy, boys	girl, girls
had, hadn't	having	freaked	freaking		he	she
saw, seen	seeing	soaked	soaking		Harwood	Michelle
found	finding	assumed	assuming		Harwood's	Christina

kept	keeping		read	reading		mark	Christine
put	putting					frank, colin	Judy, June
figured	figuring					him	her_o
said	saying		**Residence**				
gave	giving		**human**	**places**			
thought	thinking		passenger	car			
talked	talking		soldier, vet, sergeant	Vietnam, force			
came	coming		bunkmates	bed, cabin, cabins			
wrote	writing		graders, teacher student's, freshman, guys, guy, peers	school, classroom			
looked	looking		doctors, doctor, patients	hospital, infirmary			
cried	crying		minister, Christian	church			
used	using		family	home			
wondered	wondering		person, people	community			
performed	performing		Texans	Texas			
_o : when the word serves as the object in a sentence.							

1981 **Supplementary Table 1.** Full list of words used for 14 analogies. see Supplementary Figure 3F
1982 for words used in noun single plural analogy.