LoReMINE: Long Read-based Microbial genome mining pipeline

Amay A. Agrawal[1,2*], Chantal D. Bader[3,4], Ronald Garcia[3,5], Rolf Müller[3,4,5], Olga V. Kalinina[1,6,7]

1 Department of Drug Bioinformatics, Helmholtz Institute for Pharmaceutical Saarland (HIPS) / Helmholtz Centre for Infection Research (HZI), Saarbrücken, Saarland, Germany
2 Graduate School of Computer Science, Saarland University, Saarbrücken, Saarland, Germany
3 Department of Microbial Natural Products, Helmholtz Institute for Pharmaceutical Saarland (HIPS) / Helmholtz Centre for Infection Research (HZI), Saarbrücken, Saarland, Germany
4 PharmaScienceHub, Saarbrücken, Saarland, Germany
5 German Center for Infection Research (DZIF), Partner Site Hannover-Braunschweig, 38124 Braunschweig, Germany
6 Faculty of Medicine, Saarland University, Homburg, Saarland, Germany
7 Center for Bioinformatics, Saarland University, Saarbrücken, Saarland, Germany

* amayajaykumar.agrawal@helmholtz-hips.de

Abstract

Microbial natural products represent a chemically diverse repertoire of small molecules with major pharmaceutical potential. Despite the increasing availability of microbial genome sequences, large-scale natural product discovery remains challenging because the existing genome mining approaches lack integrated workflows for rapid dereplication of known compounds and prioritization of novel candidates, forcing researchers to rely on multiple tools that requires extensive manual curation and expert intervention at each step. To address these limitations, we introduce LoReMINE (**Lo**ng **Re**ad-based Microbial genome **min**ing pipelin**e**), a fully automated end-to-end pipeline that generates high-quality assemblies, performs taxonomic classification, predicts biosynthetic gene clusters (BGCs) responsible for biosynthesis of natural products, and clusters them into gene cluster families (GCFs) directly from long-read sequencing data. By integrating state-of-the-art tools into a seamless pipeline, LoReMINE enables scalable, reproducible, and comprehensive genome mining across diverse microbial taxa. The pipeline is openly available at `https://github.com/kalininalab/LoReMINE` and can be installed via Conda (`https://anaconda.org/kalininalab/loremine`), facilitating broad adoption by the natural product research community.

Author summary

For decades, microbial natural products have been a major source of medicines, with most of the clinically used antibiotics being their derivatives. Recent advances in DNA sequencing technologies now allow the reconstruction of more complete and continuous microbial genomes, revealing a vast and largely untapped diversity of biosynthetic gene

clusters responsible for natural product biosynthesis. Despite these advances, large-scale natural product discovery remains difficult because current genome mining approaches rely on many separate tools and lack an integrated workflow to dereplicate known compounds and prioritize novel biosynthetic pathways. To address these limitations, we introduce LoReMINE, an automated pipeline designed to simplify microbial genome mining directly from long-read sequencing data. LoReMINE integrates genome assembly, taxonomic classification, identification of biosynthetic gene clusters, and their clustering into gene cluster families within a single, reproducible workflow. This streamlined approach enables scalable analysis across diverse microbial taxa and facilitates comprehensive exploration of microbial biosynthetic potential. The pipeline is designed for both experimental and computational researchers, helping to advance natural product research and contribute towards the discovery of new therapeutic drugs.

Introduction

Natural products (NPs) have historically been an important source for new therapeutic drugs. They are small molecules produced by plants, microbes, and fungi that are not directly essential for growth and development, but they help the producing organism in adapting to its environment or serve as a defense mechanism, thereby supporting its survival [1]. One of the most famous example of a natural product is the antibiotic penicillin, which was derived from the fungus *Penicillium notatum* [2]. Some of the other widely prescribed drugs that are either natural products or their derivatives include aspirin (anti-inflammatory), doxorubicin (anti-cancer), amphotericin B (antifungal), oseltamivir (antiviral), acarbose (antidiabetic), avermectin (antiparasitic), tetracycline (antibiotic), etc. [3, 4]

Traditional approaches for discovering new NPs primarily relied on the biological screening of crude extracts to isolate active compounds [5]. While these methods proved effective in identifying numerous bioactive NPs, they were constrained by certain limitations. Many NPs are poorly expressed under standard laboratory conditions, making them undetectable through conventional techniques, and as a result, a vast pool of potentially valuable compounds remains inaccessible. Additionally, these approaches are labor-intensive, have low-throughput and are often hindered by the frequent rediscovery of already known molecules, thereby reducing their efficiency in uncovering novel bioactive substances [6].

As the cost of whole-genome sequencing has continuously declined over the last few decades, the focus has now shifted from traditional bioactivity-guided approaches towards genome mining based approaches for finding new NPs [7, 8]. Genome mining based approaches are based on the fact that NPs are typically synthesized by groups of enzymes, whose genes are encoded in close proximity in the genome, forming a so-called biosynthetic gene clusters (BGCs) that can be effectively found computationally. These BGCs are categorized into distinct classes based on their core enzymes and assembly logic, with major classes including non-ribosomal peptide synthetases (NRPSs), polyketide synthases (PKSs), ribosomally synthesized and post-translationally modified peptides (RiPPs), terpenes, and saccharides [9].

A key advantage of genome mining is its ability to detect "cryptic" or "silent" BGCs that are poorly expressed under standard laboratory conditions and therefore remain inaccessible via traditional methods. Once identified, these hidden pathways can be activated using strategies such as heterologous expression, unlocking a large reservoir of previously hidden chemical diversity [10]. Genome mining also allows targeted drug discovery by searching for specific genomic markers such as self-resistance genes or bioactive chemical features to identify natural products with desired biological activities [8]. Furthermore, combining genome mining with taxonomic classification

provides an evolutionary framework for prioritizing BGCs from rare or underexplored microbial lineages, which are more likely to yield novel compounds and also help to reduce the rediscovery of known natural products [11, 12].

Genome mining based NP discovery involves multiple steps, including genome assembly, identification of BGCs, comparative genomic analysis to identify similarities and differences between BGCs and organisms, and prediction of biosynthesized natural product scaffolds [13]. Despite its transformative potential, genome mining is strongly dependent on the quality of genome assemblies. Short-read sequencing technologies, such as Illumina, has been largely responsible for the rapid accumulation of draft genome assemblies at the National Centre for Biotechnology Information (NCBI), but they often yield highly fragmented assemblies. As a result, BGCs encoding large multimodular enzymes such as PKSs and NRPSs are often splitted across multiple regions, making it difficult to detect and interpret them correctly. To alleviate this, long-read sequencing platforms, such as PacBio and Oxford Nanopore Technologies (ONT), have become indispensable in genome mining studies, as they enable the generation of contiguous assemblies that span complete BGCs, providing an unprecedented opportunity to fully exploit microbial genomes for NP discovery.

Once a high-quality assembly is obtained, the next step is to identify the BGCs. Several tools like antiSMASH [14], PRISM [15], DeepBGC [16] have been developed to identify BGCs, among which antiSMASH is regarded as a gold standard tool for this purpose. It is a rule-based tool which uses profile hidden Markov models (pHMMs) to identify BGCs, and currently it contains detection rules for identifying 101 different classes and sub-classes of BGCs.

To enable exploration beyond single-genome studies, antiSMASH database [17] provides a large-scale repository of precomputed BGCs across thousands of microbial genomes, offering a valuable resource for comparative analyses across different taxa. Further, many of these predicted BGCs have also been experimentally linked to specific natural products with characterized chemical structures, giving rise to a database called Minimum Information about a Biosynthetic Gene cluster (MIBiG [18]) that currently contains more than 2500 validated gene cluster–molecule pairs. Given the enormous diversity of BGCs across these databases, comparison tools, such as BiG-SCAPE [19] and BiG-SLiCE [20], have been developed. They facilitate mapping relationships between thousands of BGCs by clustering them into gene cluster families (GCFs). BGCs belonging to different GCFs are expected to produce chemically different compounds, while the products of BGCs from the same GCF can be quite similar. The clustering output readily allows the user to identify GCFs with known members from MIBiG, while, on the other hand, GCFs with no MIBiG reference BGCs may point to biosynthetic pathways that are completely novel and unexplored.

Despite the availability of these powerful tools and databases for genome mining, a unified workflow that integrates them for large-scale natural product discovery is still missing. To address this critical gap, we present LoReMINE (**Lo**ng **Re**ad-based Microbial genome **min**ing pipelin**e**), an end-to-end workflow for microbial natural product discovery directly from long-read sequencing data. LoReMINE integrates multiple modules into a unified pipeline: (i) *de novo* genome assembly using multiple long-read assemblers with automated selection of the highest quality assembly, (ii) taxonomic classification, (iii) BGC detection, and (iv) clustering of identified BGCs into GCFs to facilitate comparative analysis across different databases and taxa. By combining these steps into a unified workflow, LoReMINE facilitates comprehensive exploration of natural product diversity which has the potential to yield novel drug candidates.

Fig 1. Workflow of the LoReMINE pipeline. LoReMINE consists of four submodules that can be run individually or as a complete workflow. Submodule 1 takes sequencing reads as input and, depending on the read type, applies an appropriate assembly strategy to generate the best-quality genome assembly. The resulting assembly can then be used as input for Submodule 2, which performs taxonomic classification of the input genome, and Submodule 3, which identifies BGCs in the input genome. The predicted BGCs, optionally combined with reference BGCs from the MIBiG database, are provided to Submodule 4, which clusters BGCs into GCFs. The resulting GCFs can be visualized to distinguish known biosynthetic pathways from potentially novel ones. Alternatively, the `"all_submodules"` option provides a fully automated workflow that takes sequencing reads as input, executes all four submodules sequentially, and directly produces GCF outputs without requiring any manual intervention.

Materials and methods

LoReMINE is designed as a fully automated, modular workflow to enable end-to-end discovery of microbial natural products directly from long-read sequencing data. The workflow integrates four core submodules: (i) assemble, (ii) taxonomy, (iii) identify_bgcs, and (iv) bgc_clustering, each of which can be executed independently or as part of the complete workflow (Figure 1). The individual submodules are described below.

assemble

This submodule performs *de novo* genome assembly from long-read sequencing data generated by PacBio (both HiFi and continuous long reads (CLR)) and Oxford Nanopore Technologies (ONT) platforms. The pipeline supports both single-strain assembly and batch processing of multiple strains in a single run, enabling scalable analysis of large sequencing datasets. To maximize assembly quality and minimize

assembler bias, LoReMINE integrates multiple state-of-the-art long-read assemblers. ₁₀₂

For PacBio HiFi reads, three variants of assemblies are independently generated ₁₀₃ using Flye [21], Hifiasm [22], and IPA [23]. For PacBio CLR and ONT reads, the ₁₀₄ assembly is first performed using Flye with default parameters. If the resulting assembly ₁₀₅ is deemed unsatisfactory by the user, the parameter (`--alt_param`) can be activated, ₁₀₆ which performs additional assemblies by adjusting the "minimum overlap" parameter of ₁₀₇ the Flye assembler. Each candidate assembly undergoes a quality control step ₁₀₈ performed using DustMasker [24, 25] to remove contigs having low complexity regions ₁₀₉ such as homopolymer runs and simple sequence repeats (SSRs). ₁₁₀

To automatically select the best genome assembly among all candidates, the pipeline ₁₁₁ employs a weighted scoring algorithm that integrates multiple quality metrics, including ₁₁₂ chromosome circularity, number of circular contigs, number of contigs, and contiguity ₁₁₃ (N50). Each assembly is evaluated across these metrics, and an assembly score is ₁₁₄ computed as described in Listing 1. The weights assigned to each metric are provided as ₁₁₅ default values but can be customized by the user as needed. Briefly, the procedure with ₁₁₆ default weights assign a very high score to assemblies containing a putative circular ₁₁₇ chromosome, defined as a contig representing at least 90% of the expected genome size ₁₁₈ (default: 5 Mbp). Additional circular contigs contribute minor positive scores, whereas ₁₁₉ fragmented assemblies incur strong penalties in the overall score. Continuity is also ₁₂₀ rewarded, with higher N50 values receiving a proportional bonus. ₁₂₁

Following the scoring step, the pipeline generates a summary file ₁₂₂ `"chosen_best_assembly.txt"`, which lists all assemblies along with their assembly ₁₂₃ statistics and ranking from best to worst (based on their computed score). The ₁₂₄ top-ranked assembly with the highest overall weighted score is automatically selected as ₁₂₅ the final genome assembly for downstream analyses. In addition, the completeness and ₁₂₆ contamination of the top-ranked assembly are also evaluated using Checkm [26] and ₁₂₇ included in this file to assist users in assessing the final assembly quality. However, ₁₂₈ users can manually review and easily identify alternative assemblies using the detailed ₁₂₉ summary information provided in this file **(Supplementary Figure 1 and 2)**. This ₁₃₀ multi-assembler, score-based approach ensures that LoReMINE consistently produces ₁₃₁ high-quality, structurally complete genome assemblies across diverse long-read datasets. ₁₃₂

```
Assembly score = (10 * (has_circular_chromosome))          133
                + (2 * number of circular contigs)          134
                - (2 * number of contigs)                    135
                + (N50 / 1e6)                                136
```

Listing 1. Weighted scoring formula used for assembly selection.

taxonomy ₁₃₇

This submodule performs automated taxonomic classification of input genomes using ₁₃₈ the DFAST_QC tool [27]. It supports two database configurations: a compact version ₁₃₉ (<1.5 GB) optimized for fast classification on resource-limited systems, and a full ₁₄₀ version (>100 GB) that provides a comprehensive coverage across bacterial taxa. Users ₁₄₁ can select either database configuration during setup, depending on their available ₁₄₂ resources and desired classification depth. DFAST_QC utilizes both the NCBI ₁₄₃ Reference Database [28] and Genome Taxonomy Database [29] reference taxonomies to ₁₄₄ ensure consistent, reliable, and up-to-date assignments. ₁₄₅

Upon completion of taxonomic analysis, the pipeline automatically integrates the ₁₄₆ outputs from both databases and consolidates them into a single user-friendly summary ₁₄₇ file called `"identified_taxonomy.txt"` **(Supplementary Figure 3, 4, 5, and 6)**, ₁₄₈ providing a unified view of the genome's taxonomic identity and facilitating downstream ₁₄₉ comparative or diversity analyses. ₁₅₀

identify_bgcs

This submodule detects BGCs in input genomes using the antiSMASH tool [14].
antiSMASH identifies a wide range of BGC types including polyketide synthases (PKS),
nonribosomal peptide synthetases (NRPS), terpenes and others, and currently
incorporates detection rules for 101 distinct BGC types. The output of this submodule
consists of all the BGCs predicted by antiSMASH, along with their genomic locations,
BGC class assignments, and detailed annotation reports, all of which can be
interactively explored and visualized in a web browser and used as an input for
subsequent analyses within the pipeline.

bgc_clustering

This submodule is used for clustering the input BGCs to identify the gene cluster
families (GCFs) that facilitate comparative and evolutionary analyses across both small
and large-scale genomic projects. Clustering can be performed with both BiG-SLiCE
(default threshold = 0.4) [20] and BiG-SCAPE (default threshold = 0.5) [19] using
either the default or a user-defined threshold. The submodule also allows users to
include reference BGCs from the MIBiG database [18], enabling a direct comparison
between predicted and experimentally described BGCs. This integration helps to
identify novel or unique GCFs that may represent previously uncharacterized natural
product biosynthetic pathways.

   Following clustering, the pipeline generates a comprehensive summary file called
"output_clusters.tsv" for both tools, which lists all BGCs along with their assigned
GCFs, similarity scores, BGC completeness, and length of the BGCs. Additionally,
BiG-SCAPE output is provided as an interactive HTML visualization that enables users
to explore cluster networks, inspect relationships among GCFs, and intuitively assess
novelty and diversity within their dataset.

all_submodules

This submodule enables execution of the entire pipeline in a single run. It supports
both single-strain and batch-mode execution, allowing users to analyze individual
isolates or large collections of strains simultaneously. In the batch mode, the pipeline
automatically identifies the best genome assemblies for all strains, determines their
taxonomy, detects BGCs in each best identified genome assembly, and subsequently
performs clustering of identified BGCs across all strains to delineate GCFs.
Additionally, users may include MIBiG reference BGCs for the clustering step to
facilitate comparative analysis and identify which GCFs correspond to known natural
product families versus potentially novel clusters. Thus, this submodule provides a fully
automated, end-to-end solution for high-throughput microbial natural product genome
mining directly from the long-read sequencing data.

Results

To illustrate how LoReMINE facilitates microbial natural product genome mining
directly from long-read sequencing data, we applied the complete pipeline to ten
bacterial strains, comprising six novel isolates and four type strains, generated using
different long-read sequencing technologies. This use case highlights the pipeline's
end-to-end capabilities, automating assembly selection, taxonomic assignment, BGC
detection, and GCF clustering. The full workflow was executed using the
all_submodules option (Listing 2), and the outputs generated by each submodule are
presented below.

```
loremine all_submodules --batch_run input_batch_run.tsv -o        197
    loremine_output -t 32 --prefix NA --asm-coverage 200 --db_path  198
    antismash_databases/ --mibig --clustering_type both --pfam_dir  199
    PFAM_database/Pfam-A.hmm                                         200
```
Listing 2. Running LoReMINE with all_submodules.

assemble   201

The pipeline began by assembling ten strains sequenced using a mixture of PacBio CLR,   202
PacBio HiFi, and Oxford Nanopore Technologies (ONT) long-reads. Leveraging the   203
`assemble` submodule, we were able to reconstruct high-quality genomes for all strains 204
(Table 1). Nine of the ten genomes were assembled into single circular contigs, while one 205
genome yielded two circular contigs, the smaller of which, only ∼2.5 kb, may represent   206
a plasmid, mobile genetic element intermediates, phage-derived elements, or assembly   207
artifacts. All assemblies contained circular chromosomes, reflecting complete or   208
near-complete genome reconstruction. For four type strains (DK1622^T, DSM43024^T,   209
DSM43181^T, and DSM43747^T), the pipeline produced assemblies that were either   210
comparable to or improved upon previously published assemblies in the literature   211
(NCBI accessions: ASM1268v1, ASM30849v1, ASM1464805v1, and SREG). Notably,   212
the assemblies for which improvements were observed had previously been generated   213
using short-read sequencing, whereas LoReMINE leveraged long-read data, resulting in   214
increased contiguity and improved assembly quality. Further quality assessment showed   215
that each assembly exhibited over 90% completeness and less than 10% contamination,   216
confirming that the pipeline consistently produced high-quality assemblies across all   217
strains.

Strain	Type of reads	No of contigs	N50	Largest contig	Total length	Circular chromosome	Completeness	Contamination
Cma13	hifi_pacbio	1	12,630,305	12,630,305	12,630,305	Yes	92.9	5.35
MNa10913	hifi_pacbio	1	11,967,386	11,967,386	11,967,386	Yes	94.52	5.60
SBAr059	hifi_pacbio	1	13,140,567	13,140,567	13,140,567	Yes	99.35	7.71
SBCy461	hifi_pacbio	1	13,235,143	13,235,143	13,235,143	Yes	100	1.95
SBMi007	clr_pacbio	1	15,470,788	15,470,788	15,470,788	Yes	94.84	5.85
SBSr281	hifi_pacbio	1	13,358,202	13,358,202	13,358,202	Yes	96.13	6.02
DK1622^T	hifi_pacbio	1	9,140,653	9,140,653	9,140,653	Yes	99.35	1.30
DSM43024^T	ont	2	7,070,657	7,070,657	7,073,155	Yes	98.87	2.11
DSM43181^T	ont	1	8,638,736	8,638,736	8,638,736	Yes	99.82	1.9
DSM43747^T	ont	1	3,989,325	3,989,325	3,989,325	Yes	99.47	0.89

Table 1. Genome assembly statistics for all ten bacterial strains. ^{T} denotes type
strains.

taxonomy   219

Following the reconstruction of high-quality genomes, the pipeline proceeded to   220
determine the taxonomy of all ten strains. As described earlier, the `taxonomy`   221
submodule integrates classification results from both the NCBI and the GTDB reference   222
databases, enabling a comprehensive taxonomic assessment. Among the analyzed   223
genomes, six strains represent novel isolates, and for these genomes, the average   224
nucleotide identity (ANI) does not exceed the 95% threshold typically required for   225
confident species-level classification. As a result, the pipeline was unable to definitively 226
assign species-level taxonomy for each of these six strains (Table 2). Nevertheless, for 227
each strain, at least one of the two databases successfully provided a nearest   228
species-level classification, even when formal classification criteria were not met. In   229
contrast, the remaining four type strains correspond to previously described organisms   230
in the literature, and for them, ANI surpassed the 95% threshold. For these genomes,   231

the taxonomic assignments produced by the pipeline were consistent with the species annotations reported in NCBI, demonstrating the accuracy of our pipeline.

Strain	GTDB classification	NCBI classification
Cma13	*Chondromyces apiculatus* (87.8%)	None
MNa10913	*Nannocystis sp026626745* (93.1%)	*Nannocystis pusilla* (92.8%)
SBAr059	*Archangium lansinium* (91.8%)	*Archangium lansingense* (91.8%)
SBCy461	*Myxococcus caerfyrddinensis* (91%)	*Pyxidicoccus caerfyrddinensis* (91%)
SBMi007	*Minicystis rosea* (86.8%)	None
SBSr281	G037157775 sp037157815 (85.6%)	*Pendulispora albinea* (85.6%)
DK1622$^{\text{T}}$	*Myxococcus xanthus* (99.9%)	*Myxococcus xanthus* (99.9%)
DSM43024$^{\text{T}}$	*Nocardia brevicatena* (99.9%)	*Nocardia brevicatena* (99.9%)
DSM43181$^{\text{T}}$	*Streptosporangium pseudovulgare* (100%)	*Streptosporangium pseudovulgare* (100%)
DSM43747$^{\text{T}}$	*Saccharopolyspora rectivirgula* (99.9%)	*Saccharopolyspora rectivirgula* (99.9%)

Table 2. Species-level taxonomic classification of ten bacterial strains. Values shown in parentheses denote the ANI (in %) to the closest matching reference genome within each respective database. $^{\text{T}}$ denotes type strains.

identify_bgcs

To assess the biosynthetic capacity of these genomes, the pipeline proceeded to identify the BGCs for all strains. In total, 389 BGCs were detected across all strains, and only two of these were fragmented. This underscores the importance of generating high-quality, near-complete assemblies, as fragmented genomes often yield incomplete BGCs, making it very challenging to reliably link metabolites to their corresponding clusters and thereby limiting genome-guided drug discovery. SBAr059 and DSM43747$^{\text{T}}$ contain the highest and lowest number of BGCs (61 and 10), respectively (Figure 2A). Although non-ribosomal peptides (NRPs) and polyketides (PKs) have historically dominated the majority of characterized natural products [30, 31], our analysis indicates that the most abundant BGC classes detected by the pipeline are terpenes and ribosomally synthesized and post-translationally modified peptides (RiPPs) (Figure 2B). This shift is likely due to recent advancements and expanded detection rules for these biosynthetic classes in state-of-the-art BGC prediction tools [14].

bgc_clustering

To explore the biosynthetic diversity encoded within these genomes, the pipeline next clustered all predicted BGCs into gene cluster families (GCFs) using BiG-SCAPE [19] and BiG-SLiCE [20] tools. Reference clusters from the MIBiG database were also incorporated in the analysis to enable direct comparison with previously characterized natural product biosynthesis pathways. BiG-SLiCE identified a total of 368 GCFs across all strains, of which only 16 (4.3%) overlapped with MIBiG, while the remaining 352 (95.7%) were unique, previously uncharacterized families (Figure 3A). A similar trend was observed using BiG-SCAPE (Figure 3B), which detected 347 GCFs in total, with only 46 (13.3%) shared with MIBiG and 301 (86.7%) classified as novel. Importantly, several well-characterized MIBiG reference clusters, including myxochromide A, myxovirescin, myxoprincomide, ectoine, and others, were consistently clustered with their corresponding or related BGCs identified in our strains by both BiG-SLiCE and BiG-SCAPE. BiG-SCAPE additionally clustered the myxochelin A/B reference cluster with its corresponding BGC from DK1622$^{\text{T}}$. Together, these results validate the ability of our pipeline to accurately group related BGCs and highlight its

Fig 2. A) Number of BGCs predicted across each strain. **B)** Distribution of BGCs across major biosynthetic classes.

utility in distinguishing known pathways from novel ones, thereby facilitating efficient prioritization for natural product discovery.

Discussion

This work introduces LoReMINE, an end-to-end, fully automated long-read based genome mining pipeline designed to streamline microbial natural product discovery. Applying the pipeline to ten bacterial strains demonstrated its ability to generate high-quality assemblies and comprehensive biosynthetic profiles. By systematically integrating multiple state-of-the-art assemblers and employing a weighted scoring framework, LoReMINE consistently produced highly contiguous circularized genomes for all strains. This level of contiguity is particularly important for detecting modular biosynthetic systems such as large PKS and NRPS clusters, where fragmented assemblies can obscure domain architecture and disrupt functional interpretation. This often leads to inaccurate GCF assignments, and hence erroneous dereplication of the resulting natural products. Clustering of predicted BGCs alongside MIBiG reference clusters revealed that well-characterized pathways were correctly grouped together, while the majority of GCFs in these strains remain uncharacterized, highlighting both the reliability of the pipeline and the vast unexplored biosynthetic diversity in these microbial genomes. These results demonstrate the value of integrated and scalable genome mining workflows for exploring and prioritizing microbial biosynthetic diversity.

A major strength of LoReMINE lies in its flexible architecture. The pipeline supports both single-strain analysis and simultaneous batch processing of multiple strains, making it suitable for small laboratory datasets as well as large comparative genomics projects. The pipeline also produces structured outputs for each submodule, which simplifies large-scale comparative analyses and supports experimental prioritization by identifying BGCs lacking similarity to known clusters from MIBiG. Furthermore, its organism-independent design enables application across diverse microbial lineages, facilitating broad exploration of microbial secondary metabolism.

Another major advantage of LoReMINE is the automation of the entire genome mining process. Traditional genome mining approaches often rely on multiple tools and lack integrated workflows, requiring extensive manual curation and expert intervention at each step, which can lead to variable results. LoReMINE streamlines this whole

Fig 3. A) Unique and shared GCFs between the ten strains and the MIBiG database as determined by BiG-SLiCE clustering. **B**) Unique and shared GCFs between the ten strains and the MIBiG database as determined by BiG-SCAPE clustering.

process by integrating all the required tools into a single automated, end-to-end workflow, minimizing manual intervention and ensuring reproducibility and reliability across large datasets.

Overall, LoReMINE provides an integrated, scalable, and reproducible framework for high-throughput microbial genome mining, enabling systematic exploration and prioritization of biosynthetic pathways to support the discovery of new natural products across diverse microbial taxa

Conclusion

LoReMINE provides a fully automated end-to-end solution for microbial genome mining by integrating long-read genome assembly, taxonomic classification, biosynthetic gene cluster (BGC) prediction, and clustering of BGCs into gene cluster families (GCFs). By producing high-quality assemblies, the pipeline reduces the number of fragmented BGCs, enhancing confidence in further downstream analyses. Its modular design provides flexibility by allowing analyses on various scales from single strains to large datasets and making it accessible to a broad range of users. Application of LoReMINE to a diverse set of bacterial strains demonstrated its ability to uncover a wide array of largely uncharacterized BGCs, while accurately grouping known biosynthetic pathways, highlighting both the reliability of the pipeline and the considerable hidden biosynthetic diversity present in these microbial genomes. Overall, LoReMINE streamlines and standardizes genome mining workflows, enabling high-throughput, reproducible exploration of microbial secondary metabolism and supporting genomics-guided discovery of novel natural products.

Acknowledgments 317

We thank Anna-Maria Kastner for sequencing the type strains used in this study. We 318
are also grateful to Guangyi Chen for testing the pipeline and providing valuable 319
feedback on the manuscript. 320

References 321

1. Dias DA, Urban S, Roessner U. A historical overview of natural products in drug 322
   discovery. Metabolites. 2012;2(2):303–336. 323

2. Mann J. Murder, magic, and medicine. Oxford University Press; 2000. 324

3. Newman DJ, Cragg GM. Natural products as sources of new drugs over the 325
   nearly four decades from 01/1981 to 09/2019. Journal of natural products. 326
   2020;83(3):770–803. 327

4. Zhang CW, Zhong XJ, Zhao YS, Rajoka MSR, Hashmi MH, Zhai P, et al. 328
   Antifungal natural products and their derivatives: a review of their activity and 329
   mechanism of actions. Pharmacol Res-Mod Chin Med. 2023;7(100262):10–1016. 330

5. Newman D. Screening and identification of novel biologically active natural 331
   compounds. F1000Research. 2017;6:783. 332

6. Walesch S, Birkelbach J, Jézéquel G, Haeckl FJ, Hegemann JD, Hesterkamp T, 333
   et al. Fighting antibiotic resistance—strategies and (pre) clinical developments to 334
   find new antibacterials. EMBO reports. 2023;24(1):e56033. 335

7. Atanasov AG, Zotchev SB, Dirsch VM, Supuran CT. Natural products in drug 336
   discovery: advances and opportunities. Nature reviews Drug discovery. 337
   2021;20(3):200–216. 338

8. Bauman KD, Butler KS, Moore BS, Chekan JR. Genome mining methods to 339
   discover bioactive natural products. Natural product reports. 340
   2021;38(11):2100–2129. 341

9. Cimermancic P, Medema MH, Claesen J, Kurita K, Brown LCW, Mavrommatis 342
   K, et al. Insights into secondary metabolism from a global analysis of prokaryotic 343
   biosynthetic gene clusters. Cell. 2014;158(2):412–421. 344

10. Rutledge PJ, Challis GL. Discovery of microbial natural products by activation 345
    of silent biosynthetic gene clusters. Nature reviews microbiology. 346
    2015;13(8):509–523. 347

11. Gavriilidou A, Kautsar SA, Zaburannyi N, Krug D, Müller R, Medema MH, et al. 348
    Compendium of specialized metabolite biosynthetic diversity encoded in bacterial 349
    genomes. Nature microbiology. 2022;7(5):726–735. 350

12. Paoli L, Ruscheweyh HJ, Forneris CC, Hubrich F, Kautsar S, Bhushan A, et al. 351
    Biosynthetic potential of the global ocean microbiome. Nature. 352
    2022;607(7917):111–118. 353

13. van Der Hooft JJ, Mohimani H, Bauermeister A, Dorrestein PC, Duncan KR, 354
    Medema MH. Linking genomics and metabolomics to chart specialized metabolic 355
    diversity. Chemical Society Reviews. 2020;49(11):3297–3314. 356

14. Blin K, Shaw S, Vader L, Szenei J, Reitz ZL, Augustijn HE, et al. antiSMASH 8.0: extended gene cluster detection capabilities and analyses of chemistry, enzymology, and regulation<? mode pagerangestyle?>. Nucleic acids research. 2025; p. gkaf334.

15. Skinnider MA, Johnston CW, Gunabalasingam M, Merwin NJ, Kieliszek AM, MacLellan RJ, et al. Comprehensive prediction of secondary metabolite structure and biological activity from microbial genome sequences. Nature communications. 2020;11(1):6058.

16. Hannigan GD, Prihoda D, Palicka A, Soukup J, Klempir O, Rampula L, et al. A deep learning genome-mining strategy for biosynthetic gene cluster prediction. Nucleic acids research. 2019;47(18):e110–e110.

17. Blin K, Shaw S, Medema MH, Weber T. The antiSMASH database version 5. Nucleic acids research. 2026;54(D1):D522–D526.

18. Zdouc MM, Blin K, Louwen NL, Navarro J, Loureiro C, Bader CD, et al. MIBiG 4.0: advancing biosynthetic gene cluster curation through global collaboration. Nucleic acids research. 2025;53(D1):D678–D690.

19. Navarro-Muñoz JC, Selem-Mojica N, Mullowney MW, Kautsar SA, Tryon JH, Parkinson EI, et al. A computational framework to explore large-scale biosynthetic diversity. Nature chemical biology. 2020;16(1):60–68.

20. Kautsar SA, van der Hooft JJ, de Ridder D, Medema MH. BiG-SLiCE: A highly scalable tool maps the diversity of 1.2 million biosynthetic gene clusters. Gigascience. 2021;10(1):giaa154.

21. Kolmogorov M, Yuan J, Lin Y, Pevzner PA. Assembly of long, error-prone reads using repeat graphs. Nature biotechnology. 2019;37(5):540–546.

22. Cheng H, Concepcion GT, Feng X, Zhang H, Li H. Haplotype-resolved de novo assembly using phased assembly graphs with hifiasm. Nature methods. 2021;18(2):170–175.

23. PacificBiosciences. GitHub - PacificBiosciences/pbipa: Improved Phased Assembler; 2022. Available from: https://github.com/PacificBiosciences/pbipa.

24. Camacho C, Coulouris G, Avagyan V, Ma N, Papadopoulos J, Bealer K, et al. BLAST+: architecture and applications. BMC bioinformatics. 2009;10(1):421.

25. Morgulis A, Gertz EM, Schäffer AA, Agarwala R. A fast and symmetric DUST implementation to mask low-complexity DNA sequences. Journal of computational biology. 2006;13(5):1028–1040.

26. Parks DH, Imelfort M, Skennerton CT, Hugenholtz P, Tyson GW. CheckM: assessing the quality of microbial genomes recovered from isolates, single cells, and metagenomes. Genome research. 2015;25(7):1043–1055.

27. Elmanzalawi M, Fujisawa T, Mori H, Nakamura Y, Tanizawa Y. DFAST_QC: quality assessment and taxonomic identification tool for prokaryotic Genomes. BMC bioinformatics. 2025;26(1):3.

28. Federhen S. The NCBI taxonomy database. Nucleic acids research. 2012;40(D1):D136–D143.

29. Chaumeil PA, Mussig AJ, Hugenholtz P, Parks DH. GTDB-Tk: a toolkit to classify genomes with the Genome Taxonomy Database; 2020.

30. Wang H, Fewer DP, Holm L, Rouhiainen L, Sivonen K. Atlas of nonribosomal peptide and polyketide biosynthetic pathways reveals common occurrence of nonmodular enzymes. Proceedings of the National Academy of Sciences. 2014;111(25):9259–9264.

31. Fischbach MA, Walsh CT. Assembly-line enzymology for polyketide and nonribosomal peptide antibiotics: logic, machinery, and mechanisms. Chemical reviews. 2006;106(8):3468–3496.