Optimizing Protein Tokenization: Reduced Amino Acid Alphabets for Efficient and Accurate Protein Language Models

Ella Rannon[1] and David Burstein[1,*]

[1]The Shmunis School of Biomedicine and Cancer research, Tel Aviv University.

*correspondence: davidbur@tauex.tau.ac.il.

Abstract

Protein language models (pLMs) typically tokenize sequences at the single-amino-acid level using a 20-residue alphabet, resulting in long input sequences and high computational cost. Sub-word tokenization methods such as Byte Pair Encoding (BPE) can reduce sequence length but are limited by the sparsity of long patterns in proteins encoded by the standard amino acid alphabet. Reduced amino acid alphabets, which group residues by physicochemical properties, offer a potential solution but their performances with sub-word tokenization have not been systematically studied. In this work, we investigate the combined use of reduced amino acid alphabets and BPE tokenization in protein language models. We pre-train RoBERTa-based pLMs de novo using multiple reduced alphabets and evaluate them across diverse downstream tasks. Our results show that reduced alphabets enable substantially shorter input sequences and faster training and inference, while maintaining comparable - and in some cases improved - performance relative to models trained on the full 20-amino-acid alphabet. These findings demonstrate that alphabet reduction facilitates more effective sub-word tokenization and provides a favorable trade-off between efficiency and predictive accuracy.

1 Introduction

Advances in high-throughput sequencing have generated vast amounts of genomic sequence data, much of which remains unannotated (Sayers *et al.* 2025). The ability of language models (LMs) to learn complex patterns from large unlabeled corpora makes them well-suited to address this challenge (Bepler and Berger 2021; Iuchi *et al.* 2021; Ofer, Brandes and Linial 2021; Zhang *et al.* 2023; Oikonomou *et al.* 2024; Rannon and Burstein 2025). In particular, protein language models (pLMs) have demonstrated strong performance in capturing evolutionary, structural, and functional signals directly from amino acid sequences (Alley *et al.* 2019; Rao *et al.* 2019; Rives *et al.* 2021; Elnaggar *et al.* 2022; Lin *et al.* 2023).

A key design choice in pLMs is how protein sequences are segmented to basic language units called tokens (Testagrose and Boucher 2025). Many pLMs adopt character-level tokenization, treating individual amino acids as tokens (Alley *et al.* 2019; Heinzinger *et al.* 2019; Rao *et al.* 2019; Cao and Shen 2021; Rives *et al.* 2021; Lin *et al.* 2023). While this approach enables position-specific predictions and maintains a small vocabulary, it results in tokens encoding limited contextual information and long input sequences, leading to increased computational cost. Fixed-length *k*-mer tokenization (Asgari and Mofrad 2015; Kimothi *et al.* 2016) partially addresses this limitation but introduces sensitivity to insertions and deletions, severe vocabulary sparsity when utilizing a large k, and is based on the unrealistic assumption that informative sequence elements share a fixed length.

Sub-word tokenization methods, such as Byte Pair Encoding (BPE) (Sennrich, Haddow and Birch 2016), provide a flexible alternative by learning variable-length tokens from frequently co-occurring amino acid patterns. By treating protein sequences as raw symbol streams without predefined word boundaries, these methods are well-suited to biological sequences lacking linguistic structure. The resulting variable-length tokens can capture higher-order sequence features, including recurrent motifs of biological relevance, while reducing vocabulary sparsity and naturally handling unseen tokens. Sub-word tokenization has been successfully applied in several pLMs (Asgari, McHardy and Mofrad 2019; Wang *et al.* 2019; Elnaggar *et al.* 2022; Ferruz, Schmidt and Höcker 2022) and

evaluated across vocabulary sizes (Suyunu, Taylan and Özgür 2024) and downstream tasks (Dotan *et al.* 2024; Tan *et al.* 2024). Nevertheless, its effectiveness is constrained by the sparsity of long patterns in the standard 20-amino-acid alphabet.

Protein sequences can be simplified by using reduced alphabets, where each character represents a group of amino acids with shared physicochemical, functional, or structural properties (Liang et al. 2022). Reducing the amino acid alphabet can increase the frequency of longer recurring patterns with biological significance, enabling BPE to construct longer and more informative tokens. While reduced amino acid alphabets have been previously used in bioinformatics (Murphy, Wallqvist and Levy 2000; Weathers *et al.* 2004; Peterson *et al.* 2009; Ofer and Linial 2015), prior evaluations of these alphabets in pLMs focused exclusively on single-residue tokenization and reported reduced model performance (Ieremie, Ewing and Niranjan 2024). The trade-off between alphabet resolution and token length has not yet been systematically explored on biological data. Combining reduced alphabets with sub-word tokenization may enable the construction of longer tokens while preserving or even enhancing the model's ability to capture relevant biological patterns.

Here, we investigated the combined use of reduced amino acid alphabets and BPE sub-word tokenization in protein language models. We pre-trained pLMs from scratch using different sizes of reduced alphabets and evaluated their performance across diverse downstream tasks. These include classification tasks for solubility, enzymes, transporter identification, two-component systems, protein-protein interactions (PPIs), as well as regression tasks for fluorescence, optimal temperature, and stability regression. We showed that reduced alphabets improved model performance on some tasks, while substantially reducing input sequence length and runtime. Our results highlight that incorporating prior knowledge of amino acid properties through alphabet reduction is an effective strategy for improving both the efficiency and, in certain tasks, the performance of protein language models.

2   Methods

2.1   Datasets

Pre-training: The pre-training dataset comprised protein sequences from assembled metagenomic contigs across various environments from EBI's Mgnify (Mitchell *et al.* 2020), together with proteins from assembled genomes and metagenomes in the NCBI GenBank Whole Genome Sequencing (WGS) database (Sayers *et al.* 2019), after filtering out Fungi, Metazoan, and Viridiplantae (downloaded on March 14, 2020). CD-HIT (Fu *et al.* 2012) (v4.6; -g 1 -s 0.8 -c 0.8) was utilized to reduce redundancy. The independent test sets were produced as follows. For genomic data, complete proteomes were assigned to the training or test set to achieve an 80:20 protein ratio. For metagenomes, samples from each environment type were randomly split to reach an 80:20 protein ratio between the training and test sets within each environment. Pre-training was performed on a random subset of 15 million proteins from the training set.

Tokenizer training: Approximately 100,000 proteins were randomly sampled from each environment in the training set of the pre-trained model; for genomic data, only proteins from RefSeq's representative and reference genomes categories were included. This resulted in a dataset of 28,300,268 proteins. A separate tokenizer evaluation set was constructed by sampling ~25,000 proteins per environment from the pre-training test set, yielding 8,650,002 proteins.

Homology detection: Protein sequences were obtained from UniRef90 (Suzek *et al.* 2015) and family annotations from InterPro (Paysan-Lafosse *et al.* 2023) (downloaded on August 3, 2025). The smallest 10% of families were removed. For each remaining family, 15 protein pairs were randomly sampled as positive examples. An approximately equal number of negative pairs was generated by sampling proteins from different families, ensuring each family appeared in 30 total pairs. The final dataset comprised 663,900 protein pairs.

Solubility and signal peptide prediction: The solubility dataset was taken from DeepLocPro (Moreno *et al.* 2024) (v1.0), and contained 9,915 training and 1,991 test proteins. The signal peptide dataset was obtained from SignalP (Teufel *et al.* 2022) (v6.0); eukaryotic sequences were removed, resulting in 3,894 training and 1,354 test proteins. In both cases, only a binary label was used.

Enzyme, transporter, and two-component system prediction: Kyoto Encyclopedia of Genes and Genomes (KEGG) (Kanehisa and Goto 2000) orthology (KO) identifiers were assigned to the pre-training datasets using the mapping from Miller, Stern, and Burstein (2022). Briefly, proteins associated with the same KO were subclustered using mmseqs2 cluster (Steinegger and Söding 2017), and each cluster was aligned with MAFFT (Katoh *et al.* 2002) and used to construct an HMM profile (Eddy 2011) for corpus annotation (Miller, Stern and Burstein 2022). Positive labels were assigned from the KEGG BRITE hierarchies (ko01000, ko02000, and ko02022, respectively), while negative examples consisted of proteins annotated with KOs not belonging to the corresponding BRITE hierarchy. KOs were split into training, validation, and test sets in an 8:1:1 ratio based on their frequency in the data. Negative proteins were sampled to achieve a 10:1 negative-to-positive ratio. Due to the large resulting dataset size, stratified subsampling was applied, retaining 25% of the data for enzyme and transporter prediction tasks and 30% for the two-component system prediction task. To reduce redundancy and prevent potential data leakage, CD-HIT (Fu *et al.* 2012) (v4.6; -g 1 -s 0.8 -c 0.9) was applied to the combined training, validation, and test. This process resulted in 4,235,473, 4,190,082, and 1,356,528 train proteins, 510,790, 497,336, and 208,524 validation proteins, and 524,708, 526,956, and 221,995 test proteins, for the enzyme, transporter, and two-component system prediction tasks, respectively.

PPI prediction: The dataset was based on B-PPI-DB (Agassy *et al.* 2025), including *H. pylori* protein pairs that were processed as the other pairs in B-PPI-DB, totaling 162,703 training, 20,338 validation, and 20,338 test protein pairs.

Stability and Fluorescence prediction: The datasets were obtained from the TAPE benchmark (Rao *et al.* 2019) (downloaded on September 16, 2025). The stability and dataset included 53,614 and 21,446 training proteins, 2,512 and 5,362 validation proteins, and 12,851 and 27,217 test proteins, respectively.

Optimal Temperature prediction: The dataset was downloaded from BRENDA (Hauenstein *et al.* 2025) (2025.1 release, version 1). Proteins with missing labels ("−999") were removed. Sequences were clustered using MMseqs2 (Steinegger and Söding 2017) (version bad16c765aac60d84a8fde3548adbb06b34980bd; -s 7.5 -c 0.8), such that proteins with a range label were removed, and their cluster members were assigned to the test set. It resulted in 6,991 train proteins and 2,605 test proteins.

2.2   Tokenizer and Model Training

We evaluated five reduced amino acid alphabets of varying sizes based on different residue properties (Table 1). For each alphabet, a BPE tokenizer (Sennrich, Haddow and Birch 2016) was trained on the tokenizer dataset using a minimum token frequency of 2 and a vocabulary size of 5,000. A corresponding RoBERTa-based model (Liu *et al.* 2019) (termed ProtBERTa_<alphabet size>) was then pre-trained, consisting of 12 attention heads, eight hidden layers, and a hidden dimension of 768. Each model was pre-trained on a single NVIDIA RTX A6000 GPU for five epochs with a batch size of 64, gradient accumulation of 8, and a maximum sequence length of 1,026 tokens, comprised of 1024 sequence tokens and two special tokens: <s> and </s> for marking the beginning and the end of the sequence, respectively. Pre-training was carried out using the masked language modeling (MLM) objective with a masking probability of 0.15.

Table 1. The amino acid alphabets used in this study and the groups of amino acids represented in their alphabet.

Alphabet Type	Size	Amino Acid Groups
Amino Acids (Baseline)	20	A, C, D, E, F, G, H, I, K, L, M, N, P, Q, R, S, T, V, W, Y
Linclust's Alphabet	12	AST, NDB, EQZ, FY, IV, KR, LM, C, G, H, P, W
Functional Groups	8	GVALI (Simple), ST (Hydroxy), CM (sulfur-containing), FY (aromatic), WHP (heterocyclic), NQ (amine-containing), DE (acidic), KR (basic)
Polarity	4	GAVLIFWMP (non-polar), STCYNQ (polar neutral), DE (negative charge), HKR (positive charge)
Hydrophilic-Hydrophobic	2	STNKEQHDRZB (hydrophilic), AGILMVPFWCY (hydrophobic)

The pre-trained models were fine-tuned on multiple downstream classification and regression tasks. For classification, a task-specific classification head was added, consisting of a dense layer with tanh activation applied to the final hidden state of the class token (<s>), followed by a linear projection layer. Models were trained using the AdamW optimizer, cross-entropy loss with a learning rate of $5\cdot10^{-5}$ and a batch size 64, with gradient accumulation of 2. The models were trained for ten epochs, except for the PPI task, which was trained for two epochs.

For regression tasks, the output hidden states of the base model were mean-pooled and fed to a classification head, composed of a 256-dimensional linear layer with SiLU activation (Elfwing, Uchibe and Doya 2017), dropout with a rate of 0.1, and a projection layer. Models were trained using MAE loss with a learning rate of $2\cdot10^{-5}$, weight decay of 0.01, 500 warm-up steps, and a batch size of 64 for 15 epochs.

For all tasks except PPI prediction, the encoder weights were frozen to assess representation quality. In the PPI task, inputs were formatted as <s> protein1_tokens </s> </s> protein2_tokens </s>, which differs from the pre-training setup and therefore, all model parameters were fine-tuned.

2.3 Model Evaluation

The pre-trained embeddings from each ProtBERTa model were evaluated on the Diverse Genomic Embedding Benchmark (DGEB) (West-Roberts *et al.* 2024). Following the benchmark protocol, embeddings from the models' middle (layer 4) and final (layer 7) layers were assessed, and the better-performing layer was reported for each task. The DGEB score was computed as the mean performance across tasks using their pre-defined primary metrics.

Zero-shot performance was evaluated on two tasks. For homology prediction, cosine similarity was calculated on mean-pooled embeddings to classify protein pairs as homologs. For signal peptide prediction, a kNN classifier ($k = 5$) based on cosine similarity between pooled embeddings was used, with classification scores defined by the proportion of positive neighbors.

Fine-tuned regression models were evaluated using mean squared error (MSE), mean absolute error (MAE), and root mean square error (RMSE), while binary classification models were evaluated using Area Under the ROC (AUROC), Area Under the Precision-Recall curve (AUPR), precision, recall, and F1 at the threshold maximizing F1. For the two-component system prediction task, metrics were computed as weighted averages across classes. Additionally, statistical significance between ProtBERTa_20 and each alternative model was assessed using McNemar's test based on F1-optimizing predictions (or the class with maximal score for multiclass tasks).

2.4 Runtime Evaluation

Training and inference times were measured on a single NVIDIA RTX A6000 GPU. For each task, the test set was randomly subsampled ten times at multiple dataset sizes (increments of 1, 5, 10, 25, and 50), and inference runtime was recorded for the models' inference on batches of 128 sequences. Prior to measurement, models were warmed up using 100 batches of size 128. For each dataset size, mean runtime and standard error were computed across the repeats. The dataset sizes of most tasks were scaled down by a factor of 1,000, except for the solubility/optimal temperature and stability prediction tasks, which were scaled down by factors of 39 and 500, respectively.

3 Results

3.1 Tokenizer Training

In this study, we investigated the merits and trade-offs of five different amino acid representations with different abstraction levels for protein language models (Table 1). Specifically, we explored:

(1) The traditional 20-letter alphabet representing the 20 different amino acids.

(2) A 12-letter representation based on the alphabet developed for the Linclust algorithm for fast clustering of proteins (Steinegger and Söding 2018).

(3) An eight-letter representation based on the functional groups of the amino acids (Jain, Jain and Jain 2014).

(4) A four-letter representation based on amino acids polarity (Ball, Hill and Scott 2014).

(5) A two-letter representation where amino acids are split according to whether they are considered hydrophilic or hydrophobic.

We thus trained a BPE tokenizer (Sennrich, Haddow and Birch 2016) for each alphabet, resulting in different lengths of tokens (Fig. 1A, Supplementary Fig. 1) and sentences (Fig. 1B, Supplementary Fig. 2, Supplementary Table 1). As the alphabet size decreases, recurring sequence patterns become more frequent, allowing BPE to merge characters into longer tokens. Thus, smaller alphabets yield more effective sequence compression and allow models to capture a broader context. This reduces running time and memory consumption, allowing utilization of more complex models (Vaswani *et al.* 2017; Korthikanti *et al.*). We pre-trained RoBERTa, a transformer-based language model (Liu *et al.* 2019), on a large corpus of microbial proteins from genomic and metagenomic samples using each tokenizer. The models were called ProtBERTa_X, where X denotes the relevant alphabet size (2, 4, 8, 12, or 20).

Fig. 1. Properties of the BPE tokenizer trained on each amino acid alphabet. A. Average token length distribution for individual proteins. **B.** Distribution of tokenized sentence lengths (top 1% omitted for clarity).

3.2 Evaluation on the Diverse Genomic Embedding Benchmark (DGEB)

To investigate the biological signals encoded in the embedding of each ProtBERTa model, we utilized the (DGEB) (West-Roberts *et al.* 2024), a predefined embedding benchmark for biological language models. DGEB includes six different tasks across 18 curated datasets, spanning sequences from all domains of life. The benchmark comprises both nucleic acid and amino acid modalities, but given the nature of our tokenizers, we have only utilized the amino acid benchmarking tasks (detailed in Supplementary Table 2). This benchmark is based on the model's pre-trained embeddings directly, without fine-tuning.

Fig. 2. The performance of the different ProtBERTa models on primary metrics of the DGEB benchmark. The metrics descriptions are detailed in Supplementary Table 2.

The best overall DGEB benchmark score, which aggregates performance across all tasks, was achieved by ProtBERTa_12 (DGEB score of 0.35), followed closely by ProtBERTa_20 (0.347) and ProtBERTa_8 (0.309, Table 2). While ProtBERTa_12 achieved the highest aggregate score, ProtBERTa_20 was the best-performing model for the majority of individual tasks (eight out of 14, Fig. 2). In contrast, ProtBERTa_12 and ProtBERTa_4 were not the top models for any individual DGEB task.

Table 2. DGEB scores of the different ProtBERTa (PBa) models. The best performance is marked in bold.

Model	PBa_2	PBa_4	PBa_8	PBa_12	PBa_20
DGEB Score	0.225	0.259	0.309	**0.35**	0.347

3.3 Zero-Shot Prediction

3.3.1 Homology Prediction (pairwise binary classification)

We further evaluated the signals encoded in the models' embeddings by zero-shot homology prediction, where the cosine similarity of the pre-trained embeddings of pairs of proteins was used to train a model determining whether the two proteins belong to the same protein family. Even without finetuning, the classifiers based on the models' embedding performed well (Fig. 3), with ProtBERTa_20 and ProtBERTa_12 achieving F1 scores of 0.818 and 0.813, respectively. Notably, ProtBERTa_2 demonstrated an especially high recall (0.927) and might thus be useful for exploring remote homologs, when recall is preferred over precision.

Fig. 3. Zero-shot performance of the five ProtBERTa models on the task of homology detection.

3.3.2 Signal Peptide Detection (*k*-nearest neighbors)

We further assessed the models' zero-shot capabilities by training a *k*-nearest neighbors (kNN) classifier to identify signal peptides based on cosine similarity between the pre-trained embeddings. The labels of the test proteins were determined by majority vote among the $k = 5$ nearest train embeddings. ProtBERTa_20 achieved the best performance, with Prot-BERTa_12 performing comparably (Fig. 4).

Examining the tradeoff between predictive performance and sequence length compression, ProtBERTa_8 enabled substantial compression (>1.5×) with only a modest decrease in performance (Supplementary Fig. 3). McNemar's tests comparing ProtBERTa_20 to each alternative model at the F1-optimizing threshold indicated that there is no significant difference in the performance of ProtBERTa_20 and ProtBERTa_12 ($p = 0.856$), while the latter provides 1.28× compression (Supplementary Fig. 3).

Fig. 4. Performance of kNN classifiers using ProtBERTa pre-trained embeddings on the task of signal peptide classification. Left: ROC curves; right: precision–recall curves.

3.4 Finetuning ProtBERTa models

3.4.1 Classification Tasks

The ProtBERTa models were further finetuned on variety of downstream classification tasks. Specifically, the models were finetuned to predict protein solubility, identify enzymes, transporters, and two component systems, and detect protein-protein interactions (PPIs). While all the models performed well across the tasks, ProtBERTa_20 consistently exhibited the highest classification performance, while ProtBERTa_12 and Prot-BERTa_8 tended to achieve comparable performance (Fig. 5). In the solubility prediction task, where proteins were predicted as either soluble or membrane-bound, all models performed remarkably well, with Prot-BERTa_8 achieving a slightly higher AUROC and AUPR measures (Supplementary Fig. 4), and ProtBERTa_20 marginally outperforming others in maximal F1. The performances of ProtBERTa_12 and ProtBERTa_8 were not statistically different from the performance of ProtBERTa_20, while ProtBERTa_8 achieved over 1.5× input compression (Fig. 5).

For the enzyme and transporter detection tasks, ProtBERTa_20 and Prot-BERTa_12 consistently achieved the strongest overall performance. In both tasks, substantial sequence compression (>1.5× for ProtBERTa_8) was achieved with only modest performance degradation (2.5–5.5%, Fig. 5). In the two-component system multiclass task, where each protein is assigned as either a sensor, a response regulator, or neither, Prot-BERTa_12 performed comparably to ProtBERTa_20 (*p*-value of 0.356 respectively, McNemar's test), while ProtBERTa_4 achieved over 2.3× compression with less than a 4% decrease in performance (Fig. 5). In contrast, the protein–protein interaction task showed a clearer dependence on alphabet size, with performance decreasing as the alphabet was reduced. Nevertheless, ProtBERTa_8 still provided over 1.5× input compression with relatively limited performance loss (93% of ProtBERTa_20's AUPR and best F1, Fig. 5).

Fig. 5. Performance vs. sentence length compression trade-off of the different Prot-BERTa models. The compression is calculated as average_sentence_length(Prot-BERTa_x)/average_sentence_length(ProtBERTa_20), while the relative performance is calculated as best_f1(ProtBERTa_x)/best_f1(ProtBERTa_20).

3.4.2 Regression Tasks

We also explored the performance of different ProtBERTa models on regression tasks, predicting protein stability, optimal temperature, and fluorescence levels. On the protein stability prediction task, the performance improved as the alphabet size increased, with ProtBERTa_20 demonstrating the best performance with an MSE score of 0.227, and ProtBERTa_12 following closely, with an MSE score of 0.232 (Fig. 6A, Supplementary Table 2). Conversely, for the optimal temperature prediction task, model performance improves as the alphabet size decreases, with ProtBERTa_2 outperforming the other models with an MSE score of 326.25 (Fig. 6B, Supplementary Table 3). Finally, on the fluorescence prediction task, Prot-BERTa_12 outperformed all the other models, achieving an MSE score of 0.883 (Fig. 6C, Supplementary Table 4). While ProtBERTa_20 and Prot-BERTa_8 also performed relatively well.

Fig. 6. MSE scores of the five ProtBERTa models on the regression tasks. A. Protein stability prediction. **B.** Optimal protein temperature prediction. **C.** Fluorescence prediction.

3.5 Runtime Comparison

Since the input sequence length directly affects computational cost, we hypothesized that the input compression achieved by reduced-alphabet tokenization would translate to shorter training and inference time. To verify this, we compared the running time of the models on downstream biological tasks described above. We observed that the decreases in training time roughly followed the models' compression ratios. Specifically, the Prot-BERTa_4 required approximately half the training time of Prot-BERTa_20, while ProtBERTa_2 required roughly one third (Table 3).

This trend is consistent with the computational structure of transformer models, which comprise self-attention layers with $O(s^2d)$ complexity and feed-forward layers with $O(sd^2)$ complexity, where s is the sequence length and d is the hidden dimension size. Since most tokenized sequences in our datasets are shorter than 200 tokens (Fig. 1B) and the models' hidden dimension size is 768, the feed-forward layers dominate the overall computation time. As a result, runtime scales approximately linearly with input length, explaining the observed reductions in training time.

We note that, except for the PPI model, all encoder parameters were frozen during fine-tuning, with only the task-specific heads updated. In addition, the stability prediction dataset contains unusually short proteins (mean length of 43.2 amino acids), which likely accounts for the smaller-than-expected runtime differences observed for this task relative to others.

We also compared the inference time of the models according to the test set sample size. We observed that a similar trend has also occurred during the inference stage, where the models exhibited approximately the same runtime ratio across different sizes of datasets, with ProtBERTa_20 running about four times longer than ProtBERTa_2. The linear relationship between the runtime and number of sequences observed across the different tasks and models (Fig. 7).

Table 3. The relative fine-tuning training time of all the ProtBERTa models (PBa) in comparison to the baseline model, PBa_20. In brackets, the relative input size (1/compression_ratio), which correlates with the runtime. TCS: Two-Component Systems

Task	PBa_12	PBa_8	PBa_4	PBa_2
Solubility	0.8 (0.77)	0.69 (0.63)	0.51 (0.43)	0.33 (0.25)
Enzyme	0.81 (0.78)	0.67 (0.62)	0.49 (0.43)	0.32 (0.25)
Transporter	0.78 (0.78)	0.65 (0.62)	0.47 (0.43)	0.32 (0.25)
TCS	0.79 (0.78)	0.66 (0.62)	0.47 (0.43)	0.32 (0.25)
PPI	0.79 (0.78)	0.66 (0.63)	0.46 (0.43)	0.29 (0.25)
Stability	0.96 (0.8)	0.94 (0.69)	0.89 (0.52)	0.83 (0.35)
Temperature	0.78 (0.78)	0.64 (0.63)	0.43 (0.43)	0.25 (0.25)
Fluorescence	0.86 (0.76)	0.79 (0.62)	0.63 (0.42)	0.55 (0.24)

4 Conclusion

Although reduced amino acid alphabets have been widely used in bioinformatics (Murphy, Wallqvist and Levy 2000; Weathers *et al.* 2004; Peterson *et al.* 2009; Ofer and Linial 2015) and previously evaluated in the context of protein language models (Ieremie, Ewing and Niranjan 2024), they had not been combined with sub-word tokenization to improve pLM efficiency. Our results indicate that, while the full 20-amino-acid alphabet achieves the highest performance on most tasks, the models trained on the reduced alphabets have outperformed the baseline model on specific tasks (e.g., ProtBERTa_2 on optimal temperature prediction and Prot-BERTa_12 on fluorescence prediction). Notably, models trained on reduced alphabets typically incurred only minor performance loss in the

cases where they were not the best ranking, while providing considerably more substantial reductions in training and inference times.

To ensure a fair comparison, all models were pre-trained and fine-tuned using identical hyperparameters. While task-specific and model-specific hyperparameter optimization could alter performance trends and potentially reduce differences between models, we avoided this approach to better isolate the effects of alphabet reduction and the associated physico-chemical properties. Future work could explore model-specific optimization strategies as well as additional reduced alphabets.

Overall, our findings highlight the merits of combining reduced amino acid alphabets with sub-word tokenization as an effective strategy for compressing pLM input sequences, enabling more efficient training and inference while preserving biologically meaningful signals.

Fig. 7. Inference run time comparison for the five ProtBERTa models on a variety of downstream tasks. Inference time is measured as a function of the dataset size (in thousands).

Acknowledgements

We thank Asaf Zorea, Chen Agassy, Guy Shur, and Dr. Karin Mittelman for their feedback during this research.

Funding

This work has been supported by the Israel Science Foundation [grant number 355/23] and by a fellowship to ER from the Edmond J. Safra Center for Bioinformatics at Tel Aviv University.

Conflict of Interest: none declared.

Data Availability

The datasets used in this study were obtained from publicly available sources, including EMBL-EBI MGnify (https://www.ebi.ac.uk/metagenomics) and NCBI Whole Genome Shotgun (WGS) (https://www.ncbi.nlm.nih.gov/genbank/wgs). The code supporting this work is publicly available on GitHub at https://github.com/burstein-lab/BioTokenizers. The trained tokenizers and pre-trained models are available via Zenodo at https://doi.org/10.5281/zenodo.18256943 and https://doi.org/10.5281/zenodo.18257091.

References

Agassy C, Samuel B, Mayo S et al. B-PPI: A Cross-Attention Model for Large-Scale Bacterial Protein-Protein Interaction Prediction. 2025:2025.12.23.696145.

Alley EC, Khimulya G, Biswas S et al. Unified rational protein engineering with sequence-based deep representation learning. Nat Methods 2019;16:1315–22.

Asgari E, McHardy AC, Mofrad MRK. Probabilistic variable-length segmentation of protein sequences for discriminative motif discovery (DiMotif) and sequence embedding (ProtVecX). Sci Rep 2019;9:3577.

Asgari E, Mofrad MRK. Continuous Distributed Representation of Biological Sequences for Deep Proteomics and Genomics. PLOS ONE 2015;10:e0141287.

Ball DW, Hill JW, Scott RJ. 18.1: Properties of Amino Acids. The Basics of General, Organic, and Biological Chemistry. LibreTexts, 2014.

Bepler T, Berger B. Learning the protein language: Evolution, structure, and function. Cell Systems 2021;12:654-669.e3.

Cao Y, Shen Y. TALE: Transformer-based protein function Annotation with joint sequence–Label Embedding. Bioinformatics 2021;37:2825–33.

Dotan E, Jaschek G, Pupko T et al. Effect of tokenization on transformers for biological sequences. Bioinformatics 2024;40:btae196.

Eddy SR. Accelerated Profile HMM Searches. PLOS Computational Biology 2011;7:e1002195.

Elfwing S, Uchibe E, Doya K. Sigmoid-Weighted Linear Units for Neural Network Function Approximation in Reinforcement Learning. 2017, DOI: 10.48550/arXiv.1702.03118.

Elnaggar A, Heinzinger M, Dallago C et al. ProtTrans: Toward Understanding the Language of Life Through Self-Supervised Learning. IEEE Trans Pattern Anal Mach Intell 2022;44:7112–27.

Ferruz N, Schmidt S, Höcker B. ProtGPT2 is a deep unsupervised language model for protein design. Nat Commun 2022;13:4348.

Fu L, Niu B, Zhu Z et al. CD-HIT: accelerated for clustering the next-generation sequencing data. Bioinformatics 2012;28:3150–2.

Hauenstein J, Jeske L, Jäde A et al. BRENDA in 2026: a Global Core Biodata Resource for functional enzyme and metabolic data within the DSMZ Digital Diversity. Nucleic Acids Res 2025:gkaf1113.

Heinzinger M, Elnaggar A, Wang Y et al. Modeling aspects of the language of life through transfer-learning protein sequences. BMC Bioinformatics 2019;20:723.

Ieremie I, Ewing RM, Niranjan M. Protein language models meet reduced amino acid alphabets. Bioinformatics 2024;40:btae061.

Iuchi H, Matsutani T, Yamada K et al. Representation learning applications in biological sequence analysis. Computational and Structural Biotechnology Journal 2021;19:3198–208.

Jain JL, Jain S, Jain N. Proteins I - General Structure. Fundamentals of Biochemistry. 7th edn. S Chand and Company Ltd., 2014, 172.

Kanehisa M, Goto S. KEGG: Kyoto Encyclopedia of Genes and Genomes. Nucleic Acids Research 2000;28:27–30.

Katoh K, Misawa K, Kuma K et al. MAFFT: a novel method for rapid multiple sequence alignment based on fast Fourier transform. Nucleic Acids Res 2002;30:3059–66.

Kimothi D, Soni A, Biyani P et al. Distributed Representations for Biological Sequence Analysis. 2016.

Korthikanti V, Casper J, Lym S et al. REDUCING ACTIVATION RECOMPUTATION IN LARGE TRANSFORMER MODELS.

Liang Y, Yang S, Zheng L et al. Research progress of reduced amino acid alphabets in protein analysis and prediction. Computational and Structural Biotechnology Journal 2022;20:3503–10.

Lin Z, Akin H, Rao R et al. Evolutionary-scale prediction of atomic-level protein structure with a language model. Science 2023;379:1123–30.

Liu Y, Ott M, Goyal N et al. RoBERTa: A Robustly Optimized BERT Pretraining Approach. 2019, DOI: 10.48550/arXiv.1907.11692.

Miller D, Stern A, Burstein D. Deciphering microbial gene function using natural language processing. Nat Commun 2022;13:5731.

Mitchell AL, Almeida A, Beracochea M et al. MGnify: the microbiome analysis resource in 2020. Nucleic Acids Res 2020;48:D570–8.

Moreno J, Nielsen H, Winther O et al. Predicting the subcellular location of prokaryotic proteins with DeepLocPro. 2024:2024.01.04.574157.

Murphy LR, Wallqvist A, Levy RM. Simplified amino acid alphabets for protein fold recognition and implications for folding. Protein Engineering 2000;13:149–52.

Ofer D, Brandes N, Linial M. The language of proteins: NLP, machine learning & protein sequences. Computational and Structural Biotechnology Journal 2021;19:1750–8.

Ofer D, Linial M. ProFET: Feature engineering captures high-level protein functions. Bioinformatics 2015;31:3429–36.

Oikonomou ED, Karvelis P, Giannakeas N et al. How natural language processing derived techniques are used on biological data: a systematic review. Netw Model Anal Health Inform Bioinforma 2024;13:23.

Paysan-Lafosse T, Blum M, Chuguransky S et al. InterPro in 2022. Nucleic Acids Res 2023;51:D418–27.

Peterson EL, Kondev J, Theriot JA et al. Reduced amino acid alphabets exhibit an improved sensitivity and selectivity in fold assignment. Bioinformatics 2009;25:1356–62.

Rannon E, Burstein D. Leveraging Natural Language Processing to Unravel the Mystery of Life: A Review of NLP Approaches in Genomics, Transcriptomics, and Proteomics. 2025, DOI: 10.48550/arXiv.2506.02212.

Rao R, Bhattacharya N, Thomas N et al. Evaluating Protein Transfer Learning with TAPE. Advances in Neural Information Processing Systems. Vol 32. Curran Associates, Inc., 2019.

Rives A, Meier J, Sercu T et al. Biological structure and function emerge from scaling unsupervised learning to 250 million protein sequences. Proceedings of the National Academy of Sciences 2021;118:e2016239118.

Sayers EW, Cavanaugh M, Clark K et al. GenBank. Nucleic Acids Research 2019:gkz956.

Sayers EW, Cavanaugh M, Frisse L et al. GenBank 2025 update. Nucleic Acids Res 2025;53:D56–61.

Sennrich R, Haddow B, Birch A. Neural Machine Translation of Rare Words with Subword Units. In: Erk K, Smith NA (eds), Proceedings of the 54th Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers). Berlin, Germany: Association for Computational Linguistics, 2016, 1715–25.

Steinegger M, Söding J. MMseqs2 enables sensitive protein sequence searching for the analysis of massive data sets. Nat Biotechnol 2017;35:1026–8.

Steinegger M, Söding J. Clustering huge protein sequence sets in linear time. Nat Commun 2018;9:2542.

Suyunu B, Taylan E, Özgür A. Linguistic Laws Meet Protein Sequences: A Comparative Analysis of Subword Tokenization Methods. 2024, DOI: 10.48550/arXiv.2411.17669.

Suzek BE, Wang Y, Huang H et al. UniRef clusters: a comprehensive and scalable alternative for improving sequence similarity searches. Bioinformatics 2015;31:926–32.

Tan Y, Li M, Zhou Z et al. PETA: evaluating the impact of protein transfer learning with sub-word tokenization on downstream applications. J Cheminform 2024;16:92.

Testagrose C, Boucher C. Tokenization and deep learning architectures in genomics: A comprehensive review. Computational and Structural Biotechnology Journal 2025;27:3547–55.

Teufel F, Almagro Armenteros JJ, Johansen AR et al. SignalP 6.0 predicts all five types of signal peptides using protein language models. Nat Biotechnol 2022;40:1023–5.

Vaswani A, Shazeer N, Parmar N et al. Attention Is All You Need. 2017, DOI: 10.48550/arXiv.1706.03762.

Wang Y, You Z-H, Yang S et al. A High Efficient Biological Language Model for Predicting Protein–Protein Interactions. Cells 2019;8:122.

Weathers EA, Paulaitis ME, Woolf TB et al. Reduced amino acid alphabet is sufficient to accurately recognize intrinsically disordered protein. FEBS Letters 2004;576:348–52.

West-Roberts J, Kravitz J, Jha N et al. Diverse Genomic Embedding Benchmark for functional evaluation across the tree of life. 2024:2024.07.10.602933.

Zhang S, Fan R, Liu Y et al. Applications of transformer-based language models in bioinformatics: a survey. Bioinformatics Advances 2023;3:vbad001.