A Reproducible Methodology for High-Resolution 3D and Orthomosaic Mapping in Forested

Streams

Baptiste Nelaton [1,2*], Eric Harvey [2,3], Katrine Turgeon [1,2]

[1] Université du Québec en Outaouais (UQO), Natural Sciences Department, 58, Rue Principale,

Ripon, Québec, Canada, J0V 1V0

[2] Groupe de Recherche Interuniversitaire en Limnologie (GRIL), Université de Montréal

C.P. 6128, Succursale Centre-Ville, Montréal, Québec, Canada, H3C 3J7

[3] Centre de Recherche sur les Interactions Bassins-Versants, Écosystèmes Aquatiques (RIVE)

Université du Québec à Trois-Rivières (UQTR), 3351, boulevard des Forges, Trois-Rivières,

Québec, Canada, G8Z 4M3

* Corresponding author E-mail address: nelb01@uqo.ca / nelaton.baptiste@gmail.com

Abstract

1 - Frequent, fine-scale assessments of forested stream morphology are essential for understanding habitat conditions and guiding management, yet dense canopy and budget constraints often limit airborne LiDAR and conventional surveys.

2 - We present a reproducible, ground-based photogrammetry workflow using a chest-mounted action camera (GoPro) and the Agisoft Metashape software to generate scaled, georeferenced 3D models and orthomosaics of stream reaches. The workflow details image acquisition under variable lighting and flow conditions, image alignment, dense cloud/mesh generation, and export of GIS-ready products.

3 - Applied in Mont-Tremblant National Park and Kenauk Nature (Québec, Canada) across 56 forest-stream reaches in a single summer field season, the workflow produced scaled, GIS-ready orthomosaics with nominal pixel sizes as low as ~1.36 mm/pixel. These products captured fine-scale channel morphology, enabling consistent reach-scale habitat mapping and temporal comparisons for restoration monitoring.

4 - By reducing equipment costs and simplifying logistics relative to airborne or terrestrial LiDAR, this practical tool enables frequent, high-resolution surveys in dense-canopy streams. Future extensions (e.g., automated substrate classification via machine learning) can further standardize habitat assessment and support long-term ecological monitoring.

Keywords: ground-based photogrammetry, structure-from-motion (SfM), forested streams, action camera, orthomosaic, 3D point cloud, habitat complexity, stream restoration

Introduction

Because of their high sensitivity to perturbations, forest streams are among the first ecosystems to respond to climate change. While water quality and trophic interactions undoubtedly influence the health and productivity of aquatic environments (Patil, 2023; Su et al., 2021; Zhao et al., 2019), the physical dimension of a stream (*e.g.*, bank morphology, bed structure, substrate composition and heterogeneity) is a major determinant of streams' ability to sustain biological communities and is key to their resilience to disturbances (Heatherly et al., 2007; Mažeika et al., 2004; Rabeni, 2000).

Although stream management and assessment often prioritize biological indicators, these indicators can be highly heterogeneous, context-dependent (*e.g.,* season), and sometimes insensitive to short-term change (Gillmann et al., 2023; Brettschneider et al., 2023; Poppe et al., 2016). Quantifying habitat heterogeneity at the reach scale provides a robust and complementary indicator of habitat quality. Understanding the physical dimension and dynamics of streams across multiple scales can inform management strategies, guide conservation efforts, and evaluate restoration programs.

Forested streams are often hard to access and survey, which increases the need for accurate, lightweight, and adaptable methods to characterize complex and heterogeneous ecosystems. Precisely describing forest-stream habitats therefore requires approaches that produce fine-scale, spatially explicit, and reliable data.

In this context, the acquisition of spatially explicit, high-resolution data has emerged as a key to unravelling the inherent complexity of fluvial systems (Bertin et al., 2015; Hodge et al., 2009). Although approaches to characterize and map river physical attributes exist (Dawson et al., 2024;

Dietrich, 2016; Legleiter, 2012; Thoms et al., 2018), they remain underutilized for several reasons.

First, they are often described as cumbersome to implement (Dawson et al., 2024; Zhou et al.,

2023). Second, they have not kept pace with the increasingly precise surveying tools that have

emerged over the past few decades (*e.g.,* drones equipped with high-resolution RGB or

multispectral cameras, RTK-GPS systems, LiDAR technologies, and photogrammetric

techniques). Finally, the lack of standardized protocols hinders the development of reliable,

reproducible diagnostics for both scientific research and ecosystem management.

Photogrammetry, particularly Structure-from-Motion (SfM; estimating 3D structure from a set of

2D images; Eltner & Sofia, 2020), has emerged as a non-invasive, flexible, and affordable solution

for acquiring detailed 3D data (Carrivick & Smith, 2019; Leduc et al., 2019; Marteau et al., 2017).

SfM leverages overlapping images taken from multiple viewpoints to reconstruct the 3D geometry

of a scene without prior knowledge of the camera's position or orientation. While this approach

has proven valuable in various contexts by providing cost-effective high-resolution digital

elevation models (DEMs) and 3D models (Westoby et al., 2012), its applications in forested

streams remain largely unexplored.

Purpose of the methodological note

In this methodological note, we present a detailed and replicable protocol for using a chest-

mounted GoPro Hero© action camera and Agisoft Metashape photogrammetry software (version

2.0.2) to generate scaled, georeferenced 3D models and orthomosaics of stream reaches.

We first outline the step-by-step procedure for image acquisition to ensure consistent coverage and

overlap, even under challenging field conditions. We then describe the image processing workflow

in Metashape, from initial photo alignment to the production of a final 3D model and orthomosaic.

To demonstrate the approach in practice, we present a case study using data collected from forested

streams in Mont-Tremblant National Park (Québec, Canada), which illustrates the accuracy and

ecological relevance of our results (see Supplementary Material for full details). Finally, we

discuss the potential applications of these 3D datasets and the advantages and limitations of the

proposed method. By offering practical guidance and highlighting key considerations, we aim to

facilitate broader adoption of this approach among researchers and environmental managers

seeking refined assessments of stream physical structure and habitat complexity.

Materials and Methods

1. Study area and field conditions

The method described is primarily intended for wadeable forested streams, those with dense

riparian vegetation, variable channel morphology, and a diverse substrate composition. In practice,

this typically includes stream reaches with an average depth of up to 1 m, ensuring safe,

manageable conditions for the operator to walk within the channel.

While the approach can be adapted to a range of environmental settings, certain conditions improve

data quality and ease of implementation. These include near-baseflow conditions (i.e., low and

stable discharge and water level during image acquisition), sufficient ambient light, and favourable

weather (e.g., no rain), as well as conditions that minimize turbidity. Although not strictly required,

these conditions help produce clearer imagery, improve image alignment, and yield more reliable

3D reconstructions. In suboptimal conditions, such as partially overcast skies or slightly elevated

turbidity, data acquisition remains feasible, albeit potentially requiring additional image filtering

or processing.

2. Equipment used

Action Camera

While a variety of action cameras can be used (e.g., DJI Osmo Action 5 Pro©, Insta360 Ace©, Akaso Brave 8©), we used a recent-generation GoPro Hero©. These cameras offer an ultra-wide-angle mode that reduces the number of photographs needed for comprehensive coverage, thereby streamlining data collection. An additional advantage of newer action camera models is the recording of GPS coordinates for each image, which facilitates approximate georeferencing and simplifies subsequent integration of the resulting models into Geographic Information Systems (GIS) platforms.

A pole extension can optionally be used to raise the camera above the water surface, which may improve the field of view and image overlap; however, it is not required for successful reconstructions, and the workflow performs well without it. If the channel and banks lack distinctive topographic features, recognizable objects (e.g., artificial targets or markers printed on paper) can serve as tie points (see Supporting Information, Fig. S1). These easily identifiable markers help ensure accurate image alignment and improve the robustness of the 3D reconstruction.

Software

For data processing, we used Agisoft Metashape (v.2.0.2; Agisoft LLC). Several commercial and free alternatives to Agisoft Metashape include RealityCapture (commercial), Pix4Dmapper (drone-focused; commercial), 3DF Zephyr (commercial), and Meshroom (free). These tools (list not exhaustive) offer comparable 3D reconstruction, orthomosaic, and mesh generation capabilities for mapping and modeling but we did not test them. While the Standard Edition of

Metashape is sufficient for most SfM workflows, it requires additional steps to produce

orthomosaics. The Professional Edition streamlines orthomosaic generation and enhances overall

accuracy. Complementary software, such as any GIS platform, can be used in conjunction with

Metashape Standard Edition to create orthomosaics and further analyze georeferenced outputs.

Processing did not require a high-end workstation; we successfully ran the workflow on a standard

laptop, with runtimes depending primarily on image count and dense-cloud quality settings.

3. Field data collection protocol

Image Acquisition Methodology

The data collection protocol involves walking in the stream (in-channel) along a predefined stream

reach and capturing images at regular intervals. Starting from the upstream end, the operator moves

downstream, taking a photograph approximately every meter. After reaching the downstream limit,

the operator retraces the route back upstream, repeating the photography process at the same

intervals. This bidirectional approach increases image overlap and improves the robustness of the

3D reconstruction.

152   3. **Data Processing with Metashape**

153   Figure 1 summarizes the six main steps of the data processing approach. The complete and

154   detailed methodology, including specific parameters and settings, is provided in the

155   Supplementary Material (see Supporting Information, Fig. S. 1).

Figure 1: Overview of the photogrammetric workflow used for stream 3D modeling, from image alignment to GIS-based analysis. Detailed processing parameters are provided in Supplementary Material.

Results

Using ground-level imagery, we produced a high-resolution 3D model and an associated orthomosaic (see Fig. 2 for an example). The final reconstruction achieved a ground sampling distance (GSD) of approximately 1.3 mm/pixel, enabling detailed visualization of channel morphology, substrate composition and heterogeneity, and microhabitat features. Because no independent accuracy assessment was conducted, the reported GSD reflects image resolution rather than absolute positional accuracy. For the Fig. 2 example, field image acquisition required ~30 minutes, and end-to-end processing on a standard laptop (MacBook, Apple M1) was typically on the order of ~1 hour for Steps 1–5 (Appendix S2 for full details). We deployed the workflow at scale across 56 wadeable forest-stream reaches during a single summer field season, demonstrating that the protocol can be implemented as a routine monitoring tool.

Figure 2 : Photogrammetric reconstruction of a forest stream reach using close-range image acquisition. (a) Oblique 3D view of the textured mesh model generated in Agisoft Metashape, showing both the channel and streambank vegetation in high detail (1,067,056 faces, 538,208 vertices). (b) Top-down orthographic view of the same model, providing a scaled orthomosaic suitable for manual mapping of microhabitats and geomorphic units. (c) Close-up view of the orthomosaic at full resolution, illustrating the level of detail available for substrate identification and manual delineation.

Discussion

Potential Ecological Interpretations

One of the key strengths of this high-resolution photogrammetry lies in its ability to capture fine-scale features essential to stream ecology. By accurately mapping streambed topography, substrate composition, and physical structures, researchers and managers can derive valuable information from habitat conditions that support aquatic biota at scales relevant to organisms' perception (e.g., macroinvertebrates to fish). Several key ecological applications include:

Habitat characterisation

High-resolution 3-D models generated through photogrammetry provide a richly detailed visual representation of the channel bed, micro-habitats, roughness elements and in-stream refuges (See Supporting Information S.3, Fig. S.2 for an example of stream habitat characterization). Those microhabitats are vital for biodiversity, from diatoms, benthic invertebrates to fish (Nemes-Kókai et al., 2024; Taira et al., 2024; Zhu et al., 2023). At the same time, small-scale roughness elements such as pebbles, cobbles, root wads, and dead wood influence flow patterns and shear stress, shaping micro-habitats heterogeneity across the channel (Wen et al., 2022).

Because this approach is essentially image based it yields only an indirect (i.e., qualitative) quantification of some habitat variables such as water depth, flow velocity and precise substrate type. These variables cannot be extracted automatically from the model itself (at least for now).

Quantification of Large Dead Wood (LDW)

Large dead wood significantly influences channel structure, nutrient cycling, and habitat heterogeneity (Cordova et al., 2007). Photogrammetry enables detailed surveys of the size,

orientation, and distribution of large dead wood, which can be used to assess its role in forming

pools, sorting substrates, and providing cover for aquatic organisms (Andrus et al., 1988; Gurnell

et al., 1995).

Temporal and Spatial Comparisons

Because photogrammetry datasets are geographically referenced and archived, they can be

revisited and compared over time (Gracchi et al., 2021), allowing for longitudinal studies of

channel evolution, restoration success, and ecological changes in response to natural events (e.g.,

floods) or management actions (e.g., LDW enhancement, bank stabilization projects).

Integration with Other Ecological and Hydrological Datasets

Once a high-resolution 3D model is generated, it can be combined with other layers of information

(Lane et al., 2020) such as fish population data, invertebrate surveys, or riparian vegetation indices

to elucidate how physical habitat correlates with biological communities. Additionally, coupling

these models with hydraulic simulations (Chen et al., 2019) can identify spatial patterns of flow

refugia, spawning habitat, and other ecologically critical areas.

211 Methodological Advantages

The presented photogrammetric approach offers several key benefits, making it both accessible

and practical for a wide range of end-users, including watershed organizations, governance and

national park managers, and academic researchers.

1. Ease of Field Implementation:

Unlike aerial surveys requiring drones or manned aircraft, this ground-based method relies on

minimal equipment and training; a chest-mounted action camera and basic field gear. Its simplicity

reduces logistical barriers and ensures that non-specialists can readily adopt the technique. This

accessibility expands the potential user base and promotes wider application in both management

and research contexts.

2. Cost-Effectiveness and Time Savings:

Compared to LiDAR campaigns or traditional topographic surveys, the presented approach

requires substantially fewer resources. Equipment costs are much lower, and field surveys can be

completed more rapidly. By streamlining data collection and processing, practitioners can allocate

resources efficiently, enabling more frequent monitoring and evaluation of stream conditions.

Moreover, this method provides objective and precise spatial data compared to subjective visual

estimations, which are often prone to observer bias and inconsistencies. As a result, the technique

supports accurate assessments and reliable decision-making.

3. Reproducibility and Long-Term Data Archiving:

The method yields spatially explicit, high-resolution datasets that can be easily stored, archived,

and revisited over time. This reproducibility facilitates comparative analyses and ensures that high-

quality, interpretable visual records are maintained for future reference. As a result, the technique

not only supports current management and research objectives but also contributes valuable

baseline information for long-term environmental assessments.

Limitations and Constraints

Despite its clear advantages, the method also faces challenges that may affect data quality and

overall usability. First, the stream reach must be safely accessible on foot so that the operator can

walk both downstream and upstream while capturing photographs; steep, densely vegetated or

hazardous channels may therefore be excluded from analysis. Uneven illumination, strong

contrasts, and shadows cast by dense forest canopies can reduce image clarity and complicate point

matching, potentially leading to gaps or inconsistencies in the 3D reconstruction. Deep, swift-

flowing sections or streambeds with homogeneously colored and textured substrates (e.g., uniform,

low-lying green vegetation) pose difficulties for the photogrammetric algorithms. Such conditions

may result in fewer discernible features for tie point extraction, diminishing the quality of the

model. Overhanging branches and dense riparian vegetation can limit the camera's line of sight,

obstructing views of the streambed. In some cases, minimal clearing may be required to ensure

adequate visibility of critical features. While Metashape and modern action cameras offer internal

correction routines, residual lens distortions or rolling shutter effects may still occur. Additional

calibration steps or the use of carefully selected camera settings can mitigate these distortions, but

they remain a potential source of error.

Conclusion

This methodological note presents a reliable, reproducible protocol for generating scaled and

georeferenced 3D models, as well as orthomosaics, of forested stream reaches using ground-based

photogrammetry. The resulting high-resolution datasets, combining precise topographic

information and advanced modeling techniques, capture the inherent complexity of these

environments and thereby enhance our ability to predict and understand hydrological and

ecological dynamics. Such detailed spatial information holds significant value not only for aquatic

ecology research but also for environmental management, habitat conservation, and long-term

restoration efforts. As these methodologies continue to evolve, their integration into long-term

ecological monitoring programs promises even greater insights into the temporal variability of

stream processes and the effectiveness of management interventions over time.

Acknowledgments.

We thank the Parc national du Mont-Tremblant (Sépaq) and Kenauk Nature for site access, logistics, and permits. We are grateful to Gabriel Marcoux-Huard and Mateusz Eugenio-Babinski for insightful field discussions that informed the development of the characterization protocol, for assistance with pilot surveys and initial processing/analyses in Agisoft Metashape. We thank François Degiorgi (Université de Franche-Comté), who introduced us to the IAM habitat characterization method. This work builds directly on that foundation and shaped our thinking on the importance of habitat in stream ecology. We also thank the Groupe de Recherche Interuniversitaire en Limnologie (GRIL) for financial support.

Author contributions

Baptiste Nelaton, Katrine Turgeon, and Éric Harvey conceived the study. Baptiste Nelaton developed the methodology, conducted fieldwork, performed the analyses, and prepared the visualizations. Katrine Turgeon and Éric Harvey supervised the project and secured resources/funding. Baptiste Nelaton drafted the manuscript; all authors revised it critically and approved the final version.

Conflict of interest

The authors declare no conflict of interest.

Bibliography

Agisoft LLC (2024) Metashape Professional, version 2.0. Agisoft LLC, St. Petersburg, Russia. Available at: https://www.agisoftmetashape.com

Andrus, C. W., Long, B. A., & Froehlich, H. A. (1988). Woody Debris and Its Contribution to Pool Formation in a Coastal Stream 50 Years after Logging. *Canadian Journal of Fisheries and Aquatic Sciences*, *45*(12), 2080–2086. https://doi.org/10.1139/f88-242

Bertin, S., Friedrich, H., Delmas, P., Chan, E., & Gimel'farb, G. (2015). Digital stereo photogrammetry for grain-scale monitoring of fluvial surfaces: Error evaluation and workflow optimisation. *ISPRS Journal of Photogrammetry and Remote Sensing*, *101*, 193–208. https://doi.org/10.1016/j.isprsjprs.2014.12.019

Carrivick, J. L., & Smith, M. W. (2019). Fluvial and aquatic applications of Structure from Motion photogrammetry and unmanned aerial vehicle/drone technology. *WIREs Water*, *6*(1), e1328. https://doi.org/10.1002/wat2.1328

Chen, Y., DiBiase, R. A., McCarroll, N., & Liu, X. (2019). Quantifying flow resistance in mountain streams using computational fluid dynamics modeling over structure-from-motion photogrammetry-derived microtopography. *Earth Surface Processes and Landforms*, *44*(10), 1973–1987. https://doi.org/10.1002/esp.4624

Cordova, J. M., Rosi-Marshall, E. J., Yamamuro, A. M., & Lamberti, G. A. (2007). Quantity, controls and functions of large woody debris in Midwestern USA streams. *River Research and Applications*, *23*(1), 21–33. https://doi.org/10.1002/rra.963

Dawson, C., Ashmore, P., & Corry, R. (2024). Evaluating river morphology change with a
geomorphic form variation approach. *Earth Surface Processes and Landforms*, *49*(2), 855–
874. https://doi.org/10.1002/esp.5744

Dietrich, J. T. (2016). Riverscape mapping with helicopter-based Structure-from-Motion
photogrammetry. *Geomorphology*, *252*, 144–157.
https://doi.org/10.1016/j.geomorph.2015.05.008

Eltner, A., & Sofia, G. (2020). Structure from motion photogrammetric technique. In
Developments in Earth Surface Processes (Vol. 23, pp. 1–24). Elsevier.
https://doi.org/10.1016/B978-0-444-64177-9.00001-1

Gracchi, T., Rossi, G., Tacconi Stefanelli, C., Tanteri, L., Pozzani, R., & Moretti, S. (2021).
Tracking the Evolution of Riverbed Morphology on the Basis of UAV Photogrammetry.
Remote Sensing, *13*(4), 829. https://doi.org/10.3390/rs13040829

Gurnell, A. M., Gregory, K. J., & Petts, G. E. (1995). The role of coarse woody debris in forest
aquatic habitats: Implications for management. *Aquatic Conservation: Marine and*
Freshwater Ecosystems, *5*(2), 143–166. https://doi.org/10.1002/aqc.3270050206

Heatherly, T., Whiles, M. R., Royer, T. V., & David, M. B. (2007). Relationships between Water
Quality, Habitat Quality, and Macroinvertebrate Assemblages in Illinois Streams. *Journal*
of Environmental Quality, *36*(6), 1653–1660. https://doi.org/10.2134/jeq2006.0521

Hodge, R., Brasington, J., & Richards, K. (2009). *In situ* characterization of grain-scale fluvial
morphology using Terrestrial Laser Scanning. *Earth Surface Processes and Landforms*,
34(7), 954–968. https://doi.org/10.1002/esp.1780

Lane, S. N., Gentile, A., & Goldenschue, L. (2020). Combining UAV-Based SfM-MVS
Photogrammetry with Conventional Monitoring to Set Environmental Flows: Modifying

Dam Flushing Flows to Improve Alpine Stream Habitat. *Remote Sensing*, *12*(23), 3868. https://doi.org/10.3390/rs12233868

Leduc, P., Peirce, S., & Ashmore, P. (2019). Short communication: Challenges and applications of structure-from-motion photogrammetry in a physical model of a braided river. *Earth Surface Dynamics*, *7*(1), 97–106. https://doi.org/10.5194/esurf-7-97-2019

Legleiter, C. J. (2012). Remote measurement of river morphology via fusion of LiDAR topography and spectrally based bathymetry. *Earth Surface Processes and Landforms*, *37*(5), 499–518. https://doi.org/10.1002/esp.2262

Marteau, B., Vericat, D., Gibbins, C., Batalla, R. J., & Green, D. R. (2017). Application of Structure-from-Motion photogrammetry to river restoration. *Earth Surface Processes and Landforms*, *42*(3), 503–515. https://doi.org/10.1002/esp.4086

Mažeika, S., Sullivan, P., Watzin, M. C., & Hession, W. C. (2004). Understanding Stream Geomorphic State in Relation to Ecological Integrity: Evidence Using Habitat Assessments and Macroinvertebrates. *Environmental Management*, *34*(5), 669–683. https://doi.org/10.1007/s00267-004-4032-8

Nemes-Kókai, Z., Borics, G., Csépes, E., Lukács, Á., Török, P., T-Krasznai, E., Bácsi, I., & B-Béres, V. (2024). Role of microhabitats in shaping diversity of periphytic diatom assemblages. *Hydrobiologia*, *851*(4), 959–972. https://doi.org/10.1007/s10750-023-05336-x

Patil, S. B. (2023). Evaluation of Physico-chemical parameters in relation to fish production of Bhima River, M.S., India. *Ecology, Environment and Conservation*, *29*(03), 1421–1424. https://doi.org/10.53550/EEC.2023.v29i03.063

Rabeni, C. F. (2000). Evaluating physical habitat integrity in relation to the biological potential of streams. *Hydrobiologia*, *422/423*, 245–256. https://doi.org/10.1023/A:1017022300825

Su, H., Feng, Y., Chen, J., Chen, J., Ma, S., Fang, J., & Xie, P. (2021). Determinants of trophic cascade strength in freshwater ecosystems: A global analysis. *Ecology*, *102*(7), e03370. https://doi.org/10.1002/ecy.3370

Taira, D., Mark, R. Y. Y., Hsiung, A. R., Jaafar, Z., & Todd, P. A. (2024). Fish responses to manipulated microhabitat complexity in urbanised shorelines. *Journal of Applied Ecology*, *61*(5), 1095–1108. https://doi.org/10.1111/1365-2664.14644

Thoms, M., Scown, M., & Flotemersch, J. (2018). Characterization of River Networks: A GIS Approach and Its Applications. *JAWRA Journal of the American Water Resources Association*, *54*(4), 899–913. https://doi.org/10.1111/1752-1688.12649

Wen, J., Chen, Y., Liu, Z., & Li, M. (2022). Numerical Study on the Shear Stress Characteristics of Open-Channel Flow over Rough Beds. *Water*, *14*(11), 1752. https://doi.org/10.3390/w14111752

Westoby, M. J., Brasington, J., Glasser, N. F., Hambrey, M. J., & Reynolds, J. M. (2012). 'Structure-from-Motion' photogrammetry: A low-cost, effective tool for geoscience applications. *Geomorphology*, *179*, 300–314. https://doi.org/10.1016/j.geomorph.2012.08.021

Zhao, C. S., Yang, Y., Yang, S. T., Xiang, H., Wang, F., Chen, X., Zhang, H. M., & Yu, Q. (2019). Impact of spatial variations in water quality and hydrological factors on the food-web structure in urban aquatic environments. *Water Research*, *153*, 121–133. https://doi.org/10.1016/j.watres.2019.01.015

Zhou, N., Sheng, S., He, L.-Y., Tian, B.-R., Chen, H., & Xu, C.-Y. (2023). An Integrated Approach

for Analyzing the Morphological Evolution of the Lower Reaches of the Minjiang River

Based on Long-Term Remote Sensing Data. *Remote Sensing*, *15*(12), 3093.

https://doi.org/10.3390/rs15123093

Zhu, P., Pan, B., Li, Z., He, H., Hou, Y., & Zhao, G. (2023). Responses of biodiversity to

microhabitat heterogeneity in debris flow gullies: Assessing the impact of hydrological

disturbance. *Science of The Total Environment*, *902*, 166509.

https://doi.org/10.1016/j.scitotenv.2023.166509

SUPPORTING INFORMATION

Appendix S1. Ground-control targets and placement along the reach (field photo)

Fig S1: Ground-control targets (GCPs) placed along a stream reach to aid image alignment and georeferencing in close-range

photogrammetry.

 SUPPORTING INFORMATION

 Appendix S2. Detailed workflow: a step-by-step guide to ground-based photogrammetry of

 forested streams (Agisoft Metashape)

1 - Data Processing with Metashape

Step 1: Setting Up the Project (~10min)

1. **Open Agisoft Metashape :**

o Launch the software on your computer.

2. **Add Photos:**

o Go to **Workflow > Add Photos**.

o Select all the images captured with the action camera.

o Click **Open** to import the images into the project.

3. **Set the Coordinate System:**

o If your images include georeferencing information or you are working in a known

397   coordinate system, select it under **Reference Settings**.

398   o For data from Quebec, consider using an appropriate projected coordinate system

399   such as **NAD83 / Quebec Lambert** (EPSG:32198) if it suits your study area.

400 **Step 2: Aligning the Photos (~15 min)**

401   1. **Photo Alignment Settings:**

402   o Go to **Workflow > Align Photos**.

403   o   Under **Accuracy**, select **High** (a good balance between processing time and

404   accuracy; choose **Highest** if you have a powerful machine and want the best

405   possible alignment).

406   o   **Key point limit:** Set this to around **80,000** to ensure sufficient feature detection.

407   o   **Tie point limit:** Set this to about **4,000** to maintain a manageable number of tie

408   points without overwhelming the project.

409   These settings typically provide a good balance: the key point limit is high enough to capture fine

410   details of the stream bed and banks, while the tie point limit helps control for noise and reduce

411   processing overhead.

412   2. **Start the Alignment:**

413   o   Click **OK** to begin photo alignment.

414   o   Wait for the alignment process to complete. Depending on the number of photos

415   and system performance, this step may take approximately 10–20 minutes.

416   **Step 3: Building the Point Cloud (~30 min)**

417   1. **Build Point Cloud:**

418   o   Go to **Workflow > Build Point Cloud**.

419   o   Choose a **Quality** setting. We recommend **Medium** quality for a reasonable trade-

420   off between processing speed and detail. Higher settings (e.g., High) offer more

421   detail but significantly increase computation time.

422   o   **Depth Filtering:** Select **Mild** depth filtering. This setting usually strikes a good

423   balance between smoothing out noise and retaining important details in complex

424   stream environments.

425   2. **Run the Process:**

426   o   Click **OK** to start building the Point cloud.

427   o   Allow the process to complete. Processing times vary based on image count and

428   computer performance.

429   3. **Save the Project:**

430   o   Go to **File > Save As**.

431   o   Name your project (e.g., "DSM_Model") and click **Save**.

432 **Step 4: Building the Textured Model (~15 min)**

433   1. **Build Mesh (if desired):**

434   o   **Workflow > Build Mesh**

435   o   Use the Point Cloud as the source.

436   o   Select a **Face Count** (e.g., Medium) to produce a detailed yet manageable mesh.

437   2. **Build Texture:**

438   o   **Workflow > Build Texture**

439   o   Use default settings or adjust as necessary for better texture quality.

440   o   Click **OK** to generate the textured model.

Step 5: Creating the Orthomosaic (~10 min)

1. **Build Orthomosaic:**

   o Go to **Workflow > Build Orthomosaic**.

   o If you have georeferenced images or GCPs, choose the appropriate **Projection** (e.g., NAD83 / Quebec Lambert).

   o If no georeferencing is available, select a **Planar** projection (Top XY) to generate a relative (non-georeferenced) orthomosaic.

2. **Start the Process:**

   o Click **OK** to begin.

   o Wait for the orthomosaic generation to complete.

3. **Complete and Save:**

   o Once finished, **File > Export Orthomosaic** to your preferred format and location.

Always use a coordinate system appropriate for your region and data sources to ensure better accuracy in analyses. Higher-quality settings (Highest accuracy, High dense cloud) demand more processing power and time. If your hardware is limited, opt for lower-quality settings. If initial results are unsatisfactory, consider adding artificial targets, adjusting camera angles, or using different key/tie point limits to improve alignment and reconstruction quality.

SUPPORTING INFORMATION

Appendix S3. Integrating close-range photogrammetry with morphodynamic habitat

assessment in a forested stream.

Because this approach is essentially image based (the analyst inspects the orthomosaic or shaded-

relief model on screen and traces the boundaries by hand) it yields only an indirect (i.e., qualitative)

quantification of habitat heterogeneity: depth, flow velocity and substrate type cannot be extracted

automatically from the model itself (at least, not for now).

Nevertheless, when photogrammetric mapping is coupled with complementary field protocols,

such as the Indice d'Attractivité Morphodynamique (IAM; Degiorgi et al. 2002), which scores

habitat quality from the diversity and attractiveness of depth, velocity and substrate classes for

fish, the spatial precision of those indicators is greatly improved. The high-resolution polygons

produced in the GIS can be overlaid on IAM survey points to refine class boundaries, verify

transitions between sequences like run - riffles - pools, and ensure that coarse elements (pebbles,

cobbles, root wads, woody debris) that influence shear stress are properly accounted for (see

example figure).

In this way, photogrammetry transforms a point-based field index into a spatially explicit map,

enhancing our ability to identify reaches that would benefit from added cover or structural

enhancement and to design interventions that maintain (or restore) habitat complexity and

ecological resilience.

Figure S.3 : Workflow for combining photogrammetric mapping with morphodynamic habitat assessment (IAM protocol) in a forested stream. Up: Orthomosaic generated from close-range photogrammetry, providing a high-resolution aerial view of the stream reach. Middle: Delineation of channel contours and boundaries in a Geographic Information System (GIS) environment based on the orthomosaic. Down: Integration of photogrammetric data and field-based IAM (Indice d'Attractivité Morphodynamique) protocol to map fish habitat attraction zones. Each polygon represents a spatial unit classified by combinations of depth, flow velocity, and substrate characteristics relevant to fish habitat suitability.