ARGformer: learning on ancestral recombination graphs with transformers

David Bonet[1,2,3]**, Cole Shanks**[1]**, Marçal Comajoan Cara**[4]
Jordi Abante[3]**, Alexander G. Ioannidis**[1,2,*]

[1]University of California, Santa Cruz   [2]Stanford University
[3]Universitat de Barcelona   [4]University of California, Berkeley

Abstract

Recent advances in inference of the ancestral recombination graph (ARG), which describes how segments of chromosomes trace back through recombination and shared lineages, have made it possible to reconstruct genome-wide genealogies for large cohorts, but it remains difficult to summarize and use this information for population genetic analyses. We present ARGformer, an encoder-only transformer that learns context-dependent embeddings with a self-supervised masked-node objective finetuned with contrastive learning for downstream retrieval tasks. We train ARGformer on genealogies from coalescent simulations and on genealogies inferred from ancient and present-day Homo sapiens genomes. Using only these learned embeddings, without access to genotype matrices, ARGformer recovers familiar patterns of global population structure and supports unsupervised ancestry inference through clustering and nearest neighbor retrieval. On genealogies that include archaic hominins, ARGformer can highlight Denisovan-derived segments in Oceanian genomes and reveals Oceanian-like ancestry in South American indigenous populations. Source code of ARGformer is available at https://github.com/AI-sandbox/ARGformer.

1. Introduction

The high dimensionality of genomic data, especially in large population-scale sequencing studies such as national biobanks, has motivated the development of a variety of methods for visualizing population structure (Bycroft et al., 2018). The most popular of these is principal component analysis (PCA) (Patterson et al., 2006; Novembre & Peter, 2016), as well as uniform manifold approximation and projection (UMAP) (Diaz-Papkovich et al., 2019). In the context of population genetics, these dimensionality reduction techniques provide insight into population structure and relatedness. Deep learning has been applied for visualizing population structure in the form of variational autoencoders (VAEs) trained on SNP genotypes. VAEs produce low-dimensional latent embeddings that capture nonlinear population structure and often preserve global geometry better than t-SNE or UMAP applied directly to SNP genotypes (Battey et al., 2021; Geleta et al., 2026). Other approaches include MAPS, which estimates time-stratified migration-rate surfaces from identity-by-descent (IBD) tracts, providing temporal visualization of structure (Al-Asadi et al., 2019). Collectively, these methods provide powerful low-dimensional summaries of genetic data, but they operate directly on genotypes or derived summaries, rather than on the underlying genealogies that generate those genotypes.

Patterns of allele sharing and population structure are embedded in the history of genealogies under the coalescent with recombination (Hudson, 1983; Griffiths & Marjoram, 1997). The

---

[*]Corresponding author: `ioannidis@stanford.edu`.

ancestral recombination graph (ARG) provides a unifying representation of this history by encoding the collection of local genealogical trees along the genome together with recombination events that rearrange ancestry through time (Griffiths & Marjoram, 1997; Lewanski et al., 2024; Nielsen et al., 2025). Genealogical interpretations of principal component analysis make this link explicit by viewing genotype structure as a projection of the underlying genealogy (McVean, 2009). In the presence of recombination, the ARG encodes information about population size changes, migration and admixture, recombination and mutation processes, linkage disequilibrium, and identity by descent (Lewanski et al., 2024; Nielsen et al., 2025). In principle, methods that learn directly from ARGs have the potential to unify many classical population genetic analyses within a common representation.

Recent work has made it possible to infer ARGs at scale, reconstructing genome-wide genealogies for large cohorts (Nielsen et al., 2025; Lewanski et al., 2024). Several methods now infer genome-wide genealogies for large cohorts and demonstrate the use of inferred ARGs for genome-wide association studies and analyses of population structure (Rasmussen et al., 2014; Speidel et al., 2019; Kelleher et al., 2019; Zhang et al., 2023; Gunnarsson et al., 2024; Deng et al., 2025). However, there is not yet a standard, scalable self-supervised framework for representation learning directly on genome-wide genealogies or ARG-derived structures analogous to the way that VAEs have been applied to genotypes. This could be related to the challenges associated with such a task. For example, it is not immediately clear how to input an ARG into a deep learning model in the way that VAEs can process genotype data. In addition, the complete ARG can be an ultra-large graph even for a modest cohort, and the marginal coalescent trees also become very large graphs for medium to large scale cohorts. More generally, although deep learning has been used for population genetic inference and for learning features from sequence data (Sheehan & Song, 2016; Flagel et al., 2019; Schrider & Kern, 2018), there is no standard framework for self-supervised representation learning directly on genome-wide genealogies. This creates a gap between what modern ARG inference methods can produce and what downstream models can conveniently consume.

One particular method for efficiently encoding sequences in natural language processing has been encoder-only transformers, and in particular Bidirectional Encoder Representations from transformers (BERT) models (Devlin et al., 2019). Masked language modeling objectives allow such models to learn rich, context-dependent representations in a fully self-supervised fashion, and recent work has introduced more efficient BERT-style encoders, such as ModernBERT, that scale to large training corpora (Warner et al., 2025). Encoder-only transformers and masked prediction objectives have also been successfully transferred to a wide range of biological sequence and graph domains, where they provide general-purpose embeddings for downstream tasks (Rives et al., 2021; Ji et al., 2021). More broadly, recent theoretical and empirical work has shown that pure transformer architectures, with suitable tokenization schemes, can act as powerful and competitive graph learners, often rivaling or surpassing message passing graph neural networks (Kim et al., 2022).

Here we explore a BERT-style encoder for the sequence of coalescent events in the ARG, which we call ARGformer. ARGformer encodes, for each extant haplotype, the path from the leaf to the root of the marginal tree as a token sequence, exploiting shared coalescent events across paths. Trained in a fully self-supervised fashion on both simulated ARGs and ARGs inferred from combinations of ancient and present-day human genomes (Wohns et al., 2022), ARGformer learns context-dependent embeddings that recapitulate global population structure, capture local genealogical relationships and ancestry, and can be used directly for unsupervised ancestry inference via clustering or nearest-neighbor retrieval in embedding space. Conceptually, our approach is related to genealogical interpretations of principal component analysis in population genetics, which view genotype structure as a projection of the underlying genealogy (McVean, 2009), but ARGformer operates directly on the inferred genealogies rather than on genotype matrices.

In applications to both simulated genealogies and ARGs inferred from ancient and present-day *Homo sapiens* genomes, we show that ARGformer embeddings alone, without access

Figure 1: Overview of ARGformer. **A**: Cartoon ARG with recombination and resulting marginal trees. **B**: Encoder-only Transformer over path tokens, with self-supervised masked-node pretraining objective predicting masked ancestral node identity. **C**: Contrastive finetuning for downstream usage of learned embeddings (visualization, clustering, retrieval for ancestry/introgression).

to genotype matrices, recover familiar patterns of global population structure and support unsupervised ancestry inference via clustering and nearest-neighbor retrieval. On ARGs that include archaic hominin genomes, ARGformer embeddings highlight Denisovan-derived segments in Oceanian genomes, consistent with previous observations of Denisovan introgression in Papuans (Jacobs et al., 2019; Vespasiani et al., 2022), and reveal Oceanian-like ancestry patterns present in some Indigenous South American populations, but entirely absent from the other Indigenous Americans. This echoes previously observed Australasian-related ancestry in Amazonian groups (Skoglund et al., 2015; Castro e Silva et al., 2021). These examples illustrate how local genealogies along the genome encode complex demographic and admixture histories, and how representation learning on ARGs can make this information accessible for visualization and downstream analyses.

2. Materials and methods

2.1. BERT model for encoding paths in ancestral recombination graphs.

There are many possibilities for encoding ARGs with a transformer. Rather than encoding an entire ARG or full marginal coalescent trees, we instead encoded the linear sequence of coalescent events along the path from the leaves to the root. This approach is similar to the sub-sampling also seen in representation learning for graphs and enables better scalability (Hou et al., 2022). ARGformer treats paths through marginal coalescent trees as sequences and augments them with positional encodings that reflect the ordering of coalescence events and the local tree topology along the path, providing a flexible representation model for ARGs. Each node in the inferred genealogy has a unique identifier, enabling ARGformer to learn latent representations that capture both genealogical relationships and their evolution through time along the genome.

ARGformer is an encoder-only transformer that operates on these path sequences to learn vector representations of ARG nodes and haplotypes. During self-supervised pretraining, we adopt a masked-node objective: we randomly mask node tokens along each path and optimize a cross-entropy loss to predict the masked nodes, analogous to masked language modeling but applied to the ARG. Concretely, let a leaf-to-root path be a sequence of tokens $\mathbf{x} = (x_1, \ldots, x_L)$, where each token is a node identifier. Let $M \subseteq \{1, \ldots, L\}$ denote the set of masked positions, sampled by independently including each position i in M with probability $p_{\mathrm{mask}} = 0.30$ (Warner et al., 2025). Let $\tilde{\mathbf{x}}$ be the corrupted input sequence obtained by replacing x_i with a special [MASK] token for all $i \in M$. Given the Transformer hidden state $h_i = f_\theta(\tilde{\mathbf{x}})_i$ at position i, we predict the original token via a softmax head over the vocabulary

$$p_\theta(t \mid \tilde{\mathbf{x}}, i) = \mathrm{softmax}(W h_i)_t, \quad t \in \mathcal{T}. \tag{1}$$

We then minimize the masked cross-entropy loss averaged over masked positions,

$$\mathcal{L}_{\text{mask}}(\theta) = -\frac{1}{|M|} \sum_{i \in M} \log p_\theta(t_i^\star \mid \tilde{\mathbf{x}}, i), \tag{2}$$

where $t_i^\star$ is the ground-truth token at position i. We build ARGformer on top of a ModernBERT-style encoder that incorporates recent architectural and optimization improvements, which substantially improves training efficiency on large collections of data (Warner et al., 2025).

We finetune the pretrained encoder for downstream tasks with a supervised contrastive objective that pulls together embeddings of sequences sharing the same reference population label while pushing apart embeddings from different labels within each minibatch. Given a batch of B labeled sequences $\{(\mathbf{x}_i, y_i)\}_{i=1}^B$ with labels $y_i \in \{1, \ldots, C\}$, we encode each sequence with the Transformer backbone followed by a pooling head to obtain embeddings:

$$\mathbf{z}_i = \frac{g_\phi(f_\theta(\mathbf{x}_i))}{\left\| g_\phi(f_\theta(\mathbf{x}_i)) \right\|_2}, \tag{3}$$

where f_θ is the Transformer encoder, g_ϕ is the pooling head, and embeddings are ℓ_2-normalized. For each anchor i, define the in-batch positive set $P(i) = \{j \neq i : y_j = y_i\}$. We minimize the supervised contrastive (InfoNCE-style) loss

$$\mathcal{L}_{\text{con}}(\theta, \phi) = \frac{1}{B} \sum_{i=1}^B \frac{1}{|P(i)|} \sum_{j \in P(i)} \left[-\log \frac{\exp(\mathbf{z}_i^\top \mathbf{z}_j / \tau)}{\sum_{k \neq i} \exp(\mathbf{z}_i^\top \mathbf{z}_k / \tau)} \right], \tag{4}$$

where $\tau > 0$ is a temperature hyperparameter (default $\tau = 0.05$). The denominator sums over all in-batch samples except the anchor, providing implicit hard negatives from other classes. Anchors with no same-class partners in the batch ($|P(i)| = 0$) are excluded from the loss. To mitigate class imbalance, we apply inverse-frequency weighting:

$$\mathcal{L}_{\text{con}}^{\text{w}}(\theta, \phi) = \frac{1}{\sum_{i:\, |P(i)|>0} w_{y_i}} \sum_{i:\, |P(i)|>0} w_{y_i} \, \ell_i, \tag{5}$$

where ℓ_i denotes the per-anchor term in $\mathcal{L}_{\text{con}}$, and $w_c = \frac{N}{C\, N_c}$ with N the total number of training examples and N_c the number in class c.

2.2. ARGformer on simulated data

We first applied ARGformer to simulated data generated using `msprime` (Kelleher et al., 2016). We simulated 1600 samples from four populations (Admixed=1000, European=200, African=200, East Asian=200) in the three-population out-of-Africa demography (AmericanAdmixture 4B18) from the `stdpopsim` catalog (Adrion et al., 2020), for a single 30 million base pair (bp) chromosome, using a flat recombination rate of 1×10^{-8} per bp generation and a mutation rate of 1.25e-8 per bp per generation (Lauterbur et al., 2023; Browning et al., 2018). We generated a dataset for pretraining using `tskit` to extract coalescent events (Wong et al., 2024). To better evaluate ARGformer on inferred ARGs, we inferred the ARG using `tsinfer+tsdate` on the simulated genotypes, without phasing or genotype error (Wohns et al., 2022; Kelleher et al., 2019). We split this dataset into training (90%) and validation (10%) for pretraining.

2.3. Application of ARGformer to an inferred ARG of ancient and modern DNA

To apply ARGformer to real data we used the inferred ARG from (Wohns et al., 2022). This consists of the following datasets: 1000 Genomes Project (1KGP) (Auton et al., 2015),

Table 1: Dataset statistics for ARGformer pretraining on the real inferred ARG from (Wohns et al., 2022).

Dataset	Statistic	Training	Validation
Archaic Introgression	Sample nodes	688	
	Vocabulary size	184,963	
	Unique paths	7,660,071	851,119
	Total tokens	120,297,364	13,369,481
Oceania-like in Americas	Sample nodes	665	
	Vocabulary size	119,067	
	Unique paths	3,473,898	385,989
	Total tokens	57,777,684	6,421,781

Simons Genome Diversity Project (SGDP) (Mallick et al., 2016), Human Genome Diversity Project (HGDP) (Bergström et al., 2020), three Neanderthal genomes (Chagyrskaya, Altai, and Vindija) (Mafessoni et al., 2020; Prüfer et al., 2014; 2017), and a Denisovan genome.

Following (Wohns et al., 2022), who used only chromosome 20, we restricted our analysis to the short arm of chromosome 20 (chr20p) due to its computational tractability while maintaining sufficient genealogical complexity. We extracted unique marginal paths from each extant sample node to the root across all trees in the tree sequence, representing the complete ancestral lineages.

We created two separate datasets for distinct analyses:

Archaic Introgression Analysis. This dataset includes archaic reference genomes (Altai, Chagyrskaya, and Vindija Neanderthals, and Denisovan), an African baseline (Yoruba), and held-out populations for validation (Utah Residents (CEPH) with Northern and Western European ancestry, Chinese Dai, Papuan Highlands, and Mandinka).

Oceania-like Ancestry in the Americas. This dataset consists of three reference groups and one test group: (1) East Asian populations (Han Chinese, Japanese), (2) Indigenous American baseline populations (Pima, Maya, Mixe), (3) Oceanian populations (Aboriginal Australian, Bougainville, Papuan populations), and a held-out test group of Indigenous American populations (Karitiana, Suruí, Chane, Piapoco, Quechua, Zapotec). Reference groups were balanced to the minimum group size to prevent biasing the model toward overrepresented populations.

For both datasets, we performed a 90%/10% train/validation split on the unique marginal path sequences. Table 1 summarizes the dataset statistics.

3. Results

We first evaluated ARGformer on coalescent simulations to ask whether path embeddings recover familiar patterns of global population structure and support ancestry-related tasks. We then applied ARGformer to ARGs inferred from ancient and present-day *Homo sapiens* genomes, using the learned embeddings to detect Denisovan ancestry in Oceania and to test for Oceanian-like affinities in Indigenous South American populations. Finally, we summarize model behavior and computational efficiency during self-supervised pretraining on large collections of marginal genealogies.

3.1. Capturing population structure

ARGformer embeddings provide a chromosomal segment-level view of population structure derived from local genealogies (Figure 2A,B). In the genotype PCA (Figure 2A), each point aggregates information across the entire genome, so individuals with contributions

Figure 2: Population structure and local-ancestry geometry on simulated data. Colors indicate population label: East Asian (pink), African (orange), European (blue), and admixed (gray). **A**: PCA of ground-truth genotypes (points are individuals; PC1 vs PC2; PC2 vs PC3). PCA is fitted on reference populations (AFR, EAS, EUR), and ADMIX samples are projected. **B**: The same PCA protocol applied to ARGformer contrastive embeddings without genotype matrices (points are haplotype marginal-path embeddings, multiple per individual).

from multiple ancestries will fall between the three continental clusters (Figure 2A). In contrast, each point in Figure 2B corresponds to a single marginal-path embedding, *i.e.*, a local genealogy segment in the genome. Under the simulated admixture demography, local segments predominantly trace to one of the unadmixed sources and therefore concentrate within reference ancestry clusters.

Using only the learned ARG-based embeddings from the contrastively finetuned encoder, we can separate local chromosomal segments without directly accessing genotype matrices. In this sense, ARGformer plays for genealogies and haplotypes a role that is analogous to PCA for genotypes, providing a low-dimensional visualization of population structure that is rooted in the inferred ARG. The encoder is first pretrained in a fully self-supervised way, without using ancestry labels, and is then finetuned with a supervised contrastive loss that explicitly pulls together embeddings of haplotypes sharing the same ancestry label and pushes apart embeddings from different ancestries (AFR, EUR, EAS). This contrastive structure in embedding space is precisely what enables simple clustering and similarity-based retrieval methods to perform well on downstream ancestry classification.

To further evaluate the ability of ARGformer to learn population structure, we also benchmarked local ancestry inference (LAI) in admixed individuals against FLARE (Browning et al., 2023). Using 10,000 unique marginal paths sampled from admixed individuals, we considered two inference strategies based solely on ARGformer embeddings. The first performs

Table 2: LAI accuracy on simulated American admixture. FLARE is run on simulated genotypes, and ARGformer is run on the inferred ARG.

Method	EUR	EAS	AFR
FLARE	**98.54**	**99.74**	96.70
ARGformer PCA clustering	97.91	99.07	97.81
ARGformer retrieval	98.00	99.04	**97.90**

PCA on embeddings of unadmixed reference individuals and retains the top 10 principal components. We then project each marginal path embedding into this 10-dimensional PC space and assign an ancestry label based on its cluster membership in this space (PCA clustering).

The second strategy mirrors dense retrieval approaches used in large language models (LLMs) and retrieval-augmented generation (RAG) systems, where both queries and documents are embedded into a shared space and relevant documents are obtained by nearest-neighbor search (Reimers & Gurevych, 2019; Lewis et al., 2020). Here we treat each admixed marginal path as a query and retrieve its nearest neighbors among embeddings of reference haplotypes in the original ARGformer embedding space, assigning ancestry labels based on the labels of the retrieved neighbors. In both cases we compare the resulting three-way local ancestry calls with those from FLARE, providing a quantitative benchmark for how well the contrastively trained ARGformer embeddings capture population structure at the level of individual genomic segments. ARGformer achieved comparable accuracy to FLARE, a state-of-the-art local ancestry inference method, and obtained higher accuracy on AFR ancestry with the nearest-neighbor retrieval (Table 2).

3.2. Identifying Denisovan ancestry in Oceania

To test whether ARGformer embeddings capture archaic introgression signals without using genotype matrices, we framed archaic ancestry detection as a nearest-neighbor retrieval problem in embedding space. For each held-out population, we retrieved the top-5 closest haplotype-path embeddings and summarized the retrieved reference labels as a row-normalized distribution over reference populations, reporting both the raw vote share and a chance-corrected enrichment (Figure 3).

Papuan Highlands stands out with an increased Denisovan neighbor fraction (3.60% of the top-5 neighbors, compared with non-Oceanian populations 1.44% (Chinese Dai), 0.94% (Utah Residents (CEPH) with Northern and Western European ancestry), and 0.71% (Mandinka) in the same analysis. This enrichment is reflected by the positive log-lift coloring in the Denisovan column (Figure 3, Panel A), where Mandinka is the only query population with a negative lift. In contrast, all query populations predominantly retrieve Yoruba-labeled neighbors (between 95.7% and 99.1% across rows), consistent with most genomic segments being closest to modern human variation. We also note that some non-Oceanian samples (*e.g.*, Utah Residents (CEPH) with Northern and Western European ancestry) can retrieve a slightly higher fraction of Denisovan-labeled neighbors than Neanderthal-labeled neighbors. Because the archaic genomes were computationally phased without reference panels or imputation, and because contrastive finetuning can be sensitive to such technical artifacts, we treat these retrieval shares as relative enrichment signals rather than admixture proportions.

Together, this shows that ARGformer embeddings learned from inferred genealogies can localize Denisovan-like segments in Oceanian genomes via unsupervised retrieval, consistent with established Denisovan introgression in Papuan-related Oceanian populations (Jacobs et al., 2019; Vespasiani et al., 2022). Panel B in Figure 3 shows a UMAP projection, highlighting distinct clusters and a subset of query haplotypes falling on archaic clusters.

Figure 3: Denisovan segment retrieval in Oceania using ARGformer embeddings. **A**: Nearest-neighbor retrieval reveals Denisovan-enriched embedding neighborhoods in Oceanian haplotypes. For each held-out query haplotype path (row), we retrieve its top-5 nearest neighbors from the train/val embedding corpus and record the neighbors' reference individual labels (columns). Each cell reports the row-normalized fraction of retrieved neighbors assigned to the corresponding reference population. Colors show the log-lift of retrieval relative to chance $(\log_2(\text{lift}) = \log_2(\hat{p}_c/p_c)$ where $\hat{p}_c$ is retrieved vote share and p_c is corpus label frequency), so values above zero indicate enrichment beyond what would be expected from corpus composition. Papuan Highlands individuals show the strongest Denisovan enrichment, followed by Chinese Dai, whereas other query populations predominantly retrieve modern African (Yoruba) neighbors reflecting shared out-of-Africa origins for Homo sapiens. **B**: UMAP projection of haplotype-path embeddings for archaic references (Denisovan and Neanderthals), modern population reference Yoruba, and query populations (Mandinka, Utah Residents (CEPH) with Northern and Western European ancestry, Chinese Dai, Papuan Highlands). Nearest-neighbor vote shares are reported for retrieval interpretability and should not be interpreted as introgression proportions, especially given potential technical artifacts affecting the computationally phased archaic references in the inferred ARG.

3.3. Oceania-like ancestry in South America

We next asked whether ARGformer embeddings capture the subtle Oceania-related affinities that have been previously reported in some Indigenous South American Amazonian populations using allele frequency based analyses (Skoglund et al., 2015; Castro e Silva et al., 2021). As in the archaic introgression analysis, we framed this question as a retrieval problem in embedding space: given a query set of marginal-path embeddings from Indigenous American populations, we retrieve the top-5 nearest neighbors of its haplotype-path embeddings from a reference corpus stratified into three regional groups (Americas, East Asian, and Oceania) and summarize neighbor identities as a row-normalized vote share, alongside a chance-corrected enrichment (Figure 4A). In this analysis, the Americas reference group comprises Pima, Maya, and Mixe individuals; the Oceania reference group comprises Australian, Bougainville, Papuan, Papuan Highlands, and Papuan Sepik; and the East Asian reference group comprises Han Chinese and Japanese.

Across query populations, retrieved neighbors at the haplotype-level are predominantly labeled as Americas, with a consistent minority labeled as East Asian, matching the expected close genealogical relationship between the Americas and East Asia under models of the peopling of the Americas. In contrast, Oceania neighbors are rare overall, but show a marked relative increase in Suruí and Karitiana. Specifically, Suruí and Karitiana retrieve Oceania-labeled neighbors at 9.84% and 8.71%, respectively. The next highest is another Amazonian group, Piapoco, at 6.55%, compared with 4.36% to 5.16% in the other Indigenous American query populations (Chane, Zapotec, Quechua). This shift is reflected in the Oceania column's log-lift shading, where Suruí and Karitiana exhibit the weakest depletion (closest to zero) relative to the background composition of the embedding corpus, consistent with a modest but detectable excess of Oceanian-reference nearest neighbors in these populations. A

Figure 4: Population-scale affinities between the Americas, East Asia, and Oceania in ARGformer embedding space. **A**: Nearest-neighbor retrieval highlights cross-regional enrichment patterns. For each query population (row), we retrieve the top-5 nearest neighbors from the embedding corpus and tabulate the neighbors' regional labels (Americas, East Asian, Oceania; columns). Each cell reports the row-normalized fraction of retrieved neighbors assigned to the corresponding region, and colors show the log-lift of retrieval. Indigenous American query populations predominantly retrieve Americas neighbors, with secondary retrieval for East Asian neighbors reflecting their shared origin in Asia. Suruí and Karitiana show the highest enrichment for Oceanian retrieval. **B**: UMAP projection of haplotype-path embeddings for populations spanning Oceania (*e.g.*, Australian, Bougainville, Papuan groups), East Asia (Han Chinese, Japanese), and the Americas (*e.g.*, Chane, Karitiana, Piapoco, Quechua, Suruí, Zapotec). **C**: Negative-control retrieval with Oceanian references removed. Top-5 nearest-neighbor vote shares and log-lift are recomputed over Americas and East Asian references only.

complementary view comes from a UMAP projection of the same haplotype-path embedding space (Figure 4B). Reference population groups form their own separated clusters with most of the query points spread on the American embedding manifold, while the Oceanian cluster contains a small set of Suruí and Karitiana embeddings, and a small set of Suruí and Piapoco points are displaced toward the Oceania side of the embedding space, consistent with the retrieval asymmetry observed above. As a robustness check, removing the Oceanian references shifts the retrieved neighbor composition primarily toward East Asian for Suruí, Karitiana, and Piapoco, whereas the other query populations remain dominated by Americas neighbors (Figure 4C).

Because each tokenized path corresponds to a marginal genealogy at a genomic interval, this enrichment can be read locally: a subset of Suruí and Karitiana segments have nearest-neighbor genealogical proximity to Oceanian reference paths that is stronger than in the other South American populations shown.

3.4. Model training and efficiency

We adopted the ModernBERT-base architecture and optimization settings (Warner et al., 2025), using a 12-layer, 12-head Transformer (Vaswani et al., 2017) with rotary position embeddings (RoPE) (Su et al., 2024), and Flash Attention 2 (Dao, 2024). We assessed the model's ability to learn genealogical representations through self-supervised training. To measure generalization to unseen haplotypes, we monitored validation loss and masked token accuracy on a held-out set comprising 10% of ancestral paths excluded from training. On this held-out set from the inferred ARG dataset, ARGformer achieved a top-1 accuracy of 95.96%, confirming it effectively reconstructs ancestral paths from context for previously unseen sequences. Training was also highly efficient. Pretraining sustained an average throughput of 189,500 tokens/sec and converged in 58 minutes on 1 NVIDIA A100 GPU with 80 GB of VRAM.

4. Conclusion

With ARGformer, we use a path-based encoding of each marginal genealogy: for every extant haplotype we trace the sequence of coalescent events from the leaf to the root and treat this ordered list of ancestral nodes as a token sequence. Although each training example contains only a single path, different paths share ancestors, so overlapping node identifiers allow the model to recover relationships among haplotypes, analogous to token co-occurrence in language modeling. Because ARGformer is trained in a fully self-supervised fashion, without ancestry labels, it provides a flexible backbone that can be adapted to many downstream tasks. For example, we apply contrastive finetuning using ancestry labels to pull together related haplotypes and separate unrelated ones. This allows ARGformer to provide a low-dimensional visualization of population structure from the ARG, and perform local ancestry inference, classifying paths in the marginal coalescent trees as originating from different populations in admixed individuals.

Together, the retrieval results support the interpretation that, although the dominant genealogical signal in South American genomes reflects shared Indigenous American ancestry with expected East Asian affinity, a subset of local genealogies in Suruí and Karitiana populations are shared with ancestry found in Oceania. Similarly, we recovered expected signals of Denisovan introgression in Oceania. Because each tokenized path corresponds to a marginal tree along the genome, this retrieval-based view highlights how ARGformer can surface localized, ancestry-informative segments directly from inferred genealogies, without explicit genotype features, by exploiting the structure of local coalescent histories encoded in the ARG.

With appropriate architectural and objective modifications, we expect that the same framework can be extended to a broad range of other challenges in population genetics and evolutionary inference. The learned representations could potentially be adapted to graph-level tasks that detect demographic bottlenecks or signatures of selection (Browning & Browning, 2015; Vaughn & Nielsen, 2024). Scaling ARG-based models to biobank cohorts will likely require more compressed representations than assigning a distinct token to every ancestor. One promising direction is to define tokens that correspond to shared lineages in the genealogy, so that each individual is represented by a sequence of higher-level ancestral lineages over the past several hundred or thousand generations, rather than by every individual node. Future work could also explore decoder-only or encoder-decoder architectures built on such lineage tokens for global graph-level tasks, while the present work focuses on encoder-only models and individual-level ancestry.

For ancestry inference, several limitations remain. Some paths in the marginal trees have few coalescent events, which make them relatively uninformative and noisy for classification. Another disadvantage is the challenge of ARG inference itself. Even the most scalable methods struggle with the greater variant density we expect in imputed data and whole-genome datasets (Gunnarsson et al., 2024). However, given the breadth of population genetic information encoded in ARGs, our results support the view that representation learning on ARGs can provide a strategy for future methodologies and applied analyses in population genetics.

Acknowledgments

We thank Leo Speidel for helpful discussions and comments on this work.

References

Jeffrey R. Adrion, Christopher B. Cole, Noah Dukler et al. A community-maintained standard library of population genetic models. *eLife*, 9:e54967, 2020.

Hussein Al-Asadi, Desislava Petkova, Matthew Stephens et al. Estimating recent migration and population-size surfaces. *PLOS Genetics*, 15(1):e1007908, 2019.

Adam Auton, Gonçalo R. Abecasis, David M. Altshuler et al. A global reference for human genetic variation. *Nature*, 526(7571):68–74, 2015.

C. J. Battey, Gabrielle C. Coffing, and Andrew D. Kern. Visualizing population structure with variational autoencoders. *G3*, 11(1):jkaa036, 2021.

Anders Bergström, Shane A. McCarthy, Ruoyun Hui et al. Insights into human genetic variation and population history from 929 diverse genomes. *Science*, 367(6484):eaay5012, 2020.

Sharon R. Browning and Brian L. Browning. Accurate non-parametric estimation of recent effective population size from segments of identity by descent. *The American Journal of Human Genetics*, 97(3):404–418, 2015.

Sharon R. Browning, Brian L. Browning, Martha L. Daviglus et al. Ancestry-specific recent effective population size in the Americas. *PLOS Genetics*, 14(5):e1007385, 2018.

Sharon R. Browning, Ryan K. Waples, and Brian L. Browning. Fast, accurate local ancestry inference with FLARE. *American Journal of Human Genetics*, 110(2):326–335, 2023.

Clare Bycroft, Colin Freeman, Desislava Petkova et al. The UK Biobank resource with deep phenotyping and genomic data. *Nature*, 562(7726):203–209, 2018.

Marcos Araújo Castro e Silva, Tiago Ferraz, Maria Cátira Bortolini et al. Deep genetic affinity between coastal pacific and amazonian natives evidenced by australasian ancestry. *Proceedings of the National Academy of Sciences of the USA*, 118(14):e2025739118, 2021.

Tri Dao. Flashattention-2: Faster attention with better parallelism and work partitioning. In *The Twelfth International Conference on Learning Representations*, 2024.

Yun Deng, Rasmus Nielsen, and Yun S. Song. Robust and accurate bayesian inference of genome-wide genealogies for hundreds of genomes. *Nature Genetics*, pp. 1–12, 2025.

Jacob Devlin, Ming-Wei Chang, Kenton Lee et al. BERT: Pre-training of deep bidirectional transformers for language understanding. In *Proceedings of the 2019 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies*, pp. 4171–4186, 2019.

Alex Diaz-Papkovich, Luke Anderson-Trocmé, Chief Ben-Eghan et al. UMAP reveals cryptic population structure and phenotype heterogeneity in large genomic cohorts. *PLOS Genetics*, 15(11):e1008432, 2019.

Lex Flagel, Yaniv Brandvain, and Daniel R. Schrider. The unreasonable effectiveness of convolutional neural networks in population genetic inference. *Molecular Biology and Evolution*, 36(2):220–238, 2019.

Margarita Geleta, Daniel Mas Montserrat, Xavier Giro-i Nieto et al. Autoencoders for genomic variation analysis. *Genome Research*, 36(2):348–360, 2026.

Robert C. Griffiths and Paul Marjoram. An ancestral recombination graph. *Progress in Population Genetics and Human Evolution*, pp. 257–270, 1997.

Árni Freyr Gunnarsson, Jiazheng Zhu, Brian C. Zhang et al. A scalable approach for genome-wide inference of ancestral recombination graphs. *bioRxiv*, 2024.

Zhenyu Hou, Xiao Liu, Yukuo Cen et al. GraphMAE: Self-supervised masked graph autoencoders. In *Proceedings of the 28th ACM SIGKDD Conference on Knowledge Discovery and Data Mining*, pp. 594–604, 2022.

Richard R. Hudson. Properties of a neutral allele model with intragenic recombination. *Theoretical Population Biology*, 23(2):183–201, 1983.

Guy S. Jacobs, Georgi Hudjashov, Lauri Saag et al. Multiple deeply divergent denisovan ancestries in papuans. *Cell*, 177(4):1010–1021.e32, 2019.

Yanrong Ji, Zhihan Zhou, Han Liu et al. DNABERT: pre-trained bidirectional encoder representations from transformers model for DNA-language in genome. *Bioinformatics*, 37 (15):2112–2120, 2021.

Jerome Kelleher, Alison M. Etheridge, and Gilean McVean. Efficient coalescent simulation and genealogical analysis for large sample sizes. *PLOS Computational Biology*, 12(5): e1004842, 2016.

Jerome Kelleher, Yan Wong, Anthony W. Wohns et al. Inferring whole-genome histories in large population datasets. *Nature Genetics*, 51(9):1330–1338, 2019.

Jinwoo Kim, Dat Nguyen, Seonwoo Min et al. Pure transformers are powerful graph learners. *Advances in Neural Information Processing Systems*, 35:14582–14595, 2022.

M. Elise Lauterbur, Maria Izabel A. Cavassim, Ariella L. Gladstein et al. Expanding the Stdpopsim species catalog, and lessons learned for realistic genome simulations. *eLife*, 12, 2023.

Alexander L. Lewanski, Michael C. Grundler, and Gideon S. Bradburd. The era of the arg: An introduction to ancestral recombination graphs and their significance in empirical evolutionary genomics. *PLOS Genetics*, 20(1):e1011110, 2024.

Patrick Lewis, Ethan Perez, Aleksandra Piktus et al. Retrieval-augmented generation for knowledge-intensive NLP tasks. *Advances in Neural Information Processing Systems*, 33: 9459–9474, 2020.

Fabrizio Mafessoni, Steffi Grote, Cesare de Filippo et al. A high-coverage Neandertal genome from Chagyrskaya Cave. *Proceedings of the National Academy of Sciences*, 117 (26):15132–15136, 2020.

Swapan Mallick, Heng Li, Mark Lipson et al. The Simons Genome Diversity Project: 300 genomes from 142 diverse populations. *Nature*, 538(7624):201–206, 2016.

Gil McVean. A genealogical interpretation of principal components analysis. *PLOS Genetics*, 5(10):e1000686, 2009.

Rasmus Nielsen, Andrew H. Vaughn, and Yun Deng. Inference and applications of ancestral recombination graphs. *Nature Reviews Genetics*, 26(1):47–58, 2025.

John Novembre and Benjamin M. Peter. Recent advances in the study of fine-scale population structure in humans. *Current Opinion in Genetics & Development*, 41:98–105, 2016.

Nick Patterson, Alkes L. Price, and David Reich. Population structure and eigenanalysis. *PLOS Genetics*, 2(12):e190, 2006.

Kay Prüfer, Fernando Racimo, Nick Patterson et al. The complete genome sequence of a Neanderthal from the Altai Mountains. *Nature*, 505(7481):43–49, 2014.

Kay Prüfer, Cesare de Filippo, Steffi Grote et al. A high-coverage Neandertal genome from Vindija Cave in Croatia. *Science*, 358(6363):655–658, 2017.

Matthew D. Rasmussen, Melissa J. Hubisz, Ilan Gronau et al. Genome-wide inference of ancestral recombination graphs. *PLOS Genetics*, 10(5):e1004342, 2014.

Nils Reimers and Iryna Gurevych. Sentence-BERT: Sentence embeddings using siamese BERT-networks. In *Proceedings of the 2019 Conference on Empirical Methods in Natural Language Processing*, 2019.

Alexander Rives, Stephan Meier, Tom Sercu et al. Biological structure and function emerge from scaling unsupervised learning to 250 million protein sequences. *Proceedings of the National Academy of Sciences of the USA*, 118(15):e2016239118, 2021.

Daniel R. Schrider and Andrew D. Kern. Supervised machine learning for population genetics: A new paradigm. *Trends in Genetics*, 34(4):301–312, 2018.

Sara Sheehan and Yun S. Song. Deep learning for population genetic inference. *PLOS Computational Biology*, 12(3):e1004845, 2016.

Pontus Skoglund, Swapan Mallick, Maria Cátira Bortolini et al. Genetic evidence for two founding populations of the americas. *Nature*, 525(7567):104–108, 2015.

Leo Speidel, Marie Forest, Sinan Shi et al. A method for genome-wide genealogy estimation for thousands of samples. *Nature Genetics*, 51(9):1321–1329, 2019.

Jianlin Su, Murtadha Ahmed, Yu Lu et al. Roformer: Enhanced transformer with rotary position embedding. *Neurocomputing*, 568:127063, 2024.

Ashish Vaswani, Noam Shazeer, Niki Parmar et al. Attention is all you need. *Advances in Neural Information Processing Systems*, 30, 2017.

Andrew H. Vaughn and Rasmus Nielsen. Fast and accurate estimation of selection coefficients and allele histories from ancient and modern DNA. *Molecular Biology and Evolution*, 41 (8):msae156, 2024.

Davide M. Vespasiani, Guy S. Jacobs, Laura E. Cook et al. Denisovan introgression has shaped the immune system of present-day papuans. *PLOS Genetics*, 18(12):e1010470, 2022.

Benjamin Warner, Antoine Chaffin, Benjamin Clavié et al. Smarter, better, faster, longer: A modern bidirectional encoder for fast, memory efficient, and long context finetuning and inference. In *Proceedings of the 63rd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pp. 2526–2547, 2025.

Anthony Wilder Wohns, Yan Wong, Ben Jeffery et al. A unified genealogy of modern and ancient genomes. *Science*, 375(6583):eabi8264, 2022.

Yan Wong, Anastasia Ignatieva, Jere Koskela et al. A general and efficient representation of ancestral recombination graphs. *Genetics*, 228(1):iyae100, 2024.

Brian C. Zhang, Arjun Biddanda, Árni Freyr Gunnarsson et al. Biobank-scale inference of ancestral recombination graphs enables genealogical analysis of complex traits. *Nature Genetics*, 55(5):768–776, 2023.