Graph Lens Lite: An interactive biological network viewer for displaying, exploring, and sharing disease pathobiology and drug mechanism of action models

Matthias Ley[*,1,2], Kinga Kęska-Izworska[1], Lucas Fillinger[1], Samuel M Walter[1], Fabio Baumgärtel[1], Enrico Bono[1,2], Louiza Galou[1,2], Peter Andorfer[1], Pirmin Hauser[3], Johannes Leierer[3], Klaus Kratochwill[#,*,1,2], Paul Perco[#1,3]

[1]Delta4 GmbH, Alser Straße 23/30, 1080 Vienna, Austria
[2]Division of Pediatric Nephrology and Gastroenterology, Department of Pediatrics and Adolescent Medicine, Comprehensive Center for Pediatrics, Medical University Vienna, Waehringer Guertel 18-20, 1090 Vienna, Austria
[3]Department of Internal Medicine IV, Medical University Innsbruck, Anichstrasse 35, 6020 Innsbruck, Austria
[#]Contributed equally
[*]Corresponding authors: matthias.ley@delta4.ai, klaus.kratochwill@delta4.ai

Abstract

Motivation: Biological network visualization together with graph-based analyses are key techniques in systems biology and network medicine to detect patterns and generate new hypotheses regarding disease pathobiology, drug target identification, or digital drug discovery. Network representations are also a way to communicate research findings and share results with colleagues and coworkers.

Results: We have developed Graph Lens Lite, a browser-based tool that combines rich visualization capabilities with a streamlined interface for exploring and sharing biological networks. It offers an expressive query language, topological network analysis, GUI-based filtering, visual grouping, customizable layouts, a data-editor, and fine-grained property-based styling options, particularly suited for visualizing molecular models of disease pathobiology or drug mechanism of action.

Availability: Graph Lens Lite is available at GitHub (`https://github.com/Delta4AI/GraphLensLite`).

Supplementary information: Supplementary data are available at *Bioinformatics* online.

Keywords: network visualization, graph exploration, disease pathobiology, drug mechanism of action

1 Introduction

Visualization of biological networks is a core technique in systems biology for representation and analysis of complex, often heterogeneous, data. Network visualization combined with quantitative graph analysis such as detection of network modules, hub or bottleneck nodes, or cross-talk between networks can lead to novel hypothesis generation or detection of relevant patterns in biomedical data [Ehlers et al., 2025]. Biological networks are of particular relevance in digital drug discovery and drug target prioritization and are used in modeling disease pathobiology as well as drug mechanism of action on a molecular level. Biological networks also represent an intuitive way of communicating and sharing research findings with collaborators or disseminating them to the broader scientific community.

Cytoscape and Gephi are considered gold standards for interactive network visualization with an exhaustive plugin ecosystem and rich layout capabilities, but are desktop-focused and lack portability or modern web-app features [Shannon et al., 2003, Bastian et al., 2009]. Other tools such as STRING or OmicsNet 2.0 prioritize data integration, enrichment analysis, and access to extensive biological databases over visualization and customization, integrating the network viewer as a helper and not as the focus of the application [Szklarczyk et al., 2025, Zhou et al., 2022]. Several web-based alternatives have emerged to address portability concerns. Cytoscape Web extends the Cytoscape ecosystem with collaborative workflows for network visualization, though focusing on core functionalities with basic filtering and styling [Ono et al., 2025]. Gephi Lite uses sigma.js for efficient WebGL-based rendering, though it compromises customization, filtering, and advanced styling. Similarly, Graphia provides both a desktop and web client with a powerful 2D/3D rendering engine, but focuses less on user-friendly styling, highlighting, grouping and filtering, prioritizing efficiency, enrichment and layout.

We have developed Graph Lens Lite (GLL) to address the need for a browser-based tool that combines visualization power with an intuitive, streamlined interface, enabling researchers to rapidly explore and evaluate complex networks without requiring expertise in specialized software. GLL offers an expressive query language alongside graphical user interface (GUI)-based filtering, visual grouping, and fine-grained styling controls. Users can compute network metrics, apply customizable layouts, and map data attributes to visual scales. GLL exports networks as portable JSON files that capture the full application state for seamless collaboration, or as data tables for downstream analysis.

2 Materials and methods

2.1 Installation

GLL is a free, open-source web application for visualization and exploration of networks. It is written using HTML, CSS, and JavaScript and runs on any modern browser without requiring additional installations. GLL is distributed under the MIT license and its source code is publicly available on GitHub.

2.2 Data input

GLL accepts spreadsheets containing node and edge tables, or a JSON format preserving the application state. Input data require an 'ID' column for nodes and 'Source ID/Target ID' columns for edges. Optional columns may specify visual attributes such as labels, shapes, sizes, colors, or coordinates. Custom properties containing user data can be added as new columns, with optional group labels in square brackets. A template with column specifications, example values, and supported data types is available on GitHub and can be generated from within the application. Additionally, a demo loader enables direct fetching of protein-protein interaction networks from the STRING database [Szklarczyk et al., 2025], with plans to extend support to further sources. To support onboarding, the application includes an interactive guided tour that walks users through the interface and its core functionalities.

2.3 The graphical user interface

The main GUI elements are shown in Figure 1.

(1) Main network view: The central window for displaying and interactively exploring the loaded network.

(2) File import: Load files in spreadsheet or GLL JSON format.

(3) Workspace management: Save and switch workspaces, reset layout, fit graph to view, and hide disconnected nodes.

Figure 1: The graphical user interface of Graph Lens Lite. (1) Main network view, (2) File import, (3) Workspace management, (4) Data editor, (5) Query editor, (6) Network and image export, (7) Node and edge filtering, (8) Node and edge tooltip, (9) Network metrics, (10) Selection panel, (11) Style panel, (12) Edit mode.

(4) Data editor: Interactive table for modifying (adding, editing, deleting) nodes and edges and their properties as well as exporting currently filtered nodes and edges.

(5) Query editor: Custom query language for nested graph filtering supporting Boolean (AND/OR/NOT), comparison ($>=,<=,..$), and set-membership (IN [..]) operators.

(6) Network and image export: Save the application state to a portable GLL JSON file or export the current view as PNG.

(7) Node and edge filtering: GUI-based filtering and visual grouping, synchronized with the

query language.

(8) Node and edge tooltip: Displays metadata for the selected node or edge elements on click.

(9) Network metrics: Controls for computing and applying network metrics to filter and select graph elements.

(10) Selection panel: Shows current selection status, lasso selection, and navigation history. An expandable section provides additional focus, search, and layout controls.

(11) Style panel: Edit node and edge styles, map parameters and network metrics to visual scales (continuous and discrete color scales, numeric size scales), and customize bubble sets.

(12) Edit mode: Fine-grained controls for GUI-based filtering.

2.4 Usage

2.4.1 Loading data

GLL starts by loading network data from spreadsheet files containing node and edge tables (Figure 1.2) or from JSON files. User-supplied properties (coordinates, styling options) are applied where specified. Users can further decide to fetch demo data from the STRING database. The workspace management panel (Figure 1.3) allows switching between independent environments, each preserving its own aesthetics, layouts, filters, and queries.

2.4.2 Exploring the network

Once loaded, users can explore the network structure through multiple approaches. The selection panel (Figure 1.10) enables element search, selection, and expansion to connected neighbors. Metadata for selected node and edge elements appear in specific tooltips (Figure 1.8). For deeper analysis, GLL computes topological metrics (e.g., node centrality measures including degree, betweenness, or PageRank) to identify key nodes within the network (Figure 1.9). Users can select a metric and examine one or more highly ranked nodes, with graph-level statistics displayed in the metric panel. In-app documentation describes each metric's methodology and provides references to relevant literature.

2.4.3 Filtering the network

GLL supports network filtering through graphical controls (Figure 1.7), with an edit mode for precise input (Figure 1.12), or a query editor for complex operations (Figure 1.5). Node and edge properties can be used for filtering and selection through either interface. The query editor uses a left-to-right syntax and ssupports Boolean operators (AND, OR, NOT), comparison ($>=,<=$), and set membership (IN) operators, as well as nested conditions using parentheses. Contextual help is accessible via an adjacent icon.

2.4.4 Styling the network

The styling panel (Figure 1.11) offers extensive visual customization options for nodes, edges, and groups. Properties such as geometry (shape, size), color (fill, border, line), labels (text, placement, font), and annotations (badges, halos, arrows) can be configured independently for each element type. Up to four bubble sets allow visual grouping of nodes with adjustable appearance. Numeric and categorical attributes, whether user-supplied or computed from network metrics, can be dynamically mapped to visual features like color and size to highlight importance.

2.4.5 Editing network data

GLL includes an integrated data editor (Figure 1.4) for modifying network data in tabular format. Supported operations include column sorting, cell editing, node and edge addition or deletion, table reset, and export to spreadsheet format. Users can also add new columns to define custom properties for nodes or edges, which become immediately available in the filtering and styling interfaces, enabling graph creation and manipulation entirely within the application.

2.4.6 Exporting results

A graph can be exported in GLL's native JSON format or as a high-resolution image (Figure 1.6). JSON exports preserve the complete application state, including views, filters, coordinates, and styling, enabling session restoration and collaborative sharing.

3 Application use case

3.1 Visualizing a network-based model of autosomal dominant polycystic kidney disease (ADPKD)

Autosomal Dominant Polycystic Kidney Disease (ADPKD) is the most common inherited kidney disorder, characterized by the gradual development and enlargement of multiple cysts in both kidneys, which ultimately leads to a progressive deterioration in kidney function [Formica and Peters, 2020]. ADPKD is a multi-factorial disease involving different disease mechanisms and molecular pathways. The exact mechanisms of ADPKD development and progression are still not fully understood and a better understanding of disease pathobiology is the basis for the discovery of novel drug targets and the development of new treatment options. We consolidated a set of biomedical data on ADPKD to model disease pathobiology and visualize molecular interactions using GLL. Literature associated ADPKD molecular features (genes and proteins) were extracted from Delta4's Hyper-C software platform that consists of sentence-level literature co-annotations between individual molecular features and ADPKD. This set of literature-associated ADPKD molecular features was complemented by genes showing differential expression in ADPKD as compared to healthy tissue based on Omics data. We downloaded the ADPKD bulk RNA-Seq dataset with the accession number GSE7869 from the Gene Expression Omnibus and re-analyzed the dataset to generate lists of differentially expressed genes [Song et al., 2009]. Global gene expression profiling was conducted on renal cysts of different volumes, and non-cancerous renal cortical tissue from nephrectomized kidneys were used as controls. Differential gene expression analysis involved data normalization, statistical modeling using linear models, identification of regulated genes based on log2 fold-change (log2FC) and adjusted p-values. Ultimately, the ADPKD phenotype model was enriched with 20 genes which showed absolute log2FC > 2 and adjusted p-values < 0.05 across all four comparisons (large, medium, and small cysts, as well as minimally cystic tissue as compared to healthy tissue from nephrectomized kidneys respectively). In addition we re-analyzed a single-nucleus RNA sequencing (sn-RNA-Seq) dataset with the GEO accession number GSE185948, offering insights into the cellular heterogeneity of ADPKD [Muto et al., 2022]. Genes with a p-value < 0.05 were included as candidates in the analysis. Ultimately, the ADPKD phenotype molecular model was enriched with genes that were expressed in at least one cell type with absolute log2FC values > 2.5. In addition we retrieved information on genetic associations with ADPKD from the Open-Targets platform [Buniello et al., 2025]. Expression in healthy tissue and relevant renal cell types of molecular features of the ADPKD molecular model, quantified as normalized transcripts per million (nTPMs), were extracted from the Human Protein Atlas consensus expression profile dataset [Karlsson et al., 2021]. Information on subcellular location for features of the ADPKD molecular model was retrieved from UniProt [Ahmad et al., 2025]. Finally, we assigned molec-

ular features of the ADPKD molecular model to mechanisms being discussed in recent reviews to be associated with ADPKD disease development and progression. Assignment of molecular features to mechanisms was done using the Gene Ontology (GO) annotation.

The final constructed ADPKD molecular model consisted of 263 molecular features that were connected by 1574 edges (**Supplementary datafile S1**). Edges in the constructed network consisted of direct protein-protein interactions consolidated from IntAct [Orchard et al., 2014], BioGRID [Oughtred et al., 2021], and Reactome [Milacic et al., 2024] as well as of literature sentence-level co-annotations of publications focusing on ADPKD using the catalogs of molecular features and phenotypes as given in Delta4's Hyper-C software platform.

The constructed molecular model can now be used to explore the pathobiology of ADPKD by either filtering for (i) certain molecular mechanisms, (ii) individual cell types, (iii) the most up- or down-regulated genes in renal tissue or specific cell types, (iv) the most central genes based on graph properties like node degree or betweenness among others. Figure 1 for example shows genes of the Wnt signaling pathway (in green for positive modulation of the pathway, red for negative modulation of the pathway, dark blue for modulation of the pathway, and light blue for genes being pathway members without any further information on regulation) as well as additional molecules being associated with ADPKD that are linked to members of the Wnt signaling pathway (in grey) via either protein-protein interactions or co-annotations in the context of ADPKD. This network view allows investigating interesting novel connections of Wnt signaling pathway members with ADPKD-associated proteins.

The molecular model can subsequently also be used to (i) screen for compounds showing beneficial impact on dysregulated disease mechanisms as shown previously in other renal diseases [Gebeshuber et al., 2023], (ii) identify drug targets of interest, investigate cell-cell interaction analysis to identify relevant receptor-ligand pairs following previously reported analyses [Evgeniou et al., 2021], or (iii) prioritize drug targets for the development of new chemical entities.

4   Conclusion

We have developed Graph Lens Lite for visualizing, exploring and sharing biological networks. GLL is designed for portability with a focus on extensive visual customization. The entire application, together with an average sized graph containing approximately 1000 nodes, can be packed into an archive of only a few megabytes. Unlike comparable tools that may require installation, GLL requires only a web browser for core functionality. GLL is distributed as platform-specific Electron bundles for Windows, macOS, and Linux, as well as a platform-independent, self-contained HTML file. This minimal distribution enables users to load demonstration data or create and work with templates without external dependencies or API calls, ensuring long-term stability and offline operation.

Acknowledgments

The authors want to thank all working group members of the EU COST Action Program PerMediK (Personalized Medicine in Chronic Kidney Disease: Improved outcome based on Big Data) for fruitful discussions during the regular COST Action project meetings.

Author contributions

M.L.: conceptualization; resources; software; visualization; writing - original draft, review & editing. K.K.-I.: data curation; validation; writing - review & editing. L.F.: validation; writing - review & editing. S.W.: validation; writing - review & editing. F.B.: validation; writing - review & editing. E.B.: validation; writing - review & editing. L.G.: validation; writing -

review & editing. P.A.: validation; writing - review & editing. P.H.: data curation; validation; writing - review & editing. J.L.: data curation; funding acquisition; validation; writing - review & editing. P.P.: conceptualization; data curation; funding acquisition; supervision; validation; writing - original draft, review & editing. K.K.: funding acquisition; supervision; validation; writing - review & editing.

Supplementary data

Supplementary datafile S1: The ADPKD molecular model input file

Conflict of interest

K.K. is a co-founder of Delta4 GmbH (Vienna, Austria). M.L., K.K.-I., L.F., S.W., F.B., E.B., L.G., P.A., and P.P. are employed at Delta4 GmbH (Vienna, Austria).

Funding

This project has received funding from the Austrian Research Promotion Agency (FFG) under grant agreement number 915133 (ADPKD Drug Discovery). Enrico Bono is supported by a grant from the European Union's Horizon Europe Marie Skłodowska-Curie Actions Doctoral Networks program project PICKED (HORIZON–MSCA–2023–DN-01, grant number 101168626). Louiza Galou is supported by a grant from the European Union's Horizon Europe Marie Skłodowska-Curie Actions Doctoral Networks Industrial Doctorates program project PROMOTE (HORIZON–MSCA–2023– DN-01, grant number 101169245). Paul Perco and Matthias Ley are members of and would like to cordially thank the EU COST Action Program PerMediK, CA21165, supported by COST (European Cooperation in Science and Technology).

Data availability

The source code, test data, templates and documentation are available at GitHub (`https://github.com/Delta4AI/GraphLensLite`).

References

Henry Ehlers, Nicolas Brich, Michael Krone, Martin Nöllenburg, Jiacheng Yu, Hiroaki Natsukawa, Xiaoru Yuan, and Hsiang-Yun Wu. An introduction to and survey of biological network visualization. *Computers & Graphics*, 126:104115, February 2025. ISSN 00978493. doi: 10.1016/j.cag.2024.104115.

Paul Shannon, Andrew Markiel, Owen Ozier, Nitin S. Baliga, Jonathan T. Wang, Daniel Ramage, Nada Amin, Benno Schwikowski, and Trey Ideker. Cytoscape: A Software Environment for Integrated Models of Biomolecular Interaction Networks. *Genome Research*, 13(11):2498–2504, January 2003. ISSN 1088-9051, 1549-5469. doi: 10.1101/gr.1239303.

Mathieu Bastian, Sebastien Heymann, and Mathieu Jacomy. Gephi: An Open Source Software for Exploring and Manipulating Networks. *Proceedings of the International AAAI Conference on Web and Social Media*, 3(1):361–362, March 2009. ISSN 2334-0770. doi: 10.1609/icwsm.v3i1.13937.

Damian Szklarczyk, Katerina Nastou, Mikaela Koutrouli, Rebecca Kirsch, Farrokh Mehryary, Radja Hachilif, Dewei Hu, Matteo E Peluso, Qingyao Huang, Tao Fang, Nadezhda T

Doncheva, Sampo Pyysalo, Peer Bork, Lars J Jensen, and Christian von Mering. The STRING database in 2025: Protein networks with directionality of regulation. *Nucleic Acids Research*, 53(D1):D730–D737, January 2025. ISSN 1362-4962. doi: 10.1093/nar/gkae1113.

Guangyan Zhou, Zhiqiang Pang, Yao Lu, Jessica Ewald, and Jianguo Xia. OmicsNet 2.0: A web-based platform for multi-omics integration and network visual analytics. *Nucleic Acids Research*, 50(W1):W527–W533, July 2022. ISSN 0305-1048. doi: 10.1093/nar/gkac376.

Keiichiro Ono, Dylan Fong, Chengzhan Gao, Christopher Churas, Rudolf Pillich, Joanna Lenkiewicz, Dexter Pratt, Alexander R Pico, Kristina Hanspers, Yihang Xin, John Morris, Mike Kucera, Max Franz, Christian Lopes, Gary Bader, Trey Ideker, and Jing Chen. Cytoscape Web: Bringing network biology to the browser. *Nucleic Acids Research*, 53(W1): W203–W212, July 2025. ISSN 0305-1048, 1362-4962. doi: 10.1093/nar/gkaf365.

Chiara Formica and Dorien J.M. Peters. Molecular pathways involved in injury-repair and ADPKD progression. *Cellular Signalling*, 72:109648, August 2020. ISSN 08986568. doi: 10.1016/j.cellsig.2020.109648.

Xuewen Song, Valeria Di Giovanni, Ning He, Kairong Wang, Alistair Ingram, Norman D. Rosenblum, and York Pei. Systems biology of autosomal dominant polycystic kidney disease (ADPKD): Computational identification of gene expression pathways and integrated regulatory networks. *Human Molecular Genetics*, 18(13):2328–2343, July 2009. ISSN 1460-2083, 0964-6906. doi: 10.1093/hmg/ddp165.

Yoshiharu Muto, Eryn E. Dixon, Yasuhiro Yoshimura, Haojia Wu, Kohei Omachi, Nicolas Ledru, Parker C. Wilson, Andrew J. King, N. Eric Olson, Marvin G. Gunawan, Jay J. Kuo, Jennifer H. Cox, Jeffrey H. Miner, Stephen L. Seliger, Owen M. Woodward, Paul A. Welling, Terry J. Watnick, and Benjamin D. Humphreys. Defining cellular complexity in human autosomal dominant polycystic kidney disease by multimodal single cell analysis. *Nature Communications*, 13(1):6497, October 2022. ISSN 2041-1723. doi: 10.1038/s41467-022-34255-z.

Annalisa Buniello, Daniel Suveges, Carlos Cruz-Castillo, Manuel Bernal Llinares, Helena Cornu, Irene Lopez, Kirill Tsukanov, Juan María Roldán-Romero, Chintan Mehta, Luca Fumis, Graham McNeill, James D Hayhurst, Ricardo Esteban Martinez Osorio, Ehsan Barkhordari, Javier Ferrer, Miguel Carmona, Prashant Uniyal, Maria J Falaguera, Polina Rusina, Ines Smit, Jeremy Schwartzentruber, Tobi Alegbe, Vivien W Ho, Daniel Considine, Xiangyu Ge, Szymon Szyszkowski, Yakov Tsepilov, Maya Ghoussaini, Ian Dunham, David G Hulcoop, Ellen M McDonagh, and David Ochoa. Open Targets Platform: Facilitating therapeutic hypotheses building in drug discovery. *Nucleic Acids Research*, 53(D1):D1467–D1475, January 2025. ISSN 1362-4962. doi: 10.1093/nar/gkae1128.

Max Karlsson, Cheng Zhang, Loren Méar, Wen Zhong, Andreas Digre, Borbala Katona, Evelina Sjöstedt, Lynn Butler, Jacob Odeberg, Philip Dusart, Fredrik Edfors, Per Oksvold, Kalle Von Feilitzen, Martin Zwahlen, Muhammad Arif, Ozlem Altay, Xiangyu Li, Mehmet Ozcan, Adil Mardinoglu, Linn Fagerberg, Jan Mulder, Yonglun Luo, Fredrik Ponten, Mathias Uhlén, and Cecilia Lindskog. A single–cell type transcriptomics map of human tissues. *Science Advances*, 7(31):eabh2169, July 2021. ISSN 2375-2548. doi: 10.1126/sciadv.abh2169.

Shadab Ahmad, Leonardo Jose da Costa Gonzales, Emily H Bowler-Barnett, Daniel L Rice, Minjoon Kim, Supun Wijerathne, Aurélien Luciani, Swaathi Kandasaamy, Jie Luo, Xavier Watkins, Edd Turner, Maria J Martin, the UniProt Consortium, Alex Bateman, Maria-Jesus Martin, Sandra Orchard, Michele Magrane, Shiqi Ye, Aduragbemi Adesina, Shadab Ahmad, Emily H Bowler-Barnett, David Carpentier, Paul Denny, Jun Fan, Leonardo Jose Da Costa Gonzales, Abdulrahman Hussein, Alexandr Ignatchenko, Giuseppe Insana, Rizwan

Ishtiaq, Vishal Joshi, Dushyanth Jyothi, Swaathi Kandasaamy, Antonia Lock, Aurelien Luciani, Jie Luo, Yvonne Lussi, Juan Sebastian Martinez Marin, Pedro Raposo, Daniel L Rice, James Stephenson, Prabhat Totoo, Nadya Urakova, Preethi Vasudev, Supun Wijerathne, Khawaja Talal Ibrahim, Minjoon Kim, Conny Wing-Heng Yu, Alan J Bridge, Lucila Aimo, Ghislaine Argoud-Puy, Andrea H Auchincloss, Kristian B Axelsen, Parit Bansal, Delphine Baratin, Teresa M Batista Neto, Marie-Claude Blatter, Jerven T Bolleman, Emmanuel Boutet, Lionel Breuza, Cristina Casals-Casas, Kamal Chikh Echioukh, Elisabeth Coudert, Beatrice Cuche, Edouard De Castro, Anne Estreicher, Maria L Famiglietti, Marc Feuermann, Elisabeth Gasteiger, Pascale Gaudet, Sebastien Gehant, Vivienne Gerritsen, Arnaud Gos, Nadine Gruaz, Chantal Hulo, Nevila Hyka-Nouspikel, Florence Jungo, Arnaud Kerhornou, Philippe Le Mercier, Damien Lieberherr, Patrick Masson, Anne Morgat, Salvo Paesano, Ivo Pedruzzi, Sandrine Pilbout, Lucille Pourcel, Sylvain Poux, Monica Pozzato, Manuela Pruess, Nicole Redaschi, Catherine Rivoire, Christian J A Sigrist, Karin Sonesson, Shyamala Sundaram, Anastasia Sveshnikova, Cathy H Wu, Chuming Chen, Hongzhan Huang, Kati Laiho, Minna Lehvaslaiho, Peter McGarvey, Darren A Natale, Karen Ross, C R Vinayaka, Yuqi Wang, Raja Mazumder, Vijay Shanker, and Jian Zhang. The UniProt website API: Facilitating programmatic access to protein knowledge. *Nucleic Acids Research*, 53(W1):W547–W553, July 2025. ISSN 0305-1048, 1362-4962. doi: 10.1093/nar/gkaf394.

Sandra Orchard, Mais Ammari, Bruno Aranda, Lionel Breuza, Leonardo Briganti, Fiona Broackes-Carter, Nancy H. Campbell, Gayatri Chavali, Carol Chen, Noemi del-Toro, Margaret Duesbury, Marine Dumousseau, Eugenia Galeota, Ursula Hinz, Marta Iannuccelli, Sruthi Jagannathan, Rafael Jimenez, Jyoti Khadake, Astrid Lagreid, Luana Licata, Ruth C. Lovering, Birgit Meldal, Anna N. Melidoni, Mila Milagros, Daniele Peluso, Livia Perfetto, Pablo Porras, Arathi Raghunath, Sylvie Ricard-Blum, Bernd Roechert, Andre Stutz, Michael Tognolli, Kim Van Roey, Gianni Cesareni, and Henning Hermjakob. The MIntAct project—IntAct as a common curation platform for 11 molecular interaction databases. *Nucleic Acids Research*, 42(D1):D358–D363, January 2014. ISSN 0305-1048, 1362-4962. doi: 10.1093/nar/gkt1115.

Rose Oughtred, Jennifer Rust, Christie Chang, Bobby-Joe Breitkreutz, Chris Stark, Andrew Willems, Lorrie Boucher, Genie Leung, Nadine Kolas, Frederick Zhang, Sonam Dolma, Jasmin Coulombe-Huntington, Andrew Chatr-Aryamontri, Kara Dolinski, and Mike Tyers. The BioGRID database: A comprehensive biomedical resource of curated protein, genetic, and chemical interactions. *Protein Science: A Publication of the Protein Society*, 30(1):187–200, January 2021. ISSN 1469-896X. doi: 10.1002/pro.3978.

Marija Milacic, Deidre Beavers, Patrick Conley, Chuqiao Gong, Marc Gillespie, Johannes Griss, Robin Haw, Bijay Jassal, Lisa Matthews, Bruce May, Robert Petryszak, Eliot Ragueneau, Karen Rothfels, Cristoffer Sevilla, Veronica Shamovsky, Ralf Stephan, Krishna Tiwari, Thawfeek Varusai, Joel Weiser, Adam Wright, Guanming Wu, Lincoln Stein, Henning Hermjakob, and Peter D'Eustachio. The Reactome Pathway Knowledgebase 2024. *Nucleic Acids Research*, 52(D1):D672–D678, January 2024. ISSN 0305-1048. doi: 10.1093/nar/gkad1025.

Christoph A. Gebeshuber, Lisa Daniel-Fischer, Heinz Regele, Helga Schachner, Christoph Aufricht, Christoph Kornauth, Matthias Ley, Seth L. Alper, Rebecca Herzog, Klaus Kratochwill, and Paul Perco. Computational drug repositioning of clopidogrel as a novel therapeutic option for focal segmental glomerulosclerosis. *Translational Research*, 259:28–34, September 2023. ISSN 1931-5244. doi: 10.1016/j.trsl.2023.04.001.

Michail Evgeniou, Juan Manuel Sacnun, Klaus Kratochwill, and Paul Perco. A Meta-Analysis of Human Transcriptomics Data in the Context of Peritoneal Dialysis Identifies Novel Receptor-Ligand Interactions as Potential Therapeutic Targets. *International Journal of Molecular Sciences*, 22(24):13277, December 2021. ISSN 1422-0067. doi: 10.3390/ijms222413277.