ChatSpatial: Schema-Enforced Agentic Orchestration for Reproducible and Cross-Platform Spatial Transcriptomics

Chen Yang[1], Xianyang Zhang[1*], Jun Chen[2*]

[1*]Department of Statistics, Texas A&M University, College Station, Texas, 77843, USA.
[2]Division of Computational Biology, Department of Quantitative Health Sciences, Mayo Clinic, Rochester, Minnesota, 55905, USA.

*Corresponding author(s). E-mail(s): zhangxiany@stat.tamu.edu; Chen.Jun2@mayo.edu;
Contributing authors: cafferychen777@tamu.edu;

Abstract

Spatial transcriptomics has transformed our ability to study tissue architecture at molecular resolution, yet analyzing these data demands navigating dozens of computational methods across incompatible Python and R ecosystems—forcing researchers to devote more effort to making tools function than to pursuing biological questions. We present ChatSpatial, a platform in which the LLM selects from pre-validated tool schemas rather than generating free-form code, with domain expertise embedded in schema descriptions for context-aware parameter inference. Built on the Model Context Protocol (MCP), ChatSpatial unifies 60+ methods across 15 analytical categories into a single conversational workflow spanning Python and R ecosystems. Replication of two published studies—recovering subclonal heterogeneity in ovarian cancer and tumor microenvironment organization in oral squamous cell carcinoma—and validation across seven LLM platforms demonstrate that schema-enforced orchestration yields near-deterministic reproducibility at the workflow level for multi-step spatial analyses. Beyond replication, exploratory cross-method analyses illustrate practical triangulation across independent analytical frameworks.

Keywords: spatial transcriptomics, artificial intelligence, bioinformatics integration, natural language processing, computational biology, software platform, cancer research, MCP, agentic orchestration

1 Introduction

Spatial transcriptomics is transforming biology by revealing how cellular identity and function are shaped by tissue architecture [1, 2]. Yet while spatial technologies generate data at an unprecedented scale, the technical expertise required to integrate fragmented computational ecosystems has become the rate-limiting step for discovery. The widespread adoption of platforms like 10x Genomics Visium has shifted the primary bottleneck from data acquisition to computational analysis, leading to a rapid proliferation of analytical tools [3]. This growth, however, has produced a fragmented ecosystem divided between Python and R—built on incompatible data objects (AnnData [4] and Seurat [5])—that translates into practical, time-consuming hurdles for biomedical researchers.

Consider a cancer biologist who wishes to identify spatial domains using SpaGCN (Python) and then analyze cell-cell communication using CellChat (R). This straightforward scientific goal requires managing conflicting software environments, writing custom data conversion scripts, and manually integrating outputs—a significant barrier for researchers without specialized programming expertise. A recent Comment in *Nature Biotechnology* identified similar issues—fragmented documentation, lack of reproducibility, and high technical barriers—as primary obstacles to adopting computational tools in single-cell biology [6].

Recent reviews have identified computational analysis as "a major challenge facing spatial transcriptomics," noting that tools are "often difficult to evaluate and apply" due to algorithmic complexity and the requirement for coding expertise [7, 8]. To address these barriers, several strategies have emerged: "bridge" tools for cross-ecosystem data conversion (e.g., `zellkonverter`), and more recently, LLM-powered systems ranging from interactive co-pilots [9, 10] to multimodal semantic exploration tools [11] to fully autonomous agents [12, 13]. However, autonomous agents pose reproducibility challenges due to non-deterministic code generation, while co-pilots typically assist with specific tasks within a single ecosystem. This leaves an important gap for researchers who need a system that combines the flexibility of natural language with the control and reproducibility required for complex, cross-platform workflows.

Here, we present ChatSpatial, a platform built on **schema-enforced orchestration**: the LLM selects from pre-validated tool schemas rather than generating free-form code, improving reproducibility at the workflow level in a domain where traditional LLM code generation exhibits substantial hallucination rates [14–16]. Our contribution is threefold: (1) schema-enforced orchestration as an architectural paradigm—built on the Model Context Protocol (MCP) [17]—in which the LLM acts as a reliable orchestrator rather than an autonomous agent or code generator, with domain expertise embedded directly in schema descriptions for context-aware parameter inference (Methods §4.1); (2) a comprehensive cross-ecosystem implementation unifying 60+ methods across Python and R through a single conversational workflow, eliminating the technical overhead of environment management and data conversion; and (3) systematic validation through replication of two published spatial transcriptomics studies and cross-model reproducibility experiments across seven LLM platforms. This design allows researchers with basic command-line familiarity to execute end-to-end spatial

analyses through natural language, enabling iterative exploration while keeping the scientist in full control.

Unlike fully autonomous systems that prioritize end-to-end automation [12, 13], ChatSpatial is designed for human-steered discovery—prioritizing analytical fidelity and reproducibility while the researcher retains strategic control (Table 1). In this work, we demonstrate how this approach enables complex cross-platform analytical strategies through a conversational workflow.

Table 1 Comparison of analysis paradigms for spatial transcriptomics: conversational orchestration, GUI-based platforms, and direct programming.

Aspect of Workflow	ChatSpatial (Conversational Orchestration)	GUI-Based Platforms (e.g., Loupe Browser, Giotto Viewer)	Traditional Workflow (Direct Programming in Python/R)
Primary Unit of Interaction	A high-level scientific goal (e.g., "Find spatial domains")	A menu-driven selection or button click (e.g., select clustering algorithm)	A specific line of code (e.g., `sc.tl.leiden(adata)`)
Cognitive Focus of User	Biological hypothesis and interpretation of results	Navigation of software interface and understanding of available options	Correct syntax, library versions, and data object manipulation
Handling Multi-Step Analysis	Fluid conversation where context is maintained by the agent	Limited to workflows supported by the platform; multi-tool chaining often unavailable	Manual scripting, requiring the user to manage state and data flow
Cross-Language Integration (e.g., Python to R)	Automated and hidden from the user. The agent manages data conversion internally.	Generally confined to a single ecosystem (Python or R); interoperability not supported	Manual and error-prone. Requires writing explicit export/import scripts (e.g., via `zellkonverter`).
Parameter Selection	Agent suggests best practices based on dialogue and data context	Exposed through interface controls with platform-set defaults	User must manually look up and specify parameters in code
Source of Reproducibility	The immutable log of the scientific conversation	Session logs or exported configuration files, where available	User-maintained script files and environment configurations (`requirements.txt`, `renv.lock`)
Role of Foundational Libraries (Scanpy, Seurat, etc.)	Act as reliable, versioned execution engines orchestrated by the agent.	Bundled internally; user interacts through the GUI layer	Act as the direct, code-level interface for the user.

2 Results

2.1 Overview of the ChatSpatial Platform

ChatSpatial transforms spatial transcriptomics analysis from a programming challenge into a scientific conversation (Figure 1a). All case study analyses and the 28 validation scenarios were conducted using a single LLM (Claude Sonnet 4.5 [18], model ID claude-sonnet-4-5-20250929) to ensure consistency; the cross-model experiments in §2.3 additionally tested Gemini 2.5 Flash and GPT-5 Mini to assess model-agnostic reproducibility. The platform coordinates 60+ methods across 15 major analytical categories, including data preprocessing, integration, cell type annotation, spatial domain

Fig. 1 ChatSpatial eliminates the implementation tax in spatial transcriptomics analysis through MCP-based tool orchestration. (**a**) Schema-enforced orchestration versus traditional code generation. Top: conventional LLM approaches generate free-form code with stochastic outputs, leading to low reproducibility due to hallucinated functions and incompatible API calls. Bottom: ChatSpatial constrains LLM outputs to pre-validated tool schemas via the Model Context Protocol (MCP), ensuring that user intent maps to defined parameter spaces with high reproducibility. (**b**) System architecture and multi-platform integration. User queries pass through the ChatSpatial API to an LLM orchestrator, which invokes tools via the MCP Protocol and Server layer. Automated object conversion (rpy2) bridges the Python environment (AnnData, Scanpy, Squidpy) and R environment (Seurat, CellChat, SingleCellExperiment), enabling seamless cross-ecosystem workflows. (**c**) Analytical toolkit spanning 9 major categories and 60+ methods: cell type annotation (SingleR, Tangram, scANVI, CellAssign, scType, MLLM-CellType), spatial domain identification (SpaGCN, STAGATE, Leiden/Louvain), spatially variable expression (SPARK-X, FlashS, SpatialDE), spatial deconvolution (FlashDeconv, Cell2location, CARD, DestVI, Stereoscope, Spotlight, Tangram), differential expression (Wilcoxon, t-test, pyDESeq2), pathway enrichment (ORA, GSEA, ssGSEA), cell-cell communication (CellChat, LIANA, CellPhoneDB, FastCCC), spatial statistics (Moran's I, Getis-Ord, Ripley's K, LISA, neighborhood enrichment), and trajectory & velocity (CellRank, Palantir, DPT, scVelo, VeloVI). (**d**) Conversational workflow in practice. An iterative discovery loop demonstrates three sequential prompts—data loading with QC, spatial domain identification, and ligand-receptor analysis—producing publication-quality results and biological insights (e.g., CAF→Cancer interactions) without manual scripting.

identification, cell communication, and deconvolution (Figure 1b–c). By accepting natural language queries, ChatSpatial enables an iterative conversational workflow that executes complex cross-ecosystem pipelines without requiring users to implement the underlying integration code (Figure 1d). This interaction model shifts the user's focus from technical implementation to biological interpretation.

These analytical categories reflect established frameworks for spatial transcriptomics computational analysis [3, 19]. Method selection within each category prioritized benchmark-validated performance [20–24], broad community adoption [25–28],

and computational efficiency for large datasets [29, 30]. Multiple complementary methods are deliberately included within each category to accommodate distinct data modalities (e.g., with versus without histology images) and algorithmic approaches, enabling users to either receive context-aware recommendations from the platform or perform comparative analyses across methods.

Table 2 Platform compatibility matrix: analytical module support across spatial transcriptomics technologies. **Legend:** ✓✓ = Optimized/Recommended, ✓ = Supported, ○ = Optional, − = Not Required/Not Applicable. Cell-resolution technologies (MERFISH, Xenium, seqFISH, CosMx) do not require deconvolution as they provide native single-cell data. Spot-based platforms (Visium, Slide-seq) benefit from deconvolution to infer cell-type compositions. All modules support standard H5AD format with optional spatial coordinates stored in `adata.obsm['spatial']`.

Analytical Module	Visium	Visium HD	MERFISH/ Xenium	seqFISH/ CosMx	Slide-seq	STARmap
Preprocessing	✓	✓	✓	✓	✓	✓
Multi-Sample Integration	✓	✓	✓	✓	✓	✓
Cell Type Annotation	✓	✓	✓	✓	✓	✓
Differential Expression	✓	✓	✓	✓	✓	✓
Spatial Domain ID	✓✓	✓	✓	✓	✓	✓
Spatial Variable Genes	✓	✓	✓	✓	✓	✓
Cell Communication	✓	✓	✓✓	✓✓	✓	✓
Deconvolution	✓✓	○	−	−	○	○
CNV Analysis	✓	✓	✓	✓	✓	✓
Trajectory Analysis	✓	✓	✓✓	✓✓	✓	✓
RNA Velocity	✓	✓	✓	✓	✓	✓
Enrichment Analysis	✓	✓	✓	✓	✓	✓

The platform's conversational interface maintains stateful context across analytical steps. A user can initiate a multi-step workflow with: *"Identify spatial domains in this breast cancer Visium sample, annotate the cell types using an scRNA-seq reference, and find genes marking the tumor-stroma boundary,"* then follow up with *"Now, zoom into domain 3 and perform cell communication analysis"* without re-specifying the dataset. This paradigm extends to method selection: when a user requests *"identify spatial domains"*, the platform recommends the most suitable method based on data characteristics (e.g., SpaGCN for Visium with histology, STAGATE without), while the researcher retains full control to direct comparative analyses across methods. A comprehensive set of example interactions is provided in Supplementary Table S2.

2.2 Case Studies: Replication and Exploratory Analysis

To validate ChatSpatial's ability to replicate expert-level analytical workflows, and to illustrate how schema-enforced orchestration enables hypothesis-generating exploration, we applied it to two published studies representing distinct biological challenges: high-resolution tumor microenvironment analysis and multi-sample cohort characterization.

Fig. 2 ChatSpatial replicates published OSCC tumor architecture analysis through conversational orchestration. (**a, b**) H&E tissue sections of two representative OSCC samples (Sample 1 and Sample 9 from GSE208253) with spatial domain annotations: Tumor Core (TC, blue) and Leading Edge (LE, orange). Spatial domains were identified by Leiden clustering on spatially-aware neighbor graphs and classified using marker gene scoring. (**c**) Spatial deconvolution map (Sample 1) showing fibroblast/CAF proportion at each Visium spot (FlashDeconv with HNSCC scRNA-seq reference [31]), revealing fibroblast concentration at the leading edge. (**d**) Per-sample cell type enrichment between TC and LE across all 12 samples. Color indicates $\log_2$ fold change (LE/TC); cells marked "n.s." are non-significant (Mann–Whitney U test, BH-FDR $q \geq 0.05$). (**e**) Consensus enrichment summary. Dashed line: 75% threshold ($\geq 9/12$ samples). Macrophages (11/12, 92%) and fibroblasts (10/12, 83%) show robust LE enrichment; cancer cells are TC-enriched (7/12, 58%). (**f**) CellChat ligand-receptor analysis identifying top Fibroblast→Cancer interactions colored by signaling pathway. Directional ECM-syndecan signaling (COL1A1→SDC1, FN1→SDC1) recapitulates the original study's mechanistic conclusion [32]. (**g**) Spatial expression of *FN1* (Sample 1), confirming localization of the CellChat-identified ligand to the LE domain. (**h**) Moran's I spatial autocorrelation for key TC and LE marker genes (Sample 1, 3,000 highly variable genes tested). TC markers *SPRR1B* (rank 6, $I = 0.54$) and LE markers *COL1A1* (rank 20, $I = 0.50$) and *FN1* (rank 23, $I = 0.49$) all rank in the top 1% of spatially variable genes.

2.2.1 Oral Cancer: Tumor Architecture and Cell-Cell Communication

We replicated the analytical workflow from a recent study by Arora et al. [32]. This study characterized the distinct transcriptional architectures of the Tumor Core (TC) and Leading Edge (LE) in oral squamous cell carcinoma (OSCC). The original authors employed a rigorous multi-step pipeline involving cohort integration, unsupervised spatial domain identification, reference-based deconvolution, and ligand-receptor analysis. We sought to replicate this workflow using ChatSpatial's conversational interface.

Step 1: Unsupervised Spatial Domain Discovery and Cohort Integration

The workflow began with identifying the primary spatial domains. To accurately replicate the study's cohort-level analysis, we directed the platform to process all 12 patient samples simultaneously: *"Load all 12 OSCC samples, filter low-quality spots (<200 genes), and identify spatial domains using Leiden clustering with spatially-aware neighbor graphs."* This single instruction coordinated the complex ingestion of the entire cohort and performed unsupervised spatial domain identification on each sample. We note that the original study employed Louvain clustering with Seurat's CCA-based integration on malignant spots only, whereas ChatSpatial used Leiden clustering on combined transcriptomic and spatial neighbor graphs across all spots—a methodological difference that did not alter the key biological conclusions, as demonstrated by the concordance analysis below.

Following the unsupervised clustering performed by the platform, we examined the top marker genes retrieved by the agent. This enabled the precise biological annotation of three distinct states described in the original study: a Tumor Core (TC) enriched for keratinization and epithelial differentiation markers (e.g., *SPRR1B*, *CLDN4*, *SPRR2E*), a Transitory state marked by *KRT6C*, and a Leading Edge (LE) enriched for partial-EMT and invasion markers (e.g., *FN1*, *LAMC2*, *ITGA5*). The molecular signatures generated by the pipeline precisely matched the definitions established by Arora et al.

Step 2: Deconvolution Reveals Conserved Microenvironment Composition

Next, to reproduce the cellular composition analysis, we performed deconvolution using the same reference dataset used in the original study. We prompted: *"Deconvolve cell types in the identified TC and LE domains using FlashDeconv, utilizing the HNSCC single-cell reference from Puram et al."* [31]. This command triggered the retrieval and processing of the specific scRNA-seq reference and executed FlashDeconv across the spatial data.

The agent-generated results replicated the original consensus findings: the Leading Edge exhibited a distinct immune-stromal landscape compared to the Tumor Core. Specifically, ChatSpatial's analysis revealed robust enrichment of macrophages (11/12 samples, 92%) and fibroblasts/CAFs (10/12, 83%) in the LE region, with endothelial cells (8/12, 67%) and myocytes (7/12, 58%) showing consistent LE-directional enrichment below the 75% consensus threshold (Figure 2a–e). Cancer cells were TC-enriched in 7/12 samples (58%). The core "fibrovascular niche" at the invasion

front—characterized by the co-enrichment of fibroblasts and macrophages in the LE—was accurately recapitulated, matching the central finding of Arora et al. We note two methodological differences that affect quantitative comparisons. First, the use of FlashDeconv (a constrained regression approach) rather than CARD (a conditional autoregressive model) can alter estimated proportions for rarer cell types. Second, our enrichment analysis compares within-spot deconvolved proportions between TC and LE regions, whereas Arora et al. assessed cell type abundance in spots *neighboring* cancer spots—a spatial neighborhood approach that is more sensitive to low-abundance populations such as T cells. These differences explain the reduced enrichment signal for dendritic and T cells in our analysis. Nevertheless, the dominant stromal and immune signatures—fibroblasts and macrophages in the LE, cancer cells in the TC—were concordant across methods, demonstrating the platform's ability to recover the central biological conclusions despite methodological variation.

Step 3: Deciphering the Interaction Mechanism via Cross-Ecosystem Orchestration

Finally, we investigated the cell-cell communication networks driving this invasion. Following the original study's focus on tumor-stroma interactions, we utilized ChatSpatial's ability to invoke native R tools. We issued the command: *"Focus on the Leading Edge (LE) domain and perform cell communication analysis between CAFs and cancer cells using CellChat. Specifically, look for interactions involving ECM ligands."*

Through seamless cross-ecosystem invocation of the R-based CellChat package, the platform identified 142 significant Fibroblast→Cancer interactions spanning six signaling pathways (COLLAGEN, FN1, TENASCIN, THBS, LAMININ, and ADGRG). The top-ranked interactions—COL1A1→SDC1, COL1A2→SDC1, and FN1→SDC1—recapitulate the original study's mechanistic conclusion that directional ECM-syndecan signaling mediates tumor progression at the invasive front (Figure 2f). Spatial expression mapping of *FN1* confirmed its localization to the LE domain (Figure 2g).

Beyond Replication: Cross-Method Spatial Autocorrelation

To demonstrate how schema-enforced orchestration connects findings across independent analytical frameworks, we performed a follow-up that Arora et al. did not report: spatial autocorrelation analysis (Moran's I) to test whether the CellChat-identified ligands are also among the most spatially variable genes. With a single prompt— *"Run spatial autocorrelation on this sample and check whether FN1 and COL1A1 are spatially variable"*—the platform computed Moran's I across 3,000 highly variable genes in Sample 1 (squidpy; permutation-based p-values with Benjamini–Hochberg FDR correction). Both LE markers ranked in the top 1%: *COL1A1* (rank 20/3,000, $I = 0.50$, FDR < 0.05) and *FN1* (rank 23, $I = 0.49$). The TC markers showed similarly strong spatial patterning: *SPRR1B* ranked 6th overall ($I = 0.54$), with *SPRR2E* (rank 28, $I = 0.48$) and *KRT6C* (rank 32, $I = 0.47$) in the top 1.1%. This illustrates multi-tool

chaining in practice: connecting cell communication signatures to spatial gene expression rankings across two independent analytical frameworks through a single follow-up prompt (Figure 2g–h).

2.2.2 Ovarian Cancer: Multi-Sample Subclone and Microenvironment Analysis

To demonstrate ChatSpatial's capacity for complex, multi-sample analytical workflows, we replicated the core findings of a recent study by Denisenko et al. on high-grade serous ovarian carcinoma (HGSOC) [33]. The original study profiled eight patient samples spanning different chemotherapy response categories and used an intricate computational pipeline to identify tumor subclones and characterize their microenvironments. We reproduced this workflow on all eight patient samples (P1–P8) using ChatSpatial's conversational interface (Figure 3).

Step 1: Multi-Sample Integration and Tumor Identification

The workflow began with processing all eight patient samples. We prompted: *"Load the HGSOC Visium samples from GSE211956 and deconvolve cell types using RCTD with the study's scRNA-seq reference."* This single instruction triggered batch processing across the cohort, applying RCTD deconvolution [34] with the study's scRNA-seq reference (8 cell types in the publicly deposited version; the original study used a finer 12-type annotation that subdivided fibroblasts into 5 subtypes). The platform automatically identified tumor-enriched spots (RCTD tumor weight ≥ 0.15, following the original study's convention) across all samples, enabling systematic downstream analysis (Figure 3a,c).

Step 2: Subclone Discovery via Copy Number Inference

Next, we identified candidate subclonal populations through copy number inference. We prompted: *"For each sample, run inferCNV using low-tumor spots as the normal reference to identify regions with distinct copy number alteration profiles."* The platform executed inferCNV [35] per sample, using spots with low RCTD tumor weights (< 0.15) as the reference profile—a critical methodological detail from the original study. Leiden clustering on the inferred CNV matrix revealed multiple spatially distinct CNV clusters in all 8 patients (3–6 clusters per sample), consistent with the original study's finding of pervasive copy number heterogeneity across the HGSOC cohort (Figure 3b).

Step 3: Cross-Patient Microenvironment Comparison

Finally, we compared tumor microenvironments across patients. We asked: *"Summarize the cell type composition and tumor burden across all patients. Which patients show the highest genomic instability?"* The resulting cross-patient analysis revealed substantial heterogeneity in both tumor burden (ranging from 2% to 98% tumor-enriched spots) and genomic instability (mean CNV scores 0.012–0.024), with patients harboring the highest tumor fractions (P3, P7) also exhibiting the most complex subclonal architectures (Figure 3c–d). These patterns are consistent with the original

Fig. 3 ChatSpatial replicates published HGSOC subclone analysis through multi-sample conversational workflow. Replication of Denisenko et al. [33] using publicly available HGSOC Visium data (GSE211956, 8 patient samples: P1–P8). (**a**) Tumor cell fraction spatial maps from RCTD deconvolution across all patients. The publicly deposited scRNA-seq reference contains 8 consolidated cell types (the original study used a 12-type annotation with 5 fibroblast subtypes; see Methods). Color intensity indicates tumor fraction (yellow = low, red = high). Tumor-enriched spots (RCTD tumor weight ≥ 0.15) were identified for downstream analysis. (**b**) inferCNV-based copy number cluster mapping reveals spatially distinct CNV profiles across patients. Multiple CNV clusters (3–6 per patient) were identified in all 8 samples via Leiden clustering on the inferred CNV matrix, consistent with the original study's observation of genomic heterogeneity validated by whole-genome sequencing. Note: the original study used manual dendrogram-based splitting; automated Leiden clustering may yield different partition granularities. (**c**) Cell type composition across patients from RCTD deconvolution, showing variable proportions of tumor cells, macrophages, fibroblasts, T cells, B/plasma cells, endothelial cells, mesothelial cells, and myofibroblasts. (**d**) Quantitative summary of tumor burden (vermillion bars, left axis: percentage of tumor-enriched spots) and genomic instability (blue bars, right axis: mean CNV score) across patients, enabling cross-patient comparison of microenvironment dynamics. (**e**) Spatially variable gene ranking for patient P3 by Moran's I, with cell type marker genes (*CD14*, *KRT7*, *CDH5*; red) and CNV-cluster marker genes (blue) highlighted. Cell type markers rank in the top 2% of spatially variable genes, while CNV markers are dispersed across the distribution. (**f**) Comparison of Moran's I distributions between CNV-cluster marker genes and background genes (Mann–Whitney U test, $p = 0.07$; not significant), indicating that spatial organization in P3 is shaped more by microenvironment composition than by CNV-cluster identity.

study's observation that intra-tumor heterogeneity varies substantially across patients and may influence differential treatment response.

Beyond Replication: Cross-Method Spatial Analysis

To illustrate schema-enforced orchestration across analytical methods, we selected patient P3—the sample with the highest tumor burden (96% tumor-enriched spots) and four distinct CNV clusters—and used a single conversational prompt to perform spatial autocorrelation (Moran's I [36]) across 2,134 expressed genes. Cell type markers from the RCTD deconvolution—*CD14* (monocyte/macrophage, rank 16/2,134), *KRT7* (epithelial/tumor, rank 24), and *CDH5* (vascular endothelial, rank 39)—emerged among the top 2% of spatially variable genes (Moran's I, FDR-corrected $p < 0.05$ via Benjamini–Hochberg). In contrast, the 69 testable CNV-cluster marker genes (top 20 differentially expressed genes per cluster) showed no enrichment for spatial patterning relative to background (Mann–Whitney U test comparing Moran's I distributions, $p = 0.99$; $n_{\mathrm{markers}} = 69$, $n_{\mathrm{background}} = 2,065$). This is a single-sample observation with limited biological inference power; it does not establish that microenvironment composition generally dominates CNV-driven spatial organization in HGSOC. Rather, it demonstrates the feasibility of chaining deconvolution, CNV inference, and spatial statistics through conversational prompts—an exploratory analysis not reported in the original study (Figure 3e–f).

Together, these two case studies demonstrate that ChatSpatial can orchestrate complex, multi-tool analytical workflows—spanning spatial domain discovery, deconvolution, copy number inference, cell communication, and cross-cohort comparison—through a conversational workflow, achieving concordance with expert-curated published findings. Both case studies also demonstrate the feasibility of cross-method exploratory analyses: spatial autocorrelation tests, performed through single follow-up prompts, connected results across independent analytical frameworks—hypothesis-generating investigations that warrant further validation.

2.3 Interactive Reasoning and Platform Robustness

Beyond the case studies above, we systematically evaluated ChatSpatial's robustness across diverse analytical conditions and its reproducibility at the workflow level under controlled experimental settings.

To validate functional coverage across diverse analytical conditions, we evaluated the platform on 28 test scenarios covering four categories: data handling and pre-processing (5 scenarios), core spatial analysis (11 scenarios), conversational workflows (5 scenarios), and scalability stress tests (7 scenarios) (Supplementary Table S2). These scenarios spanned extreme data regimes—from low-density STARmap data (300 spots, 150 genes) to ultra-high-resolution Xenium datasets (930K+ cells)—as well as complex multi-sample integration (6 Visium slides requiring batch correction) and deliberate edge cases including invalid inputs, missing spatial coordinates, and ambiguous user commands. All 28 scenarios completed successfully through conversational interaction alone, without manual code intervention. In 3 of 28 scenarios involving ambiguous prompts (e.g., under-specified clustering resolution or generic "analyze the

data" commands), the LLM's initial parameter selection required one round of conversational refinement—demonstrating the value of the human-in-the-loop design over fully autonomous execution. We note that these 28 scenarios assess functional coverage rather than statistical reproducibility; the latter is addressed by the cross-model determinism experiment below.

Beyond functional validation, we assessed reproducibility at the workflow level through two complementary experiments. First, we conducted a cross-model determinism experiment. We presented eight representative analysis prompts—spanning spatial domain identification, deconvolution, SVG detection, cell communication, and CNV inference—to three LLMs (Gemini 2.5 Flash, Claude Haiku 4.5, GPT-5 Mini) with identical MCP tool schemas, repeating each prompt 10 times at temperature = 1.0 (maximum sampling stochasticity). We deliberately selected lighter-weight models for this experiment to test whether schema enforcement maintains consistency even with less capable LLMs; the case study analyses used the more capable Claude Sonnet 4.5. We measured three metrics: *tool selection consistency* (fraction of trials selecting the same tool as the mode), *constrained parameter consistency* (agreement rate on Literal-enumerated parameters such as method names), and *free-text parameter consistency* (agreement rate on unconstrained string inputs). Tool selection was 100% consistent across all 240 trials—an expected result given that each prompt was designed to map unambiguously to a single tool category; testing with deliberately ambiguous prompts (e.g., "help me understand the tissue organization") would likely reduce this consistency and represents a direction for future evaluation. Schema-constrained parameters showed 75.7% cross-model consistency, compared to 58.3% for free-text parameters, confirming that schema constraints substantially reduce—though do not eliminate—parameter variability across models. Per-model constrained parameter consistency ranged from 58.3% (GPT-5 Mini) to 100% (Claude Haiku 4.5), with Gemini 2.5 Flash at 68.8%. Full per-prompt breakdowns are provided in the reproducibility repository.

Second, to quantify the practical advantage of schema enforcement over free-form code generation, we presented the same eight prompts to the same three LLMs but asked them to write executable Python code instead of selecting from MCP tool schemas (240 total trials). To ensure a fair comparison, we report results separately for six Python-native tasks (spatial domains, SVG detection, Moran's I, visualization, trajectory, CNV inference) and two cross-ecosystem tasks (RCTD deconvolution, CellChat communication) where code generation faces an inherent disadvantage because the requested tools are R-only. On Python-native tasks alone, the two models that reliably generated code exhibited substantial syntax error rates: Gemini 2.5 Flash at 41.7% (25/60 trials produced unparseable code) and Claude Haiku 4.5 at 15.0% (9/60). Error rates were highest for multi-step analyses requiring chained library calls—trajectory inference (90% syntax errors for Gemini, 40% for Claude) and spatial autocorrelation (90%, 10%)—while simpler single-function tasks (SVG detection, visualization) achieved near-perfect syntax. Models also hallucinated non-existent packages: Gemini invented `pyrctd`, `pyCellChat`, and `spacemk`; Claude attempted to `import cellchat` (an R-only package with no Python counterpart). GPT-5 Mini failed to produce any code for 5 of 8 tasks. On cross-ecosystem tasks, all models either hallucinated Python wrappers for R-only tools or produced code that bypassed the

requested method entirely—a structural limitation that schema-enforced orchestration resolves by routing R-based methods through automated `rpy2` bridges invisible to both the LLM and the user. We note that this comparison represents a lower bound for code generation approaches, as providing the LLMs with documentation or few-shot examples (as in RAG-augmented systems like STAgent) would likely reduce error rates. Our comparison isolates the effect of schema enforcement versus unconstrained generation.

Performance scaling was validated across datasets ranging from 1,000 to 45,000 spots and up to 930K+ cells, spanning seven major spatial transcriptomics technologies: SPOTS, Visium, MERFISH [37], seqFISH [38], STARmap [39], Slide-seq [40], and Xenium. All analyses completed without out-of-memory errors or timeouts; execution time is dominated by the underlying tool (e.g., seconds for clustering, minutes for deconvolution) with negligible overhead from the MCP orchestration layer. Dataset accession numbers and sources are provided in the Data Availability section.

3 Discussion

Our central result is that schema-enforced orchestration can coordinate complex, cross-ecosystem spatial transcriptomics workflows with high reproducibility at the workflow level while keeping the researcher in strategic control. Rather than repeating implementation details, we focus here on what the case studies and architectural evaluation reveal about the strengths, boundaries, and future directions of this approach.

The replication of two published studies—spanning HGSOC subclonal heterogeneity and OSCC tumor architecture (§2.2)—demonstrates that conversational orchestration can achieve concordance with expert-curated pipelines without sacrificing analytical rigor. Critically, these workflows each required crossing the Python/R divide (FlashDeconv deconvolution in Python followed by CellChat in R; RCTD in R followed by inferCNV in Python), a task that traditionally demands substantial scripting effort. That a conversational workflow can coordinate these cross-ecosystem transitions— while maintaining data integrity and methodological fidelity—represents a meaningful step toward closing the gap between biological questions and computational answers.

This design reflects a broader principle: scientific discovery is iterative, yet traditional analysis imposes a disjointed cycle of planning, coding, and debugging that slows exploration. By removing implementation friction between analytical steps, ChatSpatial allows researchers to pursue follow-up questions as they emerge— *"What are the marker genes for this cluster?"* followed by *"Is there enrichment of any signaling pathway?"*—maintaining the natural rhythm of hypothesis-driven inquiry while the LLM handles technical execution.

A key consequence of low-friction tool chaining is that exploratory analyses become routine rather than exceptional. The "Beyond Replication" results in both case studies (§2.2) illustrate this: in each, a single follow-up prompt connected findings from one analytical framework to an independent spatial statistics method. These cross-method analyses were not planned *a priori* but emerged naturally from the conversational workflow—precisely the kind of exploratory analyses that implementation overhead might otherwise discourage.

ChatSpatial occupies a distinct position in the computational biology landscape through its philosophy of human-steered orchestration (Supplementary Table S3). Unlike fully autonomous agents such as STAgent [12] and SpatialAgent [13] that aim to replace the research workflow with minimal human input, ChatSpatial prioritizes reliability and reproducibility through schema-enforced execution via MCP. This design choice is supported by recent findings that current single-cell LLMs do not necessarily outperform traditional, task-specific methods across all benchmarks [6]. Our approach leverages the proven strengths of the existing ecosystem—orchestrating established, best-in-class tools—rather than attempting to replace them. Furthermore, unlike agents operating within a single programming ecosystem, ChatSpatial provides a unified interface over the fragmented R and Python environments, enabling cross-platform analytical strategies previously impractical due to language and toolchain fragmentation. Tools like CellWhisperer, which leverage learned multimodal embeddings for zero-shot semantic exploration, address a complementary challenge; we envision future integration where such models could operate as tools within ChatSpatial's orchestration framework.

We also note that our comparison in Table 1 focuses on programmatic workflows. GUI-based tools such as 10x Genomics Loupe Browser, Giotto Viewer, and web platforms like Galaxy offer accessible alternatives for specific analytical tasks. However, these tools typically cover a narrower analytical scope and do not support the kind of cross-ecosystem, multi-method chaining that ChatSpatial enables. The approaches are complementary: GUI tools excel at interactive visualization and targeted exploration, while ChatSpatial addresses the integration challenge across dozens of specialized methods spanning Python and R.

Despite these strengths, ChatSpatial has several limitations that define key areas for future work. First, the platform's performance is fundamentally linked to its core components: the LLM's reasoning ability and the underlying bioinformatics tools. The natural language interface, while powerful, can misinterpret ambiguous queries, and its parameter guidance currently relies on manually curated documentation. While our MCP-based architecture ensures the platform is LLM-agnostic and not locked into any single model provider, automated parameter optimization remains an exploratory direction that would require rigorous validation to ensure reliable quantitative exploration beyond curated defaults.

Second, while ChatSpatial eliminates cross-ecosystem integration complexity, its current command-line interface still requires familiarity with terminal environments and SSH connections. This positions the platform primarily for researchers with some computational background—domain experts comfortable with command-line tools and computational biologists seeking to accelerate their workflows. To extend accessibility to bench biologists and clinicians who generate spatial data but lack computational training, our immediate roadmap prioritizes the development of an open-source, web-based user interface. This browser-based deployment will remove the final technical barrier, fulfilling our broader goal of democratizing advanced spatial analysis.

Third, the conversational paradigm introduces practical trade-offs: LLM API calls add latency and cost compared to direct scripting, and sending dataset descriptions to external LLM providers raises data privacy considerations for sensitive clinical

datasets. Local model deployment could mitigate privacy concerns, though at a potential cost to reasoning quality.

Fourth, our case study validation relies on replication of published analyses, and we cannot exclude the possibility that the LLM's parameter choices were partly informed by exposure to these studies during pretraining. While the schema constraints limit the parameter space regardless of the model's prior knowledge, a blinded evaluation on unpublished datasets would provide stronger evidence of generalizability and remains an important direction for future work.

Fifth, while ChatSpatial integrates 60+ methods, tool selection inevitably reflects curatorial judgment. Notable methods not yet integrated (e.g., BayesSpace, Giotto) may be preferred for specific applications, and our inclusion criteria—benchmark-validated performance, community adoption, and cross-platform coverage—may not capture all emerging methods.

Sixth, although the schema-enforced architecture simplifies tool updates relative to code-generation approaches, maintaining compatibility with evolving upstream packages (e.g., API changes across major scanpy versions) requires ongoing wrapper maintenance—a practical consideration for long-term sustainability.

Finally, as an integration platform, the scientific validity of ChatSpatial's results ultimately depends on the quality and correctness of the community-developed tools it integrates. While our schema-enforced architecture mitigates errors from LLM hallucinations, the platform inherits the intrinsic strengths and weaknesses of the methods in its toolkit.

The growing complexity of spatial transcriptomics analysis has created a bottleneck, limiting discovery to computationally specialized labs. ChatSpatial addresses this by shifting the paradigm from tool-centric programming to science-centric conversation, using schema-enforced orchestration across the Python/R divide to make complex comparative analyses routine. By aligning computational analysis with the natural rhythm of scientific inquiry, ChatSpatial takes a step toward a future where discovery is driven by the depth of biological questions, not the mastery of code.

4 Methods

4.1 Architecture: Schema-Enforced Reproducibility via the Model Context Protocol

To address the critical challenge of computational reproducibility in LLM-driven science, ChatSpatial is built upon the Model Context Protocol (MCP) [17], an open standard developed by Anthropic that is increasingly being adopted for integrating complex scientific software. Unlike traditional agents that rely on LLMs to generate free-form code—a stochastic process prone to hallucinating non-existent functions or producing unparseable syntax (15–42% syntax error rates even on Python-native tasks in our baseline experiment, §2.3)—our architecture imposes a strict **schema-enforced execution model**.

Conceptually, this shifts the LLM's role from writing a "free-form essay" (code generation) to solving a "fill-in-the-blank" problem (parameter selection). We expose

60+ bioinformatics methods through 20 high-level MCP tools, where each tool represents an analytical category (e.g., `deconvolve_data`, `identify_spatial_domains`) and accepts a `method` parameter that routes to specific algorithm implementations. These tools are not open-ended prompts but rigidly defined interfaces with strict input/output schemas. For instance, when a user requests deconvolution, the LLM cannot invent a method name; it must select from a pre-validated enumeration (e.g., `Literal["rctd", "card", "cell2location"]`). This constraint mechanism effectively decouples the probabilistic nature of the LLM's reasoning (understanding intent) from the deterministic nature of the tool's execution (running the algorithm). Quantitatively, across the 20 MCP tools encompassing 441 total parameters, 358 (81.2%) are schema-constrained through Literal enumerations, numeric bounds, or default values; only 83 parameters (18.8%) accept free-text input, primarily dataset identifiers and column names that reference existing data structures rather than open-ended specifications.

By enforcing type safety and parameter validity *before* any code is executed, the MCP architecture eliminates common failure modes such as syntax errors and package incompatibilities. For fixed tool choices and parameter values, execution follows deterministic software paths under fixed package and environment versions; residual variability therefore resides mainly in the LLM's intent-to-parameter mapping, which schema constraints substantially narrow (81.2% of parameters are enumerated or bounded). In a cross-model determinism experiment (§2.3), tool selection was 100% consistent across 240 trials at temperature $= 1.0$, with schema-constrained parameters showing 75.7% consistency versus 58.3% for free-text inputs. The protocol is increasingly being adopted as an industry standard, with 10x Genomics [41] and Benchling [42] releasing official MCP integrations in 2025. Our implementation supports the 2025-03-26 MCP specification through the Python SDK (v1.17.0+). Further details on the protocol architecture and system prompts are provided in the Supplementary Methods (Section S1).

4.2 Integration Architecture and Method Abstraction

We integrated the full method library (Supplementary Table S1) through an MCP-based tool integration architecture designed to ensure both analytical fidelity and a consistent interface for the LLM agent. The architecture consists of three operational layers:

(1) MCP Tool Layer.

Each analysis function is registered as an MCP tool via the `@mcp.tool()` decorator, exposing it to the LLM with strict input/output schemas that enforce parameter validation and type safety.

(2) Method Dispatch Layer.

Registered tools perform data validation, coordinate management, and route requests to algorithm-specific implementations based on user-specified method parameters.

(3) Algorithm Wrapper Layer.

Method-specific wrappers handle data preparation (coordinate extraction, quality checks, format conversions), call the original software with appropriate parameters, and standardize outputs into consistent result objects.

For methods that are only available in R—such as CellChat for cell communication analysis—the wrapper layer utilizes `rpy2` to call R from within the Python-based server, automatically converting `AnnData` objects to `Seurat` objects and translating results back. This inter-language process is encapsulated within the wrapper and invisible to the user. A detailed example of this integration process for SpaGCN spatial domain identification is provided in the Supplementary Methods (Section S2).

4.3 Knowledge Injection via Protocol: Documentation-Driven Parameter Inference

Instead of relying on rigid rule-based engines or resource-intensive model fine-tuning, ChatSpatial implements a systematic "Knowledge Injection via Protocol" strategy. We embed expert biological knowledge directly into the MCP tool schemas, transforming the interface from a passive validation layer into an active guide for the LLM.

Specifically, every parameter field in our schema includes not only data type constraints but also rich, context-aware semantic descriptions accessible to the LLM. For instance, in the spatial graph construction tool (`build_spatial_graph`), the description for the `n_neighbors` parameter explicitly encodes technology-specific heuristics: *"For 10x Visium (hexagonal grid), recommended k=6 for immediate neighbors; for single-cell resolution platforms like MERFISH, recommended k=10-15 based on cell density; for Xenium, consider Delaunay triangulation for natural cell neighborhoods."* Similarly, the `clustering_resolution` parameter documentation embeds biological guidance: *"Higher values (1.5-2.0) produce more numerous, smaller clusters ideal for detecting rare cell types; lower values (0.2-0.5) produce fewer, broader clusters suitable for identifying major tissue domains."* These descriptions encode years of methodological benchmarking and biological expertise in a format directly interpretable by the LLM.

When the LLM processes a user request (e.g., "Analyze this MERFISH dataset"), it performs a three-step **in-context inference** process: (1) it *retrieves* the relevant tool schema from the MCP registry, (2) it *reads* the embedded parameter documentation to understand platform-specific requirements, and (3) it *infers* the optimal parameter values based on the dataset context. For example, upon detecting MERFISH data characteristics (high spatial resolution, single-cell precision), the LLM dynamically selects `n_neighbors=10` without hallucinating arbitrary values. This approach decouples domain knowledge from the model weights, allowing for a **lightweight and extensible** system where methodological best practices can be updated simply by modifying the schema descriptions—eliminating the need for costly model retraining when new spatial technologies emerge (e.g., Visium HD, CosMx). Further examples of our knowledge-rich schema documentation are provided in the Supplementary Methods (Section S3).

4.4 Error Handling and Recovery Mechanisms

ChatSpatial implements error handling designed for conversational interaction rather than silent recovery. The core design principle is that errors are converted into structured result objects and returned to the LLM, enabling it to observe failures and guide users toward solutions through natural language rather than requiring manual debugging. This is achieved through two key mechanisms: (1) a semantic exception hierarchy that categorizes errors by type (data issues, parameter errors, processing failures, dependency problems), enabling the LLM to provide targeted guidance; and (2) the `@mcp_tool_error_handler` decorator that wraps all MCP tools with type-aware error responses, maintaining protocol-level consistency while returning actionable diagnostic messages. Detailed implementation is provided in the Supplementary Methods (Section S4).

Acknowledgements

We thank the MCP development team at Anthropic for creating the framework that enables ChatSpatial's LLM-native architecture. We are grateful to Dr. Jade Wang (Department of Statistics, Texas A&M University) for valuable feedback and insightful suggestions on the design of the case study analyses. We thank Jiahao Mai (Southern Medical University) for assistance with figure design and visualization improvements.

Supplementary Information

Supplementary information is available for this paper. This includes Supplementary Methods, Supplementary Tables, and detailed documentation of integrated methods.

Data availability

All public datasets used for benchmarking and validation in this study are listed below and documented in a dedicated reproducibility repository (https://github.com/cafferychen777/ChatSpatial-Reproducibility):

- Oral Squamous Cell Carcinoma (OSCC) Visium dataset: GEO accession GSE208253 [32]
- High-Grade Serous Ovarian Carcinoma (HGSOC) Visium dataset: GEO accession GSE211956 [33]
- HNSCC single-cell reference: GEO accession GSE103322 [31]

Additional datasets used for platform validation (Section 2.3) include SPOTS (GSE198353), Visium multi-sample benchmarks (GSE254652, GSE243275), MER-FISH (GSE113576), seqFISH (GSE133244), STARmap (https://www.wangxiaolab.org/data-portal-1), Slide-seq (Broad Institute Single Cell Portal SCP354), and Xenium (10x Genomics public dataset). All datasets are publicly available, and no custom datasets were generated for this study.

Code availability

The source code for ChatSpatial is publicly available on GitHub under the MIT license at https://github.com/cafferychen777/ChatSpatial. Comprehensive documentation is hosted at https://cafferyang.com/ChatSpatial/. All analysis scripts used to generate the figures and results in this paper are available in the reproducibility repository at https://github.com/cafferychen777/ChatSpatial-Reproducibility.

Declarations

- Funding: The work is supported by the National Institute of Health R01GM144351 (Chen & Zhang), National Science Foundation DMS1830392, DMS2113359, DMS1811747 (Zhang), National Science Foundation DMS2113360, and Mayo Clinic Center for Individualized Medicine (Chen).

- Competing interests: The authors declare no competing interests.
- Ethics approval and consent to participate: Not applicable. This study only used publicly available datasets and did not involve human participants or animal experiments.
- Consent for publication: Not applicable.
- Author contributions: C.Y.: Conceptualization, Methodology, Software, Validation, Formal Analysis, Investigation, Data Curation, Writing – Original Draft, Visualization. X.Z.: Conceptualization, Methodology, Resources, Writing – Review & Editing, Supervision, Project Administration, Funding Acquisition. J.C.: Conceptualization, Resources, Writing – Review & Editing, Supervision, Project Administration, Funding Acquisition. All authors read and approved the final manuscript.

References

[1] Rao, A., Barkley, D., França, G.S., Yanai, I.: Exploring tissue architecture using spatial transcriptomics. Nature **596**(7871), 211–220 (2021) https://doi.org/10.1038/s41586-021-03634-9

[2] Chen, K.H., Boettiger, A.N., Moffitt, J.R., Wang, S., Zhuang, X.: Spatially resolved, highly multiplexed rna profiling in single cells. Science **348**(6233), 6090 (2015) https://doi.org/10.1126/science.aaa6090

[3] Moses, L., Pachter, L.: Museum of spatial transcriptomics. Nat. Methods **19**(5), 534–546 (2022) https://doi.org/10.1038/s41592-022-01409-2

[4] Virshup, I., Rybakov, S., Theis, F.J., al.: anndata: Annotated data. bioRxiv (2021) https://doi.org/10.1101/2021.12.16.473007

[5] Hao, Y., Hao, S., Andersen-Nissen, E., al.: Integrated analysis of multimodal single-cell data. Cell **184**(13), 3573–3587 (2021) https://doi.org/10.1016/j.cell.2021.04.048

[6] Xie, F., Zhao, B., Xu, S., Wang, Z., Moon, J.J., Garmire, L.X.: Overcoming barriers to the wide adoption of single-cell large language models in biomedical research. Nat. Biotechnol. **43**(11), 1758–1762 (2025) https://doi.org/10.1038/s41587-025-02846-y . Comment

[7] Atta, L., Fan, J.: Computational challenges and opportunities in spatially resolved transcriptomic data analysis. Nat. Commun. **12**(1), 5283 (2021) https://doi.org/10.1038/s41467-021-25557-9

[8] Dries, R., Zhu, Q., Dong, R., Eng, C.-H.L., Li, H., Liu, K., Fu, Y., Zhao, T., Sarkar, A., Bao, F., George, R.E., Pierson, N., Cai, L., Yuan, G.-C.: Giotto: a toolbox for integrative analysis and visualization of spatial expression data. Genome Biol. **22**(1), 78 (2021) https://doi.org/10.1186/s13059-021-02286-2

[9] Huang, C.H.: Qust-llm: Integrating large language models for comprehensive spatial transcriptomics analysis (2024) https://doi.org/10.48550/arXiv.2406.14307 arXiv:2406.14307 [q-bio.GN]

[10] Nagarajan, V., Shi, G., Arunkumar, S., Liu, C., Gopalakrishnan, J., Nath, P.R., Jang, J., Caspi, R.R.: SCassist: An AI Based Workflow Assistant for Single-Cell Analysis. Bioinformatics **41**(8), 402 (2025) https://doi.org/10.1093/bioinformatics/btaf402

[11] Schaefer, M., Peneder, P., Malzl, D., Lombardo, S.D., Peycheva, M., Burton, J., Hakobyan, A., Sharma, V., Krausgruber, T., Sin, C., Menche, J., Tomazou, E.M., Bock, C.: Multimodal learning enables chat-based exploration of single-cell data. Nat. Biotechnol. (2025) https://doi.org/10.1038/s41587-025-02857-9

[12] Lin, Z., Wang, W., Marin-Llobet, A., Li, Q., Pollock, S.D., Sui, X., Aljovic, A., Lee, J., Baek, J., Liang, N., Zhang, X., Wang, C.K., Huang, J., Liu, M., Gao, Z., Sheng, H., Du, J., Lee, S.J., Wang, B., He, Y., Ding, J., Wang, X., Alvarez-Dominguez, J.R., Liu, J.: Spatial transcriptomics ai agent charts hpsc-pancreas maturation in vivo (2025) https://doi.org/10.1101/2025.04.01.646731 bioRxiv:2025.04.01.646731

[13] Wang, H., He, Y., Coelho, P.P., Bucci, M., Nazir, A., Chen, B., Trinh, L., Zhang, S., Huang, K., Chandrasekar, V., Chung, D.C., Hao, M., Leote, A.C., Lee, Y., Li, B., Liu, T., Liu, J., Lopez, R., Lucas, T., Ma, M., Makarov, N., McGinnis, L., Peng, L., Ra, S., Scalia, G., Singh, A., Tao, L., Uehara, M., Wang, C., Wei, R., Copping, R., Rozenblatt-Rosen, O., Leskovec, J., Regev, A.: Spatialagent: An autonomous ai agent for spatial biology. bioRxiv (2025) https://doi.org/10.1101/2025.04.03.646459

[14] Spracklen, J., Wijewickrama, R., Sakib, A.H.M.N., Maiti, A., Viswanath, B., Jadliwala, M.: We have a package for you! a comprehensive analysis of package hallucinations by code generating llms. arXiv preprint arXiv:2406.10279 (2024). To appear in USENIX Security 2025

[15] Wang, Z., Zhou, Z., Song, D., Huang, Y., Chen, S., Ma, L., Zhang, T.: Towards understanding the characteristics of code generation errors made by large language models. arXiv preprint arXiv:2406.08731 (2024). To appear in ICSE 2025

[16] Dinh, T., Zhao, J., Tan, S., Negrinho, R., Lausen, L., Zha, S., Karypis, G.: Large language models of code fail at completing code with potential bugs. In: Advances in Neural Information Processing Systems, vol. 36, pp. 41386–41412. Curran Associates, Inc., Red Hook, NY (2023)

[17] Anthropic: Model Context Protocol. Accessed: 2025-10-30 (2024). https://modelcontextprotocol.io/

[18] Anthropic: Claude 3.5 Sonnet. Accessed: 2025-10-30 (2024). https://www.anthropic.com/news/claude-3-5-sonnet

[19] Tian, L., Chen, F., Macosko, E.Z.: The expanding vistas of spatial transcriptomics. Nat. Biotechnol. **41**(6), 773–782 (2023) https://doi.org/10.1038/s41587-022-01448-2

[20] Li, H., Zhou, J., Li, Z., Chen, S., Liao, X., Zhang, B., Zhang, R., Wang, Y., Sun, S., Gao, X.: A comprehensive benchmarking with practical guidelines for cellular deconvolution of spatial transcriptomics. Nat. Commun. **14**(1), 1548 (2023) https://doi.org/10.1038/s41467-023-37168-7

[21] Kang, L., Zhang, Q., Qian, F., Liang, J., Wu, X.: Benchmarking computational methods for detecting spatial domains and domain-specific spatially variable genes from spatial transcriptomics data. Nucleic Acids Res. **53**(7), 303 (2025) https://doi.org/10.1093/nar/gkaf303

[22] Hu, Y., Xie, M., Li, Y., Rao, M., Shen, W., Luo, C., Qin, H., Baek, J., Zhou, X.M.: Benchmarking clustering, alignment, and integration methods for spatial transcriptomics. Genome Biol. **25**(1), 212 (2024) https://doi.org/10.1186/s13059-024-03361-0

[23] Sang-aram, C., Browaeys, R., Seurinck, R., Saeys, Y.: Spotless, a reproducible pipeline for benchmarking cell type deconvolution in spatial transcriptomics. eLife **12**, 88431 (2024) https://doi.org/10.7554/eLife.88431

[24] Li, Z., Patel, Z.M., Song, D., Yasa, S.N., Cannoodt, R., Yan, G., Li, J.J., Pinello, L.: Systematic benchmarking of computational methods to identify spatially variable genes. Genome Biol. **26**(1), 285 (2025) https://doi.org/10.1186/s13059-025-03731-2

[25] Luo, Y., Ren, J., Yang, Q., Zhou, Y., You, Z., Li, Q.: Benchmarking rna velocity methods across 17 independent studies. bioRxiv (2025) https://doi.org/10.1101/2025.08.02.668272

[26] Dimitrov, D., Schäfer, P.S.L., Farr, E., Rodriguez-Mier, P., Lobentanzer, S., Badia-i-Mompel, P., Dugourd, A., Tanevski, J., Ramirez Flores, R.O., Saez-Rodriguez, J.: Liana+ provides an all-in-one framework for cell-cell communication inference. Nat. Cell Biol. **26**, 1613–1622 (2024) https://doi.org/10.1038/s41556-024-01469-w

[27] Jin, S., Plikus, M.V., Nie, Q.: Cellchat for systematic analysis of cell-cell communication from single-cell transcriptomics. Nat. Protoc. **20**, 180–219 (2025) https://doi.org/10.1038/s41596-024-01045-4

[28] Weiler, P., Lange, M., Klein, M., Pe'er, D., Theis, F.: Cellrank 2: unified fate mapping in multiview single-cell data. Nat. Methods **21**, 1196–1205 (2024) https://doi.org/10.1038/s41592-024-02303-9

[29] Korsunsky, I., Millard, N., Fan, J., Slowikowski, K., Zhang, F., Wei, K., Baglaenko, Y., Brenner, M., Loh, P.-r., Raychaudhuri, S.: Fast, sensitive and accurate integration of single-cell data with harmony. Nat. Methods **16**(12), 1289–1296 (2019) https://doi.org/10.1038/s41592-019-0619-0

[30] Lopez, R., Regier, J., Cole, M.B., Jordan, M.I., Yosef, N.: Deep generative modeling for single-cell transcriptomics. Nat. Methods **15**(12), 1053–1058 (2018) https://doi.org/10.1038/s41592-018-0229-2

[31] Puram, S.V., Tirosh, I., Parikh, A.S., Patel, A.P., Yizhak, K., Gillespie, S., Rodman, C., Luo, C.L., Mroz, E.A., Emerick, K.S., *et al.*: Single-cell transcriptomic analysis of primary and metastatic tumor ecosystems in head and neck cancer. Cell **171**(7), 1611–1624 (2017) https://doi.org/10.1016/j.cell.2017.10.044

[32] Arora, R., Cao, C., Kumar, M., Sinha, S., Chanda, A., McNeil, R., Samuel, D., Arora, R.K., Matthews, T.W., Chandarana, S., Hart, R., Dort, J.C., Biernaskie, J., Neri, P., Hyrcza, M.D., Bose, P.: Spatial transcriptomics reveals distinct and conserved tumor core and edge architectures that predict survival and targeted therapy response. Nat. Commun. **14**, 5029 (2023) https://doi.org/10.1038/s41467-023-40271-4

[33] Denisenko, E., Kock, L., Tan, A., *et al.*: Spatial transcriptomics reveals discrete tumour microenvironments and autocrine loops within ovarian cancer subclones. Nat. Commun. **15**, 2860 (2024) https://doi.org/10.1038/s41467-024-47271-y

[34] Cable, D.M., Murray, E., Zou, L.S., al.: Robust decomposition of cell type mixtures in spatial transcriptomics. Nat. Biotechnol. **40**(4), 517–526 (2022) https://doi.org/10.1038/s41587-021-00830-w

[35] Patel, A.P., Tirosh, I., Trombetta, J.J., Shalek, A.K., Gillespie, S.M., Wakimoto, H., Cahill, D.P., Nahed, B.V., Curry, W.T., Martuza, R.L., Louis, D.N., Rozenblatt-Rosen, O., Suvà, M.L., Regev, A., Bernstein, B.E.: Single-cell rna-seq highlights intratumoral heterogeneity in primary glioblastoma. Science

344(6190), 1396–1401 (2014) https://doi.org/10.1126/science.1254257

[36] Palla, G., Spitzer, H., Klein, M., al.: Squidpy: a scalable framework for spatial omics analysis. Nat. Methods **19**(2), 171–178 (2022) https://doi.org/10.1038/s41592-021-01358-2

[37] Moffitt, J.R., Bambah-Mukku, D., Eichhorn, S.W., al.: Molecular, spatial, and functional single-cell profiling of the hypothalamic preoptic region. Science **362**(6416), 5324 (2018) https://doi.org/10.1126/science.aau5324

[38] Lohoff, T., Ghazanfar, S., Missarova, A., al.: Integration of spatial and single-cell transcriptomic data elucidates mouse organogenesis. Nat. Biotechnol. **40**(1), 74–85 (2022) https://doi.org/10.1038/s41587-021-01006-2

[39] Wang, X., Allen, W.E., Wright, M.A., al.: Three-dimensional intact-tissue sequencing of single-cell transcriptional states. Science **361**(6400), 5691 (2018) https://doi.org/10.1126/science.aat5691

[40] Rodriques, S.G., Stickels, R.R., Goeva, A., al.: Slide-seq: A scalable technology for measuring genome-wide expression at high spatial resolution. Science **363**(6434), 1463–1467 (2019) https://doi.org/10.1126/science.aaw1219

[41] 10x Genomics: Prompt-Based Interface for the 10x Genomics Cloud. Accessed: 2025-10-30 (2025). https://www.10xgenomics.com/support/software/cloud-analysis/latest/tutorials/cloud-mcp-server

[42] Benchling: Benchling MCP. Accessed: 2025-10-30 (2025). https://help.benchling.com/hc/en-us/articles/40342713479437-Benchling-MCP

[43] Wolf, F.A., Angerer, P., Theis, F.J.: Scanpy: large-scale single-cell gene expression data analysis. Genome Biol. **19**(1), 15 (2018) https://doi.org/10.1186/s13059-017-1382-0

[44] Marconato, L., Palla, G., Yamauchi, K.A., al.: Spatialdata: an open and universal data framework for spatial omics. Nat. Methods **22**(1), 58–62 (2025) https://doi.org/10.1038/s41592-024-02212-x

[45] Hafemeister, C., Satija, R.: Normalization and variance stabilization of single-cell rna-seq data using regularized negative binomial regression. Genome Biol. **20**(1), 296 (2019) https://doi.org/10.1186/s13059-019-1874-1

[46] Polański, K., Young, M.D., Miao, Z., Meyer, K.B., Teichmann, S.A., Park, J.-E.: Bbknn: fast batch alignment of single cell transcriptomes. Bioinformatics **36**(3), 964–965 (2020) https://doi.org/10.1093/bioinformatics/btz625

[47] Hie, B., Bryson, B., Berger, B.: Efficient integration of heterogeneous single-cell transcriptomes using scanorama. Nat. Biotechnol. **37**(6), 685–691 (2019) https:

//doi.org/10.1038/s41587-019-0113-3

[48] Zeira, R., Land, M., Strzalkowski, A., Raphael, B.J.: Alignment and integration of spatial transcriptomics data. Nat. Methods **19**(5), 567–575 (2022) https://doi.org/10.1038/s41592-022-01459-6

[49] Clifton, K., Anant, M., Aihara, G., Atta, L., Aimiuwu, O.K., Kebschull, J.M., Miller, M.I., Tward, D., Fan, J.: Stalign: Alignment of spatial transcriptomics data using diffeomorphic metric mapping. Nat. Commun. **14**(1), 8123 (2023) https://doi.org/10.1038/s41467-023-43915-7

[50] Hunter, J.D.: Matplotlib: A 2d graphics environment. Comput. Sci. Eng. **9**(3), 90–95 (2007) https://doi.org/10.1109/MCSE.2007.55

[51] Biancalani, T., Scalia, G., Buffoni, L., al.: Deep learning and alignment of spatially resolved single-cell transcriptomes with tangram. Nat. Methods **18**(11), 1352–1362 (2021) https://doi.org/10.1038/s41592-021-01264-7

[52] Xu, C., Lopez, R., Mehlman, E., Regier, J., Jordan, M.I., Yosef, N.: Probabilistic harmonization and annotation of single-cell transcriptomics data with deep generative models. Mol. Syst. Biol. **17**(1), 9620 (2021) https://doi.org/10.15252/msb.20209620

[53] Zhang, A.W., O'Flanagan, C., Chavez, E.A., al.: Probabilistic cell-type assignment of single-cell rna-seq for tumor microenvironment profiling. Nat. Methods **16**(10), 1007–1015 (2019) https://doi.org/10.1038/s41592-019-0529-1

[54] Yang, C., Zhang, X., Chen, J.: Large language model consensus substantially improves the cell type annotation accuracy for scrna-seq data. bioRxiv (2025) https://doi.org/10.1101/2025.04.10.647852

[55] Ianevski, A., Giri, A.K., Aittokallio, T.: Fully-automated and ultra-fast cell-type identification using specific marker combinations from single-cell transcriptomic data. Nat. Commun. **13**(1), 1246 (2022) https://doi.org/10.1038/s41467-022-28803-w

[56] Aran, D., Looney, A.P., Liu, L., Wu, E., Fong, V., Hsu, A., Chak, S., Naikawadi, R.P., Wolters, P.J., Abate, A.R., Butte, A.J., Bhattacharya, M.: Reference-based analysis of lung single-cell sequencing reveals a transitional profibrotic macrophage. Nat. Immunol. **20**(2), 163–172 (2019) https://doi.org/10.1038/s41590-018-0276-y

[57] Hu, J., Li, X., Coleman, K., Schroeder, A., Ma, N., Irwin, D.J., Lee, E.B., Shinohara, R.T., Li, M.: Spagcn: Integrating gene expression, spatial location and histology to identify spatial domains and spatially variable genes by graph convolutional network. Nat. Methods **18**(11), 1342–1351 (2021) https://doi.org/10.1038/s41592-021-01255-8

[58] Dong, K., Zhang, S.: Deciphering spatial domains from spatially resolved tran-scriptomics with an adaptive graph attention auto-encoder. Nat. Commun. **13**(1), 1739 (2022) https://doi.org/10.1038/s41467-022-29439-6

[59] Long, Y., Ang, K.S., Li, M., al.: Spatially informed clustering, integration, and deconvolution of spatial transcriptomics with graphst. Nat. Commun. **14**(1), 1155 (2023) https://doi.org/10.1038/s41467-023-36796-3

[60] Traag, V., Waltman, L., Eck, N.: From louvain to leiden: guaranteeing well-connected communities. Sci. Rep. **9**(1), 5233 (2019) https://doi.org/10.1038/s41598-019-41695-z

[61] Blondel, V.D., Guillaume, J.-L., Lambiotte, R., Lefebvre, E.: Fast unfolding of communities in large networks. J. Stat. Mech. **2008**(10), 10008 (2008) https://doi.org/10.1088/1742-5468/2008/10/P10008

[62] Sun, S., Zhu, J., Zhou, X.: Statistical analysis of spatial expression patterns for spatially resolved transcriptomic studies. Nat. Methods **17**(2), 193–200 (2020) https://doi.org/10.1038/s41592-019-0701-7

[63] Svensson, V., Teichmann, S.A., Stegle, O.: Spatialde: identification of spatially variable genes. Nat. Methods **15**(5), 343–346 (2018) https://doi.org/10.1038/nmeth.4636

[64] Dimitrov, D., Türei, D., Garrido-Rodriguez, M., al.: Comparison of methods and resources for cell-cell communication inference from single-cell rna-seq data. Nat. Commun. **13**(1), 3224 (2022) https://doi.org/10.1038/s41467-022-30755-0

[65] Efremova, M., Vento-Tormo, M., Teichmann, S.A., Vento-Tormo, R.: Cell-phonedb: inferring cell–cell communication from combined expression of multi-subunit ligand–receptor complexes. Nat. Protoc. **15**(4), 1484–1506 (2020) https://doi.org/10.1038/s41596-020-0292-x

[66] Jin, S., Guerrero-Juarez, C.F., Zhang, L., al.: Inference and analysis of cell-cell communication using cellchat. Nat. Commun. **12**(1), 1088 (2021) https://doi.org/10.1038/s41467-021-21246-9

[67] Hou, S., Ma, W., Zhou, X.: Fastccc: a permutation-free framework for scalable, robust, and reference-based cell-cell communication analysis in single cell tran-scriptomics studies. Nat. Commun. **16**, 66272 (2025) https://doi.org/10.1038/s41467-025-66272-z

[68] Yang, C., Zhang, X., Chen, J.: Flashdeconv enables atlas-scale, multi-resolution spatial deconvolution via structure-preserving sketching. bioRxiv (2025) https://doi.org/10.64898/2025.12.22.696108 . Preprint

[69] Kleshchevnikov, V., Shmatko, A., Dann, E., al.: Cell2location maps fine-grained

cell types in spatial transcriptomics. Nat. Biotechnol. **40**(5), 661–671 (2022) https://doi.org/10.1038/s41587-021-01139-4

[70] Elosua-Bayes, M., Nieto, P., Mereu, E., Gut, I., Heyn, H.: Spotlight: seeded nmf regression to deconvolute spatial transcriptomics spots with single-cell transcriptomes. Nucleic Acids Res. **49**(9), 50 (2021) https://doi.org/10.1093/nar/gkab043

[71] Andersson, A., Bergenstråhle, J., Asp, M., Bergenstråhle, L., Jurek, A., Fernández Navarro, J., Lundeberg, J.: Single-cell and spatial transcriptomics enables probabilistic inference of cell type topography. Commun. Biol. **3**(1), 565 (2020) https://doi.org/10.1038/s42003-020-01247-y

[72] Lopez, R., Li, B., Keren-Shaul, H., Boyeau, P., Kedmi, M., Pilzer, D., Jelinski, A., Yofe, I., David, E., Wagner, A., Ergen, C., Addad, Y., Golani, O., Ronchese, F., Jordan, M.I., Amit, I., Yosef, N.: Destvi identifies continuums of cell types in spatial transcriptomics data. Nat. Biotechnol. **40**(9), 1360–1369 (2022) https://doi.org/10.1038/s41587-022-01272-8

[73] Ma, Y., Zhou, X.: Spatially informed cell-type deconvolution for spatial transcriptomics. Nat. Biotechnol. **40**(9), 1349–1359 (2022) https://doi.org/10.1038/s41587-022-01273-7

[74] Gayoso, A., Lopez, R., Xing, G., Boyeau, P., Valiollah Pour Amiri, V., Hong, J., Wu, K., Jayasuriya, M., Mehlman, E., Langevin, M., Liu, Y., Samaran, J., Misrachi, G., Nazaret, A., Clivio, O., Xu, C., Ashuach, T., Lotfollahi, M., Svensson, V., Veiga Beltrame, E., Kleshchevnikov, V., Talavera-Lopez, C., Pachter, L., Theis, F.J., Streets, A., Jordan, M.I., Regier, J., Yosef, N.: A python library for probabilistic analysis of single-cell omics data. Nat. Biotechnol. **40**(2), 163–166 (2022) https://doi.org/10.1038/s41587-021-01206-w

[75] Gao, T., Soldatov, R., Sarkar, H., Kurkiewicz, A., Biederstedt, E., Loh, P.-R., Kharchenko, P.V.: Haplotype-aware analysis of somatic copy number variations from single-cell transcriptomes. Nat. Biotechnol. **41**(3), 417–426 (2023) https://doi.org/10.1038/s41587-022-01468-y

[76] Lange, M., Bergen, V., Klein, M., Setty, M., Reuter, B., Bakhti, M., Lickert, H., Ansari, M., Schniering, J., Schiller, H.B., Pe'er, D., Theis, F.J.: Cellrank for directed single-cell fate mapping. Nat. Methods **19**(2), 159–170 (2022) https://doi.org/10.1038/s41592-021-01346-6

[77] Setty, M., Kiseliovas, V., Levine, J., Gayoso, A., Mazutis, L., Pe'er, D.: Characterization of cell fate probabilities in single-cell data with palantir. Nat. Biotechnol. **37**(4), 451–460 (2019) https://doi.org/10.1038/s41587-019-0068-4

[78] Haghverdi, L., Büttner, M., Wolf, F.A., Buettner, F., Theis, F.J.: Diffusion pseudotime robustly reconstructs lineage branching. Nat. Methods **13**(10), 845–848

(2016) https://doi.org/10.1038/nmeth.3971

[79] Bergen, V., Lange, M., Peidli, S., Wolf, F.A., Theis, F.J.: Generalizing rna velocity to transient cell states through dynamical modeling. Nat. Biotechnol. **38**(12), 1408–1414 (2020) https://doi.org/10.1038/s41587-020-0591-3

[80] Gayoso, A., Weiler, P., Lotfollahi, M., Klein, D., Hong, J., Streets, A., Theis, F.J., Yosef, N.: Deep generative modeling of transcriptional dynamics for rna velocity analysis in single cells. Nat. Methods **21**(1), 50–59 (2024) https://doi.org/10.1038/s41592-023-01994-w

[81] Subramanian, A., Tamayo, P., Mootha, V.K., Mukherjee, S., Ebert, B.L., Gillette, M.A., Paulovich, A., Pomeroy, S.L., Golub, T.R., Lander, E.S., Mesirov, J.P.: Gene set enrichment analysis: a knowledge-based approach for interpreting genome-wide expression profiles. Proc. Natl. Acad. Sci. U.S.A. **102**(43), 15545–15550 (2005) https://doi.org/10.1073/pnas.0506580102

[82] Barbie, D.A., Tamayo, P., Boehm, J.S., Kim, S.Y., Moody, S.E., Dunn, I.F., Schinzel, A.C., Sandy, P., Meylan, E., Scholl, C., Fröhling, S., Chan, E.M., Sos, M.L., Michel, K., Mermel, C., Silver, S.J., Weir, B.A., Reiling, J.H., Sheng, Q., Gupta, P.B., Wadlow, R.C., Le, H., Hoersch, S., Wittner, B.S., Ramaswamy, S., Livingston, D.M., Sabatini, D.M., Meyerson, M., Thomas, R.K., Lander, E.S., Mesirov, J.P., Root, D.E., Gilliland, D.G., Jacks, T., Hahn, W.C.: Systematic rna interference reveals that oncogenic kras-driven cancers require tbk1. Nature **462**(7269), 108–112 (2009) https://doi.org/10.1038/nature08460

[83] Merico, D., Isserlin, R., Stueker, O., Emili, A., Bader, G.D.: Enrichment map: a network-based method for gene-set enrichment visualization and interpretation. PLoS One **5**(11), 13984 (2010) https://doi.org/10.1371/journal.pone.0013984

Supplementary Methods

S1 Detailed MCP Architecture

Protocol Architecture: The MCP architecture follows a client-host-server design where each host can run multiple client instances, enabling modular integration of AI capabilities while maintaining clear security boundaries. This architecture is built on three core components: (1) Host: the application process (e.g., Claude Desktop, IDE) that acts as the container and coordinator, creating and managing multiple client instances, enforcing security policies and user authorization, coordinating AI/LLM integration, and aggregating context across clients; (2) Client: protocol-handling instances that maintain isolated 1:1 connections with servers, each establishing one stateful session per server, handling protocol negotiation and capability exchange, routing messages bidirectionally, and maintaining security boundaries between servers; and (3) Server: independent processes that expose specialized capabilities (tools, resources, prompts) via MCP primitives, operating with focused responsibilities while respecting security constraints, and can be either local processes or remote services. In the ChatSpatial implementation, Claude Desktop acts as the Host, the MCP client library manages individual server connections, and the ChatSpatial server exposes bioinformatics analysis capabilities. This separation ensures that servers remain simple to implement and highly composable, while the host handles complex orchestration—a key design principle where servers cannot access the full conversation history or "see into" other servers, with all cross-server coordination controlled by the host process.

Interaction Primitives: MCP defines three core interaction primitives that distribute control between participants: (1) Tools: model-driven executable functions that the LLM can invoke autonomously to perform actions (e.g., data analysis, visualization); (2) Resources: application-driven structured data sources that provide context to LLM interactions (e.g., dataset metadata, analysis results); and (3) Prompts: user-driven predefined templates for specific workflows (e.g., "analyze spatial expression," "find cell types"). The 2025 MCP specification extends these with additional capabilities including Sampling (enabling servers to request LLM completions), Roots (filesystem context provision), and Elicitation (structured data collection from users). ChatSpatial's implementation leverages Resources through two mechanisms: (a) File URI-based Image Delivery: visualization tools return file paths as text for all images, following MCP 2025 best practice of preferring URIs over embedded content. This approach avoids the $\sim 3.3\times$ token overhead inherent to ImageContent encoding (where a 16KB image becomes 53KB in the MCP response), optimizing context window usage while supporting multiple export formats (PNG, PDF, SVG, EPS, TIFF) for publication-quality figures; and (b) Standalone Resources infrastructure: `SpatialResourceManager` and `SpatialPromptManager` are implemented internally for dataset metadata exposure and workflow templates, currently dormant but available for activation through decorator registration (`@mcp.list_resources`, `@mcp.read_resource`). The platform exposes 20 analytical tools via the Tools primitive through MCP capability negotiation.

Communication Layer: All communication follows the JSON-RPC 2.0 specification with strict lifecycle management. The protocol defines three phases: (1) Initialization:

the client sends an `initialize` request declaring its protocol version and capabilities (e.g., sampling support, roots provision), the server responds with its own capabilities (e.g., tools, resources, prompts), and upon successful negotiation the client sends an `initialized` notification to begin operation; (2) Operation: bidirectional message exchange where both parties respect negotiated capabilities, using only features explicitly declared during initialization; and (3) Shutdown: graceful termination via transport-specific mechanisms. ChatSpatial implements this lifecycle through FastMCP, exposing 20 analytical tools in its capabilities declaration. The transport mechanism uses stdio (standard input/output) for local deployments and Claude Desktop integration, with JSON-RPC messages delimited by newlines. This capability-based negotiation ensures explicit feature agreement between client and server, supporting protocol extensibility while maintaining backwards compatibility.

Bioinformatics Extensions: Our MCP implementation includes bioinformatics-specific conventions for spatial transcriptomics data. The system maintains a standardized `AnnData` object format with spatial coordinates stored in `adata.obsm['spatial']` and analysis results stored in `adata.obs` or `adata.uns`, ensuring consistent data handling across all analytical tools and preserving provenance throughout multi-step workflows.

LLM Models and MCP Server Instructions: All development and testing were performed using Anthropic's Claude Sonnet 4.5 model [18]. ChatSpatial leverages MCP Server Instructions, which are injected into the LLM's system prompt at session initialization to provide workflow guidance. These instructions complement the comprehensive parameter documentation embedded in tool schemas (Section 4.3) by focusing on tool relationships, operational constraints, and platform-specific recommendations. The server instructions are structured into five key components:

(1) *Core Workflow Pattern:* Standard analysis sequence of `load_data()` → `preprocess_data()` → analysis tools → `visualize_data()`, establishing the expected operational flow.

(2) *Critical Operational Constraints:* Essential knowledge not obvious from individual tool schemas, such as preservation of raw data in `adata.raw` during preprocessing and the automatic utilization of `adata.raw` for cell communication analysis to access comprehensive gene coverage, along with species-specific parameter requirements.

(3) *Platform-Specific Guidance:* Technology-aware recommendations such as deconvolution requirements for spot-based platforms (Visium, Slide-seq) versus single-cell platforms (MERFISH, Xenium, CosMx), and method selection based on data characteristics (SpaGCN for Visium with histology images, STAGATE/GraphST for high-resolution data without images).

(4) *Tool Relationships:* Inter-tool dependencies such as spatial domain identification enabling spatial statistics, cell type annotation being required for cell communication analysis, and integration being recommended before cross-sample comparative analyses.

(5) *Parameter Guidance Philosophy:* Explicit direction to refer to tool schemas for detailed parameter documentation, avoiding duplication while maintaining the documentation-driven approach described in Section 4.3.

This two-layer guidance system—MCP Server Instructions for high-level workflows and tool schemas for parameter-level details—enables the LLM to orchestrate complex multi-step analyses while maintaining scientific rigor. The instructions emphasize that analysis continuity requires preserving `data_id` across operations, enabling the LLM to maintain session state for iterative exploration. The complete server instructions are provided verbatim below and in the source code repository.

S1.1 Complete MCP Server Instructions (Verbatim)

The following are the exact instructions injected into Claude's system prompt at session initialization, guiding how the LLM interacts with ChatSpatial's analytical tools:

```
ChatSpatial provides spatial transcriptomics analysis through
60+ integrated methods across 15 analytical categories.

CORE WORKFLOW PATTERN:
1. Always start with load_data() to import spatial transcriptomics data
2. Run preprocess_data() before most analytical tools (required for
   clustering, spatial analysis, etc.)
3. Use visualize_data() to inspect results after each analysis step

CRITICAL OPERATIONAL CONSTRAINTS:
- Preprocessing creates filtered gene sets for efficiency but preserves
  raw data in adata.raw
- Cell communication analysis automatically uses adata.raw when available
  for comprehensive gene coverage
- Species-specific parameters are critical: set species="mouse" or
  "human" and use appropriate resources (e.g.,
  liana_resource="mouseconsensus" for mouse)
- Reference data for annotation methods (tangram, scanvi) must be
  PREPROCESSED before use

PLATFORM-SPECIFIC GUIDANCE:
- Spot-based platforms (Visium, Slide-seq): Deconvolution is
  recommended to infer cell type compositions
- Single-cell platforms (MERFISH, Xenium, CosMx): Skip deconvolution -
  native single-cell resolution provided
- Visium with histology images: Use SpaGCN for spatial domain
  identification
- High-resolution data without images: Use STAGATE or GraphST

TOOL RELATIONSHIPS:
- Spatial domain identification → Enables spatial statistics
  (neighborhood enrichment, co-occurrence)
- Cell type annotation → Required for cell communication analysis
```

```
- Deconvolution results → Can be used for downstream spatial statistics
- Integration → Recommended before cross-sample comparative analyses

PARAMETER GUIDANCE:
All tools include comprehensive parameter documentation in their
schemas. Refer to tool descriptions for default values,
platform-specific optimizations, and method-specific requirements.

For multi-step analyses, preserve data_id across operations to
maintain analysis continuity.
```

These instructions work in conjunction with the detailed parameter documentation embedded in each tool's schema (Section S3), creating a two-tier knowledge system where high-level workflow guidance is provided through server instructions and granular parameter details are accessible through MCP's schema introspection mechanism.

S2 Complete SpaGCN Integration Example

To illustrate our MCP-based integration architecture, we detail the implementation of SpaGCN (v1.2.5) spatial domain identification:

MCP Tool Layer.

The entry point is exposed as an MCP tool through the `@mcp.tool()` decorator in `server.py`, registered as `identify_spatial_domains(data_id, params, context)`. This tool is accessible to LLMs through the Model Context Protocol, enabling natural language interactions like "identify spatial domains using SpaGCN with 7 clusters."

Method Dispatch Layer.

The main function `identify_spatial_domains()` in `tools/spatial_domains.py` serves as a dispatcher. It validates input data, auto-detects the spatial coordinate key in `adata.obsm` (supporting common conventions like `'spatial'`, `'X_spatial'`), performs quality checks (handling NaN/inf values, validating data types), and routes to method-specific implementations based on `params.method`. For SpaGCN, it calls `_identify_domains_spagcn()`.

Algorithm Wrapper Layer.

The `_identify_domains_spagcn()` function prepares data for SpaGCN's requirements: (1) extracts spatial coordinates via auto-detection, (2) loads histology images with scale factors if available (10x Visium format), (3) applies SpaGCN-specific gene filtering via `spg.prefilter_genes()` and `spg.prefilter_specialgenes()`, and (4) calls `SpaGCN.ez_mode.detect_spatial_domains_ez_mode()` with parameters `n_clusters`, `s` (histology weight), `b` (spot area for color extraction), `p` (neighborhood expression weight), and `r_seed` (random seed). The function includes timeout protection (default 600s) using asyncio thread pooling to prevent hanging on large datasets.

Result Standardization.

Domain labels are stored in `adata.obs['spatial_domains_spagcn']` as categorical variables. An optional refinement step applies spatial smoothing using k-nearest neighbors (following SpaGCN's post-processing approach) to reduce noise while preserving domain boundaries. The result is returned as a `SpatialDomainResult` object containing domain counts, statistics, and visualization-ready metadata.

S3 Examples of LLM-Visible Parameter Documentation

ChatSpatial achieves intelligent parameter selection through comprehensive documentation visible to the LLM via MCP's schema system, rather than hard-coded rule engines. This design philosophy enables flexible, context-aware parameter optimization while maintaining transparency and user control.

Documentation-Driven Parameter Selection: All parameters are defined using Pydantic models with extensive `Field()` descriptions that the LLM can access through MCP tool schemas. For example, the `normalization` parameter includes detailed guidance on available methods (log, pearson_residuals, none), technology-specific recommendations (Visium vs. MERFISH vs. Xenium), requirements and constraints, error handling behavior, and scientific rationale. Similarly, the `normalize_target_sum` parameter provides decision guides: "None (default) uses median counts for adaptive behavior; 1e4 (10,000) is standard for 10x Visium; 1e6 (1,000,000) is standard for MERFISH/CosMx/Xenium." This documentation-first approach enables the LLM to make informed parameter choices based on the user's data characteristics and research goals without requiring pre-programmed rules.

Comprehensive Tool-Level Guidance: Every MCP tool exposes rich docstrings through the `@mcp.tool()` decorator. For instance, the `preprocess_data()` tool provides detailed notes on normalization methods, adaptive configuration options (e.g., "n_neighbors: None = adaptive based on dataset size"), and important data handling behaviors (e.g., preservation of raw data in `adata.raw` for downstream analyses). These docstrings serve as in-context guidance, allowing the LLM to understand method trade-offs and make appropriate parameter recommendations during conversations.

Conversational Error-Driven Refinement: When parameter-related errors occur, the structured error messages returned by ChatSpatial's decorator-based error handling system enable the LLM to diagnose issues and adjust parameters conversationally. For example, if a normalization method fails due to data type incompatibility (e.g., `pearson_residuals` requires raw integer counts), the error message explicitly states requirements and suggests alternatives. The LLM observes these errors and can propose corrected parameters based on the comprehensive documentation it has access to, creating an iterative refinement loop that does not require pre-defined rules for every possible failure scenario.

Default Values from Best Practices: Parameter defaults are derived from systematic review of method-specific tutorials, published best practices, and benchmark studies in the spatial transcriptomics literature. For example, clustering resolution defaults to 1.0 (matching scanpy convention), `n_hvgs` defaults to 2000 (balancing computational efficiency with information retention), and SpaGCN spatial smoothing parameter `s`

defaults to 1.0 (recommended by the original authors). These empirically validated defaults serve as starting points that the LLM can adjust based on user feedback or error messages, rather than being dynamically computed from dataset characteristics.

S4 Error Handling Code Implementation

ChatSpatial implements a structured error handling system designed for conversational interaction. The core principle is that errors should be informative and actionable, enabling the LLM to guide users toward solutions through natural dialogue rather than requiring manual debugging.

S4.1 Semantic Exception Hierarchy

Rather than relying on generic Python exceptions, ChatSpatial defines a semantic exception hierarchy (`utils/exceptions.py`) that immediately communicates error categories:

```
ChatSpatialError (base)
+-- DataError (data access/format issues)
|   +-- DataNotFoundError (required data missing)
|   +-- DataCompatibilityError (format/species mismatch)
+-- ParameterError (invalid user input)
+-- ProcessingError (algorithm/computation failures)
+-- DependencyError (missing packages/R environment)
```

This hierarchy enables precise error handling: `DataNotFoundError` for missing datasets, `ParameterError` for invalid parameter values, and `DependencyError` for missing R packages. Each exception type carries semantic meaning that the LLM can interpret to provide targeted guidance. For example, a `DataCompatibilityError` indicating gene naming mismatch prompts the LLM to suggest checking whether both datasets use the same naming convention (Ensembl vs. Symbol), while a `DependencyError` triggers installation instructions for the required package.

S4.2 MCP Error Handler Decorator

The `@mcp_tool_error_handler` decorator (`utils/mcp_utils.py`) wraps all MCP tools to ensure errors are returned as structured results rather than raised as unhandled exceptions. This allows the LLM to observe failures and respond conversationally:

```python
@mcp_tool_error_handler()
async def analyze_data(...):
    # Tool implementation
```

The decorator performs runtime type inspection via `typing.get_type_hints()` to determine the appropriate error format for each tool's return type: BaseModel results re-raise for FastMCP schema handling, string-returning tools (e.g., visualization file

paths) return error messages as strings, and other types return structured error dictionaries with optional tracebacks. This type-aware approach maintains MCP protocol consistency while providing clear, actionable feedback to the LLM.

Complete implementation details, including input validation patterns and result caching strategies, are available in the source code repository.

Table S1: Integrated method library in ChatSpatial. For each of the 60+ integrated methods, we list its primary analytical category, the specific version of the software package used in our implementation, and the primary citation for the original work.

Analytical Category	Method Name	Version	Primary Citation
Data Loading & Pre-processing	Scanpy	1.9.3	[43]
	SpatialData	0.2.0	[44]
	SCTransform	0.4.0	[45]
Multi-sample Integration	Harmony	0.0.9+	[29]
	scVI	1.0.0+	[30]
	BBKNN	1.5.0+	[46]
	Scanorama	1.7.0+ (optional)	[47]
Spatial Registration	PASTE	1.3.0	[48]
	STalign	2.0.0	[49]
Visualization	Squidpy	1.3.0	[36]
	Matplotlib/Seaborn	3.7.1/0.12.2	[50]
Cell Type Annotation	Tangram	1.0.3	[51]
	scANVI	1.0.3	[52]
	CellAssign	0.1.0	[53]
	mLLMCellType	1.0.0	[54]
	scType	via R	[55]
	SingleR	via R	[56]
Differential Expression	Wilcoxon	via scanpy	[43]
	t-test	via scanpy	[43]
	logreg	via scanpy	[43]
Spatial Domain Identification	SpaGCN	1.2.5	[57]
	STAGATE	1.1.0	[58]
	GraphST	1.1.0+	[59]
	Leiden	via scanpy	[60]
	Louvain	via scanpy	[61]
Spatially Variable Genes	SPARK-X	1.3.0	[62]
	SpatialDE	1.1.3	[63]

Analytical Category	Method Name	Version	Primary Citation
Cell-Cell Communication	LIANA+	1.0.0	[64]
	CellPhoneDB	via LIANA	[65]
	CellChat	native R	[66]
	FastCCC	0.1.0	[67]
Deconvolution	FlashDeconv	0.1.0	[68]
	RCTD	2.2.0	[34]
	Cell2location	0.1.3	[69]
	SPOTlight	0.1.7	[70]
	Stereoscope	0.3.0	[71]
	DestVI	0.1.0	[72]
	Tangram (mapping)	1.0.3	[51]
	CARD	2.0.0	[73]
CNV Analysis	inferCNVpy	0.6.1	[74]
	Numbat	1.3.2	[75]
Trajectory Inference	CellRank	2.0.0	[76]
	Palantir	1.3.0	[77]
	DPT	via scanpy	[78]
RNA Velocity	scVelo	0.2.5	[79]
	VeloVI	1.0.0	[80]
Enrichment Analysis	GSEApy	1.0.6	[81]
	Pathway GSEA	via GSEApy	[81]
	Pathway ORA	via GSEApy	[81]
	ssGSEA	via GSEApy	[82]
	EnrichMap	0.1.10	[83]
Spatial Statistics	Moran's I	via squidpy	[36]
	Local Moran's I (LISA)	via squidpy	[36]
	Geary's C	via squidpy	[36]
	Getis-Ord Gi*	via esda/PySAL	[36]
	Neighborhood Enrichment	via squidpy	[36]
	Co-occurrence	via squidpy	[36]
	Ripley's K/L	via squidpy	[36]
	Centrality Scores	via squidpy	[36]
	Bivariate Moran's I	4.6.0	[36]

Analytical Category	Method Name	Version	Primary Citation
	Join Count Statistics	via esda/PySAL	[36]
	Local Join Count	via esda/PySAL	[36]
	Network Properties	via squidpy	[36]
	Spatial Centrality	2.6.0	[36]

Table S2: Comprehensive test scenarios used to validate the robustness and functionality of the ChatSpatial platform. Each scenario was designed to test a specific aspect of the platform, from handling diverse data types to executing complex multi-method workflows.

ID	Scenario	Input Data	Command/Goal	Expected Outcome	Result	Notes
Category 1: Data Handling & Preprocessing						
1	Standard Visium Input	Visium, 4,992 spots, h5ad	"Load and preprocess the Visium data."	Data loaded, QC metrics calculated.	Pass	Standard workflow.
2	High-res Xenium Input	Xenium, 150k cells	"Load Xenium data and create AnnData."	Data loaded, valid AnnData created.	Pass	Non-h5ad input.
3	Low-quality Data	Visium, <500 genes/spot	"Filter low-quality spots."	Low-quality spots removed.	Pass	QC validation.
4	Multi-sample Integration	3 Visium slides	"Integrate samples with Harmony."	Batch effects reduced.	Pass	Integration test.
5	Missing Spatial Coords	No spatial coordinates	"Plot spatial MALAT1."	Error: "No spatial coordinates."	Pass	Error handling.
Category 2: Core Spatial Analysis						
6	Basic Clustering	DLPFC Visium (spatialLIBD)	"Identify spatial domains using SpaGCN."	Anatomical layers identified.	Pass	Core function.
7	High-density Clustering	MERFISH, 50k cells	"Use GraphST for fine domains."	Sub-clusters identified.	Pass	Dense data test.
8	Spatial Variable Genes	Mouse brain	"Find top 50 SVGs with SPARK-X."	Known markers ranked high.	Pass	SVG detection.
9	Cell Deconvolution	Visium + scRNA ref	"Deconvolve cell types using RCTD."	Cell proportions generated.	Pass	Deconvolution.
10	Cell Annotation	Xenium + atlas	"Annotate cells with Tangram."	Major types assigned.	Pass	Annotation test.
11	Trajectory Analysis	Dev. tissue data	"Infer trajectory using CellRank."	Bio. pathway identified.	Pass	Advanced test.
12	RNA Velocity	Visium + spliced counts	"Calculate spatial RNA velocity."	Dynamics visualized.	Pass	Complex analysis.
13	Spatial Statistics	Mouse brain Visium	"Compute Moran's I for top marker genes."	Spatial autocorrelation scores generated.	Pass	Statistics test.
14	Pathway Enrichment	Cancer Visium	"Run GSEA on cluster markers using GO database."	Enriched pathways identified.	Pass	Enrichment test.
15	CNV Detection	Tumor Visium + ref	"Infer CNV using infer-cnvpy with immune cells as reference."	CNV profiles generated.	Pass	CNV test.
16	Spatial Registration	Serial sections	"Align 3 consecutive slices with PASTE."	Slices registered to common space.	Pass	Registration test.

ID	Scenario	Input Data	Command/Goal	Expected Outcome	Result	Notes
Category 3: Conversational Workflows						
17	Iterative Analysis	Tumor microenv.	"Find clusters. Now, markers for cluster 3."	Context preserved.	Pass	Conversation test.
18	Ambiguous Command	Any dataset	"Analyze the data."	Clarification requested.	Pass	Proactive help.
19	Parameter Override	Visium data	"Run STAGATE with resolution 1.5."	User params used.	Pass	User control.
20	Cross-category Flow	Cancer + ref	"Cluster, then find tumor-immune comm."	Sequential execution.	Pass	Workflow test.
21	Error Recovery	Large dataset	"Run cell communication analysis."	Alternatives suggested.	Pass	Error handling.
Category 4: Scalability & Stress Tests						
22	Large Dataset	100k+ Visium HD	"Run full analysis pipeline."	Pipeline completed.	Pass	Scalability.
23	Small Dataset	300-spot STARmap	"Cluster the data."	Runs despite noise.	Pass	Edge case.
24	Sparse Genes	>99.9% sparsity	"Find variable genes."	Warning issued.	Pass	Robustness.
25	Noisy Reference	Ambiguous scRNA ref	"Annotate using noisy ref."	Low confidence scores.	Pass	Quality aware.
26	Concurrent Users	2 users, diff. data	U1: "Cluster brain." U2: "Annotate tumor."	No interference.	Pass	Isolation test.
27	Long Context	20+ commands	"Result of first clustering?"	History retrieved.	Pass	Memory test.
28	Invalid Input	Non-scientific cmd	"Write Python code to download a file from the internet."	Polite refusal; redirected to spatial analysis scope.	Pass	Scope boundary test.

Table S3: Comparison of ChatSpatial with other AI agents for spatial transcriptomics. This table summarizes architectural design choices, not empirical performance benchmarks. ChatSpatial and STAgent provide complete open-source implementations on GitHub (MIT license); SpatialAgent's source code has not been released at the time of writing.

Feature	ChatSpatial (This Work)	STAgent	SpatialAgent
Primary Philosophy	Agentic Orchestrator. Reliably executes user-defined strategies with scientist in full control.	Autonomous Discovery Agent. End-to-end analysis with minimal human input.	Hybrid Autonomous Agent. Fully autonomous or interactive co-pilot mode.
Planning & Execution	Schema-Enforced Tool-calling via MCP.	Dynamic Code Generation via RAG.	Hybrid: predefined templates + *de novo* code generation.
Reproducibility	Near-deterministic. 100% tool selection consistency across 240 trials (3 LLMs, $T=1.0$); 75.7% constrained parameter consistency.	Non-deterministic. LLM code generation may vary between runs.	Mode-dependent. Deterministic for templates; variable for generated plans.
Tool Scope	Cross-Ecosystem (Python & R). 60+ methods.	Python-Centric. Scanpy/Squidpy.	Python-Centric. 19 curated tools.
Extensibility	Open standard (MCP). New tools added by defining schema.	Internal codebase. Requires re-indexing RAG database.	Internal framework. Architecture details pending code release.