Evaluation of deep learning tools for chromatin contact prediction

Hoang Thien Thu Nguyen [1,2,3] & Vanessa Vermeirssen [1,2,3,*]

[1] Lab for Computational Biology, Integromics and Gene Regulation (CBIGR), Cancer Research Institute Ghent (CRIG), Ghent, Belgium

[2] Department of Biomedical Molecular Biology, Ghent University, Ghent, Belgium

[3] Department of Biomolecular Medicine, Ghent University, Ghent, Belgium

[*] Corresponding author: vanessa.vermeirssen@ugent.be

Abstract

Background: Three-dimensional chromatin organization plays a central role in gene regulation and is commonly measured using Hi-C technology. Recently, deep learning models have been developed to predict Hi-C contact maps from genomic and epigenomic features, offering a computational alternative to costly experimental assays. However, the performance, robustness, and biological interpretability of these models remain unclear due to the absence of systematic benchmarking.

Results: We present a comprehensive benchmark to evaluate five Hi-C prediction models, C.Origami, Epiphany, ChromaFold, HiCDiffusion, and GRACHIP, across multiple evaluation criteria, including accuracy, visual fidelity and loop detection. Among all models, Epiphany achieved the strongest overall performance, combining high accuracy, cell-type generalization, realistic image quality and reliable loop detection. Moreover, we evaluated predicted contact maps using four different loop-callers to assess the impact of model choice on loop detection performance. Despite the coarse resolution, many models could recover biologically relevant interactions. Notably, structural map quality was more critical than the choice of loop-caller for reliable detection. Finally, ablation analyses revealed that epigenomic signals are influential features for accurate Hi-C prediction. Despite the use of multiple input modalities in many models, only a limited subset contributed substantially to predictive performance.

Conclusions: This study provides a systematic comparison of deep learning models for Hi-C prediction and highlights the importance of specific regulatory signals in reconstructing 3D chromatin organization. The proposed evaluation framework clarifies model behaviours and offers guidance for the development and interpretation of Hi-C prediction methods.

Keywords

3D chromatin organization, 3D genome, enhancer–promoter interactions, Hi-C prediction, deep learning

Introduction

Gene expression is tightly controlled by a complex network of regulatory mechanisms that ensure genes are expressed at the right time, location, and level [1]. Among the various layers of regulation, transcriptional regulation plays a central role [2]. At this level, transcription factors (TFs) bind to promoter regions and to distal regulatory elements such as enhancers to modulate gene activity. Because enhancers can act over long genomic distances and regulatory interactions are often combinatorial, the architecture of gene regulatory networks (GRNs) is highly complex, dynamic, and context-dependent. A key source of complexity arises from the fact that many genes are controlled by distal enhancers, which may be located tens to hundreds of kilobases, or even megabases, away from their target promoters. Early studies often assumed that an enhancer regulates its nearest gene along the linear genome sequence [3]. However, this distance-based assumption has proven to be overly simplistic because the genome is folded in three-dimensional (3D) space within the nucleus, allowing distal regulatory elements to physically contact promoters [4]. Accordingly, enhancers defined from chromatin accessibility data frequently act over long genomic distances: 80.94% are located more than 2 kb away from the nearest transcription start site [5]. Moreover, these distal enhancers tend to be less conserved and more cell type-specific and hence are crucial for gene regulation biology. For instance, ZRS enhancer is located in the intron of *LMBR1*, around 1 Mb away from *SHH*, which controls limb expression [6]. Enhancer variants within the *FTO* locus were shown to act through long-range chromatin interactions to regulate *IRX3/IRX5* rather than the nearest gene [7].

To capture these long-range enhancer-gene interactions, researchers have developed technologies to decipher 3D chromatin contacts, among which Hi-C has become the most widely used [8]. Hi-C is a genome-wide chromosome conformation capture (3C) technique in which chromatin is crosslinked, restriction-digested, and proximity-ligated, followed by paired-end sequencing to identify genomic loci that are physically close in the nucleus. Hi-C revealed that 3D chromatin organization is hierarchical. At the megabase scale, chromosomes segregate into A and B compartments

corresponding to active and inactive chromatin, respectively. At an intermediate scale, the genome is

partitioned into topologically associating domains (TADs), regions with enriched internal interactions.

At a finer scale, chromatin loops connect specific loci, often linking enhancers and promoters.

Chromatin looping within TADs constrains enhancer–promoter interactions and contributes to cell-

type-specific gene regulation [8]. One of the major advantages of Hi-C is its scalability and high

throughput, allowing the detection of fine-scale chromatin interactions such as enhancer-promoter

loops [9, 10]. Furthermore, Hi-C data can be integrated with other omics datasets to provide a

comprehensive view of gene regulation. However, mapping 3D genome interactions with Hi-C remains

technically challenging and prohibitively costly. High-resolution chromatin contact maps (e.g., ~5 kb

resolution requiring ~2 billion read pairs) are therefore available for only a limited number of cell types

and experimental conditions. To overcome the scarcity of 3D chromatin organization data, researchers

have increasingly turned to computational prediction methods, particularly deep learning approaches.

These models aim to infer chromatin interactions or Hi-C contact maps using multi-omics data. In

computational terms, this task is often described as modality prediction, where one or more data

modalities are used to predict another modality. This strategy reduces experimental costs and enables

reconstruction of missing biological layers that is otherwise experimentally difficult to obtain. In

sequence-to-function models, regulatory information is directly learnt from genomic DNA sequence

to predict diverse molecular readouts such as chromatin accessibility, transcription factor binding, and

gene expression, thereby linking genotype to gene regulatory function [11]. Several successful

examples of modality prediction have been reported. For instance, BABEL predicts chromatin

accessibility from gene expression, while MultiVI can impute missing RNA or ATAC profiles in partially

observed single-cell multiome datasets [12, 13].

Recent years have seen a rapid expansion of deep learning-based models predicting 3D

chromatin contact organization from DNA sequence and commonly generated epigenomic tracks.

Convolutional neural network (CNN)-based models have been particularly successful at predicting

genome-wide chromatin interactions [14], while transformer-based models have further advanced the

field by capturing long-range dependencies through self-attention mechanisms [15]. Hybrid architectures that combine CNNs and transformers have shown additional improvements by leveraging the strengths of both, extracting local sequence features with CNNs and modelling long-range relationships with transformers [16]. The development of these models has significantly improved our ability to predict Hi-C maps from accessible data sources such as Assay for Transposase-Accessible Chromatin using sequencing (ATAC-seq) and Chromatin Immunoprecipitation of CCCTC-binding factor (CTCF ChIP / CUT & RUN). Various other architectures, including some generative models, have been applied to this problem too [17]. These approaches not only aim to maximize predictive accuracy but also to enhance the quality, generalizability, and biological interpretability of predicted Hi-C maps. However, 3D chromatin architecture is strongly cell-type specific. Models relying only on DNA sequence lack regulatory context and therefore tend to predict similar structures across cell types. This limitation has motivated the development of multimodal and context-aware models that incorporate additional molecular measurements. The models compared in this study differ substantially in their input modalities and architectural assumptions. Epiphany predicts Hi-C contact maps using only epigenomic tracks, such as chromatin accessibility and histone modifications, combining with generative adversarial networks (GAN) model, enabling cell-type-specific prediction and visual fidelity [18]. ChromaFold instead focuses on using single-cell ATAC-seq (scATAC-seq) accessibility profiles, allowing recovery of cell-type-specific chromatin interactions from a few number of modalities [19]. GRACHIP integrates DNA sequence and genomic features within a graph neural network framework to explicitly model relationships between interacting loci [20]. HiCDiffusion predicts chromatin interactions directly from genomic DNA sequence only using a transformer encoder combined with a diffusion-based generative module. This model primarily investigates whether DNA sequence alone can sufficiently capture cell-type-specific Hi-C contact maps [17]. In contrast, C.Origami, which is often used as a benchmark model, primarily learns general chromatin folding patterns from sequence-derived features and does not inherently model cell-type-specific regulatory variation [21]. These approaches aim not only to improve prediction accuracy but also to reconstruct

biologically meaningful chromatin features, enabling inference of genome organization from widely

available multi-omics data such as ATAC-seq and CTCF profiling. However, a major challenge remains:

with many deep learning models now available, which one performs best, and under what criteria?

Previous models were typically evaluated only against a limited set of baseline models (e.g., C.Origami

[21] or Akita [22]) in their own method paper, focusing primarily on accuracy while neglecting other

aspects such as generalization and biological relevance. Consequently, there is no standardized

framework, nor neutral benchmarking effort, for evaluating or comparing deep learning models for Hi-

C prediction, making it difficult to assess their relative strengths and weaknesses. A comprehensive

benchmarking effort must therefore consider multiple evaluation dimensions, including robustness

across cell types, and the biological plausibility of predicted structures.

In this manuscript, we aim to systematically compare five representative models: C.Origami

[21], Epiphany [18], ChromaFold [19], HiCDiffusion [17], and GRACHIP [20]. The evaluation focussed

on multiple perspectives, including predictive accuracy, visual quality of the generated maps,

generalization ability across different cell types or species, and biological relevance for downstream

analyses. In addition, we performed ablation analyses to assess the necessity and contribution of each

input modality to model performance. These criteria were used to determine how closely the

predicted Hi-C maps resemble experimental data and how effectively each model captured meaningful

chromatin interactions. Through this neutral benchmarking, we identified the architectural designs,

input features, and training strategies that contribute to superior model performance. Ultimately, this

framework establishes a reference for standardized evaluation in future studies of 3D genome

modelling and promotes the reliable use of in silico Hi-C prediction in downstream applications.

Results

We compared five representative models for 3D chromatin contact prediction - C.Origami, Epiphany, ChromaFold, HiCDiffusion, and GRACHIP, using the evaluation workflow summarized in Figure 1. For each model, input data were pre-processed according to the recommended settings, and predicted Hi-C contact maps were generated across four human cell lines and 22 chromosomes. The predicted maps were then compared with experimental Hi-C data to assess model performance from multiple complementary perspectives. The predictions generated by each model were assessed using three criteria: (1) predictive accuracy, (2) image quality, and (3) loop detection performance. Predictive performance was firstly evaluated by direct comparison of predicted and experimental contact matrices using three quantitative metrics: mean squared error (MSE), insulation score correlation, and observed-over-expected (O/E) Hi-C correlation. To further examine the contribution of input information, ablation analyses were performed by removing individual modalities and measuring the resulting performance changes. Second, we evaluated the visual realism of predicted contact maps using the Fréchet Inception Distance (FID). Finally, predicted contact maps were processed with a loop-calling pipeline, and the detected chromatin loops were compared with loops identified from experimental Hi-C data to assess downstream biological utility.

Figure 1. Overview of this Hi-C prediction benchmarking study. *Input data, including DNA sequences and various epigenomic features, were first preprocessed according to the protocols described in the original studies for each model. The processed data were then used to train multiple deep learning models (C.Origami, Epiphany, HiCDiffusion, Chromafold, and GRACHIP), following their respective training procedures and dataset configurations. Each trained model was used to predict Hi-C contact maps. Both the predicted and real Hi-C data were further preprocessed to ensure a comparable format. Model performance was evaluated using several metrics. For accuracy, we computed MSE, insulation score correlation, and O/E Hi-C correlation. Insulation score correlation was calculated by first applying a natural logarithm transformation to the Hi-C matrices, then computing insulation scores, and finally measuring the Pearson correlation between the predicted and ground-truth insulation profiles. For O/E Hi-C correlation, each contact matrix was normalized by subtracting its mean to account for scale differences, then flattened into a vector, and the Pearson correlation was computed between predicted and real matrices. Ablation testing was conducted to assess the contribution of different input modalities. Image quality was evaluated using Fréchet Inception Distance (FID), where features were extracted using an InceptionV3 network and the Fréchet distance was computed between the feature distributions of predicted and real Hi-C images. Finally, loop detection analysis was performed using four loop-calling algorithms: Mustache, SIP, LASCA, and HiCCUPS.*

Accuracy performance evaluation

In this section, we compared the predictive accuracy of each model across different cell lines and performed a cross-model benchmark to identify the best-performing approach. Model performance was assessed using the quantitative performance metric MSE and the more biologically relevant metrics (insulation score correlation and O/E Hi-C correlation) (Methods). The insulation score

correlation measures how well a model captures local chromatin domain structure by comparing

insulation profiles, whereas O/E Hi-C correlation measures similarity of 3D contact patterns after

correcting for distance-dependent contact decay.

a. Within-model generalization across cell types and chromosomes

First, each model was evaluated independently by examining its performance by MSE scoring

across different cell lines and chromosomes (Figure 2). The top panel showed a bubble plot

summarizing model performance across chromosomes and cell lines, while the bottom panel displayed

violin plots illustrating the distribution of scores. Three notable patterns were observed. First, an

unexpected pattern was observed for HiCDiffusion, ChromaFold, and GRACHIP, where performance on

the training cell line was lower than on unseen cell lines. Second, the variability of MSE scores was

very large, with training performance ranging from near 0 to near 1 depending on the chromosome

and cell line. Third, C.Origami showed very high performance on the training data but extremely low

values on unseen cell lines, with scores close to 0, suggesting a complete failure of prediction

(C.Origami). Although previous reports that C.Origami was known to have limited ability to capture

cell-type-specific regulatory variation, performance values near zero are unexpected, as they would

imply a complete loss of predictive signal. Therefore, the near-zero scores cannot be explained solely

by overfitting, as even an overfitted model would be expected to retain some predictive signal. Instead,

this observation suggests that the MSE-based metric may not accurately reflect the true predictive

performance of the model under this evaluation setting.

Comparing the models based on the insulation score correlation, the results were more

consistent and easier to interpret (Figure 3). First, the variance across chromosomes and cell lines

appeared more stable and followed a tighter distribution, rather than spanning the extremely wide

range observed with MSE. Second, the relationship between training and unseen data aligned with

expectations, with performance on the training cell line being slightly higher than performance on

unseen cell lines. Third, although C.Origami showed reduced generalization to unseen cell lines, its

insulation score correlation remained within a reasonable range (approximately 0.5), suggesting

decreased performance rather than the apparent complete failure implied by the normalized MSE

results. A similar trend was also observed for the O/E Hi-C correlation (Supplementary Figure S1)

This discrepancy indicated that MSE was not well-suited for comparing these models and is

not appropriate as a universal comparison metric because the models are trained with different

optimization objectives. Epiphany directly minimizes a pixel-wise mean squared error (MSE) between

predicted and experimental Hi-C maps (optionally combined with an adversarial loss). In contrast,

C.Origami is trained to reproduce structural features of chromatin organization, with performance

evaluated using measures such as insulation score and distance-stratified correlation rather than strict

intensity matching. ChromaFold is optimized to predict normalized interaction signals and significant

contacts from accessibility patterns, while GRACHIP learns interaction relationships through a graph-

based representation of chromatin interactions. HiCDiffusion further departs from reconstruction-

based training by employing a generative diffusion framework that prioritizes realistic map structure

instead of minimizing pixel-wise error. Because these models minimize different objectives during

training, an external MSE metric often rewards models trained for numerical reconstruction and

penalizes those trained to recover structural or biological features. Therefore, MSE cannot fairly

represent real predictive performance across models. Moreover, MSE quantified only pixel-level

differences between contact matrices and therefore did not directly measure whether biologically

meaningful structures (such as TAD boundaries) were preserved. Finally, because MSE is unbounded

(ranging from 0 to infinity), min–max normalization and score inversion could distort interpretation; a

low inverted normalized score reflected poorer relative performance within the benchmark rather

than true model failure. For these reasons, subsequent evaluations focused primarily on insulation

score correlation and observed-over-expected (O/E) Hi-C correlation, which have been widely used to

assess the structural similarity and biological validity of predicted Hi-C contact maps in previous

studies. In particular, prior work evaluating models such as C.Origami, Epiphany, and related methods

relied on insulation profiles, normalized Hi-C similarity, and downstream interaction detection rather

than pixel-wise reconstruction error.

Figure 2. The performance of five Hi-C prediction models using normalized inverted MSE. *Inverted*
MSE is scaled between 0 and 1 with higher values indicating better performance. Top: Bubble plot. The
y-axis shows the 22 chromosomes, and the x-axis represents the cell lines. Colors are scaled
independently for each cell line. Triangles indicate trained chromosomes, and circles indicate unseen
chromosomes. Warmer (red) colors represent higher performance, while cooler (blue) colors indicate
lower performance. Bottom: Violin plot showing the distribution of model performance within each cell
line. The y-axis denotes the performance scores, and the x-axis corresponds to the cell lines. Green
indicates trained cell lines, and yellow indicates unseen cell lines.

Figure 3. The performance of 5 Hi-C prediction models using insulation score correlation. Top: Bubble plot. *The y-axis shows the 22 chromosomes, and the x-axis represents the cell lines. Colors are scaled independently for each cell line. Triangles indicate trained chromosomes, and circles indicate unseen chromosomes. Warmer (red) colors represent higher performance, while cooler (blue) colors indicate lower performance. Bottom: Violin plot showing the distribution of model performance within each cell line. The y-axis denotes the performance scores, and the x-axis corresponds to the cell lines. Green indicates trained cell lines, and yellow indicates unseen cell lines.*

Another key observation was that model generalization varied substantially (Figure 3). C.Origami performed best on its training cell line (IMR90), achieving insulation and O/E correlations above 0.9, but its accuracy dropped sharply for unseen lines such as K562 and H1. In contrast, Epiphany maintained high performance across all cell lines, with both correlation metrics exceeding 0.9, demonstrating strong transferability of learned chromatin features. Despite relying solely on DNA sequence, HiCDiffusion also generalized well, producing stable correlations above 0.8 across datasets. ChromaFold showed consistent and robust generalization, maintaining correlations above 0.85 even for unseen cell lines. Although trained on GM12878 and IMR90, its performance on IMR90 and H1 slightly exceeded that on GM12878, suggesting that the model captured transferable regulatory

features rather than overfitting. GRACHIP achieved lower overall performance but showed minimal

variation across cell lines, indicating stable, though less accurate, generalization.

b. Cross-model comparative analysis of Hi-C prediction performance

Subsequently, the models were compared against one another across 22 chromosomes in a

specific cell line to identify the strongest performer (Figure 4). The figure reorganizes the previously

obtained results and displays the models side by side to enable direct performance comparison. As

can be seen, Epiphany achieved the highest overall performance in all metrics, averaging around 0.90

and 0.85, respectively, across all cell lines. ChromaFold followed closely, with strong consistency and

minimal variation. C.Origami, again, displayed clear overfitting on the trained cell line, while

HiCDiffusion achieved notable accuracy from sequence data alone, although its insulation score

correlations were slightly lower than its observed/expected (O/E) Hi-C correlations. GRACHIP ranked

lowest, particularly in O/E correlation, around 0.5, reflecting weaker fine-scale reconstruction, though

it retained moderate TAD-level (insulations core) accuracy.

Figure 4. Comparison of model performance for each dataset using insulation score correlation and O/E Hi-C correlation. *Top: Bar plot - The y-axis shows the performance score, and the x-axis lists the models, each represented by a distinct colour. Bottom: Line plots - The y-axis shows the performance score across chromosomes, while the x-axis lists chromosome indices. Each line corresponds to a different model, illustrating how model performance varies across genomic regions.*

When evaluating performance across individual chromosomes, it was observed that most models exhibited similar trends, consistently struggling with chromosomes 9, 15, 22. This pattern appeared regardless of the specific chromosomes used during training or held out for testing,

suggesting that these particular chromosomes might possess structural complexity that were more

challenging for models to learn and generalize from. However, despite this challenge, stronger models

such as Epiphany and ChromaFold were still able to achieve relatively high scores on these difficult

chromosomes.

c. Ablation analysis

Ablation testing was performed to quantify the contribution of different input data modalities

to Hi-C prediction accuracy, thereby identifying which biological signals were most informative for each

model. Specifically, the test was conducted to determine how individual input modalities influence Hi-

C prediction accuracy and to investigate whether different regulatory signals provide overlapping

information. We systematically removed single modalities or biologically related modality groups and

measured the resulting change in prediction performance, thereby assessing potential redundancy

and compensatory effects among the input tracks. Due to models with many inputs, only individual

modalities and biologically relevant modality groups were tested on four chromosomes (5, 6, 10, and

15). HiCDiffusion was excluded because it relies solely on DNA sequence.

Figure 5. Epiphany ablation performance across modalities, cell lines, and chromosomes, using
insulation score correlation. Top: Bar plot showing ablation results; the x-axis lists the removed
modality, and the y-axis shows insulation score correlation. Bottom: Heatmap with chromosomes on
the y-axis and removed modalities on the x-axis; each cell's color and value indicate the corresponding
performance.

Figure 5 shows the insulation score–based ablation results for Epiphany across input

modalities, cell lines, and chromosomes. Corresponding ablation results for the other models and

additional evaluation metrics were provided in the Supplementary Material (Supplementary Figure S3

- S13). For clarity, Table 1 summarized the most important input modalities for each model, as

determined by ablation results using both insulation score correlation and observed/expected (O/E)

Hi-C correlation. Following ablation testing, C.Origami showed a pronounced dependence on CTCF

input: removing the CTCF track led to a drastic reduction in performance, indicating that it was the

most critical modality for accurate prediction. Notably, the combined use of CTCF binding and ATAC-

seq signals further improved predictions, indicating that chromatin accessibility provides

complementary information to CTCF binding. In contrast, DNA and ATAC-seq signals alone contributed

little in unseen cell lines, indicating potential overfitting to the training data. Similarly, Epiphany's performance dropped sharply when CTCF binding was removed (insulation correlation <0.8), whereas excluding DNA or histone marks had minimal effect (Figure 5). For ChromaFold, ablation revealed that co-accessibility information was indispensable: removing this feature led to near-zero performance, indicating that the model depends on relationships between accessible regions rather than accessibility peaks alone. This observation is consistent with the original study, which reported that co-accessibility derived from scATAC-seq provides a substantial improvement over pseudobulk accessibility alone. In addition, removal of the CTCF binding signal also reduced performance, suggesting that CTCF binding provides complementary structural information that supports accurate prediction. GRACHIP relied heavily on DNA, with its removal reducing performance to near zero; ATAC-seq also contributed modestly to insulation accuracy. Across models, ablation effects were consistent across chromosomes, suggesting global rather than region-specific dependencies. From all the tests, it revealed that CTCF binding emerged as the most influential feature in most of models, highlighting its essential role in defining chromatin architecture (Table 1).

Table 1. Summary of important modalities in each model.

Model	Important modalities
C.Origami	1. CTCF ChIP-seq
	2. bulk ATAC-seq
Epiphany	1. CTCF ChIP-seq
ChromaFold	1. scATAC-seq
	2. CTCF motif scores
GRACHIP	1. DNA sequence
	2. bulk ATAC-seq

Figure 6. Visual realism of predicted Hi-C contact maps across cell lines. *Top: Bar plot showing Fréchet Inception Distance (FID) for each model across cell lines. Bottom: Representative predicted contact maps from each model compared with the corresponding experimental ground-truth Hi-C maps.*

Image quality evaluation

This section evaluated the quality of predicted Hi-C maps using the Fréchet Inception Distance (FID), which measures similarity between real and predicted images by comparing the statistical distributions (mean and covariance) of their feature embeddings (Methods). C.Origami, ChromaFold, and GRACHIP produced blurred or low-contrast maps, reflected in high FID scores exceeding 20. In some cases, trained cell lines even yielded higher FID values than unseen ones, consistent with these models' optimization for numerical rather than perceptual accuracy.

By contrast, Epiphany and HiCDiffusion achieved significantly better image quality. Epiphany consistently produced the lowest FID scores, which means near-realistic reconstruction of

experimental Hi-C maps. HiCDiffusion achieved intermediate performance (FID around 10), due to its

generative diffusion process. Overall, the GAN-based Epiphany generated the most visually accurate

and biologically plausible contact maps (Figure 6).

Downstream analysis: loop detection

Chromatin loop detection was used to evaluate the biological relevance of the predicted Hi-C

maps. Chromatin loop detection is a downstream Hi-C analysis task that aims to identify specific long-

range point-to-point interactions between genomic loci, which appear as focal enrichment "dots"

above the local background in Hi-C contact matrices. These loops often reflect structural or regulatory

interactions, such as enhancer–promoter contacts mediated by architectural proteins (e.g.,

CTCF/cohesin), therefore provide a biologically meaningful readout of chromatin organization. To

evaluate whether predicted Hi-C maps preserved such biologically relevant features, four loop-calling

tools, LASCA [23], HiCCUPS [24], SIP [25], and Mustache [26], were compared in the application to both

experimental and predicted maps.

a. Functional evaluation of loop detection across models and loop-caller tools

To assess the biological relevance of the detected chromatin loops, loop anchors were

compared with independent transcriptional regulatory evidence from three complementary external

resources. Curated transcription factor (TF)–target regulatory interactions were obtained from

CollecTRI [27], which compiles literature-supported regulatory relationships. Functional downstream

targets of TF perturbation were retrieved from KnockTF 2.0 [28], a database of gene expression

changes following TF knockdown or knockout experiments. Direct TF–DNA binding evidence was

obtained from ChIP-Atlas [29] using ChIP-seq datasets specific to the K562 cell line. These datasets

represent distinct levels of regulatory support: CollecTRI provides prior knowledge of regulatory

interactions, KnockTF captures functional effects of TF perturbation, and ChIP-Atlas provides cell-type-specific physical TF binding. Rather than claiming direct causality, we evaluated whether predicted chromatin loops were supported by any of these independent regulatory evidences. A loop was considered biologically supported when at least one anchor overlapped a TF binding site (ChIP-Atlas), a TF-regulated gene (KnockTF), or a curated TF–target interaction (CollecTRI). This integration enabled both quantification of loop recovery and assessment of their potential functional relevance. (Methods).

Table 2. Results of loop detection for each model and specified tools in cell line K562.

Model	Loop calling tool	Total loops	Enhancer-promoter loops (% of total)	CollecTRI (% of total)	ChIP-Atlas (% of total)	KnockTF (% of total)
C.Origami	SIP	13758	3277 (23.8%)	1519 (11.0%)	2971 (21.5%)	898 (6.5%)
	LASCA	43304	8099 (18.7%)	3538 (8.1%)	7228 (16.6%)	1841 (4.3%)
	Mustache	11891	2789(19.9%)	1014(8.5%)	2177(18.3%)	571 (4.8%)
	HICCUPS	2489	776 (31.1%)	334 (13.4%)	740 (29.7%)	259 (10.4%)
Epiphany	SIP	9370	1589 (16.9%)	694 (7.4%)	1422 (15.1%)	317 (3.4%)
	LASCA	93574	9986 (10.6%)	3804 (4.0%)	8537 (9.1%)	1504 (1.6%)
	Mustache	5515	1425 (25.8)	680 (12.3%)	1341 (24.3%)	426 (7.7%)
	HICCUPS	2664	756 (28.3%)	349 (13.1%)	728 (27.3%)	249 (9.3%)
HiCDIffusion	SIP	20823	2390 (11.4%)	1018 (4.8%)	1969 (9.4%)	369 (1.8%)
	LASCA	111045	7414 (6.6%)	2676 (2.4%)	6018 (5.4%)	983 (0.9%)
	Mustache	10617	1808 (17.0%)	793 (7.4%)	1588 (14.9%)	403 (3.8%)
	HICCUPS	4250	469 (11.0%)	115 (2.7%)	397 (9.3%)	65 (1.5%)
ChromaFold	SIP	1220	528 (43.2%)	310 (25.4%)	525 (43.0%)	319 (26.1%)
	LASCA	18000	1738 (9.6%)	636 (3.5%)	1561 (8.6%)	300 (1.7%)
	Mustache	4693	1281 (27.2%)	657 (13.9%)	1227 (26.1%)	493 (10.5%)

GRACHIP	HICCUPS	134	48 (35.8%)	29 (21.6%)	46 (34.3%)	38 (28.4%)
	SIP	4065	468 (11.5%)	194 (4.7%)	388 (9.5%)	63 (1.5%)
	LASCA	3844	422 (10.9%)	164 (4.2%)	349 (9.0%)	62 (1.6%)
	Mustache	703	91 (12.9%)	29 (4.1%)	84 (11.9%)	16 (2.3%)
True HiC (ground truth)	HICCUPS	22	2 (9.1%)	0 (0.0%)	2 (9.1%)	0 (0.0%)
	SIP	7846	1823 (23.2%)	827 (10.5%)	1768 (22.5%)	496 (6.3%)
	LASCA	194086	14855 (7.6%)	5226 (2.6%)	12020 (6.1%)	1868 (1.0%)
	Mustache	8871	2388 (26.9%)	1098 (12.3%)	2303 (25.9%)	700 (7.9%)
	HICCUPS	3513	1145 (32.5%)	499 (14.2%)	1130 (32.1%)	370 (10.5%)

As expected, loops detected from true Hi-C data showed the highest counts and served as the

reference set (Table 2). Among predicted contact maps, Epiphany and C-Origami produced the largest

number of loops, whereas GRACHIP detected substantially fewer, consistent with its lower structural

accuracy. However, loop quantity did not directly correspond to biological support. Loops overlapping

K562-specific TF binding sites from ChIP-Atlas were more frequent than those supported only by

curated regulatory associations from CollecTRI, indicating that cell-type-specific binding provides

stronger support for chromatin looping than general regulatory knowledge. This observation is

consistent with established models in which chromatin loops are mediated by active transcription

factors in a context-dependent manner. Several models recovered loops enriched for TFs known to be

active in K562 cells, including CTCF, RAD21, and NKRF. CTCF and RAD21 are central architectural

proteins involved in loop extrusion and maintenance of topologically associating domains, whereas

NKRF functions as a transcriptional repressor of immune-related genes [27, 28]. Many predicted loops

connected TF binding regions to nearby gene targets, including EIF4G2 and AP2A2 (NKRF-associated),

SVIL (RAD21-associated), and SLIT1 and S1PR1 (CTCF-associated), which are relevant to hematopoietic

cell function. Nevertheless, loops simultaneously supported by TF binding, regulatory association, and

validated downstream targets were rare even in true Hi-C data, reflecting the stringent criteria required

to define a functional regulatory chromatin interaction.

Among loop callers, LASCA detected the largest number of loops but exhibited limited overlap

with regulatory evidence, suggesting high sensitivity but lower specificity. In contrast, Mustache and

SIP detected fewer loops but a higher proportion of biologically supported interactions: approximately

25% overlapped K562-specific TF binding sites and 10% overlapped curated TF regulatory interactions,

indicating improved biological precision. HiCCUPS, which relies on sharp focal interaction peaks,

performed poorly on GRACHIP maps and detected only 22 loops.

Figure 7: Loop overlap between five models and the true Hi-C map across different loop callers.
Heatmaps show the number of overlapping chromatin loops identified between pairs of models and/or
ground-truth Hi-C data. In each heatmap, both the x- and y-axes represent the predicted Hi-C maps
from different models as well as the true Hi-C dataset. Each cell indicates the number of overlapping
loops between the corresponding pair. Color intensity represents the magnitude of overlap, ranging
from blue (lowest overlap) to red (highest overlap). Each row corresponds to a different loop-calling
algorithm (Mustache, SIP, LASCA, and HiCCUPS). Columns represent different subsets of loops, ordered

from left to right: (1) total loops detected by each loop caller (including both biologically meaningful
and non-biological loops), (2) loops overlapping enhancer–promoter interactions, (3) loops supported
by collectTRI, (4) loops supported by ChIP-Atlas, and (5) loops supported by the KnockTF database.

Figure 8. Precision–recall analysis of chromatin loops supported by ChIP-Atlas dataset. *The y-axis*
indicates precision, and the x-axis indicates recall, using loops derived from the true Hi-C map as the
ground truth reference. Each marker represents one combination of a Hi-C prediction model and a loop-
calling tool. Marker colour denotes the prediction model, while marker shape denotes the loop caller.

b. Cross-model loop overlap using individual loop caller

The biological relevance of predicted Hi-C maps was evaluated by comparing chromatin loops

identified from five prediction models against loops derived from the true Hi-C map. For consistency,

all loop calls were performed using the same loop-calling tool within each comparison. A loop was

initially considered overlapping only if both of its anchors matched those of a loop in another dataset.

C.Origami and Epiphany consistently achieved the highest overlap between predicted biologically

supported loops and loops derived from the real Hi-C map across most loop-calling tools (Figure 7).

Epiphany's strong performance was expected given its high-resolution contact maps and high visual

fidelity. Interestingly, C.Origami also performed well despite producing comparatively blurred contact

maps and demonstrating limited generalization. This suggests that key latent chromatin interaction

patterns were still preserved in C.Origami predictions, allowing loop callers, particularly LASCA and

Mustache, to recover biologically meaningful interactions even from more diffuse signals. Therefore,

visual sharpness alone was not sufficient to fully explain the biological utility of a predicted Hi-C map.

To quantify loop-calling performance, predicted loops were first compared to loops detected

in the true Hi-C map. Loops present in both the predicted and true Hi-C maps were defined as true

positives, loops detected only in the predicted map as false positives, and loops present only in the

true Hi-C map as false negatives. Using these definitions, precision and recall were calculated for each

combination of prediction model and loop-calling tool, and the results were summarized in a two-

dimensional precision–recall space (Figure 8). In addition to structural agreement with the true Hi-C

loops, we evaluated biological support using three independent regulatory evidence sources: curated

TF–target interactions (CollecTRI), functional TF perturbation targets (KnockTF 2.0), and K562-specific

TF binding sites (ChIP-Atlas). Across all loop callers, Epiphany and C.Origami consistently ranked among

the top-performing models in both precision and recall, indicating robust performance regardless of

the loop-calling method used. ChromaFold showed more variable behaviour: it achieved high precision

with SIP and obtained the best precision and recall among models when using Mustache, but

performance dropped substantially when using other loop callers. Similar trends were observed when

evaluating all detected loops and other categories of biologically supported loops (Supplementary

Figure S15). Collectively, these results indicate that Epiphany and C.Origami provide the most stable

and reproducible performance across multiple loop-calling tools.

Despite these differences, it is important to note that absolute precision and recall values

remained low across all models (both metrics typically < 0.15), indicating the inherent difficulty of

recovering true chromatin loops from predicted contact maps. To complement structural accuracy, we

evaluated the biological support of detected loops. For each loop caller, we calculated the proportion

of detected loops whose anchors overlapped independent regulatory evidence from CollecTRI,

KnockTF 2.0, or K562-specific ChIP-Atlas binding sites (Figure 9), This metric represents the fraction of

predicted loops supported by known or functional regulatory interactions relative to the total number

of loops detected, thereby distinguishing potentially functional loops from background structural

detections. Using this measure, C.Origami and Epiphany exhibited distributions similar to those of the

true Hi-C map across loop callers. This suggests that, although the exact overlap with the ground-truth

loop set was limited, these models maintained a comparable ability to generate loops enriched for

biological regulatory interactions. In other words, Epiphany and C.Origami produce fewer ground-

truth-matching loops, but the loops they do enable are biologically meaningful at a rate comparable

to real Hi-C, supporting their utility for downstream biological interpretation.

Figure 9. Percentage of biologically supported loops among all detected loops across models and
loop callers. *The y-axis represents the percentage of biologically supported loops relative to the total*
number of detected loops. Each panel contains six groups of bars, corresponding to the five prediction
models and the true Hi-C map. Bar colour indicates the loop-calling tool used to detect loops.

c. Cross-tool loop overlaps within each predicted model

Loop-calling tools also influenced overlap outcomes. HiCCUPS detected fewer overlapping

loops due to its dependence on sharp signal peaks, whereas LASCA, Mustache, and SIP were more

tolerant to noise and better captured biologically relevant structures. This highlighted the importance

of using flexible, noise-resilient tools for analysing predicted Hi-C.

To better understand the behaviour of different loop-calling tools when applied to the same

predicted Hi-C map, the overlap of loops identified by SIP, HICCUPS, LASCA, and Mustache within each

individual model was evaluated (Supplementary Figure S14). The analysis revealed limited consistency

across tools, only a small fraction of loops, particularly enhancer–promoter or TF-associated loops,

were shared by all four. Models producing higher-quality predictions, such as Epiphany and C.Origami,

exhibited greater cross-tool agreement, indicating that more accurate structural reconstructions

yielded more reproducible loop calls. In contrast, models with noisier outputs, like GRACHIP, showed

minimal overlap due to inconsistent or spurious detections.

Among the tools, Mustache and SIP demonstrated the highest overlap, likely due to their

shared computer vision–based algorithms that emphasize local spatial patterns. LASCA and HiCCUPS,

though both clustering-based, differed in behaviour: LASCA detected the most loops but with low

biological precision (only around 10% overlapped with known regulatory features), while HiCCUPS

remained overly conservative at 10 kb resolution, missing many valid interactions. Biologically

meaningful loops identified by three or more tools were rare but often involved enhancer–promoter

pairs with TF binding, suggesting that multi-tool consensus loops were highly functionally relevant.

In addition, as shown in Figure 9, HiCCUPS detected the fewest loops among the four tools,

yet the fraction of loops overlapping known biological regulatory features was among the highest. This

trend was observed not only for the ground-truth Hi-C map but also for most predicted contact maps

(except for ChromaFold), with Mustache generally showing the next best performance. This pattern

was consistent with previous reports indicating that both HiCCUPS and Mustache performed robustly

at 10 kb resolution, where their detection strategies tended to prioritise high-confidence interactions

[32]. Interestingly, ChromaFold showed a distinct behaviour: although HiCCUPS and Mustache still

yielded high biological precision, SIP consistently achieved the best performance in most cases.

Moreover, the fraction of biologically supported loops in ChromaFold was unexpectedly comparable

to, or even higher than, that observed in the ground-truth Hi-C map, despite ChromaFold producing

fewer loops than true Hi-C and fewer than other high-performing models such as Epiphany and

C.Origami. These results suggested that ChromaFold tended to produce a smaller set of loop

candidates, yet this set was preferentially enriched for biologically supported interactions and

reproducible across loop-calling methods.

Discussion

Summary of model characteristics

In this manuscript, five deep learning models, C.Origami, Epiphany, HiCDiffusion, ChromaFold

and GRACHIP, were systematically evaluated for their ability to predict Hi-C contact maps and recover

biologically meaningful chromatin features, such as loops. These models differed in their architectures,

input modalities, and training strategies, resulting in variable performance in prediction accuracy,

generalizability, image quality, and biological interpretability. For clarity, each model was compared

based on five key aspects: prediction accuracy, generalization across cell lines, input type (single-omic

or multi-omics), visual quality of contact maps, and capacity to detect chromatin loops, particularly

enhancer–promoter interactions.

C.Origami demonstrated high accuracy in the cell line on which it was trained [21]; however,

its performance dropped markedly when applied to unseen cell types, indicating limited

generalizability. The model integrates genomic sequence with epigenomic features such as ATAC-seq

and CTCF binding. Ablation analysis further revealed a strong dependence on the CTCF track, while

other modalities contributed less. Although the visual quality of its predicted maps was relatively low

and appeared blurred, the model still captured relevant biological patterns, particularly for loop

detection. This observation is consistent with the original study, which identified CTCF as a key

determinant of genome organization and loop formation. Accordingly, despite blurred contact maps,

C.Origami recovered biologically meaningful chromatin structures, including CTCF–CTCF and

promoter–enhancer loops.

Epiphany showed strong and balanced performance and generalized well to new cell types.

This agrees with the original study, which specifically designed the model to overcome the limitation

of sequence-only predictors that fail to generalize across cell types [18]. This capability is likely driven

by its use of multiple epigenomic tracks, including DNase/ATAC-like accessibility, CTCF, and histone

modifications such as H3K27ac. Furthermore, by incorporating a GAN-based framework, Epiphany

produced visually sharp contact maps that closely resembled experimental Hi-C data. Consequently,

Epiphany performed well in detecting both general and biologically supported loops. One limitation,

however, is its restricted window size of 1 Mb, which allows detection of interactions up to this distance

but may miss longer-range interactions.

HiCDiffusion, which uses only genomic DNA sequence as input, performed surprisingly well

[17]. However, sequence-based prediction inherently lacks cell-state information, and prior studies

have shown that sequence-only models tend to predict similar structures across cell types because

DNA sequence does not encode dynamic regulatory states. The diffusion-based generative framework

primarily improves visual quality by reducing blurring in predicted heatmaps and optimizing image

realism, as reflected by improvements in the FID. Therefore, although HiCDiffusion produced visually

clear maps, its biological specificity should be interpreted cautiously.

ChromaFold achieved moderate accuracy but showed good cross-cell-type generalization.

Unlike C.Origami and Epiphany, it relies primarily on single-cell chromatin accessibility and CTCF motif

information rather than multiple bulk epigenomic assays [19]. The original study demonstrated that

co-accessibility between accessible regions reflects chromatin looping events and enables prediction

of cell-type-specific interactions. Previous benchmarks also reported performance comparable to

C.Origami and even improved performance when appropriate CTCF information was included. Our

ablation results, showing a strong dependence on co-accessibility features, are consistent with this

interpretation. The model's lighter architecture and reduced modality requirements may also reduce

overfitting relative to heavily parameterized multi-omics models. Although the predicted maps

appeared blurred and the visual quality was limited, ChromaFold was still able to recover chromatin

loops, including both general and context-specific interactions.

GRACHIP showed weaker predictive performance in our evaluation despite being designed to

improve generalization. The model incorporates DNA sequence, ATAC-seq, and CUT&RUN-derived

regulatory features, including CTCF and histone marks, and additionally encodes prior chromatin

interaction intensity using a graph neural network [20]. The authors proposed that incorporating

interaction relationships would enhance cross-cell-line prediction; however, they also noted that many

predictive models, including C.Origami, exhibit performance variability across different cellular

contexts. Our results suggest that although the graph-based representation may help capture

interactions, it did not translate into improved Hi-C reconstruction accuracy or loop recovery in this

benchmark setting.

We summarized the ranking performance of each model across four evaluation categories:

accuracy, generalizability, visual quality, and loop detection (Figure 10). Overall, Epiphany ranked

highest across all evaluation criteria. C.Origami performed strongly in accuracy and loop detection but

showed poor generalization across different cell types. Despite relying only on genomic DNA sequence,

HiCDiffusion achieved moderate performance in both generalizability and loop detection. ChromaFold

showed consistently moderate performance across all categories, whereas GRACHIP demonstrated the

lowest overall performance despite using the largest number of input modalities.

	Performance				Modality	
	Accuracy	Generalizability	Image quality	Loop detection	% Effective modalities	Total modalities
C.Origami	2	5	4	2	○	3
Epiphany	1	1	1	1	·	5
HiCDiffusion	4	3	2	3	□	1
ChromaFold	3	2	5	4	●	3
GRACHIP	5	4	3	5	●	7

Figure 10. Summary of the evaluation characteristic of each chromatin contact prediction model. *Accuracy was ranked based on the average values of two biological metrics, insulation score correlation and O/E Hi-C correlation, calculated across the training cell lines. Generalizability was evaluated using the same metrics averaged across previously unseen cell lines. Visual quality was ranked according to the average FID values across all cell lines. Loop detection performance was determined by the number of biologically meaningful loops predicted by each model relative to the ground truth Hi-C map, averaged across all loop-calling tools. The number of input omics modalities used by each model was also summarized, together with the proportion of modalities contributing measurably to performance, referred to as the "% effective modalities".*

Insights from the comparative analysis

From the neutral benchmark, several key insights emerged. More input modalities did not necessarily guarantee better performance. Multi-omic models often learned disproportionately from one dominant signal, typically CTCF, while neglecting others , as shown by the ablation analysis in Figure 5 and Supplementary Figure S3-S15, where removal of the CTCF track produced the largest performance decrease compared with other modalities. HiCDiffusion, despite using only genomic sequence, performed comparably or even better than some multi-omic models, demonstrating the importance of model architecture and training strategy over the number of input features.

CTCF binding was a critical input feature across models [33]. As a central player in organizing 3D chromatin architecture, CTCF defines loop anchors and TAD boundaries [31]. Models incorporating experimentally measured CTCF binding generally achieved improved structural reconstruction, particularly for boundary and loop features. However, previous studies also noted that CTCF alone is insufficient to capture cell-type-specific chromatin organization [30]. Additional regulatory context,

such as histone modifications or co-accessibility between regulatory elements, was often required to

recover accurate and biologically meaningful interaction patterns. Thus, while CTCF provides essential

structural information, effective Hi-C prediction depends on combining it with complementary

regulatory signals rather than relying on it as a single determinant of genome architecture.

As noted above, many models incorporate multiple input modalities, yet only a subset of these

signals substantially influences performance. This suggests that current architectures may not fully

exploit the available information and may introduce unnecessary complexity. Importantly, beyond DNA

sequence and chromatin accessibility (e.g., ATAC-seq), other epigenomic signals such as histone

modifications and transcription factor binding are not as broadly available across cell types, conditions,

or species, which may limit the practical applicability of such models. In addition, these epigenomic

features are highly context-dependent, raising questions about whether signals derived from one

cellular or disease context can be effectively transferred to others. Future work should therefore focus

on developing approaches that more effectively integrate complementary regulatory signals while

accounting for their availability and context specificity, and on balancing model complexity with

informative input features. Improving how modalities are utilized may enhance both prediction

robustness and biological interpretability.

MSE proved to be a limited evaluation metric. It did not adequately capture biological

relevance or map quality and was highly dependent on model architecture and loss function. For

example, models that directly optimized MSE (e.g., C.Origami) often showed artificially low error on

training data, while models using adversarial or generative losses (e.g., Epiphany, HiCDiffusion)

exhibited higher MSE despite producing biologically realistic and visually accurate maps. Therefore,

MSE alone was insufficient to judge model performance. Although MSE is widely used in general

machine learning applications, it was not commonly adopted for evaluating Hi-C prediction models.

Among the reviewed models, only a few, such as C.Origami, used MSE to assess accuracy, primarily for

internal comparisons within the model rather than across different model [21]. In C.Origami's case,

MSE was supplemented with additional evaluation methods, including insulation-based metrics and

correlation-based measures, to better reflect biological relevance. In contrast, most comparative

studies between models, such as those involving HiCDiffusion vs C.Origami, GRACHIP vs C.Origami, or

Epiphany vs Akita, generally avoided MSE altogether. Instead, they focused on metrics more

informative for assessing biological and structural fidelity [17, 18, 20]. These typically included

correlation-based metrics, such as Pearson and Spearman correlation coefficients, which measured

linear and rank-based similarities between predicted and experimental Hi-C matrices, respectively.

Other frequently used metrics assessed the ability of models to replicate distance-dependent decay

patterns in Hi-C data, such as the O/E ratio and stratum-adjusted correlation coefficient (SCC), which

controlled for genomic distance effects [34]. Additionally, metrics based on higher-order chromatin

structures, including insulation score correlation and TAD boundary recovery rate, were employed to

evaluate the accuracy of TAD predictions [35]. In this study, we employed not only MSE but also two

biologically meaningful evaluation strategies: distance-dependent decay analysis using O/E correlation

and TAD-level evaluation using insulation score correlation. Further refinement could include metrics

like the stratum-adjusted correlation coefficient or distance-specific correlation measures, which offer

a more nuanced understanding of how well predicted contact maps reflect the complex spatial

organization of the genome.

Another important consideration is that the models evaluated in this study were originally

trained on different cell lines. To maintain fidelity to the published versions, we used the original

training settings and verified reproducibility through limited retraining. While this ensures that the

models were assessed as intended for practical use, it introduces a potential limitation in comparability

due to differences in training data. Notably, following the original papers, ChromaFold was trained on

two cell lines, whereas the other models were trained on a single cell line. This may have contributed

to differences in performance and generalizability; however, the current analysis does not allow us to

disentangle the effects of model architecture from those of training data diversity. Future work could

address this by retraining all models on standardized datasets to enable a more controlled comparison.

Finally, the performance of the same deep learning model varied across different

chromosomes. For example, the prediction accuracy tended to fluctuate across the 22 chromosomes,

with some chromosomes showing peaks in performance while others exhibited noticeable decreases.

Interestingly, in the same model, this trend was almost consistent across four different cell lines: H1,

GM12878, IMR90, and K562, despite their biological differences. Even when using five different

models, all trained on different chromosomes or cell lines, a similar performance pattern was

observed. Specifically, a drop in prediction accuracy was consistently seen on chromosomes 9, 15, and

22 across all models and cell lines. This consistent decrease suggested that chromosomes 9, 15, and

22 presented unique challenges for generalization and prediction, regardless of the model architecture

or training data. There were several potential biological and technical explanations for this

observation. First, chromosome size may play a role. Smaller chromosomes, such as chromosome 22,

contains fewer genomic loci and thus generated fewer interaction pairs in Hi-C data [36]. This results

in sparser contact maps, which were more difficult for models to learn and accurately predict. Second,

the structural complexity of certain chromosomes may affect performance. For instance,

chromosomes 9 and 15 are known to contain complex repetitive regions and were hotspots for

chromosomal translocations [37]. These structural variations lead to mapping ambiguities and reduced

the quality of Hi-C signals, making it harder for models to learn consistent patterns. Third, chromatin

interaction also varies across chromosomes: gene-rich chromosomes have denser transcriptional

activity and more regulatory interactions, whereas gene-poor chromosomes exhibit sparser patterns

[8]. If a model is trained on more chromosomes with rich regulatory interactions and then tested on

chromosomes with sparse or fundamentally different interaction landscapes, performance can drop

due to poor generalization. These differences directly affect Hi-C signal patterns and may influence

how easily a model can learn and generalize across chromosomes. In addition, variability in sequencing

depth, differences in chromatin organization (such as TADs and compartments), and uneven

distribution of epigenomic features like CTCF binding sites and histone modifications might also

contribute to performance differences across chromosomes. Taken together, these findings indicate

that both biological properties and technical factors influenced model performance across

chromosomes in our benchmark, consistent with known variability in Hi-C data and chromatin

organization.

Loop detection from predicted Hi-C map

Loop detection represents an important biologically meaningful downstream application of

predicted Hi-C contact maps. While most previous Hi-C prediction studies primarily evaluated

downstream performance using TADs, loop-level interactions have received far less attention.

Moreover, when loops were assessed, studies typically relied on a single loop-calling method, such as

HiC-DC+, to identify significant interactions. Because different loop callers rely on distinct algorithmic

principles, the choice of method can substantially influence loop detection results. To our knowledge,

few studies have systematically examined how different loop-calling algorithms perform on predicted

Hi-C maps, making this analysis an important contribution of the present work.

Our results show that, although the evaluated prediction models operated at a relatively

coarse resolution (around 10 kb), many were still able to recover biologically relevant interactions,

including enhancer–promoter loops and TF-associated chromatin contacts. Nevertheless, precision

and recall values remained low when predicted loops were directly compared with loops derived from

the true Hi-C map. This limited performance is expected for several reasons. First, prediction errors in

contact intensity and local structural patterns can introduce noise, resulting in inconsistent loop

detection across callers. Second, the 10 kb resolution itself imposes a fundamental constraint: at this

scale, fine chromatin features, particularly short-range or tightly localized interactions, may be blurred,

merged, or lost entirely. In addition, resolution mismatch and boundary uncertainty complicate the

mapping of loop anchors between predicted and true Hi-C, further reducing apparent overlap even for

biologically related interactions. This indicates resolution as a key limitation for accurate loop recovery.

Future work should explore higher-resolution predictions (e.g., 5 kb or 1 kb) or post hoc enhancement

methods to improve loop detection.

Another consideration is the choice of the loop-calling tool. Predicted maps often contained

noise, blur, or artifacts that are not present in real Hi-C data. Some tools, like HICCUPS, which are

sensitive to sharp peaks and clean signals, performed poorly on predicted maps. In contrast, tools

based on computer vision (e.g., Mustache, SIP) showed more robust performance, likely due to their

tolerance to noise and blurred patterns [32]. Similar observations have been reported in recent loop-

detection studies, where algorithm performance depends strongly on signal quality and map

resolution[32]. These observations suggest that loop-caller performance depends not only on

algorithm design but also on structural pattern of the predicted contact maps.

Importantly, the structural quality of the predicted contact maps appeared to be more critical

than the specific choice of loop-calling tool. When a predicted contact map closely resembled the

ground truth Hi-C map in both signal characteristics and visual structure, as was observed with models

like Epiphany and HiCDiffusion, most loop callers, including sensitive ones like HICCUPS, were able to

effectively detect chromatin loops. This indicates that, under high-quality input conditions, different

loop-calling algorithms tend to converge on similar biologically meaningful interactions.

It is often assumed that visual fidelity correlates with structural quality; however, an important

exception was observed for C.Origami. Although C.Origami was not explicitly optimized to improve the

visual realism of predicted contact maps, it still performed strongly in loop detection. Specifically, its

overall loop-calling performance was consistently second only to Epiphany and exceeded that of

HiCDiffusion, while also producing a substantial number of biologically supported loops overlapping

those derived from true Hi-C. Notably, C.Origami enabled recovery of a relatively large number of loops

consistently across multiple loop callers, including conservative tools such as HiCCUPS, indicating that

its predicted contact maps retained sufficient structural pattern for robust loop identification. These

results indicate that loop callers may be robust to certain forms of visual blurring, as long as key

underlying chromatin interaction patterns are preserved.

This insight also raises an important question: to what extent does visual fidelity contribute to

the overall quality of predicted Hi-C maps for reliable loop detection? In this study, it was difficult to

disentangle the effects of visual quality and prediction accuracy, as ,for example, Epiphany performed

strongly in both aspects: achieving strong accuracy, generating visually realistic maps, and showing

greater overlap with true biological loops. As Epiphany combined accurate prediction with GAN-based

refinement that improved map sharpness, the independent contribution of visual quality to loop-

calling outcomes could not be determined. Future work could address this by comparing model

variants with and without visual refinement under identical loop-calling pipelines to assess whether

improved image quality alone enhances biological discovery.

Conclusion

In conclusion, we systematically benchmarked five deep learning models for Hi-C chromatin

contact prediction across four cell lines, evaluating their predictive accuracy, visual fidelity, and ability

to support downstream loop detection. Ablation analysis revealed that epigenomic features,

particularly CTCF binding and co-accessibility, are key contributors to accurate Hi-C prediction, while

many additional modalities provide limited benefit. Among all models, Epiphany performed

consistently well across all criteria, demonstrating high accuracy, generalizability, visual quality, and

effective loop detection. Furthermore, our results highlight that predicted Hi-C maps can effectively

support loop detection.

Methods

Data and cell line selection

This study used publicly available datasets from four well-characterized human cell lines: K562,

IMR-90, GM12878, and H1-hESC, which were chosen for their extensive publicly available multi-omics

data and obtained from the ENCODE and 4DN databases (Supplementary Table S1). IMR-90, GM12878,

and H1-hESC were included in the training data of at least one evaluated model, whereas K562 was

not. This allowed assessment of model performance on both seen and unseen cell types, providing

insight into their generalization ability. Furthermore, the study only used 22 chromosomes for each

cell line, excluding sex chromosomes.

The input data used for Hi-C contact map prediction included genomic DNA sequence and

various epigenomic data. All genomic sequences were aligned to the hg38 human reference genome.

Epigenomic data comprised chromatin accessibility (ATAC or DNase), CTCF binding, and histone

modifications such as H3K4me3, H3K27ac, H3K4me1, and H3K27me3 (all by ChIP-seq).

Deep learning models for comparison

This study used five advanced deep learning models for the prediction of Hi-C contact maps:

C.Origami, Epiphany, HiCDiffusion, ChromaFold, and GRACHIP. These models collectively represent a

broad range of contemporary deep learning approaches, including CNNs, transformers, recurrent

neural networks (RNNs), graph convolutional networks (GCNs), as well as generative techniques such

as GANs and diffusion-based models (Supplementary Table S3).

All models were executed using the authors' publicly available implementations. The software

was installed in a Python (3.11) environment with PyTorch as the primary deep learning framework,

along with the dependencies specified in each repository. Training was performed on the Ghent

University high-performance computing (UGent HPC) cluster using GPU acceleration (NVIDIA GPUs),

while inference and downstream analyses were carried out on CPU nodes. Model parameters and

preprocessing steps followed the recommendations of the original publications unless otherwise

stated.

C.Origami [21] predicts Hi-C contact maps by integrating genomic and epigenomic information

(hg38), using three inputs: DNA sequence, CTCF binding, and ATAC-seq chromatin accessibility. The

genomic sequence was provided in FASTA format and one-hot encoded into five channels (A, T, C, G,

and N), which remained constant across all cell types. The ATAC-seq and CTCF data were pre-processed

with the Seq-N-Slide pipeline (https://igordot.github.io/sns/) to align raw FASTQ reads, remove low-

quality sequences, and produce normalized bigWig signal tracks. These signals were log-transformed

to reduce noise and ensure numerical stability before being used as input. The Hi-C training data were

processed at 10 kb resolution and downsampled to 8,192 bp to match the model's output format, with

a reversible natural logarithm transformation applied to stabilize training. The model architecture

consisted of two main components: feature extraction and contact map prediction. The feature

extraction stage included two one-dimensional convolutional encoders that captured local genomic

patterns, followed by a transformer module that modelled long-range dependencies. The transformer,

adapted from the BERT architecture, contained eight attention layers with 256 hidden units and eight

attention heads, using relative positional embeddings to encode genomic distance. Each input covered

a 2.1 Mb genomic region divided into 256 bins and contained seven channels: five from DNA sequence

and two from ATAC-seq and CTCF signals. After feature extraction, the transformer output was pairwise

concatenated to generate a 256 × 256 × 256 tensor, which was then decoded through five dilated

residual blocks to produce a 256 × 256 contact matrix representing predicted chromatin interaction

intensities at 8,192 bp resolution. The model was trained using MSE loss on the IMR-90 cell line, with

all chromosomes except 10 and 15 used for training; Chromosome 10 served as validation and

Chromosome 15 as the test set.

Epiphany [18] predicted Hi-C contact maps from epigenomic data representing 3D genome

organization, using DNase I hypersensitivity, CTCF binding, and three histone marks (H3K4me3,

H3K27ac, and H3K27me3). All input data were processed as described in the original method paper

through a unified pipeline in which replicate BAM files for each modality were merged and converted

into bigWig signal tracks using the bamCoverage tool with a 10 bp bin size and RPGC normalization to

ensure consistent signal intensity across samples. The Hi-C training data were processed at 10 kb

resolution and normalized using Hi-C-DC+, which applied a negative binomial regression model to

compute observed-over-expected interaction ratios while accounting for genomic distance, GC

content, and restriction fragment size. These normalized interaction values served as the model's

training targets. Epiphany employed a sliding window approach in which each 1 Mb stripe of the

contact matrix was predicted using a 1.4 Mb window of input signals, including 200 kb of padding on

both sides. During training, the model predicted 200 consecutive stripes per forward pass,

corresponding to an input tensor of size 5 channels × 3.4 Mb × 200 stripes, with a 10 kb stride between

windows. The model architecture was based on a GAN consisting of a generator and discriminator. The

generator contained multiple convolutional layers for local feature extraction followed by a

bidirectional LSTM layer to capture long-range dependencies across stripes, producing realistic contact

map predictions through a final fully connected layer. The discriminator, composed of convolutional

layers, enforced an adversarial objective to distinguish real from generated maps. The combination of

MSE and GAN losses enhanced prediction accuracy and structural realism. Epiphany was trained on

the GM12878 cell line, with chromosomes 3, 11, and 17 held out for validation and testing to assess

generalization.

HiCDiffusion [17], unlike multimodal models that integrated epigenomic data, relied solely on

sequence features derived from the hg38 human reference genome, excluding telomeric and

centromeric regions to avoid repetitive and noisy sequences. The model took a 2,097,152 base-pair (2

Mb) genomic window as input, one-hot encoded into five channels representing A, T, C, G, and N bases.

Each input corresponded to a predicted Hi-C contact matrix of 256 × 256 bins at 8,192 bp resolution.

The architecture followed a two-stage transfer learning framework composed of a pretrained encoder-

decoder backbone and a diffusion-based refinement process. The encoder compressed the 2 Mb

sequence into 256 bins with 256 feature channels using convolutional layers, residual connections,

batch normalization, and ReLU activations, followed by a transformer module with eight attention

heads to capture long-range dependencies. The decoder employed dilated convolutions to reconstruct

an initial 256 × 256 single-channel contact map, which served as the base prediction. This pretrained

encoder–decoder was then integrated into a diffusion refinement stage, where a U-Net denoising

network iteratively learned to remove Gaussian noise added to the predicted maps. During training,

the model minimized reconstruction error by progressively denoising corrupted contact maps, and

during inference, it started from random noise and refined it through learned iterative denoising steps

guided by the encoder–decoder features. This approach enabled the generation of visually realistic

and structurally coherent contact maps. HiCDiffusion was trained on the GM12878 cell line and used

all autosomal chromosomes except Chromosome 22 for testing and Chromosome 21 for validation.

ChromaFold [19] used single-cell chromatin accessibility data with CTCF motif scores to predict

HiC contact map data. The model leveraged two major features derived from scATAC-seq data:

pseudobulk chromatin accessibility and co-accessibility profiles. Pseudobulk accessibility was

generated by aggregating single-cell accessibility signals across a population of cells to provide a robust

representation of overall chromatin openness. To address the sparsity of scATAC-seq data, metacells,

clusters of similar cells, were constructed, and co-accessibility between genomic regions was

quantified using the Jaccard similarity of binarized accessibility profiles across metacells, enabling the

model to capture interaction patterns at a population level. The CTCF motif score track was computed

by scanning genomic DNA sequences with CTCF position weight matrices to identify potential binding

sites that contribute to chromatin looping and domain organization. The Hi-C training data were

processed at 10 kb resolution and normalized into Z-scores using HiC-DC+, with values clipped between

−16 and +16 to reduce the influence of outliers. ChromaFold's architecture consisted of two parallel

feature extractors: the first processed pseudobulk accessibility and CTCF motif score tracks through 15

convolutional layers to capture local context, while the second extracted interaction-specific features

from co-accessibility data. Outputs from both extractors were concatenated and passed through a

linear prediction layer that estimated contact strengths between a central genomic bin and its

surrounding bins within a 2 Mb window, forming a V-shaped stripe prediction. The model was trained

in two stages for improved convergence: first optimizing the primary extractor and temporary

prediction head, then freezing the learned weights while training the co-accessibility branch and final

layer. ChromaFold used 4.01 Mb input windows and was trained on IMR-90 and GM12878 cell lines,

with chromosomes 3 and 15 reserved for validation and chromosomes 5, 18, 20, and 21 held out for

testing.

GRACHIP [20], a graph-based deep learning model for predicting Hi-C contact maps, integrated

7 input modalities: genomic DNA sequences, ATAC-seq data, and five CUT&RUN-derived epigenomic

features: CTCF, H3K4me3, H3K4me1, H3K27ac, and H3K27me3, based on the hg38 human reference

genome. CUT&RUN data were processed through the 4DN pipeline, while ATAC-seq data followed the

ENCODE ATAC-seq pipeline. Both pipelines generated normalized bigWig signal tracks as final outputs.

For CUT&RUN, raw reads underwent quality control, adapter trimming, alignment with Bowtie2, and

filtering to retain only high-quality, unique reads before producing bigWig tracks. Similarly, ATAC-seq

reads were aligned, duplicates and mitochondrial reads were removed, and chromatin accessibility

signals were output in bigWig format. DNA sequence data were processed using a pretrained DNABert

model, which transformed nucleotide sequences into 768-dimensional embeddings that captured rich

contextual information. Hi-C training data were processed with the 4DN Hi-C pipeline at 10 kb

resolution, including alignment with BWA, filtering with pair tools, duplicate removal, and

normalization of final contact matrices after merging biological replicates. GRACHIP's architecture

combined three modules to model multi-scale genomic dependencies: a three-layer GCN to encode

genomic features and structural relationships, a 12-layer Transformer with 12 attention heads to

capture long-range dependencies, and a six-layer CNN to extract local interaction patterns. The model

produced a 200 × 200 contact matrix representing predicted chromatin interactions within a 2 Mb

genomic window at 10 kb resolution. By integrating graph-based representations with sequence and

epigenomic features, GRACHIP effectively modelled both linear and spatial genomic contexts. The

model was trained on the H1 human embryonic stem cell line, using all chromosomes for training

except chromosomes 10 and 15, which were reserved for evaluation.

Most models were unable to predict interactions across the entire length of a chromosome

due to memory and computational constraints. Instead, predictions were made on fixed-size windows,

commonly 2 Mb in length. Supplementary Table S2, S3, S4 summarize key information for each model,

including the input modalities, resolution, cell lines used for training, the specific deep learning

techniques employed in each architecture, and the source code of each model.

Overview of workflow

The workflow began with data collection and preprocessing. Each evaluated model required

specific input modalities and preprocessing procedures. To ensure fair and reproducible evaluation, all

models were retrained using the original preprocessing steps, input modalities, and training settings

described in their original publications. The same cell line and chromosome splits were also maintained

for training, ensuring that the retrained models produced results consistent with those originally

reported. Following preprocessing, the prepared data were input into each model to generate

predicted Hi-C contact maps across five human cell lines. During inference, the same preprocessing

protocols were applied to maintain methodological consistency. The predicted contact maps were then

compared with experimental Hi-C data from the corresponding cell lines. To assess prediction accuracy,

the predicted contact maps were quantitatively compared against the ground truth Hi-C maps of the

same cell lines. For image quality assessment, the FID was used to evaluate the visual similarity

between predicted and true contact maps. Finally, to evaluate the utility of the predicted maps in

downstream tasks, both predicted and ground truth contact matrices were input into loop-calling

tools. The resulting loops were compared to evaluate how well each model recovered biologically

relevant chromatin interactions. While some original model studies examined structural features such

as loops or TADs, they typically relied on a single analysis strategy and did not systematically compare

performance across multiple loop-calling algorithms. Here, we extended these approaches by applying

several loop callers and directly comparing loop recovery, providing a more standardized assessment

of downstream biological utility.

Evaluation criteria for model comparison

a. Accuracy performance

Model performance was evaluated by comparing predicted Hi-C matrices with experimentally

derived contact maps using three quantitative measures: MSE, insulation score correlation, and O/E

Pearson correlation. MSE quantifies the average squared difference between predicted and ground-

truth contact frequencies. Insulation score correlation evaluates whether the model captures local

chromatin domain organization (e.g., TAD boundaries) by computing insulation scores along the

genome from both predicted and experimental matrices and comparing the resulting insulation

profiles using Pearson correlation. Specifically, for each genomic bin, insulation scores are computed

within a fixed window (≈500 kb) by summarizing average contacts in upstream, downstream, and

central regions, and calculating the ratio $\frac{\max(upstream, downstream) + pseudocount}{central + pseudocount}$. Finally, O/E Pearson

correlation measures global agreement after normalizing contact frequencies to account for distance-

dependent decay, by flattening the observed/expected-normalized matrices and computing Pearson

correlation. Before analysis, all matrices were log-transformed using $log_{10}(count + 1)$ to normalize

data distributions. Comparisons were conducted separately for each chromosome and cell line to

assess model robustness across biological contexts. Results were also compared between training and

unseen cell lines to evaluate generalization. All performance metrics were summarized under identical

conditions to enable direct model comparison.

b. Ablation testing

To assess the contribution of each input modality, we performed ablation testing by removing selected features and measuring the resulting change in performance. Unlike Epiphany, which retrained models after masking input tracks, we conducted post-training ablation: model parameters were fixed and removed inputs were replaced with neutral signals. This approach evaluates the model's dependence on each modality during inference rather than its ability to relearn without it, and also avoids the substantial computational cost and inconsistent training procedures across models. For sequence inputs, nucleotides were replaced with the ambiguous base "N." For epigenomic features (e.g., ATAC-seq or histone marks), signal values were set to zero while preserving genomic coordinates. Models with few input types (C.Origami and ChromaFold) were tested under all modality combinations, whereas models with more inputs were evaluated using single and grouped ablations. Modalities were grouped by biological function: (1) chromatin accessibility (ATAC-seq, DNase I), (2) transcription factor binding (CTCF), (3) activating histone marks (H3K4me3, H3K27ac, H3K4me1), and (4) repressive histone marks (H3K27me3). HiCDiffusion was excluded because it relies only on DNA sequence. Ablation analyses were performed on chromosomes 5, 6, 10, and 15 as representative genomic regions.

c. Image quality

Quantitative metrics alone cannot fully assess the perceptual realism of predicted Hi-C maps. Therefore, FID was used to evaluate the visual quality of predicted Hi-C contact maps. FID is a standard metric for assessing generative models, including GANs and diffusion models, by comparing the distribution of generated images to that of real images in the feature space of a pretrained InceptionV3 network. Specifically, it fits multivariate Gaussian distributions to the extracted feature activations and computes the Fréchet distance between them based on their mean and covariance. Lower FID values indicate greater visual similarity to the experimental Hi-C maps.

d. Downstream loop detection analysis

To evaluate the biological utility of predicted Hi-C maps, downstream analysis focused on

identifying chromatin loops associated with transcriptional regulation. Four loop-calling tools were

used: LASCA [23], HiCCUPS [24], SIP [25], and Mustache [26]. These four loop callers were selected for

several reasons. First, they are well-established and user-friendly tools that can be efficiently executed

in high-performance computing (HPC) environments. Second, they represent two major categories of

loop detection algorithms with two tools selected from each category. Within each group, the selected

tools are known to perform optimally at different resolutions, allowing us to evaluate loop detection

performance across algorithmic strategies and resolution sensitivities. Among these, LASCA and

HiCCUPS were clustering-based methods, while SIP and Mustache applied computer vision techniques.

Clustering-based tools used algorithms such as DBSCAN to detect loops by grouping nearby points

based on spatial proximity and cluster size, with HiCCUPS identifying sharp focal peaks using a donut-

shaped local background, and LASCA employing graph-based community detection to handle complex

and sparse data. In contrast, computer vision methods analysed the Hi-C contact maps as images:

Mustache detects loops using scale-space theory to identify peaks at multiple scales, and SIP integrates

advanced image processing to identify loops and domains by recognizing spatial patterns. The reason

for choosing these four tools was to evaluate how predicted Hi-C maps perform in loop detection using

two different types of algorithms: clustering-based and computer vision-based methods. Within each

category, we selected two tools to capture variation in loop detection sensitivity at different

resolutions. HiCCUPS and Mustache were known to predict more loops at 10 kb resolution, while

LASCA and SIP tended to detect more loops at higher resolutions like 5 kb [32]. Since the predicted Hi-

C maps in this study have a 10 kb resolution, comparing these tools allows assessment of loop

detection performance across different algorithms and resolution sensitivities.

For this analysis, loop calling is performed on the predicted and true Hi-C maps (converted into

the required ".hic" format using juicer tool with KR normalization). The K562 cell line was chosen, as it

was not included in model training, providing an unbiased test of generalization.

After loop calling, detected loops were annotated with enhancer and promoter regions.

Enhancers were obtained from EnhancerAtlas 2.0 [38], and promoters were defined as ±2 kb around

transcription start sites using GENCODE (GRCh38) annotations. To assess biological relevance,

predicted loops were compared with three reference resources: CollecTRI [27], a curated database of

transcriptional regulatory interactions; ChIP-Atlas [29], which provides transcription factor binding

profiles; and KnockTF 2.0 [28], which contains gene expression data following transcription factor

knockdown or knockout. For the KnockTF dataset, differential expression analysis between TF

knockdown and control samples was performed using the *limma* package, executed in Python via the

rpy2 interface. Only statistically significant TF–target gene pairs (FDR < 0.05) were retained, and these

pairs were mapped onto predicted chromatin loops to identify regulatory interactions supported by

experimental evidence.

Finally, several comparisons were made:

(1) Total number of predicted loops compared to the ground truth loops from the reference Hi-C map.

(2) Overlap between enhancer-associated loops predicted by each model and true Hi-C loops.

(3) Overlap between predicted loops and curated TF–target regulatory interactions (CollecTRI).

(4) Overlap between predicted loops and transcription factor binding evidence (ChIP-Atlas).

(5) Overlap between predicted loops and expression-supported TF–target relationships derived from

KnockTF 2.0.

Results from all loop-calling tools were then compared to evaluate the performance of

predicted Hi-C maps across different loop detection methods. This framework assesses whether

predicted chromatin contacts are not only structurally plausible but also supported by independent

regulatory and gene expression evidence.

Declarations

Ethics Approval and Consent to Participate - N/A

Consent of Publication - N/A

Funding - N/A

Availability of Data and Materials

All datasets used in this study are publicly available. Hi-C datasets were obtained from the 4DN Data Portal [39]. Details of all Hi-C and other omics datasets used in this study are provided in Supplementary Table S1. The code used in this manuscript is available at https://github.com/CBIGR/bulk_hic_benchmark.

Author Contributions

Contributions according to the CRediT system (https://www.ucl.ac.uk/library/research-support/open-access/credit-taxonomy), HTTN = Hoang Thien Thu Nguyen, VV = Vanessa Vermeirssen): Conceptualization: VV, Data curation: HTTN, Formal analysis: HTTN, Funding acquisition: VV, Investigation: HTTN, VV, Methodology: HTTN, VV, Project administration: VV, Software: HTTN, Supervision: VV, Validation: HTTN, Visualization: HTTN, Writing-original draft: HTTN, VV, Writing-review and editing HTTN, VV. All authors read and approved the final manuscript.

Acknowledgements

1016   This work was facilitated through the high-performance computing (HPC) infrastructure provided by

1017   Ghent University. We thank Jens Uwe Loers for his guidance on HPC computing. We also thank the

1018   CBIGR team members for their valuable feedback and suggestions that helped improve the study.

1019

1020   **Additional File**

1021   Supplementary document includes additional figures and tables detailing data sources, analysis

1022   results, and extended visualizations.

1023

References

[1] Y. F. Li and R. B. Altman, "Systematic target function annotation of human transcription factors," *BMC Biol*, vol. 16, no. 1, p. 4, Dec. 2018, doi: 10.1186/s12915-017-0469-0.

[2] H. Ray-Jones and M. Spivakov, "Transcriptional enhancers and their communication with gene promoters," *Cell. Mol. Life Sci.*, vol. 78, no. 19–20, pp. 6453–6485, Oct. 2021, doi: 10.1007/s00018-021-03903-w.

[3] H. Tao *et al.*, "Computational methods for the prediction of chromatin interaction and organization using sequence and epigenomic profiles," *Briefings in Bioinformatics*, p. bbaa405, Jan. 2021, doi: 10.1093/bib/bbaa405.

[4] L. Yao, B. P. Berman, and P. J. Farnham, "Demystifying the secret mission of enhancers: linking distal regulatory elements to target genes," *Crit Rev Biochem Mol Biol*, vol. 50, no. 6, pp. 550–573, Nov. 2015, doi: 10.3109/10409238.2015.1087961.

[5] K. Zhang *et al.*, "A single-cell atlas of chromatin accessibility in the human genome," *Cell*, vol. 184, no. 24, pp. 5985-6001.e19, Nov. 2021, doi: 10.1016/j.cell.2021.10.024.

[6] L. A. Lettice *et al.*, "A long-range Shh enhancer regulates expression in the developing limb and fin and is associated with preaxial polydactyly," *Hum Mol Genet*, vol. 12, no. 14, pp. 1725–1735, Jul. 2003, doi: 10.1093/hmg/ddg180.

[7] S. Smemo *et al.*, "Obesity-associated variants within FTO form long-range functional connections with IRX3," *Nature*, vol. 507, no. 7492, pp. 371–375, Mar. 2014, doi: 10.1038/nature13138.

[8] E. Lieberman-Aiden *et al.*, "Comprehensive Mapping of Long-Range Interactions Reveals Folding Principles of the Human Genome," *Science*, vol. 326, no. 5950, pp. 289–293, Oct. 2009, doi: 10.1126/science.1181369.

[9] L. Chang *et al.*, "Droplet Hi-C enables scalable, single-cell profiling of chromatin architecture in heterogeneous tissues," *Nat Biotechnol*, Oct. 2024, doi: 10.1038/s41587-024-02447-1.

[10] B. R. Lajoie, J. Dekker, and N. Kaplan, "The Hitchhiker's guide to Hi-C analysis: Practical guidelines," *Methods*, vol. 72, pp. 65–75, Jan. 2015, doi: 10.1016/j.ymeth.2014.10.031.

[11] A. Sasse, M. Chikina, and S. Mostafavi, "Unlocking gene regulation with sequence-to-function models," *Nat Methods*, vol. 21, no. 8, pp. 1374–1377, Aug. 2024, doi: 10.1038/s41592-024-02331-5.

[12] K. E. Wu, K. E. Yost, H. Y. Chang, and J. Zou, "BABEL enables cross-modality translation between multiomic profiles at single-cell resolution," *Proc Natl Acad Sci U S A*, vol. 118, no. 15, p. e2023070118, Apr. 2021, doi: 10.1073/pnas.2023070118.

[13] T. Ashuach, M. I. Gabitto, R. V. Koodli, G.-A. Saldi, M. I. Jordan, and N. Yosef, "MultiVI: deep generative model for the integration of multimodal data," *Nat Methods*, vol. 20, no. 8, pp. 1222–1231, Aug. 2023, doi: 10.1038/s41592-023-01909-9.

[14] L. Alzubaidi *et al.*, "Review of deep learning: concepts, CNN architectures, challenges, applications, future directions," *J Big Data*, vol. 8, no. 1, p. 53, Mar. 2021, doi: 10.1186/s40537-021-00444-8.

[15] A. Vaswani *et al.*, "Attention is All you Need".

[16] K. Sokolova, K. M. Chen, Y. Hao, J. Zhou, and O. G. Troyanskaya, "Deep Learning Sequence Models for Transcriptional Regulation," *Annual Review of Genomics and Human Genetics*, vol. 25, no. 1, pp. 105–122, Aug. 2024, doi: 10.1146/annurev-genom-021623-024727.

[17] M. Chiliński and D. Plewczynski, "HiCDiffusion - diffusion-enhanced, transformer-based prediction of chromatin interactions from DNA sequences," *BMC Genomics*, vol. 25, no. 1, p. 964, Oct. 2024, doi: 10.1186/s12864-024-10885-z.

[18] R. Yang *et al.*, "Epiphany: predicting Hi-C contact maps from 1D epigenomic signals," *Genome Biol*, vol. 24, no. 1, p. 134, Jun. 2023, doi: 10.1186/s13059-023-02934-9.

[19] V. R. Gao *et al.*, "ChromaFold predicts the 3D contact map from single-cell chromatin accessibility".

[20] R. Wang, W. Ma, A. S. Mohammadi, S. Shahsavari, S. Vosoughi, and X. Wang, "Improving Cell-
type-specific 3D Genome Architectures Prediction Leveraging Graph Neural Networks," May 21,
2024. doi: 10.1101/2024.05.21.595047.
[21] J. Tan *et al.*, "Cell-type-specific prediction of 3D chromatin organization enables high-
throughput in silico genetic screening," *Nat Biotechnol*, vol. 41, no. 8, pp. 1140–1150, Aug.
2023, doi: 10.1038/s41587-022-01612-8.
[22] G. Fudenberg, D. R. Kelley, and K. S. Pollard, "Predicting 3D genome folding from DNA sequence
with Akita," *Nat Methods*, vol. 17, no. 11, pp. 1111–1117, Nov. 2020, doi: 10.1038/s41592-020-
0958-x.
[23] A. V. Luzhin *et al.*, "LASCA: loop and significant contact annotation pipeline," *Sci Rep*, vol. 11,
no. 1, p. 6361, Mar. 2021, doi: 10.1038/s41598-021-85970-4.
[24] S. S. P. Rao *et al.*, "A 3D Map of the Human Genome at Kilobase Resolution Reveals Principles of
Chromatin Looping," *Cell*, vol. 159, no. 7, pp. 1665–1680, Dec. 2014, doi:
10.1016/j.cell.2014.11.021.
[25] M. J. Rowley *et al.*, "Analysis of Hi-C data using SIP effectively identifies loops in organisms from
C. elegans to mammals," *Genome Res.*, vol. 30, no. 3, pp. 447–458, Mar. 2020, doi:
10.1101/gr.257832.119.
[26] A. Roayaei Ardakany, H. T. Gezer, S. Lonardi, and F. Ay, "Mustache: multi-scale detection of
chromatin loops from Hi-C and Micro-C maps using scale-space representation," *Genome Biol*,
vol. 21, no. 1, p. 256, Dec. 2020, doi: 10.1186/s13059-020-02167-0.
[27] S. Müller-Dott *et al.*, "Expanding the coverage of regulons from high-confidence prior
knowledge for accurate estimation of transcription factor activities," *Nucleic Acids Research*,
vol. 51, no. 20, pp. 10934–10949, Nov. 2023, doi: 10.1093/nar/gkad841.
[28] C. Feng *et al.*, "KnockTF 2.0: a comprehensive gene expression profile database with
knockdown/knockout of transcription (co-)factors in multiple species," *Nucleic Acids Research*,
vol. 52, no. D1, pp. D183–D193, Jan. 2024, doi: 10.1093/nar/gkad1016.
[29] Z. Zou, T. Ohta, and S. Oki, "ChIP-Atlas 3.0: a data-mining suite to explore chromosome
architecture together with large-scale regulome data," *Nucleic Acids Research*, vol. 52, no. W1,
pp. W45–W53, Jul. 2024, doi: 10.1093/nar/gkae358.
[30] C. Hou, R. Dale, and A. Dean, "Cell type specificity of chromatin organization mediated by CTCF
and cohesin," *Proc Natl Acad Sci U S A*, vol. 107, no. 8, pp. 3651–3656, Feb. 2010, doi:
10.1073/pnas.0912087107.
[31] Y. Liu and J. Dekker, "CTCF-CTCF loops and intra-TAD interactions show differential dependence
on cohesin ring integrity," *Nat Cell Biol*, vol. 24, no. 10, pp. 1516–1527, Oct. 2022, doi:
10.1038/s41556-022-00992-y.
[32] H. M. A. M. Chowdhury, T. Boult, and O. Oluwadare, "Comparative study on chromatin loop
callers using Hi-C data reveals their effectiveness," *BMC Bioinformatics*, vol. 25, no. 1, p. 123,
Mar. 2024, doi: 10.1186/s12859-024-05713-w.
[33] A. Del Moral-Morales, M. Salgado-Albarrán, Y. Sánchez-Pérez, N. K. Wenke, J. Baumbach, and E.
Soto-Reyes, "CTCF and Its Multi-Partner Network for Chromatin Regulation," *Cells*, vol. 12, no.
10, p. 1357, May 2023, doi: 10.3390/cells12101357.
[34] T. Yang *et al.*, "HiCRep: assessing the reproducibility of Hi-C data using a stratum-adjusted
correlation coefficient," *Genome Res.*, vol. 27, no. 11, pp. 1939–1949, Nov. 2017, doi:
10.1101/gr.220640.117.
[35] S. Rajderkar *et al.*, "Topologically associating domain boundaries are required for normal
genome function," *Commun Biol*, vol. 6, no. 1, p. 435, Apr. 2023, doi: 10.1038/s42003-023-
04819-w.
[36] W. Makałowski, "The human genome structure and organization.," *Acta Biochim Pol*, vol. 48,
no. 3, pp. 587–598, Sep. 2001, doi: 10.18388/abp.2001_3893.

[37]   S. Wang *et al.*, "HiNT: a computational method for detecting copy number variations and
translocations from Hi-C data," *Genome Biol*, vol. 21, no. 1, p. 73, Dec. 2020, doi:
10.1186/s13059-020-01986-5.
[38]   T. Gao and J. Qian, "EnhancerAtlas 2.0: an updated resource with enhancer annotation in 586
tissue/cell types across nine species," *Nucleic Acids Research*, p. gkz980, Nov. 2019, doi:
10.1093/nar/gkz980.
[39]   S. B. Reiff *et al.*, "The 4D Nucleome Data Portal as a resource for searching and visualizing
curated nucleomics data," *Nat Commun*, vol. 13, no. 1, p. 2365, May 2022, doi:
10.1038/s41467-022-29697-4.
1132