Wing pitch timing and wing elevation modulate forces and body pitch in forward flapping flight

Authors: Victor Colognesi[†] and L. Christoffer Johansson[†]

Author affiliations: [†] Biology department, Lund University, 223 62 Lund, Sweden

ORCID: V.C. 0000-0003-4109-8174, L.C.J. 0000-0002-1851-3635

Author Contributions: V.C. and L.C.J. conceived and planned the study and conducted the experiments. V.C. performed the PIV and data analysis and drew the associated figures. L.C.J. conducted the statistical analyses and drafted the manuscript. Both authors participated in finalizing the text and figures.

Contact information: V. C. victor.colognesi@biol.lu.se, LCJ Christoffer.Johansson@biol.lu.se

Competing Interest Statement: The authors have no competing interests.

Scientific fields: Biological Sciences/Evolution, Biomechanics, Physical Sciences/Physics, Aerodynamics

Keywords: Animal flight, aerodynamics, flight efficiency, robotic flapping wing, pitch control, kinematics, drones, tailless flight control

Abstract

Aerodynamic performance in flying animals can be controlled not only by changes in wing shape and size, but also by changes in wing motion. In flapping wings, the two wings interact aerodynamically, where the interaction depends on wingbeat phase, wing proximity, and wing attitude. Although, observations of free-flying animals show wings are relatively close during forward flight, how these interactions influence force production remain unclear. Here we used a robotic flapping wing and quantitative flow measurements to test the effect of wing interactions while varying mean wing elevation and pitch timing during upstroke–downstroke transitions. We show that both force magnitude and direction depend strongly on these parameters and their interaction. The fitted response models showed that high wing position combined with early pitching maximized vertical force, whereas low-to-mid wing position with synchronized-to-late pitching increased thrust. Efficiency metrics were highest near mid-to-high wing position combined with late pitching. In addition, we found that transition phases strongly affected thrust generation and produced substantial body pitch torques. These findings demonstrate that small kinematic adjustments can markedly alter aerodynamic performance and be used for tailless flight control. This offers mechanistic explanations for observed animal wing motions and novel strategies for controlling flapping drones.

Introduction

Animals in flapping flight regulate both the magnitude and direction of aerodynamic forces through passive wing deformations and active muscular control. Birds, bats, and insects continually adjust wing trajectory, attitude, and velocity to maintain stability (1), modulate speed (2–8), and execute maneuvers (9–12). Variations in kinematics can disproportionately influence both the magnitude and orientation of aerodynamic forces (13,14), thereby shaping flight performance across speeds, accelerations, and environmental conditions. This flexibility arises from the biological flight apparatus, which allows for virtually infinite kinematic variation. Understanding how specific wing-motion parameters affect force generation is therefore critical both for explaining the diversity of natural flight behaviors and for guiding the design of the next generation flapping-wing robots (15).

Despite major advances in animal-flight research (16–20), the aerodynamic consequences of most kinematic variation remain unresolved. The link between kinematics and aerodynamics is relatively well understood for hovering flight (14,21–24), while prior work on forward-flight remains more limited. Work on forward flapping flight has primarily examined parameters such as Strouhal number (flapping velocity relative to forward speed) (25) and wing pitch amplitude (26), or simplified flapping to heaving wings (27,28), which is insufficient to capture the 3D flow phenomena of flapping wings (29). However, studies of hovering flight dynamics and theoretical reasoning suggest additional strategies to control aerodynamics, which may apply to forward flight but remain largely unexplored. Indeed, recent experiments showed that mean wing elevation, a previously untested parameter, can modulate both force magnitude and orientation by altering wing-wing interactions during the downstroke (30). Another particularly potent parameter to control forces is pitch timing, which influences the angle of attack and wing-wake interactions in hovering-flight studies (14,31,32). In forward-flying animals, pitch timing and mean wing elevation have rarely been explicitly studied (but see (33) for a 2D study), although available evidence suggest that the parameters vary with flight speed in flying animals (4,8,34–39). However, the mechanistic links between these kinematic parameters and the resulting aerodynamic forces are difficult to isolate in vivo. A systematic parametric analysis is therefore needed to disentangle how variation in wing kinematic parameters, individually and in combination, affects lift, thrust, force orientation, efficiency, and pitch-control in forward flapping flight.

Here, we address this knowledge gap by experimentally quantifying how wing pitch timing and mean wing elevation interact to shape aerodynamic performance using a robotic flapping wing. Using a wind tunnel setup with particle image velocimetry (PIV) to measure airflow, we independently manipulate wing pitch timing and mean wing elevation and quantify the resulting lift, thrust, force orientation, and energetic costs. This approach isolates how these parameters alter aerodynamic output, offering a mechanistic framework for interpreting kinematic variability in flying animals. By revealing how targeted timing and positional adjustments regulate aerodynamic forces, our findings offer new insights into natural flight control and inform strategies for achieving robust, responsive, and energy efficient control in flapping drones.

Material and methods

Experimental setup

We used a robot (previously described in (30,40)), fitted with a novel 3D-printed wing (wing length = 150 mm, mean chord = 39 mm, maximum thickness = 6 mm, see Fig. S1). The robot is capable of independently controlling the angular elevation of the wing above (max 90 degrees) and angular depression of the wing below (max 90 degrees) the horizontal plane through the flapping axis, the wingbeat frequency (f, in the range 0-15 Hz) and the pitch angle (γ, varying ±40 degrees). These factors can be controlled as continuous functions over time and essentially take any shape allowed by motor acceleration. Here we controlled the mean wing elevation (*MWE*) and the pitch angle (γ). *MWE* was defined as the average of the maximum elevation and depression angles of the wing relative to the horizontal plane. Positive values represent wingbeats centered above the horizontal, negative below. Pitch angle was defined as the angular rotation of the wing around the spanwise axis. The robot was mounted on the wall of the wind tunnel and was controlled using a custom software via a microcontroller (30,40).

For the experiments we used fixed tunnel speed (7.2 m/s), tip-to-tip angular amplitude of the flapping (A_{ang} = 70 degrees), flapping frequency (6.7 Hz) and downstroke ratio (0.5, equal duration of down and upstroke). For all experiments, the wing flaps at a constant velocity and constant pitch for the downstrokes (-4 degrees), and upstrokes (14 degrees). At the transitions, both the velocity and the pitch follow a sinusoidal trajectory, taking 10% of the total flapping period, ensuring a continuous and smooth transition. The timing of the pitching (*TP*) was then shifted relative to the turning points with a delay of minus half of the transition time (so -5% of the period), 0 and plus half of the transition time (Fig. S2). An 'early' pitch means the wing rotates before reaching the turning point, while a 'late' pitch means rotation occurs after the turning point. We varied the *MWE* (by independently controlling the maximum elevation and depression angle of the wing) between -30 deg (low) and 30 deg (high) in steps of 30 degrees. For each kinematic condition, we made three measurements, where each measurement included four flapping cycles. The wing motion was stopped between each measurement and subsequently started again providing unique starting conditions for the wing for each sequence. We therefore considered the measurements to be statistically independent.

We defined a right-handed coordinate system with *x* in the tunnel flow direction and *z* in the upwards direction. We measured the flow using stereo particle image velocimetry (sPIV) in a plane perpendicular to the freestream flow (*yz*-plane) of the Lund University wind tunnel (41). The sPIV system (Lavision, Göttingen, Germany) includes a dual pulse laser (LDY304PIV laser, Litron Lasers, Rugby, England), operated at f_L=720 Hz, four high speed cameras (Photron Nova R2, Photron Deutschland GmbH, Reutlingen, Germany) and acquisition and analysis software (Davis 10.2.1, Lavision, Göttingen, Germany). The cameras were set up to all view the same area (~340 x 400 mm, *yz*). The analysis settings were; pre-processing with a subtract minimum over time (5 frames), followed by a vector calculation with an initial box size of 96x96 and a final box size of 24x24, with 50% overlap. The final vector field was subjected to a vector validation of strength 2. To remove erroneous vectors and noise we did a final post processing step. This included a 1x universal outlier detection, removing vectors deviating more than 2.5 standard deviation from their neighbors (7x7

115   box) and reinserting the second-best vector if less than 3 standard deviations from their neighbors.
116   This step also included interpolating missing vectors and a 5x5 denoising routine. The resulting
117   vector field was 150x177 vectors with a spacing of 2.27 mm.
118

Analysis

The vector fields were analyzed using custom written software in Matlab R2022a (Mathworks Inc.).
The data were masked to remove erroneous vectors at the edge of the vector field and mirrored in
the sagittal plane of the robot, to generate a wake representing both wings of an animal. Mirroring
the vector field is motivated by the wind tunnel wall acting as an aerodynamic mirror (42–45),
making it possible to study wing-wing interactions using a single wing (44). This procedure ignores
effects of the boundary layer but given that the boundary layer in the current tunnel is thin (46) and
that all measurements are performed at the same speed we consider these effects to be small.
In each PIV sequence, the free-stream velocity U_∞ was estimated by averaging the measured
streamwise velocity in an area unaffected by the wake of the wing. We then stacked the vector
fields in the streamwise direction with a spacing of U_∞/f_L and estimated the vorticity (ω) as the curl
of the flow velocities in the volume.
The vertical force, lift (L), was then calculated according to,
132

133    $$L = \rho U_\infty \iint_{wake\ area} (y - y_0) \cdot \omega_x(y,z)\ dydz \quad (1)$$

135   where ρ is the air density, y is the spanwise position, y_0 the spanwise position of the center of the
136   body and ω_x is the vorticity along the freestream axis.
137   We estimated the thrust (T) in the direction of flight as,
138

$$T = \frac{1}{2}\rho U_\infty \iint_{wake\ area} (y - y_0) \cdot \omega_z(y,z) - (z - z_0) \cdot \omega_y(y,z)\ dydz \quad (2)$$

where ω_z is the vorticity along the vertical axis, ω_y is the vorticity along the spanwise axis, z the
vertical position and z_0 the vertical position of the center of the body (47).
For the comparisons in this paper, we used the time-averaged force over four wingbeats. The
direction of the resultant force was determined as the average thrust to average lift ratio (T/L) and
the ability to generate force was determined by estimating the force coefficients,
146

147    $$C_L = \frac{L}{qS} \quad (3)$$

149    $$C_T = \frac{T}{qS} \quad (4)$$

151   where q is the dynamic pressure ($q = \frac{1}{2}\rho U_\infty^2$) and S is the wing area.
152   We also estimated the useful force (F_{use}) as the magnitude of the vector sum of T and L and
153   normalized according to,
154

$C_{Fuse} = \frac{F_{use}}{qS}$. (5)

We determined the kinetic energy in the wake as a measure of the cost of generating the forces
(48,49), using the following equation:

$E = \frac{1}{2}\rho \int_{Wake\ volume}(2uU_\infty + u^2 + v^2 + w^2) \cdot \left(1 + \frac{u}{U_\infty}\right) dV$ (6),

where u, v, w are the induced velocities in x, y, z, respectively. Contrarily to the vorticity field, which
is compact, the velocity field is not captured in its entirety by the PIV measurements. The first term
in the energy equation is related to the momentum change due to non-zero thrust production by the
wing. While it vanishes for flying objects at force equilibrium this term is necessary to account for
the net forces generated by the wing (50). To improve our estimation of the kinetic energy, we
performed a Helmholtz-Hedge decomposition and extended the velocity field beyond the
dimensions of the wind tunnel (here to a size of 1.2 x 1.2 m cross section) (48,49) prior to estimating
the kinetic energy. The reconstruction is based on a masked vorticity field, with the mask generated
automatically from the data. The masking started with the large vortical structures, then included a
set volume around them. The final mask applied to the 3D vorticity field was an extrusion of a 2D
mask normal to the flow direction obtained by combining all 2D slices of the initial 3D mask. Due to
the flow field being reconstructed from the vorticity based on the stacked 2D-slices of the flow,
velocity at the edges of the volume did not always become zero. We therefore subtracted the mean
streamwise velocity at the edges of the volume before calculating the kinetic energy.
Assuming no pressure work on the Treftz plane, the power was subsequently estimated by dividing
the kinetic energy in the wake by the number of wingbeats (N_{wb}= 4) and multiplying by the wingbeat
frequency (f):

$P = \frac{E}{N_{wb}}f$ (7).

We then normalized power by calculating the power coefficient (C_P) as,

$C_P = \frac{P}{qSU_\infty}$. (8)

Since the force generation differs between the kinematic settings, we estimated performance
parameters to allow for a comparison between the cases. A traditional measure of performance is
the cost of transport (COT), a measure of the relative cost of generating L, defined as the energy
required to transport one unit of weight, one unit of distance. By equating the weight with the lift
generated by the wing COT becomes:

$COT = \frac{P}{LU_\infty}$. (9)

We also determined the power factor (PF)(23,51), which is an efficiency measure of the combined
useful force generated. The power factor originates from the actuator disk model and the fact that

force is proportional to the induced velocity squared, while power is proportional to the induced
velocity cubed. PF was calculated as:
198

$$PF = \frac{C_{Fuse}^{1.5}}{C_P}. \quad (10)$$

Finally, we computed the pitch torque resulting from the wing thrust. The moment arm used for the
torque was computed as follows:

$$h(t) = r_{rc} \cdot \sin(\theta(t)), \quad (11)$$

where θ is the flapping angle. We approximated the application point of the thrust along the wing to
be located at a distance r_{rc} from the rotation point of the wing, defined as

$$r_{rc} = \frac{\int_0^b r^2(b')c(b')db'}{\int_0^b r(b')c(b')db'}, \quad (12)$$

where b is the wingspan and b' is the spanwise position along the wing. This distance was weighed
by the chord, as more force is produced where the wing is wider, and by the radius r from the
rotation point, accounting for an increase of thrust towards the wing tips.
The flapping angle (θ) throughout the wingbeat was determined from the imposed kinematics. To
synchronize the wing trajectory with the forces observed in the wake, we evaluated the relative shift
within one sequence. We first selected a PIV sequence where the tip vortex was easily identifiable
and manually selected the frame where it reached the lowest position. We then determined the
frame where the wing was at the end of the downstroke in footage of the wing taken simultaneously
to the PIV sampling. The delay between the PIV frame and the corresponding end of downstroke in
the wing footage was then applied to every sequence, assuming that the different cases, given the
fixed distance between wing and measurement plane and the constant tunnel speed, did not affect
the time for the wake to travel from the wing to the PIV plane.
The moment was finally computed as

$$M = T(t) \cdot h(t), \quad (13)$$

and made dimensionless with

$$C_M = \frac{M}{qS\bar{c}}, \quad (14)$$

where $\bar{c} = S/b$ is the mean aerodynamic chord of the wing.

Statistics

The experimental design sampled a two-dimensional kinematic parameter space with TP and MWE.
While limited to three levels per variable, this design allowed us to fit quadratic response surfaces
and test how aerodynamic outputs vary across the sampled domain. For this purpose we

performed a GLM analysis (*fitglm* function with 'quadratic' model, Matlab R2025a, Mathworks Inc.,
USA), for each of the dependent variables with *TP* and *MWE* as independent, continuous, variables
set to values between –1 and 1. Variation is given as standard error. Interaction plots of the fitted
quadratic GLM were used to visualize the effect of *TP* across *MWE*.

The GLM results were interpreted as response surfaces over the sampled TP–MWE parameter
space, and we quantified if each output was governed primarily by linear trends, curvature, or
TP*MWE interaction. For this purpose, we performed hierarchical nested-model comparisons (i.e.
incrementally removing one term at a time from the model) and quantified the incremental
explanatory power of each block of terms ($R^2_{partial}$ = (SSE$_{simple}$ - SSE$_{complex}$)/SSE$_{simple}$).

Results

Lift

The wingbeat average C_L varied non-linearly with both *TP* (*TP*: 0.0101±0.0044, p=0.0313; TP^2: -
0.0331±0.0076, p=0.000286) and *MWE* (*MWE*: 0.1466±0.0044, p=33.3 1.14e^{-19}; MWE^2: -
0.0664±0.0076, p=2.02e^{-08}). There was an increase in C_L with increasing *MWE*, regardless of *TP* (Fig.
1a). *TP*, per se, had a significant, but weak, effect on C_L. The response surface for C_L showed a
strong interaction effect between *TP* and *MWE* (*MWE*TP*: -0.1071±0.0054, p=4.25e^{-15}) (Fig. S3a, g).
Increasing *MWE* increased lift across the sampled domain, but the effect of *TP* changed sign with
MWE: at low *MWE*, earlier *TP* reduced C_L, whereas at high *MWE*, earlier *TP* increased C_L. Thus, *TP*
cannot be interpreted independently of *MWE* for C_L (Figs 1a, S5a).

The instantaneous *L* over the wingbeat showed during which phases of the wingbeat we found
differences between the treatments. In both the *TP* and *MWE* changes, most between-condition
differences arise during stroke-reversal phases (Figs 2 and S4). This identifies the turning phases as
the main window in which TP and MWE modulate aerodynamic output. Earlier *TP* and higher *MWE*
both tended to increase C_L during this phase. At the transition between upstroke and downstroke
we also found the curves diverging, but here the effects of the two kinematic variables differed.
Earlier *TP* resulted in more negative lift (reflected in reversed vortex ring during the end of upstroke,
Fig. S5), while higher *MWE* resulted in less negative C_L. We also found another effect of *MWE*, where
C_L during the early and mid-downstroke was lower the higher the *MWE*.

Thrust

The wingbeat average C_T also varied with both *TP* and *MWE*. For C_T, the fitted surface showed strong
main effects of both *TP* and *MWE,* with increasing C_T with decreasing *MWE* (*MWE*: -0.0345±0.0037,
p=6.58e^{-09}), regardless of *TP* (Fig. 1b). There was also a non-linear effect of *TP* on C_T (*TP*:
0.0631±0.0037, p=9.22e^{-14}; TP^2: -0.0439±0.0064, p=9.14e^{-07}), where C_T increased more the earlier
the *TP*. There was no interaction effect between the two factors (p=0.11) (Fig. S5b), indicating that
these two kinematic variables contribute additively rather than interactively to thrust production
(Fig. 1b).

The instantaneous C_T over the wingbeat showed that later TP reduced negative C_T during the
transition between downstroke and upstroke, but also lower C_T during the upstroke and downstroke
transition (Figs 2 and S4). Lower MWE resulted in higher C_T during the downstroke to upstroke
transition.

Thrust to lift ratio

The force-orientation metric T/L decreased with increasing MWE and increased with later TP, with a
significant $TP*MWE$ interaction reflecting a combination of the trends described above (Fig. 1c).
There was a non-linear decrease in T/L with increasing MWE (MWE: -0.1342±0.0121, p=3.31e^{-10};
MWE^2: 0.0638±0.0210, p=0.0063), regardless of TP. There was also a non-linear increase of T/L with
TP (TP: 0.0915±0.0121, p=2.14e^{-7}; TP^2: -0.0789±0.0210, p=0.0012), and a significant interaction
effect between the two factors ($MWE*TP$: 0.0496±0.0149, p=0.0032) (Fig. S5c, i). The resulting
surface indicates a controllability tradeoff: shifting toward high MWE and early TP rotates the
resultant force upward, whereas shifting toward low MWE and synchronized/later TP rotates it
forward.

Power

292   C_P varied linearly with TP (TP: -0.0459±0.0019, p=1.15e^{-16}) and non-linearly with MWE (MWE:
293   0.0117±0.0019, p=5.12e^{-06}; MWE^2: -0.0105±0.0034, p=0.00497) (Fig. 3a), while there was no
294   significant interaction between MWE and TP ($MWE*TP$: p=0.0628) (Fig. S5d, j). The earlier the pitch
295   occurred the higher the C_P. For MWE there is weak increase in C_P with increasing MWE, but with a
296   weak peak in C_P for the mid wing elevation.

Efficiency

Efficiency metrics exhibited strong $TP*MWE$ interactions (Fig. S5 d-e, k-l). Late TP consistently
improved energetic performance, but the benefit of increasing MWE depended on TP: at early TP,
higher MWE improved PF and reduced COT, whereas at late TP the same change in MWE produced
smaller gains or even the opposite trend. Thus, efficient force production emerges from a specific
combination of kinematic timing and elevation, not from either parameter alone.

For the specific efficiency measures we saw that PF varied linearly with TP (TP: 0.8681±0.0484,
p=3.32e^{-14}) and non-linearly with MWE (MWE: 0.6532±0.0484, p=8.24e^{-12}; MWE^2: -0.3729±0.0839,
p=0.00022) (Fig. 3b). There was a strong interaction effect ($MWE*TP$: -0.5256±0.0593, p=1.54e^{-08}) so
that when TP occurred early PF increased strongly with increasing MWE, but when TP occurred late
PF decreased with increasing MWE (or peaked at mid MWE).

COT varied non-linearly with TP (TP: -0.1418±0.0106, p=9.81e^{-12}; TP^2: 0.0469±0.0183, p=0.0185) and
non-linearly with MWE (MWE: -0.1118±0.0106, p=7.76e^{-10}; MWE^2: 0.0740±0.0184, p=0.000611) (Fig.
3c). There was a strong interaction effect ($MWE*TP$: 0.1280±0.0130, p=2.53e^{-09}) so that COT was

highest when *MWE* was low and *TP* occurred early and was lowest when *MWE* was high and *TP*
occurred late.

Body pitch torque

We found the highest values of the pitch torque, C_M, acting on the body when the wing tip was the
furthest from the center of the body (Fig. 4). This was the time during the wingbeat that the thrust
had the greatest moment arm for pitch generation, but it also coincided with the phase of the
wingbeat when we found peaks of thrust.

Figure 1: C_L and C_T during a wingbeat varies with timing of pitch (*TP*) and mean wing elevation
(*MWE*). (a) C_L increases with increasing *MWE*. The increase is faster when *TP* occurs early relative to
the transition between down and upstroke, than when *TP* occurs later relative to the stroke
transition. (b) C_T increases as *MWE* decreases and as *TP* occurs later relative to the transition
between down and upstroke. (c) *T/L* represents the direction of the force generated by the wing.
Highest *T/L* is achieved when *MWE* is low and the *TP* is synchronized with the flapping motion, while
the lowest *T/L* is found when *MWE* is high and *TP* is early. The data points are the wingbeat averages
for each measured sequence, and the contour plot shows the output from the glm-model fitted to
the data.

Figure 2: Instantaneous force coefficients through the flapping cycle. The left panels (**a-c**) show the impact on C_L and the right panels (**d-f**) show the impact on C_T for the timing of the pitch (*TP*) at different wing positions (*MWE* = High, Mid and Low). In each curve, the line represents the phase-averaged value over the three repeats and four wingbeats of each case, and the shaded area has a width of two standard deviations centered around the mean. Shaded background shows the upstroke.

Figure 3: Aerodynamic power and efficiency vary with timing of pitch (*TP*) and mean wing elevation (*MWE*). (a) Power coefficient (C_P) varies strongly with *TP*, increasing the earlier the pitch occurs relative to the transition between downstroke and upstroke. There is also a generally lower C_P, the lower the *MWE*. (b) Power factor (*PF*), a measure of the force/power generated, increases the later the *TP* occurs and the higher the *MWE* (except for the highest *MWE* with the latest *TP*). (c) Cost of transport (*COT*), the energy required to move one Newton of weight one meter, decreases with increasing *MWE* and delayed *TP*. The data points are the wingbeat averages for each measured sequence, and the contour plot shows the output from the glm-model fitted to the data.

Figure 4: Pitch torque (C_M) acting on the body varied with kinematics. (a) When flapping the wing in a high position, the thrust (T) generated during the upper turning point created a pitch down torque, while thrust generated at the lower turning point had little influence on C_M. (b) When the wing was in the mid position, T during both turning points resulted in increased C_M magnitude. (c) With the wing in the lower position, the lower turning point had a large impact on C_M, both during the end of the downstroke and the beginning of the upstroke. (d) Illustration of the moment arm (l_M) and T creating the pitch torque on the body during the turning phases of the wingbeat.

Discussion

Using a robotic wing to control individual aspects of wing kinematics during forward flight conditions, we have shown that both mean wing elevation (*MWE*) and the timing of wing pitch (*TP*) at up- and downstroke transitions influence the magnitude, direction and efficiency of aerodynamic force generation. Importantly, these effects are not independent, and the same *TP* shift can either enhance or reduce lift depending on *MWE*, demonstrating that *TP* must be interpreted in the geometric and aerodynamic context set by wing elevation. This parameter interaction was strongest for lift, force direction, and the efficiency measures. Depending on whether the goal is thrust production, weight support, or energetic efficiency, different regions of the *MWE–TP* control space should be selected. This reveals a rarely considered complexity of flight control that is likely available to flying animals and offers novel coupled control space for designing flapping drones. During flapping flight, the distance and angle between the wings vary throughout a wingbeat. When

the wings are close, either above or below the body, they interact aerodynamically (52). The wings
have mirror pressure distributions (52,53), which affect their aerodynamics. When the wings move
apart at the start of the downstroke, this results in a lower pressure between them than would be
found if they operated on their own, which tends to increase lift (54,55). In our measurements, we
find the expected increase in C_L when the wings are high, but the extra lift mainly comes at the end
of the downstroke rather than at the start (Fig. 2a). We interpret this as a consequence of the
downstroke ending in a position where the wing is close to the horizontal plane and pitch up during
this phase increases the angle of attack and the lift production. In addition, when the wings are high
and the aerodynamic interaction between the wings is expected to be significant, the wing elevation
results in the force generated from each wing being directed sideways, contributing relatively little
to vertical force. When *MWE* instead is low and the wings come together at the end of the
downstroke, we observed an increase in thrust, which we interpret as resulting from an increased
pressure between the wings. This is similar to when wings are in ground effect (42,43,46). Earlier
studies on flapping flight in ground effect have suggested that how the wings are pitched when they
interact with the ground affects the performance, which is thought to explain higher than predicted
energy savings for bats (46) and modelled birds (56). In agreement with these studies, we found that
the amount of lift or thrust at the end of the downstroke depends on the pitch angle of the wings
when they approach each other. If the leading edges of the wings meet first, as when using a
delayed pitch, this results in more thrust than during the synchronized case when the wings have no
pitch at the turning point. We suggest this to be the result of the high pressure on the bottom wing
surfaces accelerating air backwards during the wing-wing interaction. If instead the trailing edges
meet first, as when pitching up early, the high –pressure on the bottom wing surface would
accelerate air forwards, which would then generate negative thrust during this phase (Fig. 2). Our
results thus support the notion that the attitude of the wings, or their pitch angle, during the wing-
wing interaction makes a significant impact on the outcome of the interaction. This also proposes
the opportunity that adjusting *TP* differently for the upper and lower transitions phases will add
further controllability.

An interesting finding is that both the *PF* and *COT* suggest that efficient force generation, in our
setup, happens when *TP* occurs late and *MWE* is in the range between the mid and high position.
Looking at the components of the efficiency measures we see that this result is largely driven by a
low *CP* for later *TP* and relatively high force generation (C_L and C_T). Consequently, unless necessary
for force balance or maneuver/stability reasons, we would suggest animals to favor flapping their
wings relatively symmetrically around the horizontal plane. Overall, our findings suggest that within
our parameter space, C_L is maximized by flapping the wings elevated and with an early *TP*, while for
maximizing C_T the wing should be in a mid-to-low position with a delayed *TP*. If the goal is to change
the direction of the force generated (i.e. *T/L*), a high wing position with an early *TP* tilts the force
upwards the most and a low wing position with a synced *TP* tilts the force forwards the most (Fig. 5).
This means that simple, but relatively understudied, kinematic changes can be used to control
flight. One of the key factors with the parameters we have studied here is that they, in addition to
being allowed to vary between wingbeats, can be adjusted within a single wingbeat (Fig. 2). For
birds and bats, these results suggest that *TP* and *MWE* may function as rapid within-wingbeat
control variables, allowing animals to redistribute force between weight support, propulsion, and
body-pitch (see below) regulation without large changes in gross wing trajectory. A prediction based
on these findings is that we will be likely to find large variation in how animals generate maneuvers

or stabilize flight, depending on the phase of the wingbeat they decide to adjust their trajectory. This
will at least apply to animals with relatively low wingbeat frequency compared to the speed of their
control system (sensors and processing), such as birds and bats, since they would benefit relatively
more from course corrections within wingbeats. Indeed, one of the few studies looking at the
aerodynamics of maneuvers actually used by flying vertebrates (bats) have showed a variety of
mechanisms (including varying the *MWE* of the left and right wing separately) depending on the
phase of the wingbeat when the maneuver is initiated (10).

Our results were obtained for a flapping robot fixed to the wind tunnel. As a consequence, our robot
generated net thrust and variation in lift, while an equilibrium with zero net thrust (thrust and drag
cancel each other) and lift equaling weight is quickly reached in free flying animals and drones.
Interpreting the robot's force generation in a free flight context, we infer that the high thrust
coefficients would lead to acceleration and an increase of drag before stabilizing at a higher flight
speed. Conversely, high values of the lift coefficients suggest enabling flight at lower speeds, while
low values require higher speeds to obtain weight support. Our results thus suggest that low *MWE*
and late *TP* may provide suitable kinematics for fast flight, where low values of the lift coefficient
can produce sufficient weight support, and more thrust is required because of the increased profile
and parasitic drag. On the other hand, we suggest that high *MWE* combined with early *TP* should be
preferred at slow flight, where weight support requires high lift coefficients, and lower speed
produce less drag/thrust requirements. Interestingly, this proposed pattern with high *MWE* at low
speed and low *MWE* at high speed has been demonstrated in some freely flying birds(6,7) and
bats(4,8,38) suggesting animals have already adapted this strategy. By contrast, data on how
animals adjust *TP* in forward flight is largely lacking, while our results identify *TP* as a potentially
important control variable.

Another flight control mechanism, which is linked to the transition phases, involves the relatively
large variation in thrust when we change the *TP* (Fig. 2). Modulating thrust production during the
phases when the wings reach their most elevated or most depressed positions provides an
effective means of controlling body pitch (Fig. 4). Changes in the *MWE* simultaneously alter both
the magnitude of thrust (Figs 1 and 2), through modifications to wing–wing aerodynamic
interactions, and the moment arm of this force, by shifting the vertical position of the wings at the
phase when thrust is produced. Together, these effects determine the pitch torque acting on the
body. This mechanism thus provides a tailless pitch control that can be used to stabilize flight when
flying without a tail (37), but also to initiate maneuvers (57). More generally, this implies that it is
possible to generate yaw torques by employing different *TP* strategies for the left and right wings,
while left–right asymmetries in *MWE* can be used to produce roll torques (10,58). These control
strategies can potentially be applied in concert with other mechanism, including active wing
morphing (59,60), resulting in a flexible control mechanism that can be applied within a single
wingbeat and with a short response time. Understanding how different species utilize these
mechanisms to achieve maneuvers, depending on wingbeat phase and strength of the maneuver,
represents an exciting avenue for future research.

Conclusion

Our results demonstrate that previously overlooked kinematic strategies can substantially influence the direction, magnitude, and efficiency of aerodynamic forces generated by flapping wings during forward flight. Both mean wing elevation and the timing of wing pitch independently affect aerodynamic performance, but notably, we also uncover a strong interaction effect between them. This suggests that these two kinematic parameters can be combined to enhance force production or improve efficiency further than either parameter alone. Physically, we suggest this interaction relates to how *TP* and *MWE* alter how the wings present their pressure surfaces during close wing–wing interactions. Moreover, we show that these kinematic adjustments determine when thrust is produced within the wingbeat, thereby modulating the pitch torque acting on the body. To improve pitch torque authority, our results suggest that transition phases with large moment arm should be used. This provides a tailless mechanism that animals could exploit to stabilize flight or initiate maneuvers. By treating *TP* and *MWE* as coupled kinematic control variables, this study shows that small within-wingbeat adjustments can control force magnitude, direction, efficiency, and pitch in different ways. The results therefore provide both a mechanistic framework for interpreting animal wing motions and a control-oriented design map for bio-inspired flapping systems.

Figure 5. Kinematic control map summarizing tradeoffs across the sampled *TP–MWE* parameter space. High *MWE* with early *TP* favors lift and an upward-tilted resultant force, whereas low *MWE* with late *TP* favors thrust and a more forward-directed force. Energetic performance is best near mid-to-high *MWE* with late *TP*. The map emphasizes that *TP* and *MWE* define a control space in which different aerodynamic objectives are favored in different regions.

Acknowledgement

The research was funded by grants from the Crafoord foundation (20170584) and the Swedish Research Council (2017-03890 and 2022-02850 to L.C.J.). The PIV equipment was financed by an infrastructure grant from Lund University (https://www.lu.se/) to Anders Hedenström, Per Henningsson and L.C.J..

References

1.   Skandalis DA, Baliga VB, Goller B, Altshuler DL. The spatiotemporal richness of hummingbird
wing deformations. J Exp Biol. 2024 May 21;227(10):jeb246223. doi:10.1242/jeb.246223

2.   Aldridge HD. Kinematics and aerodynamics of the greater horseshoe bat, *Rhinolophus*
ferrumequinum , in horizontal flight at various flight speeds. J Exp Biol. 1986 Nov 1;126(1):479–
97. doi:10.1242/jeb.126.1.479

3.   Henningsson P, Spedding GR, Hedenström A. Vortex wake and flight kinematics of a swift in
cruising flight in a wind tunnel. J Exp Biol. 2008 Mar 1;211(5):717–30. doi:10.1242/jeb.012146

4.   Hubel TY, Riskin DK, Swartz SM, Breuer KS. Wake structure and wing kinematics: the flight of
the lesser dog-faced fruit bat, *Cynopterus brachyotis*. J Exp Biol. 2010 Oct 15;213(20):3427–40.
doi:10.1242/jeb.043257

5.   Tobalske BW, Hedrick TL, Biewener AA. Wing kinematics of avian flight across speeds. J Avian
Biol. 2003 Jun;34(2):177–84. doi:10.1034/j.1600-048X.2003.03006.x

6.   Tobalske BW, Warrick DR, Clark CJ, Powers DR, Hedrick TL, Hyder GA, et al. Three-dimensional
kinematics of hummingbird flight. J Exp Biol. 2007 Jul 1;210(13):2368–82.
doi:10.1242/jeb.005686

7.   Tobalske BW, Dial KP. Flight Kinematics of Black-Billed Magpies and Pigeons Over a Wide Range
of Speeds. J Exp Biol. 1996 Feb 1;199(2):263–80. doi:10.1242/jeb.199.2.263

8.   Von Busse R, Hedenström A, Winter Y, Johansson LC. Kinematics and wing shape across flight
speed in the bat, *Leptonycteris yerbabuenae*. Biol Open. 2012 Dec 15;1(12):1226–38.
doi:10.1242/bio.20122964

9.   Hedrick TL, Biewener AA. Low speed maneuvering flight of the rose-breasted cockatoo (
Eolophus roseicapillus). I. Kinematic and neuromuscular control of turning. J Exp Biol. 2007
Jun 1;210(11):1897–911. doi:10.1242/jeb.002055

10.   Henningsson P, Jakobsen L, Hedenström A. Aerodynamics of manoeuvring flight in brown long-
eared bats (Plecotus auritus). J R Soc Interface. 2018;15(148):20180441.
doi:10.1098/rsif.2018.0441

11.   Iriarte-Díaz J, Swartz SM. Kinematics of slow turn maneuvering in the fruit bat *Cynopterus*
brachyotis. J Exp Biol. 2008 Nov 1;211(21):3478–89. doi:10.1242/jeb.017590

12.   Warrick DR, Dial KP. Kinematic, Aerodynamic and Anatomical Mechanisms in the Slow,
Maneuvering Flight of Pigeons. J Exp Biol. 1998 Mar 1;201(5):655–72. doi:10.1242/jeb.201.5.655

13.   Chen Z(陈增爽), Xie Y(谢雨馨), Zhang Y(张扬), Li L(李立), Meng X(孟雪广). Aerodynamics of a
flapping wing with stroke deviation in forward flight. Phys Fluids. 2024 May 15;36(5):051908.
doi:10.1063/5.0209169

14. Dickinson MH, Lehmann FO, Sane SP. Wing Rotation and the Aerodynamic Basis of Insect
Flight. Science. 1999 Jun 18;284(5422):1954–60. doi:10.1126/science.284.5422.1954

15. Harvey C, de Croon G, Taylor GK, Bomphrey RJ. Lessons from natural flight for aviation: then,
now and tomorrow. J Exp Biol. 2023 Apr 17;226(Suppl_1):jeb245409. doi:10.1242/jeb.245409

16. Chin DD, Lentink D. Flapping wing aerodynamics: from insects to vertebrates. J Exp Biol. 2016
Apr 1;219(7):920–32. doi:10.1242/jeb.042317

17. Hedenström A, Johansson LC. Bat flight: aerodynamics, kinematics and flight morphology. J
Exp Biol. 2015 Mar 1;218(5):653–63. doi:10.1242/jeb.031203

18. Liu H, Wang S, Liu T. Vortices and Forces in Biological Flight: Insects, Birds, and Bats. Annu Rev
Fluid Mech. 2024 Jan 5;56(1):annurev-fluid-120821-032304. doi:10.1146/annurev-fluid-120821-
032304

19. Swartz SM, Konow N. Advances in the study of bat flight: the wing and the wind. Can J Zool.
2015 Dec;93(12):977–90. doi:10.1139/cjz-2015-0117

20. Tobalske BW. Aerodynamics of avian flight. Curr Biol. 2022 Oct 24;32(20):R1105–9.
doi:10.1016/j.cub.2022.07.007 PubMed PMID: 36283374.

21. Kwon HK, Chang JW. Effects of shapes and kinematics of hovering flapping wings on
aerodynamic forces and vortex structures. Sci Rep. 2025 Feb 13;15(1):5098.
doi:10.1038/s41598-025-86113-9

22. Lang X, Song B, Yang W, Yang X, Xue D. Sensitivity Analysis of Wing Geometric and Kinematic
Parameters for the Aerodynamic Performance of Hovering Flapping Wing. Aerospace. 2023 Jan
10;10(1):74. doi:10.3390/aerospace10010074

23. Lentink D, Dickinson MH. Rotational accelerations stabilize leading edge vortices on revolving
fly wings. J Exp Biol. 2009 Aug 15;212(16):2705–19. doi:10.1242/jeb.022269

24. Sane SP, Dickinson MH. The aerodynamic effects of wing rotation and a revised quasi-steady
model of flapping flight. J Exp Biol. 2002;205:1087–96. doi:10.1242/jeb.205.8.1087

25. Guerrero JE. Wake Signature and Strouhal Number Dependence of Finite-Span Flapping Wings.
J Bionic Eng. 2010 Sep 1;7:S109–22. doi:10.1016/S1672-6529(09)60224-9

26. Johnson KC, Thurow BS, Wabick KJ, Berdon RL, Buchholz JHJ. Vortex topology of a pitching and
rolling wing in forward flight. Exp Fluids. 2020 Oct 1;61(10):221. doi:10.1007/s00348-020-
03048-9

27. Nadig SV, Ghosh S. Lift enhancement via leading edge vortex delay in flapping flight utilizing
kinematic modifications. Phys Fluids. 2024 Nov 15;36(11):115168. doi:10.1063/5.0236826

28. Xue D, Liu J, Zhang B, Song B. A universal law for predicting the thrust performance of flapping
thin airfoils. Phys Fluids. 2025 Jul 24;37(7):071919. doi:10.1063/5.0276982

29. Parslew B. Predicting Trends in Avian Wing Motion and Energetics Across Scales [Internet].
bioRxiv; 2025 [cited 2025 Jul 28]. p. 2025.06.10.658879. Available from:
https://www.biorxiv.org/content/10.1101/2025.06.10.658879v2
doi:10.1101/2025.06.10.658879

30. Johansson LC. Aerodynamic efficiency explains flapping strategies used by birds. Proc Natl
Acad Sci. 2024 Nov 12;121(46):e2410048121. doi:10.1073/pnas.2410048121

31. Deetjen ME, Chin DD, Heers AM, Tobalske BW, Lentink D. Small deviations in kinematics and
body form dictate muscle performances in the finely tuned avian downstroke. Watanabe YY,
Rutz C, editors. eLife. 2024 Feb 26;12:RP89968. doi:10.7554/eLife.89968

32. Ingersoll R, Haizmann L, Lentink D. Biomechanics of hover performance in Neotropical
hummingbirds versus bats. Sci Adv. 2018 Sep 26;4(9):eaat2980. doi:10.1126/sciadv.aat2980

33. Moriche M, Flores O, García-Villalba M. On the aerodynamic forces on heaving and pitching
airfoils at low Reynolds number. J Fluid Mech. 2017 Oct 10;828:395–423.
doi:10.1017/jfm.2017.508

34. Park KJ, Rosén M, Hedenström A. Flight kinematics of the barn swallow (*Hirundo rustica*) over
a wide range of speeds in a wind tunnel. J Exp Biol. 2001 Aug 1;204(15):2741–50.
doi:10.1242/jeb.204.15.2741

35. Rosén M, Spedding GR, Hedenström A. Wake structure and wingbeat kinematics of a house-
martin *Delichon urbica*. J R Soc Interface. 2007 Aug 22;4(15):659–68.
doi:10.1098/rsif.2007.0215

36. Rosén M, Spedding GR, Hedenström A. The relationship between wingbeat kinematics and
vortex wake of a thrush nightingale. J Exp Biol. 2004;207:4255–68. doi:10.1242/jeb.01283

37. Johansson LC, Hedenström A. The vortex wake of blackcaps (*Sylvia atricapilla* L.) measured
using high-speed digital particle image velocimetry (DPIV). J Exp Biol. 2009 Oct
15;212(20):3365–76. doi:10.1242/jeb.034454

38. Wolf M, Johansson LC, Von Busse R, Winter Y, Hedenström A. Kinematics of flight and the
relationship to the vortex wake of a Pallas' long tongued bat (*Glossophaga soricina*). J Exp Biol.
2010 Jun 15;213(12):2142–53. doi:10.1242/jeb.029777

39. Hubel TY, Hristov NI, Swartz SM, Breuer KS. Changes in kinematics and aerodynamics over a
range of speeds in *Tadarida brasiliensis* , the Brazilian free-tailed bat. J R Soc Interface. 2012
Jun 7;9(71):1120–30. doi:10.1098/rsif.2011.0838

40. Ajanic E, Paolini A, Coster C, Floreano D, Johansson C. Robotic Avian Wing Explains
Aerodynamic Advantages of Wing Folding and Stroke Tilting in Flapping Flight. Adv Intell Syst.
2023 Feb;5(2):2200148. doi:10.1002/aisy.202200148

41. Pennycuick CJ, Alerstam T, Hedenström A. A new low-turbulence wind tunnel for bird flight
experiments at Lund University, Sweden. J Exp Biol. 1997;200:1441–9.
doi:10.1242/jeb.200.10.1441

42. Lighthill J. A simple fluid-flow model of ground effect on hovering. J Fluid Mech. 1979
Aug;93(04):781. doi:10.1017/S0022112079002032

43. Rayner JMV. On the aerodynamics of animal flight in ground effect. Phil Trans R Soc Lond B.
1991;334:119–28.

44. Percin M, Hu Y, van Oudheusden BW, Remes B, Scarano F. Wing Flexibility Effects in Clap-and-
Fling. Int J Micro Air Veh. 2011 Dec 1;3(4):217–27. doi:10.1260/1756-8293.3.4.217

45. Quinn DB, Moored KW, Dewey PA, Smits AJ. Unsteady propulsion near a solid boundary. J Fluid
Mech. 2014 Mar 10;742:152–70. doi:10.1017/jfm.2013.659

46. Johansson LC, Jakobsen L, Hedenström A. Flight in Ground Effect Dramatically Reduces
Aerodynamic Costs in Bats. Curr Biol. 2018 Nov;28(21):3502-3507.e4.
doi:10.1016/j.cub.2018.09.011

47. Tong W, Yang Y, Wang S. Estimating thrust from shedding vortex surfaces in the wake of a
flapping plate. J Fluid Mech. 2021 Aug 10;920:A10. doi:10.1017/jfm.2021.434

48. Von Busse R, Waldman RM, Swartz SM, Voigt CC, Breuer KS. The aerodynamic cost of flight in
the short-tailed fruit bat (*Carollia perspicillata*): comparing theory with measurement. J R Soc
Interface. 2014 Jun 6;11(95):20140147. doi:10.1098/rsif.2014.0147

49. Johansson LC, Maeda M, Henningsson P, Hedenström A. Mechanical power curve measured in
the wake of pied flycatchers indicates modulation of parasite power across flight speeds. J R
Soc Interface. 2018 Jan;15(138):20170814. doi:10.1098/rsif.2017.0814

50. Drela M. Power Balance in Aerodynamic Flows. AIAA J. 2009 Jul;47(7):1761–71.
doi:10.2514/1.42409

51. Wang ZJ. Aerodynamic efficiency of flapping flight: analysis of a two-stroke model. J Exp Biol.
2008 Jan 15;211(2):234–8. doi:10.1242/jeb.013797

52. Lehmann FO, Sane SP, Dickinson M. The aerodynamic effects of wing–wing interaction in
flapping insect wings. J Exp Biol. 2005 Aug 15;208(16):3075–92. doi:10.1242/jeb.01744

53. Tay WB. Effect of Different Types of Wing-Wing Interactions in Flapping MAVs. J Bionic Eng. 2017
Jan 1;14(1):60–74. doi:10.1016/S1672-6529(16)60378-5

54. Maxworthy T. Experiments on the Weis-Fogh mechanism of lift generation by insects in hovering
flight. Part 1. Dynamics of the 'fling'. J Fluid Mech. 1979 Jul 12;93(1):47–63.
doi:10.1017/S0022112079001774

55. Weis-Fogh T. Quick estimates of flight fitness in hovering animals, including novel mechanisms
for lift production. J Exp Biol. 1973;59:169–230. doi:10.1242/jeb.59.1.169

56. Su JY, Tang JH, Wang CH, Yang JT. A numerical investigation on the ground effect of a flapping-
flying bird. Phys Fluids. 2013 Sep 1;25(9):093101. doi:10.1063/1.4819503

57. Lee EH, Yang HH, Lee SG, Han JH. A Biologically-Inspired Flapping-Wing Air Vehicle With Active
Folding-Wings. IEEE Robot Autom Lett. 2026 Mar;11(3):2786–93.
doi:10.1109/LRA.2026.3653275

58. Anuar K, Amemiya A, Sato H, Afakh ML, Yunanto B, Mochiyama H, et al. Agile Maneuvering of
Servo-Driven Flapping Robot: Novel Approach Using Center Flapping Angle and Offset Angle
Variables. IEEEASME Trans Mechatron. 2026;1–12. doi:10.1109/TMECH.2025.3648513

59. Ajanic E, Feroskhan M, Wüest V, Floreano D. Sharp turning maneuvers with avian-inspired wing
and tail morphing. Commun Eng. 2022 Nov 24;1(1):34. doi:10.1038/s44172-022-00035-2

60. Chang E, Chin DD, Lentink D. Bird-inspired reflexive morphing enables rudderless flight. Sci
Robot. 2024 Nov 20;9(96):eado4535. doi:10.1126/scirobotics.ado4535