Benchmarking and Experimental Validation of Machine Learning Strategies for Enzyme Engineering

Zishuo Zeng[1], Jiao Jin[2], Rufang Xu[1], Xiaozhou Luo[1] [*]
1. State Key Laboratory of Quantitative Synthetic Biology, Center for Synthetic Biochemistry, Shenzhen Institute of Synthetic Biology, Shenzhen Institutes of Advanced Technology, Chinese Academy of Sciences, Shenzhen 518055, China
2. Synceres Biosciences Co. Ltd. 1100 Huanli Road, Guangming District, Shenzhen, Guangdong, China 518083
* Corresponding authors
Emails: xz.luo@siat.ac.cn

Abstract

Enzyme-directed evolution increasingly relies on computational tools to prioritize mutations, yet their practical value is difficult to assess because kinetic data are often aggregated across heterogeneous assay conditions, inflating apparent generalization. Here we introduce EnzyArena, a curated benchmark in which kinetic parameters (kcat, Km and kcat/Km) are grouped by experimental campaign and measured under matched conditions, thereby minimizing confounders such as pH, temperature, reaction, and batch. Using EnzyArena, we systematically evaluate 20 models spanning four widely used strategies for guiding enzyme evolution: protein–ligand binding affinity prediction, protein stability prediction, zero-shot fitness prediction and enzyme kinetic parameter prediction. Across subsets derived from public databases and 25 independent mutagenesis datasets, most models exhibit weak, fragile or inconsistent correlation with catalytic activity. Kinetic-parameter predictors perform strongly on database-derived subsets but lose their advantage on independent datasets, whereas zero-shot predictors show more consistent generalization. A simple consensus of multiple zero-shot models further improves the precision of identifying beneficial mutants. We prospectively validated these findings in a wet-lab campaign (150 mutants) comparing random mutants, UniKP-prioritized mutants and ESM-1v-prioritized mutants (representing supervised kinetic-parameter prediction and zero-shot fitness prediction, respectively), where ESM-1v achieved the highest utility and UniKP underperformed the random baseline. Together, this study establishes realistic baselines for computational mutant prioritization and highlights consensus zero-shot strategies as a practical starting point for enzyme engineering.

Zero-shot fitness predictors are the most competitive and generalizable class, but still achieve

only modest correlations on independent datasets. Notably, a simple consensus of multiple zero-

shot models substantially improves the precision of identifying superior mutants and currently

offers the most practical computational benefit for enzyme engineering. Our work establishes

EnzyArena as a fair benchmark for enzyme activity prediction, defines realistic performance

baselines for existing tools, and highlights consensus zero-shot strategies as the most useful

computational tool in practice for enzyme-directed evolution.

Keywords

Enzyme evolution, benchmark dataset, zero-shot prediction, docking, protein stability, enzyme

kinetic parameter prediction

<div align="center">**Introduction**</div>

Enzyme-directed evolution underpins modern biocatalysis, green chemistry [1]and industrial

biotechnology [2] by enabling the rapid optimization of catalysts for non-native substrates, process

conditions and reaction networks. Over the past few years, advances in machine learning have

transformed how many groups design and prioritize variants [3], with tools ranging from protein

language models [4-7] and neural-network kinetic predictors [8-12] to docking-based binding models

[13-17] and stability scoring predictors [18-22] now routinely appearing in high-profile enzyme

engineering studies. In principle, these approaches promise to compress the search space, reduce

the experimental burden [23] and reveal general principles of sequence–function relationships that

are difficult to infer from intuition alone.

Yet the current empirical foundation for these promises is surprisingly fragile. Many published

studies [8-12] aggregate kinetic data obtained under heterogeneous assay conditions, differing in

temperature, pH, substrate identity, cofactors, host background and assay format, and then treat

the resulting $kcat$, Km or $kcat/Km$ values as if they were directly comparable. Endpoints with

distinct biophysical meanings, such as catalytic turnover, ligand binding, protein stability and

organismal growth, are often analyzed interchangeably, with activity, "fitness" and expression

level being used as proxies for one another. On top of this, enzymology itself is marked by

substantial metrological variation: even when nominal assay conditions and protocols are

matched, measurements from different laboratories, different instruments or even two nominally

identical devices can diverge [24] because of differences in calibration, baseline correction, and

timing. Machine-learning models trained on such aggregates are therefore encouraged to fit a

mixture of sequence–function signal and instrument- or laboratory-specific biases. Finally,

models trained on large public resources such as BRENDA [25] and SABIO-RK [26] are frequently

evaluated on test sets that partially overlap with their training data, or that share closely related

sequences and experimental campaigns, leading to hidden data leakage and optimistic

performance estimates [27][28][29]. Together, assay heterogeneity, endpoint inconsistency,

metrological variability and data leakage make it difficult to know which computational

strategies genuinely enrich for variants with improved catalytic performance and which succeed

mainly by exploiting quirks of current datasets.

In this work, we address this problem from a data-centric perspective by constructing a curated

benchmark (namely, EnzyArena) for computationally guided enzyme-directed evolution built

around kinetic parameters measured under strictly matched conditions and grouped at the level

of individual experimental campaigns. We assemble datasets in which temperature, pH, substrate,

host and assay format are controlled within each subset, explicitly track potential overlaps with

public kinetic databases, and treat laboratory- and instrument-specific effects as fundamental

sources of variation rather than negligible noise (Figure 1A). On this foundation, we

systematically compare four major families of models—binding predictors, stability scorers,

zero-shot protein language models and kinetic-parameter predictors (Figure 1B)—using

evaluation protocols designed to avoid leakage and to mirror realistic directed-evolution use

cases. Under these stringent conditions, we find that many widely used models show limited and

fragile correspondence with catalytic outcomes, whereas zero-shot sequence models provide the

most robust and transferable signal for ranking enzyme variants. We then complement this

retrospective benchmarking with a prospective wet-lab enzyme engineering campaign to directly

test whether model-guided recommendations improve mutant prioritization under practical

experimental constraints.

Figure 1. Overview of the methodology in this study. Panel A shows the data cleansing process and method of evaluation. Data of enzyme KP were obtained from public databases and organized into multiple subsets where all experimental conditions are consistent across samples within subset. Predictions from various computational tools were made for each of the subsets and the Spearman correlations for all the subsets were computed and summarized for each individual predictor. Panel B summarized the computational tools included in this study for four different commonly used computational strategies, including protein-ligand binding affinity prediction, protein stability prediction, zero-shot fitness prediction, and enzyme KP prediction.

Results and Discussion

Data curation

A fair evaluation of computational enzyme predictors requires a dataset that minimizes experimental confounders while maintaining broad coverage across enzyme classes. We argue that an ideal benchmarking dataset should meet two key criteria: (1) it should encompass a wide range of enzyme types to reduce functional bias, and (2) experimental conditions—such as pH, temperature, and expression system—should remain consistent within subsets to avoid confounding factors. However, many existing kinetic datasets lack detailed metadata describing

assay conditions, which limits reproducibility and cross-study comparability [30]. In particular, the

training of current kinetic-parameter (KP) predictors often violates the second criterion, as they

aggregate data from heterogeneous sources during training. Likewise, while repositories such as

ProteinGym provide large-scale fitness datasets with diverse experimental labels, including

binding, organismal fitness, expression, stability, and activity, the majority of activity data

involve non-enzymatic functions or enzyme reactions with macromolecular substrates, which

contradicts with KP predictors in this study, as they support only small-molecule substrates.

These limitations motivated our effort to construct condition-controlled datasets suitable for

rigorous benchmarking.

Following these principles, we collected 1,571 *kcat* (turnover number), 2,250 *Km* (Michaelis

constant), and 1,351 *kcat*/*Km* (catalytic efficiency) entries from the BRENDA and SABIO-RK

databases, applying strict inclusion criteria (i.e., mutagenesis studies with ≥10 variants per assay,

including one wild-type and at least nine mutants; see Materials and Methods). The curated data

were partitioned into 130 *kcat* subsets, 174 *Km* subsets, and 110 *kcat*/*Km* subsets, ensuring

internal consistency across experimental parameters such as pH, temperature, source organism,

substrate, reaction type, and reference. This structured partitioning ensured that data within each

subset were comparable and that observed performance differences among predictors could be

attributed to algorithmic rather than experimental variation.

In addition to the KP datasets, we manually curated 25 independent datasets related to enzyme

catalytic activity that are not included in BRENDA or SABIO-RK. These comprise four deep

mutagenesis scanning (DMS) fitness score datasets, nine *kcat* datasets, nine *Km* datasets, and

three *kcat*/*Km* datasets (Table 1). These independent datasets were particularly important for

unbiased evaluation of kinetic-parameter predictors, which are frequently trained on data derived

from BRENDA and SABIO-RK. Together, these curated and independent datasets form the

foundation of **EnzyArena**, enabling fair and reproducible assessment of enzyme activity

prediction models under well-controlled experimental conditions.

Selection of Representative Predictors for Each Computational Strategy

To provide a fair and comprehensive evaluation of commonly used computational strategies for

enzyme engineering, we selected five representative tools for each of the four major paradigms

examined in this study: protein–ligand binding affinity prediction, protein stability prediction,

zero-shot fitness prediction, and kinetic-parameter (KP) prediction (Table 2). Selection of

predictors are based on the considerations of methodological diversity, widespread use, recency

of publication, and performance in independent benchmark when available. Detailed descriptions

of the individual models can be found in Supplementary Information.

Although stability, binding affinity, and zero-shot fitness are not mechanistically equivalent to

catalytic activity, they are nevertheless widely used proxies in enzyme-directed evolution for

several practical reasons. First, protein stability is often treated as a prerequisite for high activity

and evolvability: stabilizing mutations can expand the sequence space accessible to laboratory

evolution and mitigate activity–stability trade-offs [31-33]. Second, binding-affinity predictions,

particularly docking scores, are frequently used to identify mutations that strengthen substrate

interactions, with numerous studies reporting improved catalytic performance after selecting

variants with improved predicted binding [34]. Third, zero-shot fitness predictors have gained

traction due to their accessibility and scalability due to their demonstrated utility in identifying

beneficial or deleterious mutations across large mutational landscapes, including in enzymes [30,4]

[35, 36]. This widespread use underscores the need for a systematic, leakage-free, and condition-

controlled evaluation, thus motivating the benchmarking framework established in this study.

Table 3 reports the computational time required to run all models on a compute node of NVIDIA

A10 GPU with 32 CPUs. Most stability predictors and kinetic parameter (KP) predictors

completed within a short timeframe, with the exception of FoldX and EITLEM-Kinetics, which

required 17.83 hours and 8 hours, respectively. All zero-shot predictors were computationally

efficient, completing the full dataset in under 5 hours. In contrast, binding affinity prediction

tools were substantially more time-consuming. Except for PSICHIC, all docking-based methods

required between 31.5 and 112 hours to process the entire dataset, making them the slowest

among the evaluated model categories.

Figure 2. Performances overview of computational tools on subsets derived from BRENDA and SABIO-RK. Performance is measured by Spearman correlation. In each panel, red, blue, and grey dots indicate significantly (p-value < 0.05) positive, significantly negative, and non-significant Spearman correlations, respectively.

Zero-shot Fitness Predictors Outperformed Binding Affinity and Stability Predictors for All Data Sources

To begin benchmarking the different computational strategies, we first compared stability,

binding-affinity, and zero-shot fitness predictors across all three data sources, including

BRENDA, SABIO-RK, and the manually curated independent datasets—because none of these

model families were trained on these datasets. This ensures that all comparisons in this section

are free from data leakage and reflect each model's intrinsic generalizability. An overview of

model performance on BRENDA- and SABIO-RK–derived subsets is shown in Figure 2 (with

detailed breakdowns in Figures S1 and S2).

Across all data sources, zero-shot fitness predictors consistently achieved the highest correlations

with experimental measurements. Their median Spearman correlations ranged from 0.134 to

0.254 in BRENDA subsets (Figure S1), 0.173 to 0.377 in SABIO-RK subsets (Figure S2), and

0.15 to 0.25 overall—BRENDA, SABIO-RK and independent datasets (Figure 3A). This trend

also holds when sample size is accounted (Figure 3B).

In contrast, binding-affinity predictors showed near-zero association with experimental kinetic

parameters. For example, correlations with Km were minimal, with median values between –

0.017 and 0.038 (Figure 2K). Although Km is often interpreted as a proxy for substrate binding

affinity, in theory, Km reflects a composite of binding affinity (Kd), catalytic turnover ($kcat$), and

the rates of substrate association and dissociation [37]. Moreover, solvent effects such as pH and

ionic strength, which critically modulate enzyme–substrate interactions, are typically not

accounted for in computational binding models [38]. Therefore, binding-affinity predictions alone

are insufficient to capture the multifactorial determinants of experimental Km, which may

partially explain the underperformances of binding affinity predictors on Km datasets.

Similarly, protein stability predictions showed little to no correlation with experimental

measurements (with medians of correlations ranging from -0.018 to 0.051; Figure 2A-C).

Although stability and catalytic activity are theoretically independent properties, stability

predictors are widely incorporated into protein engineering workflows under the assumption that

enhanced stability may indirectly support improved activity [33], nevertheless, a recent benchmark

study reported that predictive accuracy for stability remains limited [39]. Consistent with these

findings, our results indicate that current stability predictors provide limited utility in guiding

catalytic activity optimization.

Together, these results show that evolutionary or language model–derived signals provide the

most informative basis for ranking enzyme variants across diverse conditions, even though zero-

shot models were never trained on catalytic activity labels.

Kinetic Parameter Predictors Succeed on KP Datasets but Lose Advantage on Leakage-

Free Independent Data

Because zero-shot predictors outperformed both stability and binding-affinity models across all

datasets (Figure 3A), we next compared zero-shot predictors directly with kinetic-parameter (KP)

predictors. KP models represent the most mechanistically relevant strategy for catalytic

prediction, but they are typically trained on large volumes of BRENDA and SABIO-RK data. As

a result, their performance on subsets derived from these databases is susceptible to data leakage.

Indeed, in the BRENDA and SABIO-RK subsets, one of the KP predictors, EITLEM-kinetics,

achieved the highest median Spearman correlations (median = 0.680), while the remaining KP

models performed similarly to zero-shot predictors with modest correlations (0.024-0.263)

(Figure 2). These strong performances are expected given the overlap in data sources and

highlight the need for evaluations on leakage-free datasets.

To obtain an unbiased comparison, we therefore benchmarked both strategy classes on the

manually curated independent datasets (Figure 3C), which share no overlap with the training data

of KP predictors. On these truly independent datasets, both zero-shot and KP predictors

exhibited reduced performance (Figure 3C), with zero-shot predictors reaching median

correlations of 0.086-0.200 and KP predictors reaching -0.283-0.086. These modest correlations

reflect two sources of limitation: a) model limitations, where predictors fail to generalize outside

the domain of their training data; and b) data limitations, as many of the independent datasets

contain only 6–10 variants. Such small sample sizes amplify technical noise and bias, making

rank-based metrics like Spearman correlation particularly unstable [40].

For a more robust summary that accounts for differences in dataset size, we combined

correlation estimates using Fisher z meta-analysis [41]. In this framework, correlations are

transformed to stabilize variance and then pooled using inverse-variance weighting so that larger

and more informative datasets contribute more strongly to the overall estimate (Eqn. 3; Materials

and Methods). This approach is widely used to aggregate correlation coefficients across

heterogeneous studies and is particularly appropriate when sample sizes differ substantially

between datasets {Borenstein, 2021 #1318}. When correlations were weighted by dataset size

(Figure 3D), zero-shot predictors still retained an advantage (weighted sum = 0.219 to 0.406)

over KP models (weighted sum = -0.197 to 0.157), reflecting slightly stronger generalization

despite the noisy, small-scale evaluation setting.

Overall, these results show that while KP predictors showed good perform on KP datasets

overlapped with their training sources, their advantage rapidly diminishes when evaluated on

independent, leakage-free data. In contrast, zero-shot predictors maintain relatively robust

performance across all conditions, suggesting that sequence-level evolutionary information

confer stronger generalizability than current supervised KP prediction models.

Figure 3. Comparative performance evaluation of computational predictors across datasets.
(A–B) Comparison among stability, zero-shot fitness, and binding-affinity predictors across all
three data sources (BRENDA, SABIO-RK, and independent datasets). (C–D) Comparison
between zero-shot fitness and kinetic-parameter predictors using only independent datasets.
Panels A and C show the distribution of Spearman correlation coefficients across subsets,
ordered by median correlation from highest to lowest. Panels B and D summarize the weighted
sum of correlations (weighted by sample size, Eqn. 3), also ordered from highest to lowest. To
ensure consistent interpretation, correlation signs were adjusted by taking absolute values where
appropriate to match the expected relationship with DMS scores, *kcat*, *Km*, and *kcat*/*Km* (see
Materials and Methods and Table S1), so that higher correlations uniformly indicate better model
performance.

Inter-Model Correlation Analysis Reveals Strategy-Specific Clustering

To better understand relationships among predictors, we analyzed pairwise correlations across all

model outputs (Figure 4). Models within the same computational paradigm formed clear clusters,

with intra-group Pearson correlations ranging from -0.812 to 0.941, while inter-group

correlations were generally weak (-0.518 to 0.485). Notable exceptions included: FoldX, which

showed unusually low correlation with other stability predictors (correlation = -0.060 to 0.155),

consistent with recent benchmarks noting its limited accuracy; KP predictors, which showed

moderate correlation with binding-affinity predictors in the Km subset (correlation = -0.518 to

0.485), consistent with Km's partial dependence on substrate binding. These structural

relationships between models further support our strategy to evaluate predictors by family and to

identify which paradigms generalize best across datasets.

Figure 4. Heatmap of pairwise correlation among the predictors. The heatmaps display
Pearson correlation coefficients between model predictions, with values ranging from +1 (red,
perfect positive correlation) to –1 (blue, strong negative correlation). Models are grouped and
color-coded based on computational strategy: purple (stability predictors), red (zero-shot
sequence-based models), orange (kinetic parameter–specific models), and cyan (binding affinity
models).

Prospective wet-lab validation using patchoulol synthase

Building on the benchmarking results described above, two key conclusions emerge. First, zero-

shot fitness predictors and kinetic-parameter (KP) predictors represent the strongest-performing

strategies on current public datasets, with KP models achieving high apparent accuracy when

evaluated on data sources closely related to their training distributions. Second, when evaluated

on leakage-free independent datasets, zero-shot predictors consistently show better

generalization than KP models, albeit under conditions where dataset sizes are typically small

and correlations remain modest. Given that many of these independent datasets contain only a

limited number of variants, it remains unclear whether the observed advantage of zero-shot

models fully translates to practical enzyme engineering scenarios. To address this gap and

directly assess real-world utility, we next performed a prospective wet-lab validation to compare

model-guided mutation prioritization strategies under controlled experimental conditions.

To experimentally evaluate model-guided mutation prioritization, we selected patchoulol

synthase (PTS) as a test enzyme. PTS catalyzes the cyclization of farnesyl pyrophosphate to

patchoulol, which is the major bioactive component of patchouli oil and has attracted increasing

attention due to its reported anticancer, neuroprotective, anti-inflammatory, and gastroprotective

activities {Lee, 2020 #1319}. Despite its industrial relevance, PTS is a multiproduct terpene

synthase that produces patchoulol at relatively low selectivity {Ekramzadeh, 2020 #1320},

limiting its biotechnological application and makes it a challenging target for enzyme

engineering.

We performed saturated single-site mutagenesis on PTS and used computational models to

prioritize variants for experimental testing. Based on the benchmarking results, ESM-1v and

UniKP were selected to represent the zero-shot fitness strategy and KP strategy, respectively.

Each model prioritized 50 mutants, and an additional 50 mutants were selected randomly as a

baseline, resulting in 150 variants in total. All variants were constructed and experimentally

evaluated by measuring patchoulol production relative to the wild type (Figure 5A).

The experimental results show a clear separation between strategies. Variants prioritized by

UniKP do not outperform the random baseline, whereas ESM-1v–prioritized variants show

significantly higher activity than both random and UniKP-selected mutants (Figure 5A). To

further examine model–experiment agreement, we pooled all 150 variants and performed a

retrospective correlation analysis between model predictions and experimental measurements.

UniKP predictions show a negative correlation with experimental activity ($\rho = -0.195$; Figure

5B), whereas ESM-1v predictions show a positive correlation ($\rho = 0.394$; Figure 5C). Notably,

one ESM-1v–prioritized mutant (C23S) achieved an approximately threefold higher activity over

the wild type.

Overall, this prospective validation supports the conclusions from the computational benchmark

and demonstrates that zero-shot fitness prediction provides a more robust and generalizable

strategy for prioritizing enzyme mutations in practice.

Figure 5. Model performance on a wet-lab validation dataset for model-guided mutagenesis of the PTS enzyme. (A) Distribution of experimentally measured fold change values for mutants prioritized by Random, UniKP, and ESM1v models. The red dashed line marks the wildtype (WT) level (fold change = 1). Letters above the boxes denote statistical groupings from a one-way ANOVA followed by Tukey's post-hoc test; groups that do not share a letter differ significantly ($P < 0.05$). (B) Relationship between UniKP model predictions and experimentally measured fold change relative to wild type (WT). (B) Relationship between ESM1v model predictions and experimental fold change to WT. Each point represents a mutant, colored by model category; the Spearman correlation coefficient (ρ) is indicated. The regression line shows the least-squares fit. Together, these results show that ESM1v predictions exhibit a stronger monotonic relationship with experimental measurements compared with UniKP, and that model-guided designs yield distinct distributions of functional outcomes relative to random variants.

Combination of Zero-Shot Predictors Improves the Precision of Identifying Superior

Enzyme Mutants

Given the strong individual performance of zero-shot fitness predictors demonstrated above, we

next investigated whether combining multiple predictors could further improve the success rate

of identifying mutants with enhanced catalytic activity. Our analysis focused on precision (Eqn.

1), defined as the proportion of predicted beneficial mutants that are experimentally confirmed to

outperform the reference. Because "wildtype" is context-dependent, we generated an exhaustive

pairwise comparison dataset in which every mutant in turn served as the reference, and all other

mutants were evaluated relative to it. This strategy greatly expanded the evaluation space and

enabled a robust assessment of prediction performance across diverse mutational landscapes.

For each pairwise comparison, we evaluated whether a given predictor or combination of

predictors correctly identified the mutant with superior experimental activity. To assess

combinations, we implemented a consensus strategy, where a mutant was predicted to be

superior only if all zero-shot models in the combination ranked the mutant higher than the

reference. All 31 possible combinations of the five predictors (ranging from single models to

combinations of all five) were evaluated (Figure 6A; Figure S1). Importantly, predictor outputs

were directionally standardized so that higher scores consistently indicated higher predicted

fitness.

Across datasets containing at least 20 mutants, the combination of GEMME, ProSST, SaProt,

and VESPA achieved a significantly higher average precision (0.74) compared to the best-

performing single predictor, SaProt (0.65) (Wilcoxon rank-sum test, $p = 0.044$; Figure 6B). In

contrast, for datasets with fewer than 20 mutants, all predictors, whether alone or in combination,

showed comparable performance (Figure S3). These results suggest that consensus modeling

using multiple zero-shot predictors offers a practical strategy to substantially increase the success

rate of identifying beneficial mutations, particularly when the mutational search space is

moderately large ($n \geq 20$).

382
Figure 6. Combination of zero-shot predictors improves precision in identifying beneficial enzyme mutants. (A) Precision of all 31 combinations of five zero-shot predictors, evaluated using exhaustive pairwise comparisons across datasets with at least 20 mutants. Each box plot represents the distribution of precision values across datasets, with the dashed red line indicating random baseline performance. (B) Comparison of the best-performing single predictor (SaProt) and the top-performing combination (GEMME + ProSST + SaProt + VESPA). The consensus predictor achieves a significantly higher precision (mean 0.74) than SaProt alone (mean 0.65), demonstrating the benefit of integrating multiple predictive models (p = 0.044, Wilcoxon rank-sum test).

Other considerations and concluding remarks

This study highlights several inherent pitfalls of KP predictors that must be considered when applying them to enzyme-directed evolution. First, as previously mentioned, KP data from public databases are often pooled together without aligning the experimental conditions, which can obscure the primary goal of enzyme-directed evolution: identifying sequence-level differences. In this study, we addressed this issue by sorting noisy data into subsets where experimental

conditions were consistent across samples, a critical step for accurately evaluating the

performance of computational tools.

Second, KP predictors typically use standard loss functions (such as root mean squared error or

mean squared error) during training. However, in practice, the relative ranking of mutants is

often of greater interest rather than their absolute KP values. Researchers typically aim to predict

the relative ranking among mutants to identify variants that outperform the wild type. To address

this, we focused on Spearman correlation as a metric to evaluate the ranking performance of

computational tools in guiding enzyme-directed evolution.

Additionally, published studies on computationally guided enzyme evolution may be biased

toward successful cases, while failures are often underreported. This selective reporting can

mislead future researchers, who may overestimate the utility of these tools and continue to invest

in computational methods with limited effectiveness. Our study aims to provide a more balanced

perspective, revealing both the strengths and limitations of these computational tools.

It is also important to note that, despite our efforts to ensure maximal consistency within subsets,

some inconsistencies may still exist in the curated data, such as variations in codon optimization,

culture conditions, and experimental protocols. These factors are difficult to resolve without

more comprehensive reporting in publications and the development of advanced text processing

tools. Another key limitation of our study is that it did not address epistatic interactions, where

multiple mutations co-occur and affect each other's effects. Predicting such epistatic interactions

remains a significant challenge, as many predictors (Table 2) are not compatible with these

scenarios.

In summary, we evaluated the performance of various commonly used and emerging

computational tools for guiding enzyme evolution toward improved catalytic activity. The

datasets in this study were carefully curated to ensure consistency, which is a crucial prerequisite

for meaningful comparison. Our results highlight the promising potential of large language

model-based zero-shot fitness predictors and suggest that mutagenesis data should be sufficiently

large to fully leverage the capabilities of computational tools.

Materials and Methods

Data Collection from Public Databases

Data were primarily obtained from the BRENDA database (https://www.brenda-

enzymes.org/index.php) and the SABIO-RK database (https://sabio.h-its.org/newSearch/index).

From BRENDA, entries were collected based on the "Classic view" categories of "Turnover

Number," "*Km* Value," and "*kcat*/*Km* Value." For SABIO-RK, data were retrieved by setting the

search condition Parametertype to ("*kcat*" OR "*Km*" OR "*kcat*/*Km*").

Curation of Independent Datasets

We manually curated 25 additional mutagenesis datasets. The inclusion criteria were:

a) identifiable sequences;

b) small molecule substrate (to ensure compatibility with KP predictors);

c) at least six mutant sequences (including wild type);

d) for *kcat*, *Km*, or *kcat*/*Km* datsts, publication date must be within the latest year (2025) to

avoid possible overlap with KP predictor's training data.

As a result, we managed to curate datasets with a variety of experimental measurements,

including relative activity, *kcat*, *Km*, *kcat*/*Km*, and deep mutational scanning (DMS) scores. For

the DMS data, the reported fitness scores were averaged across three replicates. Since our

downstream evaluation is based on Spearman correlation, which depends on the relative ordering

of data points, we first ranked all DMS measurements from low to high, then selected 100 data

points at fixed intervals. This strategy reduces the influence of experimental noise and increases

the likelihood that adjacent points reflect true biological differences rather than measurement

variability, thereby producing a more robust correlation assessment.

Data Preprocessing

To ensure that the curated datasets were accurate and comparable, strict filtering criteria were

applied to the raw entries from BRENDA and SABIO-RK. Entries lacking a UniProt ID,

containing multiple UniProt IDs, or missing information on substrate, temperature, pH, or

literature reference were removed. Because standardized mutation annotations were not provided

in these databases, mutation data were extracted from textual annotations.

We focused on single-point mutations and excluded entries containing the keywords 'insert',

'insertion', 'inserted', 'delete', 'deletion', 'deleted', 'double', 'triple', 'multiple', '/', 'hybrid', 'mixture',

'delta', 'truncate', 'truncated', or 'fragment' (case-insensitive). For SABIO-RK, enzyme types were

annotated based on the "Enzyme Variant" field: entries containing "wildtype" were labeled as

wildtype enzymes, and those containing "mutate," "mutated," "mutation," "mutant,"

"mutagenesis," or "variant" were labeled as mutated enzymes. For BRENDA, due to the absence

of explicit annotations, entries without mutation keywords were considered wildtype.

For entries annotated as mutated enzymes, mutation annotations were retained only if they

followed the format of "single amino acid + position number + single amino acid" and involved

exactly one mutation. Small datasets (referred to as "subsets") were constructed as follows: for

BRENDA, entries were grouped by EC number, enzyme name, UniProt ID, substrate, organism,

reference, temperature, and pH. For SABIO-RK, explicit reaction information was also included

in grouping.Only subsets containing one wildtype enzyme and at least nine single-point

mutations were retained.

All subsets were then manually validated. Using the UniProt ID, wildtype protein sequences

were retrieved from the UniProt database (https://www.uniprot.org/). For each mutation, the

amino acid at the specified position was verified against the wildtype sequence. Mutated

sequences were generated accordingly. Subsets involving enzymes longer than 1000 amino acids

were excluded due to downstream model constraints. For substrate preprocessing, Substrate

SMILES representations were obtained as following. InChI identifiers were retrieved under the

"Ligands" section and converted to SMILES using RDKit for the BRENDA entries. For SABIO-

RK entries, SMILES were obtained from the PubChem database

(https://pubchem.ncbi.nlm.nih.gov/).

In total, 441 validated subsets were obtained, including 293 from BRENDA, 121 from SABIO-

RK, and 25 from the literature.

Model Deployment and Execution

Data were analyzed using four categories of models: stability prediction, fitness prediction,

enzyme kinetic parameter prediction, and molecular docking affinity prediction. In total, 20

computational models were employed (5 models per category).

Stability Prediction Models. Five models were used to assess protein stability changes upon

mutation, all using wildtype structures generated by ESMFold. RaSP and ThermoMPNN predict

saturation mutagenesis stability scores across all possible substitutions. FoldX provides overall

protein stability scores from structural energy calculations. DDGun estimates mutation-specific

stability changes ($\Delta\Delta G$) from the wildtype structure and mutation site. Pythia also evaluates

saturation mutagenesis effects using the predicted structure. Together, these models quantify

energetic consequences of amino acid substitutions from a structural perspective.

Fitness Prediction Models. Mutation effects on protein fitness were evaluated using five models

based on sequence and structure representations. GEMME derives fitness scores from multiple

sequence alignments produced via MMseqs2. VESPA predicts saturation mutagenesis fitness

directly from the wildtype sequence. ESM1V estimates site-specific mutation fitness using

transformer-based sequence modeling. SaProt incorporates predicted protein structure and

mutation site information. ProSST integrates wildtype sequence, structure, and mutation

positions to determine mutation-induced functional changes. These models capture evolutionary

constraints and mutation impact on enzyme functionality.

Enzyme Kinetic Parameter Prediction Models. Enzymatic parameters were predicted from

protein sequences and substrate SMILES using five models. UniKP, EITLEM-Kinetics, and

CataPro each predict *kcat*, *Km*, and catalytic efficiency (*kcat*/*Km*). CatPred outputs only *kcat* and

Km, while DLKcat exclusively predicts *kcat*. All models operate without structural preprocessing,

enabling efficient evaluation of catalytic performance from sequence-level inputs.

Enzyme-substrate Binding Affinity Prediction and Docking Tools. Five models were

employed to predict protein–ligand binding affinity and docking conformations. PSICHIC

generates affinity scores using only sequence and SMILES inputs. DynamicBind uses ESMFold-

predicted protein structures and SMILES to produce binding scores and docked complexes.

SMINA performs structure-based docking using ESMFold-derived protein PDBQT files and

ligand structures converted via RDKit and OpenBabel, with binding sites identified by P2Rank.

Boltz-2 predicts affinity and docking complexes using sequence and SMILES representations

alone. DSDP follows a structure-based approach similar to SMINA to generate affinity scores

and ligand poses. These models collectively evaluate molecular recognition across both

sequence-based and structure-based frameworks.

Adjustment of model prediction directionality

Because different predictors are expected to correlate with experimental measurements in

different directions, it is essential to standardize the directionality of the correlations so that

higher (positive) correlation values consistently indicate better predictive performance. To

enable consistent comparison across models, we therefore established the following working

assumptions: a) fitness is assumed to positively correlate with *kcat* and *kcat/Km*, but negatively

with *Km*, except in cases where model outputs follow the opposite trend (e.g., VESPA). Using

these assumptions, we adjusted the sign of each predictor–measurement correlation so that, after

transformation, higher correlation values uniformly represent better performance. The complete

mapping of predictors to expected correlation directions is provided in Table S1, and the

adjusted results are shown in Figure 3.

Metric calculation

Spearman correlation, precision, and size-weighted pooled correlation are computed as in Eqn. 1,

Eqn. 2, and Eqn. 3.

$corr = 1 - \frac{6 \sum d_i^2}{n(n^2-1)}$ (Eqn. 1)

Where d_i= difference between the ranks of each pair of observations; n=number of pairs.

$precision = \frac{TP}{TP+FP}$ (Eqn. 2)

Where TP = True Positives (correctly predicted positive cases); FP = False Positives (incorrectly

predicted positive cases).

$size - weighted\ pooled\ correlation = \ \tanh\left(\frac{\sum(n_i-3)\ tanh^{-1}(\rho_i)}{\sum(n_i-3)}\right)$ (Eqn. 3)

Where n_i and ρ_i the number of mutants and correlation for the i-*th* dataset, respectively.

Wet-lab validation for the PTS mutants

Strains and Medium. *Escherichia coli* DH5α was used for plasmid construction and cultured in

LB medium supplemented with 100 mg/L ampicillin at 37 °C. The *Saccharomyces cerevisiae*

strain yCAN10, previously engineered to enhance the supply of farnesyl pyrophosphate, was

used for PTS expression {Luo, 2019 #1299}. Synthetic complete uracil dropout medium (SC-

Ura; Coolaber, Beijing, China) was used for yeast selection and cultivation. Yeast extract

peptone dextrose (YPD) medium was used for routine yeast culture, and yeast extract peptone

galactose (YPG), in which galactose replaced dextrose, was used for fermentation.

Mutant recommendation. Saturation mutagenesis of the PTS protein sequence was performed,

which were scored and ranked by UniKP (*kcat/Km model*) and ESM-1v—we selected the top 50

mutans recommended by each of these two models. In addition, 50 mutants were randomly

selected as the control group. The mutant information (mutation, sequence, and model prediction

can be found in Table S2) Primers for these mutants were designed by the Primer3 program

{Untergasser, 2012 #1301}.

Plasmids and Strains Construction. The patchoulol synthase gene (GenBank ID: AAS86323.1)

was synthesized by GenScript (Nanjing, China) with codon optimization for yeast expression.

The gene was inserted into plasmid pESC-Ura under the control of the GAL1 promoter and

CYC1 terminator using Gibson assembly to generate pESC-Ura-PTS (pGAL1-PTS-tCYC1

expression cassette). Using this plasmid as a template, mutated PTS fragments were amplified by

PCR with primers designed to introduce the desired mutations (Table S2). The mutated PTS

genes were integrated into the ARS1114a locus of the host strain using CRISPR/Cas9 genome

editing {Reider Apel, 2017 #1300}. Briefly, PTS mutational fragments together with ~1000 bp

upstream and downstream homologous arms (amplified from yCAN10 genomic DNA) and the

Cas9/sgRNA plasmid p426_Cas9_gRNA-ARS1114a (Addgene #87397) were transformed into

the host strain using the lithium acetate method. Transformants were selected on SD-Ura plates

and verified by colony PCR and sequencing. All primer sequences used in this study are listed in

Table S3.

Fermentation of PTS Mutant Strains. Single colonies of mutant strains were inoculated into

96-deep-well plates containing 500 µL YPD per well and cultured at 30 °C and 800 rpm for 18 h

to obtain primary seed cultures. Cultures were then transferred to 24-deep-well plates containing

2 mL YPG per well at a 2% inoculum and incubated under the same conditions. All strains were

cultured in three biological replicates. After 72 h of fermentation, 500 µL of broth was collected

for patchoulol quantification.

Extraction and detection methods. Patchoulol was extracted with 200 µL n-hexane using bead

beating (70 Hz; 90 s on, 30 s off; 10 cycles), followed by centrifugation at 12,000 ×g for 5 min.

The upper organic phase was collected for analysis. Patchoulol was quantified by GC-MS (8890-

7010B, Agilent, USA) equipped with an HP-5 column (30 m × 250 µm × 0.25 µm, Agilent). The

oven temperature program was: 150 °C for 1 min, ramp to 180 °C at 20 °C/min, then to 300 °C

at 80 °C/min and held for 4 min. A 1 µL sample was injected with helium as the carrier gas.

Selected ion monitoring (SIM) was used for quantification with m/z 137.9, 160.9, and 222. The

mutants' patchoulol yield relative to wildtype can be found in Table S2.

Data and code availability

606 Data in this study, including curated subsets, experimental conditions, experimental

607 measurement, and pre-computed predictions, are deposited in our GitHub repository.

608 (https://github.com/zishuozeng/EnzyArena).

Ethical statement

611 Not applicable.

Acknowledgements

614 We would like to thank all researchers who made the data and tools relevant to this study

615 available.

Authorship contribution

618 Z.Z. and X.L. conceived the ideas, analyzed the data, and wrote the manuscript; J.J. collected the

619 data and ran the predictions; R.X. performed the wet-lab experiments; X.L. revised the

620 manuscript.

Funding

622 This project is supported by National Key R&D Program of China (2025YFA0922700),

623 Shenzhen Medical Research Fund (D2301005), Guangdong S&T Program (2024B1111160007),

624 National Natural Science Foundation of China (32570096), Shenzhen Science and Technology

625 Program (KJZD20240903102304006 and ZDSYS20210623091810032), SlAT Distinguished

626 Young Scholars (E4G021).

Declaration of competing interest

629 X.L. has a financial interest in Demetrix and Synceres.

Table 1. Summary of the manually curated datasets.

Dataset	Ref	Enzyme	Substrate	Measurement	No. mutants
Dataset 1	[32]	D-amino acid oxidase	D-alanine	DMS score	100 out of 6396
Dataset 2	[42]	Aliphatic amide hydrolase	Acetamide	DMS score	100 out of 7161
Dataset 3	[42]	Aliphatic amide hydrolase	Isobutyramide	DMS score	100 out of 7161
Dataset 4	[42]	Aliphatic amide hydrolase	Propionamide	DMS score	100 out of 7161
Dataset 5	[43]	Adenylate kinase	Adenosine diphosphate	*kcat*	10
Dataset 6	[43]	Adenylate kinase	Adenosine diphosphate	*kcat*	8
Dataset 7	[43]	Adenylate kinase	Adenosine diphosphate	*kcat*	8
Dataset 8	[43]	Adenylate kinase	Adenosine diphosphate	*kcat*	7
Dataset 9	[43]	Adenylate kinase	Adenosine diphosphate	*kcat*	6
Dataset 10	[43]	Adenylate kinase	Adenosine	*kcat*	6

			diphosphate		
Dataset 11	44	Polyphenol oxidases	Catechol	*kcat*	6
Dataset 12	44	Polyphenol oxidases	Dopamine	*kcat*	6
Dataset 13	44	Polyphenol oxidases	Tyramine	*kcat*	6
Dataset 14	43	Adenylate kinase	Adenosine diphosphate	*Km*	10
Dataset 15	43	Adenylate kinase	Adenosine diphosphate	*Km*	8
Dataset 16	43	Adenylate kinase	Adenosine diphosphate	*Km*	8
Dataset 17	43	Adenylate kinase	Adenosine diphosphate	*Km*	7
Dataset 18	43	Adenylate kinase	Adenosine diphosphate	*Km*	6
Dataset 19	43	Adenylate kinase	Adenosine diphosphate	*Km*	6
Dataset 20	44	Polyphenol oxidases	Catechol	*Km*	6
Dataset 21	44	Polyphenol oxidases	Dopamine	*Km*	6
Dataset 22	44	Polyphenol oxidases	Tyramine	*Km*	6
Dataset 23	44	Polyphenol oxidases	Catechol	*kcat*/*Km*	6
Dataset 24	44	Polyphenol oxidases	Dopamine	*kcat*/*Km*	6
Dataset 25	44	Polyphenol oxidases	Tyramine	*kcat*/*Km*	6

Table 2. Summary of the selected predictors in this study.

Group	Name	Input format	Output format	Support multiple mutations	Key characteristics
Protein-ligand binding affinity prediction	SMINA [13]	Struct. of mutants, substrate	Scores of the input mutants	Yes	Traditional physics-based molecular protein-ligand binding affinity prediction program, open-source
	DynamicBind [14]	Struct. of mutants, substrate	Scores of the input mutants	Yes	Geometric diffusion network
	PSICHIC [15]	Seq. of mutants, substrate	Scores of the input mutants	Yes	Graph neural network
	DSDP [16]	Struct. of mutants, substrate	Scores of the input mutants, post-docking ligand structures	Yes	Combines traditional docking and machine learning
	Boltz-2 [17]	Seq. of mutants, substrate SMILES	Scores of the input mutants, post-docking ligand structures	Yes	AI foundation model for structure and binding affinity prediction
Stability	FoldX [18]	Struct. of	Scores of the input	Yes	Widely used

prediction		mutants	mutants		
	RaSP [19]	Struct. of wildtype	Scores of all saturated mutants	No	Deep learning model based on structural input
	ThermoMPNN [20]	Struct. of wildtype	Scores of all saturated mutants	No	Transfer learning model based on ProteinMPNN
	DDGun [21]	Struct. of wildtype, mutation descriptor	Scores of the input mutants	Yes	Model based on predefined rules derived from sequence, structure, and evolutionary conservation
	Pythia [22]	Struct. of wildtype	Scores of all saturated mutants	No	Self-supervised graph neural network
Zero-shot fitness prediction	GEMME [35]	MSA file	Scores of all saturated mutants	No	Computational model that considers conservation and epistatic effects
	VESPA [45]	A wildtype seq.	Scores of all saturated mutants	No	Transfer learning based on ProtT5, predicts effect vs. neutral
	ESM-1v [4]	A wildtype seq, Mutation descriptor	Scores of input mutants	No	LLM that quantifies benefits/deleteriousness of mutations
	SaProt [6]	Struct. of wildtype, mutation	Scores of input mutants	Yes	LLM with both sequence and structure information

		descriptor			
	ProSST [7]	Struct. of wildtype, wildtype seq,mutation descriptor	Scores of input mutants	Yes	LLM with both sequence and structure information
Kinetic parameter (KP) prediction	DLkcat[8]	Seq. of mutants, substrate SMILES	Scores of input mutants	Yes	N-gram (protein features), graph neural network (substrate features), deep learning (algorithm); predicts *kcat*
	UniKP [9]	Seq. of mutants, substrate	Scores of input mutants	Yes	ProtT5 (protein features), SMILES transformers (substrate features), ExtraTree (algorithm); predicts *kcat*, *Km*, and *kcat*/*Km*
	EITLEM-kinetics [46]	Seq. of mutants, substrate	Scores of input mutants	Yes	ESM-1v (protein features), fingerprints (substrate features), neural network (algorithm) ; predicts *kcat*, *Km*, and *kcat*/*Km*
	CataPro [11]	Seq. of mutants, substrate SMILES	Scores of input mutants	Yes	ProtT5 (protein features), MolT5 + MACCS fingerprints (substrate features); predicts *kcat*, *Km*, and *kcat*/*Km*

	CatPred [12]	Seq. of mutants, substrate SMILES	Scores of input mutants	Yes	ESM2 (protein features), D-MPNN (substrate), deep learning (algorithm); predicts $kcat$, Km, and Ki

Table 3. Model time consumption to run all data in this study.

Category	Model	Data processed	Model run time (h)	Run time for pdb/pdbqt preparation (h)	Total run time (h)
Stability	Pythia	126 wildtype protein pdb files	0.05	1	1.05
	ThermoMPNN		0.17	1	1.17
	DDGun		1.17	1	2.17
	RaSP		5	1	6
	FoldX	2195 protein pdb files	0.83	17	17.83
Kinetic Parameters	DLKcat	2886 protein sequence - substrate pairs	0.08	-	0.08
	UniKP		0.5	-	0.5
	CataPro		0.5	-	0.5
	CatPred		0.5	-	0.5
	EITLEM-kinetics		8	-	8
Fitness	SaProt	126 wildtype protein pdb files	0.33	1	1.33
	ESM1V		2	-	2
	ProSST		1	1	2
	GEMME		2.5	-	2.5
	VESPA		4.33	-	4.33
Binding Affinity	PSICHIC	2886 protein sequence - substrate pairs	0.17	-	0.17
	DSDP		1	30.5	31.5

	SMINA		16	30.5	46.5
	DynamicBind		85	17	102
	Boltz-2		112	-	112

References

(1) Radley, E.; Davidson, J.; Foster, J.; Obexer, R.; Bell, E. L.; Green, A. P. Engineering enzymes for environmental sustainability. *Angewandte Chemie International Edition* **2023**, *62* (52), e202309305.

(2) Katsimpouras, C.; Stephanopoulos, G. Enzymes in biotechnology: Critical platform technologies for bioprocess development. *Current opinion in biotechnology* **2021**, *69*, 91-102.

(3) Markus, B.; C, G. C.; Andreas, K.; Arkadij, K.; Stefan, L.; Gustav, O.; Elina, S.; Radka, S. Accelerating biocatalysis discovery with machine learning: a paradigm shift in enzyme engineering, discovery, and design. *ACS catalysis* **2023**, *13* (21), 14454-14469.

(4) Meier, J.; Rao, R.; Verkuil, R.; Liu, J.; Sercu, T.; Rives, A. Language models enable zero-shot prediction of the effects of mutations on protein function. *Advances in neural information processing systems* **2021**, *34*, 29287-29303.

(5) Elnaggar, A.; Heinzinger, M.; Dallago, C.; Rihawi, G.; Wang, Y.; Jones, L.; Gibbs, T.; Feher, T.; Angerer, C.; Steinegger, M. ProtTrans: towards cracking the language of Life's code through self-supervised deep learning and high performance computing. *arXiv preprint arXiv:2007.06225* **2020**.

(6) Su, J.; Han, C.; Zhou, Y.; Shan, J.; Zhou, X.; Yuan, F. Saprot: Protein language modeling with structure-aware vocabulary. *BioRxiv* **2023**, 2023.2010. 2001.560349.

(7) Li, M.; Tan, Y.; Ma, X.; Zhong, B.; Yu, H.; Zhou, Z.; Ouyang, W.; Zhou, B.; Tan, P.; Hong, L. Prosst: Protein language modeling with quantized structure and disentangled attention. *Advances in Neural Information Processing Systems* **2024**, *37*, 35700-35726.

(8) Li, F.; Yuan, L.; Lu, H.; Li, G.; Chen, Y.; Engqvist, M. K.; Kerkhoven, E. J.; Nielsen, J. Deep learning-based k cat prediction enables improved enzyme-constrained model reconstruction. *Nature Catalysis* **2022**, *5* (8), 662-672.

(9) Yu, H.; Deng, H.; He, J.; Keasling, J. D.; Luo, X. UniKP: a unified framework for the prediction of enzyme kinetic parameters. *Nature communications* **2023**, *14* (1), 8211.

(10) Wang, J.; Yang, Z.; Chen, C.; Yao, G.; Wan, X.; Bao, S.; Ding, J.; Wang, L.; Jiang, H. MPEK: a multitask deep learning framework based on pretrained language models for enzymatic reaction kinetic parameters prediction. *Briefings in Bioinformatics* **2024**, *25* (5), bbae387.

(11) Wang, Z.; Xie, D.; Wu, D.; Luo, X.; Wang, S.; Li, Y.; Yang, Y.; Li, W.; Zheng, L. Robust enzyme discovery and engineering with deep learning using CataPro. *Nature communications* **2025**, *16* (1), 2736.

(12) Boorla, V. S.; Maranas, C. D. CatPred: a comprehensive framework for deep learning in vitro enzyme kinetic parameters. *Nature communications* **2025**, *16* (1), 2072.

(13) Koes, D. R.; Baumgartner, M. P.; Camacho, C. J. Lessons learned in empirical scoring with smina from the CSAR 2011 benchmarking exercise. *Journal of chemical information and modeling* **2013**, *53* (8), 1893-1904.

(14) Lu, W.; Zhang, J.; Huang, W.; Zhang, Z.; Jia, X.; Wang, Z.; Shi, L.; Li, C.; Wolynes, P. G.; Zheng, S. DynamicBind: predicting ligand-specific protein-ligand complex structure with a deep equivariant generative model. *Nature Communications* **2024**, *15* (1), 1071.

(15) Koh, H. Y.; Nguyen, A. T.; Pan, S.; May, L. T.; Webb, G. I. Physicochemical graph neural network for learning protein–ligand interaction fingerprints from sequence data. *Nature Machine Intelligence* **2024**, *6* (6), 673-687.

(16) Huang, Y.; Zhang, H.; Jiang, S.; Yue, D.; Lin, X.; Zhang, J.; Gao, Y. Q. Dsdp: A blind docking strategy accelerated by gpus. *Journal of chemical information and modeling* **2023**, *63* (14), 4355-4363.

(17) Passaro, S.; Corso, G.; Wohlwend, J.; Reveiz, M.; Thaler, S.; Somnath, V. R.; Getz, N.; Portnoi, T.; Roy, J.; Stark, H. Boltz-2: Towards accurate and efficient binding affinity prediction. *BioRxiv* **2025**.

(18) Delgado, J.; Radusky, L. G.; Cianferoni, D.; Serrano, L. FoldX 5.0: working with RNA, small molecules and a new graphical interface. *Bioinformatics* **2019**, *35* (20), 4168-4169.

(19) Blaabjerg, L. M.; Kassem, M. M.; Good, L. L.; Jonsson, N.; Cagiada, M.; Johansson, K. E.; Boomsma, W.; Stein, A.; Lindorff-Larsen, K. Rapid protein stability prediction using deep learning representations. *Elife* **2023**, *12*, e82593.

(20) Dieckhaus, H.; Brocidiacono, M.; Randolph, N. Z.; Kuhlman, B. Transfer learning to leverage larger datasets for improved prediction of protein stability changes. *Proceedings of the national academy of sciences* **2024**, *121* (6), e2314853121.

(21) Montanucci, L.; Capriotti, E.; Frank, Y.; Ben-Tal, N.; Fariselli, P. DDGun: an untrained method for the prediction of protein stability changes upon single and multiple point variations. *BMC bioinformatics* **2019**, *20*, 1-10.

(22) Sun, J.; Zhu, T.; Cui, Y.; Wu, B. Structure-based self-supervised learning enables ultrafast protein stability prediction upon mutation. *The Innovation* **2025**, *6* (1).

(23) Cui, Y.; Sun, J.; Wu, B. Computational enzyme redesign: large jumps in function. *Trends in Chemistry* **2022**, *4* (5), 409-419.

(24) Mangul, S.; Martin, L. S.; Hill, B. L.; Lam, A. K.-M.; Distler, M. G.; Zelikovsky, A.; Eskin, E.; Flint, J. Systematic benchmarking of omics computational tools. *Nature communications* **2019**, *10* (1), 1393. Camacho, D. M.; Collins, K. M.; Powers, R. K.; Costello, J. C.; Collins, J. J. Next-generation machine learning for biological networks. *Cell* **2018**, *173* (7), 1581-1592. Pleiss, J. r. Modeling Enzyme Kinetics: Current Challenges and Future Perspectives for Biocatalysis. *Biochemistry* **2024**, *63* (20), 2533-2541.

(25) Chang, A.; Jeske, L.; Ulbrich, S.; Hofmann, J.; Koblitz, J.; Schomburg, I.; Neumann-Schaal, M.; Jahn, D.; Schomburg, D. BRENDA, the ELIXIR core data resource in 2021: new developments and updates. *Nucleic acids research* **2021**, *49* (D1), D498-D508.

(26) Wittig, U.; Rey, M.; Weidemann, A.; Kania, R.; Müller, W. SABIO-RK: an updated resource for manually curated biochemical reaction kinetics. *Nucleic acids research* **2018**, *46* (D1), D656-D660.

(27) Kapoor, S.; Narayanan, A. Leakage and the reproducibility crisis in machine-learning-based science. *Patterns* **2023**, *4* (9).

(28) Bernett, J.; Blumenthal, D. B.; Grimm, D. G.; Haselbeck, F.; Joeres, R.; Kalinina, O. V.; List, M. Guiding questions to avoid data leakage in biological machine learning applications. *Nature Methods* **2024**, *21* (8), 1444-1453.

(29) Graber, D.; Stockinger, P.; Meyer, F.; Mishra, S.; Horn, C.; Buller, R. Resolving data bias improves generalization in binding affinity prediction. *Nature Machine Intelligence* **2025**, 1-13.

(30) Notin, P.; Kollasch, A.; Ritter, D.; Van Niekerk, L.; Paul, S.; Spinner, H.; Rollins, N.; Shaw, A.; Orenbuch, R.; Weitzman, R. Proteingym: Large-scale benchmarks for protein fitness prediction and design. *Advances in Neural Information Processing Systems* **2023**, *36*, 64331-64379.

(31) Siddiqui, K. S. Defying the activity–stability trade-off in enzymes: taking advantage of entropy to enhance activity and thermostability. *Critical reviews in biotechnology* **2017**, *37* (3), 309-322.

(32) Vanella, R.; Küng, C.; Schoepfer, A. A.; Doffini, V.; Ren, J.; Nash, M. A. Understanding activity-stability tradeoffs in biocatalysts by enzyme proximity sequencing. *Nature Communications* **2024**, *15* (1), 1807.

(33) Zheng, N.; Cai, Y.; Zhang, Z.; Zhou, H.; Deng, Y.; Du, S.; Tu, M.; Fang, W.; Xia, X. Tailoring industrial enzymes for thermostability and activity evolution by the machine learning-based iCASE strategy. *Nature Communications* **2025**, *16* (1), 604. Jiang, F.; Li, M.; Dong, J.; Yu, Y.; Sun, X.; Wu, B.; Huang, J.; Kang, L.; Pei, Y.; Zhang, L. A general temperature-guided language model to design proteins of enhanced stability and activity. *Science Advances* **2024**, *10* (48), eadr2641. Teufl, M.; Zajc, C. U.; Traxlmayr, M. W. Engineering strategies to overcome the stability–function trade-off in proteins. *ACS Synthetic Biology* **2022**, *11* (3), 1030-1039.

(34) Yu, Y.; Rué Casamajo, A.; Finnigan, W.; Schnepel, C.; Barker, R.; Morrill, C.; Heath, R. S.; De Maria, L.; Turner, N. J.; Scrutton, N. S. Structure-based design of small imine reductase panels for target substrates. *ACS catalysis* **2023**, *13* (18), 12310-12321. Qian, S.; Clomburg, J. M.; Gonzalez, R. Engineering Escherichia coli as a platform for the in vivo synthesis of prenylated aromatics. *Biotechnology and Bioengineering* **2019**, *116* (5), 1116-1127. Mai, P.; Zocher, G.; Stehle, T.; Li, S.-M. Structure-based protein engineering enables prenyl donor switching of a fungal aromatic prenyltransferase. *Organic & Biomolecular Chemistry* **2018**, *16* (40), 7461-7469. Hua, L.; Qianqian, B.; Jianfeng, Z.; Yinbiao, X.; Shengyu, Y.; Weishi, X.; Yang, S.; Yupeng, L. Directed evolution engineering to improve activity of glucose dehydrogenase by increasing pocket hydrophobicity. *Frontiers in Microbiology* **2022**, *13*, 1044226.

(35) Laine, E.; Karami, Y.; Carbone, A. GEMME: a simple and fast global epistatic model predicting mutational effects. *Molecular biology and evolution* **2019**, *36* (11), 2604-2619.

(36) Zhang, Q.; Chen, W.; Qin, M.; Wang, Y.; Pu, Z.; Ding, K.; Liu, Y.; Zhang, Q.; Li, D.; Li, X. Integrating protein language models and automatic biofoundry for enhanced protein evolution. *Nature Communications* **2025**, *16* (1), 1553.

(37) Cornish-Bowden, A. *Fundamentals of enzyme kinetics*; John Wiley & Sons, 2013.

(38) Im, W.; Lee, M. S.; Brooks III, C. L. Generalized born model with a simple smoothing function. *Journal of computational chemistry* **2003**, *24* (14), 1691-1702.

(39) Dieckhaus, H.; Kuhlman, B. Protein stability models fail to capture epistatic interactions of double point mutations. *Protein Science* **2025**, *34* (1), e70003.

(40) James, G.; Witten, D.; Hastie, T.; Tibshirani, R. *An introduction to statistical learning*; Springer, 2013.

(41) Fisher, R. A. On the" probable error" of a coefficient of correlation deduced from a small sample. *Metron* **1921**, *1*, 3-32.

(42) Wrenbeck, E. E.; Azouz, L. R.; Whitehead, T. A. Single-mutation fitness landscapes for an enzyme on multiple substrates reveal specificity is globally encoded. *Nature communications* **2017**, *8* (1), 15695.

(43) Muir, D. F.; Asper, G. P.; Notin, P.; Posner, J. A.; Marks, D. S.; Keiser, M. J.; Pinney, M. M. Evolutionary-scale enzymology enables exploration of a rugged catalytic landscape. *Science* **2025**, *388* (6752), eadu1058.

(44) Luo, S.; Hou, Y.; Hu, S.-Q. Enhancement of preference, catalytic activity and thermostability of polyphenol oxidase from Rosa Chinensis by semi-rational engineering. *Molecular Catalysis* **2024**, *559*, 114059.

(45) Marquet, C.; Heinzinger, M.; Olenyi, T.; Dallago, C.; Erckert, K.; Bernhofer, M.; Nechaev, D.; Rost, B. Embeddings from protein language models predict conservation and variant effects. *Human genetics* **2022**, *141* (10), 1629-1647.

(46) Shen, X.; Cui, Z.; Long, J.; Zhang, S.; Chen, B.; Tan, T. EITLEM-Kinetics: A deep-learning framework for kinetic parameter prediction of mutant enzymes. *Chem Catalysis* **2024**, *4* (9).