Alignment-Free Microhaplotype Genotyping for GT-seq (Genotyping-in-Thousands by Sequencing) Using a Diploid Abundance Model

Nathan R Campbell[1], Amanda R Campbell[1], Shannon K Blair[2], Amanda J Finger[2]

[1]GTseek LLC, Twin Falls, ID, USA

[2]University of California – Davis, Davis, CA, USA

Abstract

GT-seq (Genotyping-in-Thousands by Sequencing) is widely used for high-throughput amplicon genotyping, but most analytical pipelines focus on single SNPs or rely on alignment-based variant calling. Here we present an alignment-free approach for microhaplotype genotyping that leverages the high read depth and low error rates typical of paired-end Illumina and Element sequencing. The pipeline first identifies primer-bounded reads and resolves paired-end sequences into complete amplicon sequences. Within each sample and locus, unique sequences are ranked by read abundance and the top one or two sequences are retained as candidate diploid alleles. These alleles are aggregated across samples to construct a catalog of unique haplotypes for each locus. In a second pass, reads are assigned to catalog haplotypes by exact sequence matching to produce diploid genotypes. Finally, catalog haplotype sequences are positionally compared to identify phased SNP and collapsed indel variation, generating compact microhaplotype representations suitable for population genetic analysis. This approach enables robust, alignment-free microhaplotype inference directly from high-depth amplicon sequencing data.

Introduction

Targeted amplicon sequencing has become a widely adopted approach for high-throughput genotyping in ecological, conservation, and breeding studies. Among these methods, Genotyping-in-Thousands by sequencing (GT-seq) has emerged as an efficient and cost-effective strategy for

genotyping large numbers of individuals at hundreds of loci simultaneously (Campbell et al. 2015).

GT-seq uses highly multiplexed PCR amplification of targeted genomic regions followed by next-

generation sequencing, allowing thousands of individuals to be genotyped in a single sequencing

run. The method has been widely applied in studies of population structure, mixed-stock analysis,

hybridization, and genetic monitoring of natural populations.

Since its introduction, GT-seq panels have been developed for a broad range of species and research

applications. The method is particularly useful in systems where large numbers of individuals must

be genotyped across moderately sized marker panels. For example, GT-seq panels have been

implemented for genetic monitoring and population structure analyses in wildlife and fisheries

systems where large sample sizes are required to achieve sufficient statistical power (Schmidt et al.

2020; Hayward et al. 2022). Because the method relies on targeted amplification rather than

genome-wide sequencing, GT-seq provides a scalable and cost-effective alternative for studies

requiring genotyping of thousands of individuals.

An important application of GT-seq and other targeted sequencing methods is parentage and kinship

analysis. High-throughput SNP panels generated using GT-seq have been used to assign parentage,

reconstruct pedigrees, and estimate relatedness in natural populations (Campbell et al. 2015;

Hargrove et al. 2021; Schmidt et al. 2020). The ability to genotype large numbers of individuals at

relatively low cost makes GT-seq particularly well suited for kinship-based studies in species with

large population sizes or complex breeding systems.

Most analytical pipelines developed for GT-seq data treat each locus as a single SNP marker or rely

on alignment-based variant calling approaches in which sequencing reads are mapped to a reference

prior to variant discovery (Campbell et al. 2015; Baetscher et al. 2018). While effective, these

approaches do not fully exploit the structure of targeted amplicon sequencing data. Because each

amplicon typically spans a short genomic region, multiple polymorphic sites may occur within the

same amplicon and can be observed simultaneously on individual sequencing reads. These

combinations of linked polymorphisms form haplotypes that may contain substantially more

information than individual SNP markers.

Traditional haplotype inference approaches often rely on statistical phasing methods that reconstruct

haplotypes from genotype data (Browning and Browning 2011). In contrast, targeted amplicon

sequencing frequently produces reads that span the entire amplified region, allowing haplotypes to

be observed directly from sequencing reads without statistical inference. In such cases, alignment-

based SNP pipelines introduce unnecessary analytical complexity by first reducing reads to

independent SNP calls and subsequently reconstructing haplotypes from these variants.

Microhaplotypes, defined as short genomic regions containing two or more closely spaced

polymorphisms observed on the same DNA fragment, have emerged as powerful genetic markers

for applications including ancestry inference, individual identification, and kinship analysis (Kidd et

al. 2014; Pakstis et al. 2021). Because multiple SNPs are observed together on the same sequencing

read, microhaplotypes often produce multi-allelic markers with higher heterozygosity and greater

discriminatory power than single SNP loci.

Several studies have demonstrated that microhaplotypes can substantially improve the statistical

power of relatedness analyses. Because each locus may produce multiple haplotype alleles rather

than two SNP states, microhaplotypes increase the effective information content of genetic markers

and reduce false-positive rates in kinship inference (Anderson et al. 2018; Kidd et al. 2014; Pakstis

et al. 2021). Comparative studies have shown that microhaplotype marker panels can outperform

equivalent SNP panels in distinguishing closely related individuals and resolving complex pedigree

relationships (Baetscher et al. 2018; Tomas et al. 2024).

Targeted amplicon sequencing approaches such as GT-seq are therefore particularly well suited for

microhaplotype genotyping. Sequencing reads frequently span the entire amplified region, allowing

haplotypes to be reconstructed directly from sequencing reads rather than inferred statistically from

independent SNP calls. Furthermore, the high sequencing depth typical of GT-seq experiments

provides a strong signal for distinguishing true allele sequences from sequencing errors based on

read abundance.

Here we describe an alignment-free analytical framework for microhaplotype genotyping from GT-

seq amplicon sequencing data. The method resolves paired-end reads into primer-bounded amplicon

sequences, identifies candidate allele sequences within each sample using a diploid abundance

model, and constructs a catalog of unique haplotypes across all samples. In a second pass,

sequencing reads are assigned to catalog haplotypes by exact sequence matching to produce diploid

genotype calls. Catalog haplotypes are then positionally compared to identify polymorphic sites and

generate phased microhaplotype representations suitable for downstream population genetic and

kinship analyses. Because many GT-seq amplicon panels already include loci that span multiple

polymorphic sites, existing GT-seq panels may be analyzed using this pipeline without modification

to laboratory protocols.

Materials and Methods

The analysis described here is implemented in a Python-based software script developed for

processing paired-end amplicon sequencing data generated by GT-seq panels. The script accepts

paired-end FASTQ files and a table of primer sequences defining the targeted loci. The software

performs four primary steps: (1) resolution of paired-end reads into primer-bounded amplicon

sequences, (2) identification of candidate allele sequences and construction of a locus-specific allele

catalog, (3) genotype inference using an abundance-based diploid model, and (4) extraction of

phased microhaplotype representations from catalog haplotypes. The implementation is designed to

operate directly on high-depth amplicon sequencing reads without requiring read alignment to a

reference or use other conventional variant-calling pipelines. The software is designed to operate

on standard paired-end FASTQ files such as those produced by Illumina or Element sequencing

platforms.

GT-seq Library Preparation and Sequencing

Genomic DNA samples from delta smelt (*Hypomesus transpacificus*) were genotyped using a GT-

seq amplicon sequencing panel consisting of 410 targeted loci. The panel included loci selected

from prior marker discovery efforts, including candidate microhaplotypes identified before panel

development. GT-seq library preparation followed the general protocol described by Campbell et

al. (2015), in which locus-specific primer pairs are multiplexed in a single PCR. However, the

indexing and normalization steps were performed using Nate's Plates normalization and tagging kits

(GTseek LLC, Twin Falls, Idaho, USA). The pooled GT-seq library was sequenced using an

Element AVITI sequencing instrument at the University of Minnesota Genomics Center (UMGC).

Sequencing was performed using paired-end (PE100) chemistry, producing paired FASTQ files for

each individual sample.

Ethics Statement

All fish sampling and handling were conducted by the Fish Conservation and Culture Laboratory

(FCCL) in accordance with institutional and governmental guidelines. Fin clip samples were

collected under approved animal care and use protocols (IACUC protocol number 23041).

Example Dataset

To demonstrate the performance of the alignment-free microhaplotype pipeline, a subset of

sequencing data from this GT-seq panel was used as an example dataset. The dataset consists of

paired-end (PE100) FASTQ files from 96 delta smelt (*Hypomesus transpacificus*) individuals

prepared with the 410-locus GT-seq panel. Delta smelt is a diploid species, making it appropriate

for evaluation under the diploid abundance model implemented here. To reduce file size while

preserving locus representation and genotype structure, sequencing reads were randomly

subsampled to 150,000 read pairs per individual. The resulting dataset provides sufficient

sequencing depth to demonstrate allele discovery, catalog construction, and genotype inference

using the alignment-free microhaplotype pipeline.

The example dataset is publicly available at Zenodo: https://doi.org/10.5281/zenodo.19069551

Primer-Bounded Paired-End Read Resolution

GT-seq libraries consist of PCR amplicons generated from locus-specific primer pairs and

sequenced using paired-end short-read platforms. Because each locus is defined by known primer

sequences, these primers provide natural anchors for identifying and reconstructing the targeted

amplicon sequences.

The analysis pipeline scans paired-end FASTQ files to identify reads beginning with a forward

primer sequence corresponding to a defined locus. Candidate reads are then evaluated using their

paired read to confirm the presence of the corresponding reverse primer sequence. Only read pairs

containing the expected primer combination are retained for downstream analysis.

For validated read pairs, the full amplicon sequence is reconstructed by merging the paired reads. In

cases where the amplicon length is shorter than the sequencing read length, the entire amplicon may

be contained within the first read. For longer amplicons, the overlapping regions of the paired reads

are identified and merged using a fast ungapped overlap algorithm, allowing reconstruction of the

full amplicon sequence.

All reconstructed sequences are normalized to a single orientation beginning with the forward

primer and ending with the reverse complement of the reverse primer. The resulting primer-bounded

amplicon sequences are written to locus-specific FASTQ files and represent the fundamental unit of

analysis for subsequent allele discovery and genotyping.

Allele Discovery and Catalog Construction

Allele discovery is performed using the primer-bounded amplicon sequences obtained from the read

resolution stage. For each sample and locus, unique amplicon sequences are identified and their

read counts tabulated. Because GT-seq data typically exhibit very high read depth per locus and

Illumina and Element sequencers produce high-quality reads with low error rates, true allelic

sequences occur at substantially higher frequencies than sequencing errors. Within each sample and

locus, unique sequences are therefore ranked by read abundance. Under a diploid model, at most

two alleles are expected per locus in each individual. Accordingly, the two most abundant sequences

are retained as candidate alleles. Additional filtering is applied based on allele abundance ratios.

For example, when the most abundant sequence constitutes the vast majority of reads at a locus, the

locus is classified as homozygous and only the dominant sequence is retained as the candidate

allele. When two sequences occur at substantial frequencies, both are retained as candidate alleles

representing a heterozygous genotype. Once all candidate alleles have been identified across all

samples, the sequences are aggregated to construct a catalog of unique haplotypes for each locus.

Each distinct amplicon sequence is assigned a unique allele identifier. The resulting catalog

represents the set of observed haplotypes across the dataset and serves as the reference for genotype

calling in the second pass of the analysis.

Genotype Inference Using a Diploid Abundance Model

Following construction of the allele catalog, the primer-bounded amplicon sequences are reanalyzed

in a second pass to assign reads to catalog haplotypes. Each resolved sequence is compared against

the allele catalog for the corresponding locus using exact sequence matching.

For each sample and locus, reads matching each catalog allele are counted. The two alleles with the

highest read counts are retained as the candidate genotype for that sample. Genotype classification

is then determined using the relative abundance of the second-most frequent allele.

Specifically, genotype classification is based on the proportion of reads corresponding to the second

most abundant allele (A2). Samples with a second-allele proportion below a defined threshold

(default = 10%) are classified as homozygous, whereas samples with substantial representation of

two alleles (25% – 50%) are classified as heterozygous. Loci with insufficient read depth or

ambiguous allele ratios are classified as low confidence or no-call. This abundance-based approach

leverages the high sequencing depth typical of GT-seq assays to distinguish true allelic variation

from sequencing noise.

Microhaplotype Extraction and Phased SNP Representation

The allele catalog generated in the previous step consists of complete amplicon sequences

representing observed haplotypes for each locus. Catalog haplotypes are positionally compared to

identify polymorphic sites, allowing phased SNP and indel variation to be extracted. Because each

allele sequence represents a contiguous DNA fragment observed in sequencing reads, the relative

phase of polymorphisms within the locus is inherently preserved. Consequently, the resulting

haplotypes represent phased combinations of SNPs and indels within each amplicon.

For each locus, the polymorphic sites are extracted from the catalog haplotypes to generate phased

SNP representations of each allele. These phased haplotypes constitute microhaplotypes, defined as

short genomic regions containing multiple linked polymorphisms that can be observed within a

single sequencing read or reconstructed amplicon.

Microhaplotype genotypes are therefore represented as combinations of phased allele sequences

rather than individual unlinked SNP calls. This representation captures the joint information from

multiple polymorphic sites within each amplicon and can substantially increase the information

content of loci used for kinship inference, parentage analysis, and population genetic applications.

Software Implementation

The analysis workflow described above is implemented in the Python script

gtseq_microhap_catalog_and_call.py, available through the GTseq GitHub repository:

https://github.com/GTseq/gtseq_microhap

The software accepts paired-end FASTQ files and a table of locus-specific primer sequences as

input and performs read resolution, allele catalog construction, genotype inference, and

microhaplotype extraction in a single pipeline. The implementation is designed to operate directly

on high-depth targeted amplicon sequencing data generated by GT-seq assays without requiring

reference alignment or conventional variant-calling workflows.

Results

Sequencing Summary and Read Resolution Performance

The delta smelt demonstration dataset consisted of 96 individuals prepared using a 410-locus GT-

seq panel. Across all samples, the sequencing run produced 234,935,633 raw read pairs,

corresponding to an average of 2,447,246 raw read pairs per sample. Application of the primer-

bounded read resolution step retained 164,209,863 primer-bounded read pairs, corresponding to an

average of 1,710,519 primer-bounded read pairs per sample. Overall, 69.9% of raw read pairs were

retained as primer-bounded reads suitable for downstream allele catalog construction and genotype

inference. Among individual samples, raw read counts ranged from 1,255,265 to 3,270,346 read

pairs, while primer-bounded read counts ranged from 166,594 to 2,602,617 read pairs. Most

samples exhibited consistently high recovery of primer-bounded reads, although a small number of

lower-performing samples were observed.

Public Example Dataset

To facilitate software testing and reproducibility, a trimmed example dataset was generated from the

delta smelt sequencing run and deposited at Zenodo. This public dataset consists of paired-end

FASTQ files subsampled to 150,000 read pairs per individual, together with the primer definition

file required to run the pipeline. The example dataset is available at:

https://doi.org/10.5281/zenodo.19069551

Example Locus Demonstrating Microhaplotype Genotyping Model

To illustrate the method, locus NC_061065.1_5347094 was examined in detail. This locus

contained multiple polymorphic positions, including both SNPs and a short indel variant. Because

the allele sequences span the full amplicon, the phase of these linked polymorphisms was preserved

directly in the catalog haplotypes allowing generation of phased SNP genotypes.

Alignment-Free Microhaplotype Inference

Following read resolution, primer-bounded sequences were grouped by locus and unique amplicon

sequences were ranked by read abundance within each sample. These candidate alleles were

aggregated across samples to construct a catalog of observed haplotypes for each locus (Figure 3).

In the second pass of the resolved FASTQ files, primer-bounded reads were assigned to catalog

haplotypes by exact sequence matching, allowing diploid genotype inference based on allele

abundance (Figure 4A).

This alignment-free framework recovered phased haplotypes directly from GT-seq amplicon

sequences without requiring read alignment or conventional variant calling (Figure 1). Because GT-

seq amplicons typically span the full region containing the targeted polymorphisms, haplotype

sequences could be reconstructed directly from sequencing reads following exact match genotyping

(Figure 1; Figure 5).

Diploid Genotype Inference Using the A2 Metric

Diploid genotypes were inferred from allele-specific read counts using the relative abundance of the

second most frequent allele (A2). For each sample and locus, reads matching catalog haplotypes

were counted and ranked by abundance. The two most abundant alleles were retained as the

candidate diploid genotype, and the proportion of reads corresponding to the second-most abundant

allele was used to distinguish heterozygous and homozygous genotypes.

Examples from locus NC_061065.1_5347094 illustrate this approach (Figure 4A). In heterozygous

individuals, two haplotypes were observed at similar frequencies, typically with A2 proportions

near 0.5. In contrast, homozygous individuals exhibited extremely low A2 values, reflecting the

presence of only a single dominant haplotype at the locus. This abundance-based model provided a

simple and robust method for genotype inference using high-depth amplicon sequencing data.

Across the dataset, locus-level genotype summaries revealed the distribution of haplotypes and

diploid genotypes across samples (Figure 4B). These locus dashboards provide a compact

representation of allele frequencies and genotype composition for each microhaplotype locus.

Microhaplotype Extraction and Phased SNP Representation

Catalog haplotypes were positionally compared within each locus to identify polymorphic sites,

including both single nucleotide polymorphisms and short insertion–deletion variants (indels).

Because each haplotype sequence represents a contiguous DNA fragment derived from a single

primer-bounded amplicon, the relative phase of polymorphisms within the locus was preserved

directly in the catalog haplotypes.

Locus NC_061065.1_5347094 contained multiple polymorphic positions that could be resolved into

distinct haplotype sequences (Figure 5). These haplotypes represent phased combinations of SNPs

and indels within the amplicon and therefore constitute microhaplotypes. Diploid genotypes at this

locus were represented as pairs of haplotype sequences, producing phased microhaplotype

genotypes suitable for downstream population genetic and kinship analyses.

Because haplotypes are reconstructed directly from sequencing reads rather than inferred from

independent SNP calls, the resulting microhaplotypes retain the full linkage information contained

within each amplicon. This representation captures the joint information from multiple polymorphic

sites and can substantially increase the effective information content of loci compared to single SNP

markers.

Discussion

Alignment-Free Microhaplotype Inference from Amplicon Sequencing Data

Targeted amplicon sequencing approaches such as GT-seq generate sequencing reads that frequently

span the entire amplified region, allowing combinations of linked polymorphisms to be observed

directly on individual DNA molecules. Conventional analytical pipelines typically process these

data using alignment-based variant calling approaches in which sequencing reads are mapped to a

reference genome and polymorphisms are identified as independent SNP markers. While effective

for many applications, these workflows do not fully exploit the structure of targeted amplicon data

where complete haplotypes can often be reconstructed directly from sequencing reads.

Several analytical tools have been developed to extract microhaplotypes from massively parallel

sequencing data. Many of these methods rely on alignment-based workflows in which sequencing

reads are first mapped to a reference genome and haplotypes are subsequently reconstructed from

combinations of SNP calls. For example, the microhaplot software package identifies

microhaplotypes from aligned sequencing reads and provides tools for analyzing haplotype

structure across targeted loci (Baetscher et al. 2018). While these approaches are effective when

reference genomes are available and read alignment is reliable, they treat haplotypes as a derived

product of variant calls rather than the primary signal present in sequencing reads.

The framework described here takes the opposite approach by inferring haplotypes directly from

sequencing reads prior to identifying SNP variation. Because GT-seq amplicons frequently span the

full targeted region, haplotypes can be reconstructed directly from primer-bounded reads without

reference alignment or statistical phasing. In this workflow, polymorphic sites are identified only

after the haplotype catalog has been constructed. This inversion of the traditional analysis order—

inferring haplotypes first and extracting SNP variation second—provides a simplified and

computationally efficient strategy for microhaplotype genotyping from high-depth amplicon

sequencing data.

Diploid Abundance Model and Catalog Construction

Central to this workflow is the diploid abundance model used to infer candidate alleles and

construct locus-specific haplotype catalogs. Because GT-seq assays typically generate very high

read depth per locus and Illumina and Element sequencing platforms produce predominantly high-

quality reads, true allelic sequences are expected to occur at substantially higher frequencies than

sequencing artifacts. Within each sample and locus, unique amplicon sequences are therefore

ranked by read abundance and the two most abundant sequences are retained as candidate diploid

alleles.

Aggregating these candidate alleles across samples produces a catalog of unique haplotypes for

each locus that can subsequently be used for genotype inference. This abundance-based strategy

provides a simple and robust approach for distinguishing true allelic sequences from sequencing

artifacts in high-depth amplicon datasets.

Catalog construction assumes that each locus represents a single genomic target in a diploid

organism. When multiple genomic regions are amplified by the same primer pair—such as

duplicated loci or non-specific amplification events—more than two high-frequency sequences may

be observed within a single sample. Under these conditions the diploid abundance model cannot

unambiguously determine which sequences represent the true alleles. Rather than attempting to

infer genotypes under ambiguous conditions, the algorithm intentionally fails to produce genotype

calls for such loci, resulting in empty output for the affected marker. In practice this behavior serves

as a useful diagnostic indicator of problematic loci, highlighting primer sets that amplify multiple

genomic targets or duplicated regions of the genome. In practice, such loci are identified and

excluded during panel design through in silico specificity screening and empirical optimization (as

performed during development of the example dataset used here). However, application of this

pipeline to existing GT-seq panels may result in missing data for some loci.

Because the current implementation assumes a maximum of two alleles per locus per individual, the

method is most appropriate for single-copy loci in diploid organisms. Nevertheless, the underlying

framework could be extended to accommodate more complex genotype models. For example, a

modified implementation could retain the top four sequences within each sample and apply

abundance-based genotype inference appropriate for tetraploid organisms.

Microhaplotypes as Highly Informative Genetic Markers

Microhaplotypes have emerged as powerful genetic markers because they capture multiple linked

polymorphisms within a single short genomic region. Unlike individual SNP markers, which are

typically bi-allelic, microhaplotypes often produce multi-allelic loci with substantially higher

heterozygosity and information content (Kidd et al. 2014; Pakstis et al. 2021).

Because microhaplotypes represent phased combinations of SNPs and indels observed on the same

DNA fragment, each locus can contribute considerably more information to relatedness analyses

than a single SNP marker. Comparative studies have demonstrated that microhaplotype panels can

outperform SNP panels when distinguishing closely related individuals or resolving complex

pedigree relationships (Anderson et al. 2018; Tomas et al. 2024). The multi-allelic nature of

microhaplotypes increases their discriminatory power and reduces the number of loci required to

achieve a given level of statistical confidence in kinship inference.

Targeted amplicon sequencing methods such as GT-seq are particularly well suited for

microhaplotype genotyping because sequencing reads frequently span the entire amplified region.

Consequently, many existing GT-seq panels already contain loci that can function as

microhaplotypes without modification to laboratory protocols.

Implications and Applications

The alignment-free microhaplotype pipeline described here provides a practical framework for

extracting microhaplotypes directly from GT-seq amplicon sequencing data. By operating directly

on primer-bounded amplicon sequences, the method avoids the need for reference alignment and

variant-calling pipelines while preserving the phased structure of polymorphisms within each locus.

Because many ecological and conservation genomics studies already rely on GT-seq panels for

genotyping large numbers of individuals, the ability to extract microhaplotypes from these datasets

has the potential to substantially increase the information content of existing marker panels without

requiring changes to laboratory protocols. In this sense, the alignment-free framework described

here provides a practical path for converting existing SNP-based GT-seq panels into multi-allelic

microhaplotype marker systems.

More broadly, this work demonstrates how haplotype-centric analytical approaches can simplify the

interpretation of targeted sequencing data. By treating haplotypes as the primary signal present in

amplicon reads and identifying polymorphic sites only after haplotypes have been inferred, the

alignment-free framework provides an efficient strategy for microhaplotype genotyping from high-

depth amplicon sequencing experiments.

Software Availability

The analysis pipeline described in this study is implemented as a Python script available through the

GTseq GitHub repository:

https://github.com/GTseq/gtseq_microhap

The repository contains the source code, documentation, and example usage instructions for

performing alignment-free microhaplotype genotyping from GT-seq paired-end sequencing data.

Data Availability

All sequencing data and example datasets are available at Zenodo:

https://doi.org/10.5281/zenodo.19069551. The analysis pipeline is available at

https://github.com/GTseq/gtseq_microhap.

Author Contributions

Identification and selection of microhaplotype markers for kinship analysis in delta smelt were

carried out by SKB and AJF. The analytical framework, software pipeline, and manuscript were

developed by NRC. Software testing and manuscript review and revision were contributed by

ARC, SKB, and AJF. GT-seq library preparation and laboratory operations were performed and

overseen by ARC.

References

Anderson, E. C., et al. (2018). Microhaplotypes provide increased power from short-read DNA

sequences for relationship inference. *Molecular Ecology Resources*, 18, 296–305.

Baetscher, D. S., Clemento, A. J., Ng, T. C., Anderson, E. C., & Garza, J. C. (2018). Microhaplot:

An R package for the analysis of microhaplotype data. *Molecular Ecology Resources*, 18, 1397–

1407.

Browning, S. R., & Browning, B. L. (2011). Haplotype phasing: Existing methods and future

directions. *Nature Reviews Genetics*, 12, 703–714.

Campbell, N. R., Harmon, S. A., & Narum, S. R. (2015). Genotyping-in-Thousands by sequencing

(GT-seq): A cost-effective SNP genotyping method based on custom amplicon sequencing.

Molecular Ecology Resources, 15, 855–867.

Hargrove, J. S., et al. (2021). Parentage-based tagging improves escapement estimates for ESA-

listed adult Chinook Salmon and steelhead in the Snake River basin. *Canadian Journal of Fisheries*

and Aquatic Sciences, 78, 349–360.

Hayward, K. M., et al. (2022). Development of a GT-seq panel for genetic monitoring of polar

bears (*Ursus maritimus*). *Ecology and Evolution*, 12, e8892.

Kidd, K. K., Pakstis, A. J., Speed, W. C., et al. (2014). Microhaplotype loci are a powerful new

type of genetic marker for forensic identification and relatedness inference. *Human Genetics*, 133,

143–155.

Pakstis, A. J., Speed, W. C., Fang, R., et al. (2021). Microhaplotypes: A new type of genetic marker

for forensic science. *Human Genetics*, 140, 159–170.

Schmidt, D. A., Campbell, N. R., Govindarajulu, P., Larsen, K. W., & Narum, S. R. (2020).

Development of a GT-seq panel for parentage and population genetic analyses. *Molecular Ecology*

Resources, 20, 1486–1499.

Tomas, C., Phillips, C., et al. (2024). Evaluation of microhaplotype markers for kinship analysis

and comparison with SNP and STR panels. *Genes*, 15, 67.

468 Figure 1:

```
Alignment-free microhaplotype
pipeline for GT-seq data
Paired-end FASTQ reads
        ⬇
Primer detection
        ⬇
Amplicon reconstruction
        ⬇
Unique sequence counting
        ⬇
Diploid allele inference
        ⬇
Allele catalog construction
        ⬇
Exact-match genotype calling
        ⬇
Microhaplotype extraction
```

Figure 1. Alignment-free microhaplotype genotyping pipeline for GT-seq amplicon sequencing data.

The analytical workflow implemented in the GT-seq microhaplotype pipeline processes paired-end FASTQ reads to infer diploid microhaplotype genotypes without reference alignment. Paired-end reads are first scanned to identify primer-bounded amplicons corresponding to targeted loci. Primer-bounded reads are resolved into complete amplicon sequences and grouped by locus. In the first pass of the analysis, unique amplicon sequences are identified within each sample and ranked by read abundance to infer candidate diploid alleles and construct a catalog of unique haplotypes for each locus. In the second pass, sequencing reads are assigned to catalog haplotypes by exact sequence matching. Allele counts are used to infer diploid genotypes using an abundance-based model, and polymorphic sites within catalog haplotypes are extracted to generate phased microhaplotype representations.

493 Figure 2:

A. *Locus*   *FWD primer*   *REV primer*
    NC_061065.1_5347094 ACACCGGAAATGCCCTAGAG CCCTCTGCTAGCAACACCTTT

B. R1 - reads [must begin with FWD primer]
```
ACACCGGAAATGCCCTAGAGCACCAGGAACTGGCAGAAGGTCCAACATGGCGTCGCGCGGTGTGTTAGGGTCTATCTGGATTTCGTTATCTGGTGTTAAA
ACACCGGAAATGCCCTAGAGCACCAGGAACTGGCAGAAGGTCCAACATGGCGTCGCGCGGTGTGTTAGGGTCTATCTGGATTTCGTTATCTGGTGTTAAA
ACACCGGAAATGCCCTAGAGCACCAGGAACTGGCAGAAGGTTAAAAGTCCAACATGGCGTCGCGCGGTGTGTTAGGGTCTATCTGGATTTCGTTATCTGG
ACACCGGAAATGCCCTAGAGCACCAGGAACTGGCAGAAGGTCCAACATGGCGTCGCGCGGTGTGTTAGGGTCTATCTGGATTTCGTTATCTGGTGTTAAA
ACACCGGAAATGCCCTAGAGCACCAGGAACTGGCAGAAGGTTAAAAGTCCAACATGGCGTCGCGCGGTGTGTTAGGGTCTATCTGGATTTCGTTATCTGG
```

R2 - reads [must begin with REV primer from same locus]
```
CCCTCTGCTAGCAACACCTTTAACACCAGATAACGAAATCCAGATAGACCCTAACACACCGCGCGACGCCATGTTGGACCTTCTGCCAGTTCCTGGTGCT
CCCTCTGCTAGCAACACCTTTAACACCAGATAACGAAATCCAGATAGACCCTAACACACCGCGCGACGCCATGTTGGACCTTCTGCCAGTTCCTGGTGCT
CCCTCTGCTAGCAACACCTTTAACACCAGATAACGAAATCCAGATAGACCCTAACACACCGCGCGACGCCATGTTGGACTTTTAACCTTCTGCCAGTTCC
CCCTCTGCTAGCAACACCTTTAACACCAGATAACGAAATCCAGATAGACCCTAACACACCGCGCGACGCCATGTTGGACCTTCTGCCAGTTCCTGGTGCT
CCCTCTGCTAGCAACACCTTTAACACCAGATAACGAAATCCAGATAGACCCTAACACACCGCGCGACGCCATGTTGGACTTTTAACCTTCTGCCAGTTCC
```

C. Resolved - reads [begin with FWD and end with rcREV]
```
ACACCGGAAATGCCCTAGAGCACCAGGAACTGGCAGAAGGTCCAACATGGCGTCGCGCGGTGTGTTAGGGTCTATCTGGATTTCGTTATCTGGTGTTAAAGGTGTTGCTAGCAGAGGG
ACACCGGAAATGCCCTAGAGCACCAGGAACTGGCAGAAGGTCCAACATGGCGTCGCGCGGTGTGTTAGGGTCTATCTGGATTTCGTTATCTGGTGTTAAAGGTGTTGCTAGCAGAGGG
ACACCGGAAATGCCCTAGAGCACCAGGAACTGGCAGAAGGTTAAAAGTCCAACATGGCGTCGCGCGGTGTGTTAGGGTCTATCTGGATTTCGTTATCTGGTGTTAAAGGTGTTGCTAGCAGAGGG
ACACCGGAAATGCCCTAGAGCACCAGGAACTGGCAGAAGGTCCAACATGGCGTCGCGCGGTGTGTTAGGGTCTATCTGGATTTCGTTATCTGGTGTTAAAGGTGTTGCTAGCAGAGGG
ACACCGGAAATGCCCTAGAGCACCAGGAACTGGCAGAAGGTTAAAAGTCCAACATGGCGTCGCGCGGTGTGTTAGGGTCTATCTGGATTTCGTTATCTGGTGTTAAAGGTGTTGCTAGCAGAGGG
```

Figure 2. Reconstruction of primer-bounded amplicon sequences from paired-end reads.

(A) Paired-end sequencing reads from GT-seq libraries contain locus-specific primer sequences that

define the boundaries of each amplicon. Reads beginning with the forward primer are identified and

paired with their corresponding reverse reads if the R2 read begins with the reverse primer string.

(B) For validated read pairs, the full amplicon sequence is reconstructed by merging the paired

reads. Overlapping regions of the paired reads are merged to reconstruct the full primer-bounded

amplicon sequence, which begins with the forward primer and end with the reverse complement of

the reverse primer.

Figure 3:

Figure 3. Diploid abundance model for allele discovery and catalog construction.

Within each sample and locus, primer-bounded amplicon sequences are collapsed into unique

sequences and their read counts are tabulated (A). Unique sequences are ranked by read abundance,

and the two most abundant sequences are retained as candidate diploid alleles for each sample.

Low-frequency sequences are discarded as likely sequencing artifacts (red highlight). Candidate

alleles (green highlight) identified across all samples are aggregated to construct a catalog of unique

haplotypes for each locus (B).

540 Figure 4:

Figure 4. Diploid genotype inference using the A2 abundance metric and locus-level genotype

summaries.

(A) Diploid genotypes are inferred from read counts assigned to catalog haplotypes using the

relative abundance of the second most frequent allele (A2). For each sample and locus, reads

matching each catalog allele are counted and ranked by abundance. The proportion of reads

corresponding to the second most abundant allele (A2) is used to distinguish heterozygous

genotypes, where two alleles occur at substantial frequencies, from homozygous genotypes, where

nearly all reads correspond to a single allele. Example samples from locus NC_061065.1_5347094

illustrate heterozygous and homozygous genotype calls based on allele abundance.

(B) Locus-level dashboards summarize the distribution of haplotypes and diploid genotypes across

samples, providing a compact representation of allele frequencies and genotype composition for

each microhaplotype locus.

573   Figure 5:

A.

```
Stacked Catalog entry for Locus NC_061065.1_5347094
Allele101:ACACCGGAAATGCCCTAGAGCACCAGGAACTGGCAGAAGGTTAAAAGTCCAACATGGCGTCGCGCGGTGTGTTAGGGTCTATCTGGATTTCGTTATCTGGTGTTAAAGGTGTTGCTAGCAGAGGG
Allele102:ACACCGGAAATGCCCTAGAGCACCAGGAACTGGCAGAAGGTCAAAATTCCAACATGGCGGCGCGCAGTGTGTTAGGGTCTATCTGGATTTCGTTATCTGGTGTTAAAGGTGTTGCTAGCAGAGGG
Allele103:ACACCGGAAATGCCCTAGAGCACCAGGAACTGGCAGAAGGTTAAAAGTCCAACATGGCGTCGCGCAGTGTGTTAGGGTCTATCTGGATTTCGTTATCTGGTGTTAAAGGTGTTGCTAGCAGAGGG
Allele104:ACACCGGAAATGCCCTAGAGCACCAGGAACTGGCAGAAGGTTAAAATTCCAACATGGCGTCGCGCAGTGTGTTAGGGTCTATCTGGATTTCGTTATCTGGTGTTAAAGGTGTTGCTAGCAGAGGG
Allele105:ACACCGGAAATGCCCTAGAGCACCAGGAACTGGCAGAAGGT----TCCAACATGGCGTCGCGCGGTGTGTTAGGGTCTATCTGGATTTCGTTATCTGGTGTTAAAGGTGTTGCTAGCAGAGGG
```

B.
```
Allele101   TGTG
Allele102   CTGA
Allele103   TGTA
Allele104   TTTA
Allele105   --TG
```

C.
```
sample     LocusID               uHap      phasedSNP
YF40       NC_061065.1_5347094   101105    TGTG|--TG
YF42       NC_061065.1_5347094   103104    TGTA|TTTA
YF44       NC_061065.1_5347094   102102    CTGA|CTGA
```

Figure 5. Extraction of phased microhaplotypes from catalog haplotypes.

Catalog haplotypes for locus NC_061065.1_5347094 are compared to identify polymorphic

positions within the amplicon, including both single nucleotide polymorphisms and insertion–

deletion variants (A). Because each haplotype sequence originates from a single primer-bounded

amplicon, the relative phase of polymorphisms within the locus is preserved (B). Diploid genotypes

are therefore represented as combinations of phased haplotype sequences, forming multi-allelic

microhaplotypes (C) suitable for downstream population genetic, parentage, and kinship analyses.

A. *Locus*   *FWD primer*   *REV primer*

    NC_061065.1_5347094 ACACCGGAAATGCCCTAGAG CCCTCTGCTAGCAACACCTTT

B. R1 - reads [must begin with FWD primer]

ACACCGGAAATGCCCTAGAGCACCAGGAACTGGCAGAAGGTCCAACATGGCGTCGCGCGGTGTGTTAGGGTCTATCTGGATTTCGTTATCTGGTGTTAAA
ACACCGGAAATGCCCTAGAGCACCAGGAACTGGCAGAAGGTCCAACATGGCGTCGCGCGGTGTGTTAGGGTCTATCTGGATTTCGTTATCTGGTGTTAAA
ACACCGGAAATGCCCTAGAGCACCAGGAACTGGCAGAAGGTTAAAAGTCCAACATGGCGTCGCGCGGTGTGTTAGGGTCTATCTGGATTTCGTTATCTGG
ACACCGGAAATGCCCTAGAGCACCAGGAACTGGCAGAAGGTCCAACATGGCGTCGCGCGGTGTGTTAGGGTCTATCTGGATTTCGTTATCTGGTGTTAAA
ACACCGGAAATGCCCTAGAGCACCAGGAACTGGCAGAAGGTTAAAAGTCCAACATGGCGTCGCGCGGTGTGTTAGGGTCTATCTGGATTTCGTTATCTGG

   R2 - reads [must begin with REV primer from same locus]

CCCTCTGCTAGCAACACCTTTAACACCAGATAACGAAATCCAGATAGACCCTAACACACCGCGCGACGCCATGTTGGACCTTCTGCCAGTTCCTGGTGCT
CCCTCTGCTAGCAACACCTTTAACACCAGATAACGAAATCCAGATAGACCCTAACACACCGCGCGACGCCATGTTGGACCTTCTGCCAGTTCCTGGTGCT
CCCTCTGCTAGCAACACCTTTAACACCAGATAACGAAATCCAGATAGACCCTAACACACCGCGCGACGCCATGTTGGACTTTTAACCTTCTGCCAGTTCC
CCCTCTGCTAGCAACACCTTTAACACCAGATAACGAAATCCAGATAGACCCTAACACACCGCGCGACGCCATGTTGGACCTTCTGCCAGTTCCTGGTGCT
CCCTCTGCTAGCAACACCTTTAACACCAGATAACGAAATCCAGATAGACCCTAACACACCGCGCGACGCCATGTTGGACTTTTAACCTTCTGCCAGTTCC

C. Resolved - reads [begin with FWD and end with rcREV]

ACACCGGAAATGCCCTAGAGCACCAGGAACTGGCAGAAGGTCCAACATGGCGTCGCGCGGTGTGTTAGGGTCTATCTGGATTTCGTTATCTGGTGTTAAAGGTGTTGCTAGCAGAGGG
ACACCGGAAATGCCCTAGAGCACCAGGAACTGGCAGAAGGTCCAACATGGCGTCGCGCGGTGTGTTAGGGTCTATCTGGATTTCGTTATCTGGTGTTAAAGGTGTTGCTAGCAGAGGG
ACACCGGAAATGCCCTAGAGCACCAGGAACTGGCAGAAGGTTAAAAGTCCAACATGGCGTCGCGCGGTGTGTTAGGGTCTATCTGGATTTCGTTATCTGGTGTTAAAGGTGTTGCTAGCAGAGGG
ACACCGGAAATGCCCTAGAGCACCAGGAACTGGCAGAAGGTCCAACATGGCGTCGCGCGGTGTGTTAGGGTCTATCTGGATTTCGTTATCTGGTGTTAAAGGTGTTGCTAGCAGAGGG
ACACCGGAAATGCCCTAGAGCACCAGGAACTGGCAGAAGGTTAAAAGTCCAACATGGCGTCGCGCGGTGTGTTAGGGTCTATCTGGATTTCGTTATCTGGTGTTAAAGGTGTTGCTAGCAGAGGG

A.

Sample1: NC_061065.1_5347094
```
   ...
  15 ACACCGGAAATGCCCTAGAGCACCAGGAACTGGCAGAAGGTTAAAAGTCCAACATGGCGTTGCGCGGTGTGTTAGGGTCTATCTGGATTTCGTTATCTGGTGTTAAAGGTGTTGCTAGCAGAGGG
  16 ACACCGGAAATGCCCTAGAGCACCAGGAACTGGCAGAAGGTCCAACATGGCGTCGCGCGGTGTGTTAGGGTNTATCTGGATTTCGTTATCTGGTGTTAAAGGTGTTGCTAGCAGAGGG
  16 ACACCGGAAATGCCCTAGAGCACCAGGAACTGGCAGAAGGTCCAACATGGCGTTGCGCGGTGTGTTAGGGTCTATCTGGATTTCGTTATCTGGTGTTAAAGGTGTTGCTAGCAGAGGG
  21 ACACCGGAAATGCCCTAGAGCACCAGGAACTGGCAGAAGGTCCAACATGGCGTAGCGCGGTGTGTTAGGGTCTATCTGGATTTCGTTATCTGGTGTTAAAGGTGTTGCTAGCAGAGGG
1593 ACACCGGAAATGCCCTAGAGCACCAGGAACTGGCAGAAGGTTAAAAGTCCAACATGGCGTCGCGCGGTGTGTTAGGGTCTATCTGGATTTCGTTATCTGGTGTTAAAGGTGTTGCTAGCAGAGGG
2288 ACACCGGAAATGCCCTAGAGCACCAGGAACTGGCAGAAGGTCCAACATGGCGTCGCGCGGTGTGTTAGGGTCTATCTGGATTTCGTTATCTGGTGTTAAAGGTGTTGCTAGCAGAGGG
```

Sample2: NC_061065.1_5347094
```
   ...
  19 ACACCGGAAATGCCCTAGAGCACCAGGAACTGGCAGAAGGTTAAAAGTCCAACATGGCGTCGCGCAGTGTGTTAGGGTCTATCTGGATTTCGTTATTTGGTGTTAAAGGTGTTGCTAGCAGAGGG
  20 ACACCGGAAATGCCCTAGAGCACCAGGAACTGGCAGAAGGTTAAAAGTCCAACATGGCGTAGCGCAGTGTGTTAGGGTCTATCTGGATTTCGTTATCTGGTGTTAAAGGTGTTGCTAGCAGAGGG
  21 ACACCGGAAATGCCCTAGAGCACCAGGAACTGGCAGAAGGTTAAAGTCCAACATGGCGTCGCGCAGTGTGTTAGGGTCTATCTGGATTTCGTTATCTGGTGTTAAAGGTGTTGCTAGCAGAGGG
  42 ACACCGGAAATGCCCTAGAGCACCAGGAACTGGCAGAAGGTTAAAAGTCCAACATGGCGTCGCGCAGTGTNTTAGGGTCTATCTGGATTTCGTTATCTGGTGTTAAAGGTGTTGCTAGCAGAGGG
3581 ACACCGGAAATGCCCTAGAGCACCAGGAACTGGCAGAAGGTTAAAAGTCCAACATGGCGTCGCGCAGTGTGTTAGGGTCTATCTGGATTTCGTTATCTGGTGTTAAAGGTGTTGCTAGCAGAGGG
```

Sample3: NC_061065.1_5347094
```
   ... etc.
```

B.

Catalog entry for Locus NC_061065.1_5347094
```
Allele101:ACACCGGAAATGCCCTAGAGCACCAGGAACTGGCAGAAGGTTAAAAGTCCAACATGGCGTCGCGCGGTGTGTTAGGGTCTATCTGGATTTCGTTATCTGGTGTTAAAGGTGTTGCTAGCAGAGGG
Allele102:ACACCGGAAATGCCCTAGAGCACCAGGAACTGGCAGAAGGTCAAAATTCCAACATGGCGGCGCGCAGTGTGTTAGGGTCTATCTGGATTTCGTTATCTGGTGTTAAAGGTGTTGCTAGCAGAGGG
Allele103:ACACCGGAAATGCCCTAGAGCACCAGGAACTGGCAGAAGGTTAAAAGTCCAACATGGCGTCGCGCAGTGTGTTAGGGTCTATCTGGATTTCGTTATCTGGTGTTAAAGGTGTTGCTAGCAGAGGG
Allele104:ACACCGGAAATGCCCTAGAGCACCAGGAACTGGCAGAAGGTTAAAATTCCAACATGGCGTCGCGCAGTGTGTTAGGGTCTATCTGGATTTCGTTATCTGGTGTTAAAGGTGTTGCTAGCAGAGGG
Allele105:ACACCGGAAATGCCCTAGAGCACCAGGAACTGGCAGAAGGTCCAACATGGCGTCGCGCGGTGTGTTAGGGTCTATCTGGATTTCGTTATCTGGTGTTAAAGGTGTTGCTAGCAGAGGG
```

A. **Locus: NC_061065.1_5347094**
Diploid genotype calling using the A2 metric

Sample YF40
Allele 105
Allele 101
A2 = 41%
Genotype = HET / 101105

Sample YF42
Allele 103
Allele 104
A2 = 49%
Genotype = HET / 103104

Sample YF44
Allele 102
Allele 101
A2 = 0.11%
Genotype = HOM / 102102

B. **Dashboard figure for locus NC_061065.1_5347094**

A.

```
Stacked Catalog entry for Locus NC_061065.1_5347094
Allele101:ACACCGGAAATGCCCTAGAGCACCAGGAACTGGCAGAAGGTTAAAAGTCCAACATGGCGTCGCGCGGTGTGTTAGGGTCTATCTGGATTTCGTTATCTGGTGTTAAAGGTGTTGCTAGCAGAGGG
Allele102:ACACCGGAAATGCCCTAGAGCACCAGGAACTGGCAGAAGGTCAAATTCCAACATGGCGGTCGCGCATGTGTTAGGGTCTATCTGGATTTCGTTATCTGGTGTTAAAGGTGTTGCTAGCAGAGGG
Allele103:ACACCGGAAATGCCCTAGAGCACCAGGAACTGGCAGAAGGTTAAAGTTCCAACATGGCGTCGCGCAGTGTGTTAGGGTCTATCTGGATTTCGTTATCTGGTGTTAAAGGTGTTGCTAGCAGAGGG
Allele104:ACACCGGAAATGCCCTAGAGCACCAGGAACTGGCAGAAGGTTAAATTCCAACATGGCGTCGCGCATGTGTTAGGGTCTATCTGGATTTCGTTATCTGGTGTTAAAGGTGTTGCTAGCAGAGGG
Allele105:ACACCGGAAATGCCCTAGAGCACCAGGAACTGGCAGAAGGT----TCCAACATGGCGTCGCGCGGTGTGTTAGGGTCTATCTGGATTTCGTTATCTGGTGTTAAAGGTGTTGCTAGCAGAGGG
```

B.

Allele101   TGTG

Allele102   CTGA

Allele103   TGTA

Allele104   TTTA

Allele105   --TG

C.

sample	LocusID	uHap	phasedSNP
YF40	NC_061065.1_5347094	101105	TGTG|--TG
YF42	NC_061065.1_5347094	103104	TGTA|TTTA
YF44	NC_061065.1_5347094	102102	CTGA|CTGA

Alignment-free microhaplotype pipeline for GT-seq data

Paired-end FASTQ reads

⬇

Primer detection

⬇

Amplicon reconstruction

⬇

Unique sequence counting

⬇

Diploid allele inference

⬇

Allele catalog construction

⬇

Exact-match genotype calling

⬇

Microhaplotype extraction