Emergent smartphone temporal structures reflect cognitive constraints

Enea Ceolini[1,2] , Guido Band[2], and Arko Ghosh[2*]

1. QuantActions AG, Zurich Switzerland

2. Institute of Psychology, Leiden University, Leiden, The Netherlands

*Corresponding author:

Arko Ghosh

Institute of Psychology

Leiden University Wassenaarseweg 52

Leiden, 2333 AK, the Netherlands.

Email: a.ghosh@fsw.leidenuniv.nl

Abstract

Fine-grained temporal structures emerge in smartphone behavioral recordings over multi-day periods.

Complex systems research suggests that emergent temporal structures reflect underlying resource

constraints of the system. Here we test whether cognitive abilities measured through speeded tasks

(spanning fractions of a second) are reflected in emergent smartphone temporal structures spanning

days, revealing how cognitive resource limitations shape naturalistic behavior. We analyzed smartphone

tap interval patterns accumulated over several days and used decision tree regression models to predict

performance in simple and choice reaction time tasks from these patterns. Simple reaction time was

poorly predicted ($R^2 = 0.003$), indicating that basic sensorimotor constraints play only a marginal role

in shaping real-world behavioral timing. In contrast, choice reaction time was moderately predictable

($R^2 = 0.4$), demonstrating that higher-order cognitive constraints prominently influence naturalistic

temporal organization. Notably, while task performance operates at sub-second timescales, predictive

temporal patterns in smartphone behavior spanned milliseconds to several seconds and was

accumulated over days, revealing the broad, multi-scale influence of cognitive resource constraints on

everyday behavior. Both predicted and measured choice reaction times showed age-related decline, but

the decline was more pronounced in predicted values, suggesting that age-related cognitive changes

may be amplified in naturalistic contexts. These findings demonstrate that emergent temporal structures

in smartphone use can reveal how cognitive processes measured using speeded tasks manifest, or fail

to manifest, in real-world behavior. Complex-systems approaches can bridge laboratory and naturalistic

assessments of cognition, revealing which cognitive processes meaningfully constrain real-world

behavior.

Introduction

Human behavior in naturalistic settings appears complex and variable, and behavioral outputs are apparently unpredictable. However, the timing of human activities, from mail correspondence to telephone calls to website visits, exhibits emergent temporal patterns such as scale-invariant bursts, suggesting underlying organizational principles (Barabási, 2005; Clauset et al., 2009; Malmgren et al., 2008; Vázquez et al., 2006). A hypothesis from complex systems research proposes that such patterns reflect resource constraints that shape the system's output, analogous to how server response patterns reveal bandwidth limitations (Adler et al., 1998; Li et al., 2014; Vázquez et al., 2006). Supporting this framework, smartphone touchscreen tap intervals exhibit fractal-like temporal organization spanning ~1 second to several hours, with bursts of rapid interactions interspersed with longer pauses (Pfister and Ghosh, 2020). Critically, the scaling properties of this fractal-like organization correlates with individuals' fastest tapping speeds in the sub-second range, suggesting that basic timing constraints propagate across temporal scales to shape multi-hour behavioral dynamics. This constraint-based framework gains convergent support from psychology (Salthouse, 1996): performance on speeded tasks, which probe fundamental cognitive and sensorimotor capacity operating at millisecond timescales, correlates with diverse real-world outcomes including longevity, cognitive decline, and the conduct of instrumental activities of daily living (Bielak et al., 2010; Deary and Der, 2005a; Jakobsen et al., 2011; Steinborn et al., 2016). However, these (mostly weak) associations are established through self-reported functional assessments or distal health outcomes rather than direct quantification of naturalistic behavior, leaving the actual manifestation of the cognitive constraints in everyday behavioral patterns unexplored (Sbordone, 2001).

A novel perspective on smartphone behavior enables us to address how cognitive constraints manifest in emergent behavioral patterns (Duckrow et al., 2021). Essentially, we assume that real-world behavior unfolds as a continuous flow of neurobehavioral states whose complex trajectories cannot be directly observed or interpreted. Inspired by Poincaré sections used to study complex dynamical systems (Holmes, 1990), we treat the smartphone touchscreen as a Poincaré section through this continuous neurobehavioral flow. Each touch on the screen represents a moment when the trajectory intersects this section, and the intervals between consecutive touches quantify the dynamics of this flow (Fig. 1). We characterize these intervals using joint-interval distributions (JIDs)(Brennan et al., 2001; Duckrow et al., 2021; Rodieck et al., 1962): by plotting each inter-touch interval against its successor, analogous to return maps in dynamical systems (Holmes, 1990), we construct a two-dimensional behavioral landscape from accumulated observations. This behavioral map can be used to reveal how cognitive resource limitations that constrain neurobehavioral state dynamics manifest in the temporal organization of real-world behavior.

These low-dimensional smartphone behavioral maps are sensitive to multiple factors operating across

timescales. When constructed hourly, they oscillate systematically with circadian and weekly rhythms,

as well as other multi-day oscillations (Ceolini and Ghosh, 2023). These hourly maps also reveal

signatures of epileptic neural activity (Duckrow et al., 2021). When accumulated over a day or longer,

they reflect chronological age in healthy individuals, isolated clinical events such as seizures, and

accelerated aging in disease states (Ceolini et al., 2024, 2022a; van Nieuw Amerongen et al., 2024).

Mass-univariate analyses have extended this framework by correlating regions of the behavioral map

with cognitive task performance (Ceolini et al., 2022b). Critically, choice reaction time; engaging

executive control and sensorimotor processes, correlated with large distributed map regions, while

simple reaction time; primarily sensorimotor, correlated with focal clusters of rapid touches (Ceolini et

al., 2022b). However, this correlational approach treats map regions independently, potentially missing

complex interdependencies and not simply linear relationships, and does not demonstrate predictive

generalization to new individuals.

Machine learning provides a means to test whether cognitive processes measured by laboratory tasks

can be predicted from the emergent smartphone behavioral maps. We focused on two widely used

indices: simple reaction time (SRT), which primarily captures sensorimotor processing speed, and

choice reaction time (CRT) which engages executive functions including response selection and

cognitive control. While CRT shows moderate correlations with age and general intelligence, SRT

shows weaker associations with the same variables (Deary et al., 2011; Deary and Der, 2005b). Both

demonstrate clinical sensitivity in neurological diseases (Eckner et al., 2014; Pirozzolo et al., 1981).

Here we trained decision tree regression models to predict individual reaction times from smartphone

JID features accumulated over multiple days. We leveraged interpretability tools to isolate which JID

features drove predictions, revealing that predictive patterns spanned all time scales of the JID (from

milliseconds to ~30 s). We found that CRT was moderately predictable while SRT showed negligible

predictive power, demonstrating that higher-order cognitive constraints, but not basic sensorimotor

speed, systematically shape naturalistic behavioral timing.

Results

Smartphone touchscreen dynamics predicts reaction time

Participants completed simple and choice reaction time (CRT) tasks during laboratory testing sessions.

We used leave-one-participant-out cross-validation to predict individual reaction times from

smartphone JID features and chronological age (Fig. 2). We tested multiple temporal windows and

found that behavioral data from the 4 days immediately preceding each testing session yielded optimal

predictions based on a composite performance metric (F-score; see Methods). This yielded 360 models

(one per participant), which we evaluated at two levels: participant-level predictions using median

performance across repeated sessions (n=360), and session-level predictions including all testing
occasions (n=2,633).

At the participant-level, CRT was substantially predictable from smartphone behavioral patterns (t(359)
= 15.83, p = 3.8 × 10^{-43}, R^2 = 0.41, simple linear regression), while SRT showed essentially no
relationship (t(359) = 1.05, p = 0.295, R^2 = 0.003). This striking dissociation persisted at the session-
level: CRT remained significantly predictable (t(2632) = 30.66, p = 1.0 × 10^{-176}, R^2 = 0.26), while SRT,
despite achieving statistical significance due to large sample size, showed negligible explained variance
(t(2632) = 9.80, p = 2.8 × 10^{-22}, R^2 = 0.04). These findings demonstrate that naturalistic smartphone
behavioral dynamics reflect higher-order cognitive constraints measured by CRT, but not basic
sensorimotor processing speed measured by SRT. Next, we address how these predictions alter with
age.

Predicted reaction time declines with age
121
Our sample spanned the adult lifespan (18 to 86 years of age). Given that reaction times slow with age,
we examined whether this age-related decline was evident in smartphone-predicted RT values.
Critically, we used multivariate regression to test whether predicted RT values provide distinct
information about age beyond what is captured by laboratory-measured RT values. Towards this, we
raised new sets of leave-one-out models, but the chronological age was withheld (n = 363). We then
used a multi-variate regression model with the real and predicted RT (median across sessions) as
independent variables and chronological age as the dependent variable (Fig. 2). For the choice reaction
time, the full model was strongly related to age (F(2, 360), p = 7.10 x 10^{-73} , R^2 = 0.603, multi-variate
regression). Both the predicted and real CRT independently contributed to this relationship: $\beta_{predicted}$ =
0.17 (SE = 0.014) t = 12.47, p = 6.5 × 10^{-30}, β_{real} =0.07 (SE = 0.01) t = 9.75, p = 4.5 × 10^{-20}. Notably,
the coefficient for predicted RT was more than twice as large as for measured RT, indicating that
smartphone-derived behavioral patterns capture age-related cognitive changes substantially more
strongly while also providing complementary information.

Behavioral features underlying CRT predictions
136
To identify which smartphone behavioral patterns predicted CRT, we applied SHAP-based feature
importance analysis to each leave-one-out model (see Methods). For each bin in the two-dimensional
JID map, we quantified how frequently it was selected across all 360 models (Fig. 3). JID features
representing sub-second tap intervals were consistently selected and clustered in specific regions of
the behavioral map, while features representing longer intervals (>1 second) showed spatially
distributed selection across the map without clear clustering. This pattern indicates that CRT, which
operates at sub-second timescales, relates to specific, consistent patterns of rapid smartphone
interactions, whereas its relationship to slower behaviors is more diffuse.

We next estimated the directional impact of selected features, whether they predicted slower or faster

CRT based on SHAP values (Fig. 3). Lower frequencies in clustered sub-second intervals and higher

frequencies in spatially distributed features (spanning both sub-second and longer intervals) both

predicted slower CRT. Conversely, higher frequencies in clustered sub-second intervals and lower

frequencies in distributed features predicted faster CRT. However, the relationship was not simply

divided between sub-second versus supra-second behaviors: some sub-second intervals predicted

slower CRT while others predicted faster CRT, depending on their location in the behavioral map.

Despite this complexity, a discernible core pattern emerged wherein very rapid consecutive

interactions (<0.3s intervals) most consistently predicted faster cognitive performance.

Discussion

Our findings distinguish the manifestation of two widely used speeded cognitive tasks, simple reaction time (SRT) and choice reaction time (CRT), in emergent behavioral patterns. It is well established that SRT and CRT represent different cognitive processes (Donders, 1969; Suarez et al., 2021), best reflected in the way decision-making is modeled in computational approaches of RT distributions (Ratcliff and McKoon, 2008; Smith, 1995). While previous studies showed dissociations of SRT versus CRT at the group level and in laboratory settings (Godefroy et al., 2010) our work demonstrates that this distinction extends to their manifestation in real-world behavior. Emergent temporal structures in smartphone use accumulated over multiple days strongly reflect CRT performance but show negligible relationship to SRT. This dissociation reveals two key insights: First, the cognitive processes underlying CRT, including response selection and cognitive control, pervasively influence the temporal organization of everyday behavior. Second, basic sensorimotor speed measured by SRT plays minimal role in shaping naturalistic behavioral timing, highlighting its limited relevance for understanding real-world cognitive function.

Our analysis traced cognitive processes through emergent temporal structures in naturalistic behavior. Three mechanistic interpretations merit consideration. First, cognitive constraints may directly shape behavioral organization: CRT-related processes systematically structure smartphone timing, analogous to how bandwidth constraints shape server outputs in complex systems (Pfister and Ghosh, 2020; Vazquez, 2007). Simple sensorimotor speed, in contrast, shows minimal influence. Second, use-dependent plasticity could operate in reverse: smartphone behavior might shape CRT processes. While smartphone use has been associated with neural plasticity, existing evidence focuses on sensorimotor rather than executive domains (Balerna and Ghosh, 2018; Ghosh, 2021; Gindrat et al., 2015). Third, common factors, including stable traits (age, personality) or fluctuating states (arousal, mood), could independently influence both RT performance and behavioral patterns. The recency effect, wherein the 4 days immediately preceding testing most strongly predict RT, provides crucial constraints. This temporal specificity rules out an exclusive role of stable trait factors and indicates that any operative mechanism must function on timescales of days or less. Whether this reflects cognitive constraints dynamically shaping behavior, rapid plasticity, or short-term state fluctuations remains to be fully determined.

The behavioral features predicting CRT spanned both sub-second and supra-second timescales. This is consistent with evidence that cognitive processes underlying speeded decisions also support slower choices (Krajbich et al., 2015), suggesting that executive control and response selection operate across temporal scales. This multi-scale manifestation may explain why age-related decline was more pronounced in predicted CRT compared to measured CRT values. Smartphone behavior samples CRT-related cognitive processes across diverse naturalistic contexts—from rapid typing to deliberate

browsing—providing multiple independent observations of the same underlying constraints. This

broader sampling may amplify age-related signals that are less apparent in brief laboratory

assessments. These findings align with established patterns showing that CRT, but not SRT,

demonstrates strong age-related decline and disease sensitivity (Bielak et al., 2010; Deary et al., 2011;

Myerson et al., 1990; Pirozzolo et al., 1981), likely reflecting the more widespread engagement of

executive control processes across behavioral contexts.

Our findings demonstrate that emergent smartphone behavioral structures reflect specific cognitive

constraints: CRT-related executive processes and other relatively slow cognitive processess

pervasively shape naturalistic behavior, while basic sensorimotor speed does not. This bridges

complex systems approaches to behavior with individual differences in cognitive function, revealing

how latent processess underlying laboratory-based measures manifest,and potentially amplify, in real-

world contexts. Practically, this enables passive, continuous cognitive monitoring through naturalistic

smartphone use, overcoming the logistical constraints of traditional laboratory testing. This approach

may prove particularly valuable for early detection and longitudinal monitoring of cognitive decline,

offering ecologically valid assessment that complements conventional neuropsychological methods.

Methods

Participants

We recruited healthy participants (self-reported; health status assessed using SF-36) through our online laboratory platform, with recruitment aided by the Dutch Brain Registry (Zwan et al., 2021). Portions of this dataset have been reported previously (Ceolini et al., 2024, 2022b; Ceolini and Ghosh, 2023). We recruited 720 volunteers, of whom 642 installed the smartphone data collection app (see below) and provided demographic information (235 males, 396 females, 11 prefer not to say; ages 16–86 years). The present analysis includes 360 participants who completed at least one reaction time testing session and accumulated at least 100 touchscreen interactions during the corresponding 4-day window. All procedures were approved by the local ethics committee at Leiden University.

Smartphone data collection app

Participants installed the TapCounter app (QuantActions AG, Zurich, Switzerland) from the Google Play Store on their personal Android smartphones. The app passively recorded all touchscreen interactions with millisecond-precision timestamps and associated app identifiers (Balerna and Ghosh, 2018). Data were automatically uploaded to a secure cloud platform without interfering with normal device use. For the present analysis, we used only tap timestamps to construct joint-interval distributions; app identity information was not analyzed.

Cognitive tests

Participants completed the Deary-Liewald simple and 4-choice reaction time tasks (Deary et al., 2011) via PsyToolkit (Stoet, 2017), as described previously (Ceolini et al., 2022b). Testing was conducted online on participants' personal computers (keyboard required; participants confirmed appropriate setup before beginning). Tasks were available in English or Dutch. Participants were invited to complete monthly sessions over 53 months, with participation ranging from 1 to over 100 sessions per individual. Each session included 8 shared practice trials followed by 25 SRT trials and 50 4-CRT trials. Inter-trial intervals varied randomly between 1-3 seconds. Only correct trials with RTs ≤1000 ms were analyzed (eliminating a total of 8 trials across the sample). Median RT values for each task and session were used in all analyses.

The joint interval distribution (JID)

Inter-tap intervals (ITIs) were analyzed using joint-interval distributions (JIDs) to capture sequential timing structure (Duckrow et al., 2021). Only ITIs during screen-on periods were included; screen-off intervals were excluded. Each JID represented the two-dimensional relationship between consecutive ITIs (interval k vs. interval $k+1$). ITIs were $\log_{10}$-transformed and discretized into 50×50 bins spanning $10^{0.5}$ to $10^{4.5}$ ms (~3 ms to ~30 seconds), covering the 1st-99th percentile range across participants. Joint

probability densities were estimated using scikit-learn (Pedregosa et al., 2011) yielding 2,500 features

per participant. We compared JIDs constructed from multiple temporal windows (4, 7, 10, and 21 days)

preceding each cognitive test to identify the optimal accumulation period. To identify the optimal

temporal accumulation window, we compared JIDs constructed from the 4, 7, 10, and 21 days preceding

each test session, yielding 360 (2,633 sessions), 361 (2,648), 361 (2,660), and 363 (2,687) participants

respectively. Sample sizes increased slightly with longer windows as more sessions met the minimum

data requirement ($\geq$100 taps).

Decision tree regresion models

Reaction times were predicted using XGBoost gradient-boosted decision trees(Chen and Guestrin,

2016). Predictors included 2,500 JID features (50×50 bins) from the 4-day pre-test window and session

number. Observations were weighted by tap count (higher counts indicate more reliable JID estimates).

We trained models both with and without chronological age as a predictor to assess behavioral feature

contributions beyond age-related variance. We used leave-one-out cross-validation, training 360 models

(one per participant) with conservative hyperparameters (learning_rate=0.01, max_depth=4; other

parameters at defaults). Model performance was evaluated via linear regression of predicted versus

observed values. Feature importance was assessed using SHAP values (Lundberg and Lee, 2017), which

quantify each feature's directional contribution to predictions. For each JID bin, we calculated selection

frequency across models and aggregated directional effects.

Cross-Validation and Feature Selection

We used leave-one-participant-out cross-validation (LOOCV), training n (~360) models each on n -1

participants and testing on the held-out participant. Within each training set, nested 10-fold cross-

validation with early stopping determined optimal boosting rounds. To reduce overfitting given the

limited sample size relative to features (2,500 JID bins), we implemented SHAP-based feature selection

for each LOOCV model. After training on all features, we calculated SHAP values across nested CV

folds and ranked features by importance. We then retrained using progressively smaller feature subsets

(500, 250, 125, 60, 15 features), selecting the smallest subset maintaining $\geq$90% of full-model

performance. This consistently yielded 60 features per model, though specific features varied by

training set. Models used pseudo-Huber loss and reaction times were z-scored per training set.

Performance was evaluated by pooling all test predictions and computing linear regression statistics.

Selection of the Optimal Accumulation Period

To identify the optimal accumulation period, we compared four window lengths (4, 7, 10, 21 days)

using the model variant with age. We evaluated each using four metrics: Spearman's ρ, R^2, MAE, and

RMSE. For each metric, we ranked the eight conditions and normalized ranks to a 0-100 scale (inverting

for MAE and RMSE where lower is better). The composite performance score was the mean of these

four normalized values, equally weighting all metrics. The 4-day window consistently achieved the

highest composite scores and was selected for all analyses

Aknowledgements

This project was funded by Velux Stiftung (Grant No.1283, awarded to A.G.) and postdoc Mobility

awarded to Enea Ceolini with Arko Ghosh as host (SNSF no. 199692). We also thank all participants

for contributing their time and effort. The authors used Claude (Anthropic, Claude Sonnet 4.5,

accessed January 2026) to improve the clarity, grammar, and organization of the manuscript text. The

AI was used solely for language editing; all scientific content, study design, data collection and

analysis, interpretation of results, and conclusions were developed by the authors who take full

responsibility for the accuracy and integrity of the manuscript.

References

Adler, R., Feldman, R., Taqqu, M., 1998. A Practical Guide to Heavy Tails: Statistical Techniques and Applications. Springer Science & Business Media.

Balerna, M., Ghosh, A., 2018. The details of past actions on a smartphone touchscreen are reflected by intrinsic sensorimotor dynamics. npj Digital Med 1, 1–5. https://doi.org/10.1038/s41746-017-0011-3

Barabási, A.-L., 2005. The origin of bursts and heavy tails in human dynamics. Nature 435, 207–211. https://doi.org/10.1038/nature03459

Bielak, A.A.M., Hultsch, D.F., Strauss, E., MacDonald, S.W.S., Hunter, M.A., 2010. Intraindividual variability in reaction time predicts cognitive outcomes 5 years later. Neuropsychology 24, 731–741. https://doi.org/10.1037/a0019802

Brennan, M., Palaniswami, M., Kamen, P., 2001. Do existing measures of Poincare plot geometry reflect nonlinear features of heart rate variability? IEEE Transactions on Biomedical Engineering 48, 1342–1347. https://doi.org/10.1109/10.959330

Burton, C.L., Strauss, E., Hultsch, D.F., Hunter, M.A., 2009. The Relationship between Everyday Problem Solving and Inconsistency in Reaction Time in Older Adults. Aging, Neuropsychology, and Cognition. https://doi.org/10.1080/13825580903167283

Ceolini, E., Brunner, I., Bunschoten, J., Majoie, M.H.J.M., Thijs, R.D., Ghosh, A., 2022a. A model of healthy aging based on smartphone interactions reveals advanced behavioral age in neurological disease. iScience 25, 104792. https://doi.org/10.1016/j.isci.2022.104792

Ceolini, E., Ghosh, A., 2023. Common multi-day rhythms in smartphone behavior. npj Digit. Med. 6, 1–9. https://doi.org/10.1038/s41746-023-00799-7

Ceolini, E., Kock, R., Band, G.P.H., Stoet, G., Ghosh, A., 2022b. Temporal clusters of age-related behavioral alterations captured in smartphone touchscreen interactions. iScience 25, 104791. https://doi.org/10.1016/j.isci.2022.104791

Ceolini, E., Ridderinkhof, K.R., Ghosh, A., 2024. Age-related behavioral resilience in smartphone touchscreen interaction dynamics. Proceedings of the National Academy of Sciences 121, e2311865121. https://doi.org/10.1073/pnas.2311865121

Chen, T., Guestrin, C., 2016. XGBoost: A Scalable Tree Boosting System, in: Proceedings of the 22nd ACM SIGKDD International Conference on Knowledge Discovery and Data Mining, KDD '16. Association for Computing Machinery, New York, NY, USA, pp. 785–794. https://doi.org/10.1145/2939672.2939785

Clauset, A., Shalizi, C.R., Newman, M.E.J., 2009. Power-Law Distributions in Empirical Data. SIAM Review 51, 661–703.

Deary, I.J., Der, G., 2005a. Reaction Time Explains IQ's Association with Death. Psychol Sci 16, 64–69. https://doi.org/10.1111/j.0956-7976.2005.00781.x

Deary, I.J., Der, G., 2005b. Reaction Time, Age, and Cognitive Ability: Longitudinal Findings from Age 16 to 63 Years in Representative Population Samples. Aging, Neuropsychology, and Cognition 12, 187–215. https://doi.org/10.1080/13825580590969235

Deary, I.J., Liewald, D., Nissan, J., 2011. A free, easy-to-use, computer-based simple and four-choice reaction time programme: The Deary-Liewald reaction time task. Behav Res 43, 258–268. https://doi.org/10.3758/s13428-010-0024-1

Donders, F.C., 1969. On the speed of mental processes. Acta Psychologica 30, 412–431. https://doi.org/10.1016/0001-6918(69)90065-1

Duckrow, R.B., Ceolini, E., Zaveri, H.P., Brooks, C., Ghosh, A., 2021. Artificial neural network trained on smartphone behavior can trace epileptiform activity in epilepsy. iScience 24. https://doi.org/10.1016/j.isci.2021.102538

Eckner, J.T., Kutcher, J.S., Broglio, S.P., Richardson, J.K., 2014. Effect of sport-related concussion on clinically measured simple reaction time. Br J Sports Med 48, 112–118. https://doi.org/10.1136/bjsports-2012-091579

Ghosh, A., 2021. Smartphone deprivation alters cortical sensorimotor processing of the hand. https://doi.org/10.1101/2021.03.04.433898

Gindrat, A.-D., Chytiris, M., Balerna, M., Rouiller, E.M., Ghosh, A., 2015. Use-Dependent Cortical
Processing from Fingertips in Touchscreen Phone Users. Current Biology 25, 109–116.
https://doi.org/10.1016/j.cub.2014.11.026

Godefroy, O., Roussel, M., Despretz, P., Quaglino, V., Boucart, M., 2010. Age-Related Slowing:
Perceptuomotor, Decision, or Attention Decline? Experimental Aging Research 36, 169–189.
https://doi.org/10.1080/03610731003613615

Holmes, P., 1990. Poincaré, celestial mechanics, dynamical-systems theory and "chaos." Physics
Reports 193, 137–163. https://doi.org/10.1016/0370-1573(90)90012-Q

Jakobsen, L.H., Sorensen, J.M., Rask, I.K., Jensen, B.S., Kondrup, J., 2011. Validation of reaction
time as a measure of cognitive function and quality of life in healthy subjects and patients.
Nutrition 27, 561–570. https://doi.org/10.1016/j.nut.2010.08.003

Krajbich, I., Bartling, B., Hare, T., Fehr, E., 2015. Rethinking fast and slow based on a critique of
reaction-time reverse inference. Nat Commun 6, 7455. https://doi.org/10.1038/ncomms8455

Li, J., Sharma, N.Kr., Ports, D.R.K., Gribble, S.D., 2014. Tales of the Tail: Hardware, OS, and
Application-level Sources of Tail Latency, in: Proceedings of the ACM Symposium on Cloud
Computing, SOCC '14. Association for Computing Machinery, New York, NY, USA, pp. 1–
14. https://doi.org/10.1145/2670979.2670988

Lundberg, S.M., Lee, S.-I., 2017. A unified approach to interpreting model predictions, in:
Proceedings of the 31st International Conference on Neural Information Processing Systems,
NIPS'17. Curran Associates Inc., Red Hook, NY, USA, pp. 4768–4777.

Malmgren, R.D., Stouffer, D.B., Motter, A.E., Amaral, L.A.N., 2008. A Poissonian explanation for
heavy tails in e-mail communication. Proceedings of the National Academy of Sciences 105,
18153–18158. https://doi.org/10.1073/pnas.0800332105

Myerson, J., Hale, S., Wagstaff, D., Poon, L.W., Smith, G.A., 1990. The information-loss model: a
mathematical theory of age-related cognitive slowing. Psychol Rev 97, 475–487.
https://doi.org/10.1037/0033-295x.97.4.475

Pedregosa, F., Varoquaux, G., Gramfort, A., Michel, V., Thirion, B., Grisel, O., Blondel, M.,
Prettenhofer, P., Weiss, R., Dubourg, V., Vanderplas, J., Passos, A., Cournapeau, D., Brucher,
M., Perrot, M., Duchesnay, É., 2011. Scikit-learn: Machine Learning in Python. Journal of
Machine Learning Research 12, 2825–2830.

Pfister, J.-P., Ghosh, A., 2020. Generalized priority-based model for smartphone screen touches. Phys.
Rev. E 102, 012307. https://doi.org/10.1103/PhysRevE.102.012307

Pirozzolo, F.J., Christensen, K.J., Ogle, K.M., Hansch, E.C., Thompson, W.G., 1981. Simple and
choice reaction time in dementia: Clinical implications. Neurobiology of Aging 2, 113–117.
https://doi.org/10.1016/0197-4580(81)90008-7

Ratcliff, R., McKoon, G., 2008. The Diffusion Decision Model: Theory and Data for Two-Choice
Decision Tasks. Neural Comput 20, 873–922. https://doi.org/10.1162/neco.2008.12-06-420

Rodieck, R.W., Kiang, N.Y.-S., Gerstein, G.L., 1962. Some Quantitative Methods for the Study of
Spontaneous Activity of Single Neurons. Biophysical Journal 2, 351–368.
https://doi.org/10.1016/S0006-3495(62)86860-X

Salthouse, T.A., 1996. The processing-speed theory of adult age differences in cognition.
Psychological Review 103, 403–428. https://doi.org/10.1037/0033-295X.103.3.403

Sbordone, R.J., 2001. Limitations of neuropsychological testing to predict the cognitive and
behavioral functioning of persons with brain injury in real-world settings.
NeuroRehabilitation 16, 199–201. https://doi.org/10.3233/NRE-2001-16402

Smith, P.L., 1995. Psychophysically principled models of visual simple reaction time. Psychological
Review 102, 567–593. https://doi.org/10.1037/0033-295X.102.3.567

Steinborn, M.B., Langner, R., Flehmig, H.C., Huestegge, L., 2016. Everyday Life Cognitive
Instability Predicts Simple Reaction Time Variability: Analysis of Reaction Time
Distributions and Delta Plots. Applied Cognitive Psychology 30, 92–102.
https://doi.org/10.1002/acp.3172

Stoet, G., 2017. PsyToolkit: A novel web-based method for running online questionnaires and
reaction-time experiments. Teaching of Psychology 44, 24–31.
https://doi.org/10.1177/0098628316677643

Suarez, S., Eynard, B., Granon, S., 2021. A Dissociation of Attention, Executive Function and
406   Reaction to Difficulty: Development of the MindPulse Test, a Novel Digital
407   Neuropsychological Test for Precise Quantification of Perceptual-Motor Decision-Making
408   Processes. Front. Neurosci. 15. https://doi.org/10.3389/fnins.2021.650219
409   van Nieuw Amerongen, A.R., Meppelink, A.M., Ghosh, A., Thijs, R.D., 2024. Real-world smartphone
410   data can trace the behavioural impact of epilepsy: A case study. European Journal of
411   Neurology 31, e16433. https://doi.org/10.1111/ene.16433
412   Vazquez, A., 2007. Impact of memory on human dynamics. Physica A: Statistical Mechanics and its
413   Applications 373, 747–752. https://doi.org/10.1016/j.physa.2006.04.060
414   Vázquez, A., Oliveira, J.G., Dezsö, Z., Goh, K.-I., Kondor, I., Barabási, A.-L., 2006. Modeling bursts
415   and heavy tails in human dynamics. Phys. Rev. E 73, 036127.
416   https://doi.org/10.1103/PhysRevE.73.036127
417   Zwan, M.D., van der Flier, W.M., Cleutjens, S., Schouten, T.C., Vermunt, L., Jutten, R.J., van Maurik,
418   I.S., Sikkes, S.A.M., Flenniken, D., Howell, T., Weiner, M.W., Scheltens, P., Prins, N.D.,
419   2021. Dutch Brain Research Registry for study participant recruitment: Design and first
420   results. Alzheimer's & Dementia: Translational Research & Clinical Interventions 7, e12132.
421   https://doi.org/10.1002/trc2.12132

Figure 1. Smartphone behavioral maps based on next-interval dynamics of touchscreen interactions.
(a) Schematic illustration of joint-interval distribution (JID) construction. A time series of touchscreen
interactions (top) generates inter-touch intervals (ITIs). The JID is constructed by plotting each
interval k against its immediate successor $k+1$, creating a two-dimensional return map of behavioral
dynamics. (b) A JID from an individual participant where the data was accumilated over a period of 4
days. PD, probability density. ITI, inter touch interval.
430
431
432
433

Figure 2. Smartphone behavioral maps predict choice reaction time. (a) Analysis pipeline. Joint interval distributions (JIDs) from multi-day smartphone use were used to predict reaction time performance via XGBoost regression with feature selection. (b) Predicted versus measured choice RT at session level (top) and participant level (bottom). (c) Model performance by accumulation period (Spearman's ρ). The 4-day window preceding testing yielded optimal predictions (F-score combining Spearman's ρ, R^2, MAE, RMSE, inset). (d) Age-related decline in predicted choice RT from models excluding chronological age.

Figure 3. Behavioral features underlying the prediction of choice reaction time (CRT). (a) Frequency
of feature selection across all models trained using a leave-one-participant-out cross-validation
strategy. Darker pixels indicate features that were consistently selected across participants, reflecting
their importance in predicting CRT (b) Directional contributions of individual features expressed as
population level correlation coefficients (based on all the leave one participant out models) at a given
two dimensional bin (feature) between behavioral probability and SHAP values. For instance +1
indicates strong directly proportional link: more the behaviour slower the reaction time, and -1
indicates an inversely proportional link: more the behaviour faster the reaction time.