Learning by forgetting: A computational model of insect brain

Koichiro Yamauchi[1Y], Aditya Gyanprakash Nirmale[2Y]

1 Department of Computer Science, Chubu University, Kasugai, Matsumoto-cho 1200, Japan

2 Department of Electrical Engineering, Indian Institute of Technology Bombay,

Powai, Mumbai – 400076, India

[Y]These authors contributed equally to this work.

These authors also contributed equally to this work.

Deceased

Membership list can be found in the Acknowledgments section.

* k.yamauchi@fsc.chubu.ac.jp

Abstract

In this study, resource-constrained learning methods were developed as a model for the learning behavior of

the fly brain, specifically the mushroom body. Recent research on the mushroom bodies of flies shows that

unfamiliar odors activate certain output neurons (MBONs); however, these effects are rapidly suppressed

upon repeated exposure to the same odor. Such MBON behaviors appear to reflect odor learning. We

investigated how flies continue learning about odors throughout their lives despite their small brains.

Researchers have suggested that learning about new odors can help flies forget existing memories. Therefore,

we hypothesized that the main reason for continual learning is that it serves as a strategy for forgetting. To

test the validity of this hypothesis, we designed three models using a kernel perceptron. This approach is

suitable for estimating ongoing learning capacity within a budget. According to the results of computer

simulations and theoretical analysis, the model demonstrated the importance of forgetting mechanisms for

two reasons: first, to prepare for subsequent learning sessions, and second, to reduce the negative effects of

deleting memories.

Author summary

Drosophila mushroom body output neurons (MBONs) in the $\alpha3$ compartment of the fruit fly brain are highly activated by novel odors, and their activation triggers alerting behavior. Interestingly, these specific neurons react only to unfamiliar odor information, suggesting they constantly undergo incremental learning of new odors. This study was aimed at constructing three incremental learning models of the MBON $\alpha3$ neurons. Although there have been numerous studies on complex circuit designs to reproduce activation waveforms, herein we constructed a fundamental learning model based on a kernelized learning method. Since kernelized learning models interpret Hebbian learning as the addition or subtraction of kernel functions, the model is easy to analyze theoretically. Consequently, we conclude that the forgetting property observed in the MBON $\alpha3$ neurons is essential for reducing error when learning occurs within a brain of limited capacity.

Introduction

In insects, mushroom bodies are responsible for memory and learning [1]. The nerve center of *Drosophila* is a mushroom body that consists mainly of Kenyon cells (KCs) [1], mushroom body output neurons (MBONs), and dopaminergic neurons (DANs). Some DANs are well known to encode the predicted reward of the current situation, and their output signals affect the connections between KCs and MBONs. Moreover, DANs control the learning of MBONs, which in turn send output signals to other areas of the insect brain.

Odors are sensed by olfactory sensory neurons in the antennae of *Drosophila*, and the gathered information is distributed to KCs by projection neurons (PNs). The connections between PNs and KCs appear to be random and do not exhibit plasticity. Approximately 2000 KCs exist in this region, and each KC neuron represents a sensory input. KCs send their axonal fibers to MBONs, which are divided into 15 compartments, each with its own specific function. Plasticity is observed in the connections between KCs and MBONs. The connections between KCs and MBONs are adjusted according to the reward signals from DANs. The main role of DANs is to represent predicted reward signals. Additionally, DANs represent the novelty of current stimuli.

Hattori et al. [2] investigated the MBONs in the $\alpha3$ compartments of *Drosophila* by activating them with novel odors. When the MBON $\alpha3$ neurons were activated, *Drosophila* exhibited an alerting behavior. This novel

order-evoked MBON activity was quickly suppressed by repeated stimulation with the same odor, suggesting

that *Drosophila* rapidly learns to recognize a novel odor upon repeated stimulation, which renders the odor

progressively more familiar. Thus, *Drosophila* can engage in incremental learning of novel odors, and odor

perception is critical to their life. The estimated novelty-detection capacity translates into 10–20 orthogonal

feature vectors and implies that MBONs can store 10–20 memory units. However, 10–20 memory units may be

significantly less for *Drosophila* to survive for a month. This observation raises a fundamental question: how

does the fruit fly maintain continuous learning despite such limited neural resources?

To develop technological breakthroughs, imitation of biological systems is sometimes valuable. This study

is focused on the *Drosophila* brain, which contains relatively few neurons. Due to limited resources,

performing incremental learning is challenging. Therefore, we try to gain insights into how small brains learn

by studying the *Drosophila* brain. This study develops a learning model for MBONs and DANs based on a

kernel perceptron. The kernel perceptron framework is particularly suitable for mistake-bound analyses,

which allow for a formal evaluation of learning efficiency. Using this approach, we try to characterize the

learning properties of *Drosophila* within a mistake-bound paradigm. For analysis, Forgetron [3] is considered

the base model because it reduces the weight parameters during incremental learning, such that the model fits

the learning strategy of MBONs. However, the mistake-bound model assumes that the learning machine

forgets the oldest memory in each round. The purpose of forgetting is to decrease dependence on each

memory and reduce the adverse effects of removing the oldest memory. Conversely, forgetting one memory is

a way to make room for new learning.

Furthermore, a simulation study is performed using Forgetron and a modified version of Forgetron in

changing environments. The observed results assist in determining the effects of forgetting. This study builds

on and extends the preliminary results presented in our previous research [4]. To clarify the novel

contributions of this study, the main improvements over previous studies are as follows:

1. **Clarification of Simulation Results:** Simulation settings are refined, and the results are analyzed in

greater detail to better demonstrate the effects of the forgetting mechanism.

2. **Theoretical Analysis of the Least Recently Used (LRU) Model:** For the LRU strategy (Model 3), a

detailed theoretical analysis is performed using Markov chains and the ergodic theorem, thereby establishing

the performance advantage of the LRU model.

3. **Sensitivity Analysis of the Shrinkage Coefficient (ϕ):** Sensitivity analysis of the shrinkage coefficient ϕ

is conducted to verify the effect of the mistake-bound model. By detailing the minimization of *cumulative error*,

we theoretically demonstrate that an optimal forgetting rate exists for MBONs to minimize the number of

prediction errors.

Results

Kernelized incremental learning on a budget as a model of

MBON $\alpha'3$ neurons

In this study, we develop a model of the MBONs in the $\alpha3$ compartment of *Drosophila*. The $\alpha3$ compartment

contains a single MBON layer along with associated dopamine neurons (PPL1α-3), which regulate alerting

behaviors in response to novel odors. The memory capacity of this compartment depends on the number of

orthogonal vectors in KCs, typically ranging from 10 to 20. Hattori et al. [2] reported that learning a novel odor

reduces existing memory in MBON $\alpha3$ neurons. This finding suggests that acquiring new odor memories leads

to the removal of part of the existing memory, which in turn facilitates the learning of additional new odors in

the future.

A key constraint of MBONs is the limited number of neurons available for memory storage. As new stimuli

are encountered sequentially, the system must learn and use these memories within a fixed resource budget. If

the memory capacity becomes saturated and no further forgetting occurs, the system may fail to adapt to new

situations. To solve this problem, forgetting a portion of existing memory is necessary; however, this

introduces an additional risk. Specifically, forgetting can (i) cause sudden changes in knowledge structure

owing to abrupt memory pruning, which may interfere with existing knowledge, and (ii) result in the loss of

information that could become important again in the future, thereby reducing adaptability.

To systematically investigate these trade-offs, we propose three models, each corresponding to one of the

following challenges:

Model 1 addresses the need to forget parts of memory to create space for new learning (adaptability to

new situations).

Model 2 focuses on minimizing the negative impact of the interference caused by abrupt forgetting

(stability of existing knowledge).

Model 3 considers the risk of being unable to recall previously forgotten knowledge when it

becomes relevant (long-term adaptability).

By comparing these models, we aim to clarify how different forgetting mechanisms affect the balance between

adaptability and memory retention under resource constraints. Similar to existing models [5, 6], the proposed

MBON model uses Hebbian learning guided by DANs. The main difference is that the proposed model is based

on the kernel method and is designed to evaluate incremental learning under a fixed memory budget. Unlike

previous models, the designed approach does not use reward signals because learning is assumed to be driven

by the free-energy principle. Therefore, the model does not require a reinforcement learning environment.

Preliminary: Kernelized representation of MBONs

Although the $\alpha 3$ compartment is highly likely to employ anti-Hebbian learning, its functionality can also be

represented by a Hebbian learning model. Therefore, a novelty detector can be constructed using an active

neuron that is inhibited by a Hebbian learning-based odor detector. This study uses kernelized Hebbian

learning to represent the function in a simplified manner (more details are provided in the **Validity of**

analyzing Anti-Hebbian learning as Hebbian learning section). As discussed in **the Introduction**,

approximately 2000 KCs represent random feature vectors of the sensory inputs received by the MBONs

through synaptic connections. An odor activates approximately 5–10% of the 2000 KCs. These sparse feature

vectors are nearly orthogonal to one another. Thus, sensory inputs are projected onto a higher-dimensional

space through an orthogonal transformation, and MBONs process high-dimensional feature vectors for

classification or regression. A high-dimensional feature mapping $\Phi(\tilde{S}_1)$ and $\Phi(\tilde{S}_2)$, obtained from input

vectors $\tilde{S}_1$ and $\tilde{S}_2$ using a specialized nonlinear function $\Phi(\cdot)$, has a dot product $\Phi(\tilde{S}_1)^T \Phi(\tilde{S}_2)$ that is

represented by a reproducing the kernel function $K(\tilde{S}_1, \tilde{S}_2)$ [7]. One such kernel function is the Gaussian

kernel function defined as follows:

$$K(\tilde{S}_1, \tilde{S}_2) \equiv \exp\left(-\gamma \|\tilde{S}_1 - \tilde{S}_2\|^2\right), \qquad (1)$$

130 where γ is a coefficient that depends on the nonlinear function $\Phi(\cdot)$. Using this analogy, we modify the

131 multiplication involving the KC output vector $(\tilde{v})$. The synaptic weight matrix (W_{mbon}) is

132 approximated using the kernel function output as follows:

$$\mathbf{W}_{MBON}^T \tilde{v} \simeq \sum_i a_i K(\tilde{S}_i, \tilde{S}), \qquad (2)$$

where $\tilde{S}_i$ the i-th support input vector memorized by MBONs, and a_i is the output vector corresponding to $\tilde{S}_i$.

Hebbian and anti-Hebbian learning can be represented as adding or subtracting a target vector $(a_{target}\tilde{v})$ to or

from W_{MBON}. In the kernelized algorithm, this corresponds to adding or pruning the kernel function

$K(\tilde{S}_{target}, \cdot)$. We approximate this process using a kernel perceptron with a limited number of kernels bounded

by capacity (budget) B (Figure 1).

Fig. 1. MBON and its kernelized model. Upper: Schematic of the mushroom body output neuron $\alpha 3$. Lower:

Kernelized MBON model.

Shared structure of the three models: Supervised kernel learning model for the mushroom body $\alpha'3$

This study develops three MBON $\alpha3$ learning models that differ primarily in their pruning strategies. In this section, we describe the shared structure of the three models. Assume that the model learns $\{\tilde{\boldsymbol{S}}_p\}_{p=1}^{T}$ in an online manner, where $\tilde{\boldsymbol{S}}_p \in R^n$, $\tilde{\boldsymbol{S}}_p$ represents a generalized current sensory input vector. The MBON predicts an output vector $y \in R^m$. Notably, under ordinary circumstances, y should be $\dot{x}$; however, in this study, we set y as the class label to focus on MBON learning ability under a fixed budget. $\boldsymbol{y_t} = \left[y_t^{(1)}, \cdots, y_t^{(k)}, \cdots, y_t^{(m)}\right]^T$, where $y_t^{(k)} \in \{-1,1\}$.

The model output at time t is given by

$$f_{mbon}^{(k)}[\tilde{\boldsymbol{S}}] = \sum_{i \in S_t}^{B} w_i^{(k)} \sigma_{i,t} K(\tilde{\boldsymbol{S}_i}, \tilde{\boldsymbol{S}}) \qquad (3)$$

where B is the upper bound on the number of hidden units, and S_t is the support set [1] at time t. $\sigma_{i,t}$ is the decay (forgetting) ratio, where $\sigma_{i,t} \leq 1$. At each round, $\sigma_{i,t}$ is updated according to $\sigma_{i,t+1} = \phi_t \sigma_{i,t}$, where $\phi_t \leq 1$. If the decay ratio ϕ_t is significantly large, it can degrade $\boldsymbol{f}_{mbon}$ and reduce its accuracy. However, pruning old kernels without forgetting them (shrinking) also affects $\boldsymbol{f}_{mbon}$.

Learning samples are presented individually, and the model alternates between inference and learning, as shown in Figure 2. In each round, if at least one of outputs $f_{mbon}^{(k)}[\tilde{\boldsymbol{S}}]$ for $k = 1, \cdots, m$ is incorrect, a new unit (kernel) is added. If the total number of hidden units (kernel functions) exceeds B, one unit is removed. For example, the oldest unit is removed (Algorithm 1). Notably, the oldest unit j has the smallest $\sigma_{i,t}$ because, for all $i \in S_t$, $\sigma_{i,t}$ shrinks according to $\sigma_{i,t+1} = \phi_t \sigma_{i,t}$ in each round. Thus, the hidden unit with the smallest $\sigma_{j,t}$ is removed. Accordingly, the MBON model maintains the total number of hidden units at B. Performance is evaluated using cumulative error, as shown in Fig. 2. Note that the weight shrinkage $\sigma_{i,t+1} = \phi_t \sigma_{i,t}$ is executed only when at least one of the outputs $f_{mbon}^{(k)}[\tilde{\boldsymbol{S}}]$ for $k = 1, \cdots, m$ is incorrect. Thus, weight shrinking is omitted

---

[1] The support set is the set of kernels.

when the outputs are correct, consistent with the MBONα'3 behaviors reported by [2]. In this framework, the

dopaminergic neurons PPL1-α'3 — primarily activated by novel odors — regulate the weight adaptation of

the MBON.

Fig. 2. Inference and learning procedure

$$K(\tilde{S}_i, \tilde{S}) \equiv \exp\left(-\gamma \|\tilde{S}_i - \tilde{S}\|^2\right) \qquad (4)$$

Algorithm 1 Kernelized MBON learning Model 1

Require: current time t, new input $\tilde{S}_t$ support set $S_t(|S_t| \leq B)$, , activation threshold θ, pruning threshold ϵ (≥ 0), budget B, previous result $\boldsymbol{f}_{mbon\ t}$, and shrink ratio ϕ.
  Calculate $\boldsymbol{f}_{mbon\ t}[\tilde{S}_t]$ for all k defined by Eq. 3.

  receive $\boldsymbol{y}_t${Get label.}

  If $\prod_{k \in Outputs} y_t^{(k)} f_{mbon\ t}^{(k)}[\tilde{S}_t] \leq 0$ ***then* {=Trigger of Dopamine Neuron}**

   if $K(\tilde{S}_i, \tilde{S}_t) \leq \theta$ for all $i \in S_t$ then

    $S' = S_t \cup \{t\}, \quad \sigma' = 1$

    $\boldsymbol{W}' = \boldsymbol{y}_t$

    If $|S_{t+1}| \geq B$ then

      $p = argmin_i \sigma_i$

      If $\sigma_p < \epsilon$ then

        $S_{t+1} = S' \setminus \{p\}$ {Pruning the oldest kernel}

        $\sigma_{t+1} = \sigma', \quad \boldsymbol{W}_{t+1} = \boldsymbol{W}'$ {initialize $\boldsymbol{W_{t+1}}$}

      else

        $S_{t+1} = S_t$

      end if

    else

      $S_{t+1} = S', \quad \sigma_{t+1} = \sigma'$

      $\boldsymbol{W}_{t+1} = \boldsymbol{W}'$ {initialize $\boldsymbol{W_{t+1}}$}

    end if

   end if

   For all $i \in S_t$ do

     $\sigma_i = \phi\, \sigma_i$ {decay σ_i}

   end for

  end if

  $t = t + 1$

  return $\boldsymbol{f}_{mbon\ t}$

---

174 **Algorithm 2** Kernelized MBON learning Model 2: Modified Forgetron [3]

Require: current time t, new input $\tilde{\boldsymbol{S}}_t$, support set S_t ($|S_t| \leq B$), activation threshold θ, pruning threshold ϵ (≥ 0), budget B, U defined by Eq. 7, previous result $\boldsymbol{f}_{mbon\ t}$, and shrink-ratio ϕ

   Calculate $f_{mbon\ t}^{(k)}\left[\tilde{\boldsymbol{S}}_t\right]$ for all k defined by Eq 3.

   receive $\boldsymbol{y}_t$ {Get label.}

   If $\prod_{k \in Outputs} y_t^{(k)} f_{mbon\ t}^{(k)}\left[\tilde{\boldsymbol{S}}_t\right] \leq 0$ then **{=Trigger of Dopamine Neuron}**

     $S_{t+1} = S_t \cup \{t\}$

     $\sigma_{t,t} = 1$

     $\boldsymbol{W_{t+1}} = \boldsymbol{y_t}$ {initialize $\boldsymbol{W_{t+1}}$}

     $\phi_t = \phi$

     for all $i \in S_t$ do

       $\sigma_{i,t} = \phi_t \sigma_{i,t}$ {Decay $\sigma_{i,t}$}

     end for

     If $|S_{t+1}| \geq B$ then

       $p = argmin_i \ \sigma_{i,t}$,

       $S_{t+1} = S_{t+1} \setminus \{p\}$

     Else

       $S_{t+1} = S_t$

     end if

   $t = t + 1$

   return $\boldsymbol{f}_{mbon\ t}$

176 **Algorithm 3** Kernelized MBON learning Model 3: Least recently used (LRU)

Require: current time t, new input $\tilde{\boldsymbol{S}}_t$, support set $S_t (|S_t| \leq B)$, activation threshold θ, pruning threshold $\epsilon\ (\geq 0)$, budget B, U defined by Eq. 7, and previous result $\boldsymbol{f_{mbon\ t}}$, shrink ratio when misclassification is occurs ϕ, and shrink ratio when correct classification is occurs ϕ'.

Calculate $f_{mbon\ t}^{(k)}[\tilde{\boldsymbol{S}}_t]$ for all k defined by Eq 3.

receive $\boldsymbol{y}_t$ {Get label.}

If $\prod_{k \in Outputs} y_t^{(k)} f_{mbon\ t}^{(k)}[\tilde{\boldsymbol{S}}_t] \leq 0$ then {=**Trigger of Dopamine Neuron**}

  $S_{t+1} = S_t \cup \{t\}$

  $\sigma_{t,t} = 1$

  $\boldsymbol{W_{t+1}} = \boldsymbol{y_t}$ {initialize $\boldsymbol{W_{t+1}}$}

  If $|S_{t+1}| \geq B$ then

    $p = argmin_i\ \sigma_{i,t}$,

    $S_{t+1} = S_{t+1} \setminus \{p\}$

  Else

    $S_{t+1} = S_t$

  end if

  for all $i \in S_t$ do

    $\sigma_{i,t} = \phi\sigma_{i,t}$ {Decay $\sigma_{i,t}$}

  end for

else

  $winner = argmax_j K(\tilde{\boldsymbol{S}}_j, \tilde{\boldsymbol{S}}_t)$

  $\sigma_{winner,t} = 1$

  for all $i \in S_t$ do

    $\sigma_{i,t} = \phi'\sigma_{i,t}$ {Decay $\sigma_{i,t}$}

  end for

end if

$t = t + 1$

return $\boldsymbol{f_{mbon\ t}}$

Three MBON models

Model 1

The first model removes the oldest kernel whose σ_i is less than θ when $|S_t| \geq B$. Thus, if σ_i of

the oldest kernel is larger than θ, the MBON model does not learn to recognize the current

input. Therefore, if *Drosophila* frequently encounters a novel sample, the MBON model often

ignores it. The pseudocode is presented in Algorithm 1.

This model detects the oldest kernel via weight shrinking and removes it to create space for learning new

samples. However, removing the oldest kernel may cause a significant increase in cumulative error if the

kernel remains important for ongoing tasks. Therefore, the threshold θ should be set appropriately to balance

the trade-off between adaptability to new situations and the stability of existing knowledge.

Model 2: Forgetron

189 We designed a model based on a slightly modified Forgetron [3]. The Forgetron is a kernel perceptron learning

190 machine [8-12] that introduces a weight-shrinking (forgetting) mechanism. The Forgetron removes the oldest

191 kernel whose σ_i is the smallest in S_t. Although the Forgetron does not ignore any novel samples, removing the

192 oldest kernel increases cumulative error. The basic Forgetron [3] selects Φ_t to balance these effects.

193
$$\phi_t = \min\{(B+1)^{1/(2(B+1))}, U/\|f'_{mbon\ t}\|\} \quad (5)$$

194 Here,

195
$$f'_{mbon\ t} \equiv f_{mbon\ t} + y_t K(\tilde{S}_t, \cdot), \quad (6)$$

196 and

197
$$U = \frac{1}{4}\sqrt{\frac{B+1}{\log(B+1)}}. \quad (7)$$

In the original Forgetron, the number of outputs is one. However, in this study, it is extended to

multiple outputs. Accordingly, ϕ_t in Eq. 5 is not optimal. To overcome this problem, the value of ϕ_t

that minimizes the cumulative error is selected through computational simulations. Therefore, the

Model2 fixes ϕ_t to a certain value. This simplification is also suitable as the model for forgetting in

biological brain[1][34]. Weight reduction in Forgetron (Model 2) is slightly different from that in

Model 1. In Model 1, weight shrinkage is used to detect the age of the oldest kernel. If the weight of the

oldest kernel is less thanθ, it gets removed. In Forgetron, weight shrinkage is used to detect the oldest

kernel; however, it is not used to decide whether to remove the oldest kernel. The oldest kernel is

removed when the capacity is full. Instead, weight shrinkage reduces the negative impact of removing

the oldest kernel.

The model was theoretically analyzed in detail (see **Method**), and the results show that the weight-

shrinking mechanism helps reduce the mistake bound of incremental learning on a fixed budget.

Therefore, when Forgetron is used as a model for MBON learning, the forgetting strategy in MBON is

essential for learning under limited capacity. The pseudocode is presented in Algorithm 2.

Model 3: Least Recently Used

Both Models 1 and 2 prune the oldest kernel when $|S_t| \geq B$. However, age does not always equate to

uselessness. Often, the kernels that contribute the least are those used least. If the environment

remains stable, the kernels that are accessed least recently are likely to remain rarely used; therefore,

it is reasonable to remove the least recently used kernels. To this end, Model3 resets σ_{it} to its initial

value whenever the i-th kernel shows the maximum activation among all kernels, provided that the

model's output is correct. Consequently, the the σ_{it} of the least recently used kernel eventually reaches

the minimum value. The pseudocode is presented in Algorithm 3. Note that Model3 employs a

spontaneous shrinking mechanism to estimate kernel usage frequency. It reduces weight regardless of

output accuracy, using a shrink-ratio ϕ' such that $\phi < \phi' \leq 1$. The model was also theoretically

analyzed in detail (see **Method**), and the results showed that mean lifetime (the time interval between

the kernel addition and pruning) of each kernel was extended. However, the pruned kernel in the

Model3 is not always the oldest one; therefore, Model3's damage due to pruning is sometimes larger

than that of Model2. For this reason, the number of mistakes for the Model3 is not always lower than

that of Model2.

Computer simulation

In this section, we describe the experiments conducted to evaluate model performance in changing

environments. These simulations demonstrate that forgetting plays an essential role in reducing

cumulative error. The **Method** section presents a theoretical analysis of the proposed models,

including the derivation of the crucial shrinkage ratio, which governs their behavior. As the

experimental settings differ from theoretical assumptions, the optimal shrinkage ratio is determined

empirically. Specifically, since a theoretical proof in such a complex environment has yet to be

achieved, we experimentally derive the optimal value for the shrink ratio. First, we outline the

assumed environments and their Markov chain formulations. Next, we explain the evaluation

procedure used to assess the shrinkage effect in each model. Finally, experimental results are

presented.

Assumed environments and their Markov chain model

In this section, we describe the assumed environments and their Markov chain models. To predict the

sensory inputs from KC outputs, the model must capture the changes in sensory inputs. Sensory

inputs are mainly affected by animal actions. Several researchers have investigated the walking

patterns of *Drosophila* [13,14] and reported continuous changes in the walking patterns. Accordingly,

a model has been developed to generate continuous walking patterns [13], and a Hierarchical Hidden

Markov model (HHMM) is used for its analysis [14]. The modeled HHMM shows significantly simpler

patterns. Although the model consists of two-layered HMMs, each layer is described by one-

dimensional chains of several states. Thus, each state is connected only to its two nearest-neighbor

states due to the continuously changing patterns.

Sensory input patterns from KCs are also affected by animal actions. Therefore, sensory input

patterns are represented by the HHMM (derivation is provided in the **Hidden Markov model of**

Kenyon cells' outputs section). We use a Markov chain model to generate environmental changes. For

simplicity, we assumed a single-layered Markov chain model to evaluate the performance of each model.

Therefore, for a five-dimensional generalized sensory input at time t, $\tilde{\boldsymbol{S}}_t$ is generated from a multivariate

normal distribution whose covariance matrix is $\Sigma = diag(0.01)$.

254
$$\tilde{\boldsymbol{S}}_t \sim N(\boldsymbol{m}(e_t), \Sigma), \quad e_t \sim p(e|e_{t-1}) \tag{8}$$

255 Here, e_t denotes the current state, and $e_t \in \{e_1, e_2, \cdots e_{40}\}$. $\boldsymbol{m}(e_t)$ denotes the mean vector for the

256 current state and is a fixed random vector defined for each e_i ($i = 1, 2, \cdots, 40$). Each cluster center

257 $\boldsymbol{m}(e_i)$ is generated from the uniform distribution as follows:

258
$$\boldsymbol{m}(e_i) \sim U([0,1]^5) \tag{9}$$

259   However, if the cluster centers are in proximity to each other, classification becomes difficult.

260   Therefore, we regenerate the cluster centers until the minimum distance between each pair of cluster

261   centers exceeds 0.5. The number of states is set at 40 to ensure that the classification task requires a

262   memory larger than the budget size of each model. State change is defined using a staying state

263   probability p function as follows:

264
$$p(e_i|e_j) \equiv \begin{cases} p & i = j \\ \frac{1-p}{2} & i \neq j \end{cases} \qquad (10)$$

Here, $p(e_i|e_j)\ i \neq j$ is adjusted to fit a real environment, and $p(e_i|e_j) = p(e_j|e_i)$ is set for

simplification. This setting is sufficient to evaluate learning performance. Further, we generate nine

types of synthetic datasets with $p = 0.1, 0.2, 0.3, \cdots, 0.9$. The size of each dataset is 2000. For each $\tilde{\boldsymbol{S}}_t$,

50 different datasets are prepared, as shown in Fig. 3. In each dataset, each $\tilde{\boldsymbol{S}}_t$ is stored together with

its corresponding state vector $y_i = OneHot(e_i)$, which serves as its label. To fit kernel perceptron

learning, the k-th element of y_i is $y_i^k \in \{-1,1\}$. During the computer simulation, the pairs $(\tilde{\boldsymbol{S}}_t, y_i)$ are

presented to each model.

Evaluation Method

274   Experiments were repeated at different state-change rates. The cumulative error, which is obtained by

275   summing the differences between the training output and correct labels, was used as an evaluation

276   measure, as in Eq. 11. The experiment was performed to evaluate the MBON model described in a

277   previous study.

279   **Kernelized incremental learning on a budget as a model of the MBON α3 neuron**

280

Fig. 3. Distributions used in the experiments. Here, p denotes the probability of the steady state, q

denotes the state change probability, and $p + 2q = 1$.

For all models, the single-output model was extended to a multiple-output model for the

experiments. The multiple outputs used during the simulation were one-hot representations of the

predicted labels of the current input vector x(t). Therefore, the cumulative error was modified for

each round as follows:

287
$$cumerror += \begin{cases} 1 & y \neq argmax_i f^i_{MBON,t}(\boldsymbol{x_t}) \\ 0 & otherwise \end{cases} \qquad (11)$$

Simulation Results

289 The shared network size, input size, kernel size, and output size were set to 5, 20, and 40, respectively.

290 Various shrinkage ratios were examined to evaluate the effects of weight shrinkage (forgetting)[2].

An example of model behaviors

An example of the cumulative errors of MBON Models 1, 2, and 3 and their competitors (with and

without weight shrinkage) at $p = 0.9$ is shown in Fig. 4. The shrinkage ratio ϕ was set to 0.64, where

the mean cumulative error was approximately minimal for the three models.

During testing, the budget of all models was set to 20, and γ was set to 4.0. The parameter used in

Algorithm 1 for Model 1 was set as $\theta = 0.1$. Therefore, the pruning condition for Model 1 was set as $\sigma_p <$

0.0001.

In this example, the cumulative error order was Model 3 < Model 2 < Model 1. The cumulative

error for Model 1 was larger than that for Models 2 and 3. The performance of each model is detailed

in the next section.

---

[2] From Theorem 1 and its proof, we determine ϕ using Eq 23. However, in this simulation setting, the MBON model has 40 outputs, which does not directly correspond to the Theorem. Therefore, we examine various values of ϕ in the simulation.

Model 1 sensitivity to weight shrinkage

To evaluate the effect of weight shrinkage (forgetting), the final cumulative errors after learning

2000 samples were calculated for Model 1. Points representing the cumulative error of Model 1 under

various weight-shrinkage conditions are shown in Fig 5. The kernel size and budget size were set to

20, and the kernel pruning condition was set at $\sigma_p < \epsilon$, where ϵ = 0.01, 0.001, and 0.0001. In Fig. 5,

the x-axis represents the shrinkage ratio, while the y-axis represents the mean cumulative error after

learning 2000 samples. For each shrinkage-ratio condition, 50 trials were conducted for each of the 90

state-change rates ($p = 0.1, 0.11, \cdots, 0.99$), resulting in 4500 trials. Simulation results (Fig. 5) show a

convex curve; therefore, an optimal shrinking coefficient exists at the minimum for each situation,

which are around $\phi = 0.6 \sim 0.8$. Thus, an appropriate weight shrinkage ratio exists to minimize

cumulative errors. Model 1 cannot prune any kernel when σ_p is larger than ϵ. Therefore, cases in which

Model 1 could not learn the new samples were observed. Therefore, large cumulative errors were

observed for a small value of ϕ when ϵ = 0.0001 and 0.001. The differences between these results are

shown in Fig. 7.

Fig. 4. Example of cumulative error vs number of observations (*Budget* = 20, *p* = 0.3) for Models

1, 2 (Forgetron), and 3 (Forgetron with LRU).

Fig. 5. Sensitivity of Model 1 to weight shrinkage after learning 2000 samples. Pruning threshold

ranges from ϵ = 0.01 to 0.0001.

Model 2 (Forgetron) sensitivity to weight shrinkage

Further, we evaluated the effect of weight shrinkage (forgetting) on Model 2 (Forgetron). Similar to the

previous section, the cumulative errors after learning 2000 samples were analyzed. The cumulative

error for each shrinkage ratio is shown in Fig. 6. Under all conditions, the cumulative errors were

minimal for ϕ = 0.64−0.77.

Fig. 6. Model 2 (Forgetron) sensitivity to weight shrinkage after the learning of 2000 samples.

State stay rate: p = 0.1 to p = 0.9. The errorbars denote 95% confidence intervals.

Model 1 vs Model 2 (Forgetron)

We compared the performance of Models 1 and 2 (Forgetron). Similar to the previous sections, the

cumulative errors after learning 2000 samples were analyzed. The cumulative error of Models 1 and 2

with pruning threshold ϵ = 0.05, 0.001, and 0.0001 is shown in Fig. 7.

Fig. 7. Comparison of cumulative errors between Models 1 and 2 after learning 2000 samples.

The pruning threshold of Model 1 is ϵ = 0.01, 0.001, and 0.0001. The errorbars denote 95% confidence

intervals.

The cumulative error of Model 2 was partly identical to that of Model 1. However, the cumulative

errors of Model 1 were larger than those of Model 2 in most cases where the pruning threshold ϵ was

small. Thus, Model 1 cannot prune any kernels when σ_p is consistently larger than ϵ.

Model 3: LRU vs Model2 (Forgetron)

We conducted a comparative study between Model 2 (Forgetron) and Model 3 (Forgetron with LRU).

The cumulative errors after learning 2000 samples were analyzed by sweeping the shrink ratio in the

interval [0.7,0.8],where the cumulative error of Model2 is nearly minimum. The cumulative error

points for (*Model* 2*, Model* 3) are shown in Fig. 8. The points below the line $y = x$ indicated that the

cumulative errors of Model 3 were smaller than those of Model 2. The distribution of points was

slightly more concentrated on the lower side. Specifically, the proportion of points below $y = x$ was

varied depending on the spontaneous shrink ratio ϕ'. For example, in the case of $\phi' = 0.99$, 82.7% of

the 550×9 trials (9 variations in stay probability: 0.1, 0.2 ···0.9). But the ratio was reduced when

ϕ' is closed to 1(see Table1). Thus, the LRU strategy performed relatively better than Model 2

(Forgetron). However, the LRU model predicted the future usage of each memory based on its past

usage history. The prediction was sometimes incorrect owing to variations in the inputs. In such cases,

the cumulative error in Model 3 increased. Moreover, the removed kernel was not necessarily the

oldest kernel; therefore, the impact of its removal was greater than that in Model 2.

Fig. 8. Comparison of cumulative errors between model2 (Forgetron) and model3 (Forgetron with LRU) after learning 2000 samples. Shrink ratio was sweeped from 0.7 to 0.8, where the cumulative error of model2 is nearly the smallest. The spontaneous shrinkratio was $\phi' = 0.99$ (left) and 0.9999(right). For $P \in \{0.9, 0.7, 0.5, 0.3, 0.1\}$, the proportions of points below $y = x$ across 550 trials were 57.2%, 76.7%, 84.9%, 92.7% and 93.8% for the left case, whereas these proportions were 36%,58.5%,73.6%,90.7% and 94.5% in the right case, respectively.

366   Table.1. Proportion of Model 3 superiority vs. spontaneous shrink ratio

ϕ'	P=0.1	P=0.2	P=0.3	P=0.4	P=0.5	P=0.6	P=0.7	P=0.8	P=0.9	average
ϕ'=0.99	0.94	0.96	0.93	0.96	0.85	0.80	0.77	0.66	0.57	0.83
ϕ'=0.999	0.95	0.97	0.91	0.92	0.75	0.69	0.61	0.50	0.41	0.75
ϕ'=0.9999	0.95	0.95	0.91	0.90	0.74	0.68	0.59	0.46	0.36	0.73

Discussion

Relationships with other approaches

We constructed the kernelized MBONα'3model to explain its need for forgetting in novelty detection

and learning. This model is not related to reward signals. However, almost all previous MBON models

are related to reward signals [15,16]. A new model [17] developed to predict olfactory learning in

Drosophila was used to predict the aversive or appetitive valences of odors. The model did not follow

the free energy principle proposed previously by Friston et al. [18]. Instead, the design principle was

based on reducing unfamiliar situations.

In existing literature [16,17], two models have been designed based on the behavior of MBONα3

and novel detection mechanisms. Researchers have developed models based on the prediction of

agreeable stimuli [17]. Such models do not follow the free-energy principle [18]. Instead, the design

principle is based on reducing surprise. Therefore, such models were designed to fit empirical data.

In this study, the model was designed using a learning algorithm with a fixed budget. The proposed

model was used to analyze the error bound under a fixed budget. Therefore, the results did not

directly address the two models [16,17] but instead presented new insights into MBON models from

the perspective of minimizing cumulative errors under a fixed budget.

Three forgetting models were considered for this study. However, another possibility was

emphasized. Forgetting redundant memory serves as a second possible approach. Existing MBON

models [15,16] are based on reward signals. A general model was proposed for MBON $\alpha 3$ and other

areas. From the perspective of behavior, the activity of MBON$\alpha'3$ was not directly related to reward

signals.

Biological relevance of the three models

Three candidate MBON models with different kernel-pruning strategies have been discussed.

However, additional behavioral experiments are required to determine the most appropriate model.

Based on the model error counts, Models 2 and 3 perform excellently. This section discusses the

application of the obtained results to the *Drosophila* brain.

Model 1 vs Model 2

To compare the performances of Models 1 and 2, an overloaded learning task was designed, in

which more than 20 odors were sequentially presented in our simulations.

Theoretically, if MBON learning in *Drosophila* follows Model 1, the system would ignore novel

odors after presenting approximately 10–20 odors without rest. Conversely, if the learning follows

Model 2, *Drosophila* should continue to respond to novel odors even after extensive learning. From the

perspective of the free energy principle [18],   Model 2 served as a more plausible approach than

Model 1.

Our simulation results demonstrated that Model 1 terminated learning when novel odors were

presented, leading to higher prediction errors. In contrast, Model 2 maintained a larger set of learned

odors, which allowed the system to better predict incoming sensory inputs. The experimental results

shown in Fig 7 also clearly suggest that the cumulative error of Model 2 is significantly lower than that

of Model 1. In summary, while these findings demonstrate the superior predictive performance of

Model 2, further behavioral studies are required to confirm whether actual *Drosophila* learning aligns

with the dynamics of Model 2.

Model 3 vs Model 2

Model 3 incorporates the LRU pruning strategy. In our simulations, a subset of previously learned

odors was presented intermittently during a novel-odor learning task. To discuss which model is more

appropriate, we must consider actual *Drosophila* behavior. For instance, when a fly shows alerting

behaviors to a frequently presented old odor, this pattern is consistent with Model 2. Conversely, if the

fly does not show such behaviors, its learning potentially follows Model 3. Experimental results in Fig

8 suggest that Model 3 outperforms Model 2 when the state-staying probability is small. While Model

3 showed superior average performance in our simulations, the biological validity of these models

should be evaluated based on future observations of real *Drosophila* behaviors.

Comparison between the results of theoretical analysis and computer simulations

Our sensitivity analysis demonstrates that the model effectively manages to minimize the cumulative errors

when an appropriate shrink ratio is applied. Importantly, these empirical results are consistent with our

theoretical findings, which guarantee the existence of a unique optimal shrink ratio ϕ_* within the interval

$(0, 1)$.

Validity of learning without the reward signal

MBONα3 neurons are activated by novel odor stimuli. Although existing computational models for

MBONs are usually based on reinforcement learning, they are unsuitable for MBONα3 neurons. Since

a novel stimulus cannot be guaranteed to be associated with a reward, an MBON model is proposed

without explicit reward signals.

We assume that MBONα3 behaviors can be determined following the free-energy principle

proposed by Friston et al. [18,19]. For instance, Isomura [20] adopted the free-energy method and

provided a statistical interpretation. The free-energy principle is used to model biological behavior

under the biologically inferred assumption that actions and learning are performed to reduce

surprises or unexpected situations. Interestingly, free-energy-principle-based computational models

do not always assume the presence of reward signals.

In the free-energy method, biologically inferred learning systems are assumed to maximize.

$$p(\tilde{S}, \boldsymbol{u}, \boldsymbol{\theta}) \;=\; p(\tilde{S}|\boldsymbol{u}, \boldsymbol{\theta})p(\tilde{x}|\tilde{v}, \boldsymbol{\theta})p(\boldsymbol{\theta}), \tag{12}$$

439   where $\tilde{S}, \boldsymbol{u} = (\tilde{x}, \tilde{v})$, and $\boldsymbol{\theta}$ denote a generalized sensory input vector, generalized hidden state vector, and

440   parameter vector, respectively[3].

442   Although the system is assumed to minimize surprises, defined as $S =$

443    $-\log\left(\int p(\tilde{S}|u, \theta)du d\boldsymbol{\theta}\right)$, the direct minimization of S is difficult to execute. Practically, surprises

444   can be reduced by minimizing the free-energy function [21].

$$F \;\equiv\; E_q(\boldsymbol{u}, \boldsymbol{\theta})[-\log p(\tilde{S}|\boldsymbol{u}, \boldsymbol{\theta})] \;+\; D_{KL}[q(\boldsymbol{u}, \boldsymbol{\theta}) \;\|\; p(\boldsymbol{u}, \boldsymbol{\theta}|\tilde{S})], \tag{13}$$

where $D_{KL}()$ is the Kullback–Leibler divergence, $q(u, \theta)$ denotes a recognition distribution,

and $p(\boldsymbol{u}, \boldsymbol{\theta}|\tilde{S})$ denotes a true u distribution.

Under the free-energy principle, we assume the existence of a generative model that represents

$p(\tilde{S}|\boldsymbol{u}, \boldsymbol{\theta})$. MBONs exhibit backward connections to the antennal lobe (AL) [22]. The backward

connections can be represented in the generative model $p(\tilde{S}|\boldsymbol{u}, \boldsymbol{\theta}) = N(g(\boldsymbol{u}, \boldsymbol{\theta}), \Sigma_s)$ of the *Drosophila*

brain (Fig. 9).

The MBONα3 neuron is assumed to be a part of the generative model for the hidden-state vector

$p(\tilde{x}|\tilde{v}, \theta) \;=\; N(f(\tilde{x}, \tilde{v}, \theta), \Sigma_x)$, where the cause $\tilde{v}$ is assumed to be the output vector from KCs.

---

[3] $\tilde{s} = (s, s', s'', \cdots), \tilde{x} = (x, x', x'', \cdots)$ and $\tilde{v} = (v, v', v'', \cdots)$

Fig. 9. Connectivity of mushroom body output neurons and the free-energy principle. (Extended figure in [23]).

Hebbian learning minimizes free-energy

We assume that $f(\tilde{x}, \tilde{v}, \theta) \equiv sigmoid(W_{MBON}^T u)$, where W_{MBON} denotes the weight vector of the MBON $\alpha 3$ neuron. The change in W_{MBON} can be denoted as a Hebbian learning function, described as [21,24]

$$\Delta W_{MBON} \propto sigmoid'(W_{MBON}^T u)\xi_x u, \quad (14)$$

where ξ_x denotes the output from an error-coding neuron [18,21][4]. Although we assume that the model is a single-layer network, actual MBONs exhibit multi-layered structures [1]. Thus, the model can be improved to a multi-layered version as [24].

According to existing literature [2], MBON$\alpha 3$ outputs are adjusted by anti-Hebbian learning, which is triggered by the activation of $\alpha 3$ dopaminergic neurons. Assuming that anti-Hebbian learning can be reformulated as Hebbian learning, and that activation of $\alpha 3$ dopaminergic neurons represents ξ_x in Eq. 14, then MBON$\alpha 3$ neurons can acquire learned outputs from KCs to reduce free energy.

If the learning model does not recognize the current stimulus, the surprise term increases. Consequently, the model attempts to learn to recognize the current stimulus and restore recognition. Thus, the system should encode the current stimulus.

---

[4] Strictly speaking, we have to consider the integral of $sigmoid'(W_{MBON}^T u)\xi_x u^T$ from $t = 0$ to t to derivate the change in the parameters. Moreover, the gradient of a prior distribution $p(W_{MBON})$ is also should be included. However, these operators are omitted for simplicity.

Methods

In Eqs. 3 and 15, $\sigma_{j,t}$ denotes a decay term such that $\sigma_{jt} \leq 1$. Generally, σ_{jt} is assumed to decrease at each round at a certain ratio, thereby gradually reducing the output value of the MBON model. The old kernel exhibits the smallest σ_{jt}. Thus, we can remove the oldest kernel by identifying the kernel with the smallest σ_{it} value. However, the same result can be achieved by simply removing the oldest kernel without shrinking the weights. The differences between the two methods—removing the oldest kernel with and without forgetting—were analyzed to clarify the effects of shrinkage (forgetting).

Simplification of the proposed model

To theoretically assess the incremental learning capacity under a budget constraint, we adopted the theoretical analysis of the Forgetron proposed by Dekel et al. [3]. Accordingly, we simplified the developed model without losing generality. The multidimensional output of the model was switched to one-dimensional output.

The learning samples consisted of input vectors $\boldsymbol{x_t} \in R^n$ and the corresponding label vectors $y_t \in \{-1, +1\}$. When the model predicted the correct label, the current input vector $\boldsymbol{x_t}$ was not regarded as a novel input (a new kernel was not allocated). Thus, the model was simplified to a kernel perceptron.

$$f_{MBON,t} \equiv \sum_{j=1}^{B} w_j \sigma_{j,t} K\left(x_j, \cdot\right), \tag{15}$$

where $K\left(x_j, \cdot\right)$ is an infinite-dimensional vector converted from x_j, and B denotes the upper bound of the number of kernels. Notably, $f_{MBON}(x) = \langle f_{MBON}, K(x, \cdot) \rangle$, where $\langle \cdot, \cdot \rangle$ denotes dot product operation. Similar to the proposed model, f_{MBON} learns samples $X = [x_t, y_t]^T$ online. In this analysis, f_{MBON} was evaluated using a *hinge-loss* function.

$$l(f; (x, y)) \equiv \begin{cases} 0 & \text{if } yf(x) \geq 1 \\ 1 - yf(x) & otherwise \end{cases} \tag{16}$$

The kernel perceptron alternately executed inference and learning, as shown in Fig. 2. The learning was performed to minimize the cumulative error (number of mistakes).

Mistake bound of removing the oldest kernel with forgetting

We considered the mistake bound of the kernel perceptron by removing the oldest kernel while

forgetting. Dekel et al. [3] demonstrated the mistake-bound M in Theorem 6.2 in their manuscript.

However, Theorem 6.2 should be satisfied under the condition $B \geq 83$, which is much larger than the

estimated capacity of MBON:20. Therefore, the more general mistake bound presented in Lemma 5.2

was used [3]. Moreover, the original Forgetron uses adaptive shrink ratio. In this study, we assume

that the shrink ratio is fixed to align with the biological simplicity of dopaminergic forgetting

mechanisms in the Drosophila brain [1][34]. In our previous study, we used this lemma to analyze the

mistake bounds of the MBON model [4]. As the analysis in the previous study lacked rigor, we

reanalyzed the model in this study. The following assumptions were made:

- Let g be a desired competitor function in the Hilbert space H_k such that $|g| \leq U$,
  where U is defined in Eq. 7.

- Let $\phi_t \leq 1$ be the shrinking coefficient for $\sigma_{i,t}$.

- Let $(x_1, y_1), \cdots, (x_T, y_T)$ be a sequence of examples such that $K(x_t, x_t) \leq 1$ for all t.

- Let J be a set of examples in which f_{MBON} mistakes the predicted label $J =$
  $\{t | y_t f_{MBON}(x_t) < 0\}$.

- Let $f'_{MBON,t} = f_{MBON,t}(x) + y_t K(x_t, \cdot)$

- Let $f''_{MBON,t}$ be $f''_{MBON,t} = \phi_t f'_{MBON,t}$.

- Ψ_t be the magnitude of loss due to pruning the old kernel and

$$\Psi_t \equiv \begin{cases} \psi\left(\sigma_{r_t,t+1}, y_{rt} f''_{MBON,t}(x_{rt})\right) & \text{if } t \in J \wedge |S_t| = B \\ 0 & \text{otherwise} \end{cases}, \qquad (17)$$

where $\Psi(\lambda, \mu) \equiv \lambda^2 + 2\lambda - 2\lambda\mu$, and the suffix r_t denotes the removed kernel at t. Then, the number of

mistakes of f_{MBON} satisfies the following inequality.

$$M - \left(\|g\|^2 \log\left(\prod_{t \in J} \frac{1}{\Phi_t}\right) + \sum_{t \in J} \Psi_t\right) \leq \|g\|^2 + 2\sum_{t=1}^{T} l_t^*, \qquad (18)$$

where g denotes the desired competitor function; $l_t^* = l(g; (x_t, y_t))$. A detailed derivation of Eq. 18 is

presented in a previous study [3]. From the results, M is larger than the mistake bound of the original

kernel perceptron, which does not use shrinking or pruning kernels: $M \leq \|g\|^2 + 2\sum_{t=1}^{T} l_t^*$.

In basic Forgetron (described in Fig. 5.1 of [3]), Φ_t is adaptively controlled such that Φ_t is variable. By

adapting Φ_t, Dekel et al. [3] showed that the number of prediction mistakes of the basic Forgetron is

bounded as $M \leq \|g\|^2 + 4\sum_{t=1}^{T} l_t^*$. To investigate the real duty of forgetting in the *Drosophila* MBON,

we assumed that the value of Φ_t be fixed to $\phi \leq 1$ for all t. To evaluate the mistake bound with a

constant shrink ratio ϕ , we start by estimating the deviation from the adaptive Φ_t used in Dekel et al.

[3] This estimation, as shown in the following Lemma 1, provides the basis for our subsequent proof.

Lemma 1. *Using a shrink ratio $\phi < 1$, Φ_t can be defined as*

530
$$\Phi_t \equiv \begin{cases} 1 & if\ t \in J_1 = \{t \in J; \phi\|f_t'\| \geq U\} \\ \phi & if\ t \in J_2 = \{t \in J;\ \|f_t'\| \leq U \wedge \phi\|f_t'\| < U\} \\ \dfrac{\phi\|f'\|}{U} & if\ t \in J_3 = \{t \in J;\ \|f_t'\| > U \wedge \phi\|f_t'\| < U\} \end{cases}$$

$, -\log\phi \geq -\log\Phi_t$

Proof. Since $\phi < 1$, $\log\Phi_t = 0$, where $t \in J_1$; $\log\Phi_t = \log\phi$ when $t \in J_2$; $\log\Phi_t = \log\phi + \log\frac{\|f'\|}{U}$ when $t \in J_3$.

$\log\Phi_t \geq \log\phi$. Thus, $-\log\phi \geq -\log\Phi_t$. $\square$

Notably, the MBON model reduces the mistake bound when $\phi < 1$, and shrinking (forgetting) is

essential to maintain the mistake bound low.

By using $\| g \| \leq U$ and $|J| \leq T$, we derive the lemma.

Lemma 2. *ϕ denotes the shrinking coefficient for the decay ratio of $\sigma_{i,t}, \forall i \in S_t$,*

and $0 \leq \phi \leq 1$. $U = \frac{1}{4}\sqrt{\frac{B+1}{\log(B+1)}}, \epsilon \geq 0$ The number of mistakes M is bounded by

539
$$M \leq \frac{\|g\|^2 + 2\sum_{t=1}^{T} l_t^*}{1 + \|g\|^2 \log\phi - (\phi^{2B} + 2(1+\epsilon)U\phi^{B+1} + 4\phi^B)}. \tag{19}$$

540   *Proof.* Since $\sigma_{r_t, t+1} = \phi^B$, Ψ can be rewritten as follows:

541
$$\Psi\left(\sigma_{r_t, t+1}, y_{r_t} f_t''(x_{r_t})\right) = \phi^{2B} + 2\phi^B - 2\phi^B y_{r_t} f''(x_{r_t})$$

From the Cauchy–Schwarz inequality, $\left|f_t''(\boldsymbol{x}_{r_t})\right| \le \|f_t''\| \cdot \left\|K(\boldsymbol{x}_{r_t},\cdot)\right\|$. Here, $\|f_t''\| =$

$\left\|\phi \cdot \left(f_t' + y_t k(\cdot, x_t)\right)\right\| \le \phi\|f_t\| + \|k(\cdot, x_t)\|$. Under a fixed shrink ratio ϕ, there are possibilities that

$\|f_t\| > U$. Thus, $y_{r_t} f''(\boldsymbol{x}_{r_t}) \le \phi(1+\epsilon)U + 1$ when $y_{r_t} f''(\boldsymbol{x}_{r_t}) > 0$ and $y_{r_t} f''(\boldsymbol{x}_{r_t}) \ge -\phi(1+\epsilon)U - 1$

when $y_{r_t} f''(\boldsymbol{x}_{r_t}) < 0$, where $\epsilon \ge 0$. Therefore, we

can rewrite the expression as follows:

$\Psi\left(\sigma_{r_t,t+1}, y_{r_t} f_t''(\boldsymbol{x}_{r_t})\right) \ge \phi^{2B} + 2\phi^B - 2\phi^B(\phi(1+\epsilon)U + 1)$ when $y_{r_t} f''(\boldsymbol{x}_{r_t}) > 0.$,

$\Psi\left(\sigma_{r_t,t+1}, y_{r_t} f_t''(\boldsymbol{x}_{r_t})\right) \le \phi^{2B} + 2\phi^B + 2\phi^B(\phi(1+\epsilon)U + 1)$ when $y_{r_t} f''(\boldsymbol{x}_{r_t}) < 0.$

Clearly, $\phi^{2B} + 2\phi^B + 2\phi^B(\phi(1+\epsilon)U + 1) > \phi^{2B} + 2\phi^B - 2\phi^B(\phi(1+\epsilon)U + 1)$

$\because 2\phi^B(\phi(1+\epsilon)U + 1) > 0$

After all, $\Psi\left(\sigma_{r_t,t+1}, y_{r_t} f_t''(\boldsymbol{x}_{r_t})\right) \le \phi^{2B} + 2\phi^B + 2\phi^B(\phi(1+\epsilon)U + 1)$

From Lemma 1, we rewrite Eq. 18 as follows:

$$M \le \|g\|^2 + 2\sum_{t=1}^{T} l_t^* + \left(\|g\|^2 \sum_{t \in J}(-\log \Phi_t)\right) + \sum_{t \in J} \Psi_t \qquad (20)$$

$$\le \|g\|^2 + 2\sum_{t=1}^{T} l_t^* + \left(\|g\|^2 \sum_{t \in J}(-\log \phi_t)\right) + \sum_{t \in J} \Psi_t$$

555   where the right-hand side is also bounded by

556    $\|g\|^2 + 2\sum_{t=1}^{T} l_t^* + \left(\|g\|^2 \sum_{t \in J}(-\log \phi_t)\right) + \sum_{t \in J} \Psi_t$

557    $\le \|g\|^2 + 2\sum_{t=1}^{T} l_t^* + M(-\|g\|^2 \log \phi) + M(\phi^{2B} + 2\phi^B + 2\phi^B(\phi(1+\epsilon)U + 1)).$ (21)

558   Here, Eqs. 20 and 21 yield

$$M \le \frac{\|g\|^2 + 2\sum_{t=1}^{T} l_t^*}{1 + \|g\|^2 \log \phi - (\phi^{2B} + 2(1+\epsilon)U\phi^{B+1} + 4\phi^B)}. \qquad (22)$$

$\square$

The denominator of the right-hand side of Eq. 22 depends on ϕ. Thus, we can optimize ϕ to minimize

the mistake bound. The upper bound of the number of mistakes is minimized when ϕ is set to a

certain value, as shown in Theorem 1. An example of the relationship between ϕ and the mistake

bound is shown in Fig 10. From Lemma 2, we obtain Theorem 1.

Theorem 1. Let f_{MBON} be a kernel perceptron with a budget B and a fixed shrinking coefficient ϕ for

the decay of σ_{it} ($\forall i \in S_t$). Assuming ; $T > B$, and $U = \frac{1}{4}\sqrt{\frac{1+B}{\log(1+B)}}$, there exists an optimal shrinking

coefficient ϕ_* in the interval $0 < \phi_* < 1$ that minimizes the upper bound of the number of mistakes

made by f_{MBON}.

Fig. 10. Example of a rough relationship between the shrinking coefficient ϕ and right-hand

side of Eq. 22. The numerator was set with 1 and $\|g\|^2$ with U to visualize the relationship. The

mistake bound is minimized when $\phi = \phi_* < 1$. In this example, $B = 20$ and $U = \frac{1}{4}\sqrt{\frac{1+B}{\log(1+B)}}$.

Proof. Let $D(\phi)$ be the denominator of the right-hand side of Eq. 22.

$\qquad D(\phi) \equiv 1 + \|g\|^2 \log \phi - (\phi^{2B} + 2(1+\epsilon)U\phi^{B+1} + 4\phi^B).$ (23)

The first and second derivatives of $D(\phi)$ with respect to ϕ are obtained as follows:

$\qquad D'(\phi) \equiv \frac{\|g\|^2}{\phi} - 2B\phi^{2B-1} - 2(1+\epsilon)U(B+1)\phi^B - 4B\phi^{B-1}$ (24)

$\qquad D''(\phi) = -\frac{\|g\|^2}{\phi^2} - (2B(2B-1)\phi^{2B-2} + 2(1+\epsilon)UB(B+1)\phi^{B-1} + 4B(B-1)\phi^{B-2})$ (25)

Since all parameters $\|g\|^2$, B, U, and ϵ are positive and $B > 1$, it is evident that $D''(\phi) < 0$ for all

$\phi \in (0,1]$. This implies that $D(\phi)$ is strictly convex on this interval.

Regarding the boundary behavior of the first derivative, Eq. 24 indicates that $D'(\phi) \to \infty$ as $\phi \to 0^+$.

Conversely, as $\phi \to 1^-$, we have

$$D'(1) = \|g\|^2 - \left(6B + 2(1+\epsilon)U(B+1)\right) \le U^2 - \left(6B + 2(1+\epsilon)U(B+1)\right). \qquad (26)$$

Given that $U = \frac{1}{4}\sqrt{\frac{1+B}{\log(1+B)}}$, it follows that $U^2 < B$, for $B > 1$, ensuring $D'(1) < 0$. By the

intermediate value theorem and the strict convex of $D(\phi)$, there exists a unique optimal $\phi_* \in$

$(0,1)$ that minimizes the mistake bound. $\quad \square$

This theorem indicates that the MBON model must forget memories at a certain ratio to reduce the

number of prediction mistakes.

Analysis of the MBON model with the least recently used
strategy for the pruning hypothesis

The LRU strategy is a well-known page replacement algorithm in computer science. In this section, we analyze

the performance of the LRU strategy in terms of the average lifetime. In the analogy between page

replacement algorithms and kernel-based online learning algorithms, each page represents a kernel, and the

memory budget represents the maximum number of kernels that can be stored in memory. Consider a string

reference call $w = \{r_1, r_2, \dots\}$ which describes the order of call of the pages of an algorithm A.

This string reference call corresponds to the order of appearance of the classes of input vectors in the online

learning algorithm. The input vector x_i is generated from the i th state, where we assume that $i =$

$argmax_j\, K(x_i, x_j)$ represents each r_i as a kernel. There are k kernels, and cardinality $|w| = n$. It is given that

A works under the budget B.

Converting each algorithm A to its irreducible Markov Chain with a fixed stationary state is crucial to calculate

its mistake bound relative to its performance. We use the ergodic theorem.

Let $f(\cdot)$ be a bounded function from $X \to \mathbb{R}$, with X being a superset of x_i and $\mathbb{R}$ being the set of all real

numbers. If $(x_0, x_1, \dots, x_n)$ is an irreducible, time-homogeneous, and discrete Markov Chain, then

$$\frac{\sum_{i=1}^n f(x_i)}{n} \to E[f(x)]$$

as $n \to \infty$, almost surely with probability 1. $S\pi = \pi$, where S be the transition matrix of this Markov Chain, and

$\pi = [e_1, e_2, \dots, e_n]^T$ is the stationary state of the Markov Chain. The element e_i represents the ergodic

numbers (or probabilities) as t → ∞, and it is stable (which justifies the existence of d_{avg}, later on). n is

assumed to be a large number.

P_{ij} denote the state transition probability from state i to state j

609
$$\sum_{j \neq i} P_{ij} + P_{ii} = 1$$

Let $x = \sum_{i \neq j} P_{ij} e_j$, and $y = \sum_i P_{ii} e_i$. On closer inspection, we can see that x is the probability of the switching

between states representing its "volatility" relative to its environment, and y is the probability of the fly

remaining in the same state as earlier representing its "stay" relative to its environment.

Let us now view the specific Markov Chain in terms of reference calls. Let $D = (d_0, d_1, \ldots, d_n)$ be the increase

in lifetime of each kernel with recovery that occurs at every $O(\omega) = 0$ for a string reference call ω, where

$O(\omega)$ is a function from $\omega \rightarrow O$, where elements o of O are $\{0, 1\}$, and $O(\omega)$ converts each string ω into binary

by individually labeling all first and unique instances of a kernel as 1, else 0 if it has been called in the past.

We define $|D| = Z$, where Z is the number of zeros in the $O(\omega)$ operation and $|\cdot|$ represents the cardinality of

the set D.

It is observed that kernel recoveries occur in the 0 s of this binary $O(\omega)$. After each step of the algorithm, the

pages (kernels) arrange themselves in the order of their priority, and the increments to page i are represented

as d_i.

624
$$d_{avg} = \frac{1}{Z} \sum_i d_i$$

If T samples are presented and ith pattern appears in the reference call ω, it appears $T \cdot e_i$ times under budget

B. The approximate window of i th pattern recurrence in string ω is T/e_i, for A that has no definite recoveries

in the lifetime of pages (kernels).

The i th pattern recurrence in string ω is $d_{avg} + T \cdot e_i$ for A that has definite recoveries in the lifetime of pages

(kernels), averaging as d_{avg} over the string. This will be our indicator of performance, showing the degree of

performance convergence between LRU and Forgetron.

An algorithm with conscious and consistent recoveries in pages (kernels) will have $d_{avg} > 0$.

For Forgetron, $d_{avg} = 0$; hence, the average lifetime of a kernel (page i) is longer for LRU than Forgetron.

This means that LRU's mistakes caused by a kernel pruning is less than that of Forgetron;

hence, the LRU model is expected to perform better if the damage caused by pruning and weight shrinking is

not too high.

Analogous to cache theory, on each instance of y, the LRU resets its corresponding weight to 1; it can also be

observed as the probability of "resetting" of memory, for every next page reference.

Similarly, x is the probability of "decaying" of memory, for every next page reference.

Notably, when e_i is low, it indicates a natural low recurrence environment, where the states are not clustered

or periodic but rather chaotic and random. Here, our indicator tends to a lower value (indicating "non-

convergence" in performance), and LRU is expected to perform better than Forgetron, given $d_{avg} + T \cdot e_i > 0$

for LRU and $d_{avg} = 0$ for Forgetron.

Furthermore, a low "stay" probability (y) leads to performance degradation for both algorithms due to the

random nature of the inputs. However, the performance disparity becomes more pronounced, with the

probability of LRU outperforming Forgetron (P (LRU > Forgetron)) exceeding 0.9. (see purple, green points in

Fig. 8). This phenomenon suggests that Forgetron's error-driven update mechanism may be particularly

sensitive to input volatility—a point that warrants further theoretical or empirical investigation.

A notable property of the Forgetron algorithm is that weight shrinkage occurs exclusively upon incorrect

classification. Consequently, a high "stay" probability (y) naturally enhances its accuracy owing to the repeated

presentation of similar inputs, which minimizes the performance gap where the LRU model might otherwise

outperform Forgetron (P (LRU >Forgetron) is limited to 0.57 for the spontaneous shrinkratio $\phi' = 0.99$ in our

observation) (see yellow points in Fig.8 and Table1.).

Damages caused by weight shrinking for LRU

Notably, weight shrinking is applied not only when the classification is correct but also when it is incorrect, because this shrinkage is essential to realize the least recently used strategy. This means that the damage caused by weight shrinkage is larger than that of the original Forgetron. To reduce the damage caused by weight shrinking during correct classifications, the weight shrinking ratio for the correct classification should be larger than that for the incorrect classification. By this modification, we can ignore the damage caused by weight shrinking during the correct classification.

For the insect brain model, this modification is reasonable because the dopamine neurons in the insect brain are activated only when the predicted label is incorrect.

Moreover, the data in [2] also suggest that the MBONα'3 neurons forget all odor memories for about 1 hour after the conditioning.

This means that forgetting without any stimulation in the insect brain really occurred, corresponding to the weight shrinking during correct classification.

However, the LRU strategy still causes larger damage during incorrect classification because the LRU kernel is not always the oldest kernel.

To analyze this effect, we define Ψ_t^{LRU} as the loss due to the pruning of the LRU kernel at t: $\Psi_t^{LRU} = \Psi\left(\sigma_{r,t+1}^{LRU}, y_r^{LRU} f_t''\left(x_{r_t^{LRU}}\right)\right)$, where $\sigma_{r_t^{LRU},t+1}$ denotes the decay term of the LRU kernel at t.

$\sigma_{r_{t,t+1}^{LRU}}$ is larger than $\sigma_{r_{t,t+1}}$ when the LRU kernel is not the oldest kernel, whereas $\sigma_{r_{t,t+1}^{LRU}} < \sigma_{r_{t,t+1}}$ when the LRU kernel is not activated more than B times.

Thus, the damage caused by pruning of the LRU kernel is validated depending on the situation.

In the worst case, the LRU strategy repeats correct classifications to activate all kernels uniformly and then misclassifies the input that activates the LRU kernel. In such a case, the damage caused by pruning the LRU kernel is nearly equal to $\Psi_t^{LRU} \approx \Psi\left(1, y_{r_t^{LRU}} f_t''\left(\boldsymbol{x}_{r_t^{LRU}}\right)\right)$.

Note that, in the LRU strategy, the pruned kernel's $\sigma_{r_t^{LRU},t+1}$ is at least $\sigma_{r_{t,t+1}^{LRU}} > \Phi^{T(1-e_i)}$.

Conversely, in the case of Forgetron, the pruning target parameter $\sigma_{r_{t,t+1}} = \Phi^B$.

Therefore, if $e_i \to 1$, $\sigma_{r_t^{LRU},t+1} > \sigma_{r_t,t+1}$. Thus, the difference depends on e_i.

If e_i is large, the pruning damage is correspondingly greater. We ca argue that in more "natural" environments,

patterns are less, and randomness is higher. In such settings, a lower "stay" probability is more appropriate,

suggesting that the LRU is superior to the Forgetron under "natural" conditions. This interpretation is

consistent with our simulations.

Tradeoff between the pruning damage and LRU effect

Thus, the number of mistakes of the LRU is greatly valid for the situation, and the mistake bound is hardly

analyzed generally. Summarizing the discussion, we obtain the following table.

Table 2: Comparison of number of mistakes for the LRU and Forgetron models.

e_i	Average Number of mistakes of both models	Pruning damage	Mistakes under the LRU strategy VS under the Forgetron strategy
$e_i \to 1$	Small	LRU>Forgetron	LRU $\approx$ Forgetron
$e_i \ll 1$	Large	LRU<Forgetron	LRU < Forgetron

This interpretation corresponds to the results shown Fig. 8.

Spontaneous shrinkage reduces the pruning damage

Note that the discussion so far has not accounted for the spontaneous shrink ratio ϕ', where $\phi < \phi' < 1$. This

ratio ϕ' serves to monitor kernel usage intensity even when Model3 (LRU) yields a correct classification.

Interestingly, ϕ' also helps mitigate the damage caused by pruning a kernel. Recall the loss incurred by

pruning of the LRU kernel at time t is $\Psi_t^{LRU} = \Psi\left(\sigma_{r,t+1}^{LRU}, y_r^{LRU} f_t''\left(x_{r_t^{LRU}}\right)\right)$. The magnitude of Ψ_t^{LRU} depends on

$\sigma_{r,t+1}^{LRU}$; specifically, a smaller $\sigma_{r,t+1}^{LRU}$ results in a reduced Ψ_t^{LRU}. Since all kernel's $\sigma_{r,t+1}^{LRU}$ are multiplied by ϕ', a

smaller ϕ' faciliates the reduction of $\sigma_{r,t+1}^{LRU}$ even during correct classifications, thereby minimizing Ψ_t^{LRU} as

shown in Fig.8 and Table1 results. By leveraging spontaneous weight shrinkage, we can surgically remove

target kernels while shielding essential memories from unintended decay.

Code Availability

The source code for the models and simulations presented in this study is publicly available on GitHub

at [URL: https://github.com/sus8818-beep/MBONA3models] (DOI: 10.5281/zenodo.19571114). The

repository includes all scripts necessary to reproduce the results and figures.

Acknowledgements

We would like to thank Editage (www.editage.jp) for English language editing.

Author contributions

Conceptualization: Koichiro Yamauchi

Data curation: Koichiro Yamauchi

Formal Analysis for Models 1 and 2: Koichiro Yamauchi

Formal Analysis for Model 3: Aditya Gyanprakash Nirmale

Software: Koichiro Yamauchi

Writing - original draft: Koichiro Yamauchi

Writing - review & editing: Koichiro Yamauchi, Aditya Gyanprakash Nirmale

Funding acquisition: Koichiro Yamauchi

Supervision: Koichiro Yamauchi

References

1. Aso Y, Hattori D, Yu Y, Johnston RM, Iyer NA, Ngo TT, et al. The neuronal architecture of the mushroom body provides a logic for associative learning. elifesciencesorg. 2014;3:e04577. doi:https://elifesciences.org/articles/04577.

2. Hattori D, Aso Y, Swartz KJ, Rubin GM, Abbott LF, Axel R. Representations of Novelty and Familiarity in a Mushroom Body Compartment. Cell. 2017;169:956–969. doi:http://dx.doi.org/10.1016/j.cell.2017.04.028.

3. Dekel O, Shalev-Shwartz S, Singer Y. The Forgetron: A Kernel-Based Perceptron on a Budget. SIAM Journal on Computing (SICOMP). 2008;37(5):1342–1372. doi:10.1137/060666998.

4. Yamauchi K, Hirate T. What should insect-brain forget? In: Mahmud M, Doborjeh M, Wong K, Leung ACS, Doborjeh Z, Tanveer M, editors. Neural Information Processing –31th International Conference, ICONIP 2024–. vol. LNCS15296. Springer-Verlag; 2024. p. 211–226.

5. Owald D, Perisse E, Krashes MJ, Das G, Gohl D, Silies M, et al. Layered reward signalling through octopamine and dopamine in Drosophila. Nature. 2012;492:433–437. doi:10.1038/nature11614.

6. Ardin P, Peng F, Mangan M, Lagogiannis K, Webb B. Using an Insect Mushroom Body Circuit to Encode Route Memory in Complex Natural Environments. PLOS computational biology. 2015;11(10):1–22. doi:10.1371/journal.pcbi.1004683.

7. Sch¨olkopf B. The Kernel Trick for Distances. In: Leen T, Dietterich T, Tresp V, editors. Advances in Neural Information Processing Systems. vol. 13. MIT Press; 2000.Available from: https://proceedings.neurips.cc/paper_files/paper/2000/file/4e87337f366f72d

8. Bordes A, Ertekin S, Weston J, Bottou L. Fast Kernel Classfiers with Online and Active Learning.

Journal of Machine Learning Research. 2005;6:1579–1619.

9. Kivinen J, Smola AJ, Williamson RC. Online Learning with Kernels. IEEE Transaction of Signal

Processing. 2004;52(8):2165–2176.

doi:10.1109/TSP.2004.830991.

10. Preda C. Regression models for functional data by reproducing kernel Hilbert spaces methods.

Journal of Statistical Planning and Inference. 2007;137:829–840. doi:null.

11. Orabona F, Keshet J, Caputo B. The Projectron: a Bounded Kernel-Based Perceptron. In:

ICML2008; 2008. p. 720–727.

12. He W, Wu S. A kernel-based Perceptron with dynamic memory. Neural Networks. 2012;25:105–

113. doi:10.1016/j.neunet.2011.07.008.

13. *A´varez Salvado E*, Licata AM, Connor EG, McHugh MK, King BM, Stavropoulos N. Elementary

sensory-motor transformations underlying olfactory navigation in walking fruit-flies.

elifesciencesorg. 2018;7:e37815. doi:10.7554/eLife.37815.

14. Tao L, Ozarkar S, Beck JM, Bhandawat V. Statistical structure of locomotion and its modulation

by odors. elifesciencesorg. 2019;8:e41235. doi:10.7554/eLife.41235.

15. Wessnitzer J, Young JM, Armstrong JD, Webb B. A model of non-elemental olfactory learning in

Drosophila. Journal of Computational Neuroscience. 2012;32:197–212. doi:10.1007/s10827-

011-0348-6.

16. Jiang L, Litwin-Kumar A. Models of heterogeneous dopamine signaling in an insect learning and

memory center. PLOS computational biology. 2021;17(8). doi:https://doi.org/10.1371/journal.

pcbi.1009205.

17. Zhao C, Widmer YF, Diegelmann S, Petrovici MA, Sprecher SG, Senn W. Predictive olfactory

learning in Drosophila. Scientific Reports. 2021;11(6795).

doi:https://doi.org/10.1038/s41598-021-85841-y.

18.   KJ F, J D, SJ K. Reinforcement Learning or Active Inference? PLOS computational biology.

2009;4(7):e6421. doi:https://doi.org/10.1371/journal.pone.0006421.

19.   Friston K, FitzGerald T, Rigoli F, Schwartenbeck P, O′Doherty J, Pezzulo G. Active inference and

learning. Neuroscience & Biobehavioral Reviews. 2016;68:862–879.

doi:https://doi.org/10.1016/j.neubiorev.2016.06.022.

20.   Isomura T. A Measure of Information Available for Inference. entropy.

2018;20(7)(512):e20070512. doi:https://doi.org/10.3390/e20070512.

21.   Isomura T. Introduction of the Free-Energy Principle Perception, Action, and Inference of

Another's Mind (in Japanese). The Brain & neural networks. 2018;25(3):71–85.

22.   Hu A, Zhang W, Wang Z. Functional feedback from mushroom bodies to antennal lobes in the

Drosophila olfactory pathway. Proceedings of the National Academy of Science of the United

State of America. 2010;107(22):10262–10267. doi:10.1073/pnas.0914912107.

23.   Arena P, Patan´e L, Strauss R. The Insect Mushroom Bodies: a Paradigm of Neural Reuse. In:

ECAL 2013: The Twelfth European Conference on Artificial Life. MIT Press; 2013. p. 765–772.

24.   Friston K. Hierarchical Models in the Brain. PLOS one, 2008;4(11):1–24.

doi:10.1371/journal.pcbi.1000211.

25.   Lin AC, Bygrave AM, de Calignon A, Lee T, Miesenb?ck G. Sparse, decorrelated odor coding in the

mushroom body enhances learned odor discrimination. Nature Neuroscience. 2014;17(4):559–

568. doi:10.1038/nn.3660.

26.   Inada K, Tsuchimoto Y, Kazama H. Origins of Cell-Type-Speci?c Olfactory Processing in the

Drosophila Mushroom Body Circuit. Neuron. 2017;95(2):357–367.e4.

doi:10.1016/j.neuron.2017.06.039.

27. Ahmed M, Rajagopalan AE, Pan Y, Li Y, Williams DL, Pedersen EA. Input density tunes Kenyon

cell sensory responses in the ¡em¿Drosophila¡/em¿ mushroom body. Current Biology.

2023;33(13):2742–2760.e12. doi:10.1016/j.cub.2023.05.064.

Morizawa YM, Matsumoto M, Nakashima Y, Endo N, Aida T, Ishikane H. Synaptic pruning through

glial synapse engulfment upon motor learning. Nature Neuroscience. 2022; 25(11):1458–1469.

799   doi:10.1038/s41593-022-01184-5.

28. Leier HC, Foden AJ, Jindal DA, Wilkov AJ, Costello PVdL, Vanderzalm PJ.

Glia control experience-dependent plasticity in an olfactory critical period. Neuro Sciense.

2025;doi:10.7554/elife.100989.2.

29. Berry J, Cervantes-Sandoval I, Nicholas E, Davis R. Dopamine Is Required for Learning and

Forgetting in Drosophila. Neuron. 2012;74(3):530–542. doi:10.1016/j.neuron.2012.04.007.

30. Hayashi, Tatsuya Tatz, MacKenzie, Alexander John, Ganguly, Ishani, Ellis, Kaitlyn Elizabeth,

Smihula, Hayley Marie, Jacob, Miles Solomon, Litwin-Kumar, Ashok, Caron, Sophie Jeanne

Cecile . "Mushroom body input connections form independently of sensory activity in

Drosophila melanogaster", Current Biology. 2022; 32(18):4012.e5. doi:

10.1016/j.cub.2022.07.055.

31. Dasgupta, Sanjoy, Gupta, Anupam . "An elementary proof of a theorem of Johnson and

Lindenstrauss", Random Structures & Algorithms. 2003, 22(1): 60—65,doi:

https://doi.org/10.1002/rsa.10073.

32. William B. Johnson, Joram Lindenstrauss . "EXTENSIONS OF LIPSCHITZ MAPPINGS INTO A

HILBERT SPACE", Contemporary Mathematics. 1984, 26:189—206,doi:

http://dx.doi.org/10.1090/conm/026/737400

33. Jacob A. Berry, Isaac Cervantes-Sandoval, Eric P. Nicholas, Ronald L. Davis . "Dopamine Is

Required for Learning and Forgetting in Drosophila", Neuron. 2012 74(3), 530—542, doi:

https://doi.org/10.1016/j.neuron.2012.04.007.

Fig.S1: An example of before:(a) and after:(b) snapshots of applying Eq 39 and Eq 40 in the case of

Hebbian learning. The red colored kenyon cells are activated cells and they represents the spase feature

vector of presented odor. Such weight changes are triggered by the activation of the DANs.