Interoperable genome annotation with GBOL, an extendable infrastructure for functional data mining

Jesse C.J. van Dam^{1,*}, Jasper J. Koehorst^{1,*}, Jon Olav Vik², Peter J. Schaap¹, and Maria Suarez-Diez¹

¹Laboratory of Systems and Synthetic Biology, Wageningen University & Research, Stippeneng 4, 6708 WE, Wageningen, The Netherlands

²Centre for Integrative Genetics (CIGENE), Department of Animal and Aquacultural Sciences (IHA), Faculty of Life Sciences (BIOVIT), Norwegian University of Life Sciences (NMBU), PO Box 5003, Ås, Norway

*Authors contributed equally

Background

A standard structured format is used by the public sequence databases to present genome annotations. A prerequisite for a direct functional comparison is consistent annotation of the genetic elements with evidence statements. However, the current format provides limited support for data mining, hampering comparative analyses at large scale.

Results

The provenance of a genome annotation describes the contextual details and derivation history of the process that resulted in the annotation. To enable interoperability of genome annotations, we have developed the Genome Biology Ontology Language (GBOL) and associated infrastructure (GBOL stack). GBOL is provenance aware and thus provides a consistent representation of functional genome annotations linked to the provenance.

GBOL is modular in design, extendible and linked to existing ontologies. The GBOL stack of supporting tools enforces consistency within and between the GBOL definitions in the ontology (OWL) and the Shape Expressions (ShEx) language describing the graph structure. Modules have been developed to serialize the linked data (RDF) and to generate a plain text format files.

Conclusion

The main rationale for applying formalized information models is to improve the exchange of information. GBOL uses and extends current ontologies to provide a formal representation of genomic entities, along with their properties and relations. The deliberate integration of data provenance in the ontology enables review of automatically obtained genome annotations at a large scale. The GBOL stack facilitates consistent usage of the ontology.

RDF | Genome | Annotation

Correspondence: maria.suarezdiez@wur.nl

Background

Advances in sequencing technologies have turned genomics into a data-rich scientific discipline in which the total assembled and subsequently annotated sequence data doubles every 30 months (1). To support the growth in data throughput, automated annotation algorithms have become an indispensable supplement to manual annotation (2, 3) and currently, automatic annotations in the UniProt database outnumber manual annotations 100-fold (4).

Functional genome comparison has been used to identify diagnostic markers, to develop effective treatments, and to understand genotype-phenotype associations (5–7). The volume and heterogeneity of genome annotation data has created a unique type of big data challenge, namely how to transform computational predicted annotations into actionable knowledge. Tapping into these available resources is only efficiently done by computational means and requires a consistent interlinking of data so that data becomes Findable, Accessible, Interoperable and Reusable (FAIR) (8).

The format for sharing of public genome sequence annotation data has been developed and is maintained by the International Nucleotide Sequence Database Collaboration (INSDC) a long-standing foundational initiative that operates between the DDBJ, EMBL-EBI and NCBI public repositories. However, tradeoffs between simplicity, human readability and representational power left little support for interoperability, i.e. the ability of computer systems to directly make use of information. The */inference* qualifier (9) provides a structured description of evidence that supports feature identification or assignment. Thus, within the standard formats, data provenance of computational annotations could be stored under this optional inference tag but this tag is not designed to be used for contextual, element-wise provenance.

Currently, most annotations rely on computational predictions of structure or function, and the choice of thresholds for confidence scores becomes a key consideration. Tracking the provenance of genome annotations becomes essential for scientific reproducibility and to enable critical reexamination of analyses. However, such meta-analysis is currently very time-consuming. Efficient meta-analysis would require a framework able to accommodate the various types of annotations (e.g. gene prediction, homology, protein domains) directly linked to the supporting statistical evidence. Presently, no machine-readable infrastructure exists to directly query genome annotations linked to the historical and contextual provenance. The World Wide Web consortium provides the Semantic Web and the Resource Description Framework (RDF) data model, supporting these requirements. For RDF, ontologies are essential as they provide consistency in the meaning of data elements and in the relationship between them (10).

In this respect, ontologies already exist for various aspects of biology (11). The Sequence Ontology (SO) (12) was presented over 12 years ago and was designed as a complete terminology of unambiguous terms related to genetics. However, it was never intended to function as a file format or database schema, and provides no support for linked sets of data attributes. Furthermore, it has limited support for storing based-on provenance except for some experimental codes. FALDO's (13) only purpose is to unambiguously store genetic locations on a sequence. The Synthetic Biology Open Language (SBOL) (14) was successfully designed to describe complete synthetic constructs and the interactions between each of the elements. None of these standards were designed to consistently store feature predictions with evidence provenance and therefore none of these tools provides a complete representation of the genomic information linked to the provenance it is based on.

To meet the requirements and to ensure interoperability of computational predictions, we developed an extendable provenance-centered infrastructure for interoperable genome annotations. The here presented infrastructure consists of two main elements; Firstly, the Genome Biology Ontology Language (GBOL), which directly integrates evidence provenance for the whole dataset and for each included element (dataset- and element- wise provenance). Secondly, the "GBOL stack" of enforcing tools facilitates the consistent usage of ontologies. GBOL is modular in design, extendible and linked to existing ontologies. Empusa has been developed as part of the GBOL stack to ensure consistency within and between ontology (OWL), the API and the Shape Expressions (ShEx) describing the graph structure. This enables the use of SPARQL queries to include contextual details in large scale functional analyses. Modules have been developed to serialize the linked data (RDF) and to generate a plain text format files.

Results

Ontology structure. GBOL is a genome annotation ontology developed for the application of semantic web technologies in genome annotation and mining. As such GBOL provides the means to consistently describe computationally inferred genome annotations of biological objects typically found in a genome sequence annotation data file in the public repositories. Additionally, it can describe the linked data provenance of the extraction process of genetic information from genome sequences.

An overview of the structure of GBOL is shown in Figure 1. The ontology contains 251 classes that can be categorized into 6 broad domains (Table 1). In GBOL, sequences have features, which in turn have genomic locations on the sequence. The authority of this relationship is derived from the data provenance that captures both the statistical basis of each individual annotation (element-wise provenance) as well as the programs and parameters used for the complete set of sequences under study (dataset-wise provenance). All annotations for a given sequence can be packed into a single entity called a document.

Table 1. Overview of domains, classes and properties described by the the GBOL ontology. Note that some properties might be in multiple sub domains.

Sub domain	Classes	Properties	Value sets
Genomic locations	16	17	1
Genes			
transcripts and features	114	133	17
Document structure	27	107	7
Dataset-wise provenance	22	54	0
Element-wise provenance	5	9	0
BIBO	59	90	2

Design principles. GBOL was developed focussing on its function as as file format and as database schema and has the following design principles: modularity, human readability, and annotation. These principles ensure that the ontology can be easily extended (16).

Modularity: The number of classes in the main class tree is kept as small as possible and elements within the data are described with attributes when possible. Furthermore, classes are included in the main class tree only when there are unique properties in a class or in one of the sibling classes. This approach ensures that sub-ontologies can be managed as separate entities within the main ontology and that we can use existing ontologies. As an example the class *RegulationSite* has an attribute *regulatoryClass*, which denotes the type of regulation with a separate set of classes of which all are instances of the regulatory class.

To further simplify the ontology, every attribute is defined as a direct property within the class that links to either a string, an integer, another object or a class in an enumeration set. For each class in which the attribute is used, an 'all values from' axiom is used, with an optional minimal and/or maximal cardinality constraint. The 'all values from' axiom enforces all referenced objects to be of the expected type, which is not the case with the 'some values of' axiom and therefore we excluded the use of the 'some values of' axiom. This approach is fundamentally different from the principle used in the SO, in which attributes are defined using the 'has quality' property in combination with the 'some values of' axiom that references to a class.

Human Readability: All names within the ontology adhere to a set of basic principles to increase (human) readability of the ontology. All class names represent the underlying biological concept as closely as possible avoiding the use of unreadable numbers. All classes start with uppercase whereas properties start with lowercase. All words are spelled out, and white spaces are left out of the names, instead the next word starts with uppercase. In this way, the class 'exact position' becomes 'ExactPosition' and the property 'regulatory class' becomes 'regulatoryClass'. Furthermore, where possible, the names are shortened with abbreviations, as long as they remain understandable for a human reader (e.g. XRef instead of CrossReference).

Annotation: All classes and terms within the ontology are

sequence annotation data. By addition of standard annotation tools, the GBOL stack can be at the core of a provenance-centered genome annotation framework (Figure 2).

Fig. 3. Embedding of the GBOL ontology with already existing ontologies. FALDO, ProvO, GO, EC, RHEA and SO are existing ontologies. Classes are in yellow and an explanation is provided in the main text.

Embedding with other ontologies. GBOL is embedded in the corpus of currently developed web technologies and when possible we have integrated existing ontologies such as: FALDO (13), PROV-O (22), SO (12), SBOL (14), BIBO (23), WikiData (24), FOAF (25), Gene ontology (GO) (26) and the Evidence ontology (27) as depicted in Figure 3. Annotation of genomic location is inspired by FALDO ontology, although several elements had to be modified. The PROV-O ontology was used and extended to store data provenance. Whenever applicable, we added a cross-link to exact matching terms within the FALDO, SO and SBOL ontologies. Identification of persons and institutions is done through the FOAF ontology and BIBO is used to identify publications. GBOL does not represent a vocabulary to describe genetic, molecular or cellular functions. Instead, terms can be cross-referenced to the many vocabularies that provide functional descriptions to the (products of) genetic elements, such as Gene Ontology, Enzyme commission (EC) numbers, and the CHEBI and RHEA databases (28, 29), among others.

Key GBOL classes. Common elements in genome annotations include different classes of DNA molecules such as chromosomes, plasmids and contigs, genes, transcripts, exons, introns, proteins, protein domains and functional annotations. The following sections summarize the key classes of the ontology. An extensive description for each element can be found in the documentation available at <http://gbol.life/0.1/>.

Genomic locations: Genomic locations of all features in GBOL is captured with the *Location*, *Position* and *StrandPosition* classes, which are inspired by the FALDO ontology and represented in Figure 4. The *Location* and its subclasses together with the *StrandPosition* define an interval on the Sequence, whereas *Position* defines a single position in a sequence. A location can be either: i) A region which has begin and end positions; ii) A collection of regions (ordered or unordered); iii) A single base at a given position; or iv) An

Between location denoting a location between two bases after the base of which the position is given. Each region, base and in-between location can be defined to be located on the forward, reverse or both strands, although no strand should be specified if the sequence is a single stranded DNA sequence or a protein sequence. It should be noted that elements of a collection of regions can be located on different sequences. This can be used to encode cases in which an otherwise indistinguishable genetic element is located on multiple chromosomes.

Fig. 4. Graphical view of the GBOL ontology for genomic locations. An explanation of the classes is provided in the main text.

Exactly known positions can be indicated using the *ExactPosition* class containing the *position* property. Otherwise a not exactly known position, also called fuzzy position, can be indicated using either the *BeforePosition* class containing the *position* property, the *AfterPosition* class containing the *position* property, the *InRangePosition* class containing the *beginPosition* and *endPosition* properties or the *OneOfPosition* class containing multiple *position* properties.

Genes, transcripts and other commonly encountered genomic features: GBOL has a consistent model for storing genes, exons, (alternatively spliced) transcripts, coding sequences and proteins. Central to this model is the *Sequence* class that can have multiple annotations represented in the *Feature* class. An overview is provided in Figure 5.

In GBOL a sequence can be specified as a nucleic acid (NA) or a protein sequence. The sequence is attached to the *Sequence* class via the *sequence* property, provided in the DNA, RNA or protein encoding standard. NA-sequences can represent transcripts or other elements such as chromosomes, plasmids, scaffolds, contigs or reads. No distinction is made between DNA and RNA and the *strandType* denotes that it is either a double or single stranded DNA or RNA. As indicated in Figure 5 the type of sequence determines the features it might be associated to (*ProteinFeature*, *NAFeature* or *TranscriptFeature*).

Typically, each *GBOLDocument* contains one or more *NASequences* (e.g. *Chromosome*, *Contig*, *mRNA*), which can have multiple features including all gene, exon, intron, sequence variations, and structural, regulatory and repeat annotations. Each gene is linked to its associated exons, introns and transcripts. Due to alternative splicing a gene can have multiple transcripts. Each transcript has its own unique list of exons, which is linked through the *exonList* and associated *exonList*

quick re-evaluation of evidence, for instance by using a tunable cut-off score.

GBOL has been developed to explore available genome sequences using the mining possibilities of linked data. As a result, GBOL has evolved to consistently capture annotation data generated by the Semantic Annotation Platform with Provenance (SAPP), available at <http://semantics.systemsbiology.nl>. Previous versions of the GBOL ontology have been used to compare 432 *Pseudomonas* strains through integration of genomic, functional, metabolic and expression data (39). Here GBOL was essential to capture, store and interlink the genomic and functional annotation data. Strikingly, over 432 *Pseudomonas* strains, consistent *de-novo* annotation yielded 838 additional GO-terms and 146 additional protein domains which would not have been identified using the original gene predictions. In addition to determining the functional pan- and core genome of a species, comparative genomics also enables the investigation of genotype-phenotype associations. In (40) we consistently functionally annotated and compared 80 publicly available mycoplasma genomes. The resulting semantic framework allowed us to efficiently query for functional differentiation of various mycoplasma species in relation to host specificity and phylogenetic distance.

Consistent functional annotation within a semantic framework requires a standardised ontology for the annotated elements and the associated based-on provenance. Linked data ensures that queries can be performed, mining multiple sequences at once, thereby providing a scalable alternative for large scale genome comparisons. The GBOL stack provides the ontology and corresponding API that enables the incorporation of functional annotation and provenance reducing complexity and is the outcome of efforts in a number of studies related to functional comparative genomics. Currently the GBOL stack is being used in various collaborative projects to handle genomic data of organisms across all domains of life (41–44).

GBOL has been primarily designed to handle genomic annotation. However, it has been designed in a modular and extensible manner so that in the future it can be extended to host other omics data types as proteomics and transcriptomics. The modular design of GBOL ensures that other ontologies can be incorporated and managed as separate entities. For instance, the majority of the feature and sequence classes within GBOL can be connected with those from the Sequence Ontology and are therefore linked with the *skos:exactMatch* predicate. The major difference between GBOL and SO is that SO has been defined as vocabulary of terms related to genetic elements, whereas the GBOL classes have been designed to describe genetic annotation and elements located on a sequence and is inspired on the principles of the GenBank format. However, still a number of features in the SO are not currently available in GBOL and future work should focus on including them. Another possible extension would be to link to other Minimum Information Standards like MIGS and extensions thereof (MIMARKS, MIMS) (45, 46) and cross domain experiment reporting standards like ISA-tab (47). Other

possible extensions relate to the development of the sub-ontologies GBOL links to. For instance, BIBO is used to store information on literature references, however the OWL ontology file of BIBO has to be further improved, as it does not specify to which classes all of the properties should belong. Therefore we have chosen to include a less consistent representation of the properties by adding all properties to the root class *bibo:Document*.

Empusa, a core part of the GBOL stack, ensures the correct usage of the ontology through the provided R and JAVA API. We have ensured that Empusa can be used independently of GBOL (documentation available at <http://gbol.life>) and therefore can be used to develop new ontologies combined with an automatically generated API and documentation. This reduces the complexity and time to extend and develop ontologies with corresponding API's and ensures consistent and correct usage of a defined ontology.

Conclusions

Large scale analysis of heterogeneous biological data is hampered by lack of interoperability. To improve the exchange of information formalized information models are required. GBOL provides a formal representation of genomic entities, their properties and relations. The GBOL Stack provides a framework to enforce consistent and correct usage of GBOL. The semantic basis and the integration of provenance enables FAIR genome annotations, thereby unlocking the potential of functional genome annotation data.

Methods

The GBOL ontology is OWL encoded and a ShEx schema is provided. All supporting software (Java and R API, Empusa) are written in Java with Gradle as build system. We use JENA (48) for handling and loading the RDF data into a triple store. Protégé was used for editing the ontology (34).

Storage of the genomic location is inspired by FALDO, although several elements had to be modified e.g. to account for features that start and end on different sequences. Differences include: i) *StrandPosition* is not subclassed from *Position*. Instead, an additional property is added to the region, *base* and *InBetween* location, this is done because these location object types can have both a strand position and an index position on the sequence. ii) The *reference* property is not part of a *Position*, but of a *Location*, because a location that starts on one sequence and ends on another sequence is an undefined sequence. iii) The *BaseLocation* and the *InBetween-Location* classes have been added to the ontology. iv) The *BaseLocation*, *InBetweenLocation*, *CollectionOfRegions* and *Region* are children of the *Location* class, such that the rest of the ontology can incorporate these classes. v) The *before* and *after* positions have been explicitly defined to include their semantics. vi) The classes sub-classed from *FuzzyPosition* have an integer to denote the position and do not point to another position object, which could allow for arbitrary complex location denotations. vii) The N- and C-terminal positions have been removed and all indexes are counted from

the N-terminal side. Counting from the C-terminal side can be calculated based on the sequence length. vii) The reflexive properties *beginOf* and *endOf* have been removed, because a position can also be referenced by the added base location. For consistency we have redefined all FALDO elements within our own namespace.

Cross-links to exact matching terms from other ontologies (such as FALDO, SO and SBOL) were added using `skos:exactMatch`. Additionally, several properties within the ontology point to existing ontologies, for instance: i) The *signalTarget* property of *SignalPeptide*, the *modification-Function* of *ModifiedResidue* and the *organelle* of *Sample* are interlinked with GO terms. ii) The *experiment* property of *ProvenanceAnnotation*, which denotes upon which evidence the annotation is based on, should point, where possible, to a term within the Evidence Ontology. iii) The *residue* property of *ModifiedResidue* must point to a term within the Protein Modification Ontology (49). iv) GBOL includes the GO terms for *tissueType* of the *Sample* class and points, when possible, to a term within the BRENDA Tissue and Enzyme Source Ontology (50).

The source file of the ontology encoded in the Empusa and associated generated OWL definition, ShEx schema and visualization for Cytoscape available at <http://www.gitlab.com/GBOL> under the MIT license. The generated Java and R API are available at <https://gitlab.com/gbol/GBOLapi> and <https://gitlab.com/gbol/RGBOLapi> under the MIT license. The conversion module, which is part of SAPP, is available at <http://www.gitlab.com/SAPP/conversion> under the MIT license. The supporting Empusa code generator is available at <http://www.gitlab.com/Empusa> under the MIT license. All projects are coded in Java and are based on the Gradle build system. All terms are resolvable and can be browsed for at the associated website <http://gbol.life/0.1/>.

ACKNOWLEDGEMENTS

We thank Benoit Carreres for helpful design discussions. This work has received funding from the Research Council of Norway, No. 248792 (DigiSal) and from the European Union FP7 and H2020 under grant agreements No. 305340 (INFECT), No. 635536 (EmPowerPutida) and No. 634940 (MycSynVac).

Bibliography

1. ENA. ENA european nucleotide archive statistics. <http://www.ebi.ac.uk/ena/about/statistics>, 2017.
2. Tatiana Tatusova, Michael DiCuccio, Azat Badretdin, Vyacheslav Chetvernin, Eric P Nawrocki, Leonid Zaslavsky, Alexandre Lomsadze, Kim D Pruitt, Mark Borodovsky, and James Ostell. Ncbi prokaryotic genome annotation pipeline. *Nucleic acids research*, 44 (14):6614–6624, 2016.
3. Torsten Seemann. Prokka: rapid prokaryotic genome annotation. *Bioinformatics*, 30(14): 2068–2069, 2014.
4. The UniProt Consortium. UniProt: a hub for protein information. *Nucleic acids research*, 43 (Database issue):D204–12, 2015. ISSN 1362-4962. doi: 10.1093/nar/gku989.
5. Bas E. Dutilh, Lennart Backus, Robert A. Edwards, Michiel Wels, Jumamurat R. Bayjanov, and Sacha A. F. T. van Hijum. Explaining microbial phenotypes on a genomic scale: GWAS for microbes. *Briefings in Functional Genomics*, 12(4):366–380, July 2013. ISSN 2041-2649, 2041-2657. doi: 10.1093/bfpg/elt008.
6. David N. Cooper, Michael Krawczak, Constantin Polychronakos, Chris Tyler-Smith, and Hildegarde Kehrer-Sawatzki. Where genotype is not predictive of phenotype: towards an understanding of the molecular basis of reduced penetrance in human inherited disease. *Human Genetics*, 132(10):1077–1130, October 2013. ISSN 1432-1203. doi: 10.1007/s00439-013-1331-2.
7. Jessica Alföldi and Kerstin Lindblad-Toh. Comparative genomics as a tool to understand evolution and disease. *Genome Research*, 23(7):1063–1068, July 2013. ISSN 1088-9051. doi: 10.1101/gr.157503.113.
8. Mark D Wilkinson, Michel Dumontier, IJsbrand Jan Aalbersberg, Gabrielle Appleton, Myles Axton, Arie Baak, Niklas Blomberg, Jan-Willem Boiten, Luiz Bonino da Silva Santos, Philip E Bourne, and Others. The FAIR Guiding Principles for scientific data management and stewardship. *Scientific data*, 3:160018, 2016.
9. /inference qualifier. <http://www.insdc.org>.
10. Robert Hoehndorf, Paul N. Schofield, and Georgios V. Gkoutos. The role of ontologies in biological and biomedical research: a functional perspective. *Briefings in Bioinformatics*, 16 (6):1069–1080, November 2015. ISSN 1467-5463. doi: 10.1093/bib/bbv011.
11. Jonathan B. L. Bard and Seung Y. Rhee. Ontologies in biology: design, applications and future challenges. *Nature Reviews Genetics*, 5(3):213–222, March 2004. ISSN 1471-0056. doi: 10.1038/nrg1295.
12. Karen Eilbeck, Suzanna E Lewis, Christopher J Mungall, Mark Yandell, Lincoln Stein, Richard Durbin, and Michael Ashburner. The Sequence Ontology: a tool for the unification of genome annotations. *Genome biology*, 6(5):R44, 2005. ISSN 1465-6914. doi: 10.1186/gb-2005-6-5-r44.
13. J. Bolleman, C. J. Mungall, F. Strozzi, J. Barran, M. Dumontier, R. J. P. Bonnal, R. Buels, R. Hoehndorf, T. Fujisawa, T. Katayama, and P. J. a. Cock. FALDO: A semantic standard for describing the location of nucleotide and protein feature annotation. *Journal of Biomedical Semantics*, pages 1–19, 2016. ISSN 2041-1480. doi: DOI10.1186/s13326-016-0067-z.
14. Michal Galdzicki, Kevin P Clancy, Ernst Oberortner, Matthew Pocock, Jacqueline Y Quinn, Cesar A Rodriguez, Nicholas Roehner, M. Mandy L Wilson, Y Wilson, Laura Adam, J Christopher Anderson, Bryan A Bartley, Jacob Beal, Deepak Chandran, Deepak Ch, Joanna Chen, Ran, Douglas Densmore, Drew Endy, Raik Grünberg, Jennifer Hallinan, Nathan J Hillson, Jeffrey D Johnson, Allan Kuchinsky, Matthew Lux, Goksel Misirli, Jean Peccoud, Hector A Plahar, Evren Sirin, Guy-Bart Stan, Alan Villalobos, Anil Wipat, John H Gennari, Chris J Myers, and Herbert M Sauro. The Synthetic Biology Open Language (SBOL) provides a community standard for communicating designs in synthetic biology. *Nature Biotechnology*, 32(6):545–550, 2014. ISSN 1087-0156. doi: 10.1038/nbt.2891.
15. Jesse Cj van Dam, Jasper J Koehorst, Peter J Schaap, Vitor Ap Martins Dos Santos, and Maria Suarez-Diez. RDF2Graph a tool to recover, understand and validate the ontology of an RDF resource. *Journal of biomedical semantics*, 6:39, 2015. ISSN 2041-1480. doi: 10.1186/s13326-015-0038-9.
16. Christian Bizer, Tom Heath, and Tim Berners-Lee. Linked data-the story so far. *Semantic services, interoperability and web applications: emerging concepts*, pages 205–227, 2009.
17. Alistair Miles, Brian Matthews, Michael Wilson, and Dan Brickley. SKOS Core: Simple knowledge organisation for the Web. *International Conference on Dublin Core and Metadata Applications*, 0(0):3–10, September 2005. ISSN 1939-1366.
18. Grigoris Antoniou and Frank Van Harmelen. Web ontology language: Owl. In *Handbook on ontologies*, pages 67–92. Springer, 2004.
19. Manu Sporny, Gregg Kellogg, and Markus Lanthaler. JSON-LD 1.0 - A JSON-based Serialization for Linked Data. *W3C Candidate Recommendation*, 2013.
20. Oren Ben-Kiki, Clark Evans, and Ingy dot Net. YAML Ain't Markup Language (YAML) Version 1.2. *yaml.org, Tech. Rep*, 2009.
21. Eric Prud'hommeaux, Jose Emilio Labra Gayo, and Harold Solbrig. Shape expressions: an rdf validation and transformation language. In *Proceedings of the 10th International Conference on Semantic Systems*, pages 32–40. ACM, 2014.
22. Timothy Lebo, Satya Sahoo, Deborah McGuinness, Khalid Belhajjame, James Cheney, David Corsar, Daniel Garjo, Stian Soiland-Reyes, Stephan Zednik, and Jun Zhao. Provo: The prov ontology. *W3C recommendation*, 30, 2013.
23. Frederick Giasson and Bruce D'Arcus. Bibliographic ontology. Technical report, Technical report, 2008.
24. Elvira Mittra, Andra Waagmeester, Sebastian Burgstaller-Muehlbacher, Lynn M Schriml, Andrew I Su, and Benjamin M Good. Wikidata: A platform for data integration and dissemination for the life sciences and beyond. *bioRxiv*, 2015. doi: 10.1101/031971.
25. Dan Brickley and Libby Miller. Foaf vocabulary specification 0.91, 2007.
26. M Ashburner, C A Ball, J A Blake, D Botstein, H Butler, J M Cherry, A P Davis, K Dolinski, S S Dwight, J T Eppig, M A Harris, D P Hill, L Issel-Tarver, A Kasarskis, S Lewis, J C Matese, J E Richardson, M Ringwald, G M Rubin, G Sherlock, and Gene Ontology Consortium. Gene Ontology: Tool for The Unification of Biology. *Nature Genetics*, 25(1):25–29, 2000. ISSN 1061-4036. doi: 10.1038/75556.
27. Marcus C Chibucos, Christopher J Mungall, Rama Balakrishnan, Karen R Christie, Rachael P Huntley, Owen White, Judith A Blake, Suzanna E Lewis, and Michelle Giglio. Standardized description of scientific evidence using the Evidence Ontology (ECO). *Database*, 2014, 2014.
28. Kirill Degtyarenko, Paula De matos, Marcus Ennis, Janna Hastings, Martin Zbinden, Alan McNaught, Rafael Alcántara, Michael Darsow, Mickaël Guedj, and Michael Ashburner. ChEBI: A database and ontology for chemical entities of biological interest. *Nucleic Acids Research*, 36(SUPPL. 1), 2008. ISSN 03051048. doi: 10.1093/nar/gkm791.
29. Rafael Alcántara, Kristian B. Axelsen, Anne Morgat, Eugeni Belda, Elisabeth Coudert, Alan Bridge, Hong Cao, Paula De Matos, Marcus Ennis, Steve Turner, Gareth Owen, Lydie Bougueleret, Ioannis Xenarios, and Christoph Steinbeck. Rhea - A manually curated resource of biochemical reactions. *Nucleic Acids Research*, 40(D1), 2012. ISSN 03051048. doi: 10.1093/nar/gkr1126.
30. Laurel L Haak, Martin Fenner, Laura Paglione, Ed Pentz, and Howard Ratner. Orcid: a system to uniquely identify researchers. *Learned Publishing*, 25(4):259–264, 2012.
31. C Camacho, G Coulouris, V Avagyan, N Ma, J Papadopoulos, K Bealer, and T L Madden. BLAST+: architecture and applications. *BMC Bioinformatics*, 10:421, 2009. ISSN 1471-2105. doi: 10.1186/1471-2105-10-421.
32. Lawrence Rabiner and B Juang. An introduction to hidden markov models. *ieee assp magazine*, 3(1):4–16, 1986.
33. Thomas Nordahl Petersen, Søren Brunak, Gunnar von Heijne, and Henrik Nielsen. Signalp 4.0: discriminating signal peptides from transmembrane regions. *Nature methods*, 8(10): 785–786, 2011.
34. Mark A Musen. The protégé project: a look back and a look forward. *AI matters*, 1(4):4–12, 2015.
35. Paul Shannon, Andrew Markiel, Owen Ozier, Nitin S. Baliga, Jonathan T. Wang, Daniel

- Ramage, Nada Amin, Beno Schwikowski, and Trey Ideker. Cytoscape: A software Environment for integrated models of biomolecular interaction networks. *Genome Research*, 13 (11):2498–2504, 2003. ISSN 10889051. doi: 10.1101/gr.1239303.
36. Jasper J. Koehorst, Edoardo Saccenti, Peter J. Schaap, Vitor A. P. Martins dos Santos, and Maria Suarez-Diez. Protein domain architectures provide a fast, efficient and scalable alternative to sequence-based methods for comparative functional genomics. *F1000Research*, 5(May):1987, 2016. ISSN 2046-1402. doi: 10.12688/f1000research.9416.2.
37. Derrick E Fouts, Lauren Brinkac, Erin Beck, Jason Inman, and Granger Sutton. Panoct: automated clustering of orthologs using conserved gene neighborhood for pan-genomic analysis of bacterial strains and closely related species. *Nucleic acids research*, 40(22): e172–e172, 2012.
38. Li Li, Christian J Stoeckert, and David S Roos. Orthomcl: identification of ortholog groups for eukaryotic genomes. *Genome research*, 13(9):2178–2189, 2003.
39. Jasper J Koehorst, Jesse C J Van Dam, Ruben G A Van Heck, Edoardo Saccenti, Vitor A P Martins Dos Santos, Maria Suarez-Diez, and Peter J Schaap. Comparison of 432 *Pseudomonas* strains through integration of genomic, functional, metabolic and expression data. *Scientific reports*, 6, 2016.
40. Tjerko Kamminga, Jasper J. Koehorst, Paul Vermeij, Simen-Jan Slagman, Vitor A. P. Martins dos Santos, Jetta J. E. Bijlsma, and Peter J. Schaap. Persistence of Functional Protein Domains in *Mycoplasma* Species and their Role in Host Specificity and Synthetic Minimal Life. *Frontiers in Cellular and Infection Microbiology*, 7(February):31, 2017. ISSN 2235-2988. doi: 10.3389/fcimb.2017.00031.
41. DigiSal, towards the digital salmon: From a reactive to a pre-emptive research strategy in aquaculture. <https://www.forskningsradet.no/prosjektbanken/#/project/NFR/248792/Sprak=en>, 2017.
42. INFECT, systems medicine to understand severe soft tissue infections. <http://www.fp7infect.eu>, 2017.
43. MycoSynVac, engineering mycoplasma pneumoniae as a broad-spectrum animal vaccine. <http://www.mycosynvac.eu>, 2017.
44. EmPowerPutida, exploiting native endowments by re-factoring, re-programming and implementing novel control loops in *pseudomonas putida* for bespoke biocatalysis. <http://www.empowerputida.eu>, 2017.
45. Dawn Field, George Garrity, Tanya Gray, Norman Morrison, Jeremy Selengut, Peter Sterk, Tatiana Tatusova, Nicholas Thomson, Michael J Allen, Samuel V Angiuoli, Michael Ashburner, Nelson Axelrod, Frank Oliver Glöckner, Philip Goldstein, Robert Guralnick, Dan Haft, David Hancock, Henning Hermjakob, Christiane Hertz-Fowler, Phil Hugenholtz, Ian Joint, Leonid Kagan, Matthew Kane, Jessie Kennedy, Sandra Baldauf, Stuart Ballard, Guy Cochrane, James Cole, Peter Dawyndt, Paul De Vos, Paul Gilna, Frank Oliver Glöckner, Philip Goldstein, Robert Guralnick, Dan Haft, Leonid Kagan, Matthew Kane, Jessie Kennedy, George Kowalchuk, Karen Nelson, Julian Parkhill, Lita Proctor, Owen White, Andrew Spiers, Robert Stevens, Paul Swift, Chris Taylor, Adrian Tett, Sarah Turner, David Ussery, Bob Vaughan, and Naomi Ward. The minimum information about a genome sequences (MIGS) specification. *Nat Biotechnol.*, 26(5):541–547, 2008. ISSN 1546-1696. doi: 10.1038/1360.
46. Mark A Musen. The prot(é)g(é) project: a look back and a look forward. *AI matters*, 1(4): 4–12, 2015.
47. Philippe Rocca-Serra, Marco Brandizi, Eamonn Maguire, Nataliya Sklyar, Chris Taylor, Kimberley Begley, Dawn Field, Stephen Harris, Winston Hide, Oliver Hofmann, Steffen Neumann, Peter Sterk, Weida Tong, Susanna Assunta Sansone, and Jonathan Wren. ISA software suite: Supporting standards-compliant experimental annotation and enabling curation at the community level. In *Bioinformatics*, volume 27, pages 2354–2356, 2011. ISBN 1367-4803. doi: 10.1093/bioinformatics/btq415.
48. Apache Jena. *Apache jena*, 2013.
49. Luisa Montecchi-Palazzi, Ron Beavis, Pierre-Alain Binz, Robert J Chalkley, John Cottrell, David Creasy, Jim Shofstahl, Sean L Seymour, and John S Garavelli. The psi-mod community standard for representation of protein modification data. *Nature biotechnology*, 26(8): 864–866, 2008.
50. Ida Schomburg, Antje Chang, Christian Ebeling, Marion Gremse, Christian Heldt, Gregor Huhn, and Dietmar Schomburg. Brenda, the enzyme database: updates and major new developments. *Nucleic acids research*, 32(suppl_1):D431–D433, 2004.