PARALLEL VISUAL SHORT-TERM MEMORY ENCODING

1

Parallel encoding of information into visual short-term memory

Edwin S. Dalmaijer^{1,2}, Sanjay G. Manohar^{1,3}, & Masud Husain^{1,3}

1. Department of Experimental Psychology, University of Oxford, United Kingdom

2. MRC Cognition and Brain Sciences Unit, University of Cambridge, United Kingdom

3. Nuffield Department of Clinical Neurosciences, University of Oxford, United Kingdom.

Corresponding author

Edwin S. Dalmaijer, MRC Cognition and Brain Sciences Unit, 15 Chaucer Road, Cambridge, UK, United Kingdom. edwin.dalmaijer@mrc-cbu.cam.ac.uk

Manuscript details

Abstract: 201 words

Main text

Introduction: 1044 words

Methods: 1261 words

Results: 713 words

Discussion: 591 words

Figures/tables: 3

Acknowledgements

ESD was supported through a European Union FP7 Marie Curie ITN grant (606901). SGM is supported by an MRC Fellowship MR/P00878X/1. MH is supported by the Wellcome Trust and the NIHR Oxford Biomedical Research Centre. We thank Rachel King and Chiron Oderkerk for fruitful discussions on the subject of short-term memory encoding, and Gemma Lowcock for helping with data collection for experiment 4.

Author contributions

E.S.D. and M.H. initiated the project, conceived the ideas, and designed the experiments. E.S.D. collected the data. E.S.D. and S.G.M. conceived the analysis. E.S.D. analysed the data, and wrote the manuscript with contributions from all authors.

PARALLEL VISUAL SHORT-TERM MEMORY ENCODING

2

Abstract

Humans can temporarily retain information in their highly limited short-term memory. Traditionally, objects are thought to be attentionally selected and committed to short-term memory one-by-one. However, few studies directly test this serial encoding assumption. Here, we demonstrate that information from separate objects can be encoded into short-term memory in parallel. We developed models of serial and parallel encoding that describe probabilities of items being present in short-term memory throughout the encoding process, and tested them in a whole-report design. Empirical data from four experiments in healthy individuals were fitted best by the parallel encoding model, even when items were presented unilaterally (processed within one hemisphere). Our results demonstrate that information from several items can be attentionally selected and consequently encoded into short-term memory simultaneously. This suggests the popular feature integration theory needs to be reformulated to account for parallel encoding, and provides important boundaries for computational models of short-term memory.

Keywords: attention, short-term memory, encoding, consolidation

52 Introduction

53

54 Because the world offers more visual information that humans can process, only a subset
 55 can be selected (Baddeley & Hitch, 1974; Posner, Snyder, & Davidson, 1980). Attention is often
 56 compared to a spotlight that selects information from a small sector of the visual field before
 57 shifting to other locations (Crick, 1984; Duncan, 1984; Eriksen & St. James, 1986; Saarinen &
 58 Julesz, 1991). According to the popular feature-integration theory, only attended information can be
 59 bound together and committed to visual short-term memory (Treisman & Gelade, 1980; Wheeler &
 60 Treisman, 2002), where items' features are stored in hierarchical bundles (Brady, Konkle, &
 61 Alvarez, 2011).

62 Although much research has focussed on the architecture of visual short-term memory
 63 storage (Bays, 2015; Bays & Husain, 2008; Luck & Vogel, 1997; Oberauer & Lin, 2017; Wilken &
 64 Ma, 2004; Zhang & Luck, 2008), little work has been conducted on the encoding mechanism, the
 65 process by which visual information first enters the short-term store. There exist two main theories:
 66 The serial hypothesis is central to feature integration theory, and postulates that items are attended
 67 to and consequently encoded one-by-one (Treisman & Gelade, 1980; Wheeler & Treisman, 2002),
 68 whereas the parallel hypothesis states that all items simultaneously compete for attention and access
 69 to short-term memory (Bundesen, 1990). These theories have informed contemporary
 70 computational models of short-term memory that either implicitly assume serial encoding
 71 (Manohar, Zokaei, Fallon, Vogels, & Husain, 2017), or allow parallel encoding (Matthey, Bays, &
 72 Dayan, 2015).

73 Despite the prominence of feature-integration theory, its serial encoding assumption has
 74 received little empirical testing (Liu & Becker, 2013). Encoding can be studied by varying the
 75 duration of the stimuli, and modelling demonstrates that both its rate and capacity are limited
 76 (Bundesen, 1990). This has been confirmed in more recent studies that were either agnostic about
 77 the encoding mechanism (Bays, Gorgoraptis, Wee, Marshall, & Husain, 2011), or assumed serial
 78 encoding without formal verification (Vogel, Woodman, & Luck, 2006).

79 There is some evidence that features of unattended items may still be bound together into
 80 objects (Houck & Hoffman, 1986), and that humans can attend to two non-contiguous locations at
 81 the same time from psychophysics (Hahn & Kramer, 1998; Kramer & Hahn, 1995) and
 82 neuroimaging (McMains & Somers, 2004; Müller, Malinowski, Gruber, & Hillyard, 2003).
 83 Although these findings challenge the serial attending and binding hypothesis in feature-integration
 84 theory (Treisman & Gelade, 1980), it remains unclear whether they challenge the serial encoding
 85 hypothesis (Wheeler & Treisman, 2002).

86 One crucial difference between serial and parallel encoding is the probability of *only* one
 87 item being in short-term memory when two items are presented simultaneously. Specifically, the
 88 serial model predicts a period when it is more likely that only one of the two items has been
 89 encoded, because encoding of the second item cannot begin until the first item has completed. In

PARALLEL VISUAL SHORT-TERM MEMORY ENCODING

contrast, if encoding occurred in parallel, the probability of each item being encoded should rise together, and thus the probability of only one of the two being encoded at any time is lower (**Figure 1**). Note that in a parallel model, it is still possible for only one item to be in memory, because the rates of encoding the two items might vary stochastically. However, this probability will always be lower than for a comparable serial model.

Here, we describe two competing models for short-term memory encoding: A serial process that encoded one item at a time (**Equation 1-3**), and parallel processes that encodes items at the same time (**Equation 4**). Both models are rate and capacity limited, in line with experimental observations (Bays et al., 2011; Bundesen, 1990; Vogel et al., 2006). Given the probability that each item in a memory array has been encoded by a given time, we can compute the joint probabilities that no items, only one item, and both items have been encoded by that time (**Equations 5-7**).

We denote the time at which the first item is encoded by T_1 , and the second item by T_2 . In the serial model, the probability of the first item being encoded before time t , $P(T_1 < t)$, is given by **Equation 1**, where κ is the encoding rate, and t_0 is the minimally effective exposure duration (not unlike (Bunden, 1990)) that accounts for lag in visual processing. Before the onset of encoding, when t is smaller than t_0 , P is set to 0.

$$P(T_1 < t) = \begin{cases} 0 & \text{if } t < t_0 \\ 1 - e^{-\kappa(t-t_0)} & \text{otherwise} \end{cases} \quad (1)$$

In this serial model, encoding of the second item can only start after encoding of the first item, and thus the probability of the second item being encoded by time t , $P(T_2 < t)$, is determined by the probability that the first item has been encoded, $P(T_1 < t)$. Processing time for the second item is counted from the encoding of the first, and encoding rate κ is the same for each.

$$P(T_2 < t) = \int_0^t p(T_1 = \tau) P(T_2 < t | T_1 = \tau) d\tau \quad (2)$$

Or:

$$P(T_2 < t) = \int_0^t \kappa e^{-\kappa(t-t_0)} (1 - e^{-\kappa(t-\tau)}) d\tau \quad (3)$$

PARALLEL VISUAL SHORT-TERM MEMORY ENCODING

5

120 In the parallel model, both the probability of the first item being encoded by time t , $P(T_1 < t)$,
121 and of the second item being encoded, $P(T_2 < t)$, is given by **Equation 4**.

122

$$123 \quad P(T_i < t) = \begin{cases} 0 & \text{if } t < t_0 \\ 1 - e^{-\frac{\kappa}{2}(t-t_0)} & \text{otherwise} \end{cases} \quad (4)$$

124

125 When participants recall several items in the order of their choice, later items are known to
126 be reported less precisely (Adam, Vogel, & Awh, 2017). Therefore, we included a third parameter α
127 to account for serial recall, *without* assuming a correspondence between encoding and response
128 order (see Methods).

129 Both serial and parallel models thus yield three free parameters: rate κ , lag t_0 , and second-
130 report asymptote α . For each model, the probabilities that both (**Equation 5**), only one (**Equation**
131 **6**), or no items are encoded (**Equation 7**) follow directly from the probabilities of either item being
132 encoded:

133

$$134 \quad P(T_1 < t \wedge T_2 < t) = P(T_1 < t)P(T_2 < t) \quad (5)$$

135

$$136 \quad P((T_1 < t \wedge T_2 > t) \vee (T_1 > t \wedge T_2 < t)) = P(T_1 < t)(1 - P(T_2 < t)) + P(T_2 < t)(1 - P(T_1 < t)) \\ 137 \quad (6)$$

138

$$139 \quad P(T_2 > t \wedge T_2 > t) = 1 - P(T_2 < t \wedge T_2 < t) - P((T_1 < t \wedge T_2 > t) \vee ((T_1 > t \wedge T_2 < t))) \quad (7)$$

140

PARALLEL VISUAL SHORT-TERM MEMORY ENCODING

6

Figure 1 – In four experiments, each of the 500-900 trials followed the same pattern of a central fixation marker, followed by one or two targets presented either unilaterally or bilaterally for a variable exposure duration (0-580 ms), after which they were masked by patches of random noise for 500 ms. Participants were required to memorise and respond to both targets. The top row of modelled outcomes represents how the encoding probabilities of each individual item change over time. Crucially, in the serial model the probability of each item being encoded rises sequentially, whereas they rise simultaneously in the parallel model. The bottom row of modelled outcomes shows the combined individual encoding probabilities, and represents the probabilities that no items (grey dotted line), only one item (orange dashed line), or both items (green dashed-dotted line) are encoded. Crucially, it shows that in the serial model, the probability that only one item is encoded peaks more sharply at lower encoding times. (For the modelled outcomes, the encoding rate was set to 25 Hz so that probability of the first item being encoded was 0.76 at 50 ms in a serial scenario, which is in line with empirical estimates (Bundesen, 1990; Vogel et al., 2006). In the serial model, all processing capacity was used to encode one item first, and the other item second. In the parallel model, the processing capacity was divided equally between both items, which were encoded at the same time.)

142

143 To test the models, we developed a new whole-report paradigm in which we arrest encoding
 144 by presenting stimuli for very short durations followed by a mask, but then require participants to
 145 report both stimuli. This allowed us to probe whether neither, one, or both items were encoded, after
 146 a given encoding time. In each trial, participants were asked to remember up to two items that were
 147 presented very briefly (0-580 ms), and to recall the orientation or colour of both items (**Figure 1**).
 148 By varying the exposure durations of the items before they were masked, we could probe the
 149 probabilities of items being present in short-term memory throughout the encoding process. Here,
 150 we present model fits and additional results four experiments in a total of 60 healthy participants.

PARALLEL VISUAL SHORT-TERM MEMORY ENCODING

151 Methods

152

153 Procedure

154 Participants were recruited through the University of Oxford's Experimental Psychology
155 recruitment website for healthy volunteers, with permission from the local ethics committee. They
156 were compensated at a rate of 8 British Pounds per hour. Each experiment consisted of 500-900
157 trials, and lasted no longer than two hours. A total of 60 participants took part in four experiments
158 (N=11, N=11, N=16, N=22); numbers were modelled after previous research (Bays et al., 2011;
159 Bundesen, 1990; Vogel et al., 2006).

160 In all experiments, stimuli were presented on fixed locations for brief durations, and then
161 replaced by masks. In experiments 1, 2, and 4 the targets were coloured disks (sampled from a
162 circle with radius 22 around the whitepoint in CIE L*a*b* space with L=50), and in experiment 3
163 they were black-to-white sinusoidal gratings (5 cycles per stimulus). In experiment 1, the exposure
164 durations were 0, 10, 20, 30, 50, 90, 140, and 200 milliseconds, and in experiments 2-4 they were
165 0, 10, 20, 40, 70, 120, 200, 360, and 580 milliseconds. In experiment 1 the stimuli always appeared
166 left and right; in experiments 2 and 3 there could appear one (50% of trials; randomly selected left
167 or right location) or two stimuli (50% of trials; both locations); and in experiment 4 the stimuli
168 could appear unilaterally (top and bottom on the left or right half) or bilaterally (left and right on the
169 top or bottom half). Stimuli were presented at 7.5 degrees of visual angle from the display centre,
170 and had a diameter of 2.7 degrees of visual angle.

171 Mask duration was 500 milliseconds in all experiments, after which the mouse cursor
172 appeared. At this point, participants could use the cursor to click on a mask (or the surrounding
173 colour wheel), which then reoriented towards the cursor. Participants could fine-tune their response
174 by holding down the mouse button and moving the cursor. After responding to all stimuli in the
175 order of their choice, participants could press the Space key to continue the experiment.

176 Experiments were programmed in Python (Dalmaijer, 2017; Van Rossum & Drake, 2011),
177 using the PyGaze (Dalmaijer, Mathôt, & Van der Stigchel, 2014) and PsychoPy (Peirce, 2007)
178 packages.

179

180 Data analysis

181 Error was computed as the circular difference between stimulus colour (angle in colour
182 space) or orientation, and the associated response. The average unsigned error was used as an index
183 of performance per stimulus per exposure duration. Repeated-measures ANOVAs were conducted
184 in JASP, version 0.7 (JASP Team, 2016).

185 In addition, error distributions for each exposure duration were fitted to mixture models
186 (Bays, Catalao, & Husain, 2009; Zhang & Luck, 2008), using maximum-likelihood estimation. The
187 probability density function of the first response $p(\hat{\theta}_1)$ was described by the sum of three

PARALLEL VISUAL SHORT-TERM MEMORY ENCODING

components (**Equation 8**). The first component described the responses that were made with the target at the response location in memory, and should fit Von Mises distribution $\phi_{\sigma}(\hat{\theta}_1 - \theta)$ with density parameter σ and centre 0 (the distance between response and target orientation under perfect memory). The second component described uniformly distributed random guesses at height 2π . The third component described responses that were made with the target at the other location in mind (“swap error”), and should fit Von Mises distribution $\phi_{\sigma}(\hat{\theta}_1 - \theta^*)$. In this framework, the γ_1 parameter reflected the proportion of trials in which the first response was a guess, and the β_1 parameter reflected the proportion of trials in which the first response was a swap error. The probability density function for the second response (**Equation 9**) took the same form. Each model yielded three free parameters: guessing probability γ , swapping probability β , and density σ .

$$p(\hat{\theta}_1) = (1 - \gamma_1 - \beta_1) \phi_{\sigma}(\hat{\theta}_1 - \theta) + \gamma_1 \frac{1}{2\pi} + \beta_1 \phi_{\sigma}(\hat{\theta}_1 - \theta^*) \quad (8)$$

$$p(\hat{\theta}_2) = (1 - \gamma_2 - \beta_2) \phi_{\sigma}(\hat{\theta}_2 - \theta) + \gamma_2 \frac{1}{2\pi} + \beta_2 \phi_{\sigma}(\hat{\theta}_2 - \theta^*) \quad (9)$$

We were interested in the proportion of trials in which each of the two responses corresponded to the original memory item presented at the response location (**Equation 10-11**). This was obtained by excluding the proportion of swap errors β and the proportion of guesses γ .

$$P_1 = 1 - \gamma_1 - \beta_1 \quad (10)$$

$$P_2 = 1 - \gamma_2 - \beta_2 \quad (11)$$

When participants are free to choose their response order in whole-report tasks, they show a decrease in recall accuracy as a function of response order, unlike participants whose response order was computer-determined (Adam et al., 2017). We thus introduced a parameter, asymptote α , to account for the difference in recall precision between the first and second response.

Since the response order does not necessarily reflect the order in which items are encoded, we applied the α parameter directly to the fitted probability of the second reported item being genuinely encoded, P_2 . The empirically obtained P_2 includes only trials in which the second-report item was encoded and recalled, but not those in which it was encoded and then forgotten. The α parameter describes the proportion of trials in which the second-report item was encoded but

PARALLEL VISUAL SHORT-TERM MEMORY ENCODING

consecutively forgotten. Thus, we can express the empirically obtained P_2 as a proportion of the asymptotic recall, to account for post-encoding forgetting (**Equation 12**).

$$P_{2,proportional} = \frac{P_2}{1 - \alpha} \quad (12)$$

To prevent $P_{2,proportional}$ from exceeding 1, we limited the upper bound of potential α values (**Equation 13**).

$$\alpha_{max} = 1 - \max(P_2) \quad (13)$$

After obtaining P_1 and $P_{2,proportional}$ for each exposure duration, we could fit our encoding models (serial: **Equations 1-3 and 5-7**, parallel: **Equations 4 and 5-7**) to the resulting time series. In particular, we fitted the temporal profile of the probabilities of having encoded one or both of the items, by each moment in time during encoding. The three parameters, α , κ , and t_0 were estimated using least squares, to match the empirical time course of encoding probabilities to the model predictions. Note that P_1 and $P_{2,proportional}$ were obtained for every exposure duration, and that the sampling density was higher at lower exposure durations (six were under 120 ms, and three over 200 ms). Thus ordinary least-squares estimation will over-emphasise lower exposure durations. To overcome this, fitting was performed on interpolated datapoints resampled uniformly across exposure durations. Thus, P_1 and $P_{2,proportional}$ were linearly interpolating at every millisecond of exposure duration. These interpolated values were not counted towards the actual number of data points n that was used to compute the goodness of fit measures described next.

Goodness of fit was quantified with the *adjusted* R^2 (**Equation 14**) and Bayesian information criterion (*BIC*, **Equation 20**). Differences in BIC are computed with respect to the best fitting model (which has the lowest BIC value), and interpreted according to Raftery's guidelines (Raftery, 1995): ΔBIC values of 2-6 are considered positive evidence for the best fitting model being significantly better than the other models, 6-10 strong evidence, and values over 10 very strong.

$$R_{adjusted}^2 = 1 - \frac{(1 - R^2)(n - 1)}{n - k - 1} \quad (14)$$

For which the un-adjusted R^2 was computed via **Equation 15**.

PARALLEL VISUAL SHORT-TERM MEMORY ENCODING

10

252

$$R^2 = 1 - \frac{RSS}{TSS} \quad (15)$$

254

255 The residual sum of squares (RSS, **Equation 18**) and total sum of squares (TSS, **Equation**
256 **19**) were computed using the probabilities of only one (P_{one} , **Equation 16**) or both items (P_{both} ,
257 **Equation 17**) being in visual short-term memory. Specifically, the empirically derived probabilities
258 P_{both} and P_{one} were compared with the estimated probabilities that both items (**Equation 5**) or only
259 one item (**Equation 6**) were present in short-term memory. These estimated probabilities were
260 based on either the serial (**Equations 1 and 3**) or the parallel encoding model (**Equation 4**).

261

$$P_{both} = P_1 P_{2, proportional} \quad (16)$$

263

$$P_{one} = P_1 (1 - P_{2, proportional}) + P_{2, proportional} (1 - P_1) \quad (17)$$

265

$$RSS = \sum_{i=1}^n (P_{both,i} - P(T_1 < t \wedge T_2 < t))_i^2 + (P_{one,i} - P((T_1 < t \wedge T_2 > t) \vee (T_1 > t \wedge T_2 < t)))_i^2 \quad (18)$$

268

$$TSS = \sum_{i=1}^n (P_{both,i} - \overline{P_{both}})^2 + (P_{one,i} - \overline{P_{one}})^2 \quad (19)$$

270

271 In a least-squares framework, the Bayesian information criterion (BIC) can be computed
272 from the residual sum of squares (RSS). Our models were fitted on the same numbers of samples,
273 and had the same number of free parameters, therefore, only the term including the RSS is relevant.

274

$$BIC = n + n \ln(2\pi) + n \ln\left(\frac{RSS}{n}\right) + \ln(n)(k+1) \quad (20)$$

276

PARALLEL VISUAL SHORT-TERM MEMORY ENCODING

11

Results

278

279 In our first experiment (N=11), two coloured disks were presented for 0, 10, 20, 30, 50, 90,
280 140, or 200 milliseconds, and masked directly after. After 500 milliseconds, participants could
281 respond to both stimuli in the order of their choosing, by using the mouse cursor to click on a colour
282 wheel around each placeholder. Error was computed as the unsigned circular distance between item
283 colour and response. The probability of each item being in short-term memory was estimated by
284 fitting a mixture model (Bays et al., 2009; Zhang & Luck, 2008) to the error distributions (see
285 Methods). Error decreased as a function of exposure duration [$F_{\text{greenhouse-Geisser}}(2.47, 24.7)=102.89$,
286 $p<0.001$, $\eta^2=0.91$], and was significantly lower for the first than the second response [$F(1,$
287 $10)=79.00$, $p<0.001$, $\eta^2=0.89$], but only for exposure durations of 50 milliseconds and higher [$F(4,$
288 $40)=11.34$, $p<0.001$, $\eta^2=0.53$].

289 Because all trials had two items, participants could pre-allocate their attention to one
290 location. In addition, our first study lacked an independent estimate for the first item to be encoded.
291 Therefore, we performed a second experiment (N=11) in which we introduced a single item
292 condition in which a single coloured disk could be presented on either stimulus position. We also
293 extended the range of exposure durations to 0, 10, 20, 40, 70, 120, 200, 360, and 580 milliseconds.
294 As expected, error decreased as a function of exposure duration [$F(8, 80)=178.24$, $p<0.001$,
295 $\eta^2=0.95$], and was significantly lower for the single and first than the second response [$F(2,$
296 $20)=39.78$, $p<0.001$, $\eta^2=0.80$], but only for exposure durations of 40 milliseconds and higher [$F(16,$
297 $160)=19.24$, $p<0.001$, $\eta^2=0.66$]. Importantly, no difference in error existed between the single-item
298 condition and the first-reported item in the two-item condition [$p_{\text{Holm}}=0.156$], suggesting that the
299 encoding of the second item did not slow down that of the first.

300 To determine whether our findings generalised to other kinds of information, our third
301 experiment (N=16) used memory for visual orientation instead of colour. The design was identical
302 to the second, with the exception that items were greyscale sinusoidal gratings with a clear
303 orientation. Again, error decreased as a function of exposure duration [$F(8, 120)=147.77$, $p<0.001$,
304 $\eta^2=0.91$], and was significantly lower for the single and first than the second response [$F(2,$
305 $30)=68.59$, $p<0.001$, $\eta^2=0.82$], but only for exposure durations of 40 milliseconds and higher [$F(16,$
306 $240)=17.89$, $p<0.001$, $\eta^2=0.54$].

307 Previous research has demonstrated load-dependent activity in left parietal cortex only for
308 items in the right hemifield, while activity in right parietal cortex reflected items across the entire
309 visual field (Sheremata, Bettencourt, & Somers, 2010), suggesting a degree of independence
310 between cerebral hemispheres. It is therefore possible that parallel encoding in our experiments
311 depends on the items being presented in different hemifields. To rule out this explanation for our
312 results, we conducted a fourth experiment (N=22), in which two stimuli were shown either
313 unilaterally or bilaterally to investigate multi-item encoding within the same hemisphere. As before,
314 error decreased as a function of exposure duration [$F_{\text{Greenhouse-Geisser}}(2.59, 54.32)=332.88$, $p<0.001$,
315 $\eta^2=0.94$], and was significantly lower for the first than the second response [$F(1, 21)=72.06$,

PARALLEL VISUAL SHORT-TERM MEMORY ENCODING

12

316 $p < 0.001$, $\eta^2 = 0.77$], but only for the exposure durations of 70 milliseconds and higher [$F_{\text{Greenhouse-}}$
 317 $\text{Geisser}(4.65, 97.72) = 19.05$, $p < 0.001$, $\eta^2 = 0.48$]. In keeping with research showing a degree of
 318 hemispheric independence, errors were marginally but significantly lower for bilateral than
 319 unilateral presentation [$F(1, 21) = 7.87$, $p = 0.011$, $\eta^2 = 0.27$], but only at higher exposure durations
 320 [$F(8, 168) = 2.67$, $p = 0.009$, $\eta^2 = 0.11$] (due to the lack of a difference at lower exposure durations).

321

322 Table 1

Goodness-of-fit measures across experiments and conditions for the serial and parallel models fitted to joint encoding probabilities. BIC differences are computed with respect to the best-fitting model, which was the parallel model in all experiments.

	Encoding time (ms)	Serial R^2_{adjusted}	Parallel R^2_{adjusted}	ΔBIC
Experiment 1 (bilateral, colour)	0-200	0.84	0.88	1.95
Experiment 2 (bilateral, colour)	0-580	0.89	0.89	0.95
Experiment 3 (bilateral, orientation)	0-580	0.89	0.93	3.69
Experiment 4 (unilateral, colour)	0-580	0.92	0.94	2.46
Experiment 4 (bilateral, colour)	0-580	0.89	0.92	2.62
All bilateral conditions (sum)				9.21

323

324 In all experiments, encoding probabilities were better fitted by the parallel than the serial
 325 model (**Table 1**). Collapsed across bilateral presentation conditions in experiments with the same
 326 exposure durations ($N = 49$), the parallel model fitted better than the serial model (**Figure 2**).
 327 Parameter estimates aligned well with previous research (Bundesen, 1990; Vogel et al., 2006) for
 328 both models: parallel $\kappa = 19.94$ Hz, $t0 = 5.69$ ms, $\alpha = 0.29$; serial $\kappa = 14.73$ Hz, $t0 = 0.09$ ms, $\alpha = 0.29$.

329 Although for each experiment the ΔBIC values do not seem particularly high, taken together
 330 the four experiments provide strong evidence for the parallel model. It should be noted that both
 331 models fitted very well, which limits the practical range of BIC differences. Crucially, even in
 332 theory the difference between the two models should only be obvious at the critical exposure
 333 durations when it is likely that only one of the two items has been encoded. This greatly limits the
 334 number of data points that can contribute to BIC differences. Moreover, different subjects have
 335 different times at which this critical peak occurs. Despite these limitations, all BIC differences were
 336 consistently in the direction of the parallel model, and nearly all were in a range that is considered
 337 positive evidence (Raftery, 1995).

338

PARALLEL VISUAL SHORT-TERM MEMORY ENCODING

13

Figure 2 – The plots show averages (solid lines) and standard error (shading) estimated from empirical data of the encoding probabilities of no (grey), only one (orange), or both items (green). The best fitting solutions of the serial (left) and parallel (right) models are drawn in dashed and dotted lines, and show that the parallel model fitted the data best. These data were collected in the bilateral presentation conditions of Experiments 2-4, from a total of 49 participants

Discussion

We conducted four whole-report experiments in which we briefly presented items, and asked participants to recall and reproduce all of them. Recall accuracy increased as a function of exposure duration, replicating earlier work (Bays et al., 2011; Bundesen, 1990; Vogel et al., 2006). In addition, recall accuracy was slightly better when items were presented bilaterally rather than unilaterally. Crucially, we found that when two items were presented, the probability of only one of them being encoded into visual short-term memory did not peak as sharply as one would expect under a serial encoding model. Instead, our results were better fitted by a parallel encoding model, suggesting that information from several items can be encoded independently and at the same time.

One recent study attempted to compare the serial and a parallel encoding hypotheses by employing serial and simultaneous stimulus presentation, and came to the opposite conclusion (Liu & Becker, 2013). Unfortunately, the experimental design of that study failed to account for rate-limitations of encoding: It included imbalanced exposure durations for serial (150 ms per stimulus) and simultaneous presentation (150 ms for both stimuli). In addition, the employed models were labelled ‘serial’ and ‘parallel’, but did not incorporate encoding time. Notably, the ‘parallel’ model lacked the inter-item independence that is characteristic of parallel encoding: a guessing rate parameter was fixed between items. In our opinion, the experiments and models in the current study better capture and characterise the encoding process, as they investigate encoding probability as a function of encoding time, and crucially allow for items to be independently encoded.

PARALLEL VISUAL SHORT-TERM MEMORY ENCODING

14

Although we provide evidence for parallel encoding of information into short-term memory, whether humans are able to encode information in a serial fashion remains an open question. The methods and models presented here could be used in future studies to address this, for example by incentivising the precise recall of a particular item within a whole-report trial by reward. The reward-associated item could be encoded before all others, or encoded at the same time but at a higher rate. With minor adjustments, our models would be able to differentiate between these hypotheses. Specifically, the serial model should allow for reward-dependent encoding order, and the parallel model for reward-informed bias in encoding rates.

Conclusion

In conclusion, our results provide evidence that at least two items can be encoded into short-term memory in parallel. This suggests a reformation of the popular feature-integration theory of attention (Treisman & Gelade, 1980) and short-term memory (Wheeler & Treisman, 2002) could be in order, specifically where it postulates serial binding and encoding. Additional implications pertain to two-stage cognitive models that incorporate feature-integration theory. These generally propose an initial pre-attentive parallel perceptual processing that is followed by a stage in which attention is serially deployed to bind information within each independent item (Cave & Wolfe, 1990; Duncan, 1984; Hoffman, 1979; Treisman, 1982). Contrary to these models, others have demonstrated that attention can be deployed in parallel to non-contiguous locations (Hahn & Kramer, 1998; Kramer & Hahn, 1995; McMains & Somers, 2004; Müller et al., 2003), and the current study suggests this is also true for short-term memory encoding.

We propose that attentional resources can be distributed (quantised or fluidly) among several items to form independent encoding channels that consolidate information into the same central short-term memory store. Alternatively, one channel could (rapidly) alternate between several stimuli, partially encoding each. This speaks against computational models that assume serial complete encoding, and illustrates the biological plausibility of models that allow for simultaneous encoding of several items (e.g. (Matthey et al., 2015)).

389 References

390

- Adam, K. C., Vogel, E. K., & Awh, E. (2017). Clear evidence for item limits in visual working memory. *Cognitive Psychology*, 97, 79–97. <https://doi.org/10.1016/j.cogpsych.2017.07.001>
- Baddeley, A. D., & Hitch, G. (1974). Working Memory. In *Psychology of Learning and Motivation* (Vol. 8, pp. 47–89). Elsevier. [https://doi.org/10.1016/S0079-7421\(08\)60452-1](https://doi.org/10.1016/S0079-7421(08)60452-1)
- Bays, P. M. (2015). Spikes not slots: noise in neural populations limits working memory. *Trends in Cognitive Sciences*, 19(8), 431–438. <https://doi.org/10.1016/j.tics.2015.06.004>
- Bays, P. M., Catalao, R. F. G., & Husain, M. (2009). The precision of visual working memory is set by allocation of a shared resource. *Journal of Vision*, 9(10), 1–11. <https://doi.org/10.1167/9.10.7>
- Bays, P. M., Gorgoraptis, N., Wee, N., Marshall, L., & Husain, M. (2011). Temporal dynamics of encoding, storage, and reallocation of visual working memory. *Journal of Vision*, 11(10), 1–15. <https://doi.org/10.1167/11.10.6>
- Bays, P. M., & Husain, M. (2008). Dynamic Shifts of Limited Working Memory Resources in Human Vision. *Science*, 321(5890), 851–854. <https://doi.org/10.1126/science.1158023>
- Brady, T. F., Konkle, T., & Alvarez, G. A. (2011). A review of visual memory capacity: Beyond individual items and toward structured representations. *Journal of Vision*, 11(5), 1–34. <https://doi.org/10.1167/11.5.4>
- Bundesen, C. (1990). A theory of visual attention. *Psychological Review*, 97(4), 523–547. <https://doi.org/10.1037/0033-295X.97.4.523>
- Cave, K. R., & Wolfe, J. M. (1990). Modeling the role of parallel processing in visual search. *Cognitive Psychology*, 22(2), 225–271. [https://doi.org/10.1016/0010-0285\(90\)90017-X](https://doi.org/10.1016/0010-0285(90)90017-X)
- Crick, F. (1984). Function of the thalamic reticular complex: The searchlight hypothesis. *Proceedings of the National Academy of Sciences*, 81, 4586–4590.
- Dalmaijer, E. S. (2017). *Python for experimental psychologists*. Abingdon, Oxon; New York, NY: Routledge.

PARALLEL VISUAL SHORT-TERM MEMORY ENCODING

16

- Dalmai, E. S., Mathôt, S., & Van der Stigchel, S. (2014). PyGaze: An open-source, cross-platform toolbox for minimal-effort programming of eyetracking experiments. *Behavior Research Methods*, 46(4), 913–921. <https://doi.org/10.3758/s13428-013-0422-2>
- Duncan, J. (1984). Selective attention and the organization of visual information. *Journal of Experimental Psychology: General*, 113(4), 501–517.
- Eriksen, C. W., & St. James, J. D. (1986). Visual attention within and around the field of focal attention: A zoom lens model. *Perception & Psychophysics*, 40(4), 225–240.
- Hahn, S., & Kramer, A. F. (1998). Further Evidence for the Division of Attention Among Non-contiguous Locations. *Visual Cognition*, 5(1–2), 217–256.
<https://doi.org/10.1080/713756781>
- Hoffman, J. E. (1979). A two-stage model of visual search. *Perception & Psychophysics*, 24(4), 319–327.
- Houck, M. R., & Hoffman, J. E. (1986). Conjunction of color and form without attention: Evidence from an orientation-contingent color aftereffect. *Journal of Experimental Psychology: Human Perception and Performance*, 12(2), 186–199. <https://doi.org/10.1037/0096-1523.12.2.186>
- JASP Team. (2016). JASP (Version 0.7.1.12). Retrieved from <https://jasp-stats.org>
- Kramer, A. F., & Hahn, S. (1995). Splitting the beam: Distribution of attention over noncontiguous regions of the visual field. *Psychological Science*, 6(6), 381–386.
- Liu, T., & Becker, M. W. (2013). Serial Consolidation of Orientation Information Into Visual Short-Term Memory. *Psychological Science*, 24(6), 1044–1050.
<https://doi.org/10.1177/0956797612464381>
- Luck, S. J., & Vogel, E. K. (1997). The capacity of visual working memory for features and conjunctions. *Nature*, 390, 279–281.
- Manohar, S. G., Zokaei, N., Fallon, S. J., Vogels, T., & Husain, M. (2017). A neural model of working memory. *BioRxiv*. <https://doi.org/10.1101/233007>

PARALLEL VISUAL SHORT-TERM MEMORY ENCODING

17

- Matthey, L., Bays, P. M., & Dayan, P. (2015). A Probabilistic Palimpsest Model of Visual Short-term Memory. *PLOS Computational Biology*, 11(1), e1004003.
<https://doi.org/10.1371/journal.pcbi.1004003>
- McMains, S. A., & Somers, D. C. (2004). Multiple Spotlights of Attentional Selection in Human Visual Cortex. *Neuron*, 42(4), 677–686. [https://doi.org/10.1016/S0896-6273\(04\)00263-6](https://doi.org/10.1016/S0896-6273(04)00263-6)
- Müller, M. M., Malinowski, P., Gruber, T., & Hillyard, S. A. (2003). Sustained division of the attentional spotlight. *Nature*, 424, 309–312.
- Oberauer, K., & Lin, H.-Y. (2017). An interference model of visual working memory. *Psychological Review*, 124(1), 21–59. <https://doi.org/10.1037/rev0000044>
- Peirce, J. W. (2007). PsychoPy—Psychophysics software in Python. *Journal of Neuroscience Methods*, 162(1–2), 8–13. <https://doi.org/10.1016/j.jneumeth.2006.11.017>
- Posner, M. I., Snyder, C. R. R., & Davidson, B. J. (1980). Attention and the detection of signals. *Journal of Experimental Psychology: General*, 109(2), 160–174.
- Raftery, A. E. (1995). Bayesian Model Selection in Social Research. *Sociological Methodology*, 25, 111–163.
- Saarinen, J., & Julesz, B. (1991). The speed of attentional shifts in the visual field. *Proceedings of the National Academy of Sciences*, 88(5), 1812–1814.
<https://doi.org/10.1073/pnas.88.5.1812>
- Sheremata, S. L., Bettencourt, K. C., & Somers, D. C. (2010). Hemispheric Asymmetry in Visuotopic Posterior Parietal Cortex Emerges with Visual Short-Term Memory Load. *Journal of Neuroscience*, 30(38), 12581–12588. <https://doi.org/10.1523/JNEUROSCI.2689-10.2010>
- Treisman, A. M. (1982). Perceptual grouping and attention in visual search for features and for objects. *Journal of Experimental Psychology: Human Perception and Performance*, 8(2), 194–214. <https://doi.org/10.1037/0096-1523.8.2.194>
- Treisman, A. M., & Gelade, G. (1980). A feature-integration theory of attention. *Cognitive Psychology*, 12(1), 97–136. [https://doi.org/10.1016/0010-0285\(80\)90005-5](https://doi.org/10.1016/0010-0285(80)90005-5)

PARALLEL VISUAL SHORT-TERM MEMORY ENCODING

18

- Van Rossum, G., & Drake, F. L. (2011). *Python Language reference manual*. Bristol, UK: Network Theory Ltd.
- Vogel, E. K., Woodman, G. F., & Luck, S. J. (2006). The time course of consolidation in visual working memory. *Journal of Experimental Psychology: Human Perception and Performance*, 32(6), 1436–1451. <https://doi.org/10.1037/0096-1523.32.6.1436>
- Wheeler, M. E., & Treisman, A. M. (2002). Binding in short-term visual memory. *Journal of Experimental Psychology: General*, 131(1), 48–64. <https://doi.org/10.1037/0096-3445.131.1.48>
- Wilken, P., & Ma, W. J. (2004). A detection theory account of change detection. *Journal of Vision*, 4(12), 11. <https://doi.org/10.1167/4.12.11>
- Zhang, W., & Luck, S. J. (2008). Discrete fixed-resolution representations in visual working memory. *Nature*, 453(7192), 233–235. <https://doi.org/10.1038/nature06860>