An interactive programming paradigm for realtime experimentation with remote living matter

Peter Washington^a, Karina G. Samuel-Gama^a, Shirish Goyal^a, Ashwin Ramaswami^a, and Ingmar H. Riedel-Kruse^a

^aBioengineering, Stanford University, 450 Serra Mall, Stanford, CA 94305, USA

This manuscript was compiled on September 6, 2018

Recent advancements in life-science instrumentation and automation enable entirely new modes of human interaction with microbiological processes and corresponding applications for science and education through biology cloud labs. A critical barrier for remote life-science experimentation is the absence of suitable abstractions and interfaces for programming living matter. To this end we conceptualize a programming paradigm that provides stimulus control functions and sensor control functions for realtime manipulation of biological (physical) matter. Additionally, a simulation mode facilitates higher user throughput, program debugging, and biophysical modeling. To evaluate this paradigm, we implemented a JavaScript-based web toolkit, 'Bioty', that supports realtime interaction with swarms of phototactic *Euglena* cells hosted on a cloud lab. Studies with remote users demonstrate that individuals with little to no biology knowledge and intermediate programming knowledge were able to successfully create and use scientific applications and games. This work informs the design of programming environments for controlling living matter in general and lowers the access barriers to biology experimentation for professional and citizen scientists, learners, and the lay public.

interactive experimentation | remote experimentation | programmable wet laboratory | cloud laboratory

Life-science research is increasingly accelerated through the advancement of automated, programmable instruments [50]. Nevertheless, many usage-barriers to such instruments exist, primarily due to physical access restrictions, advanced training needs, and limitations in programmability. Equivalent barriers for computing [52, 17, 28] have been solved through application programming interfaces (APIs) [2], domain-specific applications, and cloud computing [5, 38, 56, 54]. Consequently, cloud labs to remotely experiment with biological specimen have been developed and deployed for academia and industry [15], with applications including citizen science games [33, 29] and online education [20, 21, 22, 18]. Different approaches have been taken to make automated wet lab instruments programmable: Roboliq [53] uses artificial intelligence (AI) to ease the development of complex protocols to instruct liquid handling robots; BioBlocks [13] and Wet Lab Accelerator [15] are web-based visual programming environments for specifying instrument protocols on cloud labs like Transcriptic.

Here we propose a general programming paradigm to develop applications on cloud lab platforms which enable realtime interaction with living matter. In analogy to conventional computers, this can be seen as the difference between number processing by mathematicians vs. truly interactive applications like word processing [57], interactive graphical programs [41] and computer games [16] used by all strata of society. In other words, first-hand interactive experience with microbiology should become accessible for everyone.

Fig. 1. We conceptualize a web programming paradigm that enables the creation of automated, realtime interactive applications with living matter. An integrated development environment (IDE) enables programmers to rapidly develop versatile applications. The resulting application can then be run by experimenters. The underlying application programming interface (API) includes stimulus commands that are sent to a cloud lab affecting the living matter, e.g., shining light on phototactic *Euglena gracilis* cells. The API also contains biology sensor commands to detect properties of the living matter, e.g., tracking cellular movements. We termed the specific implementation of this paradigm 'Bioty'. The programmer, experimenter, and cloud lab can be spatially separated across the globe (depicted positions are of illustrative nature).

Such concepts of 'Human-Biology Interaction' (HBI) have been explored previously through interactive museum installations [34] and educational games [3], but both the software and hardware always had to be developed from the ground up. Swarm programming abstractions for easier development

Significance Statement

Biology cloud labs are an emerging approach to lower access barriers to life-science experimentation. However, suitable programming approaches and user interfaces are lacking, especially ones that enable the interaction with the living matter itself - not just the control of equipment. Here we present and implement a corresponding programming paradigm for realtime interactive applications with remotely housed biological systems, and which is accessible and useful for scientists, programmers and lay people alike. Our user studies show that scientists and non-scientists are able to rapidly develop a variety of applications, such as interactive biophysics experiments and games. This paradigm has the potential to make first-hand experiences with biology accessible to all of society and to accelerate the rate of scientific discovery.

P.W. and I.H.R.-K. conceived the project, all authors contributed ideas; P.W. implemented the software and performed experiments, user studies and analysis; K.G.S.-G., A.R., and S.G. aided implementation and design exploration; P.W. and I.H.R.-K. wrote the paper.

Please declare any conflict of interest here.

²To whom correspondence should be addressed. E-mail: ingmar@stanford.edu

Fig. 2. System architecture of Bioty. Users can write event-driven programs that trigger the function calls, which then measure or influence the state of the biological matter. The programmers develop using three types of API calls: those which provide a stimulus to the organisms on the cloud lab (such as an LED light), those which analyze the continuous frames coming from the cloud lab, and those which support overall application development (such as by drawing on the program screen). The image processing can either be called directly on the live video feed from the BPU or on a simulation of the organisms. The experimenter, programmer, and cloud lab can be distributed across the world. The realtime image processing and simulation could be implemented either on the client or on the server side. We chose to implement the image processing on the client side and the simulation on the server side. Features that were part of the previously published *Euglena* phototaxis cloud lab architecture [21] are highlighted in purple.

of interactive applications have also been proposed [32].

Here we conceptualize and implement the first integrated development environment (IDE) [46] and API for the creation of both interactive and automated applications with living matter, which is hosted on a cloud lab (Fig. 1). This paradigm enables realtime interactive applications and spatial separation of life-science instruments, programmers, and end users. As a specific implementation, we develop the JavaScript-based web toolkit ‘Bioty’ that utilizes the phototactic behavior of *Euglena* cells [21]. We conduct on-site and remote user studies with domain experts and novices to test the usability of the system and of applications developed.

Results: System

Overview. We determined through iterative design, development, and user testing that a system for remotely programming living matter should ideally have the following minimal set of components (Fig. 2): (1) a biotic processing unit (BPU) to digitally interface with the biological specimen, (2) a cluster of such BPUs hosted on the cloud, (3) realtime conversion of BPU raw output into high-level accessible data structures, (4) a set of programming functions for manipulating and sensing biological matter and integrating with standard programming logic, (5) user and programming environments supporting online and event-driven application conventions, and (6) a virtual BPU that simulates all real BPU functionalities. We developed Bioty as a specific implementation that integrates all of these components.

Biotic Processing Units (BPUs). In analogy to electronic microprocessors like GPUs [43], Biotic Processing Units (BPUs) [22, 21, 19] are devices that house, actuate and measure microbiological systems robustly over the long term. Computing is defined by the Association of Computing Machinery (ACM) as “processes that describe and transform information” [4]. A BPU performs biological computation by transforming a digital input into a physical stimulus affecting analog biological behavior, which is then converted back into a digital output. A BPU can be programmed like a conventional microprocessor, with a domain specific instruction set

where the ‘computational algorithms’ are realized through the non-deterministic biological behavior and responses of living matter [32].

Here, we use a previously described BPU architecture [21] (Fig. 2): photophobic *Euglena* cells are housed in a quasi-2D microfluidic chip, and the modifiable light intensity of four LEDs placed in each cardinal direction can stimulate cells to swim away from light, which is captured by a microscope camera (Fig. 2). More complex responses are also possible.

Biology Cloud Lab. A cloud lab has the advantage of making biology experiments accessible from anywhere. However, the presented programming paradigm is equally suitable for a local implementation.

We developed Bioty over the existing cloud lab architecture described previously in [21], which provides realtime interactive access to a cluster of BPUs (Fig. 2), e.g., through a virtual joystick.

Biological Data Structures. The raw data stream from a BPU should be preprocessed in realtime into higher level data types that enable direct access to state variables about the biological material. Such abstractions allow programmers to treat biological objects (e.g., cells) like sprites [48] or objects in a database, whose state (e.g., position, gene expression level) can be queried and manipulated in real time [32].

In Bioty, we implemented a continuous image processing layer where cells are continuously tracked (Fig. 2). Information about individual cells, such as position and orientation, is extracted and associated with a cell index. The resulting data structures can be queried directly.

Programming Abstractions. There are three fundamental categories of functions for programming living matter: stimulus control (actuation), organism sensing, and application creation (Fig. 2). The actuating (‘writing’) functions affect the state of biological matter via a physical stimulus inside the BPU. The sensor functions ‘read’ the state of the biological matter. The application creation functions are all other standard programming functionalities.

We implemented Bioty in JavaScript with the needed functions in each category. *Stimulus control* functions like *setLED*

allow manipulation of light intensity and evoke *Euglena* responses like negative phototaxis. *Organism sensor* functions like *getEuglenaPosition* provide information regarding the position of a tracked *Euglena* cell with a given id; functions for velocity, orientation and regional cell count assessment were also implemented. *Application creation* functions are Bioty-specific, e.g., drawing virtual shapes on the live video feed. Functions can be combined into new, more advanced functions. The full set of Bioty functions are detailed in Fig. S3. Users can also use the standard built-in JavaScript libraries.

Interface Design. An accessible user interface and programming environment is required to reflect the standards of online [55, 39] and event-driven [12, 42] development environments. Interactive applications can then be developed and executed by any developer and end-user.

The client side of Bioty ((Figs. 2, 3, Supplementary Movie M1) has a programming interface (Fig. 3B) and program output that includes the live BPU camera feed with virtual overlays generated by the program (Fig. 3C). The programming interface has distinct areas (Fig. 3B) for five separate event-driven functions: (1) *startProgram* runs at the beginning of program execution, (2) *endProgram* runs after program termination, (3) *run* continuously operates during program execution at a rate of 1kHz, (4) *onKeypress* runs when the user presses a key, and (5) the *onJoystickChange* function runs when the user operates the virtual joystick (Fig. 3D). The joystick angle and magnitude map onto LED intensity inside the BPU. Standard features supporting programmers and end-users are in place (Fig. 3A): ‘Start Program’ and ‘Stop Program’ buttons trigger the *startProgram* and *endProgram* events, and ‘Save Code’ and ‘Load Code’ buttons enable file handling. A user can also run the same program on different BPUs.

Simulation Mode – Virtual BPU. A virtual BPU should be integrated that can be programmatically accessed similarly to a real BPU, using the same programming commands. It should be simple for a user to switch between both. Here, the actual ‘biological computation’ will likely not be exactly the same for real and virtual BPU, as the fidelity of the underlying model is typically limited by incomplete knowledge of the biological system and by computational power. The virtual BPU is useful as it (1) allows to fast and cheap testing and debugging of programs, (2) enables application development even if there are more developers than available real BPUs, and (3) enables genuine life-science research develop models of the biological system that can be tested side-by-side against the live experiment.

We implemented a virtual BPU (Fig. 2) with a simple model where animated *Euglena* respond to simulated *setLED* stimuli with negative phototaxis (see Materials and Methods). We integrated the virtual BPU on the client side (Fig. 2), but it could also be implemented on the server, especially when there are high computational needs.

Results: User Studies

Example applications. We first illustrate the programming potential and versatility of Bioty through three applications. These applications also provide use cases of the stimulus control, organism sensor, and application creation functions -

Fig. 3. The Bioty user interface enables users to program applications and to observe the program's effect on living cells. (A) The tool bar at the top allows the user to start/stop the program and save/load their code. The user can also hide/show their code in order to preview the final prototype without seeing the underlying code. (B) User programming area. Each text box corresponds to a particular event: the program starting, the program ending, a millisecond passing, a user keypress, or the movement of the joystick control by the user. Code boxes can be expanded and collapsed. (C) Live microscope video feed, with virtual objects overlaid on the frames. This is the primary end-user program created by the user. (D) The joystick provides another method of user input beyond keypresses, for example by mapping the joystick's angle to LED direction and the joystick's drag length to LED intensity. (E) Users can write helper functions which can be used across programming areas and user programs. (F) API calls are displayed on the interface. The functions are organized by type and can be expanded and collapsed. (This figure is a schematic of the actual user interface, placed here for legibility; Fig. S4 shows a screenshot of the Bioty user interface.)

while requiring comparably few lines of code (20, 71, and 30 lines, respectively):

Realtime Tracking. This program tracks all live cells and draws a box around them with the tracking ID displayed next to it (Fig. 4A, Supplementary Movie M2).

Radial Plot. This program provides a visualization of the instantaneous average *Euglena* velocity (Fig. 4B), as might be useful for realtime data visualization for biophysics experiments.

Guess The LED Game. This program is a ‘biotic game’ [49] where the player has to guess which of the four LEDs is switched on based on the observed direction of *Euglena* swarm movement (Fig. 4C, Supplementary Movie M3), scoring one point for every correct guess. This game could be used to teach about phototactic behavior - also highlighting the few seconds of delay between light stimulus and cell reorientation.

Study with HBI Novices. To assess the accessibility of the paradigm, we recruited participants without experience developing interactive biology. Seven programmers aged 21-24 years (mean=22.57 years, SD=1.13 years; SD - Standard Deviation) participated in the study. The only inclusion criteria was previous programming experience. On a scale of 0 (‘no experience’) to 5 (‘expert’), the participants’ described their experience regarding programming (2 to 4, mean=3.57, SD=0.84), JavaScript (0 to 4, mean=2.57, SD=1.51), and biology (1 to 4, mean=2.0, SD=1.17). Participants were limited to 2 hours of total coding time, including familiarizing themselves with the interface and API.

To first familiarize the participants with the programming paradigm, they completed two structured tasks where they

Fig. 4. Versatile biological applications can be created using 100 lines of code or less. (A) *Euglena* can be tracked by their ID in real time. The code gets all the organism IDs, iterates through them, and draws a rectangle around them. This code is further abstracted into a helper function that can be reused across programs. (B) realtime data visualizations, such as the average velocity of the organisms over time, can be plotted. The code gets every organism's velocity and uses the drawing functions to make a realtime plot. (C) The Guess LED Game asks the user to guess which LED is shining based on the direction of the *Euglena* swarm. The code makes use of four of the five supported event handlers. The *start* handler initializes global variables and hides the joystick input; the *end* handler shows the joystick and displays an end message to the player; the *run* handler draws text on the screen and shines an LED light chosen randomly by the computer; the *onKeyPress* handler handles the logic for user key input for guessing which LED is on.

Task	Average Completion Time $\pm$ SD (min)
Modify first program	29.02 $\pm$ 14.19
Modify second program	38.15 $\pm$ 21.39
Program two new applications	50.32 $\pm$ 21.03

Table 1. Mean completion times for the two preliminary tasks and the free-form task during the on-site study; N=7 participants. Details about the modified programs are in the Supplementary Information.

Participant	Time (min)	Lines of Code	Organism API Calls	Sensor API Calls	Application API Calls
1	120	41	2	2	8
2	269*	121	14	12	2
		104	16	2	4
3	137	57	8	5	11
4	351	110	10	5	19
5	77	68	5	0	5

Table 2. Coding time and length of the free-form applications expert participants built for the remote study. Also included is the number of API calls made in each application, split up by function type. Application details for each program are detailed in SI9. *Participant 2 created 2 applications; reported time is combined time to create both.

modified existing programs (completion times - see Table 1, SI Detailed Procedures: Study with HBI Novices). They then performed two free-form programming tasks to determine the types of applications that novices may create, (see Table 1). All 7 participants were able to complete all required structured programming tasks (detailed in SI3). All 7 participants were also able to develop at least one free-form applications (detailed in SI9), although there were some bugs due to the 2-hour time constraint. Task completion time and lines of code per application appear in Table 1; no single programming task took more than 1.5 hours to complete.

Two notable programs developed by the participants demonstrate the application of the paradigm to data collection and a 'biotic game' [3]:

Swarm Movement Statistics. One participant (programming=4, JavaScript=4, biology=2) kept a running average of *Euglena* velocity, acceleration, and rotation over time while randomly varying the direction and intensity of light. The user was able to visualize these aggregate movement statistics on the screen while observing the moving *Euglena* and seeing the effects of the shining LED.

Moving Box Game. Another participant (programming=4, JavaScript=3, biology=1) created a game (Fig. 5A, SI9, Movie M4) where the player must get specific *Euglena*, specified by ID, into a moving virtual green box while the joystick-controlled LEDs shine in the direction of the moving box's trajectory, making the *Euglena* move away from the target goal.

Overall we found that these HBI novices were able to successfully develop versatile applications. In the post-study

questionnaire, 7 out of 7 participants mentioned the ease of use (example quote: 'the API was very straightforward and simple to use. It does not take much time to ramp up on the API, which made it fun and way faster to move towards actually using the program'). Feedback also showed that programmers learned new biology during the development process (quote: 'I realized their individual behaviors are really variable; some of them barely respond to light, and some of them respond really quickly'). This suggests that programming with living matter can facilitate experimentation and education online.

Study with HBI Experts. In order to benchmark the affordances of this development methodology to previously established approaches for creating interactive biology applications (such as [3, 20, 31, 34]), we recruited participants who had developed such applications in the past. Five HBI experts aged 26-33 years (mean=31.2 years, SD=3.0 years) were recruited for this study. On a scale of 0 ('no experience') to 5 ('expert'), the participants stated experience for programming (3-5, mean=3.6, SD=0.9), JavaScript (0-4, mean=2.4, SD=1.5), and biology (3-5, mean=3.4, SD=0.9).

All participants worked remotely and successfully developed applications of their own choosing, spending between 77 and 351 minutes (median 137 minutes), using between 42

Fig. 5. User study participants were enabled to create a variety of interactive biological applications (top row is screenshot, bottom row is illustrative picture of program): (A) (Novice user) A video game where the player must get specific *Euglena* into a moving virtual green box while the user-directed LEDs shine in the direction of the moving box, making the *Euglena* move away from the target goal. (B) (Expert user) A continuously rotating line visualizing the average orientation of all organisms detected by the BPU. (C) (Expert user) A two-player game where the first player shoots the red ball from a particular position with the aim of hitting as many *Euglena* as possible, while the second player then tries to steer the *Euglena* with the arrow keys (mapped to LEDs) so that the ball avoids as many *Euglena* as possible. (D) (Semi-expert user) A histogram of *Euglena* rotations on the screen, allowing the user to change the intensity of the four LEDs by dragging four sliders on the screen. This program was created by an undergraduate who did not participate in any study (data not included in any analysis) and who later joined the research team. Touch event listeners were not possible in Bioty until created by this user.

and 123 lines of code, and using the all types of API calls (organism, sensor, and application) with different frequency (see Table 2, SI9). Participants used both the live BPU and the simulation mode, spending the majority (77.6%, SD=11.4%) in the former. Two notable programs developed by the HBI experts demonstrate how they applied the paradigm to real-time data visualization and game design [3]:

Orientation Visualization. In order to provide a way of determining the overall response of the organisms to light stimuli, one of the programmers (programming=3, JavaScript=4, biology=3) created a visualization with a line that rotates in the direction of the average orientation of all detected *Euglena* (Fig. 5B, SI9). The program also records the average orientation every 10 seconds and saves the results to a file.

Basketball Game. Another programmer (programming=3, JavaScript=3, biology=5) created a two-player game (Fig. 5C, SI9) where the first player lines up a virtual ball using the ‘A’ and ‘D’ keys and shoots it with the space key, aiming to hit as many *Euglena* as possible and scoring a point for every cell that is hit. The second player then uses the ‘W’, ‘A’, ‘S’, and ‘D’ keys to control LEDs to try to steer the *Euglena* away from the ball in an attempt to minimize the number of points the first player scores.

When asked whether developing their application with Bioty was easier or harder than it would have been using previously existing tools, all five participants stated that Bioty was much easier. This is also indicated by the relatively low development time and few lines of code.

Evaluating End-User Programs. In order to test whether programs written in Bioty are ultimately usable for end-users, we developed a set of educational applications centered around self-guided science experiments. Fourteen remote university students aged 22-25 years (mean=23.8 years, SD=1.2 years) were recruited to participate in the guided experimentation platform. Ten of the participants identified as female; four

as male. The participants’ stated prior familiarity with *Euglena*, on a scale of 1 to 5, ranged from 1 to 4 (mean=1.7, SD=0.99), where 1 corresponds to having never heard of *Euglena*, 3 corresponds to having read about *Euglena* before, and 5 corresponds to working with *Euglena* regularly.

The applications present moving sliders to control the LED stimulus and realtime visualizations of the average orientation of all organisms (depicted through the circular variance (Fig. 3). The main learning goals were: *Euglena* respond to light, they orient with the direction of the light, the *Euglena* response depends on light intensity, and it takes a few seconds until the *Euglena* have fully responded and reoriented with the light. These applications build up in complexity over five phases (see Fig. S1). Fig. 3 and Supplementary Movies M6 and M7 show the final application in the sequence.

We recruited 14 participants (aged 22-35 years, mean=24.53 years, SD=9.70 years) who ranked their *Euglena* experience on a scale 0 to 5 (‘no experience’ to ‘work with *Euglena*’) with mean=1.73 and SD=0.96. The participants went through the five applications with questionnaires in between (see SI5). After the first activity, 7/14 participants reported movement towards or away from light. The others reported spinning around their axis. After the last activity 12/14 participants reported that *Euglena* move away from light. 9/14 participants reported that the intensity of light affects the speed at which the *Euglena* move away from light. 12/14 participants reported a response time, ranging from 2 s to 1 min (mean 35 s). The concept of circular variance was harder to grasp for the participants: only 7/14 correctly stated that ‘alpha’ meant the average orientation of the cells. Overall, participants stated that they learned certain concepts from the applications, such as the fact that *Euglena* have a negative response to light. This demonstrates that applications written in Bioty can support science education.

Fig. 6. The final program in the guided experimentation platform displays a realtime radial plot of the average orientation of all cells as well as a time series plot of average orientation. Users can change the sliders to adjust the intensity of the LED lights. For the full progression of programs used in the guided experimentation platform, see SI Fig. S1.

In the post-study questionnaire, participants were asked free-form questions about their experience (see SI5). Regarding the difference between using live vs. simulated experiments, 11/14 found the simulation to be more predictable and reliable; nevertheless 10/14 preferred the live mode over simulation, only 1/14 preferred the simulations, the others did not have a preference. They also commented on pros and cons of each: the live mode interacts with live organisms, while the simulation is easier to use. This feedback supports previous findings that both experiments and simulations are important for education [10, 36, 7], and the presented IDE supports both.

Discussion

We demonstrated the first programming API and IDE to perform realtime interactive experiments with living matter, both locally and on a cloud lab. Bioty allows for (1) the specification of interactive experimentation, (2) the program execution to adjust to the biological response via realtime feedback, (3) the integration of a simulation mode, and (4) the creation of interactive end-user programs usable by other remote experimenters. The API allows for organism sensing via realtime object tracking, organism control through communication with a remote web server with light stimuli, and application development through a user-friendly drawing and program control library.

This paradigm and implemented architecture (Fig. 2) generalizes beyond domain-specific biocomputing (*Euglena* phototaxis) to other biological, chemical, and physical systems with different control capabilities [4, 27, 32, 44, 1]. Possible advancements in the presented domain include higher spatio-temporal manipulation of cells through more complex light fields and programming abstractions, e.g., ‘move cell *i* right by 5 μm ’ [32]). With the appropriate hardware, interactive cloud laboratories could be deployed that operate on many other biological specimen.

The usability and ease of application development of this framework was successfully evaluated through three user studies. Participants from a variety of backgrounds, including

outside of the life sciences, mastered the familiarization tasks and developed applications of their choosing. The applications developed spanned several use cases, e.g., data visualization, automated scientific experiments, interactive scientific experiments, art, and games (Fig. 5) and could be created rapidly (less than 6 hours, with less than 150 lines of code; Table 2). Novice HBI users indicated that programming had a low barrier to entry, and HBI experts confirmed easier and faster development than previous approaches [30, 32, 22, 34, 21], indicating a low code-to-functionality ratio (see SI12). The third study demonstrated that end-user applications (e.g., for science education) can be implemented that leverage the realtime interactivity with the biological substrate. Hence, Bioty follows Seymour Papert’s vision of interfaces with ‘low-floor/high-ceiling/wide-walls’ [45, 47] and constitutes a significant step toward making experimentation, engineering, and interaction with living matter more accessible to a broader community.

There are many research and educational applications, such as realtime data collection, exploration, visualization, and traditional experimentation. The parallel integration of simulation and live experiments (Fig. 2) affords direct model validation, such as the whole-cell models described in [26]. Bioty could be used as a supplement to biology education kits like BioBits [23, 51], which promotes exploratory synthetic biology experiments outside of the lab. Citizen science projects like EteRNA [33] and Foldit [11] could be supported with enhanced lab capabilities. The approach is also extendable to programming and interaction with other remote physical matter [25]. This is ultimately a new form of augmented reality (AR) [37], with the benefit that ‘microbiology’ is small and could therefore deliver versatile and rich AR worlds in a cost-effective and scalable manner [37]. Bioty is run on a cloud lab that can support millions of experiments a year at a cost of \$0.01 each [21], enabling life-science education at scale [21, 19, 8]. Just as personalized computers and programming APIs revolutionized the accessibility and mass dissemination of interactive computing [40], we believe that programming toolkits like Bioty could stimulate equivalent innovations in the life-sciences.

ACKNOWLEDGMENTS. The authors thank Z. Hossain, T.R. Stones, R. Das, and members of the Riedel-Kruse lab for suggestions, all volunteers who tested the system in various stages, and NSF Cyberlearning (1324753) for funding.

References

- [1] Gerardo Beni. “From swarm intelligence to swarm robotics”. In: *International Workshop on Swarm Robotics*. Springer. 2004, pp. 1–9.
- [2] Joshua Bloch. “How to design a good API and why it matters”. In: *Companion to the 21st ACM SIGPLAN symposium on Object-oriented programming systems, languages, and applications*. ACM. 2006, pp. 506–507.
- [3] Nate J Cira et al. “A biotic game design project for integrated life science and engineering education”. In: *PLoS biology* 13.3 (2015), e1002110.
- [4] Douglas E Comer et al. “Computing as a discipline”. In: *Communications of the ACM* 32.1 (1989), pp. 9–23.
- [5] Fernando J Corbató, Marjorie Merwin-Daggett, and Robert C Daley. “An experimental time-sharing system”. In: *Proceedings of the May 1-3, 1962, spring joint computer conference*. ACM. 1962, pp. 335–344.
- [6] C Creutz and BODO DIEHN. “Motor responses to polarized light and gravity sensing in *Euglena gracilis*”. In: *Journal of Eukaryotic Microbiology* 23.4 (1976), pp. 552–556.
- [7] Ton De Jong, Marcia C Linn, and Zacharias C Zacharia. “Physical and virtual laboratories in science and engineering education”. In: *Science* 340.6130 (2013), pp. 305–308.

- [8] Christopher J Dede, Jeffrey Jacobson, and John Richards. "Introduction: virtual, augmented, and mixed realities in education". In: *Virtual, Augmented, and Mixed Realities in Education*. Springer, 2017, pp. 1–16.
- [9] B Diehn. "Phototactic response of Euglena to single and repetitive pulses of actinic light: orientation time and mechanism". In: *Experimental cell research* 56.2-3 (1969), pp. 375–381.
- [10] Helen M Doerr. "Experiment, simulation and analysis: An integrated instructional approach to the concept of force". In: *International Journal of Science Education* 19.3 (1997), pp. 265–282.
- [11] Christopher B Eiben et al. "Increased Diels-Alderase activity through backbone remodeling guided by Foldit players". In: *Nature biotechnology* 30.2 (2012), pp. 190–192.
- [12] Opher Etzion, Peter Niblett, and David C Luckham. *Event processing in action*. Manning Greenwich, 2011.
- [13] Vishal Gupta et al. "BioBlocks: Programming protocols in biology made easier". In: *ACS synthetic biology* 6.7 (2017), pp. 1230–1232.
- [14] D-P Häder. "Polarotaxis, gravitaxis and vertical phototaxis in the green flagellate, *Euglena gracilis*". In: *Archives of microbiology* 147.2 (1987), pp. 179–183.
- [15] Erika Check Hayden. "The automated lab". In: *Nature* 516.7529 (2014), p. 131.
- [16] Raymond Heidel and Richard E Snider. *Touch screen video gaming machine*. US Patent 5,342,047. Aug. 1994.
- [17] Christina Hoffa et al. "On the use of cloud computing for scientific workflows". In: *eScience, 2008. eScience'08. IEEE Fourth International Conference on*. IEEE, 2008, pp. 640–645.
- [18] Zahid Hossain and Ingmar H Riedel-Kruse. "Life-Science Experiments Online: Technological Frameworks and Educational Use Cases". In: *Cyber-Physical Laboratories in Engineering and Science Education* (2018), pp. 271–304.
- [19] Zahid Hossain et al. "Authentic Science Inquiry Learning at Scale Enabled by an Interactive Biology Cloud Experimentation Lab". In: *Proceedings of the Fourth (2017) ACM Conference on Learning@ Scale*. ACM, 2017, pp. 237–240.
- [20] Zahid Hossain et al. "Design Guidelines and Empirical Case Study for Scaling Authentic Inquiry-based Science Learning via Open Online Courses and Interactive Biology Cloud Labs". In: *International Journal of Artificial Intelligence in Education* (July 2017).
- [21] Zahid Hossain et al. "Interactive and scalable biology cloud experimentation for scientific inquiry and education". In: *Nature biotechnology* 34.12 (2016), pp. 1293–1298.
- [22] Zahid Hossain et al. "Interactive cloud experimentation for biology: An online education case study". In: *Proceedings of the 33rd Annual ACM Conference on Human Factors in Computing Systems*. ACM, 2015, pp. 3681–3690.
- [23] Ally Huang et al. "BioBits™ Explorer: A modular synthetic biology education kit". In: *Science advances* 4.8 (2018), eaat5105.
- [24] Chang Huang, Bo Wu, and Ramakant Nevatia. "Robust object tracking by hierarchical association of detection responses". In: *European Conference on Computer Vision*. Springer, 2008, pp. 788–801.
- [25] Hiroshi Ishii et al. "Radical atoms: beyond tangible bits, toward transformable materials". In: *interactions* 19.1 (2012), pp. 38–51.
- [26] Jonathan R Karr et al. "A whole-cell computational model predicts phenotype from genotype". In: *Cell* 150.2 (2012), pp. 389–401.
- [27] Evgeny Katz. "Biocomputing—tools, aims, perspectives". In: *Current opinion in biotechnology* 34 (2015), pp. 202–208.
- [28] Kate Keahey et al. "Science clouds: Early experiences in cloud computing for scientific applications". In: *Cloud computing and applications 2008* (2008), pp. 825–830.
- [29] Firas Khatib et al. "Algorithm discovery by protein folding game players". In: *Proceedings of the National Academy of Sciences* 108.47 (2011), pp. 18949–18953.
- [30] Honesty Kim, Lukas C Gerber, and Ingmar H Riedel-Kruse. "Interactive Biotechnology: Building your own Biotic Game Setup to Play with Living Microorganisms". In: *Proceedings of the 2016 CHI Conference Extended Abstracts on Human Factors in Computing Systems*. ACM, 2016, pp. 1000–1002.
- [31] Honesty Kim et al. "LudusScope: Accessible Interactive Smartphone Microscopy for Life-Science Education". In: *PLoS one* 11.10 (2016), e0162602.
- [32] Amy T Lam et al. "Device and programming abstractions for spatiotemporal control of active micro-particle swarms". In: *Lab on a Chip* 17.8 (2017), pp. 1442–1451.
- [33] Jeehyung Lee et al. "RNA design rules from a massive open laboratory". In: *Proceedings of the National Academy of Sciences* 111.6 (2014), pp. 2122–2127.
- [34] Seung Ah Lee et al. "Trap it!: A Playful Human-Biology Interaction for a Museum Installation". In: *Proceedings of the 33rd Annual ACM Conference on Human Factors in Computing Systems*. ACM, 2015, pp. 2593–2602.
- [35] Xin Li et al. "A multiple object tracking method using Kalman filter". In: *Information and Automation (ICIA), 2010 IEEE International Conference on*. IEEE, 2010, pp. 1862–1866.
- [36] Jing Ma and Jeffrey V Nickerson. "Hands-on, simulated, and remote laboratories: A comparative literature review". In: *ACM Computing Surveys (CSUR)* 38.3 (2006), p. 7.
- [37] Paul Milgram et al. "Augmented reality: A class of displays on the reality-virtuality continuum". In: *Telemanipulator and telepresence technologies*. Vol. 2351. International Society for Optics and Photonics, 1995, pp. 282–293.
- [38] James Murty. *Programming amazon web services: S3, EC2, SQS, FPS, and SimpleDB*. " O'Reilly Media, Inc.", 2008.
- [39] Brad Myers and Andrew Ko. "Studying Development and debugging to help create a better programming environment". In: *CHI 2003 Workshop on Perspectives in End User Development*. 2003, pp. 65–68.
- [40] Lois Mayer Nichols. "The influence of student computer-ownership and in-home use on achievement in an elementary school computer programming curriculum". In: *Journal of Educational Computing Research* 8.4 (1992), pp. 407–421.
- [41] Thomas C O'Rourke et al. *Graphical user interface*. US Patent 5,349,658. Sept. 1994.
- [42] Mark Overmars. "Teaching computer science through game design". In: *Computer* 37.4 (2004), pp. 81–83.
- [43] John D Owens et al. "GPU computing". In: *Proceedings of the IEEE* 96.5 (2008), pp. 879–899.
- [44] Kazunari Ozasa et al. "Two-dimensional optical feedback control of *Euglena* confined in closed-type microfluidic channels". In: *Lab on a Chip* 11.11 (2011), pp. 1933–1940.
- [45] Seymour Papert. *Mindstorms: Children, computers, and powerful ideas*. Basic Books, Inc., 1980.
- [46] Rafeeq Ur Rehman and Christopher Paul. *The Linux development platform: configuring, using, and maintaining a complete programming environment*. Prentice Hall Professional, 2003.
- [47] Mitchel Resnick and Brian Silverman. "Some reflections on designing construction kits for kids". In: *Proceedings of the 2005 conference on Interaction design and children*. ACM, 2005, pp. 117–122.
- [48] Mitchel Resnick et al. "Scratch: programming for all". In: *Communications of the ACM* 52.11 (2009), pp. 60–67.
- [49] Ingmar H Riedel-Kruse et al. "Design, engineering and utility of biotic games". In: *Lab on a Chip* 11.1 (2011), pp. 14–22.
- [50] Samuel K Sia and Matthew P Owens. "Share and share alike". In: *Nature biotechnology* 33.12 (2015), p. 1224.
- [51] Jessica C Stark et al. "BioBits™ Bright: A fluorescent synthetic biology education kit". In: *Science advances* 4.8 (2018), eaat5107.
- [52] Lizhe Wang et al. "Scientific cloud computing: Early definition and experience". In: *High Performance Computing and Communications, 2008. HPCC'08. 10th IEEE International Conference on*. IEEE, 2008, pp. 825–830.
- [53] Ellis Whitehead et al. "Automated Planning Enables Complex Protocols on Liquid-Handling Robots". In: *ACS synthetic biology* 7.3 (2018), pp. 922–932.
- [54] Bill Wilder. *Cloud architecture patterns: using microsoft azure*. " O'Reilly Media, Inc.", 2012.
- [55] Jeffrey Wong and Jason Hong. "Marmite: end-user programming for the web". In: *CHI'06 extended abstracts on Human factors in computing systems*. ACM, 2006, pp. 1541–1546.
- [56] Alexander Zahariev. "Google app engine". In: *Helsinki University of Technology* (2009), pp. 1–5.
- [57] William Knowlton Zinsser. *Writing with a word processor*. Harper & Row New York, 1983.

Materials and Methods

Technical Implementation.

Cloud Lab Implementation. The Bioty system is developed over the existing cloud lab architecture described in [21]. The original implementation contained a joystick which allowed users to control remote LEDs on a BPU. A standard web socket connection is used to send the user joystick commands from the web server and the remote BPU, allowing for realtime interaction.

Each BPU consists of a Raspberry Pi which controls 4 LEDs. The LEDs are placed over a microfluidic chamber that houses the organisms. The Raspberry Pi is also connected to a Raspberry Pi camera that is placed over a microscope lens facing the microfluidic chamber. The frames from the camera are sent back to the web server and displayed to the user in real time.

Realtime Image Processing. The client continuously manipulates the frames returned from the microscope's live feed using the Chrome browser's Portable Native Client (PNaCl) toolchain. PNaCl executes native C++ code directly in the browser, performing multiple object tracking via the Kalman filtering algorithm for motion prediction [35] in conjunction with the Hungarian algorithm [24] to continuously match detected object contours. The application control functions render over the HTML5 canvas displaying the live video feed.

Application Development Support. The programming interface follows an event-driven realtime programming mechanism. When any of the five event programming blocks (*start*, *end*, *run*, *onJoyStickChange*, or *onKeyPress*) are triggered through one of the end-user events, the code is filtered through a parser that removes any non-approved function calls. The set of approved function calls are the set of API calls plus the standard JavaScript built-in functions. The program throws a compile-time error if a non-approved function is called via the Caja compiler. For each API function that the parser evaluates, the corresponding backend code is injected into the user code, replacing the user call to the API function. If the input code block passes the pre-checks, then the modified code is evaluated as normal JavaScript code, with all built-in language constructs such as looping and program control. If the evaluation of the code throws a runtime error, the execution of the entire script terminates and the error message is displayed to the user.

Some API calls communicate directly with the microscopes, while others perform image processing on the video frames that are returned from the cloud labs. This distinction in function implementation is not seen by the user.

When code is saved by a user, the JavaScript code is saved in a formatted file on the system that contains the user code. When a user loads a previously saved program, the formatted file is parsed and placed into the corresponding code blocks on the Bioty user interface.

Simulation Mode. The following equations are used as a toy model for the motion of the *Euglena* simulation, where $x(t)$ and $y(t)$ are the positions of a *Euglena*, v is the velocity of a *Euglena* (which is assumed constant but can vary between individual *Euglena*), $\theta(t)$ is the angle of a *Euglena* in the 2D plane, and $\phi(t)$ is the angle of the LED light stimulus - all at time t ; δt is the frame rate, and η is random noise:

$$\begin{aligned}x(t + \delta t) &= x(t) + v \cos(\theta(t))\delta t \\y(t + \delta t) &= y(t) + v \sin(\theta(t))\delta t \\\theta(t + \delta t) &= \theta(t) + [\epsilon \sin(\theta(t) - \phi(t)) + \eta]\delta t\end{aligned}$$

Each *Euglena* is given a random initial position on the screen, a random initial orientation angle, and a constant velocity v sampled from a uniform distribution between 0 and 10 pixels per frame. To calibrate this range of velocities, videos of *Euglena* were analyzed to determine how many pixels on the HTML5 canvas the *Euglena* tended to move through per frame. The frame rate is set to 1 frame per 10 milliseconds. ϵ is the coupling strength, set to -0.3 . Each simulated cell is an ellipsoid with a 5:1 major-to-minor axis ratio.

We used periodic boundary conditions: when a *Euglena*'s x -position moves past the left or right edge of the screen, it retains its y position, velocity, and orientation, appearing on the other side of the screen. The same method is used when its y -position moves past the top or bottom edge of the screen. If a *Euglena* collides with another, as defined by their x and y positions being within 2 pixels of each other, then both *Euglena* are assigned new random θ .

This is a simple model capturing the basic idea of *Euglena* dynamics in response to light. More sophisticated parameter matching between real and simulated *Euglena* behavior is possible. For example, the *Euglena* model is not currently dependent on light intensity. Furthermore, more complex models capturing the subtleties of *Euglena* movement, such as 3D polygonal motion, helical swimming pattern, and spinning at high light intensities are possible, but beyond the scope of this work.

User Studies. All user studies were conducted according to Stanford IRB-18344.

Study with HBI Novices. To evaluate the remote programming of organisms, we started with an on-site study with programmers performing two structured and two free-form programming tasks. Participants were limited to 2 hours of total coding time, including familiarizing themselves with the interface and API. The version of Bioty used in this study did not include a virtual simulation mode. Participants worked onsite (instead of remote), as it allowed us to directly observe their actions and interview them.

Seven programmers aged 21-24 years (mean=22.57 years, SD=1.13 years) participated in the on-site study. Three of the participants identified as female and four identified as male. Participants were required to be fluent in English and came from a variety of academic backgrounds. Three participants were undergraduate students at the university, three were full-time software developers, and one was a clinical researcher with some coding experience.

In the recruiting form, participants were asked to describe their general programming experience, their JavaScript programming experience, and their general biology experience on a 5-point Likert scale from 1 ('no experience') to 5 ('expert'). The participants' stated programming experience ranged from 2 to 4 (mean=3.57, SD=0.84), JavaScript experience ranged from 0 to 4 (mean=2.57, SD=1.51), and biology experience ranged from 1 to 4 (mean=2.0, SD=1.17). One participant (biology=3) had prior experience working with *Euglena*. Five of the seven participants had little to no biology knowledge (rating of 1 or 2).

Before starting the familiarization tasks (see SI3), participants were shown a working demonstration of the applications that they were asked to modify. The study researchers were available to answer questions about the API and web interface logistics, but answers to the programming tasks were not provided. After the completion of the first set of structured tasks, participants were asked to complete two free-form programming tasks. Data was recorded on an online Google Form. See Supporting Information for more details about the study, including the full set of questions participants were asked.

Study With HBI Experts. In order to gather information about system usage by domain experts, we recruited participants with prior *Euglena* HBI development backgrounds to program applications on the platform over an extended period of time. We aimed to compare their prior experiences with their experience with the remote paradigm.

Five HBI experts (i.e., people who have previously developed *Euglena*-based HBI applications) aged 26-33 years (mean=31.2 years, SD=3.0 years) were recruited for the remote portion of the study. Two of the participants identified as female; three identified as male. Three participants were graduate students at the university, one was a full-time software developer, and one was a postdoctoral scholar in biophysics. The participants' stated programming experience ranged from 3 to 5 (mean=3.6, SD=0.9), JavaScript experience ranged from 0 to 4 (mean=2.4, SD=1.5), and biology experience ranged from 3 to 5 (mean=3.4, SD=0.9).

The procedure for the study with HBI experts was identical to the study with novices: they were asked to perform two structured and two free-form programming tasks. However, this time the participants were not limited to 2 hours of total coding time, instead having a week to complete their programs. Logs of the total time actually spent on the IDE were recorded. See Supporting Information for more details about the study, including the full set of questions participants were asked.

Evaluating End-User programs. In order to test whether programs written using this paradigm are ultimately usable for end-users, fourteen remote university students aged 22-25 years (mean=23.8 years, SD=1.2 years) were recruited to participate in the guided experimentation platform. The remote participants were provided with instructions for interacting with the guided experimentation platform. To verify the usability of the programs developed in an independent online setting, no help with the interface was provided by researchers at any point during the study. The simulation mode was implemented for this study. Participants were asked to use both the simulation and live modes.

The guided experimentation platform was broken up into 6 sub-modules. The first 5 submodules corresponded to a developed application. These submodules built off of each other to progressively teach the student more about *Euglena* movement patterns through increasingly interactive programs (see Supporting Information Fig. S1 for details). The final submodule asked students to perform an experiment to determine how long it takes *Euglena* to respond to light, as defined by the time it takes for the average orientation of the organisms to have a consistently low circular variance.

993 To analyze the qualitative results, two raters categorized all 1055
994 quotes. A first rater initially categorized the quotes, followed by a 1056
995 second rater who confirmed the first rater's categorizations. When 1057
996 there was disagreement, the two raters discussed the categorization 1058
997 of quotes. 1059
998 See Supporting Information for more details about the study. 1060
999 1061
1000 1062
1001 1063
1002 1064
1003 1065
1004 1066
1005 1067
1006 1068
1007 1069
1008 1070
1009 1071
1010 1072
1011 1073
1012 1074
1013 1075
1014 1076
1015 1077
1016 1078
1017 1079
1018 1080
1019 1081
1020 1082
1021 1083
1022 1084
1023 1085
1024 1086
1025 1087
1026 1088
1027 1089
1028 1090
1029 1091
1030 1092
1031 1093
1032 1094
1033 1095
1034 1096
1035 1097
1036 1098
1037 1099
1038 1100
1039 1101
1040 1102
1041 1103
1042 1104
1043 1105
1044 1106
1045 1107
1046 1108
1047 1109
1048 1110
1049 1111
1050 1112
1051 1113
1052 1114
1053 1115
1054 1116

Supporting Information (SI).

SI1: Description of Videos.

M1: *M1_Interface.mp4* - This movie demonstrates the Bioty interface.

M2: *M2_EuglenaTracking.mp4* - *Euglena* are tracked in real time and labeled with an ID that can be used to track their position, velocity, acceleration, and orientation.

M3: *M3_GuessingGame.mp4* - This movie showcases a game where a random LED is turned on and the player has to guess which LED is on based only on the swarm movement patterns of the *Euglena*.

M4: *M4_UserStudyCapture.mp4* - This is a program a user created during the user study. It is a game where the player needs to move a virtual box over a certain number of cells in order to score.

M5: *M5_UserStudyHistogram.mp4* - This is a program a user created during the user study. It displays a histogram of the orientation angles of all cells, and allows the user to move slider bars which control LED light.

M6: *M6_EducationUserStudy.mp4* - This is the program we used in the guided experimentation platform. It shows a Bioty program with a plot of the realtime average orientation of all cells as well as a plot of average orientation over time.

M7: *M7_EducationUserStudySim.mp4* - This is the same application as the previous video above except Bioty is now run in the simulation mode.

SI2: Biophysics Walkthrough.

We illustrate how a user may program with Bioty by walking through an example scenario. Amanda is a scientist who wishes to write an automated script to collect data for a biophysics research project. Specifically, she aims to come up with an equation to model the two-dimensional movement of *Euglena* in response to various intensities of light. Further, she wishes to identify in real time which *Euglena* are turning around their short axis in the image plane to align with the direction of light, and she wishes to mark these cells by drawing a red box around them. We note that such an experiment is realistic, as similar experiments have been published in microbiology and biophysics journals [6, 9, 14].

Amanda first wants to map joystick interactions to LED behavior. She therefore modifies the *onJoystickChange* event handler so that the direction of the joystick determines which LED is shining and the length that the joystick is dragged is proportional to the intensity of light:

```
if (angle >= 45 && angle < 135)
    setLED(LED.UP, intensity);
else if (angle >= 135 && angle < 225)
    setLED(LED.RIGHT, intensity);
else if (angle >= 225 && angle < 315)
    setLED(LED.DOWN, intensity);
else if (angle >= 315 || angle < 45)
    setLED(LED.LEFT, intensity);
```

She next aims to collect the velocity and rotation of each *Euglena* detected on the screen every 5 seconds. She first calls a helper function to verify the initial conditions of the microfluidic chamber and initializes some global variables to keep track of the collected data:

```
verifyInitialState();
this.time = 1;
this.recordTime = 0;
this.velocitiesOverTime = {};
this.rotationsOverTime = {};
```

The code for the helper function is:

```
var initialStateSufficient = true;
if (getEuglenaCount() < 4)
    initialStateSufficient = false;
var euglenaIDs = getAllEuglenaIDs();
for (var i = 0; i < euglenaIDs.length; i++) {
```

```
var id = euglenaIDs[i];
var eugVel = getEuglenaVelocity(id);
if (eugVel <= 0.001 && eugVel > 0)
    initialStateSufficient = false;
}
if (!initialStateSufficient)
    alert("Initial conditions failed");

Amanda then calls the getAllEuglenaIDs function in the run
update event handler every 5 seconds, iterating through the tracked
organism IDs at that time to get their velocity and rotation via the
getEuglenaVelocity and getEuglenaRotation functions, respectively.
She also draws a red box around Euglena that have rotated more
than 15 degrees in the past 5 seconds:

this.time++;
if (this.time % 5000 === 0) {
    this.time = 1;
    var euglenaIDs = getAllEuglenaIDs();
    for (var i = 0; i < euglenaIDs.length; i++) {
        var id = euglenaIDs[i];
        var timestamp = Date.now();
        this.velocitiesOverTime[this.recordTime][id]
            = getEuglenaVelocities(id);
        this.rotationsOverTime[this.recordTime][id]
            = getEuglenaRotation(id);
        if (this.recordTime > 1 &&
            Math.abs(this.rotationsOverTime
                [this.recordTime][id] -
                this.rotationsOverTime[this.recordTime-1]
                [id]) > 15) {
            var xPosition = getEuglenaPosition(id).x;
            var yPosition = getEuglenaPosition(id).y;
            drawRect(xPosition-5, yPosition-5,
                xPosition+5, yPosition+5, COLORS.RED);
        }
        this.recordTime++;
    }
}
```

Finally, Amanda wishes to save the experiment results into a JSON file for future data analysis. In the *onKeyPress* event handler, she maps the 'S' key to saving the accumulated experimental data:

```
switch (key) {
    case KEY.S:
        writeToFile("velocities.json",
            this.velocitiesOverTime, FILE.OVERWRITE);
        writeToFile("rotations.json",
            this.rotationsOverTime, FILE.OVERWRITE);
        break;
}
```

The total amount of code required for this application is relatively small, at only 38 lines or 50 lines including the helper function to verify the initial state. Amanda can now use her program to interact with the *Euglena* in real time with the joystick to collect data about how *Euglena* move in response to various intensities and directions of light. After collecting the data with her Bioty program, Amanda can analyze the data offline and use it to develop and test her biophysics model about *Euglena* phototaxis for her research project.

SI3: Detailed Procedures for Study with HBI Novices.

The study with HBI novices was the first of the three studies to be conducted.

Familiarization Programming Tasks

The familiarization tasks (Task 1 and Task 2) had the purposes of familiarizing the participants with the programming interface and API as well as ensuring a minimal level of competency with JavaScript programming. The following instructions were provided to the participants verbatim:

Fig. S1. In order to test whether programs written with this paradigm are useful to end-users, we tested a series of programs of increasing complexity written purely with Bioty. (A) The program allows the user to toggle 4 knobs which control the LED light at the corresponding position. (B) A plot of the average rotation of all the *Euglena* over time. (C) A realtime visualization of the average orientation via a circular compass. (D) Same program as (C) except the length of the compass line represents the circular variance of all of the organisms. (E) The visualizations from (B) and (D) are provided side-by-side.

Fig. S2. In the biophysics data collection example, Amanda highlights *Euglena* with red boxes that have moved in response to pulling the joystick.

- **Task 1:** The *avoidEuglenaGame* program codes a 'biotic game' where the player uses the W,A,S,D keys to move a virtual green circle from the bottom to the top of the screen. If the virtual circle comes in contact with a real *Euglena* organism on the screen, the player must start again from the bottom of the screen. Modify the *avoidEuglenaGame* program so that the user scores 1 point every time the circle reaches the top of the microscope screen, and display this score on the screen. Save the game as *avoidEuglenaGameModified*. Finally, modify the code so that the green circle increases in size every time the user levels up. This also means that collisions between the circle and *Euglena* are more likely.
- **Task 2:** The *euglenaCountExperiment* program displays the total count of the detected *Euglena* on the screen and saves this count to a file on the cloud every 10 seconds. After the program is over, the contents of the file are displayed above the microscope screen. Modify *euglenaCountExperiment* so that you get the *Euglena* density in each of the 4 quadrants of the screen. For the purposes of this study, *Euglena* density in a quadrant = (number of *Euglena* in quadrant) / (total number of detected *Euglena*). Save this information in the text file in any format you want, and display the file contents onto the screen when the user clicks the 'Stop Program' button.

Free-Form Programming Tasks

The free-form programming tasks, Task 3 and Task 4, had the purpose of exploring the design space of applications that programmers would develop when given creative freedom. The following instructions were provided to the participants verbatim:

- **Task 3:** Program a new scientific application of your choosing. Your program should teach you something you didn't know before about *Euglena*.
- **Task 4:** Program any biological application of your choosing. This can be a new scientific experiment, a new biotic game, or some other novel and interesting application that goes beyond the example programs.

Stimulus Control Function <code>setLED(led, intensity)</code>	Application Creation Functions <code>drawOnTrackedEuglena()</code> <code>drawCircle(x, y, radius, color)</code> <code>drawLine(x1, y1, x2, y2, color)</code> <code>drawText(text, xPos, yPos, size, color)</code> <code>drawRect(x1, y1, x2, y2, color)</code> <code>endProgram()</code> <code>getTimeLeft()</code> <code>setJoystickVisible()</code> <code>setInstructionText(message)</code> <code>readFromFile(filename)</code> <code>writeToFile(filename, text, mode)</code>
Organism Sensor Functions <code>getAllEuglenaIDs()</code> <code>getAllEuglenaPositions()</code> <code>getEuglenaCount()</code> <code>getEuglenaInRect(upperLeftX, upperLeftY, lowerRightX, lowerRightY)</code> <code>getEuglenaAcceleration(id)</code> <code>getEuglenaPosition(id)</code> <code>getEuglenaRotation(id)</code> <code>getEuglenaVelocity(id)</code>	

Fig. S3. The complete Bioty JavaScript API at the time the user studies were conducted, organized by function type. The function types are stimulus control (for manipulating the *Euglena* cells), organism sensors (for retrieving information about the current state of the cells), and application creation (which are non-specific to the biology but make it easy to control the graphical aspects of the program).

Fig. S4. The user interface enables users to program and to observe the program's effect onto living cells. This is a screenshot of the Bioty interface. (A) The tool bar at the top allows the user to start/stop the program and save/load their code. The user can also hide/show their code in order to preview the final prototype without seeing the underlying code. (B) User programming area. Each text box corresponds to a particular event: the program starting, the program ending, a millisecond passing, a user keypress, or the movement of the joystick control by the user. Code boxes can be expanded and collapsed. (C) Live microscope video feed, with virtual objects overlaid on the frames. This is the primary end-user program created by the user. (D) Time remaining in the session is displayed to the user. (E) API calls are displayed on the interface. The functions are organized by type and can be expanded and collapsed. (F) The joystick provides another method of user input beyond keypresses, for example by mapping the joystick's angle to LED direction and the joystick's drag length to LED intensity.

After completing all tasks, participants were asked to answer a series of questions in an online form about what they liked and disliked about the interface and the JavaScript API as well as a description of the applications they created for Task 3 and Task 4. Participants were compensated 15 US dollars for their participation.

As participants provided feedback, we iteratively made improvements to both the interface and the API. Most of these were non-biology UI improvements, such as making the event code boxes collapsible/expandable and shortening the API function names to be more concise. All improvements were complete for the next user study. Logs were recorded of all user button clicks on the interface, intermediate versions of their code, any example programs they opened, time spent programming per session, and task completion times.

The following free-response questions were asked on the Google Form after the study:

What application(s) did you end up building (and what did you name the saved code file)?

What did you like about the API?

What aspects of the API can be improved?

What did you like about the online interface?

What aspects of the online interface can be improved?

Now that you are familiar with the API, what are some examples of applications you would build if you had more time?

What are some ideas you have for extending the API and online interface?

What, if anything, did you learn about *Euglena* that you didn't know before? What did you learn about the *Euglena* from your scientific experiment application specifically?

SI4: Detailed Procedures for Study with HBI Experts.

The study with HBI experts was the second of the three studies to be conducted. The same Google Form as in the study with HBI novices was provided to participants at the end of this study, with the exact same free-response questions.

The procedure for the remote study was to conduct tasks T1 and T2 from the on-site study and then to program a free-form application of their choosing (T4). The participants programmed on their own time and had 2 weeks to complete the tasks. All logging was the same as in the lab study, including filling out the same questionnaire at the end of the study.

SI5: Detailed Procedures for Evaluating End-User Program.

The study with HBI experts was the final of the three studies to be conducted.

The first program in the sequence allows the user to toggle 4 knobs which control the LED light at the corresponding position. This activity is meant to prime the user to using the system and to understand that *Euglena* tend to move away from light.

The second program in the guided experimentation platform displays a plot of the average rotation of all the *Euglena* over time. A white bar shows the direction of the LED light. The plot is updated in real time. The user is not told the value of 'alpha', which is the average orientation of all *Euglena* on the screen. Participants are asked to infer the value of 'alpha' after using the program.

The third program in the guided experimentation platform provides another visualization of the average orientation via a circular compass which updates in real time. The participant is once again asked to find the value of 'alpha'.

The fourth program in the guided experimentation platform is the same as the previous program except the length of the compass line represents the circular variance of all of the organisms. Participants were asked to observe the value of '|R|' to infer what it represents.

The final program in the sequence incorporates both plots together. At this point in the study, it is next revealed that 'alpha' corresponds to the average orientation of the organisms and '|R|' corresponds to the circular variance of the organisms. The user is then asked to use the program to perform a science experiment determining the average response time of the *Euglena*, defined as the time it takes for the circular variance to stabilize, meaning the

line on the circular plot remains consistent and the data points on the plot stabilize around the white line.

SI6: Study 1 responses.

Note: several of the interface comments from below were fixed for user study 2 and user study 3.

What did you like about the API?

- (no response)
- I really like that the API segments each portion of the code into its own location. It's clean and organized. Having the API calls on the same page is also a fantastic idea. I dislike the idea of having to search through a separate page for information.
- I liked the thorough descriptions of each available method. I also felt like the API included methods for most of the functionality I wanted when programming my application.
- Already had some of the functions I needed.
- The API was very straightforward and simple to use. It does not take much time to ramp up on the API, which made it fun and way faster to move towards actually using the program.
- everything. it was awesome :)
- A lot! Simple and useful, with just about every basic function I would want. The tracking, id-ing, and rotation/velocity/acceleration functions are particularly nice to have.

What aspects of the API can be improved?

- I'm still pretty unfamiliar with how the code is set up, but I am wondering if it would be useful (if / once you have more traffic) to set up a virtual microscope as a code sandbox, so I can at least somewhat test my code without occupying a microscope. The virtual organisms don't even have to move or anything, as long as they correctly respond to countOrganisms() or whatever it would be really handy. Like, a screenshot of some experiment state that you can use on the IDE, with the various states using some constant
- Also, it would be fantastic if I could explore the API without having to hog a microscope to do so
- I believe a method that returns the IDs of all the euglena in a rect would be useful. I also feel like the API documentation could be organized a little more by clearly marking out a parameter subheading and a return value subheading for each method.
- Java would be great or Python.
- I think the API could be a little more robust in the information that it provides about each of the euglena. Size and age and other info tracked by ID could allow for some really cool experiments.
- It's be cool if the user could input number guesses (ie, guess the max of euglena and the min of euglena you'll see ten seconds from now, or, guess the closest/average distance bw two euglena, etc).
- getEuglenaInRect had some pretty whack behavior. Also, either getEuglenaVelocity should return a vector or it should be called getEuglenaSpeed.

What did you like about the online interface?

- (no response)
- It's very accessible. I really enjoy the fact that I'm able to save files online.
- I like being able to see the live euglena cam right next to my code and the ease of quickly seeing my changes reflected on it.
- Cloud computing.
- I liked how easily and quickly you are able to run your code and view a live sample of euglena. It was relatively simple to use and allowed you to see how your code can impact microorganisms in a really applicable way.
- everything. it was awesome :)
- I liked how there were text boxes for each function's

implementation! Made it more approachable than a giant text box.

What aspects of the online interface can be improved?

- seems like the event listeners aren't correctly absorbing events, e.g. when playing the 'game,' hitting spacebar still causes the page to scroll down half a page, etc. Might want to `event.stopPropagation()`? Also, it would be fantastic if I could explore the API without having to hog a microscope to do so.
- I would appreciate more feedback from the API itself to ensure that I'm not making mistakes. I would also appreciate a mode without a stream.
- I wish to be able to end an experiment early if I click the 'Home' button. Right now, if I exit an experiment this way, I still have to wait for the timer to run out before I can start another experiment.
- Have more programs ready for examples.
- I think more comprehensive error messaging will be extremely important for helping people move fast on the platform. Also, one problem was definitely the fact that the space key could be used to 1) press the run button and 2) to interact with the program GUI. This can cause users to accidentally restart the program when they simply want to interact with the program, leading to unpredictable behavior within that program that is pretty hard to debug. Additionally, it is easy to overwrite saved files since new files are automatically saved when you access the provided programs and run them (a typical use case if you're debugging and want to see if your program is still working properly).
- Debugging— instead of just saying that 'Error in your code: There was an error in your code.' say what it was. Layout— I liked how one half of the screen was my code and the other half was the API/video, but I wish I could have scrolled separately (then I could see what I was coding AND look at the API that I wanted to see (because I couldn't do that, I just copied pasted what I was reading)). Waiting— didn't really like having to wait for other people to finish using it. Mistaken key presses— didn't really like that if you left during your coding session (like clicked on 'home' or something, you had wait until that session ended so you could go inside again (did that make sense??)).
- Printing error messages! 'There is a bug in your code' was a bit frustrating since I didn't know where to look. It'd be neat if there were line numbers in each function for it to point out error locations, maybe using some kind of mapping to edit the error message that JavaScript gives to print the function and relative line number. Also it would start flashing at the bottom annoyingly when I kept programming after it switched to the simulation. It would also be nice to be able to add helper functions, maybe with their own text boxes. Finally, it would be nice to have a console to log to rather than sending debugging text to things with limited length/no scrolling (like drawing text on the screen or appending to the instructions text).

Now that you are familiar with the API, what are some examples of applications you would build if you had more time?

- (no answer)
- I would have liked to build a game that involved collecting coins on screen while avoiding the Euglena. However, my experience with JavaScript is limited so it would require more time and dedication.
- better version of my agar.io app, euglena sprint where euglenas would race across the screen and their finish times would be recorded, pacman where the euglena act as ghosts
- A dance floor that synchronizes with the song of your choice.
- It would be really cool to build an application that visually tracked the euglena's movement across the screen and how they interact with each other. The paths that euglena take after coming within close proximity would be really interesting, as well as the paths they take in relation to light.
- not sure

- An experiment to test reaction time, an experiment where the direction of the light revolves at different speeds to see which is the fastest that can get the Euglena to reliably rotate in the same direction, or an experiment to study whether and how Euglena react when they get close to each other.

What are some ideas you have for extending the API and online interface?

- (no answer)
- I would add an option to enter sandbox mode instead of selecting a live microscope.
- API: function to return all euglenas in rect; function to return elapsed time; function to return count of all euglena on screen (can be done with current function if bounding rect is set to screen rect); Interface: ability to end experiment early or to return to experiment if accidentally clicking 'Home'; alert if application crashed due to an internal error and instructions to reload
- More pre-built functions for faster coding.
- I would definitely add more extensive messaging and comprehensive debugging tools to make the IDE easier to use and faster to debug.
- See above for the 'can be improved' sections. Also, maybe emphasize when the code is running/is not? (currently you have an orange box appear around the pressed button, maybe make that less ugly and more noticeable? or have 'your code is running' pop up when the code is running?)
- See two questions ago. Also it'd have saved time on my experiment to have a control function that takes in an angle and magnitude and sets the LEDs the way it would be set by moving the joystick to that angle and magnitude.

Interface items fixed or added for user study 2 and 3

- We implemented the virtual sandbox simulation mode.
- The API documentation on the interface was written more clearly, with function input and output types more explicitly defined.
- Fixed the issue where the space bar mapped to scrolling behavior in some browsers. Instead, users were given full control of keypress behavior.
- Detailed stack traces were printed to the user when their program resulted in an error.

S17: Study 2 responses.

What did you like about the API?

- It was easy to understand. The pre-written examples were really helpful. I used those for syntax-lookup and to become familiar with the language. Just so you know, the 'space' key resets the whole program (it's the equivalent of the 'Run Program' button) in the avoidEuglena game for some reason, which you probably don't want.
- I liked that it incorporated all the features of javascript, and required minimal additional information to get started coding. Also the examples for the functions provided were useful.
- I think it is really cool, because being able to program applications based on data from living beings in such an easy way is a whole new thing.
- convenient access to biology experiment; data playback module is great
- The API was nice and clean

What aspects of the API can be improved?

- Maybe you can have pre-written functions or loops that people can look up and insert quickly into their code. For example, 'turn on this LED at time x', or 'record all positions of Cell 3 for the whole experiment with one data point every 2 seconds'. For a first time user, it's a lot of time to figure out syntax for everything, so some templates would speed it up a lot. For example, translating the `timeLeft` thing to a

more normal timestamp could be a pre-written function. You might also eventually want the user to be able to access the history of which buttons (or what joystick positions) they pressed during their session at what time, so that they can eventually compare that to their data.

- The API's documentation had a few minor errors, and was difficult to debug in. Also, the simulation mode sometimes did not draw properly.
- The debugging was a bit difficult. The programs crashed multiple times. So, just the normal stability issues would help. Other than that, it works well.
- each session is too short (workflow interruptions is painful)
- getTimeLeft() probably has bug ? it was giving me a negative number that was decreasing with time (increasing in magnitude).

What did you like about the online interface?

- It was easy to understand, and it was aesthetic.
- Everything was clean and easily accessible.
- It was fairly intuitive to use it, and structuring the code into start, run, end, keyPressed, etc., was very useful. It helps to have example codes, as well as all the functions that come with the API.
- live code playground format
- being able to code and see results side by side

What aspects of the online interface can be improved?

- It took me a while to understand how to operate the 'hidden' joystick when looking at the guessing LED game. Maybe you can have a button that says 'choose random joystick direction' instead. In general, you might want to have some buttons on the web interface that have simple commands (like 'randomize joystick'), or toggles things like 'label/don't label the Euglena' or 'show/hide LED direction'. Maybe you would be able to toggle them while the program is running.
- It would be nice if the area for the setInstructionText() had some word wrapping/scrolling capabilities for when I wanted to print very long arrays.
- It is probably my own fault, but I lost a lot of time building functions that actually already existed, like extracting the speed. Maybe making that more clear, that these functions exist, would help. It would be great if one could decide oneself whether one wants to be in Sandbox mode or not. I didn't have sufficient Euglena to play around with, so I ended up having to wait for at least one Euglena to show up. Sandbox mode would have helped.
- not able to test some functions in the simulation mode; some functions need more detailed documentations (example: not clear what output value of getRotation function actually means [units, orientation info, etc])
- the online editor is too squished (long lines get broken down and hard to see), also if there is a syntax error or something, that error either get reported without any context or sometimes completely hidden.

Now that you are familiar with the API, what are some examples of applications you would build if you had more time?

- One could measure a bunch of things about the way the Euglena are moving in response to the LEDs. For example, do they travel in a straighter line if the LED has a higher intensity? How long does it take for them to turn around if you change LED direction? Do they travel faster or slower when you change LED intensity? How predictable is their behavior?
- I think it would be cool to implement a program that incorporated some sort of feedback loop where the biological input directly triggered a light response. I'm not sure how to make this work on the correct time/spatial scale. But definitely the lower magnification would be ideal. Maybe it could be a feedback loop that automatically tried to keep a euglena in the field of view for as long as possible.
- I would like to build a more elaborate experiment protocol to test different behaviors of Euglena. Various little games

would be fun too, like for example 'tag all the Euglena before they leave the screen' or so.

- 3D Animation control with euglena swarm behavior
- Test the speed of euglena as you increase light intensity over time.

What are some ideas you have for extending the API and online interface?

- There's the thing I mentioned earlier about being able to access the history of the buttons you pressed during the session. I also think that it would be nice to be automatically given a visual of all the cell tracks that got recorded in your session as soon as it's over. Maybe you can select the cells that looked interesting to you and replay the movie with those highlighted or something. In terms of data recording, you can have an interface that lets you choose how often you want to record, and what you want to record/calculate from each cell (position, velocity, etc) at the beginning of the experiment. So basically, reducing that part of the code to an interface. It would also be nice to zoom in and out of the video while the experiment/game is going on, so that you can look at specific cells. But I don't know if that is a challenge optically. Maybe eventually, you'll be able to click on a Euglena and follow it, so that it doesn't go out of frame.
- See above my comment on word wrap. It would be nice to have some more consistent way to receive error messages, or step through the code line by line.
- Definitely an easier programming interface, that does not rely on knowledge of javascript would help. Also, being able to run a script on multiple BPU at the same time (especially for experiment purposes).
- it would be great if user can upload/link external libraries or their own js files
- have a separate window/tab for coding, possibly debugging interface too.

S18: Study 3 responses.

Program 1: How does moving the sliders affect the Euglena organism behaviors (it may take 20-30s to see an effect)?

- they seem to be confused before they move away from the light
- They seem to move toward the light when the sliders are turned up.
- They move away
- I should have read this first before playing around. I didnt see anything
- They seem to be moving away from the light.
- they move away
- the euglena move away from the light, and they move faster when the intensity is greater
- The organisms appear to be moving away from the side that I increase the slider on.
- They appear to be spinning.
- It looks like the Euglena are repelled by wherever the light is, which can be seen by the Euglena entering the screen from the side with light but not exiting the screen on that same side, while they're freely appearing in and out of the screen on the other three non-lit sides.
- Sometimes it makes them more likely to turn in circles. Other times it makes the move more rapidly.
- Initially, the euglena spin in circles without direction and they eventually move away from the side with slider on.
- Euglena move away from the slider that is activated.
- It affects their speed and rotational movement

Program 2: How does 'alpha' change in response to the light direction controlled by the sliders?

- higher on the L/R lights, lower on the top/bottom
- it is lower when the bottom slider is on
- lower when coming from top or bottom
- ?

1861	- Not sure what is alpha.	<i>If no, why?</i>	1923
1862	- Alpha increases when the light is on. Alpha is at 90 degrees	- no, opposite (previously R/L was 90 degrees)	1924
1863	when the left or right lights are on, and $A=0^*$ when the up	- Yes, because it corresponds to the angle of the light.	1925
1864	or down lights are on.	- Yes, it indicates the direction of movement	1926
1865	- it doesn't - alpha is based on the intensity of the pull from	- I dk	1927
1866	the sliders	- No, the degrees seem to be different depending how you are	1928
1867	- Left and right cause the alpha to be an average of 90 degrees,	from the center of the circle.	1929
1868	top and bottom sliders move alpha towards 0.	- Not sure	1930
1869	- Right and Left result in an alpha of 90	- what?	1931
1870	- Relatively low for bottom and top sliders, relatively higher	- Yes. The top/bottom sliders cause alpha to stabilize at 0	1932
1871	for left and right sliders	degrees, so the arrow within the circular plot faces up down	1933
1872	- I don't detect a consistent change. If I had to guess, it seems	(it's not rotated). When the left/right sliders are increased	1934
1873	like the sliders raise the alpha?	alpha stabilizes at 90 degrees which moves the arrow in the	1935
1874	- alpha is either +/- 90 in response to light direction	circle to point left/right.	1936
1875	- 0 when bottom slider is on; 90 when left/right slider is on;	- Seems to be	1937
1876	180 when top slider is on	- If the circular plot's behavior relates to the Euglena's	1938
1877	- The average value changes based on the slider that is turned	direction of motion, then yes, the circular plot's behavior is	1939
1878	on	consistent with the plot of alpha vs time from the previous	1940
1879	<i>Program 2: What does the 'alpha' variable represent (hint: the</i>	section. If the left slider is on, the Euglena move left to right	1941
1880	<i>unit of 'alpha' is degrees)?</i>	and the line represents horizontal motion. If the bottom	1942
1881	- XY axis	slider is on, the Euglena move bottom to top and the line	1943
1882	- the angle of the light on the Euglena	represents vertical motion.	1944
1883	- direction of movement	- I'm not sure - sorry if I am a bad study participant!	1945
1884	- I don't remember physics or math	- Yes, the circular plot visualizes the same +/- 90 direction	1946
1885	- Not sure what is alpha.	change of the euglena in response to light. Left/right in the	1947
1886	- Direction of movement	circular plot is the same as 0 in the time plot.	1948
1887	- temperature	- Yes - displays the average angle of motion of the Euglena	1949
1888	- The rotation of the organism?	over time.	1950
1889	- angle of the light	- yes but it's harder to visualize because there were very	1951
1890	- Angle	organisms so the line would move constantly.	1952
1891	- Maybe it is the temperature of the Euglena?	<i>Program 4: What do you think the length of the line represents?</i>	1953
1892	- alpha is probably average of the degree of trajectory of the	<i>We will call this value 'R'.</i>	1954
1893	euglena	- how much movement is occurring	1955
1894	- Average angle of motion of the Euglena with respect to	- How many Euglena remain in an opposing direction from	1956
1895	12:00.	the light	1957
1896	- I think it's the average direction of movement. So if the left	- speed	1958
1897	slider is on then the organisms move 90 degrees clockwise (ie	- The more organisms traveling that direction increases the	1959
1898	to the right?) and when the bottom is turned on alpha is 0	line length.	1960
1899	meaning that they just go straight up.	- The intensity of the light.	1961
1900	<i>Program 2: What have you learned about how Euglena organ-</i>	- collective direction of movement (also why is sandbox mode	1962
1901	<i>isms respond to light coming from different directions?</i>	not a thing for this use study??? i feel like you will be able	1963
1902	- confusion before moving away from light	to see the difference better that way)	1964
1903	- they move slower/faster depending on the alpha	- average speed of the euglena	1965
1904	- Euglena move away from the direction of light	- Perhaps it's the average distance of the euglena from the	1966
1905	- They tend to move away from light according to the	light source. Honestly though it's hard to tell, the size of the	1967
1906	simulated version	line was pretty jumpy even after letting it stabilize for a few	1968
1907	- They seem to go away from it.	minutes.	1969
1908	- They move at different rates	- Consistency of the Euglena's direction	1970
1909	- euglena hate light! they swim away from light, especially	- Maybe R represents the magnitude of the potential of	1971
1910	intense light	movement from Euglena. When a slider is on, the Euglena	1972
1911	- In the simulation it is really obvious that the organisms are	are 'encouraged' to move away from the side with the slider	1973
1912	moving away from the side I increase the brightness on, but	on which limits the Euglena's potential range of preferred	1974
1913	in the live view it looks like some of the organisms still move	movement.	1975
1914	all over the place but mostly away from the increased light	- consistency in the movement of the Euglena	1976
1915	source. Based on what I'm seeing they don't seem to like	- noise of euglena movement. Not all of the euglena move	1977
1916	light.	cleanly in one direction and the variation of the movement in	1978
1917	- The move away from light.	the euglena could be represented by R . The simulation had	1979
1918	- The light changes the angles at which the Euglena move	more stable R values than the live euglena.	1980
1919	because they seem to be repelled by the light.	- Average distance between the Euglena?	1981
1920	- They go away from it	- Something to do with the number of organisms - maybe the	1982
1921	- Euglena dislike intense light and tend to move away from	ratio moving in the opposite direction as the light?	1983
1922	bright light sources. The simulation euglena have cleaner	<i>Program 5: Explain what the value of R corresponds to, in</i>	1984
	more defined swarmed movement i.e. less noise when a light	<i>terms of the Euglena 'alpha' values? (Hint: think about the concept</i>	
	source is turned on. Real euglena have slower response time	<i>of standard deviation)</i>	
	and seem to have an initial phase of 'light stunned/shocked'	- whether all of the euglena move in the same direction (and	
	where they move in no direction and are disoriented.	how similar/correlated those are)	
	- They move away from the source of light.	- Instantaneous alpha	
	- They travel in the opposite direction of the light I think	- R is the percentage of euglena moving in the direction	
		caused by the light?	
		- So I think a is the is the direction of travel in regards to a	
		circle. while R is the percentage of how Euglena traveling the	

1985	most traveled direction, the length of the line represents the	- It seems like the Euglena respond faster to the higher	2047
1986	R value, line direction is the alpha value in degrees. So R can	intensities of light. Especially because the red dots stabilize	2048
1987	be used to represent the standard deviation of the average of	much faster around the white lines when the light is more	2049
1988	the Euglena moving that direction. or something	intense. However, other times it seemed like there wasn't a	2050
1989	- The larger the R the bigger the brighter the light.	large difference.	2051
1990	- Not sure	- Lower intensities result in a faster stabilization rate because	2052
1991	- the value of R (the speed of the euglena) corresponds	there is not a stunned directionless state for the euglena but	2053
1992	directly to alpha values (the intensity of light); the speeds at	it seems as though the R value is bigger in the lower intensity	2054
1993	any one light intensity is normal distributed in the sample	light as if euglenas have more degrees of freedom being able	2055
1994	- The amount or percentage of euglena that are at a particular	to move diagonally away from the light rather than just	2056
1995	alpha value.	directly opposite of the light.	2057
1996	- Appears to be deviation from the mean	- If the intensity is too low, the Euglena respond very little.	2058
1997	- I think that the value of R represents the range of preferred	It seemed to me that a high intensity has to be used in order	2059
1998	direction of motion of Euglena as explained by when 'alpha'	to observe any change.	2060
1999	values become more stable/fixed around a certain value range,	- Yes it takes much longer to stabilize with higher R values	2061
2000	R tends to have a lower value.	when intensity is low.	2062
2001	- Maybe how much degree of change there is in the motion of		2063
2002	the Euglena over time	<i>Post-study: What differences did you notice in the simula-</i>	2064
2003	- R might represent the amount of variation in angle of	<i>tion/sandbox vs. live modes?</i>	2065
2004	euglena from true directions (i.e. left, right, up, down).	- Wasn't sure how to use the simulation mode	2066
2005	- The realtime standard deviation of the angle of motion of	- Simulation did not have any lag.	2067
2006	the Euglena. High R indicates that there is a wide variation	- The sandbox was quicker to respond since it's not real	2068
2007	in the angles of motion of the Euglena; low R means the	- The simulation had showed a clear representation of how	2069
2008	angles of motion of the Euglena are close to some average	Euglena would respond to light. The live version did not	2070
2009	value.	seem to follow the theory or not noticeably.	2071
2010	- Maybe the standard deviation form the alpha value	- Simulation is much faster.	2072
2011		- Euglena are much more responsive in simulation mode,	2073
2012	<i>Program 5: In seconds, about how long does it take for Eu-</i>	results are hard to interpret in live simulation	2074
2013	<i>glena to respond to light stimuli? Measure this as the time it takes</i>	- The euglena behaved more predictably in the sandbox mode.	2075
2014	<i>for the 'alpha' values (representing average angles of Euglena ro-</i>	I often messed around in the live mode confused, then the	2076
2015	<i>tation) to stabilize around the white line after the light direction</i>	sandbox mode made my uncertain conclusions about the	2077
2016	<i>has changed.</i>	effect of light more clear.	2078
2017	- 10 seconds	- The behavior in live mode in much messier and complex.	2079
2018	- 30s	- The simulation is much more responsive.	2080
2019	- 40s	- The simulation gives a more accurate reading, while the live	2081
2020	- Never :/	mode is more realistic and takes a bit longer to try and make	2082
2021	- Seconds.	hypotheses from.	2083
2022	- Unclear	- I thought the sandbox mode was way easier because the	2084
2023	- 6	Euglena responded much faster	2085
2024	- 50 seconds	- Simulation has faster, cleaner response times. High intensity	2086
2025	- About a minute IRL, almost immediately in the simulation	light in simulation doesn't result in stunned euglena.	2087
2026	- 2-3 seconds	- Simulation mode is much quicker to respond and as a result	2088
2027	- 20-30 seconds	is easier to observe.	2089
2028	- 60 seconds	- In the simulation the behavior seems almost fake. The	2090
2029	- 40 seconds live / 5 seconds simulation	randomness and unpredictability of live organisms is missing.	2091
2030	- around 50 seconds		2092
2031		<i>Post-study: Do you prefer using the simulation or live mode?</i>	2093
2032		<i>Why?</i>	2094
2033	<i>Program 5: Do the Euglena respond differently to different in-</i>	- Live mode - easier to play around with and observe the	2095
2034	<i>intensities of light? Explain in terms of the time it takes for the</i>	behaviors	2096
2035	<i>'alpha' values (representing average angles of Euglena rotation)</i>	- Live mode, because it was cool to get a real reaction from	2097
2036	<i>to stabilize around the white line at different light intensities (or</i>	the Euglena.	2098
2037	<i>whether they stabilize at certain slider values).</i>	- Live mode because you get to see how the organism actually	2099
2038	- yes, stabilization happened immediately when the light was	respond rather than how they are supposed to.	2100
2039	dimmer	- I preferred the live version, because they are cute.	2101
2040	- It seemed like the higher intensity caused them to respond	- Simulation.	2102
2041	faster.	- playing around in live mode is more fun but much harder to	2103
2042	- They stabilize slower	interpret plots	2104
2043	- They did not seem to be very responsive to light, therefore	- The live mode is pretty neat (I'm controlling a lightbulb far	2105
2044	I always tried max intensity.	away?!), but I think the simulation mode is easier to use.	2106
2045	- Bright light they seem to move away from, low lighting they	- Live mode, it was cool being able to control living organisms	2107
2046	spin in circles.	in real-time.	2108
	- Not sure	- Live mode-it's more fun to watch the real Euglena!	
	- The greater the intensity of light, the quicker and more	- For accurate readings/answers, i prefer the simulation. For	
	precisely alpha values will stabilize around the while line	actual experimentation purposes, I prefer the live mode. Both	
	- It looked around the same to me regardless of intensity.	modes have their positives and negatives.	
	- It seems like it should take longer for the alpha to stabilize	- I liked live mode better because it seemed more realistically	
	at lower intensities. The simulation didn't really express that	slow	
	though.	- I prefer both because simulation gives quicker results but it	
	- Yes, the Euglena respond differently to different intensities	doesn't give any interesting information on why the euglena	
	of light. I would say it takes significantly longer for the	get stunned or how long they are 'paralyzed'	
	'alpha' values to stabilize around the white line at different	- Live mode is much more fun to use because the experiment	
	light intensities; the smaller the light intensity, the longer it	feels real. (Maybe if the simulation looked more similar to	
	takes for the 'alpha' values to stabilize.		

2109	the real deal this would be different?)	2171
2110	- Overall I prefer to use the live mode because it more closely	2172
2111	represents the behavior of the organism that I'm trying to	2173
2112	study. Having said that I often found myself having to wait	2174
2113	for the microscope to be available which is annoying and also	2175
2114	sometimes there weren't many organisms available on the	2176
2115	screen. If there were more microscopes so I didn't have to	2177
2116	wait for one and also could select the one with most organisms	2178
2117	at that moment, It would have improved the experience of	2179
2118	using the live mode.	2180
2119	<i>Post-study: What did you learn about Euglena organisms from</i>	2181
2120	<i>this study?</i>	2182
2121	- In terms of observing directional changes, pretty easy to	2183
2122	understand. Just took some time.	2184
2123	- Euglena hates too much light!	2185
2124	- I learned that Euglena respond to light stimuli	2186
2125	- They are supposed to react to light.	2187
2126	- They do not seem to like the light.	2188
2127	- same as before	2189
2128	- Euglena don't like light (the more intense the worse), they	2190
2129	swim away from light at an angle dependent on the source	2191
2130	and intensity of light, and they look like grains of rice.	2192
2131	- They are not big fans of light and they are easy to control	2193
2132	with a seemingly basic setup.	2194
2133	- Euglena move away from light.	2195
2134	- Euglena are repelled by light and using light can affect their	2196
2135	preferred movement.	2197
2136	- I learned they dislike light and try to go away from it	2198
2137	- The program provided very clear visuals on the direction	2199
2138	and intensity of the light and it was easy to draw a connection	2200
2139	between the behavior of the euglena and the settings of the	2201
2140	light source	2202
2141	- They run away from light.	2203
2142	- That they move away from the light source and the	2204
2143	movement is correlated with the intensity of light.	2205
2144		2206
2145	SI9: Descriptions of user programs.	2207
2146		2208
2147		2209
2148		2210
2149	Study 2.	2211
2150		2212
2151	• Participant 1: The application allows the experimenter to control the LEDs (top and bottom only) and record how many cells were on the top half and the bottom half, to see if cell numbers would decrease in the top half if the top LED is turned on. Lines of code: 41.	2213
2152		2214
2153		2215
2154	• Participant 2: This participant created two programs. One program is an experiment to determine whether it is better to use a flashing light stimulus or a steady light stimulus to induce 90 degree turns in <i>Euglena</i> . The procedure is to hold the light on for 10 seconds and detect <i>Euglena</i> swimming in the correct direction, saving their IDs, velocity, and position. If testing steady light, the program turns on the appropriate LED to induce 90 degree turn (steady light) for 5 seconds. If testing flashing light, the program turns on the appropriate LED to induce a 90 degree turn for 0.4 seconds, and turns it off for 0.1 seconds, checking the time remaining each time, for a total of 5 seconds. Lines of code: 121. The other program is a two-player game. The first player lines up a virtual green circle 'ball' using the A and D keys and 'shoots' it with space. The second player then uses the W, A, S, and D keys to control LEDs to try to steer the <i>Euglena</i> . Lines of code: 104.	2216
2155		2217
2156		2218
2157		2219
2158		2220
2159		2221
2160		2222
2161		2223
2162		2224
2163	• Participant 3: Displays the average velocity of all organisms on the screen, updated in real time. The program also displays the ID of all organisms next to the organism. Lines of code: 57.	2225
2164		2226
2165		2227
2166		2228
2167	• Participant 4: Displays the average orientation of all organisms in the display area. The visualization is a white line oriented towards the current average orientation, as shown in Fig. 5A. The program also displays the count of the organisms. Lines of code: 110.	2229
2168		2230
2169		2231
2170		2232

```

2233 SI10: realtime plot of x-velocity over time with user joystick control
2234 of light stimulus.
2235     start():
2236
2237
2238 // Data points.
2239 this.xVals = [];
2240 this.yVals = [];
2241
2242 // Axis constants.
2243 this.X_START = 100;
2244 this.X_END = 600;
2245 this.Y_START = 10;
2246 this.Y_END = 300;
2247
2248 // Data point extrema.
2249 this.MIN_X = 0;
2250 this.MAX_X = 20;
2251 this.MIN_Y = -0.2;
2252 this.MAX_Y = 0.2;
2253
2254 // Time tracking variables.
2255 this.currTime = 0;
2256 this.DATA_COLLECTION_PERIOD = 100;
2257 this.MAX_TIME = this.MAX_X*this.DATA_COLLECTION_PERIOD;
2258
2259 // Function to convert X-data point to pixel coordinate.
2260 this.dataToPixelX = function(dataVal) {
2261     return ((dataVal - this.MIN_X) /
2262             (this.MAX_X - this.MIN_X)) *
2263             (this.X_END - this.X_START) + this.X_START;
2264 }
2265
2266 // Function to convert Y-data point to pixel coordinate.
2267 this.dataToPixelY = function(dataVal) {
2268     return ((dataVal - this.MIN_Y) / (this.MAX_Y -
2269     this.MIN_Y)) * (this.Y_END - this.Y_START) +
2270     this.Y_START + Math.random();
2271 }
2272
2273 run():
2274
2275 // Draw axes.
2276 drawLine(this.X_START, this.Y_END, this.X_END,
2277     this.Y_END, COLORS.BLUE); // X axis
2278 drawText("Time", this.X_START, this.Y_END + 25,
2279     0.45*MAX_TEXT_SIZE, COLORS.WHITE);
2280 drawLine(this.X_START, this.Y_START, this.X_START,
2281     this.Y_END, COLORS.BLUE); // Y axis
2282 drawText("Average", 5, this.Y_END - 250,
2283     0.45*MAX_TEXT_SIZE, COLORS.WHITE);
2284 drawText("Velocity", 5, this.Y_END - 220,
2285     0.45*MAX_TEXT_SIZE, COLORS.WHITE);
2286
2287 // Plot graph.
2288 var dataPointsLength = this.xVals.length <= this.MAX_X ?
2289     this.xVals.length : this.MAX_X;
2290 for (var i = 1; i < dataPointsLength; i++) {
2291     // Convert from data space to pixel space.
2292     var xStart = this.dataToPixelX(this.xVals[i-1]);
2293     var xEnd = this.dataToPixelX(this.xVals[i]);
2294     var yStart = this.dataToPixelY(this.yVals[i-1]);
2295     var yEnd = this.dataToPixelY(this.yVals[i]);
2296
2297     // Draw from one data point to the next.
2298     drawLine(xStart, yStart, xEnd, yEnd, COLORS.RED);
2299 }
2300
2301 // Increase time and calculate average velocity at this
2302 // time if it is valid to do so.
2303 this.currTime++;
2304 if (this.currTime % this.DATA_COLLECTION_PERIOD === 0 &&
2305     this.xVals.length < this.MAX_X) {
2306     this.currTime = 0;
2307
2308     var euglenaIDs = getAllEuglenaIDs();
2309     var listLength = euglenaIDs.length;
2310     var avgVelocity = 0;
2311     for (var i = 0; i < listLength; i++) {
2312         var currVelocity = getEuglenaVelocity(euglenaIDs[i]).x;
2313         if (currVelocity <= this.MAX_Y &&
2314             currVelocity >= this.MIN_Y) {
2315             avgVelocity += currVelocity;
2316         }
2317     }
2318     avgVelocity /= (1.0*listLength);
2319     this.xVals.push(this.xVals.length + 1);
2320     this.yVals.push(avgVelocity);
2321 }
2322
2323 end():
2324
2325 [no code]
2326
2327 onJoystickChange(angle, intensity):
2328
2329 var ledIntensity = intensity / 1000.0;
2330 if (angle >= 45 && angle < 135) {
2331     setLED(LED.UP, ledIntensity);
2332 } else if (angle >= 135 && angle < 225) {
2333     setLED(LED.RIGHT, ledIntensity);
2334 } else if (angle >= 225 && angle < 315) {
2335     setLED(LED.DOWN, ledIntensity);
2336 } else if (angle >= 315 && angle <= 360 &&
2337     angle < 45 && angle >= 0) {
2338     setLED(LED.LEFT, ledIntensity);
2339 }
2340
2341 onKeypress(key):
2342
2343 [no code]

```

```

2357 SI11: Guess the LED.
2358
2359 start():
2360 this.currLED = LED.RIGHT;
2361 this.possibleLEDs = [LED.UP, LED.DOWN, LED.RIGHT, LED.LEFT];
2362 this.instructions = "Guess which LED is currently shining. " +
2363     "Press 'W' for top LED, 'A' for left LED, 'S' for " +
2364     "bottom LED, and 'D' for right LED.";
2365 this.score = 0;
2366 setJoystickVisible(false);
2367 var instructionText = "Which LED is currently shining? " +
2368     "Press 'W' for up, 'A' for left, 'S' for down, or 'D' " +
2369     "for right.";
2370 setInstructionText(instructionText);
2371 this.guessedKey = 'W';
2372 this.lastCorrect = 0;
2373
2374 run():
2375
2376 drawText("WHERE ARE EUGLENA RUNNING FROM?", 10, 30,
2377     0.6*MAX_TEXT_SIZE, COLORS.BLUE);
2378
2379 drawText("Press W, A, S, or D for up, left, down, or right.",
2380     10, 60, 0.5*MAX_TEXT_SIZE, COLORS.BLUE);
2381
2382 drawText("Guess 10 in a row correctly to win.",
2383     10, 90, 0.5*MAX_TEXT_SIZE, COLORS.BLUE);
2384
2385 drawText("Number correct: " + this.score, 10,
2386     150, 0.9*MAX_TEXT_SIZE, COLORS.GREEN);
2387
2388 if (this.lastCorrect === 1) {
2389     drawText("You guessed '" + this.guessedKey +
2390         "' correctly.", 10, 200, 0.5*MAX_TEXT_SIZE,
2391         COLORS.BLUE);
2392 } else if (this.lastCorrect === 2) {
2393     drawText("You guessed '" + this.guessedKey +
2394         "' incorrectly.", 10, 200, 0.5*MAX_TEXT_SIZE,
2395         COLORS.RED);
2396 }
2397
2398 setLED(this.currLED, 999);
2399 if (this.score >= 10) {
2400     endProgram();
2401 }
2402
2403 end():
2404
2405 setJoystickVisible(true);
2406 if (this.score >= 10) {
2407     alert('Guess correctly 10 times, congrats!');
2408 }
2409
2410 onJoystickChange(angle, intensity):
2411
2412 [no code]
2413
2414 onKeypress(key):
2415
2416 switch(key) {
2417     case KEY.W:
2418         if (this.currLED == LED.UP) {
2419             this.lastCorrect = 1;
2420             this.guessedKey = 'W';
2421             this.score += 1;
2422             this.currLED = this.possibleLEDs[Math.floor(
2423                 Math.random() * this.possibleLEDs.length)];
2424         } else {
2425             this.lastCorrect = 2;
2426             this.score = 0;
2427         }
2428         break;
2429     case KEY.S:
2430         if (this.currLED == LED.DOWN) {
2431             this.lastCorrect = 1;
2432             this.guessedKey = 'S';
2433             this.score += 1;
2434             this.currLED = this.possibleLEDs[Math.floor(
2435                 Math.random() * this.possibleLEDs.length)];
2436         } else {
2437             this.lastCorrect = 2;
2438             this.score = 0;
2439         }
2440         break;
2441     case KEY.D:
2442         if (this.currLED == LED.RIGHT) {
2443             this.lastCorrect = 1;
2444             this.guessedKey = 'D';
2445             this.score += 1;
2446             this.currLED = this.possibleLEDs[Math.floor(
2447                 Math.random() * this.possibleLEDs.length)];
2448         } else {
2449             this.lastCorrect = 2;
2450             this.score = 0;
2451         }
2452         break;
2453     default:
2454         break;
2455 }
2456
2457 this.lastCorrect = 1;
2458 this.guessedKey = 'A';
2459 this.score += 1;
2460 this.currLED = this.possibleLEDs[Math.floor(
2461     Math.random() * this.possibleLEDs.length)];
2462 } else {
2463     this.lastCorrect = 2;
2464     this.score = 0;
2465 }
2466 break;
2467 case KEY.S:
2468     if (this.currLED == LED.DOWN) {
2469         this.lastCorrect = 1;
2470         this.guessedKey = 'S';
2471         this.score += 1;
2472         this.currLED = this.possibleLEDs[Math.floor(
2473             Math.random() * this.possibleLEDs.length)];
2474     } else {
2475         this.lastCorrect = 2;
2476         this.score = 0;
2477     }
2478     break;
2479 case KEY.D:
2480     if (this.currLED == LED.RIGHT) {
2481         this.lastCorrect = 1;
2482         this.guessedKey = 'D';
2483         this.score += 1;
2484         this.currLED = this.possibleLEDs[Math.floor(
2485             Math.random() * this.possibleLEDs.length)];
2486     } else {
2487         this.lastCorrect = 2;
2488         this.score = 0;
2489     }
2490     break;
2491 default:
2492     break;
2493 }

```


2481 **SI12: Comparison of Bioty program to traditional program.**

2482
2483 In order to come up with a rough estimate of the work that
2484 would be involved to make the same program without Bioty, we
2485 analyze the code for the realtime plot of x-velocity over time with
2486 user joystick control of light stimulus (SI10). When spaces and
2487 comments are removed, this program has 60 lines of code. With-
2488 out Bioty, we estimate that this program would require at least
2489 several hundreds of lines of code and a vast amount of engineering
2490 knowledge beyond JavaScript programming.

2491 First, we expand each API function called in the program
2492 once, assuming that a user could write a subroutine themselves.
2493 The API functions called in SI10 are: *drawLine*, *drawText*,
2494 *getAllEuglenaIDs*, *getEuglenaVelocity*, and *setLED*. The first two
2495 functions are drawing functions, which could be implemented
2496 in one line of code without Bioty. The following are estimates
2497 of the lines of code required for each of the remaining API functions:

2496 *getAllEuglenaIDs*

2497 Assigning an ID to each organism requires multi-object tracking.
2498 Our multi-object tracking implementation, written in C++ using
2499 OpenCV to create a Kalman Filter paired with the Hungarian Al-
2500 gorithm, is over 1000 lines of code. As a generous estimation, we
2501 assume that a developer writing concise code could get a working
2502 implementation in about 500 lines of code.

2503 Since object tracking would usually not be implemented in
2504 JavaScript due to performance reasons, additional code is required
2505 to communicate between the C++ and JavaScript layers. Our im-
2506 plementation using PNaCl includes over 20 lines of C++ and over
2507 100 lines of JavaScript code for this communication. A concise de-
2508 veloper may be able to implement this in 50 lines of JavaScript and
2509 C++ code combined.

2510 In total, the implementation of *getAllEuglenaIDs* and multi-
2511 object tracking in general would take 650 lines of code.

2510 *getEuglenaVelocity*

2511 Once the multi-object tracking is implemented, only 2 extra

lines of code are required for calculating velocity and bookkeeping
the velocity for all organisms.

setLED

Turning on an LED requires the implementation of two servers:
one for the web server and one running on the embedded device
controlling the microscope video feed and LED lights. Using an
efficient web framework like ExpressJS, each base server could be
implemented in at least 10 lines of code. Using extremely generous
estimates, the code for communicating commands between servers
could be implemented in 10 lines each, the code for reading from a
live camera stream could be 10 lines. In our actual implementation,
the number of lines of code required for all of these tasks is several
orders of magnitude greater than these estimates.

Added together, implementing the code from scratch would re-
quire about 700 additional lines of code, spread over at least two
systems. This means that Bioty results, generously, in at least a
10x decrease in the amount of code required. Using our underlying
cloud lab implementation (a more realistic example), it would re-
quire thousands of lines of code to implement the same application.
This code expansion is representative of the code savings for most
programs written in Bioty that make use of both the organism and
sensor API functions. We also note that as any program expands in
code size, the development time for each additional line of code is
not linear but rather scales logarithmically due to the dependencies
between the software components.

Beyond pure lines of code, a significant amount of knowledge is
required to create such programs. The required knowledge includes
object tracking algorithm fundamentals, how to develop a server
to handle remote requests, development of an embedded system
which can control LED lights, frontend development knowledge for
drawing to an HTML canvas, handling live image streams, basic
microfluidics, and basic microscopy. Much of the work cannot be
quantified as it involves hardware development and working with
a wet lab.