Dual stochasticity in the cortex as a biologically plausible learning with the most efficient coding

Jun-nosuke Teramae

Graduate School of Informatics, Kyoto University, Kyoto, Japan

teramae@acs.i.kyoto-u.ac.jp

Abstract

Neurons and synapses in the cerebral cortex behave stochastically. The advantages of such stochastic properties have been proposed in several works, but the relationship and synergy between the stochasticities of neurons and synapses remain largely unexplored. Here, we show that these stochastic features can be inseparably integrated into a simple framework that provides a practical and biologically plausible learning algorithm that consistently accounts for various experimental results, including the most efficient power-law coding of the cortex. The derived algorithm overcomes many of the limitations of conventional learning algorithms of neural networks. As an experimentally testable prediction, we derived the slow retrograde modulation of the excitability of neurons from this algorithm. Because of the simplicity and flexibility of this algorithm, we anticipate that it will be useful in the development of neuromorphic devices and scalable AI chips, and that it will help bridge the gap between neuroscience and machine learning.

Introduction

Neurons in the cortex continuously generate irregular spike trains with fluctuating membrane potentials and greatly varying firing rates, even across trials in which an animal exhibits appropriate responses and learning in a precisely repeatable manner [1-7]. It has also been found that synapses in the cerebral cortex behave stochastically [8]. The formation, elimination and volume change of dendritic spines exhibit random fluctuations [9-15]. The release of neurotransmitter from synapses is also an inherently stochastic process [16-18].

Theoretically, it has been pointed out that algorithms incorporating these stochastic features can carry out nearly optimal computation in a noisy environment through

34 Bayesian inference [19-28]. To this time, however, the stochastic behaviors of neurons
35 and synapses have been studied separately. It remains unclear if the apparent advantage
36 gained from stochasticity depends on both neurons and synapses behaving stochastically,
37 and if so, whether there is a synergetic interaction between these two types of stochastic
38 behavior. It is also uncertain how learning generated by stochastically functioning
39 neurons and synapses can yield appropriate and precisely repeatable behavioral
40 responses.

41

42 In this paper, we show that the stochastic behaviors of neurons and synapses can be
43 inseparably integrated into a simple framework of a sampling-based Bayesian inference
44 model, in which their synergy provides an effective and flexible learning algorithm that is
45 consistent with various experimental findings of the cortex. The derived algorithm
46 accurately describes the plasticity of cortical synapses [29, 30], while it faithfully
47 generates the extremely different timescales of neural and synaptic dynamics, the
48 higher-order statistics of the topology of local cortical circuits [31], and the response
49 properties of cortical neurons, including Gabor-filter-like receptive fields [32, 33], a
50 positive relationship between the receptive field correlation and average connection
51 weight between neurons [34], and the nearly optimal power-law scaling of population
52 activity of neuron [7]. These results strongly suggest that the stochastic behaviors of
53 neurons and synapses are both essential attributes of neural computation and learning. As
54 an experimentally testable prediction of the proposed model, we derive the slow
55 retrograde modulation of the excitability of neurons by postsynaptic neurons. As far as
56 the author is aware, this is the first prediction of its kind and experiments to verify the
57 existence of such slow retrograde modulation have not yet been attempted.

58

59 The proposed algorithm can be regarded as a natural integration of the conventional
60 learning theories, error backpropagation learning [35, 36], Bayesian inference [21],
61 Boltzmann machine learning [37], and reinforcement learning [38]. This algorithm can
62 be regarded as an extension of a Boltzmann machine, and it acts as a stochastic variant of
63 error backpropagation. However, the proposed algorithm overcomes most of the
64 limitations that caused backpropagation not to be regarded as the learning principle of the
65 brain. Unlike backpropagation learning, the proposed algorithm does not require neither
66 objective functions, the fine-tuning of parameters, coordinated or synchronous updates of

variables, a feed-forward network structure, or the alternating execution of forward and backward computations [35]. Instead, learning is realized through repetition of local and asynchronous stochastic updates of states of neurons and synapses in a network. Because the algorithm is not derived as an optimization of objective functions, it rarely exhibits serious overfitting. We also discuss the close relationship between our algorithm and the temporal difference (TD) learning [38] of reinforcement learning.

Results

Neural networks

Most connections between cortical neurons are redundantly realized by multiple synapses [27, 39]. Introducing this redundancy and stochasticity of the neurons and synapses, we model a neural network whose connections are all realized by multiple synapses. Within this model, each neuron and synapse is represented by a binary stochastic variable (Fig. 1a, Methods). The value of a neural variable determines whether that neuron generates a spike, whereas the value of a synaptic variable determines whether that synapse contacts a dendrite of the postsynaptic neuron. A neuron in the network receives inputs from presynaptic neurons and generates a spike with a probability that is a function of the sum of these inputs (see Methods). External inputs, including the target outputs of supervised learning, are presented to the network as variables for some neurons, namely visible neurons, are fixed to values of these input variables. These input data, thus, should be represented by binary vectors. Other neurons in the network, which do not receive external data directly, are referred to as “hidden neurons”.

Biologically plausible learning

With the fundamentals of the network as described above, we formulate learning in the network as a continuing sampling of all the free variables, which include variables representing all synapses and hidden neurons, in the network from a posterior distribution conditioned on the external environment or a given dataset (see Methods). In other words, we hypothesize that the stochastic dynamics of the neurons and synapses in the cortex constitute a continuing random process that aimed at generating a network that suitably interprets the external world.

A sampling from the posterior distribution is computationally and biologically intractable

100 in general, due to the high dimensionality of the system and the complex dependencies
 101 among its variables. To solve this problem, we hypothesize that the sampling in the cortex
 102 is a Gibbs sampling [40]. The Gibbs sampling ensures that we can replace a sampling
 103 from the high dimensional posterior distribution with iterative samplings of each variable
 104 from a posterior distribution of that variable conditioned on all other variables.
 105 Furthermore, due to the flexibility of the Gibbs sampling, each sampling can be
 106 performed in any order and with any frequency. This implies that each neuron and
 107 synapse can asynchronously and irregularly update their variables with their own
 108 individually determined timings without any global schedule or coordination among
 109 them.

110

111 Applying Bayes' theorem to the posterior distributions, we obtain stochastic dynamics,
 112 i.e. stochastic update rules, for the neurons and the synapses (see Methods) as

$$P(x_{di} = 1 | \dots) = \sigma(v_{di} + b_{di}) \quad (1)$$

$$b_{di} \leftarrow (1 - r_b)b_{di} + r_b \sum_j w_{ij} (x_{dj} - \sigma(v_{dj})) \quad (2)$$

113 for a neuron and

$$P(s_{ijk} = 1 | \dots) = \sigma(a_{ijk} q_{ij}) \quad (3)$$

$$q_{ij} \leftarrow (1 - r_q)q_{ij} + r_q \sum_d x_{di} (x_{dj} - \sigma(v_{dj})) \quad (4)$$

114 for a synapse, where the dots represent all variables other than the target variable, x_{di} is
 115 the state of the i th neuron when the d th datum is given to the network, $v_{di} = \sum_j x_{dj} w_{ji}$ is
 116 the membrane potential of the neuron, s_{ijk} is the state of the k th synapse of the
 117 connection from i th neuron to the j th neuron, r_b and r_q are constants which
 118 characterize timescales of evolution of b_{di} and q_{ij} , respectively. $\sigma(x)$ is the sigmoidal
 119 function. Following these equations, the state of each neuron and each synapse is
 120 repeatedly updated. This simple repetition of irregular and asynchronous stochastic
 121 updates is the learning algorithm of the neural network.

122

123 Unlike backpropagation learning, in which the alternating execution of forward and
 124 backward computations is required, our algorithm realizes learning through the simple
 125 iteration of a single computation for each variable. Furthermore, the equations are local in
 126 the sense that they depend only on neurons and synapses directly connected to the

127 updated variable, i.e. the Markov blanket of the variable. In addition, the variables do not
128 require any global signals, such as the error of the current output of the network. This
129 asynchronicity and local nature of the dynamics of the learning must be particularly
130 suited to biological implementation of the algorithm.

131

132 Note the difference between the summation indices in Eqs. (2) and (4). Synaptic update
133 requires summation over the all data of a given dataset, while neural update does not. This
134 difference is a result of the difference between the data dependencies of the variables
135 (Figure 1b and 1c, see Methods for full details). Because of this difference, synapses need
136 to accumulate the neural activities for many, ideally all, data in the dataset before update
137 their states, while neurons reset their states independently in a manner that depends on
138 each datum individually. This implies that if data are provided sequentially to the network,
139 as in the brain, synapses must evolve much more slowly than neurons (Figure 1d). This
140 explains greatly different timescales of neurons and synapses in the brain. In the
141 following numerical simulations, however, we perform neural updates for all data of the
142 dataset in parallel to accelerates the computational speed.

143

144 **Synaptic plasticity**

145 The derived update rule for synapses given in Eqs. (3) and (4) yields plasticity similar to
146 that exhibited by cortical synapses [29]. Each term in the summation in Eq. (3) vanishes
147 unless the presynaptic neuron x_{di} fires, and if the neuron does fire, whether it will be
148 positive (LTP) or negative (LTD) depends on whether or not the postsynaptic neuron x_{dj}
149 fires simultaneously. For this reason, each synaptic weight increases if the network
150 receives many data in which the pre-synaptic and post-synaptic neurons of the connection
151 fire synchronously, while it decreases if the pre-synaptic and post-synaptic neurons fire
152 asynchronously (Fig. 1e).

153

154 Interestingly, the update rule depends on membrane potential, v_{dj} , in addition to the
155 spikes, x_{dj} , of the postsynaptic neuron. This is consistent with a recently proposed model
156 of STDP that accounts for various properties of synaptic plasticity by introducing the
157 average membrane potential of postsynaptic neurons into the model [30]. It is also
158 noteworthy that, unlike most existing models of synaptic plasticity, the plasticity derived
159 here does not require any artificial bound on synaptic weights. The incremental variation

160 of each synaptic weight automatically decays to zero when the magnitude of the weight
161 becomes very large (Fig. 1e), because $x_{dj} - \sigma(v_{dj})$ decays to zero in such cases.

162

163 **Retrograde modulation of excitability**

164 The term, b_{di} , of the neural dynamics given in Eq. (2) represents the retrograde
165 modulation of the firing probability of a neuron by its postsynaptic neurons. This term
166 provides a stochastic variant of the error propagation in backpropagation learning. Recall
167 that a target output is given to the network by fixing the states of the corresponding visible
168 neurons to the desired output. Assume that the j th neuron is one of these neurons. Then
169 x_{dj} gives the desired value, and the term $x_{dj} - \sigma(v_{dj})$ in the bias b_{di} of the i th neuron
170 gives the difference between the desired value and the expected value of x_{dj} when the
171 j th neuron is not fixed, which is identical to the error in backpropagation learning when
172 the squared error is used as the loss function. Owing to the retrograde modulation,
173 information regarding the desired output provided only to output neurons can spread, i.e.
174 diffuse, over the entire network, even though the variables of the neurons are updated
175 independently, without coordinated scheduling of error backpropagation.

176

177 As we will show later, unlike backpropagation learning, the retrograde modulation need
178 not be immediately affected by spikes of the postsynaptic neurons but, rather, can slowly
179 integrate the effects of the spikes. This means that the retrograde bias is determined by the
180 average spike history of the postsynaptic neurons over a finite, presumably quite long,
181 duration. Such slow modulation of the excitability of the neurons could be due to slow
182 changes in the axon initial segment or a long-term modulation of the spike threshold. This
183 seems biologically plausible, as it can be implemented in real cortical circuits. To our
184 knowledge, experiments to verify the existence of such slow retrograde modulation of the
185 excitability of neurons have not yet been attempted.

186

187 **Feedforward networks**

188 To understand how the algorithm works, we study its application to a simple problem of
189 supervised learning for a three-layered network (see Methods for full details). Figure 2a
190 displays the evolution of the training and test accuracies as functions of the number of the
191 sampling iteration. It is seen that these accuracies nearly coincide, and they quickly
192 increase to values close to unity and remain there. Significantly, even while these

193 accuracies remain nearly constant, the synaptic weights of the network continue to
194 fluctuate greatly (Fig. 2b), and the firing patterns of the hidden neurons also continue to
195 change, even when the same datum is given to the network, without converging to a fixed
196 pattern (Fig. 2c). These results are consistent with experimental observations of
197 continuing fluctuations of synapses and the trial-to-trial variability of cortical neural
198 activity.

199

200 In order to study the robustness of the algorithm with respect to constants of the algorithm,
201 we calculated the realized test accuracies of the network after learning for various
202 combinations of values of the number of synapses per connection, K , and the maximum
203 amplitude of synapses, a_0 , (Fig. 2d, see Methods). Except in a narrow range in which one
204 of these constants is so small that the possible maximum weight given by $a_0 K$ is small,
205 the network almost perfectly learns to perform the task.

206

207 Next, we consider the influence of the parameters r_b and r_q (Figure 2e, 2f). Unless r_q is
208 extremely small, and hence q evolves extremely slowly, the training and test accuracies
209 will increase and reach values near unity, while their convergence speed decreases as r_b
210 or r_q decreases. (Note that the synaptic evolution is slower than the neuronal evolution
211 even when $r_q = 1$, as discussed above. Therefore, a small value of r_q may result in
212 unrealistically slow synaptic dynamics.) We can thus conclude that the learning is not
213 practically hindered by the use of slow timescales of b .

214

215 We next study the application of the algorithm to training multilayered feedforward
216 networks using the MNIST dataset to demonstrate the applicability of the method to
217 practical problems (Fig. 3). We found that the accuracies quickly increase to values near
218 95%, while the number of required iterations and the asymptotically realized accuracies
219 decrease slightly as we increase the number of layers in the network (Fig. 3a-c). Figure 3d
220 displays examples of numerals that the network fails to recognize. These are quite
221 ambiguous and difficult even for a human to identify with confidence.

222

223 Figure 3e illustrates examples of connection weights from the input to the hidden neurons
224 in a three-layered network after training. These correspond to the receptive fields of the
225 hidden neurons. We can see that Gabor-filter-like localized structures that resemble

receptive fields of neurons in the primary visual cortex [32] are often organized through the learning. The introduction of a sparse constraint on neural activity into the loss function of learning is known to provide Gabor-filter like receptive fields for an artificial neural network [33]. It is interesting that the network can acquire similar localized structures of receptive fields even without any explicit additional constraint on the learning algorithm.

The learning algorithm can avoid serious overfitting to the training data because it is not derived as a direct optimization of any objective functions. To see this point, we trained a three-layered feedforward network using small numbers of samples of the MNIST dataset, and compared the resulting training and test accuracies with those obtained from backpropagation learning using the stochastic gradient descent (SGD) and ADAM algorithms [41] (Fig. 3f). We found that for both the SGD and ADAM algorithms, as the size of the training dataset is increased, the training accuracy decreases (in the SGD case) or remain nearly constant (in the ADAM case), while the test accuracy increases monotonically, which implies overfitting to the training dataset. Contrastingly, with the proposed algorithm, as the size of the training dataset is increased, both the training accuracy and the test accuracy increase, maintaining a slight difference between them. This implies that the serious overfitting does not occur in the proposed learning algorithm.

Most efficient power-law coding

A recent experiment carried out by simultaneously recording the activity of a very large number of neurons revealed that the variance spectrum of the principal component of neural activities obeys a power law with an exponent -1.04 that is slightly less than -1 [7]. The authors of the paper [7] proved that if the exponent is greater than -1, the population code by the neurons could not be smooth, while if the exponent is less than -1, high dimensionality of the population code is not fully realized. Thus, the experimentally observed power-law coding with an exponent slightly less than -1 is the most efficient in the sense that in this case, the population response of the neurons lies on a manifold of the highest possible dimension while maintaining high generalizability.

To test whether a network trained by the proposed algorithm realizes the most efficient

coding, we numerically calculated the variance spectrum of the principle components of the mean activity of the neurons in the hidden layer of a network trained with the MNIST dataset. As shown in Fig. 4a, the variance spectrum exhibits clear power-law decay with an exponent of -1.06. This is very close to the experimental result, and is indeed slightly less than -1. We conclude that the learning algorithm leads the network to the most efficient coding.

We next study how the exponent of the power law develops during learning. Figure 4b shows that the exponent approaches a value close to -1 from below as the learning proceeds. This result implies that the network first learns a coarse representation of the dataset and then gradually acquires finer structures while maintaining generalizability of the representation of the data in coding space. This leads us to conclude that the robustness or generalizability of the population coding takes priority over the precision of the data representation in the learning. This priority must particularly be beneficial for animals that must survive in a ceaselessly changing environment.

Recurrent networks

We next applied the algorithm to train a network with recurrent connections (Fig. 5a) using the MNIST dataset. Figure 5b displays the evolution of the training and test accuracies as functions of the number of sampling iterations. The accuracies were obtained from the states of the output neurons of the network measured after recursive evolutions of the states of the hidden neurons. We see that, as in the case of the results for the feedforward networks, the accuracies nearly coincide and rapidly increase. This implies that the algorithm is even able to train a recurrent network and rarely overfits.

Statistics of network motifs

It has been reported that local cortical circuits are highly nonrandom, and that connectivity patterns consisting of multiple neurons, known as network motifs, exhibit a characteristic distribution in which highly clustered patterns are overrepresented [31]. To study whether a recurrent network trained by the proposed algorithm acquires a similar distribution of connectivity patterns, we determined connectivity of triplets of neurons in a trained recurrent network. The statistics for the ratio of the actual counts of triplet patterns to the chance level are plotted in Figure 5c. The same ratios for the experimental

292 results are also overlaid in the figure. While there are some exceptional cases in which the
 293 ratios obtained here are somewhat larger than those obtained experimentally, the two
 294 distributions of triplet patterns are surprisingly similar. As observed experimentally,
 295 highly-connected motifs, i.e., those numbered 10 through 16 in Fig. 5c, are
 296 overrepresented by a factor several times greater than chance level. These results support
 297 the validity of the derived algorithm as a model describing the formation of local cortical
 298 circuits.

299

300 **Connection weights and receptive field correlation**

301 A recent experiment of the primary visual cortex revealed that the connection weights
 302 between pairs of pyramidal neurons become stronger as the receptive fields become more
 303 similar [34]. To test whether the trained recurrent network accounts for this relationship,
 304 we measured the connection weights between pairs of neurons and the receptive field
 305 correlations between these neurons (fig. 6a). We found that the average connection
 306 weight between neurons is positively correlated with the correlation between the
 307 receptive fields of these neurons (Fig. 6b). Particularly, by restricting our analysis to only
 308 connection weights with positive values (i.e., $w_{ij} > 0$), we were able to reproduce a
 309 nonlinear relationship between the average connection weight and the receptive field
 310 correlation (Fig. 6c), which was similar with the experimental result [34].

311

312 **Temporal sequence learning**

313 We next consider the application of the algorithm to train recurrent networks with
 314 temporal sequences (Fig. 7). We prepared periodic temporal sequences in which the same
 315 temporal inputs may appear multiple times at different times, and trained networks to
 316 predict the next input of the current sequence. In this case, networks need to learn to store
 317 the history of inputs over some interval to generate the desired output. The training
 318 procedure was the same as that used in the case considered in Figs. 2-5, except that we
 319 identified the iteration of the updates of the variables of the network as the time
 320 development. In contrast to the algorithm known as “backpropagation through time”, this
 321 procedure does not require virtually unfolding the recurrent connections of the network
 322 along the time axis.

323

324 We prepared two sequences that require one-step and two-step memories, respectively.

325 For both tasks, the networks were successfully trained to output the desired sequences by
326 the learning algorithm. We find that after learning, the output produced by the network in
327 any given case depends not only on the current input but also on past inputs. This
328 indicates that, through the learning, the algorithm causes the network to store input
329 histories into the activity of the hidden neurons.

330

331 **Discussion**

332 In this study, we showed that Gibbs sampling from a joint posterior distribution of
333 neurons and synapses in a network conditioned on an external environment or given
334 dataset explains the stochastic natures of synaptic development and neural activities of
335 cortical circuits. This provides a practical and biologically plausible learning algorithm
336 that yields results consistent with various experimental findings for cortical circuits. The
337 derived stochastic dynamics of synapses are consistent with the plasticity of cortical
338 synapses, and those of neurons naturally describe highly irregular features and the
339 trial-to-trial variability of spike trains of cortical neurons.

340

341 The evolution equation for neurons has a term that results in the retrograde modulation of
342 the excitability of a neuron by its postsynaptic neurons. Due to this term, the algorithm
343 acts as a stochastic variant of algorithms with error backpropagation through which target
344 outputs provided to a part of network can spread over the entire network. However, in
345 contrast to the case of backpropagation learning, the retrograde modulation seen in our
346 model requires neither synchronous nor precisely coordinated operations, which are
347 major reason that backpropagation has not been regarded as the learning principle of the
348 brain. Retrograde modulation need not be immediately affected by postsynaptic action
349 potentials but, rather, can slowly integrate postsynaptic spikes. The mechanisms regarded
350 as likely to be responsible for this behavior include the combination of action potential
351 backpropagation from soma to dendritic spines [42] and retrograde transsynaptic
352 transport of certain chemicals [43], glia-mediated modulation [44], and disynaptic
353 connections from postsynaptic to presynaptic neurons. Experimental confirmation of this
354 modulation would be convincing evidence to support the validity of the proposed
355 framework as a learning and computational principle of the brain.

356

357 The reason why both neurons and synapses must be stochastic in the cortex can be

understood as follows. Suppose that the primary purpose of the cortex is to generate synaptic weights that are consistent with the external environment. Mathematically, this can be formulated by generating samples of synaptic weights from a Bayesian posterior distribution conditioned on the external environment, which is derived from the likelihood function of the synaptic states determined by the dataset. However, when the network has hidden neurons, the likelihood is given by a marginal distribution of the joint conditional distribution of hidden neurons and synapses in which neural and synaptic variables are strongly coupled. Thus, sampling of synaptic states inevitably also requires sampling of neural states. In this way, the stochastic behaviors of neurons and synapses are integrated in the cortical dynamics.

It has been pointed out that the temporal difference (TD) method of reinforcement learning provides a model of spike-timing-dependent Hebbian plasticity [38]. In TD learning, the value function of the current state is updated after the delivery of a reward such that the value function includes the TD error defined as the difference between the value of the delivered reward and its predicted value. Interestingly, each term in the evolution equations of the latent variables of the synapses and neurons, i.e. b_{di} and q_{ij} , can be regarded as a representation of the TD error of the delivered spikes instead of the rewards. Indeed, each term in Equations (2) and (4) takes the form of a scaled difference between the measured spike of a postsynaptic neuron, x_{dj} , and its expected value, $\sigma(v_{dj})$, before observation of the spike. In this analogy, therefore, each spike plays the role of a reward for the presynaptic neurons and synapses from these neurons. At the same time, each spike is also transmitted to postsynaptic neurons, thereby changing their firing probabilities in a manner that depends on the corresponding synaptic weights. Thus, each spike in the cortex plays two roles, rewarding backward units and selecting next states by triggering the next spikes. It will be a fascinating topic of future research to theoretically elucidate the relationship between our algorithm and TD learning.

The algorithm developed here is closely related to the Boltzmann machine [37], which is a stochastic recurrent neural network in which neurons are represented by stochastic binary variables and iteratively updated to realize a thermal equilibrium state of a globally defined energy function specified by a given temperature. In that algorithm, symmetric connection weights between neurons are trained with a gradient descent

method to make the equilibrium state approximate a target distribution in which the neural states of given a dataset have high probability. The algorithm developed in the work can be regarded as an extension of the Boltzmann machine in which the Bayesian posterior distribution is directly considered, instead of a thermal equilibrium of an energy function, and in which synapses in addition to neurons are modeled as stochastic variables to be sampled. This extension results in biologically realistic update rules of variables that are implemented concurrently for neurons and synapses with no need for explicit switching of different computations or fine scheduling of parameters, such as simulated annealing.

In the limit of a large number of training data, the posterior distribution of Bayesian inference converges to a delta function whose peak position coincides with the result of the maximum likelihood estimation (see Methods). Therefore, if a sufficiently large amount of external data is provided to the network, our learning algorithm almost surely generates synaptic and neural variables that most suitably reflect the external data. This situation contrasts with that for backpropagation learning, in which convergence to an optimal solution is not always guaranteed, even when a large amount of data is used.

Because it seems to operate in accordance with a basic principle of neural computation and learning, we believe that our model provides a theoretical foundation for various experimental findings regarding cortical dynamics and various methods of machine learning. Most of the recent experimental findings regarding neuroscience have not yet been fully utilized in the development of machine learning. This may be because backpropagation learning is not consistent with the functioning of the brain. These experimental results include results regarding short-term plasticity of synapses [45], Dale's principle, the long-tail distribution of synaptic weights [31], columnar structure, laminar organization, canonical circuits [46, 47], and innate structure formed through developmental stages [48]. Incorporating these features into our model with the goal of clarifying their functional roles is an important future project. Introducing precise continuous dynamics of membrane potentials and spike generation mechanisms into the model are also important topic to be investigated.

References

- 424 [1] Shadlen, M. N., & Newsome, W. T. (1994). Noise, neural codes and cortical
425 organization. *Current Opinion in Neurobiology*, 4(4), 569–579.
- 426 [2] Arieli, A., Sterkin, A., Grinvald, A., & Aertsen, A. (1996). Dynamics of ongoing
427 activity: Explanation of the large variability in evoked cortical responses. *Science*,
428 273(5283), 1868–1871.
- 429 [3] Kenet, T., Bibitchkov, D., Tsodyks, M., Grinvald, A., & Arieli, A. (2003).
430 Spontaneously emerging cortical representations of visual attributes. *Nature*, 425(6961),
431 954–956.
- 432 [4] Destexhe, A., Rudolph, M., & Paré, D. (2003). The high-conductance state of
433 neocortical neurons in vivo. *Nature Reviews Neuroscience*, 4(9), 739–751.
- 434 [5] Berkes, P., Orbán, G., Lengyel, M., & Fiser, J. (2011). Spontaneous cortical activity
435 reveals hallmarks of an optimal internal model of the environment. *Science*, 331(6013),
436 83–87.
- 437 [6] Pouget, A., Beck, J. M., Ma, W. J., & Latham, P. E. (2013). Probabilistic brains:
438 knowns and unknowns. *Nature Neuroscience*, 16(9), 1170–1178.
- 439 [7] Stringer, C., Pachitariu, M., Steinmetz, N., Carandini, M., & Harris, K. D. (2019).
440 High-dimensional geometry of population responses in visual cortex. *Nature*, 571(7765),
441 361–365.
- 442 [8] Llera-Montero, M., Sacramento, J., & Costa, R. P. (2019). Computational roles of
443 plastic probabilistic synapses. *Current Opinion in Neurobiology*, 54, 90–97.
- 444 [9] Stettler, D. D., Yamahachi, H., Li, W., Denk, W., & Gilbert, C. D. (2006). Axons and
445 Synaptic Boutons Are Highly Dynamic in Adult Visual Cortex. *Neuron*, 49(6), 877–887.
- 446 [10] Yasumatsu, N., Matsuzaki, M., Miyazaki, T., Noguchi, J., & Kasai, H. (2008).
447 Principles of long-term dynamics of dendritic spines. *The Journal of Neuroscience*,
448 28(50), 13592–13608.
- 449 [11] Holtmaat, A., & Svoboda, K. (2009). Experience-dependent structural synaptic
450 plasticity in the mammalian brain. *Nature Reviews Neuroscience*, 10(9), 647–658.
- 451 [12] Chen, X., Leischner, U., Rochefort, N. L., Nelken, I., & Konnerth, A. (2011).
452 Functional mapping of single spines in cortical neurons in vivo. *Nature*, 475(7357),
453 501–505.
- 454 [13] Attardo, A., Fitzgerald, J. E., & Schnitzer, M. J. (2015). Impermanence of dendritic
455 spines in live adult CA1 hippocampus. *Nature*, 523(7562), 592–596.
- 456 [14] Mongillo, G., Rumpel, S., & Loewenstein, Y. (2017). Intrinsic volatility of synaptic

- connections - a challenge to the synaptic trace theory of memory. *Current Opinion in Neurobiology*, 46, 7–13.
- [15] Pascoli, V., Hiver, A., Van Zessen, R., Loureiro, M., Achargui, R., Harada, M., et al. (2018). Stochastic synaptic plasticity underlying compulsion in a model of addiction. *Nature*, 564(7736), 366–371.
- [16] Allen, C., & Stevens, C. F. (1994). An evaluation of causes for unreliability of synaptic transmission. *Proceedings of the National Academy of Sciences*, 91(22), 10380-10383.
- [17] Katz, L. C., & Shatz, C. J. (1996). Synaptic Activity and the Construction of Cortical Circuits. *Science*, 274(5290), 1133–1138.
- [18] Branco, T., & Staras, K. (2009). The probability of neurotransmitter release: variability and feedback control at single synapses. *Nature Reviews Neuroscience*, 10(5), 373–383.
- [19] Deneve, S., Latham, P. E., & Pouget, A. (2001). Efficient computation and cue integration with noisy population codes. *Nature Neuroscience*, 4(8), 826–831.
- [20] Ma, W. J., Beck, J. M., Latham, P. E., & Pouget, A. (2006). Bayesian inference with probabilistic population codes. *Nature Neuroscience*, 9(11), 1432–1438.
- [21] Doya, K., Ishii, S., Pouget, A., & Rao, R. P. (Eds.). (2007). *Bayesian brain: Probabilistic approaches to neural coding*. MIT press.
- [22] Soltani, A., & Wang, X.-J. (2010). Synaptic computation underlying probabilistic inference. *Nature Neuroscience*, 13(1), 112–119.
- [23] Kappel, D., Habenschuss, S., Legenstein, R., & Maass, W. (2015). Network Plasticity as Bayesian Inference. *PLoS Computational Biology*, 11(11), e1004485.
- [24] Aitchison, L., & Latham, P. E. (2015). Synaptic sampling: A connection between PSP variability and uncertainty explains neurophysiological observations. *arXiv preprint arXiv:1505.04544*.
- [25] Orbán, G., Berkes, P., Fiser, J., & Lengyel, M. (2016). Neural Variability and Sampling-Based Probabilistic Representations in the Visual Cortex. *Neuron*, 92(2), 530–543.
- [26] Neftci, E. O., Pedroni, B. U., Joshi, S., Al-Shedivat, M., & Cauwenberghs, G. (2016). Stochastic Synapses Enable Efficient Brain-Inspired Learning Machines. *Frontiers in Neuroscience*, 10(99), 796.
- [27] Hiratani, N., & Fukai, T. (2018). Redundancy in synaptic connections enables

490 neurons to learn optimally. Proceedings of the National Academy of Sciences of the
 491 United States of America, 115(29), E6871–E6879.

492 [28] Baldassi, C., Gerace, F., Kappen, H. J., Lucibello, C., Saglietti, L., Tartaglione, E., &
 493 Zecchina, R. (2018). Role of Synaptic Stochasticity in Training Low-Precision Neural
 494 Networks. *Physical Review Letters*, 120(26), 268103.

495 [29] Bi, G. Q., & Poo, M. M. (1998). Synaptic modifications in cultured hippocampal
 496 neurons: dependence on spike timing, synaptic strength, and postsynaptic cell type. *The*
 497 *Journal of Neuroscience*, 18(24), 10464–10472.

498 [30] Clopath, C., Büsing, L., Vasilaki, E., & Gerstner, W. (2010). Connectivity reflects
 499 coding: a model of voltage-based STDP with homeostasis. *Nature Neuroscience*, 13(3),
 500 344–352.

501 [31] Song, S., Sjöström, P. J., Reigl, M., Nelson, S. B., & Chklovskii, D. B. (2005).
 502 Highly nonrandom features of synaptic connectivity in local cortical circuits. *PLoS*
 503 *Biology*, 3(3), e68.

504 [32] Jones, J. P., & Palmer, L. A. (1987). An evaluation of the two-dimensional Gabor
 505 filter model of simple receptive fields in cat striate cortex. *Journal of neurophysiology*,
 506 58(6), 1233-1258.

507 [33] Olshausen, B. A., & Field, D. J. (1996). Emergence of simple-cell receptive field
 508 properties by learning a sparse code for natural images. *Nature*, 381(6583), 607–609.

509 [34] Cossell, L., Iacaruso, M. F., Muir, D. R., Houlton, R., Sader, E. N., Ko, H., et al.
 510 (2015). Functional organization of excitatory synaptic strength in primary visual cortex.
 511 *Nature*, 518(7539), 399–403.

512 [35] Bengio, Y., Lee, D.-H., Bornschein, J., Mesnard, T., & Lin, Z. (2015). Towards
 513 Biologically Plausible Deep Learning. *arXiv.org*.

514 [36] Lillicrap, T. P., Cownden, D., Tweed, D. B., & Akerman, C. J. (2016). Random
 515 synaptic feedback weights support error backpropagation for deep learning. *Nature*
 516 *Communications*, 7, ncomms13276.

517 [37] Ackley, D., Hinton, G., and Sejnowski, T. (1985). A Learning Algorithm for
 518 Boltzmann Machines. *Cognitive Science*, 9(1):147-169.

519 [38] Rao, R. P. N., & Sejnowski, T. J. (2001). Spike-timing-dependent Hebbian plasticity
 520 as temporal difference learning. *Neural Computation*, 13(10), 2221–2237.

521 [39] Feldmeyer, D., Egger, V., Lübke, J., & Sakmann, B. (1999). Reliable synaptic
 522 connections between pairs of excitatory layer 4 neurones within a single “barrel” of

523 developing rat somatosensory cortex. *The Journal of Physiology*, 521(1), 169–190.

524 [40] Geman, S.; Geman, D. (1984). "Stochastic Relaxation, Gibbs Distributions, and the
525 Bayesian Restoration of Images". *IEEE Transactions on Pattern Analysis and Machine*
526 *Intelligence*. 6 (6): 721–741.

527 [41] Kingma, D. P., & Ba, J. (2014). Adam: A method for stochastic optimization. *arXiv*
528 *preprint arXiv:1412.6980*.

529 [42] Stuart, G., Spruston, N., Sakmann, B., & Häusser, M. (1997). Action potential
530 initiation and backpropagation in neurons of the mammalian CNS. *Trends in*
531 *Neurosciences*, 20(3), 125–131.

532 [43] Regehr, W. G., Carey, M. R., & Best, A. R. (2009). Activity-Dependent Regulation
533 of Synapses by Retrograde Messengers. *Neuron*, 63(2), 154–170.

534 [44] Fields, R. D., & Stevens-Graham, B. (2002). New insights into neuron-glia
535 communication. *Science*, 298(5593), 556–562.

536 [45] Markram, H. and Tsodyks, M. (1996). Redistribution of synaptic efficacy between
537 neocortical pyramidal neurons. *Nature*. 382(6594): 807–810.

538 [46] Silberberg, G., Grillner, S., LeBeau, F. E. N., Maex, R., & Markram, H. (2005).
539 Synaptic pathways in neural microcircuits. *Trends in Neurosciences*, 28(10), 541–551.

540 [47] Bastos, A. M., Usrey, W. M., Adams, R. A., Mangun, G. R., Fries, P., & Friston, K. J.
541 (2012). Canonical Microcircuits for Predictive Coding. *Neuron*, 76(4), 695–711.

542 [48] Ullman, S. (2019). Using neuroscience to develop artificial intelligence. *Science*,
543 363(6428), 692–693.

544

545 **Figure captions**

546 **Figure 1**

547 Learning as a Gibbs sampling of synapses and neurons. (a) A neural network is modeled
548 as a population of neurons connected to each other via multiple synapses. (b) A simple
549 neural network consists of three neurons and four synapses per connection. The input,
550 hidden, and output neurons are denoted by x_0 , x_1 and x_2 , respectively. (c) A graphical
551 model representation of the network shown in (b) in the case that a dataset consisting of D
552 data is presented to the network. Note that the synaptic variables are shared by all data in
553 the dataset while neural variables are not. The white and gray circles represent free and
554 fixed variables, respectively. (d) Schematic of stochastic evolution of neural and synaptic
555 variables. Synapses must evolve much more slowly than neurons to allow the network to

incorporate many, ideally all, data in the dataset. Note that values of the visible neurons, x_0 , x_1 , and x_5 in the figure, are fixed to each datum in the given dataset. (e) Evolution of a synaptic weight (right panel) when presynaptic and postsynaptic neurons fire (left panel) synchronously (cyan) and asynchronously (magenta).

Figure 2

Supervised learning of feed-forward networks using a simple artificial dataset. (a) Training (cyan) and test (magenta) accuracies of a three-layered network as functions of the number of sampling iterations (details given in Methods). (b) Evolution of randomly chosen synaptic weights of the network. Different colors are used for different presynaptic neurons. (c) Evolution of the states of randomly chosen hidden neurons when the same datum in the dataset is presented to the network. (d) Test accuracies realized by the learning algorithm with various values of the number of synapses per connection, K , and maximum amplitude of a synapse, a_0 . (e) Evolution of accuracies for $r_b = 1.0, 0.1, 0.01, 0.001$, from top to bottom. (f) The same as (i) but for $r_q = 1.0, 0.1, 0.01, 0.001$, from top to bottom.

Figure 3

Supervised learning of feed-forward networks using the MNIST dataset. (a-c) Training accuracies (cyan) and test accuracies (magenta) as functions of the number of sampling iterations for (a) three-, (b) four-, and (c) five-layered networks. Each number in a circle indicates the number of neurons in the corresponding layer. (d) Examples of training images (upper row) and test images (lower row) that the three-layered network fails to recognize. (e) Examples of receptive fields of hidden neurons in the three-layered network. (f) Realized accuracies of the three-layered network as functions of the size of the training dataset. The network was trained by the proposed algorithm (left panel), a backpropagation learning algorithm with a naïve stochastic gradient descent (middle panel), and with the ADAM algorithm (right panel).

Figure 4

Nearly optimal power-law decay of the variance spectrum for the principal component of the neural activity. (a) Variance spectrum of the principle components of the mean activity of the hidden neurons of the three-layered network after training (cyan). The

589 variances are arranged in descending order. The line (magenta) indicates the critical slope
590 corresponding to an exponent of -1. (b) Evolution of the power-law exponent of the
591 variance spectrum as a function of the number of sampling iterations.

592

Figure 5

594 Supervised learning of a recurrent network using the MNIST dataset. (a) A recurrent
595 neural network. Each number in a circle indicates the number of neurons in the
596 corresponding layer. (b) Evolution of the training accuracies (cyan) and test accuracies
597 (magenta) of the recurrent network. (c) Average ratios of the actual numbers of
598 three-neuron patterns in the trained recurrent network to those predicted by the null
599 hypothesis (gray bars), (details given in Methods). The error bars indicate the range of
600 $\pm 2\sigma$. The green circles are experimental results for real cortical circuit [31].

601

Figure 6

603 Correlation between connection weights between pairs of neurons and the similarity of
604 the receptive fields of these neurons. (a) Correlation coefficients, c_{ij} , of the receptive
605 fields between pairs of neurons and connection weights, w_{ij} , between these neurons are
606 measured for the recurrent network after training. (b) The connection weights between
607 pairs of neurons positively correlates with the receptive field correlations between these
608 neurons. (c) The average weight of these connections with positive weights, $w_{ij} > 0$, as
609 a function of the receptive field correlation. Underlying histogram shows the distribution
610 of the receptive field correlations for the pairs of neurons. These results correspond to
611 Figure 2g and 2i of [34].

612

Figure 7

614 Supervised learning of recurrent networks using temporal sequences. (a) Network
615 structure. (b) Input sequences (upper panels) and target output sequences (lower panels)
616 of the first dataset. The asterisks indicate examples of times at which the network must
617 output different patterns while the current input to the network is the same. (c) Activities
618 of hidden neurons (upper panels) and output neurons (lower panels) after 0, 80, and 400
619 sampling iterations. (d) Input sequences (upper panels) and target output sequences
620 (lower panels) of the second dataset. (e) The same as (c), but for the second dataset.

621

622 **Methods**

623 **Neural networks**

624 Introducing the redundancy and stochasticity of the neurons and synapses, we model a
625 neural network that consists of N neurons connected via K synapses per connection. The
626 connection weight from the i th to the j th neuron is given as a weighted sum of the
627 synaptic states as $w_{ij} = \sum_{k=1}^K s_{ijk} a_{ijk}$, where $s_{ijk} \in \{0,1\}$ is a binary random variable
628 describing the state of the k th synapse of the connection from the i th to the j th neuron.
629 The weights are generally asymmetric, and we set $w_{ii} = 0$ to avoid self-connections.
630 The strength, or amplitude, of a synapse, denoted by a_{ijk} , is a constant that represents the
631 contribution of the synapse to the weight, which can be interpreted as corresponding to
632 the amplitude of the miniature postsynaptic potential (PSP) of the synaptic contact. Note
633 that a_{ijk} is a constant, and it is fixed during learning. For simplicity, we used an evenly
634 spaced sequence from $-a_0$ to a_0 for the values of the amplitude throughout the work:
635 $a_{ijk} = a_k = (2(k-1)/K-1)a_0$ ($k = 1, 2, \dots, K$).

636
637 The i th neuron receives inputs from its presynaptic neurons and randomly generates a
638 spike with the probability $P(x_i = 1) = \sigma(v_i) = \sigma(\sum_j x_j w_{ij})$, where the state of the
639 neuron, $x_i \in \{0,1\}$, is a random binary variable representing the spike firing of the
640 neuron, and $\sigma(x)$ is the activation function of a neuron, for which we use the sigmoidal
641 function $\sigma(x) = (1 + e^{-x})^{-1}$ throughout the paper. The weighted sum of inputs to the
642 neuron v_i corresponds to the membrane potential of the neuron.

643
644 Neurons in the network are classified into three groups, input, output, and hidden. Input
645 and output neurons together are referred to as visible neurons. External data, including
646 the target outputs of supervised learning, are input into the network by fixing the states of
647 visible neurons to the values of the data. Each datum, therefore, must be a binary vector.
648 When we obtain the output of the network after and during learning, we fix only input
649 neurons, keeping output and hidden neurons free.

650
651 The states of the neurons, including the hidden and visible neurons, are updated in
652 response to each datum in the dataset as it is input, while the state of a synapse depends on
653 the dataset as a whole, because the aim of the learning is generally to obtain networks, i.e.,
654 sets of synaptic states, that consistently reflect all of the data in the dataset (Figure 1c).

For this reason, we write the state of the i th neuron at the time that the network is receiving the d th datum of the dataset as x_{di} , using the data index, while the state of the synapse, s_{ijk} , does not have a data index. Figure 1c presents a graphical model representation of the data dependency of the variables for the simplest case of a three-layered neural network.

Learning algorithm

The learning of the network is modeled as a Gibbs sampling of all free variables from their posterior joint distribution conditioned on the fixed variables,

$$P\left(\{x_{di}\}_{i \in H, d \in D}, \{s_{ijk}\}_{i, j \in N, k \in K} \mid \{x_{di}\}_{i \in V}\right). \text{ Here, } d \text{ is the data index of the given dataset,}$$

D , while V and H denote the sets of visible and hidden neurons, N represents the set of all neurons, and K denotes the set of synapses for each connection. (The number of variables of the network is thus $ND + WK$, where W is the number of connections in the network.) The Gibbs sampling allows us to replace sampling from a generally high-dimensional joint distribution with a repetition of samplings of each single variable from a posterior distribution conditioned on all other variables,

$$P\left(x_{di} \mid \{x_{dj}\}_{j \neq i}, \{s_{ijk}\}\right)$$

and

$$P\left(s_{ijk} \mid \{x_{di}\}, \{s_{lmn}\}_{lmn \neq ijk}\right),$$

for a neuron and a synapse respectively. In the Gibbs sampling, the order of the samplings need not be fixed, but can be random. Also, the sampling frequencies of different variables can be different. Therefore, in general, the state of each neuron or synapse will change at times that are determined independently for each, depending only on the conditions experienced individually by that neuron or synapse.

To derive an explicit description of the posterior distribution of a neuron, let us consider the log likelihood ratio for x_{di} . Using the Bayes rule, we obtain

$$\log \frac{P(x_{di} = 1 \mid \cdots)}{1 - P(x_{di} = 1 \mid \cdots)} = \log \frac{P(x_{di} = 1 \mid \cdots)}{P(x_{di} = 0 \mid \cdots)}$$

$$\begin{aligned}
 &= \log \frac{P(x_{di} = 1)}{P(x_{di} = 0)} \prod_j \frac{P(x_{dj} | x_{di} = 0, \dots)}{P(x_{dj} | x_{di} = 1, \dots)} \\
 &= \frac{\sigma(v_{di})}{1 - \sigma(v_{di})} \\
 &+ \sum_j \begin{cases} \log \sigma(v_{dj,-i} + w_{ij}) - \log \sigma(v_{dj,-i}), & x_{dj} = 1 \\ \log(1 - \sigma(v_{dj,-i} + w_{ij})) - \log(1 - \sigma(v_{dj,-i})), & x_{dj} = 0 \end{cases} \\
 &= v_{dj} + \sum_j \begin{cases} (1 - \sigma(v_{dj})) w_{ij}, & x_{dj} = 1 \\ -\sigma(v_{dj}) w_{ij}, & x_{dj} = 0 \end{cases} \\
 &= v_{dj} + \sum_j (x_{dj} - \sigma(v_{dj})) w_{ij},
 \end{aligned}$$

680 where the dots represent all variables other than x_{di} , i.e., $\{x_{dj}\}_{j \neq i}$ and $\{s_{ijk}\}$, and we
 681 have $v_{dj,-i} = \sum_{k \neq i} x_{dk} w_{kj}$. To obtain the 5th line, we have assumed that $v_{dj,-i} \gg w_{ij}$
 682 and linearized each term of the summation with respect to w_{ij} . Solving the above
 683 equation for $p(x_{di} = 1 | \dots)$, we obtain Eq. (1) in the main text with

$$b_{di} = \sum_j w_{ij} (x_{dj} - \sigma(v_{dj})) \quad (5)$$

684 as the posterior distribution (i.e. the stochastic update rule) of the neuron.

685

686 Similarly, the log likelihood ratio for the synapse s_{ijk} is

$$\begin{aligned}
 &\log \frac{P(s_{ijk} = 1 | \dots)}{1 - P(s_{ijk} = 1 | \dots)} = \log \frac{P(s_{ijk} = 1 | \dots)}{P(s_{ijk} = 0 | \dots)} \\
 &= \log \frac{P(s_{ijk} = 1)}{P(s_{ijk} = 0)} \prod_d \frac{P(x_{dj} | s_{ijk} = 0, \dots)}{P(x_{dj} | s_{ijk} = 1, \dots)} \\
 &= q_{0,ijk} \\
 &+ \sum_d \begin{cases} \log \sigma(v_{dj,-ik} + x_{di} a_{ijk}) - \log \sigma(v_{dj,-ik}), & x_{dj} = 1 \\ \log(1 - \sigma(v_{dj,-ik} + s_{di} a_{ijk})) - \log(1 - \sigma(v_{dj,-ik})), & x_{dj} = 0 \end{cases} \\
 &= q_{0,ijk} + \sum_d \begin{cases} (1 - \sigma(v_{dj})) x_{di} a_{ijk}, & x_{dj} = 1 \\ -\sigma(v_{dj}) x_{di} a_{ijk}, & x_{dj} = 0 \end{cases}
 \end{aligned}$$

$$= q_{0,ijk} + a_{ijk} \sum_j x_{di} (x_{dj} - \sigma(v_{dj})),$$

687 where the dots represent $\{x_{di}\}$ and $\{s_{lmn}\}_{lmn \neq ijk}$, and we have $v_{dj,-ik} = \sum_l x_l w_{lj} -$
688 $x_{di} s_{ijk} a_{ijk}$. To obtain the 5th line, we have assumed $v_{dj,-ik} \gg a_{ijk}$, and approximated
689 each term in the summation as a quantity linear in a_{ijk} . The constant $q_{0,ijk}$ represents
690 the log likelihood ratio of the prior distribution, $P(s_{ijk})$, which simply vanishes unless
691 the prior distribution is biased. We assumed $q_{0,ijk} = 0$ throughout the work. Solving the
692 above equation for $P(s_{ijk} = 1 | \dots)$ gives Eq. (3) in the main text and

$$q_{ij} = \sum_d x_{di} (x_{dj} - \sigma(v_{dj})), \quad (6)$$

693 which constitute the explicit description of the posterior distribution or the update rule of
694 the synapse.

695

696 Equations (5) implies that a spike of a neuron immediately changes b_{di} and excitability
697 of presynaptic neurons. However, such immediate retrograde modulation has not been
698 experimentally reported, and seems biologically implausible. Rather, it is biologically
699 more natural that b_{di} evolves slowly while accumulating the effects of postsynaptic
700 spikes as Eq. (3) in the main text, where r_b characterizes the timescale of the evolution.
701 (Here, r_b satisfies $0 < r_b \leq 1$, while in the case $r_b = 1$, Eq. (3) reproduces to Eq. (5).)
702 Thus, b_{di} is determined by the average spike history of the postsynaptic neurons over a
703 finite, presumably quite long, duration. Similarly, we can also generalize the evolution
704 equation for q_{ij} as Eq. (4) in the main text. As demonstrated in Figure 2e and 2f, these
705 generalizations rarely decrease the learning accuracy of the algorithm.

706

707 The following is a possible biological implementation of our algorithm. (i) Each neuron
708 in the network continuously evaluates its membrane potential, v , and bias, b , and
709 stochastically generates spikes with the probability given in Eq. (1). (ii) A generated spike
710 is immediately integrated into the membrane potentials of its postsynaptic neurons, while
711 it slowly modulates the excitability of its presynaptic neurons (Eq. (2)). (iii) The spike
712 firing also modulates the latent synaptic variable, q (Eq. (4)). (iv) The state of each
713 synapse is changed asynchronously and irregularly in accordance with Eq. (3) with a
714 frequency that is sufficiently slow that sensory neurons receive a large variety of external
715 inputs during the average interval of the updates.

716

717 Numerical simulations

718 All numerical simulations are written in Python, with the open-source matrix library
 719 CuPy. In details of the procedures to train a feedforward network are as follows. (i) We
 720 first prepare ND binary variables for the N neurons and WK synapses where D is the
 721 number of data in the training dataset, W is the number of connections in the network,
 722 and K is the number of synapses per connection. (ii) Then we fix the variables of the
 723 visible neurons to the values of the data in the training dataset, and initialize the values of
 724 the hidden neurons and synapses randomly to 0 or 1 with probability 1/2. (iii) To avoid
 725 perfectly synchronized updates, we randomly choose the ratio r_x for the hidden neurons
 726 and update their variables according to Eqs. (1) and (2). (iv) Similarly, we randomly
 727 choose the ratio r_s for the WK synapses to update in accordance with Eqs. (3) and (4).
 728 (iv) We repeat (iii) and (iv) as many times as desired. The procedure to obtain the
 729 prediction of the network is the same as that for the training procedure, except that we fix
 730 only the input neurons and update the hidden and output neurons in accordance with Eqs.
 731 (1) and (2), keeping the synaptic values fixed. In order to accelerate the computation, we
 732 can use the average activities of the neurons, $\sigma(v_{di})$, instead of their binary variables,
 733 x_{di} , and omit the biases, b_{di} , during the prediction procedure. The training and test
 734 accuracies are defined as the ratio of the number of inputs that enables the network to
 735 generate the correct outputs to the total numbers of inputs of the training and test datasets.

736

737 Dataset

738 Except in the cases described by Figs. 2 and 7, we used the MNIST dataset, which
 739 consists of a training dataset of 60,000 examples and a test dataset of 10,000 examples in
 740 which each image has 28×28 pixels. Because pixels in the MNIST data range from 0 to
 741 255, we replaced them with 0 or 1, depending on whether the value of the pixel is below
 742 or above $255/2$. We thus obtain 784-dimensional binary input vectors.

743

744 In the situation considered in Fig. 2, we trained a three-layered network consisting of 40
 745 input, 40 hidden, and 2 output neurons to learn a simple task that is a noisy and
 746 high-dimensional variant of the XOR problem. The datasets were artificially generated as
 747 follows. We first prepared two-dimensional binary vectors (X_{d1}, X_{d2}) , where d is the
 748 data index of the dataset. Then, to obtain 40-dimensional binary input vectors

($Y_{d1}, \dots, Y_{d40}$), we set $Y_{di} = X_{d1}$ for $i = 1, \dots, 20$ and $Y_{di} = X_{d2}$ for $i = 21, \dots, 40$, and then flipped their values randomly with a probability of 0.1 to obtain randomized input dataset. The desired outputs of the two-dimensional vectors are given by $Z_{di} = (0, 1)$ if $\text{XOR}(X_{d1}, X_{d2}) = 0$ and $(1, 0)$ if $\text{XOR}(X_{d1}, X_{d2}) = 1$. The training dataset and test dataset each contains of 400 examples.

754

In the situation considered in Fig. 7, we used datasets consisting of temporal sequences to train recurrent networks. Let us write the input data and desired outputs at time t as $X_{di}(t)$ and $Z_{di}(t)$. These are fed into the network by fixing the neurons in the input layer as $x_{0,di}(t) = X_{di}(t)$, $0 < i \leq N_0$, and those in the output layer as $x_{2,di}(t) = Z_{di}(t)$, $0 < i \leq N_2$, where N_0 and N_2 are numbers of neurons in the input and output layers, respectively. A dataset is prepared as follows. We first prepare an integer sequence $s(t)$, where $1 \leq s(t) \leq S$ and $1 \leq t \leq T$. We then set $X_i(t) = 1$ if $(s(t) - 1)N_0/S < i \leq s(t)N_0/S$ and $X_i(t) = 0$ otherwise. The target output is set as $Z_{di}(t) = X_i(t + 1)$ if $1 \leq t < T$ and $Z_{di}(T) = X_i(0)$ otherwise. To obtain randomized input vectors $X_{di}(t)$, we replicated $X_i(t)$ and randomly flipped them as $X_{di}(t) = X_i(t)$ with probability 0.9 and $X_{di}(t) = 1 - X_i(t)$ with probability 0.05. The integer sequence $s(t)$ given by 1, 2, 3, 4, 5, 4, 3, 2, 1, 2, 3, 4, 5, 4, 3, 2 with $N_0 = 250$, $S = 5$ and $T = 16$ was used as the first dataset and 1, 1, 2, 2, 3, 3, 2, 2, 1, 1, 2, 2, 3, 3, 2, 2, 1, 1, 2, 2, 3, 3, 2, 2 with $N_0 = 150$, $S = 3$ and $T = 24$ is used for the second dataset.

769

770 Parameters

We used $r_q = 1.0$, $r_s = 0.001$, $K = 200$, $a_0 = 0.1$, and $D = 100$ in the situation considered in Fig. 1e, and $r_b = r_q = r_x = 1.0$, $r_s = 0.001$, $m_0 = m_1 = 10$, $K = 50$, $a_0 = 0.5$, and $D = 400$ in the situation considered in Fig. 2. In the situation considered in the remaining figures, except Figs. 4, 5, 6 and 7, we used $r_b = 0.01$, $r_x = 0.9$, $r_q = 0.1$, $r_s = 0.001$, $m_0 = m_1 = 20$, $K = 100$, and $a_0 = 0.1$. In the case of Fig. 4, we use $K = 200$, and in the case of Figs. 5 and 6, we used $r_x = 0.5$, and in the case of Fig. 7, we used $r_b = 0.1$, $r_x = 1$, $r_q = 0.01$, $r_s = 0.01$ and $D = 4000$. The numbers of hidden neurons in the three-layered network that are not specified in the figures are 1000 for Figs. 3f and 4, 100 for Figs. 5 and 6, and 500 for Fig. 7. Connection probability was 1.0 and 0.5 for feed forward connections and recurrent connections, respectively.

781

782 **Data analysis**

783 **Spectrum variance of principle components**

784 After we trained the three-layered neural network considered in Fig. 3a using the MNIST
 785 dataset, we fixed the synapses and obtained the average activities of the hidden neurons
 786 $\{\sigma(v_{di})\}_{i \in H}$. Note that the quantities v_{di} for the hidden neurons were deterministic in
 787 this case because both the input neurons and the synaptic connections from them were
 788 fixed. The principle component analysis was applied to the average activities after they
 789 were standardized. Then we obtained the explained variance of each principle component,
 790 which is the eigenvalue of the covariance matrix of the standardized average activities,
 791 and ordered them in descending order. The exponent of the power law was estimated with
 792 a least-square linear fit of the variance spectrum in log-log space.

794 **Statistics of network motifs**

795 We trained a three-layered recurrent network with 100 hidden neurons. Then, we
 796 determined the number of connection patterns among the triplets of neurons over all
 797 possible combinations of 3 neurons chosen from 100, i.e. for $100 \cdot 99 \cdot 98/6 =$
 798 161,700 triples. Here, we only counted connections whose synaptic weights were
 799 greater than or equal to 0.27, in order to exclude small and negative connections. Null
 800 hypothesis of the counts is defined as the same way that provided in the paper [31].
 801 Namely, we determined the numbers of unidirectional and bidirectional connections in all
 802 pairs of neurons and calculated the predicted number of three-neuron patterns by
 803 assuming all constituent pairs of neurons in each triplet pattern are chosen independently,
 804 while maintaining the probabilities of the measured unidirectional and bidirectional
 805 connections. We performed 20 learning trials in order to obtain the mean and standard
 806 deviation, σ , of the ratio of the actual number of each triplet pattern to that obtained with
 807 the null hypothesis.

809 **Limit of large training data size**

810 Let us represent all free variables of a network consisting of neurons $\{x_{di}\}$ and synapses
 811 $\{s_{ijk}\}$ collectively by θ . We can reasonably assume that the prior distribution $P(\theta)$ is
 812 positive for all values of θ and that each training datum is independently generated from
 813 a data distribution $P_d(x)$. Then, the posterior distribution satisfies

$$\begin{aligned}
 P(\theta|\{x_d\}) &\propto \prod_d P(x_d|\theta)P(\theta) \\
 &= \exp\left(\sum_d \log P(x_d|\theta) + \log P(\theta)\right) \\
 &\cong \exp\left(N_d \int \log P(x|\theta) P_d(x)dx + \log P(\theta)\right),
 \end{aligned}$$

814 which generally converges to a delta function $\delta(\theta - \theta_0)$ in the limit of a large number of
815 training data, $N_d \rightarrow \infty$, where $\theta_0 = \operatorname{argmax}_{\theta} \int \log P(x|\theta) P_d(x)dx$. (If maximum is
816 realized of multiple values of θ simultaneously, the posterior distribution will converge
817 to the sum of the corresponding delta functions.)

a **b**