Technical Note: Quantifying music-dance synchrony with the application of a deep learning-based 2D pose estimator

Filip Potemski BSc,^{1,2,3,4} Andrea Sabo BSc,^{1,5} Kara K Patterson PT, PhD^{1,2,6}

¹KITE-Toronto Rehabilitation Institute, University Health Network, Toronto, Canada

²Department of Physical Therapy, University of Toronto, Toronto, Canada

³Department of Arts & Sciences, University of Toronto, Toronto, Canada

⁴Department of Applied Health Sciences, Brock University, St. Catharines, Canada

⁵Institute of Biomedical Engineering, University of Toronto, Toronto, Canada

⁶Rehabilitation Sciences Institute, University of Toronto, Toronto, Canada

Conflict of Interest Disclosure: None.

Correspondence Address:

Kara K Patterson, PT, PhD

Department of Physical Therapy

University of Toronto

160-500 University Avenue

Toronto, ON, Canada M5G 1V7

Email: kara.patterson@utoronto.ca

Running Title: Quantifying music-dance synchrony

Abstract

Dance interventions are more effective at improving gait and balance outcomes than other rehabilitation interventions. Repeated training may culminate in superior motor performance compared to other interventions without synchronization. This technical note will describe a novel method using a deep learning-based 2D pose estimator: OpenPose, alongside beat analysis of music to quantify movement-music synchrony during salsa dancing. This method has four components: i) camera setup and recording, ii) tempo/downbeat analysis and waveform cleanup, iii) OpenPose estimation and data extraction, and iv) synchronization analysis. Two trials were recorded: one in which the dancer danced synchronously to the music and one where they did not. The salsa dancer performed a solo basic salsa step continuously for 90 seconds to a salsa track while their movements and the music were recorded with a webcam. This data was then extracted from OpenPose and analyzed. The mean synchronization value for both feet was significantly lower in the synchronous condition than the asynchronous condition, indicating that this is an effective means to track and quantify a dancer's movement and synchrony while performing a basic salsa step.

Keywords: synchronization, dancing, OpenPose, human pose tracking algorithm, motion analysis

Introduction

Dance is a universal human activity that confers many benefits including aerobic fitness, better balance, emotional and social well-being, and stress reduction.^{1,2} Anyone can benefit from dance including trained dancers, recreational dancers, older adults, and people with neurological conditions including Parkinson's disease and stroke.³⁻¹⁰ As an adjunct to rehabilitation, dance interventions are more effective at improving gait and balance outcomes than other rehabilitation interventions.¹¹

The advantages of dance over conventional exercise interventions may be derived from the synchronized movement to the rhythmic cues embedded in music. The extensive connectivity between the auditory and motor systems forms the basis for entrainment between rhythmic auditory signals and motor responses such as tapping your foot along to the beat in music.¹²⁻¹⁸ These spontaneous synchronized movements may result from the processing of perceived rhythms by motor areas in the brain including the basal ganglia, supplementary motor area.^{16,19,20} Thus, during dance, the rhythmic cues embedded in music, combined with the goal of synchronizing movement to those cues, may drive motor output. Repeated training may culminate in superior motor performance (such as better balance control) compared to other interventions without synchronization. This proposed mechanism is supported by the fact that music enhances motor performance and reduces metabolic costs of exercise in healthy adults^{12,21-23} and rhythmic auditory cueing during rehabilitation sessions improves gait performance²⁴ and brain activation patterns²⁵ post-stroke.

To investigate this potential mechanism, it will be necessary to measure the movement of people while they are dancing and quantify how well they synchronize their movement to the music. The accuracy of this type of measurement depends heavily on the device used as well as

the location of that device on the body.^{20,26} Quantitative movement analysis often requires costly devices such as 3D capture systems, accelerometers, gyroscopes, or force plates^{27,28}. However, vision-based tracking systems are less expensive and less cumbersome alternatives.²⁹ With this in mind, our group used OpenPose,^{30,31} a deep learning-based 2D keypoint estimator, to track dancer movements and subsequently compare the timing of their footfall events to the timing of the beat of the music to quantify movement synchronization. OpenPose^{30,31} has been used for many different objectives including 3D pose estimation,³² 3D model generation,³³ and analyzing features of gait.³⁴ This open-source software automatically obtains joint coordinates of the individuals in the image or video, enabling the calculation of parameters of interest. In this technical note, we will describe our novel method using OpenPose^{30,31} alongside beat analysis of music to quantify movement-music synchrony during salsa dancing.

Methods

Our method quantifies how well a dancer's steps synchronize with the downbeat of the music to which they are dancing. We used 1 webcam (Logitech Meetup³⁵, 1920x1080 pixels, 30 fps) 1 desktop computer (Windows PC), and computer speakers in this process. A recreational salsa dancer (5 years experience) performed a solo basic salsa step continuously for 90 seconds to a salsa track while her movements and the salsa track (1411 Kbps) were recorded with the webcam. The method and analysis have four components: i) camera setup and video recording of salsa dancing, ii) tempo/downbeat analysis and waveform cleanup, iii) OpenPose estimation and data extraction, and iv) synchronization analysis. Figure 1 provides a visual summary of the data flow and interaction between these components.

84 *Figure 1:*

85

86 **Figure 1** – Workflow for salsa synchrony measure. Abbreviations: FL = Fruity loops; X = x coordinates, Y = y coordinates, C =
87 confidence values.

Camera Setup and Video Recording of Salsa Dancing:

The webcam was positioned to capture the dancer's whole body in a sagittal view and to avoided filming at an angle to reduce image distortion (dance video). This is important to avoid parallax error in lateral views.³⁶ We also reduced visual background clutter and ensured the participant was well lit to avoid further information inaccuracies during OpenPose analysis. We placed the speaker playing the salsa track next to the microphone of the webcam to ensure consistency between audio waveforms of the salsa track and the dance video. We recorded audio on the same device as the video. Our participant performed a basic salsa step (Figure 2), continuously for 90 seconds under two conditions. In the synchronous condition, she danced on in time with the music. In the asynchronous condition, she intentionally danced out of time with the music.

Figure 2:

Figure 2 – Salsa Step Pattern. The positioning (represented by shoe prints) and direction (represented by arrows) of steps for the basic salsa step. The music counts on which each step occurs are listed above.

Tempo/Downbeat Analysis and Waveform Cleanup:

Separate from the video recording of the salsa dancing, we analyzed the tempo of the salsa track with the free version of Fruity Loops (FL) Studio (Edition 20.6, Image Line Software, Ghent, Belgium) digital audio workstation (DAW) and its built-in tempo analysis. From this analysis, we

created a new audio track of audible beats matched to the salsa song (downbeat track). We used a tone for the audible beats with limited distortion to ensure a clean audio waveform for later analysis. We visually and aurally evaluated the downbeat track to ensure it aligned with the salsa track and exported the track as a .WAV file.

To clean up the audio waveforms recorded in the dance video as well as the song track for later analysis, we used FL Studio. We used the equalizer tool to cut all frequencies below 40Hz in both recordings to reduce background noise. We then used the multiband compressor tool to highlight high and low frequencies in the recordings to make the peaks and troughs of the waveforms more differentiable. We used a second equalizer tool to further boost relevant frequencies, followed by a limiter to prevent clipping the audio on the high end and distorting the waveform. Finally, we exported the mastered audio files as .WAV files for analysis.

OpenPose Estimation and Data Extraction:

A public release of OpenPose (Version 1.5.0) was run on a Windows machine and used to analyze the dance video. Each frame of the dance video was processed to output a .JSON file containing the X and Y coordinates and confidence values for each of the 25 estimated keypoints (Figure 2). These files were then zipped into a single folder. To avoid working with many small files, the data from the .JSON files were extracted to a .CSV file using a Python script and ordered as a function of frame number.

Footfall & Salsa Synchrony Analysis:

The .CSV file created in Python was imported to MATLAB (Version 9.7, Mathworks, Natick, MA, USA) where the keypoints defined by OpenPose, and corresponding to the big toe of the left and right feet (keypoints 19 and 22 respectively³⁷) were used to create a new table. All frames with confidence values under 20% were dropped and data was interpolated using

MATLAB's *interp1*³⁸ function, then NaN values were interpolated using the *inpaint_NaN*s function³⁹ with a plate equation and an interpolating operator of delta cubed. Data was then filtered with a lowpass filter (2nd order Butterworth with a cut-off frequency at 4 Hz) using the zero-phase filtering operation: *filtfilt*⁴⁰ and normalized to -1,1 coordinates. The time of each frame was derived from the frame number over the recording device's frames per second rate.

The audio waveforms from the dance video, salsa track, and downbeat track were also imported into MATLAB and lowpass filtered (2nd order Butterworth with a cut-off frequency of 0.707 Hz). Then, using MATLAB's *alignsignals*⁴¹ function, the salsa track waveform was synced up to the video waveform. Based on the time difference between the two waveforms, the downbeat track waveform was aligned to match up to the video waveform. Utilizing MATLAB's *findpeaks*⁴² function, each peak of the downbeat track waveform was marked to represent the music's downbeats.

Since the participant was recorded in a sagittal view most of the movement or interest was captured by the x-values. The peaks or troughs of the keypoint of interest's X-value position were used to indicate foot strikes. Using MATLAB's *findpeaks*⁴² function again, these peaks were found. We then overlaid the downbeat points onto the foot position data for a visual representation of movement synchrony as seen in Figure 3. Time, foot strike, and beats were combined into a single table and exported as an .XLS file for further analysis. Synchronization of the participant's steps to the music was quantified by calculating the difference in time (seconds) between the occurrence of beats 1 and 5 of the music to the occurrence of the nearest right backward and left forward footfall events respectively (as described in Figure 2). These values were averaged for each foot over each of the two conditions (synchronous and asynchronous).

152 *Figure 3*

153

154 **Figure 3a/b** – Plot of Estimated Synchronized & Asynchronous Left Foot Strikes against Downbeat 5. Black circles indicate
 155 downbeats, red stars indicate foot strikes, and blue lines indicate keypoint position.

Data Analysis:

The mean synchronization values for the right and left feet were each compared between the synchronous and asynchronous conditions using a two-sample t-test assuming unequal variances using Microsoft Excel.⁴³ Statistical significance was set to 0.05.

Results

For the synchronous condition, 23.3% and 15% of the frames for keypoint 22 and 19 respectively were removed due to low OpenPose confidence values and interpolated. For the asynchronous condition, 15.3% and 12.7% of the frames for keypoint 22 and 19 respectively were removed and interpolated.

Figure 3 illustrates the detected foot strikes and downbeats for the left and right feet in the synchronous and asynchronous conditions. The mean (standard deviation) synchronization value for the right foot was significantly lower in the synchronous condition (0.25(0.12) sec) than the asynchronous condition (0.86 (0.56) sec) ($t(28) = -5.6418$, $p < 0.001$). Similarly, the mean synchronization value for the left foot was significantly lower in the synchronous condition (0.13 (0.08) sec) than the asynchronous condition (0.91 (0.57) ($t(27) = -7.0508$, $p < 0.001$).

Discussion

Using the OpenPose library alongside Python, MATLAB, and some basic audio production knowledge, we have developed a cost-efficient method for quantifying movement synchrony with music during salsa dancing. We were able to track and quantify a dancer's movements while performing a basic salsa step. We then compared this information to the downbeats of the salsa song to which the dancer performed the movement to determine how close the timing of the salsa steps was to the downbeat of the song. Being able to quantify movement synchrony while dancing

is useful for future work that will explore the relationship between the physical and psychosocial benefits of dance and the capacity for movement synchronization to music.

Potential problems that occur with our methods include background noise and low OpenPose keypoint confidence values. Due to this fact, our method uses audio waveforms to sync up the audio and video information, however, background noise can interfere with waveform analysis. We attempted to address this by positioning the speaker playing the salsa track as close as possible to the webcam recording the dance video. Another concern is that confidence values for some keypoints can be very low depending on angles and the type of movement recorded. For example, these low confidence values can indicate a dropped frame or OpenPose confusing body parts. We attempted to address this by removing visual clutter in the frame, properly lighting the participant during trials, removing points with low confidence, and interpolating between the points with higher confidence.

OpenPose has already been used in gait analysis research.^{34,44,45} We believe that our work here adds to the research on using accessible and affordable deep-learning-based keypoint estimators in the analysis of complex movements such as dance.

Acknowledgements

This work was supported by a Collaboratives Health Research Project (CHRP) grant jointly funded by the National Science and Engineering Research Council and the Canadian Institutes of Health Research.

References

1. Garber CE, McKinney JS, Carleton RA. Is aerobic dance an effective alternative to walk-jog exercise training? *J Sports Med Phys Fitness*. 1992;32(2):136-141. Accessed May 28, 2019. <http://www.ncbi.nlm.nih.gov/pubmed/1434581>
2. Quiroga Murcia C, Kreutz G, Clift S, Bongard S. Shall we dance? An exploration of the perceived benefits of dancing on well-being. *Arts Health*. 2010;2(2):149-163. doi:10.1080/17533010903488582
3. Crotts D, Thompson B, Nahom M, Ryan S, Newton RA. Balance Abilities of Professional Dancers on Select Balance Tests. *J Orthop Sport Phys Ther*. 1996;23(1):12-17. doi:10.2519/jospt.1996.23.1.12
4. Gerbino PG, Griffin ED, Zurakowski D. Comparison of standing balance between female collegiate dancers and soccer players. *Gait Posture*. 2007;26(4):501-507. doi:10.1016/j.gaitpost.2006.11.205
5. Verghese J. Cognitive and mobility profile of older social dancers. *J Am Geriatr Soc*. 2006;54(8):1241-1244. doi:10.1111/j.1532-5415.2006.00808.x
6. Zhang J-G, Ishikawa-Takata K, Yamazaki H, Morita T, Ohta T. Postural stability and physical performance in social dancers. *Gait Posture*. 2008;27(4):697-701. doi:10.1016/j.gaitpost.2007.09.004
7. Beaudry L, Fortin S, Rochette A. Adapted dance used in subacute rehabilitation post-stroke: impacts perceived by patients, relatives and rehabilitation therapists. *Disabil Rehabil*. Published online 2019:1-10. doi:10.1080/09638288.2019.1581845
8. López-Ortiz C, Egan T, Gaebler-Spira DJ. Pilot study of a targeted dance class for physical rehabilitation in children with cerebral palsy. *SAGE open Med*. 2016;4:2050312116670926-2050312116670926. doi:10.1177/2050312116670926
9. McKay JL, Ting LH, Hackney ME. Balance, Body Motion, and Muscle Activity After High-Volume Short-Term Dance-Based Rehabilitation in Persons With Parkinson Disease: A Pilot Study. *J Neurol Phys Ther*. 2016;40(4):257-268. doi:10.1097/NPT.0000000000000150
10. Salgado R, de Paula Vasconcelos LA. The Use of Dance in the Rehabilitation of a Patient with Multiple Sclerosis. *Am J Danc Ther*. 2010;32(1):53-63. doi:10.1007/s10465-010-9087-x
11. Shanahan J, Morris ME, Bhriain ON, Saunders J, Clifford AM. Dance for People With Parkinson Disease: What Is the Evidence Telling Us? *Arch Phys Med Rehabil*. 2015;96(1):141-153. doi:10.1016/j.apmr.2014.08.017
12. Simpson SD, Karageorghis CI. The effects of synchronous music on 400-m sprint performance. *J Sports Sci*. 2006;24(10):1095-1102. doi:10.1080/02640410500432789
13. Chen JL, Penhune VB, Zatorre RJ. Moving on Time: Brain Network for Auditory-Motor Synchronization is Modulated by Rhythm Complexity and Musical Training. *J Cogn Neurosci*. 2008;20(2):226-239. doi:10.1162/jocn.2008.20018

- 236 14. Chen JL, Zatorre RJ, Penhune VB. Interactions between auditory and dorsal premotor
237 cortex during synchronization to musical rhythms. *Neuroimage*. 2006;32(4):1771-1781.
238 doi:10.1016/j.neuroimage.2006.04.207
- 239 15. Grahn JA, Brett M. Rhythm and Beat Perception in Motor Areas of the Brain. *J Cogn*
240 *Neurosci*. 2007;19(5):893-906. doi:10.1162/jocn.2007.19.5.893
- 241 16. Grahn JA, Rowe JB. Feeling the beat: premotor and striatal interactions in musicians and
242 nonmusicians during beat perception. *J Neurosci*. 2009;29(23):7540-7548.
243 doi:10.1523/JNEUROSCI.2018-08.2009
- 244 17. Thaut MH, Abiru M. Rhythmic Auditory Stimulation in Rehabilitation of Movement
245 Disorders: A Review Of Current Research. *Music Percept*. 2010;27(4):263-269.
246 doi:10.1525/mp.2010.27.4.263
- 247 18. Zatorre RJ, Chen JL, Penhune VB. When the brain plays music: auditory-motor interactions
248 in music perception and production. *Nat Rev Neurosci*. 2007;8(7):547-558.
249 doi:10.1038/nrn2152
- 250 19. O'Halloran J, Hamill J, McDermott WJ, Remelius JG, Van Emmerik REA. Locomotor-
251 respiratory coupling patterns and oxygen consumption during walking above and below
252 preferred stride frequency. *Eur J Appl Physiol*. 2011;112(3):929-940. doi:10.1007/s00421-
253 011-2040-y
- 254 20. Atallah L, Lo B, King R, Yang G-Z. Sensor Positioning for Activity Recognition Using
255 Wearable Accelerometers. *IEEE Trans Biomed Circuits Syst*. 2011;5(4):320-329.
256 doi:10.1109/tbcas.2011.2160540
- 257 21. Karageorghis CI, Drew KM, Terry PC. Effects of Pretest Stimulative and Sedative Music
258 on Grip Strength. *Percept Mot Skills*. 1996;83(3_suppl):1347-1352.
259 doi:10.2466/pms.1996.83.3f.1347
- 260 22. Rendi M, Szabo A, Szabó T. Performance Enhancement with Music in Rowing Sprint. *Sport*
261 *Psychol*. 2008;22(2):175-182. doi:10.1123/tsp.22.2.175
- 262 23. Bacon CJ, Myers TR, Karageorghis CI. Effect of music-movement synchrony on exercise
263 oxygen consumption. *J Sports Med Phys Fitness*. 2012;52(4):359-365.
- 264 24. Thaut MH, Leins AK, Rice RR, et al. Rhythmic Auditor y Stimulation Improves Gait More
265 Than NDT/Bobath Training in Near-Ambulatory Patients Early Poststroke: A Single-Blind,
266 Randomized Trial. *Neurorehabil Neural Repair*. 2007;21(5):455-459.
267 doi:10.1177/1545968307300523
- 268 25. Luft AR, McCombe-Waller S, Whittall J, et al. Repetitive bilateral arm training and motor
269 cortex activation in chronic stroke: a randomized controlled trial. *JAMA*.
270 2004;292(15):1853-1861. doi:10.1001/jama.292.15.1853
- 271 26. Cleland I, Kikhia B, Nugent C, et al. Optimal placement of accelerometers for the detection
272 of everyday activities. *Sensors (Basel)*. 2013;13(7):9183-9200. doi:10.3390/s130709183
- 273 27. Muro-de-la-Herran A, García-Zapirain B, Méndez-Zorrilla A. Gait analysis methods: An
274 overview of wearable and non-wearable systems, highlighting clinical applications. *Sensors*

- (Switzerland). 2014;14(2):3362-3394. doi:10.3390/s140203362
28. Yang CC, Hsu YL. A review of accelerometry-based wearable motion detectors for physical activity monitoring. *Sensors*. 2010;10(8):7772-7788. doi:10.3390/s100807772
29. Simon SR. Quantification of human motion: Gait analysis - Benefits and limitations to its application to clinical problems. *J Biomech*. 2004;37(12):1869-1880. doi:10.1016/j.jbiomech.2004.02.047
30. Cao Z, Hidalgo Martinez G, Simon T, Wei S-E, Sheikh YA. OpenPose: Realtime Multi-Person 2D Pose Estimation using Part Affinity Fields. *IEEE Trans Pattern Anal Mach Intell*. Published online July 17, 2019:1-1. doi:10.1109/tpami.2019.2929257
31. Hidalgo Martinez G, Simon T, Wei S-E, Sheikh YA, Cao Z, Joo H. OpenPose library. <https://github.com/CMU-Perceptual-Computing-Lab/openpose>
32. Panteleris P, Oikonomidis I, Argyros A. Using a Single RGB Frame for Real Time 3D Hand Pose Estimation in the Wild. In: *Proceedings - 2018 IEEE Winter Conference on Applications of Computer Vision, WACV 2018*. Vol 2018-January. Institute of Electrical and Electronics Engineers Inc.; 2018:436-445. doi:10.1109/WACV.2018.00054
33. Joo H, Simon T, Sheikh Y. Total Capture: A 3D Deformation Model for Tracking Faces, Hands, and Bodies. *CVPR*. Published online 2018.
34. Sato K, Nagashima Y, Mano T, Iwata A, Toda T. Quantifying normal and parkinsonian gait features from home movies: Practical application of a deep learning-based 2D pose estimator. *PLoS One*. 2019;14(11). doi:10.1371/journal.pone.0223549
35. Logitech. Logitech MeetUp Video Conference Camera. Published 2020. Accessed August 16, 2020. <https://www.logitech.com/en-ca/product/meetup-conferencecam?crd=1689>
36. Sih BL, Hubbard M, Williams KR. Correcting out-of-plane errors in two-dimensional imaging using nonimage-related information. *J Biomech*. 2001;34(2):257-260. doi:10.1016/s0021-9290(00)00185-8
37. Hidalgo G, Fujisaka Y. OpenPose Demo - Output. Github. Published 2019. Accessed September 23, 2020. <https://github.com/CMU-Perceptual-Computing-Lab/openpose/blob/master/doc/output.md>
38. MathWorks. 1-D data interpolation (table lookup) - MATLAB interp1. Published 2020. Accessed August 10, 2020. <https://www.mathworks.com/help/matlab/ref/interp1.html>
39. D'Errico J. inpaint_nans. MathWorks File Exchange. Published 2012. https://www.mathworks.com/matlabcentral/fileexchange/4551-inpaint_nans
40. MathWorks. Zero-phase digital filtering - MATLAB filtfilt. Published 2020. Accessed August 10, 2020. <https://www.mathworks.com/help/signal/ref/filtfilt.html>
41. MathWorks. Align two signals by delaying earliest signal - MATLAB alignsignals. Published 2020. Accessed August 10, 2020. <https://www.mathworks.com/help/signal/ref/alignsignals.html>
42. MathWorks. Find local maxima - MATLAB findpeaks. Published 2020. Accessed August

313 10, 2020. <https://www.mathworks.com/help/signal/ref/findpeaks.html>

314 43. Microsoft Corporation. Microsoft Excel. Published online 2018.
315 <http://office.microsoft.com/excel>

316 44. Ng KD, Mehdizadeh S, Iaboni A, Mansfield A, Flint A, Taati B. Measuring Gait Variables
317 Using Computer Vision to Assess Mobility and Fall Risk in Older Adults with Dementia.
318 *IEEE J Transl Eng Heal Med.* 2020;8. doi:10.1109/JTEHM.2020.2998326

319 45. Stenum J, Rossi C, Roemmich RT. Two-dimensional video-based analysis of human gait
320 using pose estimation. *bioRxiv.* Published online July 26, 2020:2020.07.24.218776.
321 doi:10.1101/2020.07.24.218776