1 The neural basis of intelligence in fine-grained cortical topographies

2 Ma Feilong¹, J. Swaroop Guntupalli², James V. Haxby^{1*}

3 ¹Center for Cognitive Neuroscience, Dartmouth, Hanover NH

4 ²Vicarious AI, Union City CA

5 *Address correspondence to JVH (james.v.haxby@dartmouth.edu)

Abstract

Intelligent thought is the product of efficient neural information processing, which is embedded in fine-grained, topographically-organized population responses and supported by fine-grained patterns of connectivity among cortical fields. Previous work on the neural basis of intelligence, however, has focused on coarse-grained features of brain anatomy and function, because cortical topographies are highly idiosyncratic at a finer scale, obscuring individual differences in fine-grained connectivity patterns. We used a computational algorithm, hyperalignment, to resolve these topographic idiosyncrasies, and found that predictions of general intelligence based on fine-grained (vertex-by-vertex) connectivity patterns were markedly stronger than predictions based on coarse-grained (region-by-region) patterns. Intelligence was best predicted by fine-grained connectivity in the default and frontoparietal cortical systems, both of which are associated with self-generated thought. Previous work overlooked fine-grained architecture because existing methods couldn't resolve idiosyncratic topographies, preventing investigation where the keys to the neural basis of intelligence are more likely to be found.

Introduction

Intelligent thought is the product of efficient neural information processing, but the neural architecture that makes some brains capable of quick wit and deep insight, while others struggle with simple problems, remains an open question. Previous work on the neural basis of intelligence has focused on coarse-grained features of brain anatomy and function, such as the size and shape of the brain and its parts (e.g., Cox et al., 2019; Luders et al., 2007; Schmitt et al., 2019) or the size and strength of connections between large cortical fields (e.g., Dubois et al., 2018; Finn et al., 2015; Kong et al., 2019; Shen et al., 2017). Neural information processing, however, is embedded in fine-grained, topographically-organized population responses (Haxby et al., 2014, 2001). Functional connectivity varies vertex-by-vertex (Guntupalli et al., 2018), and even neuron-by-neuron (Park et al., 2017), to support such information processing. Therefore, fine-grained functional connectivity depicts in detail how information is exchanged and processed between cortical regions, in contrast to coarse-grained region-by-region connectivity, which depicts the overall synchronization between regions. We investigated whether individual differences in general intelligence are a function of information embedded in fine-grained cortical architecture.

Fine-grained patterns of activity and connectivity can be studied with functional magnetic resonance imaging (fMRI), but the topographies of these patterns are idiosyncratic, impeding study of their role in the neural basis of individual differences in cognitive ability. We used hyperalignment (Feilong et al., 2018; Guntupalli et al., 2018, 2016; Haxby et al., 2020, 2011) to resolve the interindividual variation of fine-grained topographies of functional connectivity. Hyperalignment remixes the connectivity profiles of loci in a cortical field into a

high-dimensional common space to maximize the similarity across brains in fine-grained, vertex-by-vertex patterns. Individual variation in the residuals around common fine-grained patterns are more reliable than individual variations around common coarse-grained patterns, after resolving idiosyncratic topographies with hyperalignment (Feilong et al., 2018). We found that predictions of general intelligence based on fine-grained (vertex-by-vertex) patterns of connectivity were markedly stronger than predictions based on coarse-grained (region-by-region) patterns. Intelligence was best predicted by fine-grained connectivity in the default and frontoparietal cortical systems, both of which are associated with self-generated thought. These results demonstrate that the neural mechanisms of intelligence reside more in fine-grained interactions of cortical regions than in synchronization of oscillations in large cortical fields.

Results

We used data from 876 participants of the Human Connectome Project (HCP) (Van Essen et al., 2013). Each participant had about 47 minutes of task fMRI data, collected during the performance of seven tasks, one hour of resting-state fMRI data, and scores on 10 cognitive tests. We used connectivity hyperalignment (Guntupalli et al., 2018) to factor out idiosyncrasies in fine-grained topographies and model information encoded in local functional connectivity patterns that is shared across brains. We hyperaligned both the HCP task fMRI and resting fMRI datasets. Connectivity hyperalignment projects idiosyncratic cortical topographies for individual brains into a common model connectivity space in which the patterns of connectivity across vertices in a cortical field with connectivity targets elsewhere in the brain are maximally similar across brains. We measured general intelligence (Spearman,

1904) as a general factor based on 10 cognitive test scores included in the HCP database (Dubois et al., 2018).

For each of 360 cortical regions, from a parcellation tailored to the HCP dataset (Glasser et al., 2016), we computed fine-grained task fMRI and resting fMRI connectivity profiles for each individual (Figure 1). The connectivity profile for each cortical vertex differs from profiles for other vertices in the region with a granularity in the common model space that is equivalent to spatial variation across cortical loci within individual brains (Guntupalli et al., 2018). We factored out the effect of coarse-grained connectivity by subtracting the mean connectivities between pairs of regions (coarse-grained connectivity profiles; Figure 1, middle row) from the vertex-wise connectivities (full fine-grained connectivity profiles; Figure 1, top row), to examine the predictive power of fine-grained connectivity unconfounded with prediction based on coarse-grained connectivity. These residual fine-grained connectivity profiles were used throughout the analysis, and we refer to them as fine-grained connectivity profiles for short. Results based on these residual profiles were very similar to those based on full fine-grained connectivity profiles (Supplementary Figure S2). We calculated coarse-grained connectivity on the same hyperaligned data used for calculation of fine-grained connectivity (see Supplementary Figure S2).

Figure 1. Schematic illustration of coarse- and fine-grained functional connectivity.

Each brain region (e.g., area 150 shown here) comprises multiple cortical vertices (on average 165). Correlations between their time series and time series for all 59,412 vertices in the whole cortex form that region's full fine-grained connectivity matrix (top row). The fine-grained connectivity profiles for 360 brain regions each have approximately 10 million such correlations. The coarse-grained connectivity profile for the same region (middle row) comprises the average functional connectivity between all of the vertices in that region and all of the vertices in each of the 360 brain regions. Thus, the coarse-grained connectivity profiles for 360 brain regions each have 360 mean correlations. The residual fine-grained connectivity profile (bottom row) for each region is obtained by subtracting the mean correlation for a pair of regions (e.g., region 1 and region 150) from the full fine-grained

connectivity profile for that pair and is, thus, unconfounded with coarse-grained functional connectivities. We refer to these unconfounded profiles as fine-grained connectivity profiles for short.

We built prediction models based on regional connectivity profiles using cross-validated principal component regression with ridge regularization. We divided the data into k test participants from one family ($k = 1$ to 6) and the remaining $876 - k$ training set participants (Figure 2). Thus, each test participant's intelligence was predicted using regression weights derived from other participants' data. We assessed the performance of these models using a coefficient of determination (R^2), which denotes the percent of intelligence score variance accounted for (VAF) by the prediction models. We made separate prediction models for hyperaligned fine-scale task and resting connectivity, for coarse-grained task and resting connectivity, and for non-hyperaligned fine-scale task and resting connectivity.

Figure 2. Schematic illustration of analysis pipeline. We used a leave-one-family-out cross-validation scheme. For each data fold, we built a prediction model based on the

training subjects' data (yellow color) to predict general intelligence (g) from the connectivity profile of a cortical region, and applied the model to test subjects' connectivity profiles to predict their general intelligence scores (Steps 1 and 2). We aggregated predicted and actually measured g across all cross-validation folds to assess model performance with cross-validated R^2 (Step 3), and repeated this procedure for other cortical regions' connectivity profiles (Step 4). After the entire pipeline, we obtained an R^2 for each of the 360 cortical regions, which stands for the amount of variance in g that can be accounted for by the region's connectivity profile. We repeated the pipeline for different kinds of connectivity profiles (spatial granularity, dataset, and alignment method) and compared them systematically (Figures 3–5), and these repetitions only differ in the connectivity profiles fed into the pipeline.

Hyperaligned fine-grained versus coarse-grained connectivity profiles

Regional hyperaligned fine-grained task and resting connectivity profiles were highly predictive of general intelligence (Figures 3A and 4A) and accounted for twice as much variance in general intelligence as compared to coarse-grained connectivity profiles (Figures 3B, 3C, 4B, and 4C).

Prediction of intelligence based on task fMRI connectivity profiles

On average across all cortical regions, prediction models based on hyperaligned fine-grained task fMRI connectivity accounted for 27.3% of variance in general intelligence (min: 11.2%, max: 38.9%). In other words, the correlation between predicted and measured intelligence scores ranged from $r = 0.34$ in the least predictive brain region to $r = 0.62$ in the

most predictive brain region. By contrast, prediction models based on coarse-grained task fMRI connectivity (Figure 3B) accounted on average for only 14.9% of variance (min: 3.3%, max: 26.5%), which is only 54.2% (95% CI: [48.7%, 58.8%]) of VAF by hyperaligned fine-grained connectivity overall. VAF by hyperaligned fine-grained task connectivity was higher than VAF by coarse-grained connectivity in all 360 ROIs (Figure 3C). These results suggest that the information encoded in fine-grained interaction patterns between brain regions affords markedly stronger predictions of intelligence than information in coarse-grained patterns.

The 30 most predictive regions (Figure 3D and 3E; 33.8% to 38.9% VAF) were in bilateral inferior parietal cortex (15 regions), bilateral medial and superior prefrontal cortex (11 regions), bilateral medial parietal (2 regions), and bilateral posterior lateral temporal cortex (2 regions). The cortices in these regions were predominantly part of the default mode and frontoparietal systems (38.9% and 34.5% of cortical vertices, respectively) with small portions in the ventral and dorsal attention systems (11.3% and 10.6%, respectively; Figure 3D and 3E) (Yeo et al., 2011). Assignment to cortical systems in a different parcellation tailored to the Glass parcellation (Ji et al., 2019) similarly revealed the dominant role played by the default and frontoparietal systems (Supplementary Figure S11).

Prediction based on task fMRI functional connectivity

A Hyperaligned fine-grained FC

B Coarse-grained FC

C

D

E

Figure 3. Predicting general intelligence based on regional task fMRI connectivity profiles.

Prediction based on hyperaligned fine-grained (A) and coarse-grained (B) connectivity profiles, assessed by the variance in general intelligence accounted for. The scatter plot (C) shows that predictions based on hyperaligned fine-grained profiles accounted for more

variance in all 360 ROIs. Prediction models based on each region's fine-grained hyperaligned task functional connectivity profile accounted for 1.85 (95% CI: [1.70, 2.05]) times more variance in general intelligence on average than did models based on coarse-grained functional connectivity profiles. Each circle is a cortical region, and the color of each circle corresponds to the cortical system where it resides, using the same color scheme as in (E). Dashed lines denote average difference in R^2 (gray), or identical R^2 (black). (D) The thirty regions whose hyperaligned fine-grained connectivity best predicted general intelligence are colored as in panels A and B. The default mode network is outlined in red, and the frontoparietal network is outlined in orange (Yeo et al., 2011). (E) Proportion of vertices in these regions that are in seven cortical systems delineated with resting state fMRI functional connectivity (Yeo et al., 2011).

Prediction of intelligence based on resting fMRI connectivity profiles

Prediction of general intelligence based on resting fMRI connectivity showed a similar advantage for hyperaligned fine-grained profiles, relative to coarse-grained profiles (Figure 4), but performance was substantially lower than for task fMRI connectivity, consistent with previous reports (Greene et al., 2018; Jiang et al., 2020). Models based on hyperaligned fine-grained resting fMRI connectivity accounted on average for 19.8% of variance (Figure 4A; min: 4.7%, max: 31.2%), whereas models based on coarse-grained connectivity accounted on average for 8.1% of variance (Figure 4B; min: -1.2%, max: 17.4%), which is only 40.5% [CI: 34.2%, 45.8%] of VAF by hyperaligned fine-grained resting connectivity. Hyperaligned fine-grained resting fMRI connectivity, as compared to coarse-grained resting fMRI connectivity, accounted for more variance in all 360 ROIs (Figure 4C). The vertices of 30 regions whose

173 resting hyperaligned fine-grained connectivity was most predictive of general intelligence
 174 (25.3% to 31.2% VAF) had a distribution that was similar to that for hyperaligned task
 175 connectivity, sharing 68.3% of cortical vertices (compare Figures 3D and 4D), with vertices
 176 mostly in the default mode network (49.0%) and smaller parts in the frontoparietal (19.4%),
 177 dorsal attention (15.8%) and ventral attention (10.0%) systems (Figure 4E; see also
 178 Supplementary Figure S11).

Prediction based on resting fMRI functional connectivity

A Hyperaligned fine-grained FC

B Coarse-grained FC

C

D

E

Figure 4. Predicting general intelligence based on regional hyperaligned resting fMRI

connectivity profiles. Prediction based on fine-grained (A) and coarse-grained (B)

connectivity profiles. The scatter plot (C) shows that regional predictions based on

hyperaligned fine-grained profiles accounted for more variance in all 360 ROIs. Prediction

models based on each region's fine-grained hyperaligned resting functional connectivity profile accounted for 2.48 (95% CI: [2.18, 2.93]) times more variance in general intelligence on average than did models based on coarse-grained functional connectivity profiles. Each circle is a cortical region, and the color of each circle corresponds to the cortical system where it resides, using the same color scheme as in (E). Dashed lines denote average difference in R^2 (gray), or identical R^2 (black). (D) The thirty regions whose hyperaligned fine-grained connectivity best predicted general intelligence are colored as in panels A and B. The default mode network is outlined in red, and the frontoparietal network is outlined in orange (Yeo et al., 2011). (E) Proportion of vertices in these regions that are in seven cortical systems delineated with resting state fMRI functional connectivity (Yeo et al., 2011).

Consistent with previous reports (Greene et al., 2018; Jiang et al., 2020), task fMRI connectivity was significantly more predictive of general intelligence than was resting fMRI connectivity for both hyperaligned fine-grained data (difference = 7.6% VAF; 95% CI: 5.3% to 9.9%) and coarse-grained data (difference = 6.8% VAF; 95% CI: 5.0% to 8.6%). Task connectivity accounted for more variance than did resting connectivity in 358 of 360 ROIs for hyperaligned fine-grained data and in 343 of 360 ROIs for coarse-grained data (Supplementary Figure S1).

Hyperaligned versus MSM-aligned fine-grained connectivity profiles

To test the efficacy of hyperalignment for revealing predictive individual differences in fine-grained connectivity topographies, we trained another set of models based on fine-grained functional connectivity of data without hyperalignment. These data were aligned with

Multimodal Surface Matching (MSM) (Robinson et al., 2014). Models based on MSM-aligned fine-grained task connectivity and resting connectivity accounted for, on average across ROIs, 17.6% (min: 5.1%; max: 28.7%) and 11.1% (min: 0.8%; max: 22.5%), respectively, of variance in general intelligence, which was 64.3% (95% CI: [59.9%, 68.3%]) and 56.0% (95% CI: [49.7%, 61.7%]) of that accounted for by models using hyperaligned data (Figure 5). Predictions based on hyperaligned fine-grained task connectivity were better than predictions based on MSM-aligned fine-grained connectivity in all 360 regions (Figure 5C). Predictions based on hyperaligned fine-grained resting connectivity were better than predictions based on MSM-aligned fine-grained connectivity in 357 of 360 regions (Figure 5D). The difference in model performance was larger for brain regions with more functional topographic idiosyncrasy for both task and resting connectivity ($r = 0.435$ and 0.425 , respectively, $p < 10^{-14}$), with two- to three-fold increases in VAF in the most idiosyncratic regions. As for hyperaligned fine-scale connectivity and for coarse-scale connectivity, MSM-aligned fine-scale task connectivity was more predictive of intelligence than was MSM-aligned fine-scale resting connectivity (difference = 6.5% VAF; 95% CI: [5.0%, 8.0%]; Supplementary Figure S1C). Consistent with our previous findings (Feilong et al., 2018), these results show that hyperalignment factors out idiosyncrasies in functional topography to reveal how individuals differ in information encoded in fine-grained cortical functional architecture.

Prediction based on MSM-aligned fine-grained connectivity

A Task fMRI connectivity

B Resting fMRI connectivity

C

D

Figure 5. Predicting general intelligence based on MSM-aligned fine-grained

connectivity profiles. Prediction based on task fMRI (A) and resting fMRI (B) connectivity.

Scatterplots compare regional predictions based on MSM-aligned to predictions based on

hyperaligned task connectivity (**C**) and resting connectivity (**D**) data (comparison to results in Figures 3A and 4A).

Discussion

The results show that individual differences in fine-grained patterns of functional connectivity are a markedly better predictor of general intelligence than are coarse-grained patterns, indicating that differences in cortical architecture that underlie inter-individual variation in the efficiency of information processing are more evident at the same spatial scale as topographic patterns that encode information. Discovering the dominant role of fine-grained connectivity patterns in the neural basis of intelligence required a method that resolves individual differences in these idiosyncratic patterns, a method that was not available prior to hyperalignment (Feilong et al., 2018; Guntupalli et al., 2018, 2016; Haxby et al., 2020, 2011; Nastase et al., 2020).

Differences in intelligence are indexed by tests of the ability to understand and manipulate information embedded in the meanings of words, logical relations, and visual patterns. We predicted that differences in performance would be more related to the fine-grained topographic patterns that represent these kinds of information than to coarse-grained patterns that blur fine distinctions. The results confirm our hypothesis. Hyperaligned, fine-grained, vertex-by-vertex connectivity patterns accounted for 1.85 to 2.48 times more variance in general intelligence than did coarse-grained, region-to-region connectivity patterns.

To examine the predictive power of fine-grained connectivity unconfounded with coarse-grained connectivity, we built models using the residual fine-grained connectivity profiles. In separate analyses we built models on the full fine-grained patterns and found that

adding coarse-grained information contributed little to VAF (Supplementary Figure S2), underscoring the stronger role that fine-grained cortical architecture plays in the neural basis of intelligence than that played by coarse-grained architecture.

Functional connectivity shows fine-grained variation vertex-by-vertex within a cortical field (Guntupalli et al., 2018) and even neuron-by-neuron within an fMRI voxel (Park et al., 2017). Transmission of information between cortical fields, therefore, involves more than simple synchronization of global activity. Information is transformed, as evidenced by changes in the representational geometries that are embedded in the fine-grained structure of local topographies (Connolly et al., 2016; Guntupalli et al., 2017; Kriegeskorte et al., 2008). Our results indicate that investigating the efficiency of information processing should focus on fine-grained patterns of connectivity that support information processing.

Hyperalignment resolves functional topographic idiosyncrasies at both coarse and fine spatial scales (see Jiahui et al., 2020 for an example of aligning functional topographies), which is critical for assessing individual differences in information processing. Alternatively, individualized parcellations (e.g., Kong et al., 2019; Glasser et al., 2016) can be used to resolve coarse-scale topographic idiosyncrasies, which also improves prediction performance (Kong et al., 2021). However, the improvement for coarse-grained functional connectivity was smaller than for fine-grained functional connectivity in predicting general intelligence (Supplementary Figure S2).

Previous work could not reveal the role that information embedded in fine-scale topographies plays in the neural basis of intelligence because individual differences in information were concealed by idiosyncrasies in fine-scale topographies that could not be

aligned with prior methods. Hyperalignment resolves the shared information embedded in idiosyncratic topographies, making it possible to investigate these individual differences (Feilong et al., 2018). Fine-grained information in hyperaligned data accounted for 1.56 to 1.79 times more individual variation in intelligence than did fine-grained information in non-hyperaligned data.

Results also show that fMRI data collected during performance of cognitive tasks better predict intelligence than resting state fMRI data, consistent with previous reports (Greene et al., 2018; Jiang et al., 2020). Previous studies used whole-brain, coarse-grained connectivity for prediction. Here we show that the added predictive power of task fMRI data, relative to resting fMRI data, extends to both hyperaligned and MSM-aligned fine-grained connectivity patterns.

Our results show further that the neural basis of intelligence resides mostly in the fine-grained structure of connectivity in the default mode and frontoparietal networks (Buckner et al., 2008; Raichle et al., 2001; Yeo et al., 2011). Small parts of the most predictive regions were in the dorsal and ventral attention networks, and an even smaller proportion was in the visual system. The most predictive brain regions did not encroach on the systems for auditory, somatosensory, motor, or limbic function. The predominance of the default mode network was found for both task connectivity and resting connectivity, suggesting that the efficiency of these connections is evident in both. A strong role for the frontoparietal network was more evident in task connectivity, suggesting that efficiency of this system's connections is better revealed during performance of tasks that increase its activity.

The predominant role of the default and frontoparietal systems in our results suggests that intelligence rests on self-generated and stimulus-independent thinking (Andrews-Hanna et al., 2014; Buckner et al., 2008; Dixon et al., 2018; Raichle et al., 2001), or on the apperceptive mass that provides the foundation and context for perception and thought (Raichle, 2006), for finding correct solutions to problems and generating novel insights. The functions of the default system are mostly ill-defined because it does not respond to features of external stimuli in a consistent way (Andrews-Hanna et al., 2014; Buckner et al., 2008; Golland et al., 2007). Although default system activity during movie watching and in the resting state is idiosyncratic, it is highly correlated across default areas (Buckner et al., 2008; Golland et al., 2007) and has a fine-scale structure that can be modeled with hyperalignment (Feilong et al., 2018; Guntupalli et al., 2018), indicating that this activity has structure and meaning. It has been associated with thinking about others' mental states (Buckner et al., 2008; Frith and Frith, 1999; Gobbin et al., 2007; Saxe and Kanwisher, 2003), activation of person knowledge about familiar others (Gobbin and Haxby, 2007), autobiographical memory and envisioning the future (Addis et al., 2007), as well as other aspects of internally-driven cognition. The most predictive regions overlapped only a portion of the default network involving primarily the dorsal medial subsystem with smaller parts in the core subsystem (Andrews-Hanna et al., 2014, 2010). The dorsal medial subsystem has been associated with mentalizing, social cognition, story comprehension, and semantic conceptual processing (Andrews-Hanna et al., 2014).

The frontoparietal system may similarly reflect the role of self-directed thought in the neural basis of general intelligence. Dixon et al. (2018) have identified a subdivision of the

315 frontoparietal network that interacts primarily with the default mode system. They propose
 316 that this part of the frontoparietal system is involved in the regulation of introspective
 317 processes.

318 The efficiency of the default system apparently rests more on fine-grained features of
 319 its functional connectivity than on coarse-grained functional connectivity. The bases for the
 320 organization of its fine-grained topographies and the transformations of representational
 321 geometries between default regions are unknown, but the keys to understanding the neural
 322 basis of intelligent thought may reside in the information processing embedded in these
 323 topographies.

324 **Acknowledgements**

325 We would like to thank Guo Jiahui, Samuel Nastase, Jeremy Huckins, and Maria Ida Gobbini for
326 helpful comments, suggestions, and discussion. We would like to thank Yaroslav Halchenko
327 for support with software.

328 Data were provided by the Human Connectome Project, WU-Minn Consortium (Principal
329 Investigators: David Van Essen and Kamil Ugurbil; 1U54MH091657) funded by the 16 NIH
330 Institutes and Centers that support the NIH Blueprint for Neuroscience Research; and by the
331 McDonnell Center for Systems Neuroscience at Washington University.

332 This work was supported with funds from NSF grants 1607845 and 1835200.

333 **Author contributions**

334 Conceptualization, M.F., J.V.H.; Methodology, M.F., J.S.G., J.V.H.; Software, M.F., J.S.G.;
335 Formal analysis, M.F.; Resources, J.V.H.; Writing - original draft, M.F., J.V.H.; Writing - review
336 and editing, M.F., J.S.G., J.V.H.; Visualization, M.F., J.V.H.; Supervision and Funding
337 acquisition, J.V.H.

338 **Declarations of interests**

339 The authors declare no competing interests.

340 **Methods**

341 **Dataset**

342 We used data from the Human Connectome Project (HCP) (Van Essen et al., 2013) for
 343 our analysis. The final S1200 data release of the HCP Young Adult dataset contains multi-
 344 modal MR imaging and behavioral data from 1206 participants that are 22-35 years old. This
 345 includes about one hour of resting-state fMRI data (4 runs, 14.5 minutes each), 47 minutes of
 346 task fMRI data (7 tasks, 2 runs each), and extensive cognitive tests for each participant. Out of
 347 the 1206 participants, 888 have complete task and resting fMRI data, 1181 have complete
 348 scores of 10 cognitive tests, and 876 participants have both. In our analysis, we always used as
 349 many participants with complete data as possible to maximize statistical power. That is, we
 350 used data from the 1181 participants to derive the general intelligence score, data from the 888
 351 participants to derive hyperalignment models and compute topographic idiosyncrasy, and
 352 data from the overlapping 876 participants for prediction analysis.

353 We used a multi-modal cortical parcellation tailored to this dataset (Glasser et al., 2016)
 354 to delineate cortical regions and compute connectivity targets for hyperalignment as described
 355 below. This parcellation is usually labeled as "Q1-Q6_RelatedParcellation210" or "210P" in the
 356 HCP dataset, and sometimes referred to as HCP MMP 1.0.

357 **Measuring general intelligence**

358 General intelligence is a common factor, often referred to as g , underlying all cognitive
 359 abilities (Spearman, 1904). In this study, we measured general intelligence as the general
 360 factor obtained based on 10 cognitive test scores using a factor analysis with a bi-factor model

(Dubois et al., 2018). These cognitive tests (Barch et al., 2013) include those from the NIH Toolbox for Assessment of Neurological and Behavioral Function (<http://www.nihtoolbox.org>) and additional computerized tests (Bilker et al., 2012; Gur et al., 2010), covering a range of memory, attention, language, and reasoning abilities. General intelligence can be accurately and consistently identified through different test batteries (Johnson et al., 2008, 2004), and our findings are robust over choices of intelligence measures (Supplementary Figures S6 and S7). For this dataset, the general factor of intelligence was derived from the code of Dubois et al., (2018), and it accounts for 58% of the covariance structure of cognitive tasks (Dubois et al., 2018).

MRI acquisition

MRI data were acquired with a Siemens 3 T Skyra MRI scanner and a 32-channel head coil at Washington University (Van Essen et al., 2013). The scanner was customized with a gradient coil and gradient power. Each subject has 2 T1w and 2 T2w scans with 0.7 mm isotropic voxels, which were used to reconstruct high-resolution cortical surfaces.

Functional MRI data were acquired with a TR of 0.72 s, 2 mm isotropic voxels, and a multi-band acceleration factor of 8. Every volume comprised 72 slices with $208 \times 180 \text{ mm}^2$ FOV each. Half of the fMRI runs were scanned with the LR phase encoding direction, and the other half were with RL. Spin-echo field maps were collected along with the fMRI data that allow susceptibility distortion correction.

Resting fMRI data were acquired with 4 runs of 1200 TRs each. Each of the 7 tasks were acquired with 2 runs, and the duration of each run varied across tasks (min: 176 TRs, max: 405

TRs). In total, for each participant, 57.6 minutes of resting fMRI data and 46.6 minutes of task fMRI data were acquired. See (Uğurbil et al., 2013) for additional details of MRI acquisition.

MRI preprocessing

We used the same standard procedure to preprocess fMRI data for all task and resting fMRI data. Our preprocessing was based on the minimally preprocessed version of the dataset (Glasser et al., 2013), where data had been corrected for distortion and head motion, and aligned to a standard cortical surface mesh using Multimodal Surface Matching (MSM) (Robinson et al., 2014), which aims to match multimodal properties across individuals while preserving topology. These data were labeled as "MSMAll" in the HCP data files, and we refer to them as "MSM" for short.

We first normalized all fMRI data to percent signal change units, then used linear regression to remove nuisance components from them. These nuisance components include 6 motion parameters and their derivatives, 5 principal components from white matter and cerebrospinal fluid (Behzadi et al., 2007), global signal, and polynomial trends up to the 3rd order. The white matter and cerebrospinal fluid components were extracted from volumetric data based on eroded anatomical masks. Both the regressors and data were low-pass filtered with a Gaussian kernel (standard deviation = 1 TR) prior to regression. These preprocessing steps were analogous to previous work (Dubois et al., 2018; Finn et al., 2015; Greene et al., 2018; Shen et al., 2017).

Hyperalignment

We performed hyperalignment using these preprocessed data to align the fine-grained cortical functional architecture across individuals, and obtained two sets of hyperaligned data (one based on task fMRI data, one based on resting fMRI data) besides the original MSM-aligned dataset. Specifically, we used connectivity hyperalignment (Guntupalli et al., 2018) to align fine-grained cortical functional architecture across individuals. We used regional average time series of the 360-region multi-modal cortical parcellation (Glasser et al., 2016) as connectivity targets. For each of the 59,412 cortical vertices, we computed its connectivity profile as the correlations between its own time series and the 360 regional average time series. Therefore, each connectivity profile is a vector comprising 360 correlation coefficients. In each brain region, we derived a transformation matrix for each individual using these connectivity profiles, which remixes each individual's vertices into a common set of model dimensions through an improper rotation of a high-dimensional space. Each model dimension has similar functional properties across individuals instead of the same anatomical position, and these model dimensions together constitute a common model space. The common model space is usually instantiated as a reference brain, where each vertex corresponds to a model dimension. The information content in each individual's data — the configuration of connectivity vectors in the high-dimensional feature space — is perfectly preserved during the rotation, whereas how and where this information is encoded in idiosyncratic topographies is factored out into the transformation matrix.

In this study, hyperalignment was performed for each brain region separately (i.e., in a similar manner to Haxby et al., 2011 rather than Guntupalli et al., 2016), and the

transformation was constrained to be an improper rotation (i.e., rotation that allows reflection) with no scaling. This was to strictly ensure that the information content within a brain region was identical before and after hyperalignment, and only the cortical topography of the information was changed (i.e., better aligned). Searchlight hyperalignment (Guntupalli et al., 2016) allows information to be moved in and out of a brain region to some extent, which is preferable in general, because the same function doesn't always reside in the same anatomical region for all participants (Eickhoff et al., 2018). However, in this case it can make it difficult to interpret the results. For example, an improvement of prediction performance after searchlight hyperalignment can be caused by better alignment of information in a region, but it can also be caused by additional information moved into the region or noise moved out of the region.

We used the HCP task fMRI dataset to derive the hyperalignment common model and transformations (i.e., to train hyperalignment) when we analyzed the task fMRI data, and resting fMRI dataset when we analyzed the resting fMRI data. Therefore, the task and resting fMRI datasets remain independent throughout the analysis. It is possible to train hyperalignment using one dataset and apply it to another, and such results are summarized in Supplementary Figure S2.

Functional connectivity profiles

We used functional connectivity profiles to depict a brain region's functional interactions with the entire cerebral cortex. These connectivity profiles are different from the connectivity profiles used in connectivity hyperalignment as described above.

For each of 360 cortical regions, we computed a fine-grained connectivity matrix for each participant (Figure 1, top row), which comprises pairwise interactions between all vertices in the region (165 vertices on average) and all vertices of the cerebral cortex (59,412 vertices). We vectorized this connectivity matrix to form a long vector comprising millions of connectivity strengths (9.8 million on average across all regions), which we refer to as the participant's full fine-grained connectivity profile of the region. This fine-grained connectivity profile depicts in detail the region's information exchange with the rest of the cortex, and it contains information encoded in fine-grained connectivity patterns up to the same resolution as the input fMRI data (2 mm for this dataset).

To separate information encoded in different spatial scales, we split the full fine-grained connectivity profile into a coarse-grained connectivity profile and a residual fine-grained connectivity profile. The coarse-grained connectivity profile for a given region is a vector comprising 360 elements, where each element is the average connectivity strength between all cortical vertices in this region and all vertices in another region (Figure 1, middle row). Similar to previous work (Dubois et al., 2018; Finn et al., 2015; Shen et al., 2017), coarse-grained connectivity profiles depict the information exchange between a pair of regions with a single connectivity strength. A residual fine-grained connectivity profile comprises pattern residuals obtained by subtracting the mean connectivity with each region (an element of the coarse-grained connectivity profile) from each element of the vertex-by-vertex connectivity pattern with the region (part of the full fine-grained connectivity profile). Because a coarse-grained connectivity profile is comprised of region-by-region averages of the corresponding fine-grained connectivity profile, a regression model using coarse-grained connectivity profile

(expanded to the same size as the fine-grained connectivity profile) as the independent variable and fine-grained connectivity profile as the dependent variable will always have a slope of 1. Therefore, the difference between the two profiles is also the residual of the regression model. Similar to a full fine-grained connectivity profile, a residual fine-grained connectivity profile comprises millions of elements, and the only difference is that these elements are connectivity residuals instead of connectivities. In other words, a residual fine-grained connectivity profile contains only fine-scale information, instead of combined fine- and coarse-scale information.

The analysis involves data aligned in 3 different ways: MSM, hyperalignment based on task fMRI data, and hyperalignment based on resting fMRI data. For each alignment method, we computed these 3 kinds of connectivity profiles for each participant and each region. The results of fine-grained connectivity profiles reported in the main text are based on residual fine-grained connectivity profiles, and similar results were obtained using full fine-grained connectivity profiles (Supplementary Figure S2).

Topographic idiosyncrasy

We measured the level of each region's functional topographic idiosyncrasy as the average dissimilarity of hyperalignment transformation matrices across participant pairs for that region, after correcting for region size. Specifically, for each brain region, we computed the Frobenius norm of the difference between the two transformation matrices for each pair of participants, and averaged it across all participant pairs to obtain an average matrix dissimilarity (i.e., average difference matrix norm) for the region. The 360 cortical regions differ in size (measured as the number of vertices in each region). As a result, transformation

matrices also differ in size for different regions, and the average matrix norm was predominantly determined by region size. Across all 360 regions, the average matrix norm and the square root of region size had a correlation of $r > 0.9999$. To remove the confounding effects of region size, we fit a linear regression model across the 360 regions using $\sqrt{\text{region size}}$ as the independent variable and the average matrix dissimilarity as the dependent variable. We used the residual of the linear regression model to depict the heterogeneity of a region's functional topography across individuals.

We performed hyperalignment twice in our analysis — once using task fMRI data, once using resting fMRI data — and therefore obtained two sets of transformation matrices for each region. Topographic idiosyncrasy indices based on each of the two sets are essentially identical ($r = 0.960$, $p = 4 \times 10^{-200}$). When we analyzed task fMRI data, we used topographic idiosyncrasy based on task fMRI (Figure 5C), and when we analyzed resting fMRI data, we used that based on resting fMRI (Figure 5D).

Cross-validation scheme

We used leave-one-family-out cross-validation (Dubois et al., 2018) to assess prediction models. The 876 participants were from 411 families, and each family had 2.13 members on average (range: 1–5; with 103 participants with no other family members and 177, 107, 22, and 2 families with 2 to 5 participants, respectively). Therefore, this cross-validation scheme divided the entire dataset into 411 folds. Each time we leave out a family of k individuals (i.e., related to each other) as test data, and use the remaining $876 - k$ individuals (i.e., not related to test participants) as training data to train the model. We repeated this procedure, each time using a different family as test data. Therefore, after looping through all families, each

individual's general intelligence score was predicted by a model trained with unrelated individuals.

For each cross-validation fold (i.e., each family as test data), we further split the training data into three sub-folds and used nested cross-validation to choose the optimal model parameters. In other words, model parameters were always chosen based only on training data.

To test the robustness of our prediction models against particular ways of splitting data, we replicated our analysis using an alternative cross-validation scheme. Instead of the leave-one-family-out cross-validation, we repeated 10-fold cross-validation 50 times, and each time the data was split randomly into 10 chunks in a different way. To accommodate the family structure of the dataset, we ensured that each time individuals from the same family were always in the same chunk. The average model performance across the 50 repetitions was highly similar to that based on leave-one-family-out cross-validation across all regions and connectivity profile types (Supplementary Figure S8), suggesting our prediction model performance evaluation was accurate and unbiased.

Regression models

We used principal component regression with ridge regularization to predict general intelligence based on functional connectivity. First, we used principal component analysis (PCA) to derive principal components (PCs) from functional connectivity patterns based on training data. Dimensions in the PC space capture principal ways that individuals' connectivity profiles differ. Thus, the connectivity profile for a region in each training set participant was transformed into a set of scores across PC dimensions. Then, we trained a ridge regression

model to predict general intelligence based on these PC scores. The PCA and ridge regression models were then applied to test data to obtain the model predicted general intelligence scores. Model parameters (the number of PCs and the regularization parameter) were always chosen using nested cross-validation as stated above. Candidate model parameters were distributed evenly on a logarithmic scale. Choices for the number of PCs were 10, 20, 40, 80, 160, 320, and all PCs (i.e., no dimensionality reduction). The maximum number of PCs was usually 360 for coarse-grained connectivity profile and 876-k for fine-grained connectivity profile. Choices for the regularization parameter α were 81 values from 10^{-20} to 10^{20} .

Model evaluation

We evaluated our models using the cross-validated coefficient of determination (R^2). R^2 denotes the percent of variance in general intelligence that was accounted for (VAF) by prediction models. The formula is

$$R^2 = 1 - \frac{\sum_i (y_i - \hat{y}_i)^2}{\sum_i (y_i - \bar{y}_{i,train})^2}$$

where y_i is the measured score for subject i , $\hat{y}_i$ is the model predicted score for subject i , and $\bar{y}_{i,train}$ is the prediction by the null model. The prediction of the null model is simply the average score of all training data, and thus it doesn't use any information from the features (fine- or coarse-grained functional connectivity in this case) at all. R^2 maximizes at 100%, which means perfect prediction; 0 means model performance is only the same as the null model. In rare cases, cross-validated R^2 can also be negative, which suggests the model performance is even worse than the null model.

To assess model performance against chance, we used permutation testing to create a null distribution of R^2 . The HCP dataset has subjects that are from the same family, and they are more likely to have similar general intelligence scores compared with non-related subjects (Plomin and Deary, 2015). Therefore, the subject labels are not fully exchangeable, and we used multi-level block permutation (Winkler et al., 2015) to resolve the issue. With this hierarchical permutation approach, the data exchangeability is properly modeled, providing more accurate estimates of false positive rates.

For each of the 2160 conditions (360 brain regions $\times$ 3 connectivity profile types $\times$ 2 fMRI data types), we ran a permutation test by training and evaluating prediction models 100 times based on shuffled subject labels. Each time, we permuted general intelligence scores across the entire dataset in the beginning, and re-ran the entire prediction pipeline with these permuted scores. That is, for each cross-validation fold, we chose the optimized parameters using a nested cross-validation based on the training participants and their permuted scores, and used these parameters to train a new model based on the entire training set, which was used to predict the scores of the left-out family. After looping through all cross-validation folds (i.e., all families), we assessed model performance based on the permuted scores. In other words, we repeated the entire process — including parameter optimization, prediction, and model evaluation — using permuted general intelligence score as the target variable instead of the original general intelligence score.

Across conditions (Supplementary Figure S4) the maximum R^2 of all 100 permutations was less than the value obtained with the prediction model (i.e., $p < 0.01$) for all models based

on hyperaligned fine-grained connectivity or on MSM-aligned fine-grained task connectivity and for all models based on coarse-scale connectivity or on MSM-aligned fine-grained resting connectivity that had a R^2 over 1.3%.

Estimating confidence intervals

We used bootstrap tests to estimate confidence intervals (CIs) for contrasts between VAF by different prediction models. In each of 1,000,000 repetitions, we randomly sampled a group of 876 individuals used for model evaluation by sampling with replacement from the 876 original individuals. In other words, in each bootstrapped sample, a participant might be selected once, multiple times, or not selected at all. For each bootstrapped sample, we computed VAF differences and VAF ratios. The 95% CI of a difference or ratio is estimated as the 2.5th and 97.5th percentiles of the difference or ratio from the bootstrapped samples (i.e., the sampling distribution of the difference or ratio estimated by bootstrapping participants). The bootstrapping procedure used here only affects the participants used for model evaluation (i.e., the test set), and the model used to predict a participant's score was always trained with the same training set (i.e., participants who are not from the same family as the test participant). This was because prediction performance depends on training sample size (Supplementary Figure S8), and duplicate instances in the training data don't have the same effect on machine learning algorithms as "real" new data (e.g., noise from two duplicate instances are not independent), which makes the bootstrapped sample no longer representative of the population. Therefore, we only bootstrapped the participants used for model evaluation, so that the sampling distribution is not biased by training sample size or dependency.

594 **Pearson correlation**

595 We used the Pearson correlation coefficient to assess the relationship between regional
596 topographic idiosyncrasy and the difference in prediction performance based on hyperaligned
597 and MSM-aligned data (Figure 5, panels C and D), and the relationship between the square
598 root of a region's size and the average transformation matrix dissimilarity. In both cases, n (the
599 number of regions) is always 360, and the degrees of freedom is always 358.

600 **Dice coefficient**

601 We used the Dice similarity coefficient (Dice, 1945) to quantify the amount of overlap
602 between the 30 most predictive regions based on task fMRI data and those based on resting
603 fMRI data. The formula is

$$= \frac{2|A \cap B|}{|A| + |B|}$$

604 where A is the set of vertices covered by the 30 most predictive regions based on task fMRI
605 data, and B is that based on resting fMRI data. $|A|$ denotes set cardinality. DSC is short for Dice
606 similarity coefficient.

607 **Overlap with cortical systems**

608 The cerebral cortex can be divided into 7 cortical systems based on functional
609 connectivity (Yeo et al., 2011). For each of the 360 regions, we computed the percentage of
610 vertices belonging to each of the 7 systems as the number of vertices belonging to the system
611 divided by the total number of vertices in the region. For the 30 most predictive regions, we
612 computed the percentage of vertices across all 30 regions that belonged to each system
613 (Figures 3E and 4E). Similar results were found with an alternative division into 12 cortical

systems by Ji et al. (2019) (see Supplementary Figure S11). In the scatter plots (Figures 3C and 4C), each region was assigned to one of the cortical systems, which is the system that had the largest amount of vertices in the region.

Software used

We implemented our analysis using Python and Python packages including NumPy (<https://numpy.org/>), SciPy (<https://www.scipy.org/>), and NiBabel (<https://nipy.org/nibabel/>). The code for performing hyperalignment and nuisance regression was adapted from PyMVPA (<http://www.pymvpa.org/>) (Hanke et al., 2009).

622

Supplemental material

623

Comparison of predictions based on task fMRI and resting fMRI data

624

625

626

627

628

629

630

631

632

Supplementary Figure S1. Scatterplots comparing VAF by regional prediction models using task fMRI and resting fMRI connectivity. A. Hyperaligned, fine-grained connectivity. B. Coarse-grained connectivity. C. MSM-aligned fine-grained connectivity. Each circle represents one region. The color of each circle corresponds to the cortical system that each region is part of (based on a plurality of vertices), using the same color scheme as in Figures 3D and 4D.

633

634

635

Results showed that task fMRI data produced better predictions of general intelligence than did resting fMRI for hyperaligned residual fine-grained, coarse-grained, and MSM-aligned residual fine-grained connectivity.

636 Comparison of alignments and predictions based on single task connectivity

A Prediction based on residual fine-grained functional connectivity

B Prediction based on coarse-grained functional connectivity

C Prediction based on full fine-grained functional connectivity

637

638 Supplementary Figure S2. Histograms of VAF by predictions of general intelligence using different
639 fMRI connectivity datasets and different alignment methods. A. Prediction based on residual fine-
640 grained connectivity. B. Predictions based on coarse-grained connectivity. C. Predictions based on
641 full fine-grained connectivity, which includes information in both fine-grained and coarse-grained
642 patterns. CHA is short for connectivity hyperalignment.

643 Connectivity hyperalignment based on task fMRI data produced stronger predictions of general
644 intelligence based on task connectivity than did connectivity hyperalignment based on resting fMRI
645 data. Predictions based on resting connectivity were equivalent for connectivity hyperalignment based
646 on task fMRI and resting fMRI. Prediction based on hyperaligned residual fine-grained connectivity and
647 on hyperaligned full fine-grained connectivity profiles (A and C) were essentially identical.

648 Hyperalignment transformations remix the time series for cortical vertices, which alters the mean of
 649 correlations between the vertices of two regions - namely, the coarse-scale functional connectivity
 650 between these regions (B). Analyses of hyperaligned fine-grained connectivity profiles all used the
 651 coarse-grained connectivity profiles calculated on the same hyperaligned data for comparison. In
 652 practice the effect of calculating coarse-grained connectivity profiles on task hyperaligned task fMRI,
 653 hyperaligned resting fMRI, and MSM-aligned fMRI is small and does not affect the results of these
 654 analyses (Supplementary Figure S2).

Predicting intelligence based on connectivity during single tasks

Supplementary Figure S3. Histograms of VAF by regional prediction models based on connectivity calculated from fMRI during single tasks. For every single fMRI task (4.2 to 9.7 min) fine-scale hyperaligned connectivity data produced better predictions of general intelligence than did coarse-scale connectivity. The strongest predictions from single task fMRI were obtained from data during performance of the working memory (WM), language, and social cognition tasks.

Null distribution of model performance based on permutation testing

A Permutation results based on task fMRI data

B Permutation results based on resting fMRI data

Supplementary Figure S4. Permutation testing. For each of the 2160 conditions (360 brain regions $\times$ 3 connectivity profile types $\times$ 2 fMRI data types), we ran a permutation test by training and evaluating prediction models 100 times based on shuffled subject labels. For 2148 out of 2160 conditions (99.4%), the actual R^2 was larger than all 100 permuted R^2 's. For the remaining 12 conditions, the actual R^2 was close to 0 (all $< 1.3\%$). In other words, for any model that had a R^2 of at least 1.3%, it's also larger than the maximum R^2 of all 100 permutations (i.e., $p < 0.01$).

Distribution of model parameter choices based on nested cross-validation

A Parameters of models trained on task fMRI data

B Parameters of models trained on resting fMRI data

Supplementary Figure S5. Distribution of regularization parameters α and number of PCs for prediction models. For each kind of fMRI data (Panel A: task fMRI; Panel B: resting fMRI) and each kind of connectivity profile (hyperaligned fine-grained, MSM-aligned fine-grained, coarse-grained), we summarize the distribution of model parameters (the regularization parameter, α , and the number of PCs) across all cross-validation folds (411 families $\times$ 360 regions = 147,960). The maximum number of PCs was usually 360 for coarse-grained connectivity profile and close to 876 for fine-grained connectivity profile (depending on training sample size). Models trained on fine-grained connectivity profiles (left and middle columns) tend to use less regularization (smaller alphas) and more PCs compared with models trained on coarse-grained connectivity profiles (right column), especially models trained on hyperaligned fine-grained connectivity profiles. More PCs used by the model suggests that there are more dimensions in the connectivity profiles that are

684 related to general intelligence, and less regularization suggests these PCs contain more signal
685 relative to noise.
686

Predicting alternative measures of intelligence

Supplementary Figure S6. Predicting alternative measures of intelligence based on connectivity profiles. Our prediction models and connectivity profiles can also be trained to predict other measures of intelligence, such as fluid intelligence measured with the Penn Matrices (Panel A, variable "PMAT24_A_CR" in the dataset) and general intelligence measured as the Cognitive Function Composite score of the NIH Toolbox (Panel B, "CogTotalComp_Unadj"). Similar to the results of the main paper (shown here as Panel C for comparisons), predictions based on fine-grained hyperaligned connectivity profiles account for approximately 2 times more variance in intelligence compared with coarse-grained connectivity profiles for task fMRI data, and 3 times more for resting fMRI data. The 4 columns on the left side are based on connectivity profiles computed from task fMRI data, and the 4 on the right from resting fMRI data. For each kind of data, we computed fine-grained connectivity profiles based on 3 different alignment methods (MSM, hyperalignment based on resting fMRI data, and hyperalignment based on task fMRI data),

701 which we colored as blue, orange, and red respectively. The orange and red colors denote the kind
702 of data used to derive hyperalignment transformations. In the results shown in this figure, they
703 may not be the same as data used to compute connectivity profiles.
704

Fluid intelligence as Penn Matrices score

General intelligence as NIH Toolbox Cognitive Function Composite score

Supplementary Figure S7. Predicting alternative intelligence measures based on regional hyperaligned fine-grained task fMRI connectivity profiles. Regional connectivity profiles that were more predictive of factor analysis-based general intelligence scores were more likely to be more predictive of matrix reasoning-based fluid intelligence scores (top row, $r = 0.92$) and NIH Toolbox-based general intelligence scores (bottom row, $r = 0.96$). This suggests our results were robust over intelligence measure choices.

712 Alternative cross-validation schemes and the effect of training sample size

Task fMRI functional connectivity

Resting fMRI functional connectivity

Supplementary Figure S8. Comparison between cross-validation schemes. We replicated our analysis using the 10-fold cross-validation scheme (repeated for 50 times), and compared model performance based on 10-fold cross-validation (average across 50 repetitions) with that based on leave-one-family-out cross-validation (Panels A and C). Each dot denotes a brain region, and error bars denote the standard deviation of R^2 across the 50 repetitions. All dots were close to the identity line (gray dotted line), which indicates that model performance was highly similar for leave-one-family-out cross-validation and 10-fold cross-validation. On average across all regions, model performance based on leave-one-family-out cross-validation was slightly higher than that based on 10-fold cross-validation, which was likely driven by the difference in training sample size (i.e., approximately 90% versus 99.8% of the entire dataset). This was confirmed by additional analysis showing further reduction of model performance based on smaller k values and correspondingly smaller training sample sizes (Panels B and D; $k = 2, 3$, or 5 for k -fold cross-validation; training data was 50%, 66.7%, and 80% of the entire dataset respectively).

Task fMRI functional connectivity

Resting fMRI functional connectivity

Supplementary Figure S9. Overestimation of model performance due to lack of data independence. We trained new prediction models based on the k-fold cross-validation scheme, but without controlling for family structure. That is, for each testing participant, other members from the same family might be in training data. Compared with the k-fold results that controlled for family structure (Supplementary Figure S8; dashed lines in this Figure), results without controlling for family structure consistently overestimate model performance (average R^2 difference across regions: 0.9% to 2.1%; solid lines in this Figure). This demonstrates the necessity of ensuring data independence between training and testing data to avoid biased model evaluations (see Varoquaux et al., 2017 for a similar issue with leave-one-trial-out). Specifically, training and testing data should not have members from the same family.

738 The effect of hyperparameter choices on model performance

Task fMRI functional connectivity

Resting fMRI functional connectivity

Supplementary Figure S10. The effect of hyperparameter choices on prediction performance. Besides using fine-tuned hyperparameters based on nested cross-validation (rightmost columns in gray), we trained prediction models based on another 8 sets of hyperparameter choices. These 8 sets of hyperparameters are combinations of 4 levels of dimensionality reduction (80 PCs, 160 PCs, 320 PCs, or all PCs) and 2 levels of regularization ($\alpha = 0.1$ or $\alpha = 10^{-20}$). These hyperparameter levels are the levels most frequently chosen based on nested cross-validation (Supplementary Figure S5). The histograms denote R^2 distribution across brain regions, and horizontal bars are the average R^2 across regions. For prediction models based on coarse-grained connectivity profiles, regularization is critical for prediction model performance, and with insufficient regularization models overfit dramatically with more PCs. When the regularization is large enough, the model performance slightly increases with higher number of PCs. For prediction models based on fine-grained connectivity profiles, model performance is hardly affected by regularization level, and consistently increases with higher number of PCs. This suggests PCs based on fine-grained connectivity profiles contain more information related to individual differences in intelligence and less noise. Note that even with only 80 PCs, prediction models based on hyperaligned fine-grained

Neural basis of intelligence in fine-grained cortical topographies Feilong 51

755 connectivity profiles still account for approximately two times more variance than those based on
756 coarse-grained connectivity profiles.

Alternative definition of cortical networks

Supplementary Figure S11. Proportion of vertices of the 30 most predictive regions in 12 cortical networks defined in Ji et al. (2019). (A) The 30 regions that are most predictive of general intelligence based on hyperaligned fine-grained task fMRI connectivity are in the default (34.0% of vertices in the 30 regions), frontoparietal (33.0%), cingulo-opercular (20.2%), dorsal attention (5.7%), and visual 2 (6.7%) networks. (B) The 30 regions that are most predictive of general intelligence based on hyperaligned fine-grained resting fMRI connectivity are in the default (39.3%), frontoparietal (22.5%), cingulo-opercular (14.4%), dorsal attention (13.9%), visual 2 (4.9%), language (2.8%) and visual 1 (1.7%) networks. The 12 cortical networks are defined based on Ji et al. (2019). Note that different cortical network parcellations are in agreement with each other in general, and the proportion of cortical vertices in these 12 networks are similar to the proportion in the 7 cortical systems based on Yeo et al. (2011). Most of the vertices are in default, frontoparietal, and dorsal attention networks based on both Yeo et al. (2011) and Ji et al. (2019); some regions in the ventral attention network based on Yeo et al. (2011) are labeled as cingulo-opercular in Ji et al. (2019).

773 Assessing the effects of head motion

774 The level of in-scanner head motion (usually measured as framewise displacement, or FD for
775 short) is correlated with many subject measures, and participants who move more in the
776 scanner are more likely to have lower cognitive test scores (Siegel et al., 2017). Therefore,
777 when the connectivity pattern is affected by motion-related artifacts, it is possible for prediction
778 models to take advantage of these spurious patterns and predict these subject measures to
779 some extent. For the dataset used in this study, the correlation between g and FD is $r(874) = -$
780 0.29 , $p < 10^{-18}$, which means a perfect head motion predictor can account for 8.6% of variance
781 in general intelligence (Supplementary Figure S12 A). To assess the influence of head motion
782 on our prediction models, we performed two additional analyses.

783 In the first analysis, we created a low motion sub-sample of the dataset, and evaluated
784 prediction performance based on this sub-sample. This sub-sample comprises participants
785 whose average FD is less than 0.15 mm across all fMRI runs, and has a sample size of 437.
786 Because sample size has a great influence on prediction performance (Supplementary Figure
787 S8), we created 10 control sub-samples. These control sub-samples have the same sample
788 size and almost identical mean and standard deviation of g as the low-motion sub-sample
789 (Supplementary Figure S12, Panel D), but have the full spectrum of head motion (Panel C).
790 Therefore, if the prediction models take advantage of the correlation between g and head
791 motion to predict g , we expect the model performance based on the control sub-samples to
792 outperform the low motion sub-sample.

793 Across all 3 kinds of connectivity profiles (coarse-grained, MSM-aligned fine-grained,
794 hyperaligned fine-grained) and 2 kinds of fMRI data (task fMRI, resting fMRI), we observed no
795 difference in prediction performance between models based on the low-motion sub-sample and
796 models based on control sub-samples (all $p > 0.11$; Supplementary Figure S12 Panel E). This
797 suggests that head motion has little influence on the performance of our prediction models.

Supplementary Figure S12. Prediction performance based on a low head motion sub-sample. General intelligence has a moderate correlation with head motion (Panel A), and a "motion detector" can predict general intelligence to some extent. To assess the effect of head motion variation on prediction performance, we trained another set of models based on a sub-sample of participants with minimal head motion (FD < 0.15 mm, n = 437, Panel B), and another 10 sets of models based on control sub-samples (see Panel C for an example control sub-sample). The control sub-samples had similar general intelligence variation but larger head motion variation

compared with the low motion sub-sample (Panel D). Prediction performance was similar between the low motion sub-sample and the control sub-samples (Panel E), suggesting larger variation in head motion level (while keeping sample size constant) has little effect on the prediction performance for general intelligence.

Note that in the low motion sub-sample, small variation in head motion still exists (Supplementary Figure S12, Panel D), and is slightly correlated with g ($r = -0.14$). Therefore, it is possible for a prediction model to take advantage of motion-related connectivity patterns, and account for up to 1.9% of variance in g if it can detect motion from functional connectivity perfectly. To further assess the effect of head motion, we performed a second analysis in a more strict way.

In the second analysis, we regressed out FD from functional connectivity profiles, and used the residual profiles to build our prediction models. This allows us to completely remove the variance in functional connectivity that covariates with head motion. Traditionally certain preprocessing pipelines are used to mitigate the effects of head motion on functional connectivity and reduce the prediction performance overestimation caused by head motion (Siegel et al., 2017; Ciric et al., 2017, 2018). However, it is unclear which preprocessing pipeline is most effective in removing motion-related artifacts in fine-grained connectivity, and it's practically challenging to compute fine-grained functional connectivity using multiple preprocessing pipelines. Therefore, we chose to use regression to remove covariation between functional connectivity and head motion. Note that regression is an aggressive approach and will also remove variance in "true" functional connectivity that covariates with FD. As a result, the maximal possible R^2 is no longer 100% but rather 91.4%, because the 8.6% of variance in g that covaries with FD can never be accounted for by these residual profiles.

To account for the effect of the new R^2 ceiling, we trained another 100 sets of prediction models, where each set was based on functional connectivity residuals after regressing out a random variable that had the same level of correlation with g (i.e., $r = 0.29$), and therefore had the same R^2 ceiling. For simplicity, we will refer to these models as control models and the models based on regressing out FD as FD-residual models. With these models, it is possible to separate the effect of R^2 ceiling by comparing original models and control models, and the effect specific to head motion by comparing control models with FD-residual models.

Compared with the original models, control models had lower R^2 , and the difference was 2.8%, 3.1%, and 4.2% for coarse-grained, MSM-aligned fine-grained, and hyperaligned fine-grained connectivity profiles respectively based on task fMRI data; the difference was 1.9%, 2.5%, 3.9% respectively based on resting fMRI data. This demonstrates that regressing out variables correlating with g from functional connectivity profiles will reduce model performance in general. Note that the R^2 difference was larger for connectivity profiles that are more predictive of g (e.g., hyperaligned fine-grained connectivity profiles for both task and resting fMRI data), suggesting that high-performance models are more influenced by the R^2 ceiling, probably because their performances are closer to the ceiling.

FD-residual models had lower R^2 compared with these control models, and the difference was 2.5%, 2.8%, and 2.7% respectively based on task fMRI data, and 1.3%, 2.0%, 1.1% respectively based on resting fMRI data (Supplementary Figure S13). These results suggest that head motion has a small (1.1% to 2.8%) but statistically significant effect on predicting g based on functional connectivity. Based on resting fMRI data, the effect of head motion was smaller for fine-grained connectivity profiles that are hyperaligned compared with those MSM-aligned ($\Delta R^2 = 0.9\%$, $p = 0.01$). This suggests using functional connectivity based on hyperaligned data may reduce the influence of head motion on prediction models.

Task fMRI functional connectivity

Resting fMRI functional connectivity

Supplementary Figure S13. Regressing out head motion from functional connectivity. We regressed out head motion (measured as framewise displacement) from functional connectivity profiles and built prediction models based on the residual connectivity profiles, and compared their performance with 100 sets of control models. Each dot is a brain region, and error bars denote the standard deviation across 100 control model sets. For each set of control models, a random variable that has the same level of correlation with g was regressed out from functional connectivity profiles instead of head motion to control for the effect of lower R^2 ceiling caused by regression. Compared with the control models, models based on regressing out head motion had slightly lower performance (range: 1.1% to 2.8%), as demonstrated by that the dots are slightly

865 below the diagonal in general. This difference suggests that the shared variance between
866 functional connectivity and head motion may cause a slight overestimation of model performance.
867 However, the effect is small and cannot explain the difference between models based on different
868 types of connectivity profiles.

869

References

- 870 Addis DR, Wong AT, Schacter DL. 2007. Remembering the past and imagining the future:
871 common and distinct neural substrates during event construction and elaboration.
872 *Neuropsychologia* **45**:1363–1377. doi:10.1016/j.neuropsychologia.2006.10.016
- 873 Andrews-Hanna JR, Reidler JS, Sepulcre J, Poulin R, Buckner RL. 2010. Functional-anatomic
874 fractionation of the brain's default network. *Neuron* **65**:550–562.
875 doi:10.1016/j.neuron.2010.02.005
- 876 Andrews-Hanna JR, Smallwood J, Spreng RN. 2014. The default network and self-generated
877 thought: component processes, dynamic control, and clinical relevance. *Ann N Y Acad*
878 *Sci* **1316**:29–52. doi:10.1111/nyas.12360
- 879 Barch DM, Burgess GC, Harms MP, Petersen SE, Schlaggar BL, Corbetta M, Glasser MF,
880 Curtiss S, Dixit S, Feldt C, Nolan D, Bryant E, Hartley T, Footer O, Bjork JM, Poldrack R,
881 Smith S, Johansen-Berg H, Snyder AZ, Van Essen DC, WU-Minn HCP Consortium.
882 2013. Function in the human connectome: task-fMRI and individual differences in
883 behavior. *Neuroimage* **80**:169–189. doi:10.1016/j.neuroimage.2013.05.033
- 884 Behzadi Y, Restom K, Liao J, Liu TT. 2007. A Component Based Noise Correction Method
885 (CompCor) for BOLD and Perfusion Based fMRI. *Neuroimage* **37**:90–101.
886 doi:10.1016/j.neuroimage.2007.04.042
- 887 Bilker WB, Hansen JA, Brensinger CM, Richard J, Gur RE, Gur RC. 2012. Development of
888 abbreviated nine-item forms of the Raven's standard progressive matrices test.
889 *Assessment* **19**:354–369. doi:10.1177/1073191112446655
- 890 Buckner RL, Andrews-Hanna JR, Schacter DL. 2008. The brain's default network: anatomy,
891 function, and relevance to disease. *Ann N Y Acad Sci* **1124**:1–38.
892 doi:10.1196/annals.1440.011
- 893 Ciric, R., Rosen, A. F. G., Erus, G., Cieslak, M., Adebimpe, A., Cook, P. A., Bassett, D. S.,
894 Davatzikos, C., Wolf, D. H., & Satterthwaite, T. D. (2018). Mitigating head motion artifact
895 in functional connectivity MRI. *Nature Protocols*, **13**(12), 2801–2826.
896 <https://doi.org/10.1038/s41596-018-0065-y>
- 897 Ciric, R., Wolf, D. H., Power, J. D., Roalf, D. R., Baum, G. L., Ruparel, K., Shinohara, R. T.,
898 Elliott, M. A., Eickhoff, S. B., Davatzikos, C., Gur, R. C., Gur, R. E., Bassett, D. S., &
899 Satterthwaite, T. D. (2017). Benchmarking of participant-level confound regression
900 strategies for the control of motion artifact in studies of functional connectivity.
901 *NeuroImage*, **154**, 174–187. <https://doi.org/10.1016/j.neuroimage.2017.03.020>
- 902 Connolly AC, Sha L, Guntupalli JS, Oosterhof N, Halchenko YO, Nastase SA, Castello MV di O,
903 Abdi H, Jobst BC, Gobbini MI, Haxby JV. 2016. How the Human Brain Represents
904 Perceived Dangerousness or “Predacity” of Animals. *J Neurosci* **36**:5373–5384.
905 doi:10.1523/JNEUROSCI.3395-15.2016
- 906 Cox SR, Ritchie SJ, Fawns-Ritchie C, Tucker-Drob EM, Deary IJ. 2019. Structural brain imaging
907 correlates of general intelligence in UK Biobank. *Intelligence* **76**:101376.
908 doi:10.1016/j.intell.2019.101376
- 909 Dice LR. 1945. Measures of the Amount of Ecologic Association Between Species. *Ecology*
910 **26**:297–302. doi:10.2307/1932409
- 911 Dixon ML, Vega ADL, Mills C, Andrews-Hanna J, Spreng RN, Cole MW, Christoff K. 2018.
912 Heterogeneity within the frontoparietal control network and its relationship to the default
913 and dorsal attention networks. *PNAS* **115**:E1598–E1607. doi:10.1073/pnas.1715766115
- 914 Dubois J, Galdi P, Paul LK, Adolphs R. 2018. A distributed brain network predicts general
915 intelligence from resting-state human neuroimaging data. *Philosophical Transactions of*
916 *the Royal Society B: Biological Sciences* **373**:20170284. doi:10.1098/rstb.2017.0284
- 917 Eickhoff, S. B., Constable, R. T., & Yeo, B. T. T. (2018). Topographic organization of the

- 918 cerebral cortex and brain cartography. *NeuroImage*, 170, 332–347.
- 919 <https://doi.org/10.1016/j.neuroimage.2017.02.018>
- 920 Feilong M, Nastase SA, Guntupalli JS, Haxby JV. 2018. Reliable individual differences in fine-
- 921 grained cortical functional architecture. *Neuroimage* **183**:375–386.
- 922 doi:10.1016/j.neuroimage.2018.08.029
- 923 Finn ES, Shen X, Scheinost D, Rosenberg MD, Huang J, Chun MM, Papademetris X, Constable
- 924 RT. 2015. Functional connectome fingerprinting: identifying individuals using patterns of
- 925 brain connectivity. *Nat Neurosci* **18**:1664–1671. doi:10.1038/nn.4135
- 926 Frith CD, Frith U. 1999. Interacting minds--a biological basis. *Science* **286**:1692–1695.
- 927 doi:10.1126/science.286.5445.1692
- 928 Glasser MF, Coalson TS, Robinson EC, Hacker CD, Harwell J, Yacoub E, Ugurbil K, Andersson
- 929 J, Beckmann CF, Jenkinson M, Smith SM, Van Essen DC. 2016. A multi-modal
- 930 parcellation of human cerebral cortex. *Nature* **536**:171–178. doi:10.1038/nature18933
- 931 Glasser MF, Sotiropoulos SN, Wilson JA, Coalson TS, Fischl B, Andersson JL, Xu J, Jbabdi S,
- 932 Webster M, Polimeni JR, Van Essen DC, Jenkinson M, WU-Minn HCP Consortium.
- 933 2013. The minimal preprocessing pipelines for the Human Connectome Project.
- 934 *Neuroimage* **80**:105–124. doi:10.1016/j.neuroimage.2013.04.127
- 935 Gobbini MI, Haxby JV. 2007. Neural systems for recognition of familiar faces. *Neuropsychologia*
- 936 **45**:32–41. doi:10.1016/j.neuropsychologia.2006.04.015
- 937 Gobbini MI, Koralek AC, Bryan RE, Montgomery KJ, Haxby JV. 2007. Two takes on the social
- 938 brain: a comparison of theory of mind tasks. *J Cogn Neurosci* **19**:1803–1814.
- 939 doi:10.1162/jocn.2007.19.11.1803
- 940 Golland Y, Bentin S, Gelbard H, Benjamini Y, Heller R, Nir Y, Hasson U, Malach R. 2007.
- 941 Extrinsic and intrinsic systems in the posterior cortex of the human brain revealed during
- 942 natural sensory stimulation. *Cereb Cortex* **17**:766–777. doi:10.1093/cercor/bhk030
- 943 Greene AS, Gao S, Scheinost D, Constable RT. 2018. Task-induced brain state manipulation
- 944 improves prediction of individual traits. *Nature Communications* **9**:1–13.
- 945 doi:10.1038/s41467-018-04920-3
- 946 Guntupalli JS, Feilong M, Haxby JV. 2018. A computational model of shared fine-scale structure
- 947 in the human connectome. *PLOS Computational Biology* **14**:e1006120.
- 948 doi:10.1371/journal.pcbi.1006120
- 949 Guntupalli JS, Hanke M, Halchenko YO, Connolly AC, Ramadge PJ, Haxby JV. 2016. A Model
- 950 of Representational Spaces in Human Cortex. *Cereb Cortex* **26**:2919–2934.
- 951 doi:10.1093/cercor/bhw068
- 952 Guntupalli JS, Wheeler KG, Gobbini MI. 2017. Disentangling the Representation of Identity from
- 953 Head View Along the Human Face Processing Pathway. *Cereb Cortex* **27**:46–53.
- 954 doi:10.1093/cercor/bhw344
- 955 Gur RC, Richard J, Hughett P, Calkins ME, Macy L, Bilker WB, Brensinger C, Gur RE. 2010. A
- 956 cognitive neuroscience-based computerized battery for efficient measurement of
- 957 individual differences: standardization and initial construct validation. *J Neurosci*
- 958 *Methods* **187**:254–262. doi:10.1016/j.jneumeth.2009.11.017
- 959 Hanke M, Halchenko YO, Sederberg PB, Hanson SJ, Haxby JV, Pollmann S. 2009. PyMVA: A
- 960 python toolbox for multivariate pattern analysis of fMRI data. *Neuroinformatics* **7**:37–53.
- 961 doi:10.1007/s12021-008-9041-y
- 962 Haxby JV, Connolly AC, Guntupalli JS. 2014. Decoding neural representational spaces using
- 963 multivariate pattern analysis. *Annu Rev Neurosci* **37**:435–456. doi:10.1146/annurev-
- 964 neuro-062012-170325
- 965 Haxby JV, Gobbini MI, Furey ML, Ishai A, Schouten JL, Pietrini P. 2001. Distributed and
- 966 overlapping representations of faces and objects in ventral temporal cortex. *Science*
- 967 **293**:2425–2430. doi:10.1126/science.1063736
- 968 Haxby JV, Guntupalli JS, Connolly AC, Halchenko YO, Conroy BR, Gobbini MI, Hanke M,

- 969 Ramadge PJ. 2011. A common, high-dimensional model of the representational space in
970 human ventral temporal cortex. *Neuron* **72**:404–416. doi:10.1016/j.neuron.2011.08.026
- 971 Haxby JV, Guntupalli JS, Nastase SA, Feilong M. 2020. Hyperalignment: Modeling shared
972 information encoded in idiosyncratic cortical topographies. *eLife* **9**:e56601.
973 doi:10.7554/eLife.56601
- 974 Ji, J. L., Spronk, M., Kulkarni, K., Repovš, G., Anticevic, A., & Cole, M. W. (2019). Mapping the
975 human brain's cortical-subcortical functional network organization. *NeuroImage*, **185**,
976 35–57. <https://doi.org/10.1016/j.neuroimage.2018.10.006>
- 977 Jiahui, G., Feilong, M., Visconti di Oleggio Castello, M., Guntupalli, J. S., Chauhan, V., Haxby,
978 J. V., & Gobbini, M. I. (2019). Predicting individual face-selective topography using
979 naturalistic stimuli. *NeuroImage*, 116458.
980 <https://doi.org/10.1016/j.neuroimage.2019.116458>
- 981 Jiang R, Zuo N, Ford JM, Qi S, Zhi D, Zhuo C, Xu Y, Fu Z, Bustillo J, Turner JA, Calhoun VD,
982 Sui J. 2020. Task-induced brain connectivity promotes the detection of individual
983 differences in brain-behavior relationships. *NeuroImage* **207**:116370.
984 doi:10.1016/j.neuroimage.2019.116370
- 985 Johnson W, Bouchard TJ, Krueger RF, McGue M, Gottesman II. 2004. Just one g: Consistent
986 results from three test batteries. *Intelligence* **32**:95–107. doi:10.1016/S0160-
987 2896(03)00062-X
- 988 Johnson W, Nijenhuis J te, Bouchard TJ. 2008. Still just 1 g: Consistent results from five test
989 batteries. *Intelligence* **36**:81–95. doi:10.1016/j.intell.2007.06.001
- 990 Kong R, Li J, Orban C, Sabuncu MR, Liu H, Schaefer A, Sun N, Zuo X-N, Holmes AJ, Eickhoff
991 SB, Yeo BTT. 2019. Spatial Topography of Individual-Specific Cortical Networks
992 Predicts Human Cognition, Personality, and Emotion. *Cereb Cortex* **29**:2533–2551.
993 doi:10.1093/cercor/bhy123
- 994 Kong, R., Yang, Q., Gordon, E., Xue, A., Yan, X., Orban, C., Zuo, X.-N., Spreng, N., Ge, T.,
995 Holmes, A., Eickhoff, S., & Yeo, B. T. T. (2021). Individual-Specific Areal-Level
996 Parcellations Improve Functional Connectivity Prediction of Behavior. *BioRxiv*,
997 2021.01.16.426943. <https://doi.org/10.1101/2021.01.16.426943>
- 998 Kriegeskorte N, Mur M, Bandettini P. 2008. Representational similarity analysis - connecting the
999 branches of systems neuroscience. *Front Syst Neurosci* **2**:4.
1000 doi:10.3389/neuro.06.004.2008
- 1001 Luders E, Narr KL, Bilder RM, Thompson PM, Szeszko PR, Hamilton L, Toga AW. 2007.
1002 Positive correlations between corpus callosum thickness and intelligence. *Neuroimage*
1003 **37**:1457–1464. doi:10.1016/j.neuroimage.2007.06.028
- 1004 Nastase SA, Liu Y-F, Hillman H, Norman KA, Hasson U. 2020. Leveraging shared connectivity
1005 to aggregate heterogeneous datasets into a common response space. *Neuroimage*
1006 **116865**. doi:10.1016/j.neuroimage.2020.116865
- 1007 Park SH, Russ BE, McMahon DBT, Koyano KW, Berman RA, Leopold DA. 2017. Functional
1008 Subpopulations of Neurons in a Macaque Face Patch Revealed by Single-Unit fMRI
1009 Mapping. *Neuron* **95**:971–981.e5. doi:10.1016/j.neuron.2017.07.014
- 1010 Plomin R, Deary IJ. 2015. Genetics and intelligence differences: five special findings. *Molecular*
1011 *Psychiatry* **20**:98–108. doi:10.1038/mp.2014.105
- 1012 Raichle ME. 2006. The Brain's Dark Energy. *Science* **314**:1249–1250. doi:10.1126/science.
1013 1134405
- 1014 Raichle ME, MacLeod AM, Snyder AZ, Powers WJ, Gusnard DA, Shulman GL. 2001. A default
1015 mode of brain function. *Proc Natl Acad Sci U S A* **98**:676–682.
- 1016 Robinson EC, Jbabdi S, Glasser MF, Andersson J, Burgess GC, Harms MP, Smith SM, Van
1017 Essen DC, Jenkinson M. 2014. MSM: a new flexible framework for Multimodal Surface
1018 Matching. *Neuroimage* **100**:414–426. doi:10.1016/j.neuroimage.2014.05.069
- 1019 Saxe R, Kanwisher N. 2003. People thinking about thinking people. The role of the temporo-

1020 parietal junction in “theory of mind.” *Neuroimage* **19**:1835–1842. doi:10.1016/s1053-
1021 8119(03)00230-1

1022 Schmitt JE, Neale MC, Clasen LS, Liu S, Seidlitz J, Pritikin JN, Chu A, Wallace GL, Lee NR,
1023 Giedd JN, Raznahan A. 2019. A Comprehensive Quantitative Genetic Analysis of
1024 Cerebral Surface Area in Youth. *J Neurosci* **39**:3028–3040.
1025 doi:10.1523/JNEUROSCI.2248-18.2019

1026 Shen X, Finn ES, Scheinost D, Rosenberg MD, Chun MM, Papademetris X, Constable RT.
1027 2017. Using connectome-based predictive modeling to predict individual behavior from
1028 brain connectivity. *Nat Protoc* **12**:506–518. doi:10.1038/nprot.2016.178

1029 Siegel, J. S., Mitra, A., Laumann, T. O., Seitzman, B. A., Raichle, M., Corbetta, M., & Snyder, A.
1030 Z. (2017). Data quality influences observed links between functional connectivity and
1031 behavior. *Cerebral Cortex*, 27(9), 4492–4502. <https://doi.org/10.1093/cercor/bhw253>

1032 Spearman C. 1904. “General Intelligence,” Objectively Determined and Measured. *The*
1033 *American Journal of Psychology* **15**:201–292. doi:10.2307/1412107

1034 Uğurbil K, Xu J, Auerbach EJ, Moeller S, Vu A, Duarte-Carvajalino JM, Lenglet C, Wu X,
1035 Schmitter S, Van de Moortele PF, Strupp J, Sapiro G, De Martino F, Wang D, Harel N,
1036 Garwood M, Chen L, Feinberg DA, Smith SM, Miller KL, Sotiropoulos SN, Jbabdi S,
1037 Andersson JL, Behrens TE, Glasser MF, Van Essen D, Yacoub E. 2013. Pushing spatial
1038 and temporal resolution for functional and diffusion MRI in the Human Connectome
1039 Project. *Neuroimage* **80**:80–104. doi:10.1016/j.neuroimage.2013.05.012

1040 Van Essen DC, Smith SM, Barch DM, Behrens TEJ, Yacoub E, Ugurbil K, WU-Minn HCP
1041 Consortium. 2013. The WU-Minn Human Connectome Project: an overview.
1042 *Neuroimage* **80**:62–79. doi:10.1016/j.neuroimage.2013.05.041

1043 Varoquaux, G., Raamana, P. R., Engemann, D. A., Hoyos-Idrobo, A., Schwartz, Y., & Thirion,
1044 B. (2017). Assessing and tuning brain decoders: Cross-validation, caveats, and
1045 guidelines. *NeuroImage*, 145, 166–179.
1046 <https://doi.org/10.1016/j.neuroimage.2016.10.038>

1047 Winkler AM, Webster MA, Vidaurre D, Nichols TE, Smith SM. 2015. Multi-level block
1048 permutation. *NeuroImage* **123**:253–268. doi:10.1016/j.neuroimage.2015.05.092

1049 Yeo BTT, Krienen FM, Sepulcre J, Sabuncu MR, Lashkari D, Hollinshead M, Roffman JL,
1050 Smoller JW, Zöllei L, Polimeni JR, Fischl B, Liu H, Buckner RL. 2011. The organization
1051 of the human cerebral cortex estimated by intrinsic functional connectivity. *J*
1052 *Neurophysiol* **106**:1125–1165. doi:10.1152/jn.00338.2011