Water yield modelling, sensitivity analysis and validation: a study for Portugal

Bruna Almeida^{1¶*}, Pedro Cabral^{1¶}

¹ NOVA Information Management School (NOVA IMS), Universidade Nova de Lisboa, 1070-312 Lisboa, Portugal

* Corresponding author

E-mail: bruna.campus.unl@gmail.com

¶ These authors contributed equally to this work.

Abstract

The spatially explicit assessment of freshwater is key to introduce the ecosystem service (ES) concept into decision-making processes. Many tools are being developed to model water balance and to analyse the effects of meteorological conditions on water ES behaviours at multiple spatial scales. Nevertheless, there is a lack of studies that analyse the sensitivity of these models and estimate the model's accuracy. The current research uses the InVEST Water Yield Model (WYM) to assess freshwater ES between 1990 and 2018 at River Basin District (RBD) level in mainland Portugal. The methodology included sensitivity analysis simulations to test different parameters of the model over two different sources of meteorological data. We validated the model with the European Environment Agency (EEA) database on the quantity of Europe's freshwater resources. To evaluate the models' sensitivity, Pearson's correlation coefficients and statistical methods were calculated for each simulation. The model which obtained the best performance in the sensitivity tests was retained for further analysis and calibration and its accuracy was assessed by comparing the mean estimated water yield (WY) with mean observed values for 2018. Results at the national level show a correlation coefficient of 0.803 with statistical significance for 0.01 one-tail. The WY in the RBDs of the North of the country was underestimated by 56.5 mm/ha/year and for the RBDs in the South of Portugal, the WY was overestimated by 58.1 mm/ha/year. This difference was explained through the spatial-temporal assessment of the main climatic variables used as input. This study contributes to a methodology to assess the level of confidence in WYM outputs and can be used to support the trustworthiness of water availability studies at sub-watershed, watershed, or RBD, using open access data and software.

36

37

1. Introduction

38

39 Ecosystem services (ES) represent the benefits human populations derive, directly or indirectly, from
40 ecosystem functions [1]. Most of nature's contributions to people are not fully replaceable, and
41 some are irreplaceable [2]. The long-term security of many ecosystem functions and services,
42 especially in changing environments, is likely to depend upon local biodiversity, which has been
43 facing growing pressures from human activities [3]. Some of those activities result in modifications in
44 the natural landscapes around rivers and wetlands to the point that their biodiversity is put at risk
45 [4]. Freshwater ecosystems are crucially important providers of ecosystem services as they provide
46 clean water for multiple uses including water for drinking, irrigation, or recreation [5]. Since 1970,
47 land-use change has had the largest relative negative impact on this service, followed by direct
48 exploitation, in particular, overexploitation [2].

49 Climate change poses another set of pressures on water-related ES [6] with extreme weather
50 events perceived as the top risk affecting immediately the agricultural sector [7]. Over one-third of
51 the world's land surface and nearly three-quarters of available freshwater resources are devoted to
52 crop or livestock production [2]. The water demand is strongly influenced by population and
53 agricultural production, and water availability is linked to the frequency and amount of precipitation
54 [8]. The negative impacts of climate change on water availability call for urgent action to allocate
55 and to use water more wisely [6]. More than half the world's population, some four billion people,
56 are exposed to drought for at least one month per year [7].

57 For the seventh consecutive year, the Global Risks Report 2018 listed water crises among the top
58 five global risks both in terms of impact and in terms of likelihood [9]. To deal with that, adaptive
59 management practices must be implemented to increase the adaptation capacity of river basins to
60 changing conditions, such as climate and global change [5]. River Basin District (RBD) represents the
61 natural boundaries of a complex ecological system [10] that according to the report carried out by
62 the Water Resources Group in 2009, by 2030 over a third of the world population will be living in
63 river basins that will have to cope with significant water stress [11].

64 Projections indicate that the most rapid increase in water demand will be in urban contexts [7].
65 As climate change and the lack of adequate adaptation strategies are the biggest threat to Europe's
66 water environment [12], an approach to face this issue is to identify sustainable pathways that
67 would anticipate and manage the inevitable increases in water scarcity and water-related risks [6].
68 River basins resilience measure the degree to which a catchment can adjust to normal functioning
69 following perturbations from events such as drought or extreme precipitation [13] and also under
70 some activities such as energy production and crop irrigations [12].

71 A step towards the harmonisation of water, ecosystems and society can be achieved through the
72 assessment, mapping and valuation of ecosystem services [5]. Nowadays, we are seeing a more
73 explicit quantification of the value of nature in defining human-water interactions [4]. Several
74 spatially-based decision support tools have emerged for ESs assessment [14], and one of them is the
75 InVEST (Integrated Valuation of Ecosystem Services and Tradeoffs) developed by the Natural Capital
76 Project - Stanford University. The InVEST Reservoir Hydropower Production Water Yield Model
77 (WYM) estimates the relative contributions of water from different parts of a landscape, offering
78 insights into how changes in land-use patterns affect water balance, freshwater provision accounts
79 and hydropower production [15].

80 The mapping and evaluation of ecosystems and their services is a key action to communicate the
81 characteristics, trends, and rate of change in ecosystem services and biodiversity [16]. It provides

useful information for decision-makers [17] in planning and acting to strengthen the resilience of economies and societies to protect them from water-related disasters [6]. The existing challenges to introduce the ESs concept into decision-making processes are related to the requirement for accurate mapping and evaluation, and a deep understanding of models' sensitivities [15].

Sensitivity analysis is an effective tool for identifying important uncertainty sources and improving model calibration and predictions [18]. It is an integral part of model development and involves an analytical examination of input parameters to aid in model validation and provide guidance for future research [19]. This technique consists of changing values of inputs and internal parameters of a model to determine the effect on the behavior and output of the model [20], increasing our understanding of which parameters must be determined with the greatest accuracy, and thus helping to prioritize data collection requirements [18].

All parameters in the InVEST WYM display some degree of sensitivity [21]. Previous studies (e.g. [22]) show that the model can be very sensitive to changes in drivers such as land-use and meteorological data. Extremes variations in those drivers can alter hydrologic cycles, affecting patterns of evapotranspiration, infiltration, and water retention [23]. The goal of the InVEST model is not to reproduce observations with a high degree of accuracy and precision, but to provide reliable geospatial information to support decisions [24]. However, an important and often overlooked question is how accurate are the outputs of the WYM with empirical observations [15].

This paper aims to answer this question by studying the WYM uncertainties and estimating its accuracy, through sensitivity analysis and validation. The model's sensitivity is evaluated by testing: two different sources of climatic data; different values for the seasonality coefficient (Z); different grids of plant available water content and biophysical table, and model's outputs were validated with the European Environment Agency (EEA) database on the quantity of Europe's water resources of 2018. Model's accuracy was calculated comparing mean estimated water yield with mean observed values from the validation data, and to evaluate the model's sensitivity, Pearson's correlation coefficients and statistical methods were calculated for each simulation. Analysing the sensitivity of the WYM and estimating its accuracy aim to build confidence in the model's outputs, and to support studies related to the spatial estimation of water availability and water ESs' behaviours at sub-watershed, watershed, or RBD.

2. Materials and methods

2.1. Study area

Portugal is in the Iberian Peninsula (south-western Europe) comprising a continental part and two autonomous regions, Azores, and Madeira archipelagos. The territory total area is 92 072 km² and the population is about 9.8 million [25].

In the climatic perspective, it lays in the transitional region between the subtropical anticyclone and the sub-polar depression zones [26]. The most conditioning climate factors are latitude, orography and the effect of the Atlantic Ocean, characterizing high spatial and temporal variability [27] that affect the water cycle primarily through changes in the precipitation and temperature [28]. In mainland Portugal, the large temporal variability of the precipitation rates leads to precipitation extreme events and intense dry months, resulting in impacts in water resources, fire risk and ecosystem degradation [27].

As other southern European regions, Portugal is quite vulnerable to climate variability, namely to

droughts and desertification, especially in the southern sector [29]. Mean annual precipitation ranges from less than 500 mm in the South of Portugal up to 3000 mm in the North, with 40% of the annual amount falling in winter [26]. High temperatures and high evapotranspiration lead to higher average water consumption per hectare in southern European countries [30]. Water abstraction for irrigated agriculture has changed the flow regime of many river basins and lowered groundwater levels, particularly in these European regions [12]. Episodes of water scarcity occur in PTRH5 (Tejo and Ribeiros do Oeste) and in all RBDs to the south of it where rain is more concentrated in fewer days during the year, and the "normal" year corresponds closely to a "dry" year [31]. Nevertheless, if there is suitable sustainable water management, the available water resources are sufficient to satisfy the needs [32].

The most represented land use classes in Portugal are agricultural areas and forest and semi-natural areas, namely transitional woodland-shrub [33]. The proportion of extensive crop production and extensive grazing is particularly high (59%) which could lead to better ecosystem condition under reduced pressures [34]. Therefore, changes in the vegetation cover and a poorly planned and managed forests have considerable impacts on the water cycle causing pressures on the water environment [12]. Portugal is one of the European countries with the highest diversity of organisms and farming systems, but at the same time is one of the countries more vulnerable to the loss of that diversity [32].

Portugal is also one of the European countries that are reliant on water resources that originate outside their territory [30]. The share of Portugal in the respective international RBDs with Spain is PTRH1 (Minho 9% and Lima 47.6% of the ES010), PTRH3 (19.1% of the ES020), PTRH5A (31.1% of the ES030) and PTRH7 (17.2% of the ES040) [31]. *Fig 1* shows the transboundary water management by RBDs. The boundaries of the National and International RBDs are displayed using version 1.4 of the Water Information System for Europe River Basin Districts dataset available from the European Environment Agency [35]. This dataset is based on data reported to WISE by the EU Member States [35].

Fig 1. Overview of the national/ international RBDs.

The localid refers to the RBDs abbreviations: PTRH1 (Minho and Lima, 2465 km²); PTRH2 (Cávado, Ave and Leça, 3584 km²); PTRH3 (Douro, 19219 km²); PTRH4A (Vouga, Mondego and Lis, 16981 km²); PTRH5A (Tejo and Ribeiros do Oeste, 25665 km²); PTRH6 (Sado and Mira, 12149 km²); PTRH7 (Guadiana, 11611 km²); PTRH8 (Ribeiros do Algarve, 5511 km²); PTRH9 (Azores, 10047 km²); PTRH10 (Madeira, 2248 km²). Source: [35].

At a national level, the main problems associated with the management of water resources are related to water quality, nature conservation, supply and demand, water domain and planning, irrigation, information and knowledge, economic and financial regime, and energy security [32]. Nowadays, hydropower forms a considerable contribution to the Portuguese energy sector representing 30% of the national electricity consumed [35].

According to the most recent European assessment under the Second River Basin Management Plans for Portugal [31], droughts and water abstraction have been reported to be relevant for a major part of Portugal, representing significant pressures on both surface and groundwater ecosystems with direct impacts on water availability. The seriousness of ecosystem degradation and scarcity of the services, as well as the existing institutional context, should always be the starting point for designing analysis and governance solutions [2]. Water yield is a key ecosystem service in river basins [36] and has a provisioning function that represents water balance across space and time [37].

2.2. The InVEST Water Yield model

The WYM is defined by physical expressions and spatial and temporal resolutions, providing as outputs maps, outcomes of water services, impacts of environmental changes and analyses of spatial patterns (Sharp et al., 2020). The InVEST WYM approach relates the LULC types with the Evaporative Index (EI) using the methodology developed by [38]. It does the water balance, estimating the annual water yield (Y) for each pixel (x) through the difference between precipitation and actual evapotranspiration. The WYM physical expressions are extensively described in [22] and [38]. The InVEST WYM calculates water yield, water consumption and hydropower valuation. In this study the focus is to calculate freshwater resources availability, i.e. water yield, at a national scale by RBD.

2.3. Data

In the InVEST WYM, the runoff from each pixel cell in a catchment is determined based on the water balance concept [39]. For that, the model requires five biophysical parameters as georeferenced rasters (LULC, root depth, plant available water content (PAWC), annual precipitation and evapotranspiration), a vectorial format layer delimiting the study catchment areas, and a biophysical table in CSV format [38].

All required data were obtained freely on the Internet from research centres and public institutions. The datasets Root restriction layer depth and PAWC were provided by the European Soil Data Centre (ESDAC), a European reference Centre for soil-related data [40]. The annual precipitation was obtained from WorldClim database [41] and the reference evapotranspiration from the Consortium of Spatial Information, Global-Aridity and Global-PET Database [42], a product derived from the WorldClim global data. These datasets were modelled based on a high number of climate observations and Shuttle Radar Topography Mission (SRTM) data. The other source of climatic data was obtained by the National Information System of Hydric Resources [43] who collects, processes, and publishes meteorological data at the national scale.

LULC data for years (1990, 2000, 2006, 2012 and 2018) were obtained from Copernicus Global Land Service products [44]. Land cover maps represent spatial information on different types (a total of 44 classes) of physical coverage of the Earth's surface, using a Minimum Mapping Unit (MMU) of 25 hectares (ha) for areal phenomena and a minimum width of 100 m for linear phenomena.

The CSV biophysical table required by the model has values associated with each LULC class, rooting depth (mm), and plant evapotranspiration coefficient (k_{xj}). This latter is used to calculate potential evapotranspiration by using plant physiological characteristics to modify the reference evapotranspiration. The table was built using data available in the literature [38,45,46].

2.4. Sensitivity analysis

Sensitivity analysis was performed by adapting the methodologies proposed by: [15,22,24]. Two different data sources of precipitation (P1; P2) and evapotranspiration (E1; E2) were tested. P1 and E1 refer to precipitation and evapotranspiration indices based on satellite data from WordClim database; P2 and E2 were collected, processed, and published by the National Information System of Hydric Resources (SNIRH). The model was also tested with two different PAWC. The main PAWC is

the official dataset provided by the European reference Centre for soil-related data. In mainland Portugal this dataset has pixels values varying between 0.03 and 0.14 with a mean value equal to 0.08. The lowest values are mostly related with coarse-textured soils (sands and loamy sands) which have low ability to retain water [47]. Apart from particle size affecting the volume of water that can be stored, different degrees of PAWC fractions depend on soil depth [48]. To test the model under extreme values of PAWC and soil depth, a new dataset was created by reclassifying the original PAWC, obtaining fractions between 0.03 and 0.98. The reclassification was meant to test the model to the maximum possible value, which is 1.

The sensitivity of the model to Zhang seasonality coefficient can also be interpreted as the sensitivity to the PAWC since these parameters play a similar role in the model structure [24]. The Z coefficient (Z1, Z2) is estimated at $0.2 \cdot N$, where N is the number of rain days (> 1 mm) per year [38]. The N1 values were obtained from the *Portal do Clima* PROJECT [49] which provides several climatic indicators aiming to quantify the occurrence and risk of different atmospheric events [50]. The N2 values were obtained from the Portuguese Institute of the Sea and the Atmosphere [51] database [27]. This institution supports the nation with wide climate-related information products. Table 1 shows the assigned values to this seasonality term (Z) for mainland Portugal.

Table 1. The number of rain days (N1, N2) per year and the values assigned to the Zhang coefficient ($Z = 0,2 \cdot N$).

Year	N1 [49]	Z1	N2 [51]	Z2
1990	82	16	99	20
2000	106	21	115	23
2006	100	20	102	20
2012	94	19	129	26
2018	93	18	123	25

Considering the increasing of fire events in the last years [2] and assuming that they have impacts on water ecosystem functions due to loss of diversity and modifications on vegetation structure [52], an alternative biophysical table was created after changing the value of the plant evapotranspiration coefficient (kc) of the LULC classified as 334 (burnt areas) by 10% higher. Uncertainties on this parameter are large since it remains difficult to provide accurate estimates of the actual evapotranspiration from forests [24]. Table 2 summarizes the input data and their sources by the sensitivity analysis tests.

Table 2. Input data required in the WYM grouped by the 4 sensitivity analysis tests.

WYM Parameters/ data source	Test 1 (T1)	Test 2 (T2)	Test 3 (T3)	Test 4 (T4)
Average Annual precipitation (mm)	P1 (WorldClim-CSI); P2 (SNIRH)	P1 (WorldClim-CSI); P2 (SNIRH)	P1 (WorldClim-CSI); P2 (SNIRH)	P1 (WorldClim-CSI); P2 (SNIRH)
Seasonality coefficient	Z1; Z2	Z1; Z2	Z1; Z2	Z1; Z2
Land use/land cover	LULC- (Copernicus)	LULC- (Copernicus)	LULC- (Copernicus)	LULC- (Copernicus)
Average annual evapotranspiration (mm)	E1 (WorldClim-CSI)	E1 (WorldClim-CSI)	E1 (WorldClim-CSI)	E2 (SNIRH)
Plant available water	Reclassified: NewPawc =	Reclassified:	PAWC	PAWC

content fraction	PAWC (values ≥ 0.08) * 7	NewPawc = PAWC (values ≥ 0.08) * 7	(ESDAC)	(ESDAC)
Watersheds	RBD (EEA-WISE)	RBD (EEA- WISE)	RBD (EEA- WISE)	RBD (EEA- WISE)
Root restricting layer depth (mm)	ESDAC	ESDAC	ESDAC	ESDAC
Biophysical Table	Modified - LULC classes 334 burnt areas with values to kc (plant evapotranspiration coefficient) 10% higher- (FAO)	Referential Biophysical Table – (FAO)	Referential Biophysical Table - (FAO)	Referential Biophysical Table - (FAO)

2.5. Validation

The minimum requirement when validating assessment models is to establish an adequate scientific basis for credibility [18]. The model is said to be validated if its accuracy and predictive capability in the validation period have been proven to lie within acceptable limits [53]. If a test determines that a model does not have enough accuracy for any of the sets of experimental conditions, then the model is invalid. However, determining that a model has sufficient accuracy for numerous experimental conditions does not guarantee that a model is valid everywhere in its applicable domain [54].

Model validation is defined as the process of demonstrating that a given site-specific model can make sufficiently accurate estimations [53]. The confidence-building view defines the validation of impact assessment models as the process of building scientific confidence in the methods used to perform such an assessment [18].

In this study, is reported the water yield estimates for the 8 RBDs (PTRH1 to PTRH8) covering all mainland Portugal's extent. These districts represent the administrative jurisdictions responsible to manage the Water Framework Directive (WFD) on the national scale. To validate the model, we compare the mean estimated water yield in the RBDs to the European Environment Agency (EEA) databases on the quantity of Europe's water resources. The EEA's Waterbase [35] contains data on freshwater resources availability, delivered by EEA member countries, in the scope of the current WISE SoE - Water Quantity (WISE-3) Water Information System for Europe (WISE).

3. Results and discussion

3.1. Meteorological data analysis

In the WYM, precipitation and actual evapotranspiration are related to the spatial distribution of meteorological factors and land cover types [39]. To study the meteorological outcomes, we started performing an exploratory data analysis of the precipitation data based on their relationship to some critical output values.

The boxplots in **Fig 2**, show the annual average precipitation by river basin district (RBD). The value is maximum (1850 mm) in the RBD (PTRH1) located in the northwest coast of the country, where the high elevation in the coastal zones contributes to the development of convective systems that promote the occurrence of precipitation events [27]. The minimum value (less than 500 mm) is

in the PTRH8 district in the south of Portugal, where are located the most vulnerable regions to drought events, being observed the lowest precipitation indices and the highest temperatures [31].

Fig 2. Boxplots: Annual average precipitation by river basin district (mm).

This exploratory analysis is suggesting two main patterns, one with the highest precipitation indices and other with the lowest. Through a spatially exploratory analysis in a GIS environment, the study area could be divided into two sectors, following the concept that Portugal is divided between North and South by the Tagus river that cuts the territory East to West [55].

The north of the country (NPT) is representing 40.62% of the total study area, including the RBDs: PTRH1, PTRH2, PTRH3, PTRH4; and the other sector (SPT – South of Portugal) is representing 59.38% and includes the following river basin districts: PTRH5, PTRH6, PTRH7, PTRH8.

Fig 3 is showing plots of the annual average precipitation (P1 – WorldClim; P2 – SNIRH) in the study years (1990, 2000, 2006, 2012 and 2018), by these 2 sectors, P1, P2 for NPT (North of Portugal) and P1, P2 for SPT (South of Portugal).

Fig 3. Annual average precipitation (mm) by data source and sectors.

P1 – WorldClim; P2 – SNIRH; NPT – North of Portugal (PTRH1, PTRH2, PTRH3, PTRH4); SPT – South of Portugal (PTRH5, PTRH6, PTRH7, PTRH8).

The precipitation data from SNIRH (P2) shows a continuous decreasing of the values over the years, while the data from WordClim (P1) shows high variability. Pearson's correlation between P1 and P2 in the NPT sector is equal to -0.409, in the SPT sector is -0.754. The spatial variability from North to South of Portugal is explained by the latitude and topographic configuration that influence the rain events and their temporal distribution [27]. As referred by [26], the years 1990 and 2012 are identified as being particularly dry within the Iberian Peninsula territory recording severe drought events.

3.2. Dryness Index & Evaporative Index outcomes

The Budyko curve relates to the Dryness Index (DI) and the evaporative index (EI). Together, these indexes define the energy limit and the water limit of a hydrologic system. The DI is also applied to derive climate classifications for different zones: Hyper-arid ($DI > 20$), Arid ($5 < DI \leq 20$), Semiarid ($2 < DI \leq 5$), Dry sub-humid ($1.5 < DI \leq 2$) and Humid ($DI < 1.5$) [56]. The EI values close to 1 mean that almost all amount of rain is returning to the atmosphere by evapotranspiration from the vegetation and soil, and the lowest values indicate higher water yield capacity.

The University of Leuven, with support of the International Water Management Institute and the International Centre for Integrated Mountain Development [42] estimated for mainland Portugal an area of 46365 km² that is highly vulnerable to drought events and is classified as an arid zone. This area represents 50.36% of the country's extent, which is comparable with the sector (SPT – South of Portugal) that represents 59.38%.

The mean difference between the global reference evapotranspiration (E1) and that obtained from the national database (E2) is nearly -10%. E1 shows a standard deviation equal to 31 mm against 2.5 mm in E2, these values were obtained comparing datasets from years (1990, 2000, 2006, 2012 and 2018). The following boxplots are representing the DI (**Fig 4**) & EI (**Fig 5**) results by RBD. It

is showing the same pattern occurred with the precipitation data permitting to group the national river basin districts in two sectors, NPT – North of Portugal (PTRH1, PTRH2, PTRH3, PTRH4) and SPT – South of Portugal (PTRH5, PTRH6, PTRH7, PTRH8).

Fig 4. Boxplots: Dryness indexes by RBD.

Fig 5. Boxplots: Evaporative indexes by RBD.

The highest DI & EI values are in the SPT sector. These values are showing the high vulnerability of this sector to severe drought events. The EI values classify SPT sector in Dry sub-humid and Semiarid zone and the NPT sector as Humid/Dry sub-humid zone as proposed by the Global Map Aridity [42].

The Budyko curve is bounded by two limits – an energy limit in which actual evapotranspiration (AET) is equal to the potential evapotranspiration, and a water limit for which actual evapotranspiration is equal to precipitation [38]. Due to spatial and temporal variability in climate forcing, the asynchronicity of water availability (P) and demand (PET), the imperfect capacity of the root zone to buffer that asynchronicity, and lateral redistribution of water within the catchment, the Budyko curve lies below those two limits [24]. To understand the concept and to verify the WYM, a Budyko curve graphic with DI & EI outcomes is plotted in Fig 6. It shows results of the sensitivity analysis simulations for tests T3 (E1) and T4 (E2).

Fig 6. Budyko curve by sensitivity analysis tests.

P1 – WorClim; P2 – SNIRH; T3 – E1; T4 – E2; Green Cluster: NPT (PTRH1, PTRH2, PTRH3, PTRH4); Yellow Cluster: SPT (PTRH5, PTRH6, PTRH7, PTRH8).

Examining the Budyko curve with mean values of DI and EI of the five studied years, we can distinguish two main clusters referring to these two sectors, NPT (North of Portugal) and SPT (South of Portugal). As water yield is greater in those points close to zero, the cluster formed by points from the NPT sector show better water availability, with the greatest value in the simulation T3 using P1 and E1, and for the SPT sector, with test T4 using P2 and E2.

3.3. Corine LULC changes

The change in land use can influence the integrity of natural systems [8] and the WYM is assessing the impacts of land cover changes in each pixel cell offering insights into how changes in land-use patterns affect annual surface water yield [38]. The five main categories of the Corine land cover datasets are artificial surfaces (1), agricultural areas (2), forest and semi-natural areas (3), wetlands (4) and water bodies (5).

Analyzing the land cover changes in national scale (LULC_PT) in the five main Corine Land Cover categories between 1990 and 2018, the numbers show that artificial areas have increased more than 100%, followed by surface water bodies and wetlands, with 34% and 7%, respectively. Agricultural, and forest and semi-natural areas have decreased by 2% and 3%, respectively. The studied categories followed the same pattern in the NPT and SPT sectors (LULC_NPT; LULC_SPT).

Fig 7 shows the evolution (CLC_Evolution) and variation (Var_18_90) for the main land use/land cover categories of Corine data (1-Artificial surfaces, 2-Agricultural area, 3-Forest and seminatural

areas, 4-wetlands, 5-water bodies). Each red dot is referring to values estimated for the studied years (1990, 2000, 2006, 2012, and 2018). The variable Var_18_90 is the variation between years 1990 and 2018.

Fig 7. Tables showing Corine Land Cover evolution (CLC_Evolution) and variation (Var_18_90) for the main land use/land cover categories.

1-Artificial surfaces, 2-Agricultural area, 3-Forest and seminatural areas, 4-wetlands, 5-water bodies. Each red dot is referring to values estimated for the studied years (1990, 2000, 2006, 2012, and 2018). LULC (Land Use/Land Cover), NPT (North of Portugal), SPT (South of Portugal), PT (mainland Portugal).

At the national scale, as the number of artificial areas increased the number of superficial water bodies also increased, showing a Person's correlation equal to 0.897. The inverse situation is observed when comparing artificial areas with agricultural and forest areas, showing a Person's correlation equal to -0.702 and -0.661, respectively.

The growing of the artificial areas demands an effort of the water-related ecosystems services. To respond to that, in the last 18 years, many dams have been constructed, to satisfy water supply, agriculture irrigation, industry and to deal with water scarcity in the most vulnerable regions. The Alqueva dam, located in the SPT sector is the largest superficial water body in Europe [35], and it started being operational in 2002 in the Guadiana River.

3.4. Sensitivity analysis

Sensitivity analysis provides a logical and verifiable method of optimizing the distribution of resources used to determine the most important parameters [18]. Considering the spatial pattern established by the meteorological outcomes, this step began investigating the sensitivity of the WYM outcomes by sectors NPT (North of Portugal) and SPT (South of Portugal). We assessed and compared the model's performance over sensible ranges to determine the effect of these variations. Fig 8 shows water yield result of each test by RBD for NPT sector. The year 2006 has only 8 estimated WY values because Z1 was equal to Z2.

Fig 8. Sensitivity analysis tests by river basin district (RBD) of the North of Portugal.

In the NPT sector, 91% of the simulations show a Person's correlation of more than 0.85, against 0.58 in the SPT sector (Fig 9). The lowest correlation observed on both sectors was 0.6. The NPT sector shows sensitivity to all the tests throughout the studied years. The SPT sector shows high sensitivity, especially in the years 1990, 2012 and 2018. In most of the tests, when using the largest value to Z (Z2), the results are slightly higher when compared to Z1. The PTRH5A shows the lowest variations between tests.

Fig 9. Sensitivity analysis tests by river basin district (RBD) of the South of Portugal.

The RBDs in the SPT sector show higher sensitivity to the alternative PAWC (T1 and T2). In both sectors, the model shows higher sensitivity to the tests in the years 1990 and 2012, where is known that the annual precipitation was lower due to the drought events occurred in those years, as referred in the literature [26]. The storage capacities provided by reservoirs and lakes drive the

possibility for water to be spared between periods with recharge (high precipitation indices) and periods of consumption [57]. Catchments with high resistance can store water over long periods (months or years) and release water gradually to the stream [13] that can also affect the results.

The highest sensitivity in the PTRH7 is observed when running the model with an alternative PAWC (T1, T2) and alternative biophysical table (T1). Those extremes values have occurred because in this RBD exists the largest superficial water body in Europe, the Alqueva dam [31], and the PAWC in those pixels had a maximum possible value which is 0.98. The reservoir behaves as a “tank” receiving water from rainfall on the surface and inlets or returns and exporting water through evaporation, infiltration, losses, withdrawals and outlets [57].

3.5. Model validation

The most convincing evidence that a scientific theory or model is correct is through direct comparison of model predictions with experimental observations [18]. The EEA’s Waterbase [35] contains the volume of freshwater resources by RBD for 2018, that will be compared with the best simulations for the same year. Fig 10 presents the estimated volume of water yield in 2018 by RBD of the North of Portugal and the observed volumes (WISE18). The best performance simulation in this year was Z2P2T4 which is marked in the legend of the image.

Fig 10. Estimated WY volume (m3) in 2018 by RBD/NPT sector and observed values.

In the SPT sector (Fig 11) the best simulation was considering the test Z1P1T4. The differences between these two tests are on the number of rain days considered, and the source of the precipitation data.

Fig 11. Estimated WY volume (m3) in 2018 by RBD/SPT sector and observed values.

After calibrating the model by sectors with the best simulation performance in 2018, the mean volume of the estimated water yield by RBD was compared with the freshwater resources availability volume, published by [35]. Results at the national level show a correlation coefficient of 0.803 with statistical significance for 0.01 one-tail. Table 3 has the values used to estimate model’s accuracy.

Table 3. Mean estimated WY, observed values and the error in the estimations.

Sector	NPT					SPT		
Best performance/sector	Z2P2T4					Z1P1T4		
RBD	PTRH1	PTRH2	PTRH3	PTRH4A	PTRH5A	PTRH6	PTRH7	PTRH8
area (ha)	246500	358400	1921900	1698100	2566500	1214900	1161100	551100
WY_Est_2018 (m ³ /ha)	4746	2037	159	224	31	468	449	2323
WY_Obs_2018 (m ³ /ha)	4851	2280	492	1801	-176	1455	-1368	1033
error/RBD (m ³ /ha)	-105	-243	-333	-1577	207	-988	1817	1290
Mean error/sector	-56.5 mm/year					58.1 mm/year		

WY_Est_2018 (mean estimated WY); WY_Obs_2018 (mean observed WY - WISE WaterBase).

442

443 The WY in the NPT sector was underestimated by 56.5 mm/year and the SPT sector was
444 overestimated by 58.1 mm/year. The difference in the estimations by sectors is explained by the
445 spatial and temporal variability of precipitation and the sensitivities of the model to the climatic
446 variables. Fig 12 shows the spatially assessment of the errors normalized by each sector. In the NPT
447 sector, aside of the RBD PTRH4A that has the maximum error, all others RBDs show minimum
448 normalized errors. In the SPT sector the maximum error was in the RBD PTRH7, medium errors in the
449 PTRH6 and PTRH8, and minimum normalized error in the PTRH5A.

450

451 **Fig 12. RBD error normalized by the mean error of each sector.**

452 The errors in the estimations can be explained by other variables that the is not taking in
453 account, such as surface runoff, losses or gains to groundwater systems, and storage dynamics.
454 Complex land use patterns or underlying geology may induce complex water balances as it is not
455 precisely captured by the model [38]. However, the InVEST WY model shows a good capability to
456 model water balance and water circulation through sub-surface porous media, and to analyse the
457 effects of meteorological pressures on water ecosystem conditions at RBD level.

458 4. Conclusions

459

460 Through the analytical examination of the sensitivity tests, this study contributes to a better
461 understanding of which input parameters affect most the model's behaviour. The sensitivity of the
462 WYM to the climatic variables was confirmed when comparing simulations with two different
463 climatic datasets, and its sensitivity to land cover changes was confirmed when running simulations
464 with the alternative PAWC. The drought events which occurred in mainland Portugal in the years
465 1990 and 2012, helped to understand the effects of the meteorological conditions in the freshwater
466 availability. Comparing the model's performance for the sensitivity tests, the WYM shows to be
467 reactive to changes in the Zhang values (number of rain days in a year), precipitation, and
468 evapotranspiration indices. The model has shown the highest sensitivities when extreme climate
469 conditions occurred.

470 Models' accuracy was verified calculating the correlation coefficient at the national level and
471 comparing the mean estimated water yield with mean observed values. Mean WY was
472 underestimated in the NPT sector, and overestimated in the SPT sector. The estimations would be
473 better if the model were calibrated and run separately for each RBD. Nevertheless, the model shows
474 correlation coefficient of 0.803 with statistical significance for 0.01 one-tail. The uncertainties that
475 exist in the model, such as the fact that the WYM is not considering surface water and groundwater
476 interactions and is not differentiating surface runoff and baseflow, combined with complex land-use
477 patterns, such as wetlands, or underlying geology, such as alluvial deposits, could explain the
478 difference between estimated values and observed values.

479 The comparison of the simulations' tests and the validation of the model were important to build
480 confidence in the models' outputs, to support studies related to the spatial estimation of water
481 availability at sub-watershed, watershed, or RBD, and to provide guidance for future research. Better
482 performance can be achieved considering multi-site calibration/validation and multi-parameters
483 checks, especially if spatially variability is observed, and complex land cover and geology are known.

484 5. References

485 1. Costanza R, d'Arge R, de Groot R, Farber S, Grasso M, Hannon B, et al. The value of the

- 486 world's ecosystem services and natural capital. *Nature*. 1997;387: 253–260.
- 487 2. IPBES. IPBES:Summary for policymakers of the global assessment report on biodiversity and
488 ecosystem services of the Intergovernmental Science-Policy Platform on Biodiversity and
489 Ecosystem Services. Bonn, Germany: IPBES secretariat; 2019.
490 doi:<https://doi.org/10.5281/zenodo.3553579>
- 491 3. Newbold T, Hudson LN, Hill SLL, Contu S, Lysenko I, Senior RA, et al. Global effects of land use
492 on local terrestrial biodiversity. *Nature*. 2015;520: 45–50. doi:10.1038/nature14324
- 493 4. Green PA, Vörösmarty CJ, Harrison I, Farrell T, Sáenz L, Fekete BM. Freshwater ecosystem
494 services supporting humans: Pivoting from water crisis to water solutions. *Glob Environ*
495 *Chang*. 2015;34: 108–118. doi:10.1016/j.gloenvcha.2015.06.007
- 496 5. Liqueste C, Maes J, Notte A, Bidoglio G. Securing water as a resource for society: An ecosystem
497 services perspective. *Ecohydrol Hydrobiol*. 2011;11: 247–259. doi:10.2478/v10104-011-0044-
498 1
- 499 6. World Bank. World Bank. [cited 15 Feb 2019]. Available:
500 <https://wits.worldbank.org/countrysnapshot/en/GHA>
- 501 7. Lundqvist J, Unver O. Alternative pathways to food security and nutrition - Water
502 predicaments and human behavior. *Water Policy*. 2018;20: 871–884.
503 doi:10.2166/wp.2018.171
- 504 8. Bassi AM, Gallagher LA, Helsing H. Green Economy Modelling of Ecosystem Services along
505 the “ Road to Dawei .” 2016; 1–21. doi:10.3390/environments3030019
- 506 9. The Global Risks Report 2018 13th Edition Insight Report. 2018.
- 507 10. Vogt J, Soille P, Jager A de., Rimavičiūtė E, Mehl W, Foisneau S, et al. A pan-European river
508 and catchment database. Publications Office; 2007.
- 509 11. Addams L. Charting Our Water Future: Economic frameworks to inform decision-making.
510 Water. 2009.
- 511 12. EEA. EEA Catchments and Rivers Network System ECRINS v1.1 - Rationales, building and
512 improving for widening uses to Water Accounts and WISE applications. 2012.
513 doi:10.2800/51667
- 514 13. Carey SK, Tetzlaff D, Seibert J, Soulsby C, Buttle J, Laudon H, et al. Inter-comparison of hydro-
515 climatic regimes across northern catchments: synchronicity , resistance and resilience.
516 2010;3602: 3591–3602. doi:10.1002/hyp.7880
- 517 14. Posner S, Verutes G, Koh I, Denu D, Ricketts T. Global use of ecosystem service models.
518 *Ecosyst Serv*. 2016;17: 131–141. doi:10.1016/j.ecoser.2015.12.003
- 519 15. Redhead JW, Stratford C, Sharps K, Jones L, Ziv G, Clarke D, et al. Empirical validation of the
520 InVEST water yield ecosystem service model at a national scale. *Sci Total Environ*. 2016;569–
521 570: 1418–1426. doi:10.1016/j.scitotenv.2016.06.227
- 522 16. Maes J, Fabrega N, Zulian G, Barbosa A, Vizcaino P, Ivits E, et al. Mapping and Assessment of
523 Ecosystems and their Services. 2016. doi:10.2779/351581

- 524 17. Sahle M, Saito O, Fürst C, Yeshitela K. Quantifying and mapping of water-related ecosystem
525 services for enhancing the security of the food-water-energy nexus in tropical data-sparse
526 catchment. *Sci Total Environ.* 2019;646: 573–586. doi:10.1016/j.scitotenv.2018.07.347
- 527 18. Mallants D, Bekele E, Schmid W, Miotlinski K. Human and environmental exposure
528 conceptualisation: Soil to shallow groundwater pathways. 2017.
- 529 19. Hamby DM. A Comparison of Sensitivity Analysis Techniques. *Health Phys.* 1995;68: 195–204.
530 doi:10.1097/00004032-199502000-00005
- 531 20. Leal F, Costa RF da S, Montevechi JAB, Almeida DA de, Marins FAS. A practical guide for
532 operational validation of discrete simulation models. *Pesqui Operacional.* 2011;31: 57–77.
533 doi:10.1590/S0101-74382011000100005
- 534 21. Hoyer R, Chang H. Assessment of freshwater ecosystem services in the tualatin and Yamhill
535 basins under climate change and urbanization. *Appl Geogr.* 2014;53: 402–416.
536 doi:10.1016/j.apgeog.2014.06.023
- 537 22. Sánchez-Canales M, López Benito A, Passuello A, Terrado M, Ziv G, Acuña V, et al. Sensitivity
538 analysis of ecosystem service valuation in a Mediterranean watershed. *Sci Total Environ.*
539 2012;440: 140–153. doi:10.1016/j.scitotenv.2012.07.071
- 540 23. Terrado M, Acuña V, Ennaanay D, Tallis H, Sabater S. Impact of climate extremes on
541 hydrological ecosystem services in a heavily humanized Mediterranean basin. *Ecol Indic.*
542 2014;37: 199–209. doi:10.1016/j.ecolind.2013.01.016
- 543 24. Hamel P, Guswa AJ. Uncertainty analysis of a spatially explicit annual water-balance model:
544 Case study of the Cape Fear basin, North Carolina. *Hydrol Earth Syst Sci.* 2015;19: 839–853.
545 doi:10.5194/hess-19-839-2015
- 546 25. Eurostat / Regions and Cities Illustrated (RCI). 2019. Retrieved December 12, 2020, from
547 <https://ec.europa.eu/eurostat/cache/RCI/#?vis=nuts1.population&lang=en>
- 548 26. de Lima MIP, Santo FE, Ramos AM, Trigo RM, Isabel de Lima MP, Espírito Santo F, et al.
549 Trends and correlations in annual extreme precipitation indices for mainland Portugal, 1941–
550 2007. *Theor Appl Climatol.* 2014;119: 55–75. doi:10.1007/s00704-013-1079-6
- 551 27. Belo-Pereira M, Dutra E, Viterbo P. Evaluation of global precipitation data sets over the
552 Iberian Peninsula. *J Geophys Res Atmos.* 2011;116: 1–16. doi:10.1029/2010JD015481
- 553 28. Oliveira MM, Novo ME, Lobo Ferreira JP. Models to predict the impact of the climate changes
554 on aquifer recharge. *IAHS-AISH Publ.* 2007; 103–110.
- 555 29. Miranda PMA, Coelho Fátima ES, Tomé AR, Valente MA, Carvalho A, Pires C, et al. 2 20 th
556 Century Portuguese Climate and Climate Scenarios. : 23–83.
- 557 30. UNEP. Hydropolitical Vulnerability and Resilience along International Waters. 2009.
- 558 31. Second River Basin Management Plans: Portugal - EUROPEAN COMMISSION. 2019.
- 559 32. Pereira HM, Domingos T, Vicente L. Portugal Millennium Ecosystem Assessment: State of the
560 Assessment Report. *Cent Biol Ambient Fac Ciências da Univ Lisboa.* 2004; 1–68.

- 561 33. Ramos TB, Horta A, Gonçalves MC, Pires FP, Duffy D, Martins JC. The INFOSOLO database as a
562 first step towards the development of a soil information system in Portugal. *Catena*.
563 2017;158: 390–412. doi:10.1016/j.catena.2017.07.020
- 564 34. Maes J, Liqueste C, Teller A, Erhard M, Paracchini ML, Barredo JI, et al. An indicator framework
565 for assessing ecosystem services in support of the EU Biodiversity Strategy to 2020. *Ecosyst*
566 *Serv.* 2016;17: 14–23. doi:10.1016/j.ecoser.2015.10.023
- 567 35. European Environment Agency. WISE Water Framework Directive Database — European
568 Environment Agency. 2020.
- 569 36. Pessacq N, Flaherty S, Brandizi L, Solman S, Pascual M. Getting water right: A case study in
570 water yield modelling based on precipitation data. *Sci Total Environ.* 2015;537: 225–234.
571 doi:10.1016/j.scitotenv.2015.07.148
- 572 37. Budyko MI. *Climate and Life*. Budyko MI, editor. New York Acad Press. 1974;18: 1–510.
- 573 38. Sharp et al. (2020). Annual Water Yield — InVEST 3.8.9.post10+ug.gf658986 documentation.
574 Retrieved November 8, 2020, from [http://releases.naturalcapitalproject.org/invest-](http://releases.naturalcapitalproject.org/invest-userguide/latest/reservoirhydropowerproduction.html#limitations-and-simplifications)
575 [userguide/latest/reservoirhydropowerproduction.html#limitations-and-simplifications](http://releases.naturalcapitalproject.org/invest-userguide/latest/reservoirhydropowerproduction.html#limitations-and-simplifications)
- 576 39. Xu J, Xiao Y, Xie G, Jiang Y. Ecosystem Service Flow Insights into Horizontal Ecological
577 Compensation Standards for Water Resource: A Case Study in Dongjiang Lake Basin, China.
578 *Chinese Geogr Sci.* 2019;29: 214–230. doi:10.1007/s11769-019-1025-3
- 579 40. Panagos P, Van Liedekerke M, Jones A, Montanarella L. European Soil Data Centre: Response
580 to European policy support and public data requirements. *Land use policy.* 2012;29: 329–338.
581 doi:10.1016/j.landusepol.2011.07.003
- 582 41. Fick SE, Hijmans RJ. WorldClim 2: new 1-km spatial resolution climate surfaces for global land
583 areas. *Int J Climatol.* 2017;37: 4302–4315. doi:10.1002/joc.5086
- 584 42. Trabucco A, Zomer RJ. Global Aridity Index and Potential Evapotranspiration (ET0) Climate
585 Database v2. CGIAR Consort Spat Inf. 2018; 10. doi:10.6084/m9.figshare.7504448.v3
- 586 43. SNIRH. (2020). SNIRH: Sistema Nacional de Informação de Recursos Hídricos. Retrieved
587 November 15, 2020, from <https://snirh.apambiente.pt/>
- 588 44. CGLS. (2020). Copernicus Global Land Service. Retrieved November 15, 2020, from
589 <https://land.copernicus.eu/global/>
- 590 45. Allen RG, Pereira LS, Raes D, Smith M, Ab W. Fao,1998. Irrig Drain Pap No 56, FAO. 1998; 300.
591 doi:10.1016/j.eja.2010.12.001
- 592 46. Cabral P, Feger CC, Levrel H, Chambolle MM, Basque D. Assessing the impact of land-cover
593 changes on ecosystem services: A first step toward integrative planning in Bordeaux, France.
594 *Ecosyst Serv.* 2016;22: 318–327. doi:10.1016/j.ecoser.2016.08.005
- 595 47. O’Geen AT. Soil Water Dynamics. *Nature Education Knowledge.* 2013 pp. 4–9.
- 596 48. Dalgliesh, N. and Foale, M. 1998. Soil matters: monitoring soil water and nutrients in dryland
597 farming. Toowoomba, Queensland, Agricultural Production Systems Research Unit.

598 49. CLIMATE CHANGE PORTAL. (2020). CLIMATE CHANGE PORTAL. Retrieved November 15, 2020,
599 from <http://portaldoclima.pt/en/>

600 50. Gomes S, Deus R, Nogueira M, Viterbo P, Miranda M, Antunes S, et al. The Portuguese
601 Climate Portal. *Geophys Res Abstr - EGU Gen Assem.* 2016;18: 16517.

602 51. IPMA. (2020). Portuguese Institute for Sea and Atmosphere. Retrieved November 15, 2020,
603 from <https://www.ipma.pt/en/produtoseservicos/index.jsp?page=dataset.pt02.xml>.

604 52. Cardinale BJ, Duffy JE, Gonzalez A, Hooper DU, Perrings C, Venail P, et al. Biodiversity loss and
605 its impact on humanity. 2012; 0–9. doi:10.1038/nature11148

606 53. Refsgaard JC. Parameterisation , calibration and validation of distributed hydrological models.
607 1997;198: 69–97.

608 54. Sargent RG. Validation and verification of simulation models. *Proceedings - Winter Simulation
609 Conference.* IEEE; 1992. pp. 104–114. doi:10.1145/167293.167311

610 55. Ferreira AMPJ. Caracterização de Portugal Continental. *Dados Geoquímicos Base Sedimentos
611 Fluviais Amostragem Baixa Densidade Port Cont Estud Factores Variação Reg.* 2000; 19–61.

612 56. Gunkel A, Lange J. Water scarcity, data scarcity and the Budyko curve—An application in the
613 Lower Jordan River Basin. *J Hydrol Reg Stud.* 2017;12: 136–149.
614 doi:10.1016/j.ejrh.2017.04.004

615 57. EUROPEAN COMMISSION - DIRECTORATE GENERAL ENVIRONMENT. Preparatory Action -
616 Development of Prevention Activities to halt desertification in Europe - Service Contract to
617 contribute to the building of Water and Ecosystem accounts at EU level Final Report 3. 2012.

618

619

RBDs

country,localId

ES,ES010; PT,PTRH1
ES,ES020; PT,PTRH3
ES,ES030; PT,PTRH5A
ES,ES040; PT,PTRH7
PT,PTRH2
PT,PTRH4A
PT,PTRH6
PT,PTRH8

Annual Average Precipitation (mm)

Budyko Curve

LULC_NPT	CLC Evolution	Var_18_90
1		118%
2		-2%
3		-3%
4		15%
5		26%

LULC_SPT		Var_18_90
1		86%
2		-2%
3		-3%
4		3%
5		36%

LULC_PT		Var_18_90
1		101%
2		-2%
3		-3%
4		7%
5		34%

Sensitivity Analysis – Tests
NPT (North of Portugal)

Sensitivity Analysis – Tests
SPT (South of Portugal)

WY

1990 2000 2006 2012 2018

—●— PTRH5A —●— PTRH6 —●— PTRH7 —●— PTRH8

WY volume (m³) by RBD/NPT – 2018

WY volume (m³) by RBD/SPT – 2018