Prediction of antibiotic resistant strains of bacteria from their beta-lactamases protein

**Lubna Maryam^{†1}, Anjali Dhall^{†1}, Sumeet Patiyal^{†1}, Salman Sadullah Usmani¹, Neelam
Sharma¹, and Gajendra Pal Singh Raghava^{*1}**

1. Department of Computational Biology, Indraprastha Institute of Information
Technology, Okhla Phase 3, New Delhi-110020, India.

Emails of Authors:

LM: lucymary20@gmail.com

AD: anjalid@iiitd.ac.in

SP: sumeetp@iiitd.ac.in

SSU: salman007usmani@gmail.com

NS: neelams@iiitd.ac.in

GPSR: raghava@iiitd.ac.in

[†]**These authors have contributed equally to this work.**

***Corresponding author**

Prof. G.P.S. Raghava,

Head of Department, Department of Computational Biology, Indraprastha Institute of
Information Technology, Okhla Phase 3, New Delhi-110020, India.

E-mail address: raghava@iiitd.ac.in

Phone No: +91-11-26907444

27 Abstract

28 Number of beta-lactamase variants have ability to deactivate ceftazidime antibiotic, which is
 29 the most commonly used antibiotic for treating infection by Gram-negative bacteria. In this
 30 study an attempt has been made to develop a method that can predict ceftazidime resistant
 31 strains of bacteria from amino acid sequence of beta-lactamases. We obtained beta-
 32 lactamases proteins from the β -lactamase database, corresponding to 87 ceftazidime-sensitive
 33 and 112 ceftazidime-resistant bacterial strains. All models developed in this study were
 34 trained, tested, and evaluated on a dataset of 199 beta-lactamases proteins. We generate 9149
 35 features for beta-lactamases using Pfeature and select relevant features using different
 36 algorithms in scikit-learn package. A wide range of machine learning techniques (like KNN,
 37 DT, RF, GNB, LR, SVC, XGB) has been used to develop prediction models. Our random
 38 forest-based model achieved maximum performance with AUROC of 0.80 on training dataset
 39 and 0.79 on the validation dataset. The study also revealed that ceftazidime-resistant beta-
 40 lactamases have amino acids with non-polar side chains in abundance. In contrast,
 41 ceftazidime-sensitive beta-lactamases have amino acids with polar side chains and charged
 42 entities in abundance. Finally, we developed a webserver “ABCRpred”, for the scientific
 43 community working in the era of antibiotic resistance to predict the antibiotic
 44 resistance/susceptibility of beta-lactamase protein sequences. The server is freely available at
 45 (<http://webs.iitd.edu.in/raghava/abcrpred/>).

46 **Keywords:** Antibiotic-resistance strains, Beta-lactamases, Ceftazidime antibiotic, Prediction
 47 method, Machine learning techniques

49 Key Points

- 50 • Ceftazidime is commonly used to treat infection caused by Gram-negative bacteria.
- 51 • Beta-lactamase is responsible for lysing ceftazidime, make it resistant to bacteria.
- 52 • Comparison of resistant and sensitive variants of beta-lactamase.
- 53 • Classification of sensitive and resistant strain of bacteria based on beta-lactamase.
- 54 • Prediction models have been developed using different machine learning techniques.

58

59

60

Author's Biography

61

1. Lubna Maryam is currently working as a Post-Doctoral Fellow in the Department of Computational Biology, Indraprastha Institute of Information Technology, New Delhi, India.

62

63

64

2. Anjali Dhall is currently working as a Ph.D. scholar in Bioinformatics from Department of Computational Biology, Indraprastha Institute of Information Technology, New Delhi, India.

65

66

67

3. Sumeet Patiyl is currently working as a Ph.D. scholar in Bioinformatics from Department of Computational Biology, Indraprastha Institute of Information Technology, New Delhi, India.

68

69

70

4. Salman Sadullah Usmani has completed his Ph.D. in Bioinformatics from CSIR-IMTECH, Chandigarh, India and is now working as Research Associate-I in the Department of Computational Biology, Indraprastha Institute of Information Technology, New Delhi, India.

71

72

73

5. Neelam Sharma is currently working as a Ph.D. scholar in Bioinformatics from Department of Computational Biology, Indraprastha Institute of Information Technology, New Delhi, India.

74

75

76

6. G.P.S. Raghava is currently working as Professor and Head of Department of Computational Biology, Indraprastha Institute of Information Technology, New Delhi, India.

77

78

79

80

81

82 Introduction

83 Antimicrobial resistance (AMR) is the ability of bacteria to resist the effect of antibiotics that
 84 are administered during infection (Figure 1). In 2020, WHO declared AMR as one of the
 85 world's top 10 public health threats. There is a number of reasons for drug resistance that
 86 include overuse of antibiotics and the emerging strain of bacteria. Moreover, the alarming
 87 spread of multi-drug resistant bacteria (MDR) continues to lurk our capability to treat
 88 common infections (e.g., sepsis, sexually transmitted infections, urinary tract infections,
 89 diarrhea). There are a number of mechanisms adopted by the bacteria to evade killing by
 90 antimicrobial molecules that include, production of antibiotic lysing enzymes (e.g., Beta-
 91 lactamases), lowering the permeability of cell membrane, and modification of the antibiotics
 92 binding site [1]. Beta-lactam antibiotics are the most prescribed antibiotics to fight broad
 93 spectrum infections, i.e., 65% of the total antibiotics in the market [2]. These antibiotics have
 94 four membered beta-lactam rings in their molecular structure, which are destroyed by beta-
 95 lactamases [3]. Thus, beta-lactamases are responsible for multi-drug resistance against beta-
 96 lactam antibiotics [4]. The number of beta-lactamases is continuously growing, around 7166
 97 beta-lactamases have been already identified [5]. There are only a few variants of beta-
 98 lactamases on which beta-lactam antibiotics are working (sensitive). Resistant beta-lactamase
 99 genes that are spread via diffusion of mobile genetic elements, spread of epidemic plasmids,
 100 dispersion of specific clones and horizontal gene transfer [6]. Therefore, there is an urgent
 101 need to develop prediction models that can discriminate antibiotics sensitive and resistant
 102 variants of beta-lactamases.

Figure 1: Pictorial representation of how antibiotic resistance occurs.

105

106 The standard technique to test the resistance and susceptibility of a strain to a particular
 107 antibiotic is the disc diffusion test. This method is reliable and reproducible, but it is time
 108 consuming and labour-intensive. Thus, there is a need to develop computational methods that
 109 can predict antibiotic resistant strains of bacteria. Due to advancements in the next-generation
 110 sequencing (NGS) technologies, it is in routine to sequence a gene or whole genome of
 111 bacteria or metagenome. Several repositories have been already developed to maintain the
 112 information regarding the genes, mutations, genomes and metagenomes of bacterial strains
 113 [7]. This information has been used to develop methods for predicting drug resistant strains
 114 of bacteria. These methods are mainly based on identification of antibiotic resistant gene,
 115 mutation, whole genome and metagenome [8–11]. Almost all the existing tools are generic in
 116 nature, where these methods predict whether a bacterial strain is resistant to all antibiotics. In
 117 other words, these methods predict multi-antibiotics resistant bacteria. In the past, a large
 118 number of antibiotics have been discovered to kill bacteria by a different mechanism. It is
 119 possible that bacterial strain is only resistant to a particular antibiotic or class of antibiotics
 120 but sensitive to other class of antibiotics. Thus, it is important to develop a method that can
 121 predict antibiotic-specific sensitive or resistant bacterial strains; similar to personalized
 122 medicine [12–14]. This is very important to manage treatment of bacterial infection using a
 123 particular antibiotic which is sensitive to bacteria responsible for a given infection. In simple
 124 worlds there is need to treat a bacterial infection using strain-specific antibiotics which is
 125 similar to personalize drugs. Best of our knowledge, there is no computational tool that can
 126 predict whether a bacterial strain is sensitive or resistant to a antibiotics. In this study, we first
 127 time made an attempt to develop method for antibiotic ceftazidime that belongs to beta-
 128 lactam group. We selected ceftazidime because it is routinely used for treatment of wide
 129 range of bacterial infections like meningitis, sepsis, joint infection, urinary tract infection. In
 130 addition, ceftazidime has been tested clinically on a number of bacterial strains where MIC
 131 have been determined. In order to identify sensitive and resistant strain from MIC values,
 132 European Committee on Antimicrobial Susceptibility Testing (2020) proposed that the
 133 Enterobacterales are susceptible to ceftazidime when its concentration is less than or equal to
 134 1 mg/ml and resistant when concentration is greater than 4 mg/ml. It is well known fact that
 135 beta-lactamases are responsible for lysing ceftazidime or causing resistance. Thus, we have
 136 designed a model for predicting beta-lactamase variants that make ceftazidime sensitive or
 137 resistant to a bacterial strain. We used state of the arts techniques mainly based on machine
 138 learning techniques to develop prediction models [15]. This will help in predicting

ceftazidime resistance/susceptibility towards beta-lactamase carrying bacterial species that could emerge in the near future. The platform will provide vista to find out the beta-lactamases strains which are sensitive to ceftazidime antibiotic.

Methods and Material

Dataset Collection

The main dataset was collected from the β -lactamases database [16]. It incorporates 2383 Minimum Inhibitory Concentration (MIC) values (in the presence and absence of beta-lactamase genes) of 980 beta-lactamases (with their protein sequences) with different antibiotics and the fold change in MIC values [16]. The database comprises experimentally validated 21 different types of antibiotics corresponding to class-A, B, C, D beta-lactamase proteins. In this study, we have considered the ceftazidime antibiotic dataset with different β -lactamase protein sequences. Our final dataset included 199 β -lactamase protein sequences. Further, we set a cutoff on MIC values of ceftazidime with β -lactamase proteins. The proteins having (MIC value ≤ 4) were considered as antibiotic susceptible/sensitive proteins, and proteins having (MIC value > 4) were taken as antibiotic resistant ones [17,18]. Finally, we got 87 antibiotic-sensitive and 112 antibiotic-resistant unique proteins, referred to as positive and negative dataset, respectively. Moreover, we have also collected 22 ceftazidime resistance beta-lactamase protein sequences from Resistance Gene Identifier (RGI) database for external validation [19].

Generation of Features

To generate a wide range of features from protein sequences, we have used Pfeature [20]. In this study, we have used the standalone package of the Pfeature tool to compute thousands of protein/peptide features. This tool also calculates the structural and functional properties of protein sequences. We have generated 9149 composition-based features/descriptors using the composition-based feature module of the Pfeature package. It incorporates 15 different type of descriptors such as Amino acid composition (AAC), Dipeptide composition (DPC), Tripeptide composition (TPC), Atomic and bond composition (ABC), Residue repeat Information (RRI), Distance distribution of residue (DDOR), Shannon-entropy of protein (SE), Shannon entropy of all amino acids (SER), Shannon entropy of physicochemical property (SEP), Conjoint triad calculation of the descriptors (CTD), Composition-enhanced transition distribution (CeTD), Pseudo amino acid composition (PAAC), Amphiphilic pseudo

amino acid composition (APAAC), Quasi-sequence order (QSO) and Sequence order coupling number (SOCN).

Pre-processing and Feature selection

The biggest challenge is to find out the most important features/descriptors which can classify the two classes more accurately. The standardization or scaling of the dataset is the most common requirement for the machine learning techniques. In the current study, to standardize the dataset, we used MinMaxScaler using the sklearn pre-processing package. This scaling function converts the given values into a minimum and maximum range. After the pre-processing step, we identified the best set of features from a huge dimension vector. For determining the best features several dimension reduction methods are currently available. We have used standard feature selection methods in which firstly we removed all low variance features using the variance threshold method of the scikit-learn package [21]. It removes all zero-variance features, so we were left with 275 features. Then, we applied the SVC-L1 feature selection method for the selection of important set of features [21]. This method is based on the support vector classifier (SVC) with linear kernel, penalized with L1 regularization. SVC-L1 method was performed on earlier deduced 275 features which provided 33 features. Further we ranked the features based on their performance, using feature selector tool. We developed our final machine learning models on selected 10, 20, and 33 features.

Machine Learning

In the present study, we have implemented several machine learning techniques to classify ceftazidime antibiotic-resistant and sensitive/non-resistant proteins. We incorporated K-nearest neighbors (KNNs), Decision tree (DT), Random Forest (RF), Gaussian Naive Bayes (GNB), Logistic Regression (LR) and Support Vector Classifier (SVC) and XGBoost (XGB) classification methods in the study (ref). These techniques are based on different algorithm such as, KNN is a simple and supervised machine learning algorithm. It assumes the similarity between the new data and the available data and put the new data into the category that is most similar to the available categories [22]. DT is a tree-structured classifier based on non-parametric machine learning models, which uses a decision tree as a model to go from observations about a data to conclusions about new data. RF classification method uses ensemble-based techniques which uses several decision trees for the training and prediction of the outcome [23], GNB (Gaussian Naïve Bayes) are a group of supervised classification

algorithms based on Bayes theorem which uses probabilistic approach for the classification. LR is a statistical model that measures the relationship between the categorial dependent variable and one or more independent variable by guessing the likelihoods using a logistic function [24]. SVC get the best fit of the data provided, the features can then be fed to see what the predicted class is. XGB uses an iterative approach for the classification. It is a decision tree-based ensemble machine learning technique that uses an approach where new models are created that predict the errors of prior models and then added together to make the final prediction. All these techniques were executed using python-library scikit-learn [21].

Evaluation Techniques

In order to evaluate the classification models, we have used five-fold cross-validation (CV) and external validation method. For the training, testing, and evaluation, the dataset was divided into 80:20 ratio. We have used the standard criterion for the evaluation, in which 80% of the data was used for training and 20% was used for external validation [25]. In 5-fold CV, 80% of the data was divided into five equal portions/folds, one-fold was used for testing, and four folds was used for the training purpose. A similar process was repeated five times, in which each portion/fold was utilized for internal training and testing. Further, we checked the performance of machine learning models on external dataset. In this study we have used well established evaluation parameters [26]. It incorporates threshold-dependent and independent parameters. We measured threshold-dependent parameters like sensitivity (Sens), Specificity (Spec), Accuracy (Acc) and Matthews correlation coefficient (MCC) with the help of following equations. The standard threshold-independent parameter is Area Under the Receiver Operating Characteristic (AUROC) curve [27–29] which was computed to estimate the performance of different modes.

$$Sensitivity = \frac{TP}{TP+FN} \times 100 \dots\dots\dots (1)$$

$$Specificity = \frac{TN}{TN+FP} \times 100 \dots\dots\dots (2)$$

$$Accuracy = \frac{TP+TN}{TP+FN+FP+TN} \times 100 \dots\dots\dots (3)$$

$$Matthews Correlation Coefficient = \frac{(TN \times TP) - (FN \times FP)}{\sqrt{[(FP+TP)(FN+TP)(FP+TN)(FN+TN)]}} \times 100 \dots\dots\dots (4)$$

The measurements obtained from the above parameters are expressed in terms of TP=True Positive, FP=False Positive, TN=True Negative, FN=False Negative.

233

234 Results

235 We have used 87 beta-lactamases proteins that are ceftazidime sensitive, having MIC values
236 less than or equal to 4 and 112 ceftazidime resistant beta-lactamase protein sequences with
237 MIC values greater than 4. All analysis and model development have been done on the above
238 dataset.

239 Analysis based on the amino acid composition

240 We have analyzed the average amino acid composition for each residue for ceftazidime
241 resistant and sensitive beta-lactamase sequences and found out that residues such as A, G, L,
242 P, and R, is higher in ceftazidime resistant beta-lactamase sequences as compared to sensitive
243 sequences. Whereas, in the case of ceftazidime sensitive sequences, D, I, K, N, T, and Y
244 residues are higher, as shown in Figure 2.

245

246

247 Figure 2: Average amino acid composition of each amino acid residues for ceftazidime-resistant and
248 ceftazidime-sensitive beta-lactamases.

249

250 Predictions based on machine-learning models

251 We have implemented various machine learning classifiers such as KNN, DT, RF, GNB, LR,
252 SVC and XGB to develop the prediction model to classify the sequences of ceftazidime
253 resistant and sensitive beta-lactamases. We have calculated each protein sequence's features
254 using the composition-based module of Pfeature, which resulted in 9149 features. On
255 applying the feature selection method using the support vector classifier with L1
256 regularization, we were left with 33 most relevant features. We have ranked these 33 features
257 using feature selector python package and generated prediction models for the top 10, 20, and

33 features. For top 10 features, RF has obtained balanced results with AUROC of 0.78 with MCC of 0.44 for training dataset, whereas AUROC and MCC for the validation dataset are 0.76 and 0.49, respectively. Performance for all the implemented classifier is exhibited in Table 2. To understand the difference between the positive and negative datasets, we calculated the average values of the top-10 features of ceftazidime-sensitive and ceftazidime-resistant beta-lactamases as represented in Table 1.

Table 1: Brief description of top 10 features and their average values in ceftazidime-sensitive and ceftazidime-resistant beta-lactamases.

Name of features	Description of features	#Average Value-1	#Average Value-2
total_bonds	Bond composition of peptide	4980.345	5353.161
hydrogen_bonds	Bond composition of peptide	2747.425	2958.643
single_bond	Bond composition of peptide	4544.747	4890.884
R_ddor	Distance distribution of Arginine	47.46805	36.44679
Y_ddor	Distance distribution of Tyrosine	55.61483	69.62223
Grantham_gap1	Quasi sequence order of peptide	9422.904	9228.332
Grantham_gap3	Quasi sequence order of peptide	9815.743	9486.559
CeTD_33_SA	Number of transitions taking place from group 1 residues to group 2 residues for solvent accessibility attribute	65.29885	53.53571
CeTD_22_PC	Number of transitions taking place from group 2 residues to group 2 residues for polarizability attribute	66.2069	55.08036
CeTD_33_PO	Number of transitions taking place from group 3 residues to group 3 residues for polarity attribute	67.4023	53.71429

#Average Value-1: average values of ceftazidime-resistance beta-lactamases; # Average Value-2: average values of ceftazidime-sensitive beta-lactamases.

Table 2: Performance of various classifiers using top 10 features.

Classifier	Training Dataset	Validation dataset
------------	------------------	--------------------

	Sens	Spec	Acc	AUROC	MCC	Sens	Spec	Acc	AUROC	MCC
KNN	83.33	67.21	76.26	0.83	0.51	76.47	57.69	68.33	0.72	0.35
DT	60.26	72.13	65.47	0.72	0.32	76.47	65.38	71.67	0.72	0.42
RF	76.92	67.21	72.66	0.78	0.44	76.47	73.08	75.00	0.76	0.49
GNB	55.13	77.05	64.75	0.71	0.32	23.53	80.77	48.33	0.64	0.05
LR	69.23	68.85	69.06	0.73	0.38	61.76	65.38	63.33	0.67	0.27
SVC	76.92	78.69	77.70	0.78	0.55	70.59	73.08	71.67	0.74	0.43
XGB	78.21	65.57	72.66	0.75	0.44	76.47	65.38	71.67	0.78	0.42

Sens: Sensitivity; Spec: Specificity; Acc: Accuracy; AUROC: Area Under Receiver Operating Curve; MCC: Matthews Correlation Coefficient

Similarly, RF model developed using top 20 features performed best among all the classifiers, with AUROC of 0.79 and MCC of 0.48 on training dataset, and AUROC 0.76 and MCC 0.4 on validation dataset. Performance using other classifiers is given in Table 3.

Table 3: Performance of various classifiers using top 20 features.

Classifier	Training Dataset					Validation dataset				
	Sens	Spec	Acc	AUROC	MCC	Sens	Spec	Acc	AUROC	MCC
KNN	78.21	68.85	74.10	0.82	0.47	73.53	57.69	66.67	0.71	0.32
DT	61.54	62.30	61.87	0.67	0.24	70.59	61.54	66.67	0.68	0.32
RF	74.36	73.77	74.10	0.79	0.48	67.65	73.08	70.00	0.76	0.40
GNB	53.85	77.05	64.03	0.70	0.31	29.41	73.08	48.33	0.63	0.03
LR	70.51	70.49	70.50	0.77	0.41	76.47	65.38	71.67	0.69	0.42
SVC	56.41	85.25	69.06	0.75	0.43	64.71	84.62	73.33	0.74	0.49
XGB	75.64	63.93	70.50	0.72	0.40	70.59	65.38	68.33	0.71	0.36

Sens: Sensitivity; Spec: Specificity; Acc: Accuracy; AUROC: Area Under Receiver Operating Curve; MCC: Matthews Correlation Coefficient

For all 33 features, RF obtained the maximum AUROC of 0.80 with 0.48 MCC on the training dataset, and AUROC of 0.79 with MCC of 0.46 on the validation dataset. We have reported performance for all classifiers using 33 features in the Table 4.

Table 4: Performance of various classifiers using 33 selected features on training and validation datasets.

Classifier	Training Dataset					Validation dataset				
	Sens	Spec	Acc	AUROC	MCC	Sens	Spec	Acc	AUROC	MCC
KNN	74.36	77.05	75.54	0.81	0.51	73.53	57.69	66.67	0.74	0.32

DT	65.38	70.49	67.63	0.72	0.36	79.41	69.23	75.00	0.73	0.49
RF	74.35	73.77	74.10	0.80	0.48	73.53	73.08	73.33	0.79	0.46
GNB	56.41	72.13	63.31	0.67	0.29	29.41	73.08	48.33	0.64	0.03
LR	74.36	65.57	70.50	0.77	0.40	76.47	69.23	73.33	0.78	0.46
SVC	57.69	88.52	71.22	0.74	0.47	50.00	88.46	66.67	0.74	0.40
XGB	74.36	73.77	74.10	0.77	0.48	76.47	76.92	76.67	0.79	0.53

Sens: Sensitivity; Spec: Specificity; Acc: Accuracy; AUROC: Area Under Receiver Operating Curve; MCC: Matthews Correlation Coefficient

In order to check the robustness of our final model, we have downloaded 22 ceftazidime resistant protein sequences from Resistance Gene Identifier (RGI) database and checked the performance by implementing random forest based model developed on top 33 features. 19 out of 22 sequences were giving the correct result, with AUROC of 0.81 and MCC of 0.50 on training dataset, and AUROC 0.79 and MCC 0.71 on validation dataset.

Webserver implementation

We have developed a webserver named ABCRpred (<https://webs.iitd.edu.in/raghava/abcrpred/>) using Random Forest based machine learning approach to serve the scientific world. Since, we wanted to identify sensitive strains of beta-lactamases therefore we developed this method to discriminate between antibiotic resistant and sensitive variants of beta-lactamase strains. 87 antibiotic-sensitive and 112 antibiotic-resistant beta-lactamases protein sequences data were used for training and testing, while building the webserver. The complete architecture of ABCRpred is shown in figure 3.

Figure 3: Overall ABCRpred architecture that shows process of creating datasets, features selection, model development and process of model evaluation.

The ‘Predict’ page on the webserver has been developed to predict resistance/susceptibility of any new beta-lactamase protein sequence towards ceftazidime antibiotic. The page enables the users to enter the sequence in FASTA format or upload the file with multiple peptide sequences. User is required to set a random forest threshold and select physicochemical properties as per their requirement. Prediction of each sequence will be carried out according to the selected model. After submitting the input, the output file contains various columns of sequence ID, random forest score, prediction outcome whether the input sequence is resistant or susceptible and the result of selected physicochemical properties. The standalone package (<https://webs.iitd.edu.in/raghava/abcrpred/stand.php>) has also been incorporated in the webserver to let the users predict the resistance/susceptibility profile of protein sequences even in the absence of the internet. The standalone version incorporated our best models and can work on Linux or Unix operating systems.

Discussion

The beta-lactam antibiotics are regarded as the drug of choice for the treatment of severe infections caused by *Enterobacteriaceae*. Most of the beta-lactam antibiotics face resistance against beta-lactamases carrying bacteria. Moreover, exposure of beta-lactamase carrying bacterial strains to multitude of beta-lactams has induced active continuous production and mutation of beta-lactamases expanding their activity even against the newly developed beta-

lactam antibiotics. In this study we used MIC data of ceftazidime (a beta-lactam antibiotic) against beta-lactamase carrying bacteria for building a prediction model to predict resistance and susceptibility of any newly emerged variant of beta-lactamase carrying bacterial strain. A total of 199 experimental MIC data was collected from a comprehensive database of beta-lactamase enzymes called as β -lactamase Database [16]. Our data of ceftazidime MIC against various beta-lactamase carrying bacterial strains was divided into two sets. One set have MIC values greater than 4 referred to as ceftazidime-resistant strain; other set have MIC values less than or equal to 4 called as ceftazidime-sensitive strains. We obtained beta-lactamase corresponding to each strain; a beta-lactamase corresponding to resistant strain is called resistant beta-lactamase and a beta-lactamase corresponding to sensitive strain is called sensitive beta-lactamase. Our final dataset have sensitive and resistant variants of beta-lactamase.

Amino acid composition analysis revealed that certain residues like Alanine, Glycine, Leucine, Proline and Arginine are more frequent in ceftazidime resistant beta-lactamases as compared to ceftazidime sensitive ones. Similarly, in case of ceftazidime sensitive beta-lactamases the residues like Aspartic acid, Isoleucine, Lysine, Asparagine, Threonine and Tyrosine are more in abundance in comparison to resistant beta-lactamases. From these findings it can be inferred that in ceftazidime-resistant beta-lactamases, amino acids with non-polar side chains predominates. No wonder this gives these resistant beta-lactamases extra stability making it hard for ceftazidime to inhibit their activity. In case of ceftazidime-sensitive beta-lactamases, amino acids with polar side chains predominates. Moreover, amino acid with charged entities is more in number in this case. This makes these proteins quite unstable and prone to attack by the antibiotic.

In this study, Pfeature software has been used to compute different types of descriptors that includes amino acid composition, dipeptide composition, residue entropy, repeats, distribution of amino acids. In order to identify relevant features, we adopt different techniques to remove useless features or descriptors. All descriptors having low variance has been removed as they are not suitable for classification. Highly correlated or redundant has been removed to decrease the noise. Finally algorithms in Scikit-learn has been used for selecting important descriptors for developing prediction models. We employed different machine learning algorithms using python-library-scikit-learn. We implemented widely used machine learning classifiers, like KNN, DT, RF, GNB, LR, SVC and XGB [30]. In order to our models we used internal and external validations [31] [32]. The result of the generated

model was analysed using various parameters called as threshold-dependent parameters and threshold-independent parameters [33] [34]. We also validated the sturdiness of our model by cross checking the resistance of 22 ceftazidime resistance beta-lactamases downloaded from RGI database. Our model correctly predicted 19 ceftazidime resistance strains out of 22. We hold an opinion that this method will be very helpful in prior prediction of ceftazidime resistance/susceptibility towards any newly emerging strain of beta-lactamases. This also open vista for researchers to look for alternative therapeutic options to fight continuously emerging beta-lactamases. The method also has a major utility in doing prediction of sensitive beta-lactamase strains in metagenomics data.

Conclusion

In conclusion, this is the first study of resistance/sensitivity prediction model development using one particular antibiotic. The study brings about in-silico model to predict resistance/susceptibility of ceftazidime antibiotic towards beta-lactamases(<http://webs.iiitd.edu.in/raghava/abcrpred/>). This will help in identification of ceftazidime sensitive beta-lactamases strains. Prediction can be done even when only protein sequence of any beta-lactamase is known. We believe in future, researchers will build similar model for other antibiotics. Prior prediction of sensitive antibiotics against a bacterial infection will lead to era of strain-specific antibiotics; basically, end of present hit and trial era. This will reduce time and cost of treatment as well a significant reduction in side-effects due to the treatment by inappropriate antibiotics.

Conflict of Interest

The authors declare no competing financial and non-financial interests.

Author Contributions

LM, SSU, AD, and SP collected and processed the datasets. LM, AD, SP, SSU and GPSR implemented the algorithms. SP and AD developed the prediction models. LM, AD, SP, SSU and GPSR analysed the results. SP, NS and AD created the back-end of the web server and front-end user interface. LM, AD, SP, SSU, NS and GPSR penned the manuscript. GPSR conceived and coordinated the project and gave overall supervision to the project. All authors have read and approved the final manuscript.

Acknowledgement

Authors are thankful to J.C. Bose National Fellowship, Department of Science and Technology (DST), Government of India, and DST-INSPIRE, NPDF-SERB, and DBT for fellowships and the financial support.

Data Availability Statement

All the datasets generated for this study are either included in this article/Supplementary material or available at the “ABCRpred” webserver, <https://webs.iiitd.edu.in/raghava/abcrpred/download.php> as mentioned in the Materials and Methods section.

References

1. Munita JM, Arias CA. Mechanisms of Antibiotic Resistance. *Microbiol. Spectr.* 2016; 4(2):481-511.
2. Thakuria B, Lahon K. The Beta Lactam Antibiotics as an Empirical Therapy in a Developing Country: An Update on Their Current Status and Recommendations to Counter the Resistance against Them. *J. Clin. Diagn. Res.* 2013; 7(6):1207–1214.
3. Tooke CL, Hinchliffe P, Bragginton EC, et al. beta-Lactamases and beta-Lactamase Inhibitors in the 21st Century. *J. Mol. Biol.* 2019; 431(18):3472–3500.
4. Bush K. Past and Present Perspectives on beta-Lactamases. *Antimicrob. Agents Chemother.* 2018; 62(10).
5. Naas T, Oueslati S, Bonnin RA, et al. Beta-lactamase database (BLDB) - structure and function. *J. Enzyme Inhib. Med. Chem.* 2017; 32(1):917–919.
6. Canton R, Novais A, Valverde A, et al. Prevalence and spread of extended-spectrum beta-lactamase-producing Enterobacteriaceae in Europe. *Clin. Microbiol. Infect.* 2008; 14:144–153.
7. Maryam L, Usmani SS, Raghava GPS. Computational resources in the management of antibiotic resistance: Speeding up drug discovery. *Drug Discov. Today* 2021.
8. Aytan-Aktug D, Clausen PTLC, Bortolaia V, et al. Prediction of Acquired Antimicrobial Resistance for Multiple Bacterial Species Using Neural Networks. *mSystems* 2020; 5(1).
9. Ransom EM, Potter RF, Dantas G, et al. Genomic Prediction of Antimicrobial Resistance: Ready or Not, Here It Comes! *Clin. Chem.* 2020; 66(10):1278–1289.
10. Kim J, Greenberg DE, Pifer R, et al. VAMPr: VARIant Mapping and Prediction of antibiotic resistance via explainable features and machine learning. *PLoS Comput. Biol.* 2020; 16(1):e1007511.
11. Nguyen M, Olson R, Shukla M, et al. Predicting antimicrobial resistance using conserved genes. *PLoS Comput. Biol.* 2020; 16(10):e1008319.
12. Gupta S, Chaudhary K, Kumar R, et al. Prioritization of anticancer drugs against a cancer using genomic features of cancer cells: A step towards personalized medicine. *Sci. Rep.* 2016; 6(1):1-11.

- 423 13. Dhanda SK, Vir P, Singla D, et al. A Web-Based Platform for Designing Vaccines against
424 Existing and Emerging Strains of Mycobacterium tuberculosis. *PLoS One* 2016; 11(4):e0153771
- 425 14. Gupta S, Chaudhary K, Dhanda SK, et al. A Platform for Designing Genome-Based Personalized
426 Immunotherapy or Vaccine against Cancer. *PLoS One* 2016; 11(11):e0166372.
- 427 15. Jamal S, Khubaib M, Gangwar R, et al. Artificial Intelligence and Machine learning based
428 prediction of resistant and susceptible mutations in Mycobacterium tuberculosis. *Sci. Rep.* 2020;
429 10(1):1-16.
- 430 16. Keshri V, Diene SM, Estienne A, et al. An Integrative Database of beta-Lactamase Enzymes:
431 Sequences, Structures, Functions, and Phylogenetic Trees. *Antimicrob. Agents Chemother.* 2019;
432 63(5).
- 433 17. Forest Laboratories, LLC, at 1-800-678-1605 or FDA at 1-800-FDA-1088 or
434 www.fda.gov/medwatch. Revised: 02/2015.
- 435 18. European Committee On Antimicrobial Susceptibility Testing Breakpoint Tables For
436 Interpretation Of Mics And Zone Diameters Version 10.0, valid from 2020-01-01.
- 437 19. Alcock BP, Raphenya AR, Lau TTY, et al. CARD 2020: Antibiotic Resistome Surveillance with
438 the Comprehensive Antibiotic Resistance Database. *Nucleic Acids Res.* 2020; 48(D1):D517–D525.
- 439 20. Pande A, Patiyal S, Lathwal A, et al. Computing wide range of protein/peptide features from their
440 sequence and structure. *bioRxiv* 2019;599126.
- 441 21. Pedregosa F, Varoquaux G, Gramfort A, et al. Scikit-learn: Machine Learning in Python. *J. Mach.*
442 *Learn. Res.* 2011; 12:2825–2830.
- 443 22. Hussain HM, Benkrid K, Seker H. Dynamic partial reconfiguration implementation of the
444 SVM/KNN multi- classifier on FPGA for bioinformatics application. *Annu. Int. Conf. IEEE Eng.*
445 *Med. Biol. Soc. IEEE Eng. Med. Biol. Soc. Annu. Int. Conf.* 2015; 2015:7667–7670.
- 446 23. Mushtaq M-S, Mellouk A. 2 - Methodologies for Subjective Video Streaming QoE Assessment.
447 *Quality of Experience Paradigm in Multimedia Services*, 27–57.
- 448 24. Tolles J, Meurer WJ. Logistic Regression: Relating Patient Characteristics to Outcomes. *JAMA*
449 2016; 316(5):533–534.
- 450 25. Agrawal P, Bhalla S, Chaudhary K, et al. In Silico Approach for Prediction of Antifungal
451 Peptides. *Front. Microbiol.* 2018; 9:323.
- 452 26. Dhall A, Patiyal S, Sharma N, et al. Computer-aided prediction and design of IL-6 inducing
453 peptides: IL-6 plays a crucial role in COVID-19. *Brief. Bioinform.* 2021; 22(2):936–945.
- 454 27. Bhalla S, Kaur H, Dhall A, et al. Prediction and Analysis of Skin Cancer Progression using
455 Genomics Profiles of Patients. *Sci. Rep.* 2019; 9(1):1-16.
- 456 28. Patiyal S, Agrawal P, Kumar V, et al. NAGbinder: An approach for identifying N-
457 acetylglucosamine interacting residues of a protein from its primary sequence. *Protein Sci.* 2020;
458 29(1):201–210.
- 459 29. Sharma N, Patiyal S, Dhall A, et al. AlgPred 2.0: an improved method for predicting allergenic
460 proteins and mapping of IgE epitopes. *Brief. Bioinform.* 2020.

- 461 30. Ivanescu AE, Li P, George B, et al. The importance of prediction model validation and assessment
462 in obesity and nutrition research. *Int. J. Obes. (Lond)*. 2016; 40(6):887–894.
- 463 31. Debray TPA, Vergouwe Y, Koffijberg H, et al. A new framework to enhance the interpretation of
464 external validation studies of clinical prediction models. *J. Clin. Epidemiol.* 2015; 68(3):279–289.
- 465 32. Nagpal G, Usmani SS, Dhanda SK, et al. Computer-aided designing of immunosuppressive
466 peptides based on IL-10 inducing potential. *Sci. Rep.* 2017; 7(1):1-10.
- 467 33. Kumar V, Agrawal P, Kumar R, et al. Prediction of cell-penetrating potential of modified peptides
468 containing natural and chemically modified residues. *Front. Microbiol.* 2018; 9:725.
- 469 34. Robin X, Turck N, Hainard A, et al. pROC: an open-source package for R and S+ to analyze and
470 compare ROC curves. *BMC Bioinformatics* 2011; 12(1):1-8.