Fully Convolutional Networks for pathophysiological Intracranial Pressure waveform classification

¹O. Vrabie, ²R. Faltermeyer, ²N.O. Schmidt, ²A. Brawanski and ¹E. W. Lang

¹CIML Group, Biophysics, University of Regensburg,
93040 Regensburg, Germany

²Department of Neurosurgery, University Hospital Regensburg,
93042 Regensburg, Germany

Email: *oleg.vrabie@ur.de*

Abstract

It is generally assumed that the analysis of intracranial pressure (ICP) waveforms could be used for the detection of multiple cerebral pathophysiologicals. A main obstacle for the analysis of ICP waveforms is given by the large variation of their generating signal, the arterial blood pressure (ABP). Using extended principal component analysis (PCA) we show that it is possible to distinguish between ICP waveforms generated by pathological ABP waveforms, e.g. in the case of a heart failure, without losing information about the state of the cerebral compliance. We also create a dataset for ICP pulse classification that can be used to train models to distinguish between an intact and diminished cerebral compliance, as a function of the ICP-generating ABP pulse. As a baseline for classification we build a fully convolutional network (FCN) that reaches high performance with relatively few data.

1 Introduction

The treatment of patients suffering from Traumatic Brain Injury (TBI) or sub-arachnoid hemorrhage (SAB) aims to avoid secondary brain injury by continuous monitoring of different physiological parameters like intracranial pressure (ICP) and arterial blood pressure (ABP). During treatment a main focus is placed on the assessment of the cerebral compliance which can be defined as the ability of the cerebral compartment to compensate for volume changes in terms of pressure. A diminished cerebral compliance caused by a severe brain swelling may lead to pronounced increase in ICP and subsequently to a life threatening reduction of the cerebral perfusion.

From a time series analysis point of view a diminished cerebral compliance should be detectable by means of specific patterns occurring in the ICP recording during an episode of severe brain swelling. A common method to identify such patterns is the examination of individual ICP waveforms. ICP waveforms are intracranial pressure waves that are generated by the ABP pulse waves running through the cerebral vessels and are strongly influenced by the state of the cerebral compartment. However evaluating ICP waveforms in real time by a human expert is a demanding task simply due to the mere amount of data.

In this regard considerable efforts have been spent to automatize both extraction and categorization tasks. One prominent example is the morphological clustering and analysis of intracranial pressure (MOCAIP) algorithm [9, 10]. The algorithm first identifies an individual ICP pulse wave and then computes a set of 24 so-called MOCAIP metrics to characterize this individual pulse. Among other things the metrics contain the height of the different peaks of such a pulse and the

43 distance between them. Subsequently the metrics are fed into a separate classi-
44 fier. However, the 24 manually picked metrics contain redundant information and
45 quickly become very time-consuming to be analyzed.

46 Contrary, some efforts are focused on leaving the entire feature extraction pro-
47 cedure to a non-biased "agent". An example of this paradigm is presented in [18]
48 where cerebrospinal fluid pulse pressure waveforms (CSFPPWs) are classified by
49 an artificial neural network (ANN). The authors defined four distinct morpholog-
50 ical classes of the cerebrospinal fluid (CSF) pulses ranging from normal to patho-
51 logical and subsequently labeled 486 CSFPPWs from 160 patients with different
52 neurosurgical conditions, to form the training set of the ANN. The normalized
53 waves were mapped onto an embedding vector of ten radial basis function coef-
54 ficients. This vector served as input for the ANN. After training the network, 60
55 new CSFPPWs were used to evaluate it's accuracy by comparing the performance
56 of the model with a human expert. They reached 88.3% classification concor-
57 dance, an unquestionably good result, considering that the model was exposed to
58 less than 500 examples.

59 The influence of human experts happens either at the feature definition and
60 selection phases, or during picking and labeling the training examples. Safely
61 excluding the human expert from the analysis can be an almost impossible task
62 but would help to bypass the above mentioned issues. It could be done in phases,
63 as was demonstrated in the automatic feature selection for the MOCAIP algorithm
64 [9], letting the model to find patterns on its own using, for example, an ANN-based
65 classifier like in Nucci *et al.* [18], or combining them towards a more generalizable
66 approach.

67 In this study we analyze the influence of diminished cerebral compliance on

the ICP waveform using a fully convolutional network (FCN). To minimize the influence of human expert knowledge on the classification task, we made use of a mathematical toolkit called Selected Correlation Analysis (SCA) that reliably detects episodes of diminished cerebral compliance by analyzing the coherence of low frequency components of ABP and ICP signals [7, 8, 19]. To identify morphological categories of waveforms for the above mentioned episodes we use principal component analysis (PCA) and several clustering methods. Additionally we determined the influence of the ABP waveform on the ICP wave form using a similar procedure. First we looked for three different types of ABP waveforms, described in the literature [6, 17], representing a healthy heart, a heart dysfunction and a severe sepsis that already influences the stiffness of the vessels. With a further cluster analysis we find that the above mentioned morphological categories of ICP waveforms can be additionally subdivided when accounting for the morphology of the associated ABP waveforms. ICP pulses could be separated by means of both the state of compliance and the type of the input ABP waveform. The FCN model was trained on the six-class dataset (two compliance states $\times$ three ABP waveform states) reaching a high accuracy on a hold-out test set. In addition to high classification accuracy, the use of an FCN allowed us to construct class activation maps (CAMs), which helped visualizing exclusive regions in the ICP pulses that determined the pulse classification.

2 Materials and Methods

2.1 Patients and data acquisition

The data was collected from a cohort consisting of seven patients suffering from TBI and Subarachnoid hemorrhage (SAH). The summary of patients' physiological variables is depicted in Table 1 (for more details see Table 1). The ICP time series were recorded continuously in the intensive care unite (ICU) using an intraparenchymal piezoelectric sensor, which was inserted into the brain tissue at a depth of around 2 *cm*. The ABP time series were simultaneously recorded at the radial artery. Both quantities were measured continuously with a sampling rate of 1 *kHz* [8, 13, 21].

Table 1: Mean and median of physiological variables

Parameter	Value	Range
N	7	
Gender (f/m)	3/4	43/57%
Age (mean)	51.3	36.3 – 65.4
Diagnosis (SAH/TBI)	5/2	71/29%
GCS at admission (median)	10	6 – 14
GOS at last follow up (median)	3	1 – 5

SAH Subarachnoid hemorrhage; *TBI* traumatic brain injury; *GCS* Glasgow coma scale; *GOS* Glasgow outcome scale.

The study was conducted in accordance with the ethical guidelines of the Institutional Review Board of the University of Regensburg. Informed consent was obtained from the patient's relatives and all study results were stored and analysed in an anonymized fashion.

2.2 Selected Correlation Analysis

The motivation for the development of the selected correlation analysis (SCA) comes from predictions of a mathematical model of cerebral perfusion and oxygen supply [3, 8]. Simulating the time evolution of ICP under the condition of a diminished cerebral compliance caused by a severe brain swelling, the model predicts two different states. In case of an intact cerebral autoregulation the diminished compliance leads to a negative correlation between the homeostatic components of the ABP and the ICP signal. In case of a disturbed autoregulation the diminished compliance leads to a positive correlation between the above mentioned signals. If autoregulation is intact and the compliance is not disturbed, no such correlations are predicted.

To detect the above mentioned correlations in real world data we use SCA, a set of mathematical tools based on frequency analysis in a time-resolved way [8]. By splitting both time series into isochronous, fixed length segments, the multi-taper coherence spectrum and the multi-taper power spectra of the segments are calculated. From this spectral information an index called selected correlation (sc) is deduced, which reflects the strength of correlation of the data segments with respect to a specific frequency window. Additionally, the mean Hilbert phase difference of the segments is calculated to reflect the phasing of the data segments. Using a specific statistical test against false positives the data segments are subsequently labeled as sc positive (scp), sc negative (scn) or no sc (nsc). A positive selected correlation (scp) indicates a diminished compliance with defective autoregulation, whereas a negative selected correlation (scn) indicates a diminished cerebral compliance with an intact cerebral autoregulation. Finally, no significant

126 correlation (nsc) indicates no disturbance of cerebral compliance or autoregulation.
127

128 In the current study, the SCA was used to determine data segments where a
129 diminished cerebral compliance caused by a severe brain swelling is indicated
130 (labeled scp). Additionally we determined data segments where no disturbance
131 of the cerebral compliance is detectable (labeled nsc). Only scp- and nsc-marked
132 segments were selected from the recordings in order to ease interpretability. The
133 complete parameter set used for SCA was adopted from Faltermeier *et al.* [7]. In
134 the following section, the utilization of a pre-processing routine is described.

135 **2.3 Pre-processing of pulsatile data**

136 Utilizing a Matlab package developed by Achhammer [1], representative pulses
137 were extracted. This was accomplished by averaging over a 10 s-long window of
138 SCA-catalogued ICP segments. In the first step, the routine is cutting each pulse
139 from minimum to minimum (Fig. 1 panel B). In the next step, a pair-wise comparison
140 between each of the raw pulses is performed, using the Jensen-Shannon
141 Distance (JSD) as a similarity measure. The pulse with the highest mean similarity
142 is considered a temporary reference pulse in the next intermediate step. A
143 JSD-similarity between the reference and each of the other pulses is then computed
144 and compared to a custom threshold - all the pulses with a value above that
145 threshold are rejected, otherwise sent to the next step. This step prevents highly
146 dissimilar pulses, e.g. mechanical noise or movement artifacts, from smearing the
147 representative pulse.

148 This is followed by the alignment of pulses by shifting the curves in order to

Figure 1: The process of creating a representative ICP pulse wave from a 10s-long window. (A) The raw sequence is cut into pieces, (B) from minimum to minimum, and then stacked together (C). In this example the last three pulses from B were excluded by the JSD-based artifact removal. The curves are shifted along the x -axis s.t. the Euclidean distance between pulses gets minimal (D). The resulted stack of waves is averaged (E) and normalized (F). On the x -axis the time is captured in milliseconds. On the y -axis (A-B) the ICP amplitude is captured in mmHg, whereas in the following panels is the normalized amplitude. Figure obtained from Achhammer [1].

149 minimize the Euclidean distance between them (Fig. 1 panels C-D). The mean
150 of the aligned pulses is computed (Fig. 1E), and the resulting prototype pulse is
151 normalized (Fig. 1F). An additional step was included in order to ease the further
152 analysis, by resizing the pulses to an average length of 780 sample points.

153 **2.4 Extracting pulse modes**

154 **2.4.1 PCA**

155 In order to visualize the structure of the our data, the principal component analysis
156 (PCA) was used as a means of dimensionality reduction. Given an input set, this
157 technique performs a transformation to a new space of uncorrelated variables,
158 called principal components (PCs), that contain most of the variance present in
159 the original variables [12]. We applied PCA to the dataset of extracted ICP pulses
160 from the entire cohort.

161 **2.5 Clustering**

162 Two clustering techniques were used to reveal the hidden structure of the dataset:
163 Gaussian Mixture Models (GMMs) and HDBSCAN, both chosen for their flexi-
164 bility and highly customizable parameters. GMMs represent a probabilistic method
165 that attempts to find a mixture of multi-dimensional Gaussian probability distribu-
166 tions that best fit a dataset. The parameter search for these models is usually based
167 on a maximum likelihood estimation (MLE), using the Expectation-Maximization
168 (EM) algorithm [2]. The advantage of using GMMs for clustering comes from the
169 ability of the user to define the number of components into which to decompose
170 the dataset. HDBSCAN, on the other hand, is an advanced density-based cluster-

ing algorithm based on hierarchical density estimates [4, 16]. The main advantage of using HDBSCAN is that it allows clusters with varying densities of points.

2.5.1 Fully Convolutional Network for time-series classification

Figure 2: Schematic of the FCN architecture. The 1D input is subjected to three successive convolutions. The weights of the last convolutional layer undergo GAP. This is followed by the last, fully-connected softmax layer with 6 nodes, each representing a class (orange for scp; green for nsc).

For our purposes, we used a variation of CNNs called Fully Convolutional Neural Networks (FCN) that has been recently popularized for semantic segmentation [15]. More importantly for us, it recently achieved state-of-the-art performance from scratch in time series classification [20]. Apart from being easy to train, FCNs offer additional significant advantages like, for example, the invariance in the number of parameters in convolutional layers. The difference between a typical CNN and an FCN rests on two main points: (1) there are no local pooling or down-sampling layers in between convolutions and (2) the number of parame-

ters is considerably lower due to the replacement of the final fully connected (FC) layer with a global average pooling (GAP) operation [14].

GAP layers were first proposed by Lin *et al.* [14] as an alternative to traditional FC layers. Instead of creating a further downsampled feature map, it takes the feature maps of size $(height \times width \times n_channels)$ of the last convolutional layer and computes a single (average) number per channel resulting in $(1 \times 1 \times n_channels)$. This procedure enforces a correspondences between feature maps and categories without the need of additional learnable parameters to be optimized, reducing therefore the risk of overfitting.

Besides the afore mentioned advantages of GAPs, they also allow building class activation maps (CAMs), which highlight regions in the input contributing to the classification, therefore aiding interpretability of the model [11, 20, 22]. In principle, they work as follows: specific units in a convolution layer are selectively activated depending on the visual patterns that fall in its receptive field. These activations are further up-sampled to match the size of the input image, constructing the CAM. See the complete definition of CAMs in 7.3.

The architecture of our model is depicted in Fig. 2. It was implemented in Keras [5] and was inspired by the FCN model from Ismail Fawaz *et al.* [11]. The one-dimensional CAMs that have been used in this study were introduced by Wang *et al.* [20]. This allowed us to visualize which regions in the ICP pulses contributed the most to the label assigned by our FCN during testing (Figs. S6 and S7).

3 Results and Discussion

3.1 Inter-patient ICP pulse classification

3.1.1 Individual ICP pulses

The first step in the ICP classification pipeline was to extract individual ICP pulses using the pre-processing pipeline described in Section 2.3. As a result, we ended up with a database (Table 2) consisting of normalized scp and nsc ICP pulses from the recordings of seven human subjects.

Table 2: Number of pulses extracted from raw ABP and ICP time-series for each human subject.

Patient ID	Number of pulses	
	scp	nsc
1	9408	2702
2	6053	2258
3	7255	3418
4	3970	1941
5	4181	4941
6	6171	2575
7	6835	3986

3.1.2 ICP modes

After extracting all individual pulses, the second step was to identify modes, or patterns of vibration across these pulses. We achieved it by projecting pulses onto their first three principal components using PCA. The projection in Fig. 3 of the entire ICP dataset onto the first three PCs revealed that there is no major structural difference that could be responsible for the variability in pulse shape of nsc and scp data. Therefore we proceeded to a patient-wise extraction of modes by means

218 of clustering.

219 The results of the patient-wise clustering of pulsatile ICP are presented in
220 grid plots in Fig. S1 showing the mean ICP pulse wave for each found cluster.
221 Surprisingly, both scp and nsc segments amounted to almost the same number of
222 clusters, i.e. 46 for nsc and 45 for scp. Apart from regular ICP modes there are
223 plenty of noise modes in the data. Some of them may correspond to movements
224 of the patient lying in bed, others could catch the plugging and unplugging of
225 the sensors. There are also some modes that correspond to improperly cut pulses
226 during data pre-processing.

227 3.1.3 ICP pulse classification

228 The premise of this part of the study was that inspecting data from seven different
229 patients will reveal injured brain states that could potentially capture the tran-
230 sitions between “ignorable” and “dangerous” conditions. Projecting ICP pulses
231 from additional patients unveiled, as anticipated, a wide variety of waves residing
232 in agglomerated clusters. At this point we have used the knowledge of a human
233 expert to pick representative ICP waveforms out of the above mentioned cluster
234 means (see Fig. S1) that best represent four classes: **nsc**, **scp**, **intermediate** and
235 **noisy**.

236 Based on these classes we defined an inter-patient dataset that could be used
237 to train a pulse classifier. As a choice for the classification algorithm we selected
238 a Fully Convolutional Neural Network (FCN) for its performance and ease of
239 training (see Section 2.5.1). The model was trained on a set of 42711 waves split
240 into four classes with the following proportions: 5018 : 21946 : 4486 : 11261
241 (nsc, scp, intermediate and noise, respectively). After a small amount of training

Figure 3: Projections of concatenated nsc (a) and scp (b) ICP pulses from all the seven patients onto first three PCs.

time, the model converged to a reasonable validation accuracy. The final test was performed on a hold-out test set, consisting of 10678 waves with class proportions: 1274 : 5483 : 1193 : 2728. This model reached 93.1 % accuracy on this set. Training and testing data sets were obtained by randomly splitting data of all seven patients.

3.2 Improved ICP-ABP classification

3.2.1 ABP modes

In theory, the most prominent influence on the shape of the ICP wave is given by the appropriate ABP pulse wave, which can be interpreted as the generating signal of the ICP wave. Therefore physiologically-conditioned variants of the ABP waveform may have strong ramifications on the interpretation of ICP waveforms with respect to cerebral compliance. Medical literature roughly describes three systemic variants of the ABP pulse waves, a typical healthy one, one originating from a heart failure [6] and a third one showing multiple reflections [17] due to strong vasoconstriction (see prototypes of these waveforms in Fig. 4). To estimate the influence of the above mentioned ABP pulse wave variants on the detection of scp and nsc ICP waves we first performed a patient-wise pre-processing of the ABP pulses, identical to that used for ICP pre-processing (see Section 2.3).

The result of the patient- and selected correlation-wise clustering of pulsatile ABP is presented in Figs. S2 and S3. At first glance, each patient exhibits at least six different morphologies for both scp and nsc types. Few noise components, e.g. nsc components 16, 20, 30 and 44 (Fig. S2) and scp components 11, 37, 44, 49 and 54 (Fig. S3), were probably caused by external mechanical per-

Figure 4: Chosen ABP WFs from our recordings. First representative WF is taken from patient 7 nsc and corresponds to a normal (most common in our cohort) ABP wave; second wave is from patient 10 scp and corresponds to a heart failure; the third comes from patient 37 scp and corresponds to multiple reflections, i.e. vasoconstriction or stiff blood vessels.

turbations. Also moderate intra-subject variation can be recognized, which, however, is stronger when comparing pulses between patients. Another aspect to be mentioned is the larger number of scp clusters in the ABP data, namely 75 in comparison with 61 nsc clusters, resulting in a significantly imbalanced dataset. On the other hand, ABP recordings contained twice as much scp than nsc annotations.

Through visual inspection, we identified all ABP clusters with cluster prototype waveforms (see Figs. S2 and S3) similar to the waveforms given in Fig. 4 as a function of sc-index. The selected ABP components are listed in Table 3.

Table 3: The chosen ABP components from figures S3 and S2 divided into three physiological categories: regular, heart failure and multiple reflections, and two cerebral compliance states: scp and nsc. Notation: index of the ABP component from each sc-index.

sc-index	regular	heart failure	reflections
scp	1, 9, 17, 45, 50	7, 15	65, 8
nsc	5, 6, 36, 46	17	31, 59

In order to visualize the shape of ICP pulses corresponding to chosen ABP components, we aggregated ABP pulses by physiological category and sc-index

from the selected clusters and extracted the corresponding ICP pulses (Fig. 5). Furthermore, to analyze the variety of ICP pulses that contributed to those means, we turned back to PCA. The first three PCs were extracted and used to project the pulses for a further clustering step. This task was achieved using the HDBSCAN algorithm (See Fig. 6 for scp and Fig. 7 for nsc).

Figure 5: Mean of selected ABP pulses (first row) and corresponding to them ICP pulses (second row). First column corresponds to common ABP WF; second column – heart failure; third column – multiple reflections. Orange pulses corresponds to scp whereas green ones to nsc.

3.2.2 Selected correlation or input ABP

By calculating the ratios of ABP waveforms (*wf1*, *wf2* and *wf3*) that constituted each ICP cluster in Figs. 6 and 7, we could identify which of the ABP components was mainly responsible for the resulting ICP. Given these ratios, the question arose: *Are we able to distinguish between ICP waves created by the same type of input ABP waveform, but belonging to a different selected correlation type?* In other words, is the difference between selected correlation types dominating the

Figure 6: PCA-projection of **scp** ICP waves corresponding to chosen WFs. Clusters identified by HDBSCAN are marked by different colours. The gray points correspond to noise points considered by the algorithm. In the legend are captured the ratios of each WF that contributed to the found cluster.

Figure 7: PCA-projection of **nsc** ICP waves corresponding to chosen WFs. Clusters identified by HDBSCAN are marked by different colours. The gray points correspond to noise points considered by the algorithm. In the legend are captured the ratios of each WF that contributed to the found cluster.

influence of the input ABP waveform or not? To answer this question, we grouped together identified ICP clusters from both sc types to see (1) if these clusters are at all separable or, if not completely, (2) what is the rate of pulses from each sc type that build up those additional clusters.

An example of such a grouping is depicted in Fig. S4, where the 867 **scp** ICP pulse clusters and the 241 **nsc** ICP pulse clusters are both predominantly (99.7 % and 99.6 %) caused by ABP waveform 1. A GMM with 5 components was able to separate the clusters. The prototype components (cluster means) are plotted in Fig. S5.

Additionally projecting the cluster components onto the first two principal components (PCs) revealed, without exception, that all components were separable in the PC subspace using GMM clustering. All results of this pair-wise analysis are presented in Table 4.

3.2.3 Classification

The data arranged in Table 4 was exploited as a dataset for end-to-end training and testing the FCN classifier described in Section 2.5.1. The six types of ICP pulses (Fig. 5) that can be assigned to the ABP waveforms regular, heart failure and reflective input, respectively, and separated by sc-index come naturally as class labels. Based on this premise a training dataset was curated (see Table 5). Even though the dataset is highly imbalanced, after fitting the FCN on the training set (80 % of the dataset) it reached an average accuracy of 96 % on the hold-out test set.

With the purpose of understanding what determined the model to classify each type of pulses, a part of the test set was subjected to the CAMs technique (see

Table 4: Additional clustering results of pair-wise (scp-nsc) selected ICP clusters corresponding to chosen ABP waveforms.

ABP WF	scp cluster	nsc cluster	Additional clustering			
			Algorithm	Size	scp (%)	nsc (%)
regular	867	241	GMM(5)	241	0	100
				178	100	0
				121	100	0
				242	100	0
				326	100	0
		165	GMM(3)	165	0	100
				416	100	0
				451	100	0
	447	241	GMM(2)	241	0	100
				447	100	0
		165	GMM(2)	165	0	100
				447	100	0
heart failure	1547	301	GMM(4)	169	1.2	98.8
				124	2.4	97.6
				335	99.4	0.6
				1220	99.1	0.9
reflections	216	94	GMM(2)	216	100	0
	94			0	100	
	1610		GMM(4)	94	0	100
				775	100	0
				534	100	0
				301	100	0

Figs. S6 and S7), as described in Section 2.5.1. One common characteristic among the majority of these CAMs is the weight with which the initial slope of the pulse contributes to its classification. This phenomenon is especially striking in the *scp-common* class (see first panel in Fig. S6), where the majority of the contribution is focused right at the beginning of the pulse sample, since one would expect that the label will be assigned based on the ripples recorded in 150 – 500 segment.

One definite conclusion that can be drawn from these results is that the ABP

Table 5: Training dataset consisting of six classes, divided into **scp** and **nsc**, additionally split into regular, heart failure and multiple reflections input ABP waveforms.

Selected correlation type	input ABP-WF	Nr. of ICP pulses
scp	regular	2181
	heart failure	1555
	reflections	1826
nsc	regular	406
	heart failure	293
	reflections	95

318 waveforms, viewed as an input driving the ICP, definitely introduce detectable
319 changes in the shape of ICP waves. Furthermore, these alterations are not substan-
320 tial enough to smear out differences between sc types. Moreover, the techniques
321 applied, namely PCA for dimensionality reduction and GMMs with HDBSCAN
322 for clustering, proved to be very accurate and practical in uncovering patterns and
323 correlations in the ICP and ABP pulsatile data never observed before.

324 4 Conclusions

325 The variations induced by a diminished cerebral compliance on ICP waveforms
326 depend on a large number of internal and external influences. For an automatic de-
327 tection of medically relevant information contained in these variations it is there-
328 fore inevitable to categorize the most apparent influences and to reduce disrupting
329 factors. In this study we tried to minimized the subjective influence of a human
330 expert by selecting ICP data segments hallmarked by diminished or intact cere-
331 bral compliance via a well established mathematical method called selected cor-
332 relation analysis (SCA). From this labeled data we extracted the appropriate ICP

333 waveforms for further analysis. Using dimensionality reduction in combination
334 with clustering methods we found multiple modes of pulsatile ICPs originating
335 from the two different states of cerebral compliance under investigation. This
336 multitude of modes could be further exploited by constructing a training data set
337 for a custom fully convolutional network. A small number of training steps were
338 enough for the network to reliably distinguish the two states of pulsatile ICPs.

339 Subsequently we focused on the influence of ABP waveform variants trig-
340 gered by various diseases on the ICP waveform sets reflecting the state of the
341 cerebral compliance. Once again using methods identical to those used for ICP,
342 we were able to show that distinct variants of ABP waveforms generate detectable
343 sub-clusters in the ICP modes. But more importantly, these sub-clusters were still
344 separable in terms of cerebral compliance state. Based on these observations we
345 constructed a second dataset that can be used for training a classifier for distin-
346 guishing between six different kinds of ICPs - two states of the cerebral compli-
347 ance times three sub-classes of ABP waveform variants. Our network was trained
348 on this dataset and achieved high accuracy, hence can serve as a baseline for pul-
349 satile ICP classification. These findings provide a proof of concept for further
350 development of this type of analysis targeting the real time detection of numerous
351 cerebral pathophysiologies occurring during traumatic brain injury.

352 **5 Limitations**

353 Even though we succeeded in detecting and identifying several hitherto unknown
354 types of ICP and ABP pulses, we still lack decent knowledge on their interpre-
355 tation and significance in a patient-oriented treatment. Our entire methodology

356 can be drastically improved with further research. For example, we used the exact
 357 same pre-processing routine for pulsatile ABP as for ICP, but the former could
 358 have very different dynamics which could require a different extraction method.
 359 Another drawback is the small number of patients present in our cohort. This
 360 is a critical variable that has to be increased, in order to sample the majority of
 361 conditions for an unbiased and significant diagnosis. All these points have to be
 362 seriously considered in order to arrive at an end-to-end system that can be included
 363 in a monitor or alert system at the ICU. Our hope is that medical institutions will
 364 begin to collaborate more frequently and, more importantly, share their multivari-
 365 ate recordings with institutions and teams specialized in medical data analysis.
 366 This type of collaborations is already bringing higher precision and more confi-
 367 dence in the diagnosis of specific pathologies. And with multi-disciplinary efforts
 368 medical system's effectiveness will only be improved.

369 **6 Acknowledgments**

370 We acknowledge the deposition of the manuscript on the bioRxiv preprint server
 371 under <https://doi.org/10.1101/2020.11.17.381517>.

372 **References**

- 373 1. Achhammer, T. *An Empirical Mode Decomposition to investigate Intracra-*
 374 *nial Pressure Profiles to distinguish brain disease states* (Unpublished). MS
 375 thesis (Universität Regensburg, Regensburg, Germany, 2017).

- 376 2. Bishop, C. M. *Pattern Recognition and Machine Learning* (ed Jordan M.
377 Kleinberg J., S. B.) (Springer-Verlag New York, 2006).
- 378 3. Böhm, M., Faltermeier, R., Brawanski, A. & Lang, E. W. Mathematical
379 modeling of human brain physiological data. *Physical Review E - Statistical,*
380 *Nonlinear, and Soft Matter Physics* **88** (2013).
- 381 4. Campello, R. J., Moulavi, D. & Sander, J. Density-based clustering based on
382 hierarchical density estimates. *Lecture Notes in Computer Science (including*
383 *subseries Lecture Notes in Artificial Intelligence and Lecture Notes in*
384 *Bioinformatics)* **7819 LNAI**, 160–172 (2013).
- 385 5. Chollet, F. *et al. Keras* <https://keras.io>. 2015.
- 386 6. Denardo, S. J., Nandyala, R., Freeman, G. L., Pierce, G. L. & Nichols, W. W.
387 Pulse wave analysis of the aortic pressure waveform in severe left ventricular
388 systolic dysfunction. *Circulation: Heart Failure* **3**, 149–156 (2010).
- 389 7. Faltermeier, R., Proescholdt, M. A., Bele, S. & Brawanski, A. Parameter
390 Optimization for Selected Correlation Analysis of Intracranial Pathophysi-
391 ology. *Computational and Mathematical Methods in Medicine* **2015** (2015).
- 392 8. Faltermeier, R., Proescholdt, M. A., Bele, S. & Brawanski, A. Windowed
393 multitaper correlation analysis of multimodal brain monitoring parameters.
394 *Computational and Mathematical Methods in Medicine* **2015** (2015).
- 395 9. Hu, X., Glenn, T., Scalzo, F., Bergsneider, M., Sarkiss, C., Martin, N. &
396 Vespa, P. Intracranial pressure pulse morphological features improved detec-
397 tion of decreased cerebral blood flow. *Physiological Measurement* (2010).

- 398 10. Hu, X., Xu, P., Scalzo, F., Vespa, P. & Bergsneider, M. Morphological clus-
399 tering and analysis of continuous intracranial pressure. *IEEE Transactions*
400 *on Biomedical Engineering* (2009).
- 401 11. Ismail Fawaz, H., Forestier, G., Weber, J., Idoumghar, L. & Muller, P. A.
402 Deep learning for time series classification: a review. *Data Mining and Knowl-*
403 *edge Discovery* **33**, 917–963. arXiv: 1809.04356 (2019).
- 404 12. Jolliffe, I. T. Principal Component Analysis, Second Edition. *Encyclopedia*
405 *of Statistics in Behavioral Science* (2002).
- 406 13. Jung, A. Statistical analysis of biomedical data. eprint: 10.5283/epub.
407 10168 (2003).
- 408 14. Lin, M., Chen, Q. & Yan, S. Network In Network. arXiv: 1312.4400
409 (Dec. 2013).
- 410 15. Long, J., Shelhamer, E. & Darrell, T. Fully Convolutional Networks for Se-
411 mantic Segmentation. arXiv: 1411.4038 (Nov. 2014).
- 412 16. McInnes, L. & Healy, J. Accelerated Hierarchical Density Based Clustering.
413 *IEEE International Conference on Data Mining Workshops, ICDMW 2017-*
414 **Novem**, 33–42. arXiv: 1705.07321 (2017).
- 415 17. Nirmalan, M. & Dark, P. M. Broader applications of arterial pressure wave
416 form analysis. *Continuing Education in Anaesthesia, Critical Care and Pain*
417 **14**, 285–290 (2014).
- 418 18. Nucci, C. G., De Bonis, P., Mangiola, A., Santini, P., Sciandrone, M., Risi,
419 A. & Anile, C. Intracranial pressure wave morphological classification: au-

- 420 tomated analysis and clinical validation. *Acta Neurochirurgica* **158**, 581–
421 588 (2016).
- 422 19. Proescholdt, M. A., Faltermeier, R., Bele, S. & Brawanski, A. Detection of
423 impaired cerebral autoregulation using selected correlation analysis: A val-
424 idation study. *Computational and Mathematical Methods in Medicine* **2017**
425 (2017).
- 426 20. Wang, Z., Yan, W. & Oates, T. Time Series Classification from Scratch
427 with Deep Neural Networks: A Strong Baseline. *CoRR* **abs/1611.0**. arXiv:
428 1611.06455 (2016).
- 429 21. Zeiler, A. Weighted Sliding Empirical Mode Decomposition and its Appli-
430 cation to Neuromonitoring Data. eprint: 10.5283/epub.27783 (2012).
- 431 22. Zhou, B., Khosla, A., Lapedriza, A., Oliva, A. & Torralba, A. Learning
432 Deep Features for Discriminative Localization. *Proceedings of the IEEE*
433 *Computer Society Conference on Computer Vision and Pattern Recognition*,
434 2921–2929. arXiv: 1512.04150 (2016).

435 7 Supplementary Materials

436 7.1 Supplementary tables

Table 1: Physiological variables of involved patients

ID	Gender	Age	Diagnosis	GCS	GOS (last follow up)
1	m	60.2	TBI	10	3
2	m	51.6	SAH	8	1
3	f	51.6	SAH	9	3
4	m	65.4	TBI	6	3
5	f	50.4	SAH	14	5
6	f	43.4	SAH	11	1
7	m	36.3	SAH	12	3

SAH Subarachnoid hemorrhage; *TBI* traumatic brain injury; *GCS* Glasgow coma scale; *GOS* Glasgow outcome scale.

437 7.2 Supplementary figures

(a)

(b)

Figure S1: Means of ICP **nsc** (a) and **scp** (b) clusters. Notation: patient (mean index). Different colours correspond to different patients.

Figure S2: Means of ABP **nsc** clusters. Notation: patient (mean index). Different colours correspond to different patients.

Figure S3: Means of ABP **scp** clusters. Notation: patient (mean index). Different colours correspond to different patients.

Figure S4: Example of additional clustering using GMMs with 5 components onto the two clusters: 867 **scp** and 241 **nsc** ICP pulses from ABP-WF1.

Figure S5: ICP means corresponding to found cluster in the projection (Fig. S4).

438 **7.3 Class Activation Maps (CAMs) definition**

439 Given a time series, let $S_k(x)$ be the k -th activation filter in the last convolutional
 440 layer at temporal location x . The output of the GAP for filter $k \in [1, M]$ is
 441 $f_k = \sum_k S_k(x)$. With ω_k^c as the weight of the final softmax function for the k -th
 442 filter and the class c , the input of the softmax function will be

$$g_c = \sum_k \sum_x \omega_k^c S_k(x) . \quad (1)$$

443 One can define M_c as the class activation map for class c , then each temporal
 444 element will be given by

$$M_c = \sum_k \omega_k^c S_k(x) . \quad (2)$$

445 This quantity comprises a univariate time series with each element equal to the
 446 weighted sum of the M data points at position x , the weights being learned by the
 447 network [1]. Therefore $M_c(x, y)$ will indicate the importance of the activation at
 448 location x_i that lead to the classification of the series y to class c .

Figure S6: Examples of CAMs from classes 0 $\rightarrow$ 2. The true label is displayed together with the predicted one and its `softmax` probability. Darker colors along the shape of the pulses show the regions that contributed the most to the classification.

Figure S7: Examples of CAMs from classes 3 $\rightarrow$ 5. The true label is displayed together with the predicted one and its `softmax` probability. Darker colors along the shape of the pulses show the regions that contributed the most to the classification.

449 **References**

- 450 1. Ismail Fawaz, H., Forestier, G., Weber, J., Idoumghar, L. & Muller, P. A.
451 Deep learning for time series classification: a review. *Data Mining and Knowl-
452 edge Discovery* **33**, 917–963. arXiv: 1809.04356 (2019).