Combining Multi-Dimensional Molecular Fingerprints to Predict hERG

Cardiotoxicity of Compounds

Weizhe Ding^{1#}, Li Zhang^{1,2,3*#}, Yang Nan¹, Juanshu Wu¹, Xiangxin Xin¹, Chenyang

Han¹, Siyuan Li¹, Hongsheng Liu^{2,3,4*}

¹School of Life Sciences, Liaoning University, Shenyang 110036, China

²Technology Innovation Center for Computer Simulating and Information Processing
of Bio-macromolecules of Liaoning Province, Shenyang 110036, China

³Engineering Laboratory for Molecular Simulation and Designing of Drug Molecules
of Liaoning, Liaoning University, Shenyang, 110036, China

⁴School of Pharmaceutical Sciences, Liaoning University, Shenyang 110036, China

*Corresponding author

Hongsheng Liu

School of Pharmaceutical Sciences, Liaoning University

Address: No. 66, Chongshan Zhonglu, Shenyang, Liaoning, 110036, China

liuhongsheng@lnu.edu.cn

Li Zhang

School of Life Sciences, Liaoning University

Address: No. 66, Chongshan Zhonglu, Shenyang, Liaoning, 110036, China

lizhang@lnu.edu.cn

[#]These co-first authors contributed equally to this work.

21   **Abstract**

22   At present, drug toxicity has become a critical problem with heavy medical and
 23   economic burdens. acLQTS (acquired Long QT Syndrome) is acquired cardiac ion
 24   channel disease caused by drugs blocking the hERG channel. Therefore, it is
 25   necessary to avoid cardiotoxicity in the drug design and computer models have been
 26   widely used to fix this plight. In this study, we present a molecular fingerprint based
 27   on the molecular dynamic simulation and uses it combined with other molecular
 28   fingerprints (multi-dimensional molecular fingerprints) to predict hERG
 29   cardiotoxicity of compounds. 203 compounds with hERG inhibitory activity (pIC₅₀)
 30   were retrieved from a previous study and predicting models were established using
 31   four machine learning algorithms based on the single and multi-dimensional
 32   molecular fingerprints. Results showed that MDFP has the potential to be an
 33   alternative to traditional molecular fingerprints and the combination of MDFP and
 34   traditional molecular fingerprints can achieve higher prediction accuracy. Meanwhile,
 35   the accuracy of the best model, which was generated by consensus of four algorithms
 36   with multi-dimensional molecular fingerprints, was 0.694 (RMSE) in the test dataset.
 37   Besides, the number of hydrogen bonds from MDFP has been determined as a critical
 38   factor in the predicting models, followed by rgyr and sasa. Our findings provide a new
 39   sight of MDFP and multi-dimensional molecular fingerprints in building models of
 40   hERG cardiotoxicity prediction.

41   **Keywords:** Molecular dynamic simulation; Molecular fingerprint; Machine learning;
 42   hERG;

43   **1. Introduction**

44   Drug-induced toxicity has become a critical reason for the failure of drug
45   discovery and development in recent years (Wallace, 2015). A previous study showed
46   that there were more than half of drugs failed (54%) in clinical development among
47   640 novel therapeutics, while 17% of them failed because of drug-induced toxicity
48   (Hwang et al., 2016). Besides, it has also been reported that the mean costs required to
49   bring a new drug to market increased from \$374.1 million to \$1335.9 million after
50   counting for costs of failed trials (Wouters et al., 2016). Thus, it has become an urgent
51   task to find ways to identify the toxicity of compounds on a large scale in drug
52   development.

53   Acquired Long QT syndrome (acLQTS), one of the most important diseases
54   caused by drug-induced toxicity, is a potentially life-threatening cardiac arrhythmia
55   disease that increases the risk for syncope, sudden cardiac death (SCD), and seizures
56   (Tester & Ackerman, 2014). The hERG protein is a tetrameric potassium ion channel
57   and mainly relates to cardiotoxicity and acLQTS (Liu et al., 2020). It has been
58   reported that the potassium ion channel (hERG channel) may be blocked caused by
59   antiarrhythmic drug binding, which leads to prolonged repolarization time and
60   acLQTS (Witchel, 2007). At present, multiple drug candidates have failed due to the
61   cardiotoxicity of hERG, such as cisapride, terfenadine, sertindole, pimozone, and
62   astemizole, which have become a significant limiting factor in drug discovery and
63   development (Bergström & Lindmark, 2019; Villoutreix & Taboureau, 2019).

64   Computer-aided drug design (CADD) has been thought of as an alternate choice

65 to reduce the amount of time and money in the development of drug design,
 66 especially in predicting drug toxicity (Maia et al., 2020). Molecular fingerprints are a
 67 way of CADD and are used to encoding the structure of molecules (O'Boyle et al.,
 68 2011). It has been deployed as descriptors for predicting biological activities and
 69 compound properties (Muegge & Mukherjee, 2014). Frequently used molecular
 70 fingerprints are structure-based and property-based (Kelley, 2018; Rogers & Hahn,
 71 2010; Riniker & Landrum, 2013; Riniker, 2017). A previous study of hERG
 72 cardiotoxicity prediction showed that the accuracy of the best model developed by
 73 molecular descriptors reached 0.54 (R^2), while RMSE was 0.63 (Johnson et al., 2007).
 74 Another study of the hERG channel also showed that the accuracy of the regression
 75 model by descriptors was 0.60 (Q^2) and 0.55 (RMSE) for pIC50 (Radchenko et al.,
 76 2017). These results showed the practicalities and effectiveness based on commonly
 77 used molecular fingerprints. However, there are still no fingerprints that considered
 78 the time factor applied on the cardiotoxicity prediction of hERG.

79 Molecular dynamics fingerprints (MDFP) are the fingerprints based on
 80 calculating the trajectory of molecular dynamic simulation and have rapidly become a
 81 hotspot. After adding the dimension of time, MDFP can be seen as a choice of the
 82 traditional molecular fingerprint. The study of p-glycoprotein substrates prediction
 83 showed that gradient tree boosting (GTB) methods in combination with MDFP was
 84 the only model which achieved a good accuracy on the in-house dataset (Esposito et
 85 al., 2020). Meanwhile, the research of free-energy prediction showed good
 86 performance with a heterogeneous fusion model by MDFP (Riniker, 2017). Besides,

studies of self-solvation free energies and application of MDFP in SAMPL6 octanol–water log P blind challenge also revealed a high prediction rate (Gebhardt et al., 2020; Wang & Riniker, 2019). As a consequence, MDFP can be an alternative choice of traditional molecular fingerprints and has great application potential on the cardiotoxicity prediction of hERG.

Multi-dimensional molecular fingerprints are indicated as multiple molecular fingerprints combining together in order to predict more accurately. Previous studies showed that multi-dimensional molecular fingerprints were better than the single molecular fingerprint in drug development (Kyaw et al., 2020). Thus, in this study, we studied MDFP and multi-dimensional molecular fingerprints (MDFP with other molecular fingerprints) in predicting hERG cardiotoxicity of compounds. The extensive open dataset of hERG compounds with IC50 values has been collected from previous studies. Then, molecular dynamic simulation was conducted to generate MDPF and traditional molecular fingerprints have also been generated by Baseline2D, ECFP4, and PropertyFP. Finally, the regression models were built by machine learning with four algorithms. Our study provides new sights on the combination of multi-dimensional molecular fingerprints and the research of predicting the hERG cardiotoxicity of compounds.

2. Methods

2.1. Toxicity Datasets

A high-quality hERG inhibitor dataset has been collected from the previous study (Munawar et al., 2019). The IC50 value is the biochemical half-maximal

109 inhibitory concentration and has been used to represent the inhibiting abilities of
110 compounds on hERG in this dataset (Kalliokoski et al., 2013). The data of toxicity
111 have been eliminated if the name and IC50 values were repeated. The repeated
112 molecules have also been averaged if the difference IC50 values were less than one
113 order of magnitude (Feng et al., 2021). Finally, 203 compounds have been collected
114 with specific IC50 values of the hERG. The distribution of training and testing sets
115 followed by 80% and 20%, respectively. The training sets were used for 5-fold
116 cross-validation and the testing sets were used to check the prediction performance of
117 the established model for new compounds. Besides, pIC50 is the negative log unit of
118 the IC50 values and has been used to represent inhibiting abilities better than IC50
119 (Cortés-Ciriano et al., 2020). Therefore, IC50 of compounds was converted to pIC50.

120 **2.2. MD Simulations**

121 Molecular dynamics (MD) simulation was performed by GROMACS (2020.4).
122 For compounds in the dataset, mol2 files were obtained from Zinc15
123 (<http://zinc15.docking.org/>) by using SMILES files. The topology of compounds was
124 generated with AMBER14SB force field by ACPYPE (<https://www.bio2byte.be/>)
125 (Sousa da Silva et al., 2012). Afterward, the compounds were placed in a
126 dodecahedron box with a size of 1.0 nm centrally and solvated with the TIP3P water
127 model. Then, the descent energy minimization with 100ps was applied to the system.
128 An additional equilibration of 1ns under NVT and NPT conditions was carried out,
129 while the constant temperature was 300 K and the constant pressure was 1 bar,
130 respectively (Sun et al., 2020). Finally, the system was performed with running 5 ns

MD simulation and coordinates were written every 10ps, energies every 1ps.

2.3. 2D Molecular Fingerprints

Three types of molecular fingerprints have been used in this study. Baseline2D was obtained using RDKit and its elements mainly consisted of 10 counts: number of heavy atoms, number of rotatable bonds, number of N, O, F, P, S, Cl, Br, and I atoms (Riniker, 2017; Wang & Riniker, 2019). The PropertyFP fingerprint was also obtained using the Descriptastorus package from RDKit (Kelley, 2018). It contained nearly 200 atoms features and properties. Besides, ECFP4 was generated using the RDKit implementation of the Morgan algorithm with a vector length of 2048 and a radius of 2 (Rogers & Hahn, 2010).

2.4. MD Fingerprints

The MD trajectories were analyzed by the GROMACS toolkit (Ogunwa, 2019). Following features has been generated: radius of gyration (rgyr), solvent-accessible surface area (sasa), root mean squared error (rmsd), total energy (tenergy), hydrogen bonds (hbond), kinetic energy (kinetic), Lennard-Jones short-range energies (LJ-SR) and Lennard-Jones 1-4 energies (LJ-14). The average (avr), median (mid), and standard deviation (std) of features were calculated using the R version 3.6.1 (Team, 2013). Fig. 1 showed the MDFP with all properties.

2.5. Feature Selection

Feature selection is critically important for predictive models, especially in machine learning (Johnson et al., 2018). It provides an effective way to reduce the dimensionality of data sets, identify informative features, and remove irrelevant

features, improving the learning accuracy of machine learning models (Holder et al., 2017). In this study, zero variation and near-zero variation features were deleted firstly using the nearZeroVar function in the R package caret (version 6.0–84) (Kuhn, 2008). Then, recursive feature elimination (RFE) was performed to select the optimal feature subset using the rfe function in the caret package in a 10 times 5-fold cross-validation setting (Darst et al., 2018). In the RFE process, all features are first ranked according to the feature importance values obtained by the random forest (RF) algorithm, and then RF models are trained iteratively on the features that are gradually reduced according to the ranking to evaluate the performance of the feature subsets (Tang et al., 2020).

2.6. Model Construction

In this study, RF, SVM, gradient boosting machine (GBM), and partial least square regression (PLS) was used for machine learning model construction. All models were executed beyond R (version 3.6.1) with using the randomForest (version 4.6–12) (Liaw & Wiener, 2002), the kernlab (version 0.9-25) (Karatzoglou et al., 2004), the gbm (version 2.1.5) (Brandon et al., 2019), and the pls (version 2.7-1) packages (Bjørn-Helge et al., 2019), respectively.

2.6.1 Random forest

RF is the machine learning ensemble classifier and has been applied in many fields (Breiman, 2001). By constructing multiple decision trees, the RF classifier has been considered as better performance than the single decision tree (Gandhi et al., 2018). In the current study, the randomforest function has been used to build RF

classifiers. The number of classification trees and variables randomly selected for each node split have been set as $n_{tree} = 500$, while m_{try} was optimized from one-third of the number of features minus 10 to plus 15. The relative importance of molecular fingerprints has also been calculated by the important function of the package.

2.6.2 Support vector machine

SVM is a generalized linear classifier based on the principle of structural risk reduction for pattern recognition (Huang et al., 2018). It is well known as a supervised learning algorithm that analyzes data and recognizes patterns (Nedaie et al., 2018). In this study, the radial basis function (RBF) kernel was used for building the SVM classifier. Meanwhile, the random search method (Bergstra & Bengio, 2012) was also applied to optimize specific SVM parameters with the regularization parameter C and σ parameter by using the caret package, while C was from e^{-2} to e^6 , σ was from e^{-7} to e with the step of $e^{0.5}$.

2.6.3 Gradient boosting machine

GBM is also a tree-based machine learning model. It has been considered as a step-wise, additive type model which sequentially fits new-tree-based models (Golden et al., 2019). Meanwhile, it also has many advantages, especially worked well in practice (Cho et al., 2019). In this study, the total number of trees (n_{trees}) and the maximum depth of each tree (interaction. depth) have been optimized by using the caret package and have been set from 1 to 3000 and 1 to 10, respectively. Besides, shrinkage and $n_{minobsinnode}$ were set as 0.005 and 10.

2.6.4 Partial least square regression

197 PLS calculates a group of latent variables in connection with the output
198 maximally and determines the relationship between the input and output data (Foodeh
199 et al., 2020). It is a stretch of the multiple linear regression models and is widely used
200 in many domains (Wu et al., 2020). Unlike multiple linear regression (MLR), it can
201 handle the data with noisy, strongly collinear, and X-variables (Dong et al., 2018). In
202 this study, n_components for PLS were optimized from 1 to the greatest features or
203 sample sizes.

204 **2.7. Model Evaluation**

205 In order to test the predictive performance of the models, 5-fold cross-validation
206 with 10 repeats has been used to evaluate the models. After randomly divided the
207 original dataset into five equal subsets, four of them were used for training and the
208 other was used for testing. Then the 5-fold cross-validation was repeated ten times to
209 reduce the randomness. This cross-validation progress was performed 10 times with
210 different random seeds of 2, 4, 8, 16, 32, 64, 128, 256, 512, and 1024. Then, average
211 values were calculated to evaluate the prediction performance of the models.

212 Root-mean-squared error (RMSE), mean unsigned error (MUE), and R^2 has been
213 used to evaluate the predictive performance of the models. These indicators were
214 calculated by the following formulas:

$$RMSE = \sqrt{\frac{1}{n} \sum_{i=1}^n (P - E)^2}$$

$$MUE = \frac{1}{n} \sum_{i=1}^n |P - E|$$

$$R^2 = 1 - \frac{\sum_i (P - E)^2}{\sum_i (\bar{E} - E)^2}$$

Where P, $\bar{E}$, E, n represent predictive value, the average of experimental value, experimental value, and compound numbers, respectively.

3. Results and discussion

3.1. Feature selection

In this study, 203 compounds were collected from the previous study and divided into training and testing datasets with 80% to 20%, respectively. In order to build models to predict hERG cardiotoxicity, MDFP, Baseline2D, ECFP4, and PropertyFP have been calculated for the compounds in the dataset. [Table 1](#) illustrated the number of features calculated from each type of molecular fingerprint and the detailed description of these features is shown in the supplementary files ([Table S1](#) and [Table S2](#)). After the feature selection by RF-RFE, 11 and 6 features have been selected from MDFP and Baseline2D, respectively. Meanwhile, there were also 99 features selected from ECFP4 and 71 from PropertyFP. Percentage increase in MSE (%IncMSE) obtained by RF was used to evaluate the importance of features. [Fig. 2](#) showed the top ten features (Baseline2D for six) which important to the prediction models. The results of MDFP showed that the number of hydrogen bonds between compounds and water has a significant effect on predicting hERG cardiotoxicity, followed by kinetic energy and surface area. Besides, the results of 2D molecular fingerprints indicated that the number of heavy atoms, number of O atoms (oxygenes), and number of F atoms (fluorines) were the most important features in Baseline2D, while MolLog P in PropertyFP and 3218693969 in ECFP4. Above all, after calculating features in all

molecular fingerprints, the following features have been selected as the most critical with heavyatoms, oxygens, fluorines, the median of hydrogen bonds, and 3218693969. These features may be played important roles in predicting the hERG cardiotoxicity and should be paid extra attention in the development of drug candidates.

3.2. Prediction performance of the models

After performing feature selection, the GBM, PLS, RF, and SVM algorithms were used for generating ML models based on the resulting fingerprints. The performance of these machine learning models was evaluated by 10 times 5-fold cross-validation and their performances were presented in [Table 2](#). The results showed that the RMSE of each machine learning model based on PropertyFP is the lowest, with a range of 0.860-0.960, followed by MDFP, with a range of 0.967-1.039, while ECFP4 and Baseline2D are poor quality. R^2 and MUE also showed the same pattern. [Table 3](#) illustrated the performance of these models which were used to predict the pIC50 of the molecules in the testing set. In general, the models show better RMSE values in the test set than in the 5-fold cross-validation, indicating that the model has not been overfitted. Meanwhile, compared with the models based on different molecular fingerprints, the performance in the testing set was similar, while Baseline2D was slightly better (RMSE=0.721 to 0.795) and MDFP also obtained a good performance (RMSE=0.755 to 0.819). These results indicated that MDFP can effectively predict the activity of hERG inhibitors, and the predictive performance of the MDFP was similar to the traditional molecular fingerprints.

The predictive performance of the MDFP model combined with other molecular

fingerprints was also investigated in this study. [Table 4](#) and [Table 5](#) showed the performance of models in the 5-fold cross-validation sets and testing sets while MDFP combined with other molecular fingerprints, respectively. The results showed that the combination of MDFP and other molecular fingerprints can obtain a model with better prediction performance. For example, the model established by the single molecular fingerprint (MDFP or PropertyFP) in the 5-fold cross-validation had the best performance as PropertyFP-SVM (RMSE=0.860). However, the model established by multi-dimensional molecular fingerprints (MDFP and PropertyFP) was MDFP+PropertyFP-SVM (RMSE=0.837), which showed a better performance than using the single molecular fingerprints. Besides, models combining MDFP with other molecular fingerprints also showed better predictive performance in the testing set ([Table 5](#)), while the best model was the SVM model trained on MDFP++ (MDFP with all other fingerprints) (RMSE=0.696±0.015). These results illustrated that the performance of multi-dimensional molecular fingerprints was better than the single molecular fingerprints and MDFP may provide additional effective predictors for the prediction of hERG inhibitor activity.

In order to improve the prediction performance of the model, we further averaged the prediction results of the four machine learning models to obtain a consensus value. The prediction performance was shown in [Table 3](#) and [Table 5](#). [Fig. 3](#) and [Fig. 4](#) showed the predicted values vs experimental values for MDFP and MDFP++, respectively. The values of other molecular fingerprints have been demonstrated in the supplementary files ([Fig. S1 to S6](#)). It was found that the

performance of consensus models was significantly better than the other models (except PropertyFP). Among the models established by a single molecular fingerprint, the consensus model based on Baseline2D had the highest accuracy (RMSE=0.713), while the consensus model based on MDFP also obtained a better RMSE of 0.745. Meanwhile, in the model based on the multi-dimensional molecular fingerprints, MDFP+ECFP4 and MDFP++ obtained high accuracy with RMSE of 0.694 and 0.695, respectively. These results indicated that the integrated model can obtain a better method for predicting the activity of hERG inhibitors.

In summary, these results illustrated that the MDFP was effective compared with traditional molecular fingerprints and can truly be an alternative to the other molecular fingerprints. Meanwhile, the prediction accuracies of all ML models on multi-dimensional molecular fingerprints were better than the single molecular fingerprints in predicting the hERG cardiotoxicity. Besides, the integrated models showed the best prediction than the single models among most of the molecular fingerprints. Thus, the models obtained by multiple machine learning methods could be more accurate in predicting the hERG cardiotoxicity of compounds.

3.3. MDFP features associated with cardiotoxicity

To further reveal the contributions of fingerprint features associated with cardiotoxicity, the correlation coefficient has been used to determine the feature between MDFP and pIC50. Correlation is a measure of a monotonic association between 2 variables and Pearson's correlation coefficient has become one of the most frequently used statistics (Armstrong, 2019). In this study, Pearson, Kendall, and

302 Spearman correlations were used to evaluate the important features of MDFP with
 303 pIC50. Table 6 showed the correlation coefficient between the feature of MDFP and
 304 pIC50. The median of rgyr has been determined as the most relevant feature with
 305 pIC50 (Kendall = 0.35, Pearson = 0.51, and Spearman = 0.49), followed by the
 306 median of sasa and kinetic with the high correlation coefficient. These results showed
 307 the features which extracted from MDFP had strong correlations with pIC50 and can
 308 be used to predict cardiotoxicity in the future study.

309 **3.4. Compared with other models**

310 Recently, a couple of computational models have been developed for toxicity
 311 prediction. Among them, cardiotoxicity prediction has become a hotspot with multiple
 312 studies. Table 7 showed the comparisons between our model and other models for
 313 cardiotoxicity prediction. Compared with other models, the consensus model with
 314 MDFP and ECFP4 showed the lowest RMSE and MUE, with higher R^2 . Meanwhile,
 315 the molecular fingerprints of previous studies were used by only one dimension,
 316 which may prove that multi-dimensional fingerprints performed well in predicting the
 317 cardiotoxicity of hERG. Besides, although it was lower than QSAR-SVM, the
 318 consensus with MDFP still better than the other models as 0.745 ± 0.005 (RMSE),
 319 which illustrated the advantages of MDFP. These findings showed that MDFP and
 320 multi-dimensional molecular fingerprints with machine learning methods can be an
 321 outstanding model in predicting cardiotoxicity.

322 **4. Conclusion**

323 In this study, MDFP and multi-dimensional molecular fingerprints were used for

324 building machine learning models to predict the hERG cardiotoxicity of compounds.
 325 203 compounds were firstly identified to establish the 5-fold cross-validation and
 326 testing datasets. Then molecular dynamic simulation has been used to generate
 327 molecular dynamic molecular fingerprints. Baseline2D, ECFP4, and PropertyFP were
 328 used to generate traditional molecular fingerprints. After that, critical features have
 329 been selected by RF-RFE and 4 machine learning algorithms, namely RF, SVM,
 330 GBM, and PLS were used for building predicting models based on the single
 331 fingerprints and multi-dimensional molecular fingerprints. Besides, the correlation
 332 between MDFP and pIC50 has also been surveyed. Results showed that MDFP has
 333 the potential to be an alternative choice of molecular fingerprints and
 334 multi-dimensional molecular fingerprints are better than single fingerprints in
 335 predicting cardiotoxicity. It also illustrated that the consensus model with MDFP and
 336 ECFP4 has the optimum prediction effect and hydrogen bonds are critically important
 337 in the models with MDFP. Our finding provides a new sight into the application of
 338 MDFP and multi-dimensional molecular fingerprints in predicting the hERG
 339 cardiotoxicity of compounds. Cell and animal experiments will be carried out to
 340 validate further.

341 **Conflict of interests**

342 The authors declare that they have no conflict of interests.

343 **Acknowledgements**

344 This study was supported by the National Natural Science Foundation of China (No.
 345 82003655), the Key R&D Program of Liaoning Province (No. 2019JH2/10300041),

346 Scientific Research Project from Department of Education of Liaoning Province (No.
347 LQN201906), Shenyang Science and Technology Plan Project (No. 17-65-7-00,
348 19-302-3-04).

349 **Data Availability Statement**

350 All data and models generated or used during the study appear in the submitted
351 article.

352 **Author contributions**

353 WZD, LZ, and HSL conceived the project, developed the prediction method, designed,
354 and implemented the experiments, analyzed the result, and wrote the paper. YN, JSW,
355 and XXX implemented the experiments, analyzed the result, and wrote the paper.
356 SYH and SYL analyzed the result. All authors read and approved the final manuscript.

357 **References**

- 358 Armstrong RA., 2019. Should Pearson's correlation coefficient be avoided? *Ophthalmic Physiol*
359 *Opt.* 39, 316-327. <https://doi.org/10.1111/opo.12636>
- 360 Bergstra J., Bengio Y., 2012. Random search for hyper-parameter optimization. *J. Mach. Learn.*
361 *Res.* 13, 281-305.
- 362 Bergström F., Lindmark B., 2019. Accelerated drug discovery by rapid candidate drug
363 identification. *Drug Discov Today.* 24, 1237-1241.
364 <https://doi.org/10.1016/j.drudis.2019.03.026>.
- 365 Bjørn-Helge M., Ron W., and Kristian L., 2019. Partial Least Squares (PLS) and Principal
366 Component Regression. R package v2.7.1 (version 2.7.1).
367 <https://CRAN.R-project.org/package=pls>

368 Brandon G., Bradley B., Jay C., and GBM Developers., 2019. Generalized Boosted Regression
369 Models (GBM). R package v2.1.5 (version 2.1.5). <https://CRAN.R-project.org/package=gbm>

370 Breiman L., 2001. Random Forests. Mach. Learn. 45, 5–32.
371 <https://doi.org/10.1023/A:1010933404324>.

372 Cho G., Yim J., Choi Y., Ko J., Lee SH., 2019. Review of Machine Learning Algorithms for
373 Diagnosing Mental Illness. Psychiatry Investig. 16, 262-269.
374 <https://doi.org/10.30773/pi.2018.12.21.2>.

375 Cortés-Ciriano I., Škuta C., Bender A., Svozil D., 2020. QSAR-derived affinity fingerprints (part
376 2): modeling performance for potency prediction. 12, 41.
377 <https://doi.org/10.1186/s13321-020-00444-5>.

378 Darst BF., Malecki KC., Engelman CD., 2018. Using recursive feature elimination in random
379 forest to account for correlated variables in high dimensional data. BMC Genet. 19, 65.
380 <https://doi.org/10.1186/s12863-018-0633-8>.

381 Dong J., Wang NN., Yao ZJ., Zhang L., Cheng Y., Ouyang D., Lu AP., Cao DS., 2018.
382 ADMETlab: a platform for systematic ADMET evaluation based on a comprehensively
383 collected ADMET database. J Cheminform. 10, 29.
384 <https://doi.org/10.1186/s13321-018-0283-x>.

385 Esposito C., Wang S., Lange UEW., Oellien F., Riniker S., 2020. Combining Machine Learning
386 and Molecular Dynamics to Predict P-Glycoprotein Substrates. J Chem Inf Model. 60,
387 4730-4749. <https://doi.org/10.1021/acs.jcim.0c00525>.

388 Feng H., Zhang L., Li S., Liu L., Yang T., Yang P., Zhao J., Arkin IT., Liu H., 2021. Predicting
389 the reproductive toxicity of chemicals using ensemble learning methods and molecular

390 fingerprints. *Toxicol Lett.* 340, 4-14. <https://doi.org/10.1016/j.toxlet.2021.01.002>.

391 Foodeh R., Ebadollahi S., Daliri MR., 2020. Regularized Partial Least Square Regression for
392 Continuous Decoding in Brain-Computer Interfaces. *Neuroinformatics.* 18, 465-477.
393 <https://doi.org/10.1007/s12021-020-09455-x>.

394 Gandhi K., Schmidt B., Ng A.H., 2018. Towards data mining based decision support in
395 manufacturing maintenance. *Procedia CIRP.* 72, 261-265.
396 <http://doi.org/10.1016/j.procir.2018.03.076>.

397 Gebhardt J., Kiesel M., Riniker S., Hansen N., 2020. Combining Molecular Dynamics and
398 Machine Learning to Predict Self-Solvation Free Energies and Limiting Activity Coefficients.
399 *J Chem Inf Model.* 60, 5319-5330. <http://doi.org/10.1021/acs.jcim.0c00479>.

400 Golden CE., Rothrock MJ Jr., Mishra A., 2019. Comparison between random forest and gradient
401 boosting machine methods for predicting *Listeria* spp. prevalence in the environment of
402 pastured poultry farms. *Food Res Int.* 122, 47-55.
403 <http://doi.org/10.1016/j.foodres.2019.03.062>.

404 Holder LB., Haque MM., Skinner MK., 2017. Machine learning for epigenetics and future
405 medical applications. *Epigenetics.* 12, 505-514.
406 <http://doi.org/10.1080/15592294.2017.1329068>.

407 Huang S., Cai N., Pacheco PP., Narrandes S., Wang Y., Xu W., 2018. Applications of Support
408 Vector Machine (SVM) Learning in Cancer Genomics. *Cancer Genomics Proteomics.* 15,
409 41-51. <http://doi.org/10.21873/cgp.20063>.

410 Hwang TJ., Carpenter D., Lauffenburger JC., Wang B., Franklin JM., Kesselheim AS., 2016.
411 Failure of Investigational Drugs in Late-Stage Clinical Development and Publication of Trial

412 Results. JAMA Intern Med. 176, 1826-1833.
 413 <http://doi.org/10.1001/jamainternmed.2016.6008>.

414 Johnson SR., Yue H., Conder ML., Shi H., Doweiko AM., Lloyd J., Levesque P., 2007.
 415 Estimation of hERG inhibition of drug candidates using multivariate property and
 416 pharmacophore SAR. Bioorg Med Chem. 15, 6182-6192.
 417 <http://doi.org/10.1016/j.bmc.2007.06.028>.

418 Johnson KW., Torres Soto J., Glicksberg BS., Shameer K., Miotto R., Ali M., Ashley E., Dudley
 419 JT., 2018. Artificial Intelligence in Cardiology. J Am Coll Cardiol. 71, 2668-2679.
 420 <http://doi.org/10.1016/j.jacc.2018.03.521>.

421 Kalliokoski T., Kramer C., Vulpetti A., Gedeck P., 2013. Comparability of mixed IC₅₀ data - a
 422 statistical analysis. PLoS One. 8, e61007. <http://doi.org/10.1371/journal.pone.0061007>.

423 Karatzoglou A., Smola A., Hornik K., Zeileis A., 2004. Kernel-an S4 package for kernel methods
 424 in R. J. Stat. Softw. 11, 1–20.

425 Kelley B. Descriptor Computation(Chemistry) and (Optional) Storage for Machine Learning.
 426 DescriptaStorus, version 2.2.0. <https://github.com/bp-kelley/descriptastorus>.

427 Kuhn M., 2008. Building predictive models in R using the caret package. J. Stat. Softw. 26, 1–26.

428 Kyaw Zin PP., Borrel A., Fourches D., 2020. Benchmarking 2D/3D/MD-QSAR Models for
 429 Imatinib Derivatives: How Far Can We Predict? J Chem Inf Model. 60, 3342-3360.
 430 <http://doi.org/10.1021/acs.jcim.0c00200>.

431 Liaw A., Wiener M., 2002. Classification and regression by randomForest. R News 2, 18–22.

432 Liu M., Zhang L., Li S., Yang T., Liu L., Zhao J., Liu H., 2020. Prediction of hERG potassium
 433 channel blockage using ensemble learning methods and molecular fingerprints. Toxicol Lett.

- 434 332, 88-96. <http://doi.org/10.1016/j.toxlet.2020.07.003>.
- 435 Maia EHB., Assis LC., de Oliveira TA., da Silva AM., Taranto AG., 2020. Structure-Based
436 Virtual Screening: From Classical to Artificial Intelligence. *Front Chem.* 8, 343.
437 <http://doi.org/10.3389/fchem.2020.00343>.
- 438 Muegge I., Mukherjee P., 2016. An overview of molecular fingerprint similarity search in virtual
439 screening. *Expert Opin Drug Discov.* 11, 137-148.
440 <http://doi.org/10.1517/17460441.2016.1117070>.
- 441 Munawar S., Vandenberg JL., Jabeen I., 2019. Molecular Docking Guided Grid-Independent
442 Descriptor Analysis to Probe the Impact of Water Molecules on Conformational Changes of
443 hERG Inhibitors in Drug Trapping Phenomenon. *Int J Mol Sci.* 20, 3385.
444 <http://doi.org/10.3390/ijms20143385>.
- 445 Nedaie A., Najafi AA., 2018. Support vector machine with Dirichlet feature mapping. *Neural*
446 *Netw.* 98, 87-101. <http://doi.org/10.1016/j.neunet.2017.11.006>.
- 447 O'Boyle NM., Banck M., James CA., Morley C., Vandermeersch T., Hutchison GR., 2011. Open
448 Babel: An open chemical toolbox. *J Cheminform.* 3, 33.
449 <http://doi.org/10.1186/1758-2946-3-33>.
- 450 Ogunwa TH., Laudadio E., Galeazzi R., Miyanishi T., 2019. Insights into the Molecular
451 Mechanisms of Eg5 Inhibition by (+)-Morelloflavone. *Pharmaceuticals (Basel).* 12, 58.
452 <http://doi.org/10.3390/ph12020058>.
- 453 Radchenko EV., Rulev YA., Safanyaev AY., Palyulin VA., Zefirov NS., 2017. Computer-aided
454 estimation of the hERG-mediated cardiotoxicity risk of potential drug components. *Dokl*
455 *Biochem Biophys.* 473, 128-131. <http://doi.org/10.1134/S1607672917020107>.

456 Riniker S., Landrum GA., 2013. Open-source platform to benchmark fingerprints for ligand-based
457 virtual screening. *J Cheminform.* 5, 26. <http://doi.org/10.1186/1758-2946-5-26>.

458 Riniker S., 2017. Molecular Dynamics Fingerprints (MDFP): Machine Learning from MD Data
459 To Predict Free-Energy Differences. *J Chem Inf Model.* 57, 726-741.
460 <http://doi.org/10.1021/acs.jcim.6b00778>.

461 Rogers D., Hahn M., 2010. Extended-connectivity fingerprints. *J Chem Inf Model.* 50, 742-754.
462 <http://doi.org/10.1021/ci100050t>.

463 Sousa da Silva AW., Vranken WF., 2012. ACPYPE - AnteChamber PYthon Parser interface.
464 *BMC Res Notes.* 5, 367. <http://doi.org/10.1186/1756-0500-5-367>.

465 Subramanian G., Ramsundar B., Pande V., Denny RA., 2016. Computational Modeling of
466 β -Secretase 1 (BACE-1) Inhibitors Using Ligand Based Approaches. *J Chem Inf Model.* 56,
467 1936-1949. <http://doi.org/10.1186/10.1021/acs.jcim.6b00290>.

468 Sun CP., Yan JK., Yi J., Zhang XY., Yu ZL., Huo XK., Liang JH., Ning J., Feng L., Wang C.,
469 Zhang BJ., Tian XG., Zhang L., Ma X., 2019. The study of inhibitory effect of natural
470 flavonoids toward β -glucuronidase and interaction of flavonoids with β -glucuronidase. *Int J*
471 *Biol Macromol.* 143, 349-358. <http://doi.org/10.1016/j.ijbiomac.2019.12.057>.

472 Tang J., Wang Y., Luo Y., Fu J., Zhang Y., Li Y., Xiao Z., Lou Y., Qiu Y., Zhu F., 2020.
473 Computational advances of tumor marker selection and sample classification in cancer
474 proteomics. *Comput Struct Biotechnol J.* 18, 2012-2025.
475 <http://doi.org/10.1016/j.csbj.2020.07.009>.

476 R Core Team., 2013. R: A language and environment for statistical computing. R Foundation for
477 Statistical Computing. <http://www.R-project.org>

- 478 Tester DJ., Ackerman MJ., 2014. Genetics of long QT syndrome. *Methodist Debaquey Cardiovasc*
479 *J.* 10, 29-33. <http://doi.org/10.14797/mdcj-10-1-29>.
- 480 Villoutreix BO., Taboureaux O., 2015. Computational investigations of hERG channel blockers:
481 New insights and current predictive models. *Adv Drug Deliv Rev.* 86, 72-82.
482 <http://doi.org/10.1016/j.addr.2015.03.003>.
- 483 Wallace KB., 2015. Multiple Targets for Drug-Induced Mitochondrial Toxicity. *Curr Med Chem.*
484 22, 2488-2492. <http://doi.org/10.2174/0929867322666150514095424>.
- 485 Wang S., Riniker S., 2020. Use of molecular dynamics fingerprints (MDFPs) in SAMPL6
486 octanol-water log P blind challenge. *J Comput Aided Mol Des.* 34, 393-403.
487 <http://doi.org/10.1007/s10822-019-00252-6>.
- 488 Witchel HJ., 2007. The hERG potassium channel as a therapeutic target. *Expert Opin Ther Targets.*
489 11, 321-336. <http://doi.org/10.1517/14728222.11.3.321>.
- 490 Wouters OJ., McKee M., Luyten J., 2020. Estimated Research and Development Investment
491 Needed to Bring a New Medicine to Market, 2009-2018. *JAMA.* 323, 844-853.
492 <http://doi.org/10.1001/jama.2020.1166>.
- 493 Wu ML., Wang YT., Cheng H., Sun FL., Fei J., Sun CC., Yin JP., Zhao H., Wang YS., 2020.
494 Phytoplankton community, structure and succession delineated by partial least square
495 regression in Daya Bay, South China Sea. *Ecotoxicology.* 29, 751-761.
496 <http://doi.org/10.1007/s10646-020-02188-2>.

Fig.1. Schematic representation of the MDFP variant with all properties: kinetic, LJ-14, LJ-SR, tenergy, rgyr, hbond, sasa, rmsd. Each property is represented by the avr (average), std (standard deviation), and mid (median).

Fig. 2. The most important features selected by RF-RFE from MDFP, Baseline2D, ECFP4, and PropertyFP fingerprints.

Fig. 3. pIC50: The experimental values of the 10th operation for the data set. Predictions were generated using consensus, GBM, PLS, RF, SVM trained on MDPF. The linear regression lines are shown in blue.

Fig. 4. pIC50: The experimental values of the 10th operation for the data set. Predictions were generated using consensus, GBM, PLS, RF, SVM trained on MDPF++. The linear regression lines are shown in blue. MDPF++ including MDPF, Baseline2D, ECFP4, and PropertyFP.

Table 1 The number of features for the different molecular fingerprints.

fingerprints	number of features	number of selected feature
MDFP	24	11
Baseline2D	10	6
ECFP4	2298	99
PropertyFP	200	71

Table 2 Cross-validation performance for models trained using different ML algorithms on the molecular fingerprints (MDFP, Baseline2D, ECFP4, PropertyFP). Performance metrics are represented as average and standard deviation of 10 times 5-fold cross-validation runs of different random seeds.

fingerprint	ML models	RMSE	R ²	MUE
MDFP	GBM	0.985±0.005	0.523±0.004	0.774±0.005
	PLS	1.039±0.005	0.482±0.006	0.797±0.003
	RF	0.977±0.005	0.534±0.006	0.768±0.004
	SVM	0.967±0.007	0.541±0.006	0.745±0.007
Baseline2D	GBM	1.112±0.009	0.394±0.009	0.884±0.006
	PLS	1.189±0.004	0.321±0.007	0.956±0.003
	RF	1.036±0.011	0.465±0.011	0.813±0.008
	SVM	1.014±0.006	0.492±0.006	0.791±0.006
ECFP4	GBM	1.072±0.006	0.433±0.007	0.837±0.007
	PLS	1.084±0.004	0.433±0.004	0.850±0.006
	RF	1.043±0.004	0.464±0.004	0.827±0.004
	SVM	1.009±0.004	0.497±0.004	0.800±0.004
PropertyFP	GBM	0.941±0.008	0.562±0.006	0.747±0.007
	PLS	0.959±0.008	0.551±0.006	0.776±0.008
	RF	0.960±0.004	0.559±0.004	0.763±0.005
	SVM	0.860±0.006	0.634±0.006	0.676±0.009

Table 3 Cross-validation performance for models tested using different ML algorithms on the molecular fingerprints (MDFP, Baseline2D, ECFP4, PropertyFP). Performance metrics are represented as average and standard deviation of 10 times 5-fold cross-validation runs of different random seeds.

fingerprint	ML models	RMSE	R ²	MUE
MDFP	GBM	0.772±0.008	0.479±0.008	0.582±0.009
	PLS	0.755±0	0.494±0	0.564±0
	RF	0.819±0.011	0.398±0.012	0.570±0.006
	SVM	0.802±0.010	0.458±0.007	0.586±0.005
	consensus	0.745±0.005	0.495±0.005	0.524±0.003
Baseline2D	GBM	0.794±0.005	0.472±0.004	0.568±0.004
	PLS	0.772±0.000	0.441±0.000	0.548±0.000
	RF	0.795±0.015	0.423±0.015	0.545±0.011
	SVM	0.721±0.005	0.525±0.005	0.520±0.011
	consensus	0.713±0.003	0.520±0.004	0.507±0.002
ECFP4	GBM	0.858±0.008	0.348±0.010	0.664±0.009
	PLS	0.752±0.001	0.495±0.010	0.578±0.006
	RF	0.865±0.009	0.315±0.011	0.635±0.011
	SVM	0.737±0	0.491±0	0.553±0
	consensus	0.761±0.001	0.457±0.003	0.571±0.003
PropertyFP	GBM	0.813±0.005	0.432±0.006	0.632±0.008
	PLS	0.764±0.002	0.492±0.003	0.596±0.001
	RF	0.709±0.006	0.529±0.009	0.540±0.006
	SVM	0.761±0.035	0.488±0.040	0.605±0.033
	consensus	0.730±0.008	0.508±0.010	0.560±0.008

Table 4 Cross-validation performance for models trained using different ML algorithms on the molecular fingerprints (MDFP + Baseline2D, MDFP + ECFP4, MDFP + PropertyFP, MDFP++). Performance metrics are represented as average and standard deviation of 10 times 5-fold cross-validation runs of different random seeds.

fingerprint	ML models	RMSE	R ²	MUE
MDFP + Baseline2D	GBM	0.991±0.005	0.516±0.005	0.767±0.005
	PLS	1.068±0.007	0.458±0.004	0.820±0.004
	RF	0.950±0.006	0.560±0.006	0.738±0.005
	SVM	0.938±0.008	0.568±0.007	0.717±0.008
MDFP + ECFP4	GBM	0.975±0.005	0.529±0.006	0.745±0.006
	PLS	1.021±0.010	0.509±0.005	0.797±0.009
	RF	0.945±0.005	0.566±0.004	0.740±0.005
	SVM	0.935±0.005	0.569±0.004	0.740±0.005
MDFP + PropertyFP	GBM	0.915±0.008	0.585±0.006	0.722±0.009
	PLS	0.948±0.011	0.568±0.009	0.754±0.011
	RF	0.944±0.005	0.578±0.004	0.742±0.004
	SVM	0.837±0.006	0.654±0.006	0.659±0.007
MDFP++	GBM	0.920±0.008	0.580±0.006	0.723±0.008
	PLS	0.958±0.007	0.556±0.005	0.754±0.007
	RF	0.940±0.005	0.578±0.004	0.742±0.005
	SVM	0.873±0.007	0.623±0.005	0.686±0.007

Table 5 Predictions were generated using different ML models trained on MDFP combined with multi-dimensional molecular fingerprints (MDFP + Baseline2D, MDFP + ECFP4, MDFP + PropertyFP, MDFP++) in test. MDFP++ including MDFP, Baseline2D, ECFP4, and PropertyFP.

fingerprint	ML models	RMSE	R ²	MUE
MDFP + Baseline2D	GBM	0.728±0.008	0.525±0.008	0.544±0.008
	PLS	0.751±0.007	0.502±0.011	0.559±0.006
	RF	0.789±0.009	0.427±0.011	0.560±0.008
	SVM	0.781±0.003	0.494±0.002	0.551±0.001
	consensus	0.721±0.003	0.524±0.003	0.518±0.003
MDFP + ECFP4	GBM	0.758±0.007	0.491±0.007	0.569±0.004
	PLS	0.702±0	0.555±0	0.535±0
	RF	0.750±0.012	0.472±0.016	0.553±0.007
	SVM	0.698±0.003	0.550±0.004	0.522±0.008
	consensus	0.694±0.002	0.548±0.003	0.515±0.004
MDFP + PropertyFP	GBM	0.799±0.009	0.456±0.010	0.615±0.008
	PLS	0.794±0.000	0.481±0.004	0.610±0.003
	RF	0.709±0.008	0.527±0.011	0.549±0.009
	SVM	0.723±0.011	0.518±0.012	0.578±0.012
	consensus	0.719±0.003	0.523±0.003	0.554±0.003
MDFP++	GBM	0.811±0.008	0.448±0.009	0.619±0.009
	PLS	0.702±0	0.587±0	0.526±0
	RF	0.718±0.010	0.513±0.014	0.554±0.006
	SVM	0.696±0.015	0.564±0.011	0.516±0.017
	consensus	0.695±0.004	0.557±0.004	0.518±0.003

Table 6 Correlation coefficient between the features of MDFP and pIC50.

feature	kendall	pearson	spearman
rgyr mid	0.35	0.51	0.49
sasa mid	0.30	0.41	0.43
kinetic mid	0.28	0.32	0.42
LJ-SR mid	0.28	0.25	0.41
rgyr avr	0.23	0.20	0.33
sasa avr	0.20	0.16	0.29
sasa std	0.17	0.01	0.25
hbond avr	-0.08	-0.14	-0.12
hbond std	-0.09	-0.09	-0.13
hbond mid	-0.12	-0.19	-0.17
tenergy mid	-0.28	-0.42	-0.41

Table. 7 Performance indicators of several cardiotoxicity prediction models reported in the literature.

models	RMSE	R^2	MUE	Reference
QSAR-SVM	0.79 ± 0.05	0.58 ± 0.05	-	(Simeon & Jongkon, 2019)
QSAR-DNN	0.90 ± 0.06	0.49 ± 0.04	-	
MLR-Canvas	1.186	0.191	0.941	(Subramanian et al., 2016)
DNN-DeepChem	1.03	0.351	0.763	
PLS-FFD	1.07	0.48	-	(Munawar et al., 2019)
consensus-MDFP	0.745 ± 0.045	0.495 ± 0.005	0.524 ± 0.003	
consensus-MDFP+ECFP4	0.694 ± 0.002	0.548 ± 0.003	0.515 ± 0.004	