SomaticSiMu: A mutational signature simulator

David Chen¹, Gurjit S. Randhawa², Maximillian P.M. Soltysiak¹, Camila P.E. de Souza³, Lila Kari², Shiva M. Singh¹ and Kathleen A. Hill^{1,*}

¹Department of Biology, Western University, London, Ontario, Canada.

²School of Computer Science, University of Waterloo, Waterloo, Ontario, Canada.

³Department of Statistical and Actuarial Sciences, Western University, London, ON, Canada.

*To whom correspondence should be addressed.

Abstract

Summary: SomaticSiMu is an *in silico* simulator of mutations in genome sequences. SomaticSiMu simulates single and double base substitutions, and single base insertions and deletions in an input genomic sequence to mimic mutational signatures. The tool is the first mutational signature simulator featuring a graphical user interface, control of mutation rates, and built-in visualization tools of the simulated mutations. SomaticSiMu generates simulated FASTA sequences and mutational catalogs with imposed mutational signatures. The reliability of SomaticSiMu to simulate mutational signatures was affirmed by supervised machine learning classification of simulated sequences with different mutation types and burdens, and mutational signature extraction from simulated mutational catalogs. SomaticSiMu is useful in validating sequence classification and mutational signature extraction tools.

Availability and Implementation: SomaticSiMu is written in Python 3.8.3. The open-source code, documentation, and tutorials are available at <https://github.com/HillLab/SomaticSiMu> under the terms of the Creative Commons Attribution 4.0 International License.

Contact: khill22@uwo.ca

Supplementary information: Supplementary data are appended.

1 Introduction

Somatic mutagenesis in cancer arises from the interplay between inherited genomic instabilities, acquired mutations associated with error-prone replication and faulty repair, as well as endogenous and exogenous DNA damaging mechanisms. Sources of somatic mutagenesis associated with cancer genomes are known to generate characteristic patterns of small-scale base substitutions, insertions, and deletions known as mutational signatures (Supplementary Data A) (Alexandrov *et al.*, 2020; Bacolla *et al.*, 2014; Forbes *et al.*, 2016). The set of mutation types, local sequence contexts, and burden from multiple mutational signatures arising in different cancer types and mutagen exposures can cumulatively alter genome sequence composition.

Optimizing sequence classification tools and mutational signature extraction tools can be achieved by systematically assessing their performance using simulated datasets. First, mutation simulations offer capacity to generate large datasets as input to benchmark machine learning-based tools for supervised classification of genomic sequences with

specific predefined mutational signatures. Computationally generated sequences can upsample minority classes of rare cancer genomic sequences to produce datasets with balanced class distributions. This is needed to correct systematic performance biases by machine learning-based sequence classifiers against minority classes. Second, ground truth genomic sequence datasets with imposed mutational signatures and known sets of mutation types, contexts, and burdens can also be used to benchmark the accuracy of mutational signature extraction tools. SomaticSiMu (Supplementary Section B) is a new mutational signature simulator with confirmed utility for these applications.

While genomic sequences from cancer biosamples remain the gold standard input for benchmarking machine-learning based sequence dissimilarity tools for supervised classification performance, there remain several advantages of a simulation approach to generate cancer genomic sequences *in silico* to complement validation with real data (Mangul *et al.*, 2019). Simulation allows for the fine-tuned control of parameters needed to produce large and highly customized sequence datasets. Moreover, simulated sequences have known sets of mutation types and burdens while real sequences are susceptible to random error in mutation detection

due to sequencing artifacts, incorrect local read alignments, and tumor heterogeneity (Semeraro *et al.*, 2018).

Current tools used to simulate mutations associated with cancer include SigProfilerSimulator (Bergstrom *et al.*, 2020), Xome-Blender (Semeraro *et al.*, 2018), esiCancer (Minussi *et al.*, 2018), simuG (Yue *et al.*, 2019), and Simulome (Price *et al.*, 2017). Compared to SomaticSiMu, these simulators cannot simulate mutations on custom subsets of the genome (e.g., SimuG), output CSV or VCF files instead of FASTA sequence files needed to evaluate the performance of sequence classification tools (e.g., esiCancer and SigProfilerSimulator), or are not designed to simulate the mutational types and burdens associated with multiple mutational signatures at once (e.g., Xome Blender and Simulome).

2 Features

SomaticSiMu is a standalone software tool that simulates mutational signatures operative in human cancer genomes and introduces user-friendly features such as an interactive graphical user interface and an option to visualize the simulated mutations. SomaticSiMu offers a range of features that allows users to simulate realistic mutation types and proportions associated with known single base substitution (SBS) and double base substitution (DBS) mutational signatures, and single base insertions and deletions (indel) as part of a wide range of experimental scenarios. For instance, the Catalogue of Somatic Mutations in Cancer (COSMIC) database of somatic mutational signatures can be used to simulate mutations associated with mutational signatures operative in human cancer (Tate *et al.*, 2018). In simulation mode (Supplementary Section C), the tool generates novel mutations on an input genomic FASTA sequence based on the mutation rates derived from the basis and coefficient matrices of COSMIC mutational signatures. The simulation also produces a mutation catalog of the position, frequency and local sequence context of each mutation in CSV files. In visualization mode (Supplementary Section D), SomaticSiMu can plot simulated mutations as GUI-based interactive mutational signature plots using the 96 SBS, 78 DBS and single base indel mutational classification schemes, as well as visualize mutational burden for each simulated sequence. The rich selection of input parameters and multiprocessing make SomaticSiMu both easy-to-use and scalable for high performance computing applications.

3 Methods

SomaticSiMu first preprocesses the input reference sequence by mapping the sequence k -mer composition. Next, SomaticSiMu samples the set of SBS, DBS, and single base indel signatures operative in a user-specified cancer type. The tool samples subsets of active signatures based on their prevalence among COSMIC tumor samples associated with the user-specified cancer type for each simulation. Mutation probability is defined as the probability that any given mutation type found in the SBS-96, DBS-78, and single base indel classification schemes will occur at a specific local sequence context type in the simulated genome. SomaticSiMu introduces novel mutations in the reference sequence at random indexes, based on the vector of mutation types and their associated mutation probabilities derived from reference mutational signatures and user-defined controls.

4 Performance

To assess the speed and memory consumption of SomaticSiMu, we simulated 20 genomic sequences, each for five cancer types, using the 50 Mb Chromosome 22 from the human genome assembly GRCh38.p13 (NCBI accession: NC_000022.11) as the input reference sequence (Supplementary Table S4). Performance tests were conducted on a MacBook Pro A2141 with a 2.3GHz 8-core Intel Core i9 9880H processor, 16GB DDR4 2667MHz SDRAM, and eight parallel processes. SomaticSiMu took less than 700 seconds to complete each simulation run and recorded a peak memory consumption of less than 10GB.

Eleven benchmark experiments (Supplementary Section E) suggest that SomaticSiMu can accurately simulate mutation types and proportions comparable to mutation types and proportions observed in cancer genome sequences from COSMIC (cosine similarities > 0.95 , and 11 out of 12 Wilcoxon rank-sum tests indicating no significant difference, $p > 0.05$).

To test the reliability of SomaticSiMu, sequences with combinations of high or low mutational burden and high or low cosine similarity between mutational signatures were simulated. A sequence classification tool (Machine Learning with Digital Signal Processing, MLDSP; Randhawa *et al.*, 2019) was used to confirm the expected nature of the simulations. Five experimental tests showed that simulated sequence datasets with higher total sequence mutational burden and more dissimilar mutation types faithfully reproduced the expected increase in MLDSP classification accuracy (Supplementary Section F). Also, simulated mutational catalogs with high and low mutation counts were used to extract mutational signatures. Signature extraction tested on 100 simulated mutational catalogs showed that SigProfilerExtractor (Islam *et al.*, 2021) consistently extracted mutational signatures with high mutation counts as expected (Supplementary Section G). Both the classification of simulated sequences and the extraction of mutational signatures from simulated mutational catalogs affirmed the faithful simulation of mutation types and burdens using SomaticSiMu.

Acknowledgements

We thank Akshaj Jonnalagadda and Adrian Yung for testing SomaticSiMu.

Funding

This work was supported by Natural Science and Engineering Research Council of Canada Grants R3511A12 to K.A.H., R2824A01 to L.K., and R2258A01 to S.M.S.. The funders had no role in study design, data collection and analysis, decision to publish, or preparation of the manuscript. The authors declare no competing interests.

References

- Alexandrov L.B. *et al.* (2020) The repertoire of mutational signatures in human cancer, *Nature*, **578**(7793), 94-101.
- Bacolla A. *et al.* (2014) Mechanisms of base substitution mutagenesis in cancer genomes, *Genes*, **5**(1), 108-146.
- Bergstrom E.N. *et al.* (2020) Generating realistic null hypothesis of cancer mutational landscapes using SigProfilerSimulator, *BMC Bioinformatics*, **21**(1), 438.
- Forbes S.A. *et al.* (2016) COSMIC: somatic cancer genetics at high-resolution, *Nucleic Acids Research*, **45**(D1), D777-D783.
- Islam S.M.A. *et al.* (2021) Uncovering novel mutational signatures by de novo extraction with SigProfilerExtractor, *bioRxiv*
- Mangul S. *et al.* (2019) Systematic benchmarking of omics computational tools, *Nature Communications*, **10**(1), 1393.
- Minussi D.C. *et al.* (2018) EsiCancer: Evolutionary in Silico Cancer Simulator, *Cancer Research*, **79**(5), 1010-1013.
- Price A. *et al.* (2017) Simulome: A genome sequence and Variant Simulator, *Bioinformatics*, **33**(12), 1876-1878.
- Randhawa G.S. *et al.* (2019) ML-DSP: Machine learning with digital signal processing for ultrafast, accurate, and scalable genome classification at all taxonomic levels, *BMC Genomics*, **20**(1), 267.
- Semeraro R. *et al.* (2018) Xome-Blender: A novel cancer genome simulator, *PLOS ONE*, **13**(4), e0194472.
- Tate J.G. *et al.* (2018) COSMIC: The catalogue of somatic mutations in cancer, *Nucleic Acids Research*, **47**(D1), D941-D947.
- Yue J. *et al.* (2019) simuG: A general-purpose genome simulator, *Bioinformatics*, **35**(21), 4442-4444.