CRSP: Comparative RNA-seq pipeline for species lacking both a reference genome and annotated transcriptome

Atefeh Bagheri¹, Colin Dewey^{2,3}, Ron Stewart⁴, Peng Jiang^{1,5,6*}

¹Department of Biological, Geological and Environmental Sciences, Cleveland State University, Cleveland, OH 44115, USA

²Department of Biostatistics and Medical Informatics, University of Wisconsin-Madison, Madison, WI 53706, USA

³Department of Computer Science, University of Wisconsin-Madison, Madison, WI 53706, USA

⁴Morgridge Institute For Research, Madison, WI 53706, USA

⁵Center for Gene Regulation in Health and Disease, Cleveland State University, Cleveland, OH 44115, USA

⁶Center for Applied Data Analysis and Modeling, Cleveland State University, Cleveland, OH 44115, USA

*To whom correspondence should be addressed: p.jiang@csuohio.edu

Summary: RNA sequencing (RNA-seq) has been a widely used high-throughput method to characterize transcriptomic dynamics spatiotemporally. However, typical RNA-seq data analysis pipelines depend on either a sequenced genome or annotated reference transcripts. This restriction makes the use of RNA-seq for species lacking both of sequenced genomes and reference transcripts challenging. To solve this problem, we developed CRSP, an RNA-seq pipeline integrating a comparative species strategy but not depending on a specific sequenced genome or reference transcripts. Benchmarking suggests the CRSP tool can achieve high accuracy to quantify gene expression levels.

Availability: CRSP and documents are available at:
<https://github.com/pjiang1105/CRSP>.

1 INTRODUCTION

RNA sequencing (RNA-seq) has been widely used for characterization of transcriptomic dynamics with different biological contexts, such as development and diseases. Current RNA-seq tools either rely on an annotated reference genome or reference transcripts (e.g., RSEM). For species lacking both of sequenced genomes and reference transcripts, performing RNA-seq data analysis remains challenging. This limits most of the RNA-seq studies to these high quality genomic sequenced model species. Our prior studies along with others suggest combining *de novo* transcripts assembly (Grabherr, et al., 2011) with several cross-species comparative computational strategies, such as mapping contigs to a protein database, can partially solve this problem (Jiang, et al., 2017). However, there has been little benchmarking of these approaches, and thus it is largely unknown that how well they perform.

To facilitate a general use of RNA-seq to species without any prior annotated references, we developed CRSP (Comparative RNA-seq pipeline). CRSP integrates a set of computational steps, such as mapping *de novo* transcriptomic assembly contigs to a protein database, using Expectation-Maximization (EM) algorithm to assign reads mapping uncertainty, and integrative statistics to quantify gene expression values. Our evaluations of CRSP show that its estimated gene expression values are highly correlated with gene expression values estimated by directly mapping to a reference genome. To facilitate a general use of CRSP, we characterized the number of RNA-seq reads required for accurate estimation via simulation studies. Our simulations suggest

that 10 to 20 million single-end reads are sufficient to achieve reasonable gene expression quantification accuracy while a pre-compiled *de novo* transcripts assembly from deep sequencing (although not required) can dramatically decrease the minimal reads requirement for the rest of RNA-seq experiments.

2 METHODS

CRSP: As shown in **Figure 1A**, CRSP takes RNA-seq raw reads and the transcriptomic assembly contigs (e.g., generated by Trinity (Grabherr, et al., 2011)) as input, and then integrate a set of computational steps to estimate gene expression levels. The CRSP workflow contains the following steps: (a) Merging assembly (Contigs): The contigs from different tissues, conditions or batches are merged and then reduced to a non-redundant contig set; (b) Mapping contigs to a protein database: the non-redundant

transcriptomic contig set is mapped to a protein database (e.g., human or mouse protein database) via the NCBI BLASTX tool (Altschul, et al., 1990). CRSP excludes hits with E-value $\geq 10^{-5}$, and the best hit is selected for each contig; (c) Mapping RNA-seq reads to contigs: The RNA-seq reads are mapped to contigs, and then a contig level abundance estimation is performed via RSEM (Li and Dewey, 2011); (d) For each RNA-seq sample, gene-level RNA-seq mapped read counts are obtained by summing the counts of the contigs that are mapped to proteins with the same gene symbol; (f) Relative abundances, in terms of transcripts per million (TPM), for genes are computed by first normalizing each gene's fragment count by the sum of the "effective lengths" (length less the read length) of the contigs mapped to that gene and then scaling the resulting values such that they sum to one million over all genes. A more detailed workflow of CRSP can be found in **Supplementary Figure S1**.

RNA-seq datasets: The single-end reads (human, embryonic stem cell (ES), H1 cell line) was from our published work (Hou, et al., 2015). We also generated 80 million $\times$ 2 paired-end reads (human, H1 ES cells) as a second dataset to evaluate our CRSP tool. The detailed RNA-seq protocols for this newly generated RNA-seq data for this study can be found in **Supplementary Methods**. We have submitted the paired-end RNA-seq data to GEO (accession number: GSE194237).

3 RESULTS

To evaluate the performance of CRSP, we pooled 578 million human ES single-end RNA-seq reads (Hou, et al., 2015), and then generated a gold-standard gene expression value set by directly mapping to human reference genes via RSEM tool (Li

and Dewey, 2011). As shown in **Figure 1B**, the gene expression values which were estimated by CRSP (*de novo* assembly, mapping to mouse protein database) are highly correlated with the gold-standard gene expression values (Spearman's rank correlation coefficient $Rho = 0.89$). We also generated 80 million $\times$ 2 paired-end reads (human, H1 ES cells) as a second dataset testing. As shown in **Figure 1C**, the CRSP also achieved a high accuracy (Spearman's $Rho = 0.86$) on this dataset. To further estimate the minimal reads requirement to run CRSP, we randomly sampled RNA-seq reads from pooled 578 million human ES single-end RNA-seq reads, and then estimated the Spearman's Rho of gene expression values estimated from CRSP and from directly mapping to human reference genes, respectively. As shown in Figure 1D, although the performance of CRSP progressively increased with more sequencing reads, 10-20 million single-end reads can be sufficiently to achieve reasonable accuracy. Importantly, if we have a pre-compiled transcriptomic contigs set from a deep sequencing (optional but not required), CRSP does not require deep read depth to achieve high accuracy (**Figure 1D, blue line**). Together, our study suggest that CRSP is a useful tool making RNA-seq as a general tool to interrogate transcriptomic dynamics but not only limited to species with sequenced genomes or known transcripts.

ACKNOWLEDGEMENTS

This study was supported by Cleveland State University startup to PJ.

REFERENCES

Altschul, S.F., *et al.* Basic local alignment search tool. *J Mol Biol* 1990;215(3):403-410.

Grabherr, M.G., *et al.* Full-length transcriptome assembly from RNA-Seq data without a reference genome. *Nat Biotechnol* 2011;29(7):644-652.

Hou, Z., *et al.* A cost-effective RNA sequencing protocol for large-scale gene expression studies. *Sci Rep* 2015;5:9570.

Jiang, P., *et al.* Analysis of embryonic development in the unsequenced axolotl: Waves of transcriptomic upheaval and stability. *Dev Biol* 2017;426(2):143-154.

Li, B. and Dewey, C.N. RSEM: accurate transcript quantification from RNA-Seq data with or without a reference genome. *BMC Bioinformatics* 2011;12:323.

Supplementary Data

Supplementary Methods

Paired-end RNA-seq: To further evaluate CRSP on paired-end RNA-seq data, we generated 80 million $\times$ 2 paired-end RNA-seq reads on human H1 ES cells. Briefly, total RNA was purified from RLT-Plus Buffer using RNeasy Plus Mini Kits (Qiagen, Netherlands) and quantified with both the Quant-It RNA Assay Kit (ThermoFisher, Massachusetts) and the Bioanalyzer RNA 6000 Pico Kit (Agilent, California). The TruSeq RNA Library Prep Kit v2 (Illumina, San Diego), as per the manufacturer's directions, was used to prepare and index all cDNA libraries. The RNA-seq library was sequenced on Illumina HiSeq 2500. We have submitted the paired-end RNA-seq data to GEO (accession number: GSE194237).

Supplementary Figures